AUTO-CONDITIONED LSTM NETWORK FOR EXTENDED COMPLEX HUMAN MOTION SYNTHESIS

ABSTRACT

We present a real-time method for synthesizing highly complex human motions using a novel LSTM network training regime we call the auto-conditioned LSTM (acLSTM). Recently, researchers have attempted to synthesize new motion by using autoregressive techniques, but existing methods tend to freeze or diverge after a couple of seconds due to an accumulation of errors that are fed back into the network. Furthermore, such methods have only been shown to be reliable for relatively simple human motions, such as walking or running. In contrast, our approach can synthesize arbitrary motions with highly complex styles, including dances or martial arts in addition to locomotion. The acLSTM is able to accomplish this by explicitly accommodating for autoregressive noise accumulation during training. Furthermore, the structure of the acLSTM is modular and compatible with any other recurrent network architecture, and is usable for tasks other than motion. Our work is the first to our knowledge that demonstrates the ability to generate over 18,000 continuous frames (300 seconds) of new complex human motion w.r.t. different styles. An anonymous video of the results can be found here.

1 INTRODUCTION

The synthesis of realistic human motion has recently seen increased interest Holden et al. (2016; 2017); Fragkiadaki et al. (2015); Jain et al. (2016); Bütepage et al. (2017); Martinez et al. (2017) with applications beyond animation and video games. The simulation of human looking virtual agents is likely to become mainstream with the dramatic advancement of Artificial Intelligence and the democratization of Virtual Reality. A challenge for human motion synthesis is to automatically generate new variations of motions while preserving a certain style, e.g., generating large numbers of different Bollywood dances for hundreds of characters in an animated scene of an Indian party. Aided by the availability of large human-motion capture databases, many database-driven frameworks have been employed to this end, including motion graphs Kovar et al. (2002); Safonova & Hodgins (2007); Min & Chai (2012), as well as linear Safonova et al. (2004); Chai & Hodgins (2005); Tautges et al. (2011) and kernel methods Mukai (2011); Park et al. (2002); Levine et al. (2012); Grochow et al. (2004); Moeslund et al. (2006); Wang et al. (2008), which blend key-frame motions from a database. It is hard for these methods, however, to add new variations to existing motions in the database while keeping the style consistent. This is especially true for motions with a complex style such as dancing and martial arts. More recently, with the rapid development in deep learning, people have started to use neural networks to accomplish this task Holden et al. (2017; 2016; 2015). These works have shown promising results, demonstrating the ability of using high-level parameters (such as a walking-path) to synthesize locomotion tasks such as jumping, running, walking, balancing, etc. These networks do not generate new variations of complex motion, however, being instead limited to specific use cases.

In contrast, our paper provides a robust framework that can synthesize highly complex human motion variations of arbitrary styles, such as dancing and martial arts, without querying a database. We achieve this by using a novel deep auto-conditioned LSTM (acLSTM) network architecture.

LSTM networks are autoregressive deep learning frameworks which seek to predict sequences of data similar to a training distribution. Such a framework is intuitive to apply to human motion, which can be naturally modeled as a time series of skeletal joint positions. We are not the first to leverage LSTM or RNN networks for this task Fragkiadaki et al. (2015); Jain et al. (2016); Bütepage et al.

(2017); Martinez et al. (2017), and these works produce reasonably realistic output at a number of tasks such as sitting, talking, smoking, etc. However, these existing methods also have a critical drawback: the motion becomes unrealistic within a couple of seconds and is unable to recover.

This issue is commonly attributed to error accumulation due to feeding network output back into itself Holden et al. (2017). This is reasonable, as the network during training is given ground-truth input sequences to condition its subsequent guess, but at run time, must condition this guess on its own output. As the output distribution of the LSTM will not be identical to that of the ground-truth, it is in effect encountering a new situation at test-time. The acLSTM structure compensates for this by linking the network's own predicted output into its future input streams during training. Our method is light-weight and can be used in conjunction with any other LSTM or RNN based learning scheme. Though straightforward, this technique fixes the issue of error accumulation, and allows the network to output incredibly long sequences without failure, on the order of hundreds of seconds (see Figure 5). Though we are yet as unable to prove the permanent stability of this structure, it seems empirically that motion can be generated without end. In summary, we present a new LSTM architecture capable for the first time of synthesizing potentially indefinitely long sequences of realistic and complex human motions with respect to different styles.

2 RELATED WORK

Many approaches have developed over the years in order to generate realistic human motion. In this section, we first review the literature that has dealt with motion synthesis using simulation methods and database-driven methods, then review the more recent deep learning approaches.

Simulation-based Methods. Simulation-based techniques are able to produce physically plausible animations Levine & Popović (2012); Clegg et al. (2015); Hämäläinen et al. (2015); Ha et al. (2012), including realistic balancing, motion on terrain of various heights, and recovery from falling. These techniques tend to consider physical constraints on the human skeleton while optimizing a motion objective. For example, in the work of Levine et al. Levine & Popović (2012), one task they employ is moving the skeleton in a certain direction without falling over. Similarly, in Ha et al. Ha et al. (2012), given initial fall conditions, they seek to minimize joint stress due to landing impact while ensuring a desired landing pose. Though the output is plausible and realistic, they require specific objectives and constraints for each individual task. It is not feasible to use such explicit objectives or constraints for stylized motion. The correct arch of the back and flourishes of the limbs for a dance cannot be described a priori and must instead be inferred from the data.

Database-driven Methods. Motion graphs Kovar et al. (2002); Safonova & Hodgins (2007); Min & Chai (2012), which stitch transitions into segments queried from a database, can generate locomotion along arbitrary paths, but are in essence limited to producing memorized sequences. Frameworks based on linear Safonova et al. (2004); Chai & Hodgins (2005); Tautges et al. (2011) and kernal methods Mukai (2011); Park et al. (2002); Levine et al. (2012); Grochow et al. (2004); Moeslund et al. (2006); Wang et al. (2008) have also shown reasonable success. Taylor et al. Taylor & Hinton (2009) use conditional restricted boltzmann machines to model motion styles. Grochow et al. Grochow et al. (2004) and Wang et al. Wang et al. (2005) both use Gaussian Process Latent Variable Models (GPLVM) to control motion. Levine et al. Levine et al. (2012) apply reinforcement learning in a reduced space to compute optimal motions for a variety of motion tasks, including movement, punching, and kicking. Kee et al. Lee et al. (2010) use a representation of motion data called motion-fields which allows users to interactively control movement of a character. The work of Xia et al. Xia et al. (2015) is able to achieve real-time style transfers of unlabeled motion. Taylor et al. Taylor et al. (2007) use binary latent variables which are connected between different time steps while Liu et al. Liu et al. (2005) estimate physical parameters from motion capture data. Database methods have limitations in synthesizing new variations of motion, in addition to the high memory costs for storing complex motions.

Deep Learning Approaches. The use of recurrent networks is a natural approach to dealing with the problem of human motion. LSTM and RNN networks are trained to generate output sequentially, each output conditioned on the previous elements in the sequence. These networks have shown much success in Natural Language Processing for generating text Sutskever et al. (2011), hand written

characters Graves (2013); Gregor et al. (2015), and even captioning images Vinyals et al. (2014). For the purpose of motion prediction and generation, Fragkiadaki et al. Fragkiadaki et al. (2015) propose to use encoder-recurrent-decoder (ERD), jointly learning a skeleton embedding along with sequential information, in order to make body positions more realistic. In Jain et al. Jain et al. (2016), the authors employ RNNs to learn spatio-temporal graphs of interaction, a structure which naturally applies to the human skeleton over time–joint positions are related over consecutive frames, and joints also interact with each other spatially (arms and legs interact with each other, the spine interacts with all other joints). Bütepage et al. Bütepage et al. (2017) attempt to learn dance sequentially, but they are unable to produce varied and realistic output. More recently, Martinez et al. Martinez et al. (2017) propose using a sequence-to-sequence architecture along with sampling-based loss. A main problem with these approaches, even in the case of the ERD, is that motion generation tends to converge to a mean position over time. Using our proposed training method, motion neither halts nor becomes unrecognizable for any period of time.

Holden et al. Holden et al. (2015) demonstrate that a manifold of human motion can be learned using an autoencoder trained on the CMU dataset. They Holden et al. (2016) extend this work by using this deep convolutional auto-encoder, in addition to a disambiguation network, in order to produce realistic walking motion along a user-defined path. They are also able to use the embedding space of the encoder to perform style transfer across different walks. Using the same autoencoder and a different disambiguation network, they can also perform other user defined tasks such as punching and kicking. Their method does not use an RNN structure and so it can only generate fixed length sequences based on the architecture of the disambiguation network. More recently, Holden et al. Holden et al. (2017) use a Phase-Functioned Neural Network which takes the geometry of the scene into account to produce motion along a user-defined path. This method makes use of humans' periodic change of gait to synthesize realistic walking motion but has not demonstrated the ability to generate motions that have more complex step movements.

3 METHODOLOGY

Figure 1: Visual diagram of an unrolled Auto-Conditioned RNN (right) with condition length $v = 4$ and ground truth length $u = 4$. I_t is the input at time step t. S_t is the hidden state. O_t is the output.

Auto-Conditioned LSTM Network. LSTM networks are well documented in the literature. A good survey and introduction can be found at Karpathy (2015); Olah (2015). In short, a recurrent network can be represented as a function with a hidden memory unit, $x_{t+1} = f(x_t, m_t)$, where m_t is the "memory" of the network, and is updated during every forward pass, and initialized at 0. The motivation is that the memory stores important information about a sequence up until that point, which can help with the prediction of the next element. An LSTM is a special case of an RNN that has longer-term persistent memory.

As mentioned in the introduction, the major drawback of using LSTM/RNN deep learning methods for motion prediction is the problem of error accumulation. Following the conventional way to train an RNN, the network is recursively given a sequence of ground truth motion data, $G_{1,k} = [g_1, ..., g_k]$, and asked to produce the output $G_{2,k+1}[g_2, ..., g_{k+1}]$. Specifically, at training time, the recursive module at time step t, M_t, is conditioned on the input $[g_1, ..., g_{t-1}]$, and the error is measured between its output and g_t. Because of this, the backpropagation algorithm Williams & Zipser (1995) used for updating the parameters will always optimize w.r.t. the input ground-truth sequences $[g_1, ..., g_{t-1}]$. The parameters are accustomed to ground truth input — something it does not have access to at test-time. It is easy to see why problems will emerge: even if initial input is similar to ground truth, those slight differences will accumulate as the output is fed back in, producing output that become

progressively worse until the sequence diverges or freezes. Effectively, the network is encountering a completely novel situation during test time as compared to training time, and so cannot perform well. The issue is so prevalent, in fact, that previous methods fail to produce realistic output after several seconds Fragkiadaki et al. (2015); Jain et al. (2016); Martinez et al. (2017).

Interestingly enough, this problem does not emerge in the more popular usages of LSTM networks for NLP problems such as sequential text generation Sutskever et al. (2011). Network output for these models is interpreted as probability vectors over characters, the output character being the entry with the highest probability. It is easy to round these to resemble ground-truth instances by setting the output character value to 1 and the other to 0, so there is no major difference between training and test time input. One might imagine a similar approach to deal with motion. A naive solution could be to fix the length of the bones before throwing it back in, for example, but it does not guarantee against other failure cases, such as impossible angles of joints.

Holden et al. Holden et al. (2015) show that an autoencoder framework can to some degree "fix" broken input, and some researchers have tried jointly learning such an encoder-decoder network alongside RNNs to better condition subsequent input Gregor et al. (2015); Fragkiadaki et al. (2015). However, in the case of this framework being applied to motion as in ERD Fragkiadaki et al. (2015), it does not generalize to indefinitely long sequences, as shown in Jain et al. (2016). It seems as though the autoencoder might mitigate error accumulation, but does not eliminate it.

The acLSTM, on the other hand, deals with poor network output explicitly by using it during training. Instead of only feeding in ground-truth instances, we use subsequences of the network's own outputs at periodic intervals. For instance, sticking with the example above, instead of conditioning the network on $G_{1,k} = [g_1, ..., g_k]$, we use $\hat{G}_{1,k} = [g_1, ..., g_u, p_{u+1}, ..., p_{u+v}, g_{u+v+1}.., g_k]$ to predict $G_{2,k+1} = [g_2, ..., g_{k+1}]$. The variable p_{u+1} is the network output conditioned on $[g_1, ..., g_u]$, and p_{u+2} is conditioned on $[g_1, ..., g_u, p_{u+1}]$. In this example, we refer to v as the "condition length" and u as the "ground-truth length". As the network is conditioned on its own output during training, it is able to deal with such input during synthesis. Figure 1 details an unrolled Auto-Conditioned RNN with condition length $u = v = 1$, and Figure 10 shows a more detailed view or our network.

Auto-conditioning also has the interpretation of training the network to produce longer sequences without further input. Whereas with standard training the network error is measured only against p_{u+1} when conditioned with $[g_1, ..., g_u]$, under auto-conditioning the error is computed on the entire sequence $p_{u+1}, ..., p_{u+v}$ w.r.t. the same input. This effectively forces the network to produce v frames of output simultaneously as opposed to only one. Martinez et al. Martinez et al. (2017) also use contiguous sequences of network output during training, but unlike us they do not alternate these with ground-truth input at regular intervals.

Data Representation.   We use the publicly available CMU motion-capture dataset for our experiments. The dataset is given as sequences of 57 skeleton joint positions in 3D-space. First, we define a root joint, whose position at time t is given by $r_t = (r_{1,t}, r_{2,t}, r_{3,t})$. In order to better capture relative motion, we instead use the displacement of the root from the previous frame for input — $\tilde{r}_t = (r_{1,t} - r_{1,t-1}, r_{2,t} - r_{2,t-1}, r_{3,t} - r_{3,t-1})$. For every other joint at time t, with position $j_t = (j_{1,t}, j_{2,t}, j_{3,t})$, we represent it as as the relative distance in the world-coordinate system to the root joint, $\tilde{j}_t = (j_{1,t} - r_{1,t}, j_{2,t} - r_{2,t}, j_{3,t} - r_{3,t})$. All distances are stored in meters. We use a skeleton with height 1.54 meters in neutral pose for all experiments.

We found this representation to be desirable for several reasons. Primarily, if there is periodic motion in the dataset, we would like frames at the same point in the repeated activity to have small Euclidean distance. If we instead used absolute positions, even if it were only for the hip, this would certainly not be the case. We note that there are alternative representations which achieve the same property. Fragkiadaki et al. (2015) express joint positions as rotations relative to a parent joint, and Holden et al. (2016) define them in the body's relative coordinate system along with a relative rotation of the body w.r.t. the previous frame.

Training.   We train the acLSTM with three fully connected layers with a memory size of 1024, similar to Fragkiadaki et al. (2015); Jain et al. (2016); Bütepage et al. (2017). The main difference is that for every u ground-truth inputs of the time series, we connect v instances of the network's own output into its subsequent input streams (see section 2.1). In the main body of the paper, we set $u = v = 5$. We carry out further experiments with varying u and v in the appendix. We train with a

sequence length of 100 for 500000 iterations using the ADAM backpropagation algorithm Kingma & Ba (2014) on an NVIDIA 1080 GPU for each dataset we experiment on. We use Euclidean loss for our objective function. The initial learning rate is is set to 0.0001. We implement the training using the python caffe framework Jia et al. (2014). We sample sequences at multiple frame-rates as well as rotate and translate the sequence randomly in order to increase the training size.

In detail, if at time t we input the network H with ground truth, then the loss is given by:

$$L(x_t) = ||H(x_t, m_t) - x_{t+1}||_2^2 \tag{1}$$

where x_t and x_{t+1} are the ground truth motions for time steps t and $t + 1$.

If at time t the network is input with its own previous output, the loss is given by:

$$L(x_t) = \left|\left|H(\hat{x_t}^k, m_t) - x_{t+1}\right|\right|_2^2 \tag{2}$$

where $\hat{x_t}^k = H(H(...H(x_{t-k}, m_{t-k}), m_{t-1}), m_t)$. k indicates how many times the network has fed itself is its own input since the last injection of ground-truth. It is bounded by the condition length (see previous section).

4 EXPERIMENTAL RESULTS

We evaluate our synthesized motion results on different networks trained on each of four distinct subsets from the CMU motion capture database: martial arts, Indian dance, Indian/salsa hybrid, and walking.

Figure 2: **Motion change** between subsequent frames of different motion styles, given as Euclidean distance in prediction results, at different frames. All acLSTM networks here are trained with condition length 5. Predictions are generated with 10 frames (approximately 170 ms) of seed motion from test set. Results are averaged over 20 random seed motions. Low value in motion change indicates the freezing of motion. Note that acLSTM and vanilla have exactly the same architecture - differences are due solely to training. Results averaged over 20 seed motions.

Quantitative Results. Table 1 shows the prediction error as Euclidean distance from the ground truth for different motion styles at various time frames.

We compare with a 3-layer LSTM (LSTM-3LR), as well as ERD Fragkiadaki et al. (2015) and the seq2seq framework of Martinez et al. (2017). Though our goal is long-term stable synthesis

Figure 3: Comparison between the vanilla LSTM and our method at 250,000 iterations of training. **top:** vanilla LSTM, **bottom:** acLSTM. The two synthesized motions are initialized with the same 10 frames of ground truth motion. The motion generated by the vanilla LSTM freezes after around 60 frames. Our method does not freeze.

Table 1: **Motion prediction error** for different styles of motion at {80, 160, 240, 320, 400, 480, 560, 640} ms after seed motion of 10 frames (approximately 170 ms) from test set. All acLSTM networks here are trained with condition length 5. Error given as Euclidean distance from the ground truth for the corresponding frame. All results averaged over 20 random seed motions. Longer motion prediction is not feasible due to randomness of human motion.

Architecture	80 ms	160 ms	240 ms	320 ms	400 ms	480 ms	560 ms	640 ms
Walking
LSTM-3LR	2.46	2.41	2.28	2.27	2.41	2.65	2.91	3.15
acLSTM-3LR	1.05	1.77	2.20	2.46	2.66	2.79	2.99	3.24
ERD	0.13	0.22	0.34	0.50	**0.71**	**0.95**	**1.19**	**1.42**
seq2seq	**0.09**	**0.13**	**0.24**	**0.42**	0.74	1.22	1.85	2.79
Indian Dance
LSTM-3LR	2.82	2.83	2.85	2.88	2.89	2.90	2.92	2.92
acLSTM-3LR	0.685	0.99	**1.22**	**1.53**	**1.89**	**2.08**	**2.27**	**2.55**
ERD	0.51	**0.74**	1.25	1.96	2.62	3.31	3.76	3.86
seq2seq	**0.49**	0.79	1.48	2.95	5.41	8.88	13.29	18.73
Martial Arts
LSTM-3LR	0.69	0.86	1.11	1.36	1.60	1.83	2.03	2.19
acLSTM-3LR	0.52	0.74	0.95	1.14	1.35	1.56	1.73	**1.88**
ERD	0.32	0.44	**0.63**	**0.90**	**1.14**	**1.40**	**1.61**	**1.88**
seq2seq	**0.28**	**0.43**	0.87	1.57	2.53	3.89	5.83	8.62

and not prediction, it can be seen in Table 1 that acLSTM performs reasonably well in this regard, achieving the best performance at 640 ms in both the Indian Dance and Martial Arts categories. The method of Martinez et al. (2017) performs the best in the short term, but has the worst error by far past the half-second mark. As noted in Fragkiadaki et al. (2015), the stochasticity of human motion makes longer-term prediction infeasible. Table 2 in the appendix shows this error difference between versions of the Indian dance network trained with different condition lengths. Figure 2 shows the average change between subsequent frames for different frame times for the acLSTM and the basic scheme. For the more complex motions of Martial Arts and Indian Dance, it is clear from the graph that acLSTM continues producing motion in the long-term while the basic training scheme (LSTM-3LR) without auto-conditioning results in stagnated motion, as the network freezes into a converged mean position. Likewise, Figure 9 in the appendix shows this average change for the Indian dance network trained with different condition lengths. We note that while the methods of Fragkiadaki et al. (2015); Martinez et al. (2017) do not simply freeze completely, as with the basic scheme, their motion becomes unrealistic at around the same time (Figure 7)

Figure 4: Motion sequences generated by acLSTM, sampled at various frames. Motion style from **top to bottom**: martial arts, Indian dancing, Indian/salsa hybrid and walking. All the motions are generated at 60 fps, and are initialized with 10 frames of ground truth data randomly picked up from the database. The number at the bottom of each image is the frame index. The images are rendered with BVHViewer 1.1 van Basten (2017)

Qualitative Results. Figure 4 shows several example frames taken from 50 second synthesized outputs, representing both the extended long term complexity and plausibility of the output. In comparison, our implementations of ERD and seq2seq are only able to generate motion for a couple of seconds before they become unrealistic (Figure 7). We also demonstrate the possibility of creating hybrid motions by mixing training sets in third row of Figure 4.

It should be noted that the motion in our framework, while never permanently failing, also does not remain perfectly realistic, and short-term freezing does sometimes occur. This, however, does not occur for the network trained just on walking. It is perhaps that the movement of the feet in conjunction with the absolute movement of the root joint is not as easy to discern when the feet leave the ground aperiodically, or there are jumping motions.

Figure 5: Sample frames from a 300+ second generated sequence.

Figure 6: Example of the acLSTM recovering from short term stagnated motion.

When motion does stagnate, it recovers relatively quickly, and the motion never diverges or freezes completely (see Figure 6). The short-term freezing could possibly be explained by "dead-times" in the

Figure 7: Frames of alternative methods at latest failure-points out of 20 generated 1000-frame motion samples. acLSTM did not fail in any of 20 generated samples. **Top**: seq2seq failure starting around frame 40. Motion becomes unrealistic and does not recover. **Bottom**: ERD failure between frames 400 and 500; slight motion occurs, but pose remains unaltered. Examples trained on Indian Dance.

training sequence, where the actor is beginning or ending a sequence which involves a rest position. Note that when training with two different datasets, as in the case of the Indian/Salsa combined network, motion borrows from both dance styles. We also demonstrate in Figure 5 that our method does not freeze even after 20,000 frames of synthesis, which is approximately 333 seconds of output.

One can see a qualitative comparison of acLSTM with a basic LSTM-3R in Figure 3, both trained on the Indian dance dataset. We find the performance of the vanilla network to be consistent with the results reported in Fragkiadaki et al. (2015); Jain et al. (2016); Bütepage et al. (2017); Martinez et al. (2017), freezing at around 1000 ms. It never recovers from the motion. Our network, on the other hand, continues producing varied motion for the same time frame.

5 DISCUSSION AND FUTURE WORK

We have shown the effectiveness of the novel acLSTM architecture to produce extended sequences of complex human motion. We believe our work demonstrates qualitative state-of-the-art results in motion generation, as all previous work has focused on synthesizing relatively simple human motion for extremely short time periods. These works demonstrate motion generation up to a couple of seconds at most while acLSTM does not fail even after over 300 seconds. Though we are as of yet unable to prove indefinite stability, it seems empirically that acLSTM can generate arbitrarily long sequences. It should be noted that our method is compatible with any other autoregressive training procedure, including Fragkiadaki et al. (2015); Jain et al. (2016); Martinez et al. (2017), for further improvement. Current problems that exist include choppy motion at times, self-collision of the skeleton, and unrealistic sliding of the feet. This latter issue seems to effect only one foot at a time. In this vein, we believe combining our technique with physically based simulation to ensure realism after synthesis is a natural next step. Finally, it is important to study the effects of using various condition lengths during training. We begin the exploration of this topic in the appendix, but further analysis is needed.

REFERENCES

Judith Bütepage, Michael Black, Danica Kragic, and Hedvig Kjellström. Deep representation learning for human motion prediction and classification. *arXiv preprint arXiv:1702.07486*, 2017.

Jinxiang Chai and Jessica K Hodgins. Performance animation from low-dimensional control signals. In *ACM Transactions on Graphics (TOG)*, volume 24, pp. 686–696. ACM, 2005.

Alexander Clegg, Jie Tan, Greg Turk, and C Karen Liu. Animating human dressing. *ACM Transactions on Graphics (TOG)*, 34(4):116, 2015.

Katerina Fragkiadaki, Sergey Levine, Panna Felsen, and Jitendra Malik. Recurrent network models for human dynamics. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 4346–4354, 2015.

Alex Graves. Generating sequences with recurrent neural networks. *CoRR*, abs/1308.0850, 2013. URL http://arxiv.org/abs/1308.0850.

Karol Gregor, Ivo Danihelka, Alex Graves, Danilo Jimenez Rezende, and Daan Wierstra. Draw: A recurrent neural network for image generation. *arXiv preprint arXiv:1502.04623*, 2015.

Keith Grochow, Steven L Martin, Aaron Hertzmann, and Zoran Popović. Style-based inverse kinematics. In *ACM transactions on graphics (TOG)*, volume 23, pp. 522–531. ACM, 2004.

Sehoon Ha, Yuting Ye, and C Karen Liu. Falling and landing motion control for character animation. *ACM Transactions on Graphics (TOG)*, 31(6):155, 2012.

Perttu Hämäläinen, Joose Rajamäki, and C Karen Liu. Online control of simulated humanoids using particle belief propagation. *ACM Transactions on Graphics (TOG)*, 34(4):81, 2015.

Daniel Holden, Jun Saito, Taku Komura, and Thomas Joyce. Learning motion manifolds with convolutional autoencoders. In *SIGGRAPH Asia 2015 Technical Briefs*, pp. 18. ACM, 2015.

Daniel Holden, Jun Saito, and Taku Komura. A deep learning framework for character motion synthesis and editing. *ACM Transactions on Graphics (TOG)*, 35(4):138, 2016.

Daniel Holden, Taku Komura, Jun Saito, Xi Zhao, Myung-Geol Choi, Ruizhen Hu, Paul Guerrero, Niloy J Mitra, Steve Tonneau, Rami Al-Ashqar, et al. Phase-functioned neural networks for character control. *ACM Transactions on Graphics (TOG)*, 36(4), 2017.

Ashesh Jain, Amir R Zamir, Silvio Savarese, and Ashutosh Saxena. Structural-rnn: Deep learning on spatio-temporal graphs. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5308–5317, 2016.

Yangqing Jia, Evan Shelhamer, Jeff Donahue, Sergey Karayev, Jonathan Long, Ross Girshick, Sergio Guadarrama, and Trevor Darrell. Caffe: Convolutional architecture for fast feature embedding. In *Proceedings of the 22nd ACM international conference on Multimedia*, pp. 675–678. ACM, 2014.

Andrej Karpathy. The unreasonable effectiveness of recurrent neural networks, 2015. URL http://karpathy.github.io/2015/05/21/rnn-effectiveness/.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Lucas Kovar, Michael Gleicher, and Frédéric Pighin. Motion graphs. In *ACM transactions on graphics (TOG)*, volume 21, pp. 473–482. ACM, 2002.

Yongjoon Lee, Kevin Wampler, Gilbert Bernstein, Jovan Popović, and Zoran Popović. Motion fields for interactive character locomotion. In *ACM Transactions on Graphics (TOG)*, volume 29, pp. 138. ACM, 2010.

Sergey Levine and Jovan Popović. Physically plausible simulation for character animation. In *Proceedings of the ACM SIGGRAPH/Eurographics Symposium on Computer Animation*, pp. 221–230. Eurographics Association, 2012.

Sergey Levine, Jack M Wang, Alexis Haraux, Zoran Popović, and Vladlen Koltun. Continuous character control with low-dimensional embeddings. *ACM Transactions on Graphics (TOG)*, 31 (4):28, 2012.

C Karen Liu, Aaron Hertzmann, and Zoran Popović. Learning physics-based motion style with nonlinear inverse optimization. *ACM Transactions on Graphics (TOG)*, 24(3):1071–1081, 2005.

Julieta Martinez, Michael J Black, and Javier Romero. On human motion prediction using recurrent neural networks. *arXiv preprint arXiv:1705.02445*, 2017.

Jianyuan Min and Jinxiang Chai. Motion graphs++: a compact generative model for semantic motion analysis and synthesis. *ACM Transactions on Graphics (TOG)*, 31(6):153, 2012.

Thomas B Moeslund, Adrian Hilton, and Volker Krüger. A survey of advances in vision-based human motion capture and analysis. *Computer vision and image understanding*, 104(2):90–126, 2006.

Tomohiko Mukai. Motion rings for interactive gait synthesis. In *Symposium on Interactive 3D Graphics and Games*, pp. 125–132. ACM, 2011.

Christopher Olah. Understanding lstm networks, 2015. URL http://colah.github.io/posts/2015-08-Understanding-LSTMs/.

Sang Il Park, Hyun Joon Shin, and Sung Yong Shin. On-line locomotion generation based on motion blending. In *Proceedings of the 2002 ACM SIGGRAPH/Eurographics symposium on Computer animation*, pp. 105–111. ACM, 2002.

Alla Safonova and Jessica K Hodgins. Construction and optimal search of interpolated motion graphs. In *ACM Transactions on Graphics (TOG)*, volume 26, pp. 106. ACM, 2007.

Alla Safonova, Jessica K Hodgins, and Nancy S Pollard. Synthesizing physically realistic human motion in low-dimensional, behavior-specific spaces. *ACM Transactions on Graphics (TOG)*, 23 (3):514–521, 2004.

Ilya Sutskever, James Martens, and Geoffrey E Hinton. Generating text with recurrent neural networks. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pp. 1017–1024, 2011.

Jochen Tautges, Arno Zinke, Björn Krüger, Jan Baumann, Andreas Weber, Thomas Helten, Meinard Müller, Hans-Peter Seidel, and Bernd Eberhardt. Motion reconstruction using sparse accelerometer data. *ACM Transactions on Graphics (TOG)*, 30(3):18, 2011.

Graham W Taylor and Geoffrey E Hinton. Factored conditional restricted boltzmann machines for modeling motion style. In *Proceedings of the 26th annual international conference on machine learning*, pp. 1025–1032. ACM, 2009.

Graham W Taylor, Geoffrey E Hinton, and Sam T Roweis. Modeling human motion using binary latent variables. *Advances in neural information processing systems*, 19:1345, 2007.

B.J.H. van Basten. Development in motion, 2017. URL http://www.developmentinmotion.nl/.

Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. Show and tell: A neural image caption generator. *CoRR*, abs/1411.4555, 2014. URL http://arxiv.org/abs/1411.4555.

Jack M Wang, David J Fleet, and Aaron Hertzmann. Gaussian process dynamical models. In *NIPS*, volume 18, pp. 3, 2005.

Jack M Wang, David J Fleet, and Aaron Hertzmann. Gaussian process dynamical models for human motion. *IEEE transactions on pattern analysis and machine intelligence*, 30(2):283–298, 2008.

Ronald J Williams and David Zipser. Gradient-based learning algorithms for recurrent networks and their computational complexity. *Backpropagation: Theory, architectures, and applications*, 1: 433–486, 1995.

Shihong Xia, Congyi Wang, Jinxiang Chai, and Jessica Hodgins. Realtime style transfer for unlabeled heterogeneous human motion. *ACM Transactions on Graphics (TOG)*, 34(4):119, 2015.

Figure 8: Selected frames of a rigged animation example using the martial arts network.

A   THE EFFECT OF CONDITION LENGTH

Figure 9: **Motion change** between subsequent frames using different condition lengths, given as Euclidean distance in prediction results, at different frames. Predictions are initialized with 10 frames (approximately 170 ms) of seed motion from test set. Results are averaged over 20 random seed motions. All networks are trained on the Indian dance dataset.

Table 2: **Motion prediction error** for different condition lengths {80, 160, 240, 320, 400, 480, 560, 640} ms after seed motion of 10 frames (approximately 170 ms) from test set. Error given as Euclidean distance from the ground truth for the corresponding frame. All results averaged over 20 random seed motions. All networks are trained on the Indian dance dataset

Architecture	80 ms	160 ms	240 ms	320 ms	400 ms	480 ms	560 ms	640 ms
Indian Dance								
c-length 10	**0.41**	**0.52**	**0.68**	**0.86**	**1.04**	**1.23**	**1.39**	**1.55**
c-length 5	0.685	0.99	1.22	1.53	1.89	2.08	2.27	2.55
c-length 2	0.83	1.28	1.61	1.87	2.09	2.31	2.51	2.66
c-length 1	0.89	1.40	1.78	2.14	2.48	2.70	2.84	2.93

B   PREDICTION ERROR

It seems that Table 2 and Figure 9 might imply some sort of trade off between motion change over time and short-term motion prediction error when training with different condition lengths. However, it is also possible that limiting motion magnitude on this particular dataset might correspond to lower error. Further experiments of various condition lengths on several motion styles need to be conducted to say anything meaningful about the effect.

C   VISUAL DIAGRAM OF AUTO-CONDITIONED LSTM

Figure 10: Detailed visual diagram of an unrolled Auto-Conditioned LSTM. I_t is the input at time step t. O_t is the output state. Rectangles indicate the neural network layer. Circles indicate point wise operation. Triangles indicate concatenation.