COCO-GAN: COnditional COordinate Generative Adversarial Network

ABSTRACT

Recent advancements on Generative Adversarial Network (GAN) have inspired a wide range of works that generate synthetic images. However, the current processes have to generate an entire image at once, and therefore resolutions are limited by memory or computational constraints. In this work, we propose COnditional COordinate GAN (COCO-GAN), which generates a specific patch of an image conditioned on a spatial position rather than the entire image at a time. The generated patches are later combined together to form a globally coherent full-image. With this process, we show that the generated image can achieve competitive quality to state-of-the-arts and the generated patches are locally smooth between consecutive neighbors. One direct implication of the COCO-GAN is that it can be applied onto any coordinate systems including the cylindrical systems which makes it feasible for generating panorama images. The fact that the patch generation process is independent to each other inspires a wide range of new applications: firstly, "Patch-Inspired Image Generation" enables us to generate the entire image based on a single patch. Secondly, "Partial-Scene Generation" allows us to generate images within a customized target region. Finally, thanks to COCO-GAN's patch generation and massive parallelism, which enables combining patches for generating a full-image with higher resolution than state-of-the-arts.

1 INTRODUCTION

Human perception has only partial access to the surrounding environment due to the limited acuity area of fovea, and therefore human learns to recognize or reconstruct the world by moving their eyesight. Computational vision models mostly assume machines always have full access to the whole scene, which is one of the key bottlenecks of modern models when dealing with large field-of-view and differently-shaped input data in different tasks.

This paper explores the idea of implementing spatial disentanglement into generative adversarial networks (GANs) (Goodfellow et al., 2014). We propose and develop a new GAN architecture: COnditional COordinate GAN (COCO-GAN). Given a latent vector and spatial positions, the generator of COCO-GAN learns to produce image patches independently. On the other hand, the discriminator learns to judge whether adjacent generated patches are structurally sound and visually homogeneous. The generated patches then can directly be used to compose a complete full-image without further post-processing. Thanks to the adversarial loss provided by the discriminator, the composed full-image is locally smooth and globally convincing. We show several randomly-selected full-images generated by COCO-GAN in Figure 2a. In Section 3.2, we visualize the learned spatial disentanglement via the task of spatial positions interpolation. Further quantitative evaluations with "Frchet Inception Distance" (FID) (Heusel et al., 2017) score are presented in Table 1. Without additional hyper-parameter tuning, the evaluations on CelebA (Liu et al., 2015) and LSUN (Yu et al., 2015) datasets suggest that COCO-GAN is competitive with other state-of-the-art GANs.

Besides the spatial disentanglement property, COCO-GAN is a flexible coordinate-system-aware framework that is suitable for different spatial coordinate systems. Common learning frameworks are confined to Cartesian coordinate system. Lacking awareness of coordinate restricts those frameworks from learning the characteristics of certain image formats. For instance, panoramas should be

---

We will release data and author's implementation after paper published.

Figure 1: An overview of COCO-GAN (training phase). The full-images are only generated during testing phase (Figure 10 in the Appendix).

trained with a cylindrical coordinate system, which has a "cyclic topology" in the horizontal direction. In comparison, COCO-GAN directly learns with a cylindrical coordinate system. In Figure 6 and Figure 7, the generated full scenes are naturally cylindrical and continuous while crossing the left and right borders.

In addition to COCO-GAN's capability of learning spatial disentanglement and being flexible to different coordinate systems, we find COCO-GAN has multiple interesting applications and characteristics. We select three representative new applications as case studies: "Patch-Inspired Image Generation", "Partial-Scene Generation" and "Computation-Friendly Generation".

"Patch-Inspired Image Generation" takes a real image patch as input. COCO-GAN can be inspired by the given patch and further generates a full-image proposal. This proposal is partially similar to the given patch, while globally realistic and reasonable. This setting is different from conventional image completion/reconstruction since the information loss during cropping is extreme and the spatial position information is not provided to the model. Therefore, COCO-GAN has to infer the position of the given patch before generating the whole image. Further experiments are presented in Section 3.4.

"Partial-Scene Generation" shows that COCO-GAN can generates partial scenes without spending additional computation outside certain designated regions. This capability is exclusively beneficial to applications that are only interested in partial information of the full scene. For instance, virtual reality (VR) is only interested in the user's viewport direction, and COCO-GAN can seamlessly adapt to such viewport-aware settings.

"Computation-Friendly Generation" demonstrates the computational related merits of COCO-GAN. First, since the patches are produced independently, the generator is able to generate patches with high parallelism. Second, as the full-image generation is decomposed to patches generation, the minimum memory requirement of generating images can be reduced. This characteristic enables COCO-GAN to generate images of very high resolution or containing much more complex structures.

In this work, we propose the COCO-GAN , aiming at learning spatial disentanglement with GANs. Without additional hyper-parameter tuning, both qualitative and quantitative results suggest COCO-GAN is competitive with other state-of-the-art GANs in terms of generation quality. Furthermore, COCO-GAN is a coordinate-system-aware framework. We investigate panorama generation with a cylindrical coordinate system, where the generated panoramas have built-in cyclic property in the horizontal direction. We also investigate three new applications as case studies, including "Patch-Inspired Image Generation", "Partial-Scene Generation", and "Computation-Friendly Generation".

2 COCO-GAN

Overview. COCO-GAN consists of three networks: a generator G, a discriminator D, and a aux-iliary head Q. These three networks are trained with four loss terms: patch Wasserstein loss L_W, patch gradient penalty loss L_{GP}, spatial consistency loss L_S, and content consistency loss L_C. Compared to conventional GANs that use full images as input for both G and D, COCO-GAN only uses micro patches for G, and macro patches for D. The details of micro and macro patches will be described in the paragraph "Spatial coordinate system design". D has two auxiliary prediction heads: the content vector prediction head (Q) and the spatial condition prediction head. Q is trained with an extra optimizer independent to G and D. It aims to minimize L_C and is used to estimate the original latent vector of the given sample. The spatial condition prediction head, on the other hand, is jointly trained with the discriminator. It aims at minimizing L_S and is used to estimate the macro spatial position of the given sample. Both of the two auxiliary prediction heads are simple feed-forward networks that take inputs from one of the high-level feature maps of the discriminator.

COCO-GAN considers two coordinate systems: a micro coordinate system m, which refers to the annotated component that related to the finer coordinate system, on the generator's side, and a macro coordinate system M, which is related to the coarser macro coordinate system on the discriminator's side. The discriminator learns to distinguish between the generated macro patch $\tilde{p}^M$ and the real macro patch p^M. The discriminator also learns to predict two auxiliary outputs: a predicted macro coordinate $\tilde{c}^M$ and a predicted latent vector $\tilde{z}^M$. Outputs from these two networks are then used to compute two auxiliary losses: Spatial Consistency Loss (L_S) and Content Consistency Loss (L_C).

The objective function of the discriminator D is $L_W + L_{GP} + L_S + L_C$, the generator G is $-L_W + L_S + L_C$, and the content vector prediction head Q is $-L_W + L_C$.

Spatial coordinate system. Before presenting the details of these four loss terms, we introduce our notations first. We start with designing two spatial coordinate systems, a *micro* coordinate system C^m for the generator G and a *macro* coordinate system C^M for the discriminator D. Let S^N be a space of spatial position sequences, each spatial position sequence $s = \langle c_i^m \rangle_{i=1}^N \in S^N$ is an ordered sequence, which $c_i^m \in C^m$. During COCO-GAN training, R is some predefined spatial constraints for sampling s from a uniform distribution $\mathcal{U}(S^N, R)$. The generator G is conditioned by each spatial position c_i^m, and learns to accordingly produce micro patches $\tilde{p}_i^m = G(z|c_i^m)$. The $\langle \tilde{p}_i^m \rangle_{i=1}^N = \langle G(z|c_i^m) \rangle_{i=1}^N$ is a sequence of micro patches produced ***independently*** while sharing the same latent vector z across the spatial position sequence s.

The design of R may need to be slightly changed with respect to the selection of C^M and C^m. The design principle of R is that the accordingly generated micro patches $\langle \tilde{p}_i^m \rangle_{i=1}^N$ should be spatially close to each other. Then the micro patches are merged by a merging function $T_{(m \to M)}$ to form a complete macro patch $\tilde{p}^M = T_{(m \to M)}(\langle \tilde{p}_i^m \rangle_{i=1}^N)$ as a coarser partial-view of the full-scene $\tilde{x}$. Meanwhile, we assign $\tilde{p}^M$ with a new spatial position c^M under the macro coordinate system for s.

In Figure 1, we illustrate one of the simplest design for the above heuristic functions that we have adopted throughout our experiments. The four micro patches are always a neighbor of each other and can be directly combined into a square macro patch with $T_{(m \to M)}$, which is just simple con-catenation. Figure 3 shows some examples of micro and macro patches generation.

On the real samples side, we also sample $s \sim S$, but we directly infer s to macro position c^M. Then we design a transformation $T_{(X \to M)}$ with respect to $T_{(m \to M)}$ to transform a real full-image x to a real macro patch p^M by $T_{(X \to M)}(x|c^M)$. The shape of p^M should be the same as $\tilde{p}^M$. In our simplest experiment setting, $T_{(X \to M)}$ is a simple cropping function that crops x into p^M, which has the same shape as $\tilde{p}^M$.

During the testing phase, depending on the design of C^m, we can directly infer a corresponding spa-tial position sequence $\langle c_j^m \rangle_{j=1}^K$. It is used to independently produce spatially-disentangled patches that constitute the full-image. Figure 10 demonstrates how the full-image is generated during the testing phase. Figure 2a shows some examples of the full-image generation.

Loss functions. The patch Wasserstein loss L_W is a patch-level Wasserstein distance loss similar to Wasserstein-GAN (Arjovsky et al., 2017) loss. It forces the discriminator to discriminate between

the real macro patch p^M and the generated macro patch $\tilde{p}^M$, and on the other hand, encourages the generator to confuse the discriminator with seemingly realistic $\tilde{p}^M$. Its complete form is

$$L_W = \mathbb{E}\left[D(T_{(X \to M)}(x|c^M)) \right] - \mathbb{E}\left[D(T_{(m \to M)}(\langle G(z|c_i^m)\rangle_{i=1}^N)) \right], \qquad (1)$$

where $x \sim \mathbb{P}_r$ and $\langle c_i^m \rangle_{i=1}^N \sim \mathcal{U}(S^N, R)$. Note that $\mathbb{P}_r$ is the real data distribution. We also apply Gradient Penalty (Gulrajani et al., 2017) to the patches generation:

$$L_{GP} = \mathbb{E}\left[(\|\nabla_{\tilde{p}^M} D(\tilde{p}^M)\|_2 - 1)^2 \right], \qquad (2)$$

where $\tilde{p}^M \sim \mathbb{P}_g$. Note that $\mathbb{P}_g$ is the generator distribution.

The spatial consistency loss L_S is similar to ACGAN loss (Odena et al., 2017). A slight difference is that c_i^m has relatively more continuous values than the discrete setting of ACGAN. As a result, we apply a distance measurement loss for L_S, which is an L_2-loss between $\tilde{c}^M$ and c^M. It aims to train the generator of COCO-GAN to generate the corresponding micro patch by $G(z|c_i^m)$ with respect to the given spatial condition c_i^m. The spatial consistency loss is

$$L_S = \mathbb{E}\left[\|c^M - \tilde{c}^M\|_2 \right]. \qquad (3)$$

On the other hand, the content consistency loss L_C is similar to a hybrid of infoGAN loss (Chen et al., 2016) and the latent space constraint loss (Chang et al., 2018). The former one uses a separate optimizer to optimize an auxiliary network Q, which aims to reconstruct the original latent vector. The latter one suggests that the latent space consistency loss can be a distance measurement instead of minimizing the KL-divergence as the original infoGAN does. In our experiments, we train the extra Q network with a separate optimizer and directly minimize L_1-loss between $\tilde{z}$ and z. L_C aims to force the generator to produce shared context between patches that share the same latent vector but locate at different micro coordinate positions. The content consistency loss is defined by

$$L_C = \mathbb{E}\left[\|z - \tilde{z}\|_1 \right]. \qquad (4)$$

To ensure that Z, C^m, and C^M are all having a similar scale, we directly concatenate and feed them to the generator. We evaluate the maximum possible pixel position of C^m and C^M, then normalize the range into $[-1, 1]$. For the latent space Z, although using uniform sampling between $[-1, 1]$ should be numerically more compatible with the normalized spatial condition space, we empirically do not observe significant differences even if we switch to random sampling with a zero-mean and unit-variance normal distribution. For simplicity, we adopt uniform sampling strategy throughout our experiments.

Training details. Our generator and discriminator architectures follow the idea of projection discriminator (Miyato & Koyama, 2018), both with ResNet (He et al., 2016) based architecture and adding class-projection to the discriminator. All convolutional and feed-forward layers of generator and discriminator are added with the spectral-normalization scheme (Miyato et al., 2018) as suggested in (Zhang et al., 2018). A more detailed architecture diagram is illustrated in Appendix B.

We also add conditional-batch-normalization (CBN) (Dumoulin et al., 2016) to the generator. In our design, CBN is conditioned on the given spatial positions and the input latent vector. It learns to normalize the feature maps with respect to the given conditions. However, our implementation has a crucial difference from the one described in (Miyato & Koyama, 2018): our spatial positions are real values rather than discrete classes. We alternatively adopt similar strategy to (de Vries et al., 2017) with a slight modification. Instead of using MLPs to produce $\Delta\gamma$ and $\Delta\beta$, we make MLPs directly output γ and β. For a K-channel input feature map i_K with mean recorder μ_K and variance recorder σ_K, we creates two learnable MLP layers, MLP_γ and MLP_β. The output feature map o_M is calculated as

$$o_M = ((i_K - \mu_K)/\sigma_K) * \text{MLP}_\gamma(i_K) + \text{MLP}_\beta(i_K). \qquad (5)$$

We use Adam (Kingma & Ba, 2014) optimizer with $\beta_1 = 0$ and $\beta_2 = 0.999$ for both the generator and the discriminator. The learning rates are based on the Two Time-scale Update Rule (TTUR) (Heusel et al., 2017), setting 0.0001 for the generator and 0.0004 for the discriminator. We do not specifically balance the generator and the discriminator by manually setting how many iterations to update the generator once as described in the WGAN paper (Arjovsky et al., 2017).

(a) CelebA (128×128).   (b) LSUN (256×256).   (a) Micro patch (32×32). (b) Macro patch (64×64).

Figure 2: Without any post-processing, the generated full-images of COCO-GAN are visually smooth and globally coherent. More full-image generation results are shown in Figure 13.

Figure 3: Generated samples of micro/macro patches. Each micro patch, macro patch, and full-image in Figure 2a at the same relative position uses the same latent vector.

3 EXPERIMENTS

Although COCO-GAN framework supports the spatial positions to be uniformly and continuously sampled within normalized range $[-1, 1]$, we empirically find that only sampling the discrete spatial positions that is used to inference will result in better generation quality. For instance, if the full-image is formed by concatenating four micro patches on each axis, the model only uniformly samples spatial positions from the set of four discrete points, $\{-1, -1/3, 1/3, 1\}$ on each axis of the coordinate system. We adopt this uniform and discrete sampling strategy throughout the experiments. The root cause of degradation in generation quality is still unclear. One possible hypothesis is that the task difficulty dramatically increases while sampling with uniform and continuous spatial positions. We flag further analysis and solution toward this phenomenon as an important future research direction.

3.1 QUALITY OF GENERATED IMAGES

We start with validating COCO-GAN on CelebA (Liu et al., 2015) and the bedroom category of LSUN (Yu et al., 2015). For CelebA dataset, the resolutions of full-image, micro patch, and macro patch are 128×128, 32×32, and 64×64, respectively. We choose 32×32 for micro patches in this experiment since smaller patch size would be too small for the model (neither for human) to observe useful information. On the other hand, larger patch size makes macro patch size too similar to the full-image size, which is hard to demonstrate the idea of the discriminator can learn without access to the full-image. For LSUN dataset, the full-image is with 256×256 resolution, micro patches with 64×64 resolution and macro patches with 128×128 resolution. We choose 64×64 for micro patch size in this experiment since the micro patch to full-image ratio is the same with the CelebA experiment.

We report Frchet Inception Distance (FID) (Heusel et al., 2017) in Table 1 as quantitative comparisons with state-of-the-art GANs. Since many other state-of-the-art models do not use full-resolution of the datasets, we accordingly run COCO-GAN in different resolutions without changing hyperparameters other than input size and micro/macro patch size. Throughout these experiments, we choose to always retain the micro patch size to be 1/16 (1/4 for height and 1/4 for width) of the full-image size and macro patch size to be 1/4 (1/2 for height and 1/2 for width) of the full-image size. Without additional hyper-parameter tuning, the results suggest COCO-GAN is both qualitatively and quantitatively competitive with other state-of-the-art GANs.

In Appendix F, we also provide Wasserstein distance and FID score through time as training indicators. The curves suggest that COCO-GAN is stable during training.

Table 1: The FID score suggests that COCO-GAN is competitive with other state-of-the-art GANs. FID scores are measured between 50,000 real and generated samples based on the original implementation provided at https://github.com/bioinf-jku/TTUR.

Dataset	DCGAN + TTUR	PGGAN	WGAN-GP + TTUR	COCO-GAN
CelebA (64×64)	12.5	-	-	**4.99**
CelebA (128×128)	-	**7.30**	-	8.35
LSUN - Bedroom (64×64)	57.5	-	**9.5**	-
LSUN - Bedroom (128×128)	-	-	-	**3.06**
LSUN - Bedroom (256×256)	-	**8.34**	-	16.59

3.2 LATENT SPACE CONTINUITY

To demonstrate more precisely the space continuity of COCO-GAN , we perform the interpolation experiment in three directions: micro patches interpolation, spatial positions interpolation, and full-images interpolation.

- **Micro Patches Interpolation**
  The simplest interpolation experiment is the in-class (*e.g.* fixed spatial condition) interpolation between latent vectors. With a fixed spatial position c_i^{micro}, we randomly sample two latent vectors z_1 and z_2. Then perform interpolation between z_1 and z_2 through a slerp-path (White, 2016). The results in Figure 4a suggest that for each of the spatial position, the latent space Z has continuity.

- **Spatial Positions Interpolation**
  Another simple interpolation experiment is inter-class (*e.g.* between classes) interpolation with a fixed latent vector. We directly linearly-interpolate spatial position between $[-1, 1]$ when the latent vector z is fixed. The results in Figure 5 show that, although we only uniformly sample spatial positions within a discrete spatial position set, the spatial position interpolation is still continuous.

  An interesting observation is about the interpolation at the position between the eyebrows. In this example, COCO-GAN does not know the existence of the smooth area (glabella) between two eyes due to the discrete and sparse spatial positions sampling strategy. Instead, it learns to directly deform the shape of eye to switch from one eye to another. This phenomenon raises an interesting discussion, even the model learns to produce high-quality face images, it still may learn wrong relationship of objects behind the scene.

- **Full-Images Interpolation**
  The hardest interpolation is to directly interpolate full-images between two latent vectors. All micro patches generated with different spatial positions must all change synchronously to make the full-image interpolation smooth. We randomly sample two latent vectors z_1 and z_2. With any given interpolation point z' in the slerp path between z_1 and z_2, the generator uses the full spatial position sequence $\langle c_j^m \rangle_{j=1}^K$ to generate all corresponding patches. Then we merge all generated micro patches with $T_{(m \to M)}$ and forms a full-image x'. The interpolation results in Figure 4a and Figure 4b show that all micro patches can interpolate smoothly and synchronously. This result suggests that COCO-GAN learns the main latent space Z as well as the correlation between micro patches, and the spatial conditions C^m are disentangled.

3.3 PANORAMA GENERATION AND PARTIAL SCENE GENERATION

Generating panoramas using GANs is an interesting problem but has never been carefully investigated. Different from simple image generation, panoramas are expected to be cylindrical and cyclic in the horizontal direction. However, normal GANs do not have built-in ability to handle such cyclic characteristic if without special types of padding mechanism support (Cheng et al., 2018). In contrast, COCO-GAN is a coordinate-system-aware learning framework. We can easily adapt a

|(a) Micro patches interpolation.|(b) Full images interpolation.|

Figure 4: (a) Micro patches interpolation with fixed spatial position. Note that each left-right pair of interpolation sample uses the same latent vectors. (b) Full-images interpolation between two latent vectors. More interpolation results are shown in Appendix D
.

Figure 5: Two examples of spatial positions interpolation for showing the spatial continuity of the micro patches. The spatial conditions are interpolated between range $[-1, 1]$ of the micro coordinate with a fixed latent vector. More examples are shown in Appendix G.

cylindrical coordinate system, and generate panoramas that are cyclic in the horizontal direction as shown in Figure 6 and Figure 7.

To train COCO-GAN with a panorama dataset under a cylindrical coordinate system, the spatial position sampling strategy needs to be slightly modified. In the horizontal direction, the sampled value within the normalized range $[-1, 1]$ is treated as an angular value θ, and then is projected with $\cos(\theta)$ and $\sin(\theta)$ individually to form a unit-circle on a 2D surface. Along with the normal sampling on the vertical axis, a cylindrical coordinate system is formed.

We first take the sky-box format of Matterport3D (Chang et al., 2017) dataset to obtain panoramas for training and testing. The sky-boxes consist of six faces of a 3D cube. We preprocess and project the sky-box to a cylinder using Mercator projection, the resulting cylindrical image size is 768×512. Since the Mercator projection creates extreme sparsity near the northern and southern poles, which lacks information, we directly remove the upper and lower $1/4$ areas. Eventually, the size of panorama we used for training is 768×256 pixels.

We also find COCO-GAN has interesting connection with virtual reality (VR). VR is known to have tight computational budget due to high frame-rate requirement and high resolution demand. It is hard to generate full-scene for VR in real time using standard generative models. Some recent VR studies on omnidirectional view rendering and streaming (Corbillon et al., 2017b; Ozcinar et al., 2017; Corbillon et al., 2017a) are focusing on reducing computational cost or network bandwidth by adapting the user's viewport. COCO-GAN can easily inherit the same strategy and achieve user-viewport-aware partial-scene generation based on its effectiveness in spatial disentanglement and panorama generation. This can largely reduce unnecessary computational cost outside the region of interest, thus making image generation in VR more applicable.

3.4 PATCH-INSPIRED IMAGE GENERATION

The content consistency loss equips the discriminator with the ability to approximate the original latent vector of generated macro patch $\tilde{p}^{macro}$ using the discriminator's auxiliary content vector prediction $\tilde{z}$. This property can also generalize to any real macro patch p^{macro}. The approximation

Figure 6: The generated panorama is cyclic in the horizontal direction since COCO-GAN is trained with a cylindrical coordinate system in this experiment. Here we paste the same generated panorama twice (from $360°$ to $720°$) to illustrate that it indeed has the cyclic property.

Figure 7: More examples of generated panoramas. All samples possess the cyclic property along the horizontal direction. Each sample is generated with a resolution of 768×256 pixels.

process does not require a spatial position; the spatial position is implicitly inferred by the spatial position prediction $\tilde{c}^M$. The generator can accordingly generate a full-image x' with respect to $\tilde{z}$. The generated x' should be partially similar to the given macro patch and also be globally coherent. Such x' can be seen as a generated sample inspired by the given macro patch. One important footnote is that most of the information of a real full-image is lost while retrieving p^M. As a result, the produced **guess** of full-image is not guaranteed to be identical to the original real image. We provides some examples of patch-inspired image generation in Figure 8. The results show that x' can loosely retain some local structure or global characteristic of the original image, such as gender, face direction, and facial expression.

This process is also similar to image inpainting except two key differences. First, the spatial position of the macro patch is not explicitly given. Existing image inpainting frameworks assume the spatial position of remaining parts of the image is known, while COCO-GAN can infer by itself. Second, most inpainting frameworks do not assume the image is extremely damaged, like loosing 75% of information in our examples. In Figure 9, we accordingly compare COCO-GAN with partial convolution (Liu et al., 2018a), which is one of the state-of-the-art image inpainting methods. For the partial convolution method, we simply place the macro patch at the center since the spatial position of the macro patch is unknown. The results show that, unlike COCO-GAN , the partial convolution method (Liu et al., 2018a) cannot handle this situation well.

3.5 COMPUTATION-FRIENDLY GENERATION

Recent studies in high-resolution image generation (Karras et al., 2017; Mescheder et al., 2018) have gained lots of success. We observe a shared conundrum of these existing works is the memory requirement. They usually require some workarounds to improve memory consumption during training, such as decreasing the batch size (Karras et al., 2017) or cutting down the number of feature maps (Mescheder et al., 2018). The memory requirement problem cannot be easily resolved without specific hardware support, which makes the generation of *over* 1024×1024 resolution images hard to achieve. These types of high-resolution images are commonly seen in panoramas, street views, and medical images.

| (a) Real full-images. | (b) Real macro patches. | (c) Patch-inspired macro patch generation. | (d) Patch-inspired full-image generation. |

Figure 8: Patch-inspired image generation can loosely retain some local structure or global characteristic of the original image. The red boxes are the sampled spatial positions that crop the full-images in (a) into the macro patches in (b). (c) & (d) show the patch-inspired generated macro patches and full-images based on $\tilde{z}$. The blue boxes visualize the predicted spatial position $\tilde{c}^m$. Since the information loss of the cropping process (from (a) to (b)) is critical, we do not expect (a) and (d) to be identical. Instead, (b) and (c) should be visually similar and (d) should be globally coherent. More examples are shown in Appendix E.

In contrast, COCO-GAN has spatial disentanglement, which only requires partial views of the full-image for both training and inference. This characteristic largely reduces the minimum memory requirement while dealing with high-resolution images. In Section 3.1, we show that COCO-GAN can generate and compose a 128×128 image with patches of 32×32 resolution. In other words, we can train a CIFAR-10-sized model to generate 128×128 resolution images while the results are still high quality. The characteristic of spatial disentanglement is the first step toward super-high-resolution image generation with limited memory resource. Moreover, some state-of-the-art structures of deep models tend to require more parameters (if without reducing number of channels), such as the skip-connection structure (He et al., 2016) used in projection discriminator (Miyato & Koyama, 2018), inception (Szegedy et al., 2015), and self-attention (Zhang et al., 2018). COCO-GAN is able to equip many of these complex structures since our COCO-GAN model is relatively light-weight with a smaller receptive field and a shallower structure.

Figure 9: Patch-inspired image generation is globally more coherent than the partial convolution method (Liu et al., 2018a).

Furthermore, the spatial disentanglement makes the generation of micro patches independent after the latent vector and the spatial positions are decided. This characteristic enables the generation of micro patches to have high parallelism and take advantage of modern computation architectures.

4 RELATED WORK

Generative Adversarial Network (GAN) (Goodfellow et al., 2014) has shown its potential and flexibility to many different tasks. Recent studies on GANs are focusing on generating high-resolution and high-quality synthetic images in different settings. For instance, generating images with 1024×1024 resolution (Karras et al., 2017; Mescheder et al., 2018), generating images with low-quality synthetic images as condition (Shrivastava et al., 2017), and by applying segmentation map as conditions (Wang et al., 2017). However, these prior work share the similar assumptions: the model must access and generate the full-image in a single shot. This assumption consumes an unavoidable and significant amount of memory when the size of the targeting image is relatively large, and therefore making it difficult to satisfy memory requirements for both training and inference. Searching for a solution towards this problem is one of the initial motivations of this work.

COCO-GAN shares some similarities to Pixel-RNN (van den Oord et al., 2016), which is a pixel-level generation framework while COCO-GAN is a patch-level generation framework. Pixel-RNN transforms the image generation task into a sequence generation task, maximizes the log-likelihood directly. In contrast, COCO-GAN aims at disentangling the spatial dependencies between micro patches. It also utilizes the adversarial loss to ensure smoothness between adjacent micro patches.

CoordConv (Liu et al., 2018b) is another similar work but with fundamental differences. Coord-Conv provides spatial positioning information directly to the convolutional kernels in order to the coordinate transform problem and shows multiple improvements in different tasks. In contrast, COCO-GAN uses spatial conditions as an input condition of the generator and an auxiliary output of the discriminator. This setting enforces both the generator and the discriminator to learn spatial disentanglement and correlations between the generated micro patches. We have also considered incorporating CoordConv into COCO-GAN . However, empirical results show little visual improvement.

Group convolution (Krizhevsky et al., 2012) is another work that is highly related to COCO-GAN . While group convolution aims at reducing computational costs by disentangling channels inside a convolution layer, our model learns to disentangle on the spatial level and is highly parallelizable. However, the micro-patch generation of COCO-GAN uses padding in all feature maps while applying convolution. This problem causes a large number number of FLOPs for each image generation. We are particularly interested in this phenomenon and flag utilizing the spatial disentanglement to reduce the total number of FLOPs as an important future work.

5 CONCLUSION AND DISCUSSION

In this work, we propose a new generative model, COCO-GAN. Through the experiments, we show that COCO-GAN can learn spatial disentanglement with limited partial views. Although COCO-GAN is restrained from accessing the full scene, COCO-GAN can still generate high-quality samples without extra hyper-parameter tuning. We also demonstrate COCO-GAN is a coordinate-system-aware learning framework, and take panorama generation within a cylindrical coordinate system as case study. Furthermore, we highlight the advantages of COCO-GAN by showcasing three applications, including "Patch-Inspired image generation", "User-Viewport-Aware Partial Scene Generation", and "Computation-Friendly Generation".

Despite the generation quality of COCO-GAN being competitive with other state-of-the-art GANs without any post-processing, sometimes we still observe that local structures of generated samples may be discontinued or mottled. This indicates that extra refinements and blending methods are still important for COCO-GAN to generate more stable and reliable samples.

We adopt a discrete uniform sampling strategy over spatial positions since we observe a huge drop in generation quality if we use continuous uniform sampling. Although in practice COCO-GAN successfully learns the spatial disentanglement using discrete sampling, continuous sampling, in theory, should still be preferred over discrete sampling since the spatial domain is continuous. Achieving such a goal would require deeper understanding and insights about the root cause of the generation quality drop.

We demonstrate that COCO-GAN can generate panoramas under a cylindrical coordinate system. However, another commonly used panorama format is sky-sphere under a hyperbolic coordinate system. Consider that the image patches with the hyperbolic coordinate is not square-shaped, further studies on incorporating special convolution schemes like Spherical-CNN (Cohen et al., 2018) and implementing COCO-GAN under a hyperbolic coordinate system would be required.

The size of micro patches is crucial to the results of COCO-GAN. A rule-of-thumb is that the size should be large enough to cover sufficient information. The precise lower bound requires experiments to examine if COCO-GAN learns undesired spatial patterns. Figure 5 shows that the model can be misled to learn reasonable but incorrect spatial relationship. An effective evaluation for the lower bound of the micro patch size is needed as future investigation.

REFERENCES

Martín Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, pp. 214–223, 2017.

Angel X. Chang, Angela Dai, Thomas A. Funkhouser, Maciej Halber, Matthias Nießner, Manolis Savva, Shuran Song, Andy Zeng, and Yinda Zhang. Matterport3d: Learning from RGB-D data in indoor environments. In *2017 International Conference on 3D Vision, 3DV 2017, Qingdao, China, October 10-12, 2017*, pp. 667–676, 2017.

Chia-Che Chang, Chieh Hubert Lin, Che-Rung Lee, Da-Cheng Juan, Wei Wei, and Hwann-Tzong Chen. Escaping from collapsing modes in a constrained space. In *The European Conference on Computer Vision (ECCV)*, September 2018.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 2172–2180, 2016.

Hsien-Tzu Cheng, Chun-Hung Chao, Jin-Dong Dong, Hao-Kai Wen, Tyng-Luh Liu, and Min Sun. Cube padding for weakly-supervised saliency prediction in 360 videos. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Taco S. Cohen, Mario Geiger, Jonas Khler, and Max Welling. Spherical CNNs. In *International Conference on Learning Representations*, 2018.

Xavier Corbillon, Alisa Devlic, Gwendal Simon, and Jacob Chakareski. Optimal set of 360-degree videos for viewport-adaptive streaming. In *Proceedings of the 2017 ACM on Multimedia Conference, MM 2017, Mountain View, CA, USA, October 23-27, 2017*, pp. 943–951, 2017a.

Xavier Corbillon, Gwendal Simon, Alisa Devlic, and Jacob Chakareski. Viewport-adaptive navigable 360-degree video delivery. In *IEEE International Conference on Communications, ICC 2017, Paris, France, May 21-25, 2017*, pp. 1–7, 2017b.

Harm de Vries, Florian Strub, Jérémie Mary, Hugo Larochelle, Olivier Pietquin, and Aaron C. Courville. Modulating early visual processing by language. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 6597–6607, 2017.

Vincent Dumoulin, Jonathon Shlens, and Manjunath Kudlur. A learned representation for artistic style. *CoRR*, abs/1610.07629, 2016.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada*, pp. 2672–2680, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martín Arjovsky, Vincent Dumoulin, and Aaron C. Courville. Improved training of wasserstein gans. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 5769–5779, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pp. 770–778, 2016.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 6629–6640, 2017.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *CoRR*, abs/1710.10196, 2017.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems 25: 26th Annual Conference on Neural Information Processing Systems 2012. Proceedings of a meeting held December 3-6, 2012, Lake Tahoe, Nevada, United States.*, pp. 1106–1114, 2012.

Guilin Liu, Fitsum A. Reda, Kevin J. Shih, Ting-Chun Wang, Andrew Tao, and Bryan Catanzaro. Image inpainting for irregular holes using partial convolutions. *CoRR*, abs/1804.07723, 2018a.

Rosanne Liu, Joel Lehman, Piero Molino, Felipe Petroski Such, Eric Frank, Alex Sergeev, and Jason Yosinski. An intriguing failing of convolutional neural networks and the coordconv solution. *CoRR*, abs/1807.03247, 2018b.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Lars M. Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for gans do actually converge? In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, pp. 3478–3487, 2018.

Takeru Miyato and Masanori Koyama. cgans with projection discriminator. *CoRR*, abs/1802.05637, 2018.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *CoRR*, abs/1802.05957, 2018.

Augustus Odena, Christopher Olah, and Jonathon Shlens. Conditional image synthesis with auxiliary classifier gans. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, pp. 2642–2651, 2017.

Cagri Ozcinar, Ana De Abreu, and Aljosa Smolic. Viewport-aware adaptive 360 video streaming using tiles for virtual reality. In *2017 IEEE International Conference on Image Processing, ICIP 2017, Beijing, China, September 17-20, 2017*, pp. 2174–2178, 2017.

Ashish Shrivastava, Tomas Pfister, Oncel Tuzel, Joshua Susskind, Wenda Wang, and Russell Webb. Learning from simulated and unsupervised images through adversarial training. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 2242–2251, 2017.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott E. Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2015, Boston, MA, USA, June 7-12, 2015*, pp. 1–9, 2015.

Aäron van den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, pp. 1747–1756, 2016.

Ting-Chun Wang, Ming-Yu Liu, Jun-Yan Zhu, Andrew Tao, Jan Kautz, and Bryan Catanzaro. High-resolution image synthesis and semantic manipulation with conditional gans. *CoRR*, abs/1711.11585, 2017.

Tom White. Sampling generative networks: Notes on a few effective techniques. *CoRR*, abs/1609.04468, 2016.

Fisher Yu, Yinda Zhang, Shuran Song, Ari Seff, and Jianxiong Xiao. LSUN: construction of a large-scale image dataset using deep learning with humans in the loop. *CoRR*, abs/1506.03365, 2015.

Han Zhang, Ian J. Goodfellow, Dimitris N. Metaxas, and Augustus Odena. Self-attention generative adversarial networks. *CoRR*, abs/1805.08318, 2018.

APPENDIX A   COCO-GAN DURING TESTING PHASE

Figure 10: An overview of COCO-GAN during testing phase. The micro patches generated by G are directly combined into a full-image as the final output.

APPENDIX B   MODEL ARCHITECTURE DETAILS

(a) Generator Overall Architecture

(b) Generator Residual Block

Figure 11: The detailed generator architecture of COCO-GAN for generating micro patches with a size of 32×32 pixels. We directly duplicate/remove the last residual block if we need to enlarge/reduce the size of output patch.

(a) Discriminator Overall Architecture (b) Discriminator Residual Block

(c) Discriminator Auxiliary Head

Figure 12: The detailed discriminator architecture of COCO-GAN for discriminate macro patches with a size of 64×64 pixels. We directly duplicate/remove the first residual block if we need to enlarge/reduce the input patch size. Both the content vector prediction head (Q) and the spatial condition prediction head use the same structure shown in (c).

APPENDIX C MORE FULL-IMAGE GENERATION EXAMPLES

(a) CelebA 128×128

(b) LSUN (bedroom) 256×256

Figure 13: More full-image generation examples of COCO-GAN.

APPENDIX D   MORE INTERPOLATION EXAMPLES

Micro Patches Interpolation   **Full-Images Interpolation**

(a) CelebA (128 × 128).

Micro Patches Interpolation   **Full-Images Interpolation**

(b) LSUN (bedroom category) (256 × 256).

Figure 14: More interpolation examples. Given two latent vectors, COCO-GAN generates the micro patches and full-images that correspond to the interpolated latent vectors.

APPENDIX E   PATCH-INSPIRED IMAGE GENERATION

(a) (CelebA 128×128) Real full-images.   (b) (CelebA 128×128) Real macro patches.

(c) (CelebA 128×128) Patch-inspired full-image gen-   (d) (CelebA 128×128) Patch-inspired macro patch
eration.   generation.

Figure 15: Patch-inspired image generation can loosely retain some local structure or global characteristic of the original image. The red boxes are the sampled spatial positions that crop the full-images in (a) into the macro patches in (b). (c) & (d) show the patch-inspired generated macro patches and full-images based on $\tilde{z}$. The blue boxes visualize the predicted spatial position $\tilde{c}^m$. Since the information loss of the cropping process (from (a) to (b)) is critical, we do not expect (a) and (c) to be identical. Instead, (b) and (d) should be visually similar and (d) should be globally coherent.

(a) (LSUN 256×256) Real full-images.

(b) (LSUN 256×256) Real macro patches.

(c) (LSUN 256×256) Patch-inspired full-image generation.

(d) (LSUN 256×256) Patch-inspired macro patch generation.

Figure 16: Patch-inspired image generation can loosely retain some local structure or global characteristic of the original image. The red boxes are the sampled spatial positions that crop the full-images in (a) into the macro patches in (b). (c) & (d) show the patch-inspired generated macro patches and full-images based on $\tilde{z}$. The blue boxes visualize the predicted spatial position $\tilde{c}^m$. Since the information loss of the cropping process (from (a) to (b)) is critical, we do not expect (a) and (c) to be identical. Instead, (b) and (d) should be visually similar and (d) should be globally coherent. **Note that the diversity and difficulty of LSUN (bedroom category) is higher than CelebA. The Q network can only capture the structure, shape, and orientation of the room and the bed, but it fails to capture detailed texture of objects**.

APPENDIX F   TRAINING INDICATORS

(a) Wasserstein distance

(b) FID

Figure 17: Both Wasserstein distance and FID through time show that the training of COCO-GAN is stable. Both two figures are logged while training on CelebA with 128×128 resolution.

APPENDIX G   SPATIAL POSITIONS INTERPOLATION

Figure 18: Spatial interpolation shows the spatial continuity of the micro patches. The spatial conditions are interpolated between range $[-1, 1]$ of the micro coordinate with a fixed latent vector.