GENERALIZING ACROSS DOMAINS VIA CROSS-GRADIENT TRAINING

ABSTRACT

We present CROSSGRAD, a method to use multi-domain training data to learn a classifier that generalizes to new domains. CROSSGRAD does not need an adaptation phase via labeled or unlabeled data, or domain features in the new domain. Most existing domain adaptation methods attempt to erase domain signals using techniques like domain adversarial training. In contrast, CROSSGRAD is free to use domain signals for predicting labels, if it can prevent overfitting on training domains. We conceptualize the task in a Bayesian setting, in which a sampling step is implemented as data augmentation, based on domain-guided perturbations of input instances. CROSSGRAD jointly trains a label and a domain classifier on examples perturbed by loss gradients of each other's objectives. This enables us to directly perturb inputs, without separating and re-mixing domain signals while making various distributional assumptions. Empirical evaluation on three different applications where this setting is natural establishes that (1) domain-guided perturbation provides consistently better generalization to unseen domains, compared to generic instance perturbation methods, and that (2) data augmentation is a more stable and accurate method than domain adversarial training.

1 INTRODUCTION

We investigate how to train a classification model using multi-domain training data, so as to generalize to labeling instances from unseen domains. This problem arises in many applications, viz., handwriting recognition, speech recognition, sentiment analysis, and sensor data interpretation. In these applications, domains may be defined by fonts, speakers, writers, etc. Most existing work on handling a target domain not seen at training time requires either labeled or unlabeled data from the target domain at test time. Often, a separate "adaptation" step is then run over the source and target domain instances, only after which target domain instances are labeled. In contrast, we consider the situation where, during training, we have labeled instances from several domains which we can collectively exploit so that the trained system can handle new domains without the adaptation step.

1.1 PROBLEM STATEMENT

Let $\mathcal{D}$ be a space of domains. During training we get labeled data from a proper subset $D \subset \mathcal{D}$ of these domains. Each labeled example during training is a triple $(\mathbf{x}, y, d)$ where $\mathbf{x}$ is the input, $y \in \mathcal{Y}$ is the true class label from a finite set of labels $\mathcal{Y}$ and $d \in D$ is the domain from which this example is sampled. We must train a classifier to predict the label y for examples sampled from all domains, including the subset $\mathcal{D} \setminus D$ not seen in the training set. Our goal is high accuracy for both in-domain (i.e., in D) and out-of-domain (i.e., in $\mathcal{D} \setminus D$) test instances.

One challenge in learning a classifier that generalizes to unseen domains is that $\Pr(y|\mathbf{x})$ is typically harder to learn than $\Pr(y|\mathbf{x}, d)$. While Yang & Hospedales (2015) addressed a similar setting, they assumed a specific geometry characterizing the domain, and performed kernel regression in this space. In contrast, in our setting, we wish to avoid any such explicit domain representation, appealing instead to the power of deep networks to discover implicit features.

Lacking any feature-space characterization of the domain, conventional training objectives (given a choice of hypotheses having sufficient capacity) will tend to settle to solutions that overfit on the set of domains seen during training. A popular technique in the domain adaptation literature to

generalize to new domains is domain adversarial training (Ganin et al., 2016; Tzeng et al., 2017). As the name suggests, here the goal is to learn a transformation of input $\mathbf{x}$ to a domain-independent representation, with the hope that amputating domain signals will make the system robust to new domains. We show in this paper that such training does not necessarily safeguard against over-fitting of the network as a whole. We also argue that even if such such overfitting could be avoided, we do not necessarily want to wipe out domain signals, if it helps achieve high accuracy for in-domain test instances.

1.2 CONTRIBUTION

In a marked departure from domain adaptation via amputation of domain signals, we approach the problem using a form of data augmentation based on domain-guided perturbations of input instances. If we could model exactly how domain signals for d manifest in $\mathbf{x}$, we could simply replace these signals with those from suitably sampled other domains d' to perform data augmentation. We first conceptualize this in a Bayesian setting: discrete domain d 'causes' continuous multivariate $\mathbf{g}$, which, in combination with y, 'causes' $\mathbf{x}$. Given an instance $\mathbf{x}$, if we can recover $\mathbf{g}$, we can then perturb $\mathbf{g}$ to $\mathbf{g}'$, thus generating an augmented instance $\mathbf{x}'$. Because such perfect domain perturbation is not possible in reality, we first design an (imperfect) domain classifier network to be trained with a suitable loss function. Given an instance $\mathbf{x}$, we use the loss gradient w.r.t. $\mathbf{x}$ to perturb $\mathbf{x}$ in directions that change the domain classifier loss the most. The training loss for the y-predictor network on original instances is combined with the training loss on the augmented instances. We call this approach *cross-gradient training*, which is embodied in a system we describe here, called CROSSGRAD. We carefully study the performance of CROSSGRAD on a variety of domain adaptive tasks: character recognition, handwriting recognition and spoken word recognition. We demonstrate performance gains on new domains without any out-of-domain instances available at training time.

2 RELATED WORK

Domain adaptation has been studied under many different settings: two domains (Ganin et al., 2016; Tzeng et al., 2017) or multiple domains (Mansour et al., 2009; Zhang et al., 2015), with target domain data that is labeled (Daumé III, 2007; Daumé III et al., 2010; Saenko et al., 2010) or unlabeled (Gopalan et al., 2011; Gong et al., 2012; Ganin et al., 2016), paired examples from source and target domain (Peng et al., 2017), or domain features attached with each domain (Yang & Hospedales, 2016). Domain adaptation techniques have been applied to numerous tasks in speech, language processing and computer vision (Woodland, 2001; Saon et al., 2013; Jiang & Zhai, 2007; Daumé III, 2007; Saenko et al., 2010; Gopalan et al., 2011; Li et al., 2013; Huang & Belongie, 2017; Upchurch et al., 2016). However, unlike in our setting, these approaches typically assume the availability of some target domain data which is either labeled or unlabeled.

For neural networks a recent popular technique is domain adversarial networks (DANs) (Tzeng et al., 2015; 2017; Ganin et al., 2016). The main idea of DANs is to learn a representation in the last hidden layer (of a multilayer network) that cannot discriminate among different domains in the input to the first layer. A domain classifier is created with the last layer as input. If the last layer encapsulates no domain information apart from what can be inferred from the label, the accuracy of the domain classifier is low. The DAN approach makes sense when all domains are visible during training. In this paper, our goal is to generalize to unseen domains.

Ganin et al. (2016) tackle a similar problem. They use a DAN to achieve domain generalization. A major flaw in this approach is that DANs can be easily misled by a representation layer that overfits the set of training domains. In the extreme case, a representation that simply outputs label logits via a last linear layer (making the softmax layer irrelevant) can keep both the adversarial loss and label loss small, and yet not be able to generalize to new test domains. In other words, not being able to infer the domain from the last layer does not imply that the classification is domain-robust.

Our Bayesian model to capture the dependence among label, domains, and input is similar to Zhang et al. (2015, Fig. 1d), but the crucial difference is the way the dependence is modeled and estimated.

Since we do not assume any extra information about the test domains, conventional ML approaches for generalizability are also relevant. Of these, the method most related is the adversarial training of (Goodfellow et al., 2014; Miyato et al., 2016) that perturbs examples along the gradient of the clas-

sifier loss. The only extra information we possess is that training data is grouped by domain labels. Our method attempts to model domain variation in a continuous space and project perturbation in that space to the instances.

3 OUR APPROACH

We assume that input objects are characterized by two uncorrelated or weakly correlated tags: their *label* and their *domain*. E.g. for a set of typeset characters, the label could be the corresponding character of the alphabet ('A', 'B' etc) and the domain could be the font used to draw the character. In general, it should be possible to change any one of these, while holding the other fixed.

We use a Bayesian network to model the dependence among the label y, domain d, and input $\mathbf{x}$ as shown in Figure 1. Variables $y \in \mathcal{Y}$ and $d \in \mathcal{D}$ are discrete and $\mathbf{g} \in \mathbb{R}^q, \mathbf{x} \in \mathbb{R}^r$ lie in continuous multi-dimensional spaces. The domain d induces a set of latent domain features $\mathbf{g}$. The input $\mathbf{x}$ is

Figure 1: Bayesian network to model dependence between label y, domain d, and $\mathbf{x}$.

obtained by a complicated, un-observed mixing[1] of y and $\mathbf{g}$. In the training sample L, nodes $y, d, \mathbf{x}$ are observed but L spans only a proper subset D of the set of all domains $\mathcal{D}$. During inference, only $\mathbf{x}$ is observed and we need to compute the posterior $\Pr(y|\mathbf{x})$. As reflected in the network, y is not independent of d given $\mathbf{x}$. However, since d is discrete and we observe only a subset of d's during training, we need to make additional assumptions to ensure that we can generalize to a new d during testing. The assumption we make is that integrated over the training domains the distribution $P(\mathbf{g})$ of the domain features is well-supported in L. More precisely, generalizability of a training set of domains D to the universe of domains $\mathcal{D}$ requires that

$$P(\mathbf{g}) = \sum_{d \in \mathcal{D}} P(\mathbf{g}|d)P(d) \approx \sum_{d \in D} P(\mathbf{g}|d)\frac{P(d)}{P(D)} \tag{A1}$$

Under this assumption $P(\mathbf{g})$ can be modeled during training, so that during inference we can infer y for a given $\mathbf{x}$ by estimating

$$\Pr(y|\mathbf{x}) = \sum_{d \in \mathcal{D}} \Pr(y|\mathbf{x}, d) \Pr(d|\mathbf{x}) = \int_{\mathbf{g}} \Pr(y|\mathbf{x}, \mathbf{g}) \Pr(\mathbf{g}|\mathbf{x}) \approx \Pr(y|\mathbf{x}, \hat{\mathbf{g}}) \tag{1}$$

where $\hat{\mathbf{g}} = \text{argmax}_{\mathbf{g}} \Pr(\mathbf{g}|\mathbf{x})$ is the inferred continuous representation of the domain of $\mathbf{x}$.

We next elaborate on how we estimate $\Pr(y|\mathbf{x}, \hat{\mathbf{g}})$ and $\hat{\mathbf{g}}$ using the domain labeled data $L = \{(\mathbf{x}, y, d)\}$. The main challenge in this task is to ensure that the model for $\Pr(y|\mathbf{x}, \hat{\mathbf{g}})$ is not over-fitted on the inferred $\mathbf{g}$'s of the training domains. In many applications, the per-domain $\Pr(y|\mathbf{x}, d)$ is significantly easier to train. So, an easy local minima is to choose a different $\mathbf{g}$ for each training d and generate separate classifiers for each distinct training domain. We must encourage the network to stay away from such easy solutions. We strive for generalization by moving along the continuous space $\mathbf{g}$ of domains to sample new training examples from hallucinated domains. Ideally, for each training instance $(\mathbf{x}_i, y_i)$ from a given domain d_i, we wish to generate a new $\mathbf{x}'$ by transforming its

---

[1]The dependence of y on $\mathbf{x}$ could also be via continuous hidden variables but our model for domain generalization is agnostic of such structure.

(inferred) domain $\mathbf{g}_i$ to a random domain sampled from $P(\mathbf{g})$, keeping its label y_i unchanged. Under the domain continuity assumption (A1), a model trained with such an ideally augmented dataset is expected to generalize to domains in $\mathcal{D} \setminus D$.

However, there are many challenges to achieving such ideal augmentation. To avoid changing y_i, it is convenient to draw a sample $\mathbf{g}$ by perturbing $\mathbf{g}_i$. However, $\mathbf{g}_i$ may not be reliably inferred, leading to a distorted sample of $\mathbf{g}$. For example, if the $\mathbf{g}_i$ obtained from an imperfect extraction conceals label information, then big jumps in the approximate $\mathbf{g}$ space could change the label too. We propose a more cautious data augmentation strategy that makes only small moves along the estimated domain features of an input. We arrive at our method in three steps, as follows.

Domain inference: We create a model $G(\mathbf{x})$ to extract domain features $\mathbf{g}$ from an input $\mathbf{x}$. We supervise the training of G to predict the domain label d_i as $S(G(\mathbf{x}_i))$ where S is a softmax transformation. We use J_d to denote the cross-entropy loss function of this classifier. Specifically, $J_d(\mathbf{x}_i, d_i)$ is the domain loss at the current instance.

Domain perturbation: Given an example $(\mathbf{x}_i, y_i, d_i)$, we seek to sample domain features $\mathbf{g}_i'$ that would correspond to an example $(\mathbf{x}_i', y_i)$ (i.e., with the same label y_i), whose domain is as "far" from d_i as possible. To this end, consider setting $\mathbf{g}_i' = \hat{\mathbf{g}}_i + \epsilon \nabla_{\hat{\mathbf{g}}_i} J_d(\mathbf{x}_i, d_i)$, where $\hat{\mathbf{g}}_i = G(\mathbf{x}_i)$ and ϵ is a suitable step size. The direction of this perturbation roughly corresponds to changing the domain as much as possible, for a given budget of $\|\mathbf{g}_i' - \hat{\mathbf{g}}_i\|$. However, this approach presupposes that the direction of domain change in our domain classifier is not highly correlated with the direction of label change. To enforce this in our model, we shall train the domain feature extractor G to avoid domain shifts when the data is perturbed to cause label shifts.

Recovering perturbed input: Having sampled $\mathbf{g}_i'$ as above, we define our new augmented input instance $\mathbf{x}_i'$ as

$$G^{-1}(\mathbf{g}_i') = G^{-1}\big(G(\mathbf{x}_i) + \epsilon \nabla_{\hat{\mathbf{g}}_i} J_d(\mathbf{x}_i, d_i)\big).$$

We show next that the perturbed $\mathbf{x}_i'$ can be approximated by $\mathbf{x}_i + \epsilon' \nabla_{\mathbf{x}_i} J_d(\mathbf{x}_i, d_i)$.

In this proof we drop the subscript i for ease of notation. In the forward direction, the relationship between $\Delta \mathbf{x}$ and $\Delta \hat{\mathbf{g}}$ can be expressed using the Jacobian $\mathbb{J}$ of $\hat{\mathbf{g}}$ w.r.t. $\mathbf{x}$:

$$\Delta \hat{\mathbf{g}} = \mathbb{J} \Delta \mathbf{x} \tag{2}$$

To invert the relationship for a non-square and possibly low-rank Jacobian, we use the Jacobian transpose method devised for inverse kinematics (Balestrino et al., 1984; Wolovich & Elliott, 1984). Specifically, we write $\Delta \hat{\mathbf{g}} = \hat{\mathbf{g}}(\mathbf{x}') - \hat{\mathbf{g}}(\mathbf{x})$, and recast the problem as trying to minimize the squared L2 error

$$L_{\hat{\mathbf{g}}}(\mathbf{x}) = \tfrac{1}{2} \left(\hat{\mathbf{g}}(\mathbf{x}') - \hat{\mathbf{g}}(\mathbf{x})\right)^\top \left(\hat{\mathbf{g}}(\mathbf{x}') - \hat{\mathbf{g}}(\mathbf{x})\right)$$

with gradient descent. The gradient of the above expression w.r.t. $\mathbf{x}$ is

$$\theta_d = (\theta_d^1, \theta_d^2)$$

Figure 2: CROSSGRAD network design.

$$\nabla_{\mathbf{x}} L_{\hat{\mathbf{g}}} \quad = \quad -\left(\Delta \hat{\mathbf{g}}^\top \frac{\partial \hat{\mathbf{g}}}{\partial \mathbf{x}}\right)^\top \quad = \quad -\mathbb{J}^\top \Delta \hat{\mathbf{g}}$$

Hence, the necessary gradient descent step to affect a change of $\Delta \hat{\mathbf{g}}$ in the domain features would increment $\mathbf{x}$ by $\epsilon' \mathbb{J}^\top \Delta \hat{\mathbf{g}}$. Assuming local linearity and for a suitable ϵ', we can approximate the complete gradient descent process with this single step. The Jacobian, which is a matrix of first partial derivatives, can be computed by back-propagation. Thus we get

$$\Delta \mathbf{x} = \epsilon' \mathbb{J}^\top \nabla_{\hat{\mathbf{g}}} J_d(\hat{\mathbf{g}}, d) = \epsilon' \sum_i \frac{\partial \hat{g}^i}{\partial \mathbf{x}}^\top \frac{\partial J_d(\hat{\mathbf{g}}, d)}{\partial \hat{g}^i}, \tag{3}$$

which, by the chain rule, gives

$$\Delta \mathbf{x} = \epsilon' \nabla_{\mathbf{x}} J_d(\mathbf{x}, d). \tag{4}$$

The above development leads to the network sketched in Figure 2, and an accompanying training algorithm, CROSSGRAD, shown in Algorithm 1. Our proposed method integrates data aug-

mentation and batch training as an alternating sequence of steps. We compute not only the standard $\nabla_X J_l(X, Y; \theta_l)$, but also the complementary $\nabla_X J_d(X, D; \theta_d)$. Here X, Y, D correspond to a minibatch of instances. Next we construct cross-objectives $\tilde{J}_l$ and $\tilde{J}_d$, and update their respective parameter spaces

---

Algorithm 1 CROSSGRAD training pseudocode.

1: **Input:** Labeled data $\{(\mathbf{x}_i, y_i, d_i)\}_{i=1}^M$, step sizes ϵ_l, ϵ_d, learning rate η, data augmentation weights α_l, α_d, number of training steps n.
2: **Output:** Label and domain classifier parameters θ_l, θ_d
3: Initialize θ_l, θ_d $\{J_l, J_d$ are loss functions for the label and domain classifiers, respectively$\}$
4: **for** n training steps **do**
5:     Sample a labeled batch (X, Y, D)
6:     $X_d := X + \epsilon_l \cdot \nabla_X J_d(X, D; \theta_d)$
7:     $X_l := X + \epsilon_d \cdot \nabla_X J_l(X, Y; \theta_l)$
8:     $\theta_l \leftarrow \theta_l - \eta \nabla_{\theta_l}((1 - \alpha_l) J_l(X, Y; \theta_l) + \alpha_l J_l(X_d, Y; \theta_l)$
9:     $\theta_d \leftarrow \theta_d - \eta \nabla_{\theta_d}((1 - \alpha_d) J_d(X, D; \theta_d) + \alpha_d J_d(X_l, D; \theta_d)$
10: **end for**

If y and d are completely correlated, CROSSGRAD reduces to traditional adversarial training. If, on the other extreme, they are perfectly uncorrelated, removing domain signal should work well. The interesting and realistic situation is where they are only partially correlated. CROSSGRAD is designed to handle the whole spectrum of correlations.

4 EXPERIMENTS

In this section we demonstrate that CROSSGRAD provides effective domain generalization on four different classification tasks under three different model architectures. We provide evidence that our Bayesian characterization of domains as continuous features is responsible for such generalization. We establish that CROSSGRAD's domain guided perturbations provides a more consistent generalization to new domains than label adversarial perturbation (Goodfellow et al., 2014). Also, we show that DANs, a popular domain adaptation method that suppresses domain signals, provides little improvements over the baseline (Ganin et al., 2016; Tzeng et al., 2017).

We describe the four different datasets and present a summary in Table 3.

Character recognition across fonts We created this dataset from Google Fonts[2]. The task is to identify the character, and the fonts of the characters are considered as domains. The label set consists of twenty-six letters of the alphabet and ten numbers. The data consists of a mix of 109 fonts which are partitioned among train, test and validation folds in the proportion 65%, 25%, and 10%. For each font and label, two to eighteen images are generated by randomly rotating the image around the center and adding pixel-level random noise. The neural network is LeNet (LeCun et al., 1998) modified to have three pooled convolution layers instead of two and ReLU activations instead of tanh.

Handwriting recognition across authors We use the LipiTk dataset that comprises various handwritten characters from the Devanagari script made available by HP Labs as part of the Indic script corpus[3]. Each writer of the characters is considered as a domain, and the task is to recognize the character. The images are split among train, test and validation sets in the proportions of 65%, 15%, 25% respectively. The neural network for this dataset is the same as for the fonts dataset above.

MNIST across synthetic domains This dataset derived from MNIST was introduced by Motiian et al. (2017). Here, labels comprise the 10 digits and domains are created by rotating the images in multiples of 15 degrees: 0, 15, 30, 45, 60 and 75. The domains are labeled with the angle by which they are rotated, e.g., M15, M30, M45. We tested on domain M15 while training on the rest. The network is the 2-layer convolutional one used by Motiian et al. (2017).

---

[2] https://fonts.google.com/?category=Handwriting&subset=latin
[3] http://lipitk.sourceforge.net/hpl-datasets.htm

Dataset	Label	Domain
Font	36 characters	109 fonts
Handwriting	111 characters	74 authors
MNIST	10 digits	6 rotations
Speech	12 commands	1888 speakers

Table 3: Summary of datasets.

Spoken word recognition across users This is the Google Speech Command Dataset[4] that consists of spoken word commands from a large number of speakers in different acoustic settings. The task is to identify the spoken words. The domains are the speakers. We used 20% of domains each for testing and validation. The number of training domains was 100 for the experiments in Table 4. We also report numbers with varying number of domains later in Table 8. We use the architecture of Sainath & Parada (2015) [5].

For all four datasets, the set of domains in the training, test, and validation sets were kept totally disjoint. We selected the various hyper-parameters based on accuracy on the validation set as follows. For LABELGRAD the parameter α was chosen from $\{0.1, 0.25, 0.75, 0.5, 0.9\}$ and for CROSSGRAD we chose $\alpha_l = \alpha_d$ from the same set of values. We chose ϵ ranges so that L_∞ norm of the perturbations are of similar sizes in LABELGRAD and CROSSGRAD. The multiples in the ϵ range came from $\{0.5, 1, 2, 2.5\}$. The optimizer for the first three datasets is RMS prop with a learning rate of 0.02 whereas for the last Speech dataset it is SGD.

4.1 Overall comparison

In Table 4 we compare CROSSGRAD with domain adversarial networks (DAN), label adversarial perturbation (LABELGRAD), and a baseline that performs no special training. For the MNIST dataset the baseline is CCSA (Motiian et al., 2017). We observe that, for all four datasets, CROSSGRAD provides an accuracy improvement. DAN, which is designed specifically for domain adaptation, is worse than LABELGRAD, which does not exploit domain signal in any way. While the gap between LABELGRAD and CROSSGRAD is not dramatic, it is consistent as supported by this table and other experiments that we later describe.

Method Name	Fonts	Handwriting	MNIST	Speech
Baseline	68.5	82.5	95.6	72.6
DAN	68.9	83.8	98.0	70.4
LABELGRAD	71.4	86.3	97.8	72.7
CROSSGRAD	**72.6**	**88.6**	**98.6**	**73.5**

Table 4: Accuracy on four different datasets. The baseline for MNIST is CCSA.

Changing model architecture In order to make sure that these observed trends hold across model architectures, we compare different methods with the model changed to a 2-block ResNet (He et al., 2016) instead of LeNet (LeCun et al., 1998) for the Fonts and Handwriting dataset in Table 5. For both datasets the ResNet model is significantly better than the LeNet model. But even for the higher capacity ResNet model, CROSSGRAD surpasses the baseline accuracy.

Method Name	Fonts		Handwriting	
	LeNet	ResNet	LeNet	ResNet
Baseline	68.5	80.2	82.5	91.5
DAN	68.9	81.1	83.8	88.5
LABELGRAD	71.4	80.5	86.3	91.8
CROSSGRAD	**72.6**	**82.4**	**88.6**	**92.1**

Table 5: Accuracy with varying model architectures.

---

[4] https://research.googleblog.com/2017/08/launching-speech-commands-dataset.html

[5] We use the code available in tensorflow https://www.tensorflow.org/versions/master/tutorials/audio_recognition

(a) **g** of domain *45* lies between **g** of *60* and *30*.

(b) **g** of domain *15* lies between **g** of *0* and *30*.

(c) Adding **g** of perturbed domain *45* to above.

(d) Adding **g** of perturbed domain *15* to above.

Figure 6: Comparing domain embeddings (**g**) across domains. Each color denotes a domain.

4.2 WHY DOES CROSSGRAD WORK?

We present insights on the working of CROSSGRAD via experiments on the MNIST dataset where the domains corresponding to image rotations are easy to interpret.

In Figure 6a we show PCA projections[6] of the **g** embeddings for images for three different domains, corresponding to rotations by *30, 45, 60* degrees in green, blue, and yellow respectively. The **g** embeddings of domain *45* (blue) lies in between the **g** of domains *30* (green) and *60* (yellow) showing that the domain classifier has successfully extracted continuous representation of the domain even when the input domain labels are categorical. Figure 6b shows the same pattern for domains *0, 15, 30*. Here again we see that the embedding of domain *15* (blue) lies in-between that of domain *0* (yellow) and *30* (green).

Next, we show that the **g**, perturbed along gradients of domain loss, does manage to generate images that substitute for the missing domains during training. The CROSSGRAD perturbations on one domain generates embeddings that are closer to the embeddings from other domains. For example, the embeddings of the domain *45*, when perturbed, scatters towards the domain *30* and *60* as can be seen in Figure 6c: note the scatter of *perturbed 45* (red) points inside the *30* (green) zone, without any *45* (blue) points. Figure 6d depicts a similar pattern with perturbed domain embedding points (red) scattering towards domains *30* and *0* more than unperturbed domain *15* (blue). For example, between x-axis -1 and 1 dominated by the green domain (domain *30*) we see many more red points (perturbed domain *15*) than blue points (domain *15*). Similarly in the lower right corner of domain *0* shown in yellow. This highlights the mechanism of CROSSGRAD working; that it is able to augment training with samples closer to unobserved domains.

---

[6]We got similar patterns on t-SNE projections.

(a) Domain M30   (b) Domain M45

Figure 7: Comparing domains embeddings (**g**) across labels. Each color denotes a label. Unclustered colors indicates that label information is mostly absent from **g**.

Finally, we observe in Figure 7 that the embeddings are not correlated with labels. For both domains *30* and *45* the colors corresponding to different labels are not clustered. This is a consequence of CROSSGRAD's symmetric training of the domain classifier via label-loss perturbed images.

4.3 WHEN IS DOMAIN GENERALIZATION EFFECTIVE?

We next present couple of experiments that provide insights on the settings in which CROSSGRAD is most effective.

First, we show the effect of increasing number of training domains. Intuitively, we expect CROSS-GRAD to be most useful when training domains are scarce and do not directly cover the test domains. We verified this on the speech dataset where the number of available domains is large. We varied the number of training domains while keeping the test and validation data fixed. Table 8 summarizes our results. Note that CROSSGRAD outperforms the baseline and LABELGRAD most significantly when the number of training domains is small (40). As the training data starts to cover more and more of the possible domain variations, the marginal improvement provided by CROSSGRAD decreases. In fact, when the models are trained on the full training data (consisting of more than 1000 domains), the baseline achieves an accuracy of 88.3%, and the accuracy difference of both CROSSGRAD and LABELGRAD is statistically insignificant. DAN, like in other datasets, provides unstable gains and is difficult to tune. LABELGRAD shows smaller relative gains than CROSSGRAD but follows the same trend of reducing gains with increasing number of domains.

Method Name	40 domains	100 domains	200 domains	1000 domains
Baseline	62.2	72.6	79.1	88.3
LABELGRAD	+1.4	+0.1	-0.1	-0.7
DAN	+0.4	-2.2	+0.7	-3.3
CROSSGRAD	+2.3	+0.9	+0.7	-0.4

Table 8: Accuracy on Google Speech Command Task. For each method we show the relative improvement (positive or negative) over the baseline.

Next, we show that CROSSGRAD is more effective for test domains that can be interpolated from the training domains. We illustrate this effect on the MNIST dataset where the domains correspond to rotations and therefore there is an easy way to characterize interpolation.

Test domains →	M0	M15	M30	M45	M60	M75
CCSA	84.6	95.6	94.6	82.9	94.8	82.1
LABELGRAD	**89.7**	97.8	98.1	97.1	96.6	**92.1**
DAN	86.7	98.0	97.8	97.4	96.9	89.1
CROSSGRAD	88.3	**98.6**	**98.0**	**97.7**	**97.7**	91.4

Table 9: Accuracy on rotated MNIST.

We conducted leave-one-domain-out experiments by picking one domain as the test domain, and providing the others as training domains. In Table 9 we compare the accuracy of different methods. We also compare against the numbers reported by the CCSA method of domain generalization (Motiian et al., 2017) as reported by the authors. CROSSGRAD performs better than other methods when test domains are M15, M30, M45 and M60. Each of these can be interpolated from their corresponding training domains. As we showed in Figures 6c and 6d, the perturbed **g** during training covers for the missing test domains. In contrast when M0 or M75 are in the test set, CROSSGRAD's domain loss gradient does not point in the direction of domains outside the training domains.

5   CONCLUSION

Domain d and label y interact in complicated ways to influence the observable input **x**. Most domain adaption strategies implicitly consider domain signal to be extraneous and seek to remove its effect to train more robust label predictors. We presented CROSSGRAD, which considers them in a more symmetric manner. CROSSGRAD provides a new data augmentation scheme based on the y (respectively, d) predictor using the gradient of the d (respectively, y) predictor over the input space, to generate perturbations. Experiments comparing CROSSGRAD with various recent adversarial paradigms show that CROSSGRAD can make better use of partially correlated y and d, without requiring explicit distributional assumptions about how they affect **x**. CROSSGRAD is at its best when training domains are scarce and do not directly cover test domains well. Future work includes extending CROSSGRAD to exploit labeled or unlabeled data in the test domain, and integrating the best of the LABELGRAD and CROSSGRAD into a single algorithm.

REFERENCES

A. Balestrino, G. De Maria, and L. Sciavicco. Robust control of robotic manipulators. *IFAC Proceedings Volumes*, 17(2):2435–2440, 1984.

Hal Daumé III. Frustratingly easy domain adaptation. *Association for Computational Linguistics (ACL)*, 2007.

Hal Daumé III, Abhishek Kumar, and Avishek Saha. Co-regularization based semi-supervised domain adaptation. In *Advances in neural information processing systems (NIPS)*, pp. 478–486, 2010.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor S. Lempitsky. Domain-adversarial training of neural networks. *Journal of Machine Learning Research*, 17:59:1–59:35, 2016.

Boqing Gong, Yuan Shi, Fei Sha, and Kristen Grauman. Geodesic flow kernel for unsupervised domain adaptation. In *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, pp. 2066–2073. IEEE, 2012.

Ian Goodfellow, Jon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *ArXiv e-prints*, 2014.

Raghuraman Gopalan, Ruonan Li, and Rama Chellappa. Domain adaptation for object recognition: An unsupervised approach. In *IEEE International Conference on Computer Vision (ICCV)*, pp. 999–1006. IEEE, 2011.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Xun Huang and Serge J. Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. *CoRR*, abs/1703.06868, 2017.

Jing Jiang and ChengXiang Zhai. Instance weighting for domain adaptation in nlp. In *ACL*, volume 7, pp. 264–271, 2007.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. In *Proceedings of the IEEE*, 1998.

H. Li, H. Zhang, Y. Wang, J. Cao, A. Shamir, and D. Cohen-Or. Curve style analysis in a set of shapes. *Computer Graphics Forum*, (to appear), 2013.

Yishay Mansour, Mehryar Mohri, and Afshin Rostamizadeh. Domain adaptation with multiple sources. In *Advances in neural information processing systems*, pp. 1041–1048, 2009.

Takeru Miyato, Andrew Dai, and Ian Goodfellow. Virtual adversarial training for semi-supervised text classification. *CoRR*, abs/1605.07725, 2016.

Saeid Motiian, Marco Piccirilli, Donald A. Adjeroh, and Gianfranco Doretto. Unified deep supervised domain adaptation and generalization. In *IEEE International Conference on Computer Vision (ICCV)*, 2017.

Kuan-Chuan Peng, Ziyan Wu, and Jan Ernst. Zero-shot deep domain adaptation. *CoRR*, abs/1707.01922, 2017.

Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. *Computer Vision–ECCV 2010*, pp. 213–226, 2010.

Tara Sainath and Carolina Parada. Convolutional neural networks for small-footprint keyword spotting. In *16th Annual Conference of the International Speech Communication Association (INTERSPEECH)*, 2015.

George Saon, Hagen Soltau, David Nahamoo, and Michael Picheny. Speaker adaptation of neural network acoustic models using i-vectors. In *ASRU*, pp. 55–59, 2013.

Eric Tzeng, Judy Hoffman, Trevor Darrell, and Kate Saenko. Simultaneous deep transfer across domains and tasks. In *International Conference in Computer Vision (ICCV)*, 2015.

Eric Tzeng, Judy Hoffman, Trevor Darrell, and Kate Saenko. Adversarial discriminative domain adaptation. In *Computer Vision and Pattern Recognition (CVPR)*, 2017.

Paul Upchurch, Noah Snavely, and Kavita Bala. From A to Z: supervised transfer of style and content using deep neural network generators. *CoRR*, abs/1603.02003, 2016.

W. A. Wolovich and H. Elliott. A computational technique for inverse kinematics. In *IEEE Conference on Decision and Control*, pp. 1359–1363, 1984.

Phil C Woodland. Speaker adaptation for continuous density hmms: A review. In *ISCA Tutorial and Research Workshop (ITRW) on Adaptation Methods for Speech Recognition*, 2001.

Yongxin Yang and Timothy M. Hospedales. A unified perspective on multi-domain and multi-task learning. In *International Conference on Learning Representations (ICLR)*, 2015.

Yongxin Yang and Timothy M. Hospedales. Multivariate regression on the grassmannian for predicting novel domains. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

Kun Zhang, Mingming Gong, and Bernhard Schölkopf. Multi-source domain adaptation: A causal view. In *AAAI*, 2015.