Transformation Autoregressive Networks

Abstract

The fundamental task of general density estimation has been of keen interest to machine learning and statistics alike. Recent advances in density estimation have either: a) proposed using a flexible model to estimate the conditional factors of the chain rule, $p(x_i|x_{i-1}, \ldots)$; or b) used flexible, nonlinear transformations of variables of a simple base distribution. Instead, this work jointly leverages transformations of variables and autoregressive models, and proposes novel methods for both. We provide a deeper understanding of our models, showing a considerable improvement with our methods, through a comprehensive study over both real world and synthetic data. Moreover, we illustrate the use of our models in outlier detection and image modeling tasks.

1 Introduction

Density estimation is at the core of a multitude of machine learning applications. However, this fundamental task, which encapsulates the understanding of data, is difficult in the general setting due to issues like the curse of dimensionality. Furthermore, general data, unlike spatial/temporal data, does not contain a priori known correlations among covariates that may be exploited and engineered with. For example, image data has known correlations among neighboring pixels that may be hard-coded into a model, whereas one must find such correlations in a data-driven fashion with general data.

In order to model high dimensional data, a large number of methods have considered autoregressive models, which model the conditional factors of the chain rule (**?**). I.e these models estimate the conditionals: $p(x_i|x_{i-1}, \ldots, x_1)$, for $i \in \{1, \ldots, d\}$. While some methods directly model the conditionals, $p(x_i|x_{i-1}, \ldots)$ using sophisticated semiparametric density estimates, other methods apply sophisticated transformations of variables $x \mapsto z$ and take the conditionals over z to be a restricted, often independent base distribution $p(z_i|z_{i-1}, \ldots) \approx f(z_i)$ (**?**). In this paper we take a step back from these previous approaches that have considered either: a) a flexible autoregressive scheme with simple or no transformations of variables (Figure 1:middle); or b) a simple autoregressive scheme with flexible transformations of variables. (Figure 1:left) We leverage both of these approaches, develop novel methods for each, and show a considerable improvement with their combination. (Figure 1:right)

Contributions: The following are our contributions. First, we propose two flexible autoreggressive models for modeling conditional distributions: the linear autoregressive model (LAM), and the recurrent autoregressive model (RAM). LAM employs a simple linear form to condition on previously seen covariates in a flexible fashion. RAM uses a recurrent neural network (RNN) to evolve conditioning features as the set of conditioning covariates expands. Furthermore, this paper proposes several novel transformations of variables: 1) we propose an efficient method for learning a linear transfromations on covariates; 2) we develop an invertible RNN-based transformation that directly acts on covariates; 3) we also propose an additive RNN-base transformation. To better capture correlations in general data, we combine our novel autoreggresive models and transformations of variables. That is, we propose transformation autogressive networks (TAN) that use a flexible transformation over the original covariates and a powerful autoregressive model to estimate the conditional probabilities over the transformed space. To assess the efficacy of models, we performed a comprehensive evaluation of possible autoregressive models and transformations. Extensive

experiments on both real and synthetic datasets show the power of TAN in capturing complex dependencies between the covariates. Moreover, we show that the learnt model can be used for outlier detection, and image modeling.

The remainder of the paper is structured as follows. First, we present two novel methods for modeling condition distributions across covariates in section 2.1. Next, in section 2.2, we describe several transformations to use in conjunction with our proposed conditional models. After, we discuss related work and contrast our approach to previous methods. We then illustrate the efficacy of our methods with both synthetic and real-world data.

Figure 1: Illustration from left to right (left) An independent autoregressive scheme with flexible transformations of variables (middle) A flexible autoregressive scheme with no transformations of variables and (right) Transformation Autogressive Network (TAN) that has a flexible autoregressive scheme and a flexible transformation

2 TRANSFORMATION AUTOREGRESSIVE NETWORKS

First, we propose two autoregressive models to estimate the conditional distribution of input covariates $x \in \mathbb{R}^d$. After, we shall show how we may use such models over a transformation $z = q(x)$, while renormalizing to obtain density values for x.

2.1 AUTOREGRESSIVE MODELS

Autoregressive models decompose density estimation of a multivariate variable $x \in \mathbb{R}^d$ into multiple conditional tasks on a growing set of inputs through the chain rule:

$$p(x_1, \ldots x_d) = \prod_{i=1}^{d} p(x_i \mid x_{i-1}, \ldots, x_1). \tag{1}$$

That is, autoregressive models will look to estimate the d conditional distributions $p(x_i|x_{i-1}, \ldots)$. A particular class of autoregressive models can be defined by approximating conditional distributions through a mixture model, $\mathrm{MM}(\theta(x_{i-1}, \ldots, x_1))$, with parameters depending on $x_{i-1}, \ldots, x_1$:

$$p(x_i|x_{i-1}, \ldots, x_1) = p(x_i \mid \mathrm{MM}(\theta(x_{i-1}, \ldots, x_1))), \tag{2}$$
$$\theta(x_{i-1}, \ldots, x_1) = f(h_i) \tag{3}$$
$$h_i = g_i(x_{i-1}, \ldots, x_1), \tag{4}$$

where $f(\cdot)$ is a fully connected network that may use a element-wise non-linearity on inputs, and $g_i(\cdot)$ is some general mapping that computes a hidden state of features, h_i, which help in modeling the conditional distribution of $x_i|x_{i-1}, \ldots, x_1$. One can control the flexibility of the autoregressive model through g_i. It is important to be powerful enough to model our covariates while still generalizing. In order to achieve this we propose two methods for modeling g_i.

First, we propose the linear autoregressive model (LAM), using a straightforward linear map as g_i:

$$g_i(x_{i-1}, \ldots, x_1) = W^{(i)} x_{<i} + b, \tag{5}$$

where $W^{(i)} \in \mathbb{R}^{p \times (i-1)}$, $b \in \mathbb{R}^p$, and $x_{<i} = (x_{i-1}, \ldots, x_1)^T$. Notwithstanding the simple form of (eq. 5), the resulting model is quite flexible as it may model consecutive conditional problems $p(x_i | x_{i-1}, \ldots, x_1)$ and $p(x_{i+1} | x_i, \ldots, x_1)$ very differently.

Next we propose the recurrent autoregressive model (RAM), which features a recurrent relation between g_i's. Given the expanding set of covariates progressively fed into g_i's, it is natural to consider a hidden state that evolves according to an RNN recurrence relationship:

$$h_i = g\left(x_{i-1}, g(x_{i-2}, \ldots, x_1)\right) = g\left(x_{i-1}, h_{i-1}\right), \tag{6}$$

where $g(x, s)$ is a RNN function for updating one's state based on an input x and prior state s (see Figure 2). In the case of gated-RNNs, the model will be able to scan through previously seen dimensions remembering and forgetting information as needed for conditional densities without making any strong Markovian assumptions.

(a) LAM   (b) RAM

Figure 2: Illustration of both LAM (left) and RAM (right) models. Hidden states h_k's are updated and then used to compute the parameters of the next conditional density for x_k. Not that in LAM the hidden states h_j's are not tied together, where in RAM the hidden state h_j along with x_j are used to compute the hidden state h_{j+1} which determines the parameters of $p(x_{j+1} | h_{j+1})$.

Both LAM and RAM are flexible and able to adjust the hidden states to model the distinct conditional tasks $p(x_i | x_{i-1}, \ldots)$. However, there is a trade-off of added flexibility and transferred information between the two models (see Figure 2). LAM treats the conditional tasks for $p(x_i | x_{i-1}, \ldots)$ and $p(x_{i+1} | x_i, \ldots)$ in a largely independent fashion. This makes for a very flexible model, however the parameter size is also large and there is no sharing of information among the conditional tasks. On the other hand, RAM provides a framework for transfer learning among the conditional tasks by allowing the hidden state h_i to evolve through the distinct. conditional tasks. This leads to fewer parameters and more sharing of information in respective tasks, but also yields less flexibility since condition estimates are tied, and may only change in a smooth fashion.

2.2 TRANSFORMATIONS

Several methods (8**?**) have shown that the expressive power of very simple conditional densities (eq. 1) (such as independent Gaussians) can be greatly improved with transformations of variables. Although the chain rule holds for arbitrary distributions, a limited amount of data and parameters limits the expressive power of our models. Hence, we expect that combining our conditional models with transformations of variables will also further increase flexibility. When using an invertible transformation of variables $z = (q_1(x), \ldots, q_d(x)) \in \mathbb{R}^d$, one renormalizes the pdf of x as:

$$p(x_1, \ldots x_d) = \left|\det \frac{dq}{dx}\right| \prod_{i=1}^{d} p\left(q_i(x) | q_{i-1}(x), \ldots, q_1(x)\right), \tag{7}$$

where $\left|\det \frac{\mathrm{d}q}{\mathrm{d}x}\right|$ is a normalizing factor of the Jacobian of the transformation.

For analytical and computational considerations, we require transformations that are invertible, efficient to compute and invert, and have a structured Jacobian matrix. In order to meet these criteria we consider the following transformations, which we shall couple with LAM and RAM.

Linear Transformation: First, we propose a linear transformation:

$$z = Ax + b, \tag{8}$$

where we take A to be invertible. Note that even though this linear transformation is simple, it includes permutations, and may also perform a PCA-like transformation, capturing coarse and highly varied features of the data before moving to more fine grained details. In order to not incur a high cost for updates, we wish to compute the determinant of the Jacobian efficiently. We do so by directly working over an LU decomposition $A = LU$ where L is a lower triangular matrix with unit diagonals and U is a upper triangular matrix with arbitrary diagonals. As a function of L, U we have that $\det \frac{\mathrm{d}z^{(\ell)}}{\mathrm{d}x} = \prod_{i=1}^{d} U_{ii}$; hence we may efficiently optimize the parameters of the linear map. Furthermore, inverting our mapping is also efficient through solving two triangular matrix equations.

Recurrent Transformation: Recurrent neural networks are also a natural choice for variable transformations. Due to their dependence on only previously seen dimensions, RNN transformations have triangular Jacobian, leading to simple determinants. Furthermore, with an invertible output unit, their inversion is also straight-forward. We consider the following form to an RNN transformation:

$$z_i = r_\alpha \left(y x_i + w^T s_{i-1} + b \right), \quad s_i = r \left(u x_i + v^T s_{i-1} + a \right), \tag{9}$$

where r_α is a leaky ReLU unit $r_\alpha(t) = \mathbb{I}\{t < 0\}\alpha t + \mathbb{I}\{t \geq 0\}t$, r is a standard ReLU unit, $s \in \mathbb{R}^\rho$ is the hidden state y, u, b a are scalars, and $w, v \in \mathbb{R}^\rho$ are vectors. As compared to the linear transformation, the recurrent transformation is able to transform the input differently depending on its values. Inverting (eq. 9) is a matter of inverting outputs and updating the hidden state (where the initial state s_0 is known and constant):

$$x_i = y^{-1} \left(r_\alpha^{-1} \left(z_i^{(r)} \right) - w^T s_{i-1} - b \right), \quad s_i = r \left(u x_i + v^T s_{i-1} + a \right). \tag{10}$$

Furthermore, the determinant of the Jacobian for (eq. 9) is the product of diagonal terms:

$$\det \frac{\mathrm{d}z}{\mathrm{d}x} = y^d \prod_{i=1}^{d} r_\alpha' \left(y x_i + w^T s_{i-1} + b \right), \tag{11}$$

where $r_\alpha'(t) = \mathbb{I}\{t > 0\} + \alpha \mathbb{I}\{t < 0\}$.

Recurrent Shift Transformation: It is worth noting that the rescaling brought on by the recurrent transformation effectively incurs a penalty through the log of the determinant (eq. 11). However, one can still perform a transformation that depends on the values of covariates through a shift operation. In particular, we propose an additive shift based on the a recurrent function based through the prior dimensions:

$$z_i = x_i + m(s_{i-1}), \quad s_i = g(x_i, s_{i-1}), \tag{12}$$

where g is some recurrent function for updating states, and m is a fully connected network. Inversion proceeds as before:

$$x_i = z_i - m(s_{i-1}), \quad s_i = g(x_i, s_{i-1}), . \tag{13}$$

The Jacobian is again lower triangular, however due to the additive nature of (eq. 12), we have a unit diagonal. Thus, $\det \frac{\mathrm{d}z}{\mathrm{d}x} = 1$. One interpretation of this transformation is that one can shift the value of x_k based on $x_{k-1}, x_{k-2}, \ldots$ for better conditional density estimation without any penalty coming from the log-determinant term in (eq. 7).

Composing Transformations: Lastly, we considering stacking (i.e. composing) several of these transformations $q = q^{(1)} \circ \ldots \circ q^{(T)}$ and renormalizing:

$$p(x_1, \ldots x_d) = \prod_{t=1}^{T} \left| \det \frac{\mathrm{d}q^{(t)}}{\mathrm{d}q^{(t-1)}} \right| \prod_{i=1}^{d} p\left(q_i(x) \mid q_{i-1}(x), \ldots, q_1(x)\right), \tag{14}$$

where we take $q^{(0)}$ to be x. We note that composing several transformations together allows one to leverage the respective strengths of each transformation. Moreover, inserting a reversal transformation $(x_1, \ldots, x_d \mapsto x_d, \ldots, x_1)$ in between transformations yields biderectional relationships for several transformations.

2.3 Composite Approach

We combine the use of both transformations of variables and rich autorgressive models by: 1) writing the density of inputs, $p(x)$, as a normalized density of a transformation: $p(q(x))$ (eq. 14). Then we estimate the conditionals of $p(q(x))$ using an autoregressize model. I.e. to learn our model we minimize the negative log likelihood:

$$-\log p(x_1, \ldots x_d) = -\sum_{t=1}^{T} \log \left| \det \frac{\mathrm{d}q^{(t)}}{\mathrm{d}q^{(t-1)}} \right| - \sum_{i=1}^{d} \log p\left(q_i(x) \mid h_i\right), \tag{15}$$

which is obtained by substituting (eq. 2) into (eq. 14) and h_i is defined in (eq. 4).

3 Related Work

Nonparametric density estimation has been a well studied problem in statistics and machine learning (20). Unfortunately, nonparametric approaches like kernel density estimation suffer greatly from the curse of dimensionality and do not perform well when data does not have a small number of dimensions ($\lesssim 3d$). To alleviate this, several semiparametric approaches have been explored. Such approaches include forest density estimation (13), which assumes that the data has a forest (i.e. a collection of trees) structured graph. This assumption leads to a density which factorizes in a first order Markovian fashion through a tree traversal of the graph. Another common semiparametric approach is to use a nonparanormal type model (12). This approach uses a Gaussian copula with a rank-based transformation and a sparse precision matrix. While both approaches are well-understood theoretically, their strong assumptions often lead to inflexible models.

In order to provide greater flexibility with semiparametric models, recent work has employed deep learning for density estimation. The use of neural networks for density estimation dates back to early work by (6) and has seen success in areas like speech (21; 17), music (7), etc.. Typically such approaches use a network to learn to parameters of a parametric model for data. Recent work has also explored the application of deep learning to build density estimates in image data (15; 9). However, such approaches are heavily reliant on exploiting structure in neighboring pixels, often reshaping or re-ordering data and using convolutions to take advantage of neighboring correlations. Modern approaches for general density estimation in real-valued data include (19; 18; 10; 8).

NADE is a restricted-Boltzmann-machine-inspired density estimator that uses a weight-sharing scheme across conditional densities directly on input covariates (18). It may be written as a special case of the autoregressive model (eq. 4) with

$$q_i\left(x_{i-1}, \ldots, x_1\right) = W_{<i} x_{<i} + b, \tag{16}$$

where $W_{<i} \in \mathbb{R}^{p \times i-1}$ is the weight matrix compose of the first $i-1$ columns of a shared matrix $W = (w_1, \ldots w_d)$.

Even though the weight-sharing scheme in (eq. 16) reduces the number of parameters in ones model, it also greatly limits the types of distributions one can model. Roughly speaking, the NADE weight-sharing scheme makes it difficult to adjust conditional distributions when expanding the conditioning set with a covariate that has a small information gain.

We illustrate these kinds of limitations with a simple example. Consider the following 3-dimensional distribution:

$$x_1 \sim \mathcal{N}(0, 1), \quad x_2 \sim \mathcal{N}(\text{sign}(x_1), \epsilon), \quad x_3 \sim \mathcal{N}\left(\mathbb{I}\{|x_1| < C_{0.5}\}, \epsilon\right) \tag{17}$$

where $C_{0.5}$ is the 50% confidence interval of a standard Gaussian distribution, and $\epsilon > 0$ is some small constant. That is, x_2, and x_3 are marginally distributed as an equi-weighted bimodel mixture of Gaussian with means $-1, 1$ and $0, 1$, respectively. Due to NADE's weight-sharing linear model, it will be difficult to adjust h_2 and h_3 jointly to correctly model x_2 and x_3 respectively. However, given their additional flexibility, both LAM and RAM are able to adjust hidden states to remember and transform features as needed.

NICE models assume that data is drawn from a latent independent Gaussian space and transformed (8). The transformation uses several "additive coupling" shifting transformations on the second half of dimensions, using the first half of dimensions. That is, additive coupling proceeds by splitting inputs into halves $x = (x_{<d/2}, x_{\geq d/2})$, and transforming the second half as an additive function of the first half:

$$z = \left(x_{<d/2}, \, x_{\geq d/2} + m(x_{<d/2})\right), \tag{18}$$

where $m(\cdot)$ is the output of a fully connected network. Inversion is simply a matter of subtraction $x = \left(z_{<d/2}, \, z_{\geq d/2} + m(z_{<d/2})\right)$. The full transformation is the result of stacking several of these additive coupling layers together followed by a final rescaling operation. Furthermore, as with the RNN shift transformation, the additive nature of (eq. 18) yields a simple determinant, $\det \frac{\mathrm{d}z}{\mathrm{d}x} = 1$.

We also note that are several methods for obtaining samples from an unknown distribution that by-pass density estimation. For instance, generative adversarial networks (GANs) apply a (typically noninvertible) transformation of variables to a base distribution by optimizing a minimax loss over a discrimator and the transformation (11). Furthermore, one can also obtain samples with only limited information about the density of interest. For example, if one has an unnormalized pdf, one may use Markov chain Monte Carlo (MCMC) methods to obtain samples (14).

4 EXPERIMENTS

We compare models using several experiments on synthetic and real-world datasets. First, we compute the average log likelihoods across instances of held out test data. Then, to gain further context of the efficacy of models, we also use their density estimates for anomaly detection, where we take low density instances to be outliers. Moreover, we look at an illustrative MNIST image modeling task.

We study the performance of various combinations of conditional models and transformation. That is, we consider various models for the conditionals $p(q_i(x) | q_{i-1}(x), \ldots, q_1(x))$ and various transformations $q(\cdot)$ (eq. 14). In particular the following conditional models were considered: `LAM`, `RAM`, `Tied`, `MultiInd`, and `SingleInd`. Here, LAM, RAM, and `Tied` are as described in equations (eq. 5), (eq. 6), and (eq. 16), respectively. `MultiInd` takes $p(q_i(x) | q_{i-1}(x), \ldots, q_1(x))$ to be $p(q_i(x) | \text{MM}(\theta_i))$, that is we shall use d distinct independent mixtures to model the transformed covariates. Similarly, `SingleInd` takes $p(q_i(x) | q_{i-1}(x), \ldots, q_1(x))$ to be $p(q_i(x))$, the density of a standard single component. Moreover, we considered the following transformations: `None`, `RNN`, `2xRNN`, `4xAdd+Re`, `4xSRNN+Re`, `RNN+4xAdd+Re`, and `RNN+4xSRNN+Re`. `None` indicates that no transformation of variables was performed. `RNN` and `2xRNN` performs a single recurrent transformation (eq. 9), and two recurrent transformations with a reversal permutation in between, respectively. `4xAdd+Re`, performs four additive coupling transformations (eq. 18) with reversal permutations in between followed by an element-wise rescaling: $x \mapsto x * \exp(s)$, where s is a learned variable. Similarly, `4xSRNN+Re`, performs four recurrent shift transformations (eq. 12) with reversal permutations in between, followed by an element-wise rescaling. `RNN+4xAdd+Re`, and `RNN+4xSRNN+Re` are as before, but performing an initial recurrent transformation. Furthermore, we also considered performing an initial linear transformation (eq. 8). We flag this by prepending an `L` to the transformation; e.g. `L RNN` denotes a linear transformation followed by a recurrent transformation.

Models were implemented in Tensorflow (4). Both RAM conditional models as well as the RNN shift transformation make use of the standard `GRUCell` GRU implementation[1]. We take the mixture models of conditionals (eq. 2) to be mixtures of 40 Gaussians. We optimize all models using the `AdamOptimizer` (?) with an initial learning rate of 0.005. 30 000 iterations were ran, with mini-batches of size 256. The learning rate was decreased by a factor of 0.1, or 0.5 (chosen via a validation set) every 5 000 iterations. Gradient clipping with a norm of 1 was used. After training, the best model according to the validation set loss was used to produce the test set mean log likelihoods.

4.1 SYNTHETIC

We perform a thorough empirical analysis over synthetic data. By carefully constructing data we will be able to pinpoint strengths and short-comings of conditional models and transformations. We study a dataset with a first-order Markovian structure, and one with a star-shaped structure; they are described below.

4.1.1 MARKOVIAN DATA

First, we describe experiments performed on a synthetic dataset with a Markovian structure that features several exploitable correlations among covariates. The dataset is sampled as follows: $y_1, y_2, y_3 \sim \mathcal{N}(0, 1)$ and $y_i \mid y_{i-1}, \ldots, y_1 \sim f(i, y_1, y_2, y_3) + \epsilon_i$ for $i > 3$ where $\epsilon_i \sim \mathcal{N}(\epsilon_{i-1}, \sigma)$, $f(i, y_1, y_2, x_3) = y_1 \sin(y_2 g_i + y_3)$, and g_i's are equi-spaced points on the unit interval. That is, instances are are sampled using random draws of amplitude, frequency, and shift covariates y_1, y_2, y_3, which determine the mean of the other covariates, $y_1 \sin(y_2 g_i + y_3)$, stemming from function evaluations on a grid, and random noise ϵ_i with a Gaussian random walk. The resulting instances are easy to visualize, and contain many correlations among covariates (for instance, y_4 is highly informative of y_5). To test robustness to correlations from distant (by index) covariates, we observe covariates that are shuffled using a fixed permutation π chosen ahead of time: $x = (y_{\pi_1}, \ldots, y_{\pi_d})$. We take $d = 32$, and the number of training instances to be 100 000.

We detail the mean log-likelihoods on a test set for TANs using various combinations of conditional models and transformations below in Table 4. Note that the performance of previous approaches that considered a complex conditional model with simple or no transformation and vice-verse are illustrated by `None & Tied` (NADE), `4xAdd+Re & SingleInd` (NICE) models, as well as by the entire row corresponding to `None` transformation and the `MultiInd` and `SingleInd` columns. We see that both `LAM` and `RAM` conditionals are providing most of the top models. We observe good samples from best performing model (picked on validation dataset) as shown in Figure 3. Here we also observe relatively good performance stemming from `MultiInd` conditionals with more complex transformations.

Figure 3: Samples from the `RNN+4xSRNN+Re` with `RAM` model. We plot the sample values of unpermuted dimensions $y_4, \ldots, y_{32} \mid y_1, y_2, y_3$ in blue and the expected value of these dimensions (i.e. without the Markovian noise) in green. One may see that the model is able to correctly capture both the sinusoidal and random walk behavior of our data.

4.1.2 STAR DATA

Next, we consider a dataset with a star-structured graphical model where fringe nodes are very uninformative with each-other. We divide the covariates into disjoint center and vertex

---

[1]Code will be made public upon publication.

sets $C = \{1, \ldots, 4\}$, $V = \{5, \ldots, d\}$ respectively. For center nodes $j \in C$, $y_j \sim \mathcal{N}(0, 1)$. Then, for $j \in V$, $y_j \sim \mathcal{N}(f_j(w_j^T y_C), \sigma)$ where f_j is a fixed step function with 32 intervals, $w_j \in \mathbb{R}^4$ is a fixed vector, and $y_C = (y_1, y_2, y_3, y_4)$. We note that this dataset poses a difficult density estimation problem since the distribution of each of the fringe vertices will be considerably different from each other, the fringe vertices are largely uninformative from one another, and the distribution of the fringe vertices are difficult to estimate without conditioning on all the center nodes. As before we observe covariates that are shuffled using a fixed permutation π chosen ahead of time: $x = (y_{\pi_1}, \ldots, y_{\pi_d})$, with $d = 32$.

We again detail the mean log-likelihoods on a test set for TANs using various combinations of conditional models and transformations below in Table 13. Once more we observe that both `LAM` and `RAM` conditionals are providing most of the top models. However, simpler conditional methods are unable model the data well, suggesting that the complicated dependencies need a two-prong TAN approach. We observe a similar pattern when learning over data with $d = 128$ (see Appendix, Table 6).

4.2 Test-Data Log Likelihoods

We used multiple datasets from the UCI machine learning repository (2) and Stony Brook outlier detection datasets collection (ODDS) (1), to evaluate log-likelihoods on held-out test data. Broadly, the datasets can be divided into: **Particle acceleration**: `higgs`, `hepmass`, and `susy` datasets where generated for high-energy physics experiments using Monte Carlo simulations; **Music**: The `music` dataset contains timbre features from the million song dataset of mostly commercial western song tracks from the year 1922 to 2011; (5). **Word2Vec**: `wordvecs` consists of 3 million words from a Google News corpus. Each word represented as a 300 dimensional vector trained using a word2vec model (3). **ODDS datasets**: We used several ODDS datasets–`shuttle`, `forest`, `pendigits`, `satimage2`. These are multivariate datasets from varied set of sources meant to provide a broad picture of performance across anomaly detection tasks. To not penalize models for low likelihoods on outliers in ODDS, we removed anomalies from test sets when reporting log-likelihoods.

As noted in (8), data degeneracies and other corner-cases may lead to arbitrarily low negative log-likelihoods. In order to avoid such complications, we first standardized all datasets, and added independent Gaussian noise with a standard deviation of 0.01 to training sets.

We report average log-likelihoods on test data in Table 1. For each dataset and each conditional model, we report the test log-likelihood of the top-2 transformations (picked on a validation dataset). First we note that the best performing model across all dataset had either LAM or RAM conditionals. We also note that the best model picked on validation set (denoted by *) is also the best on test set. The full table detailing test log-likelihoods for all combinations of conditional models and transformations for each dataset may be found in the Appendix (see Tables 8-14). We also observe that `L RNN+4xAdd+Re & LAM` and `L RNN & RAM` are consistently among the top-10 picked models.

4.3 Anomaly Detection

Next, we apply density estimates to anomaly detection. Typically anomalies or outliers are data-points that are unlikely given a dataset. In terms of density estimations, such a task is framed by identifying which instances in a dataset have a low corresponding density. That is, we shall label an instance x, as an anomaly if $\hat{p}(x) \leq t$, where $t \geq 0$ is some threshold and $\hat{p}$ is the density estimate based on training data. Note that this approach is trained in an unsupervised fashion. However, each methods' density estimates were evaluated on test data with anomaly/non-anomaly labels on instances. We used thresholded log-likelihoods on the test set to compute precision and recall. We use the average-precision metric: avg-prec $= \sum_{k=1}^{N_{\text{test}}} \text{precision}_r (\text{recall}_r - \text{recall}_{r-1})$ where $\text{precision}_r = \frac{tp_r}{tp_r + fp_r}$, $\text{recall}_r = \frac{tp_r}{tp_r + fn_r}$, and tp_r, fp_r, fn_r are true positive anomalies, false positives and false negative respectively among the bottom r log-likelihood instances in test data. Our results are shown in Table 2. We see that RAM performs the best on all three datasets. Beyond providing another use

Dataset	LAM		RAM		Tied		MultiInd		NADE	NICE
forrest
d= 10
N=286,048	2.389
L RNN+
4xAdd+Re	2.297
L RNN+
4xSRNN+Re	**2.672**∗
L RNN+
4xAdd+Re	2.443
L RNN+
4xSRNN+Re	0.909
L 4xAdd+
Re	0.857
RNN+
4xAdd+Re	0.754
L 4xSRNN+
Re	0.600
L RNN+
4xSRNN+Re	−0.653	−0.492
pendigits
d= 16
N=6,870	**6.923**∗
None	5.854
4xSRNN+
Re	3.896
2xRNN	3.911
None	1.437
None	−2.299
L RNN	−5.010
4xAdd+
Re	−4.742
L RNN+
4xAdd+Re	1.437	−6.498
susy
d= 18
N=5,000,000	17.673
L 4xAdd+
Re	17.474
L RNN+
4xAdd+Re	**18.941**∗
L RNN+
4xSRNN+Re	18.389
L RNN	15.397
L 4xSRNN+
Re	13.765
RNN+
4xAdd+Re	12.161
L 4xSRNN+
Re	12.105
L RNN+
4xSRNN+Re	−5.721	4.245
higgs
d= 28
N=11,000,000	−3.396
L RNN+
4xAdd+Re	−3.756
L RNN+
4xSRNN+Re	**−0.340**∗
L RNN	−2.116
RNN+
4xSRNN+Re	−8.052
L RNN+
4xAdd+Re	−8.006
L 4xAdd+
Re	−8.223
L 4xSRNN+
Re	−9.378
L RNN+
4xSRNN+Re	−13.883	−15.138
hepmass
d= 28
N=10,500,000	3.906
L RNN+
4xAdd+Re	3.759
L RNN+
4xSRNN+Re	4.935∗
RNN	**5.047**
L RNN	−0.239
L RNN+
4xSRNN+Re	−0.863
L RNN+
4xSRNN+Re	−5.747
L 4xSRNN+
Re	−6.091
4xSRNN+
Re	−4.948	−11.387
satimage2
d= 36
N=5,803	−1.716
None	−7.728
RNN	**−0.550**∗
L 2xRNN	−0.773
L RNN	−2.137
2xRNN	−2.549
4xSRNN+
Re	−1.570
L None	−1.699
L 2xRNN	−9.296	−17.977
music
d= 90
N=515,345	**−51.572**∗
L RNN+
4xAdd+Re	−52.617
L RNN+
4xSRNN+Re	−55.665
L 4xSRNN+
Re	−56.190
L RNN+
4xAdd+Re	−58.885
L RNN+
4xAdd+Re	−59.093
L 4xAdd+
Re	−69.484
L RNN+
4xAdd+Re	−69.887
L 4xAdd+
Re	−98.047	−83.524

Table 1: Average log-likelihood on held-out test data. For each data and each conditional, top-2 transformations are selected using log-likelihood on validation set and their test log-likelihood are reported. ∗ denotes the best model picked by CV. Largest values per dataset are shown in **bold**.

Dataset	LAM		RAM		Tied		MultiInd		NADE	NICE
forrest
O=2,747	0.936
L RNN+
4xAdd+Re	0.902
L RNN+
4xSRNN+Re	**0.944**
L RNN+
4xAdd+Re	**0.944**
L RNN+
4xSRNN+Re	0.918
L 4xAdd+
Re	0.923
RNN+
4xAdd+Re	0.928
L 4xSRNN+
Re	0.882
L RNN+
4xSRNN+Re	0.866	0.802
pendigits
O=156	0.930
None	0.956
4xSRNN+
Re	**0.981**
2xRNN	0.918
None	0.919
None	0.916
L RNN	0.927
4xAdd+
Re	0.915
L RNN+
4xAdd+Re	0.919	0.933
satimage2
O=71	0.986
None	0.987
RNN	**0.990**
L 2xRNN	0.947
L RNN	**0.990**
2xRNN	0.989
4xSRNN+
Re	0.975
L None	0.969
L 2xRNN	**0.990**	0.981

Table 2: Average precision score on outlier detection datasets. For each dataset and for each conditional, average precision corresponding to the top-2 best transformation model, picked using likelihood on validation set, is shown here. The best score for each dataset is in **bold**.

for our density estimates, seeing good performance in these outlier detection tasks further illustrates that our models are learning semantically meaningful patterns.

4.4 Digit Modeling

For illustrative purposes, we consider modeling MNIST digits. In keeping with our focus of general data modeling, we treat each image as a flattened vector of 784 dimensions. Here we demonstrate that our proposed models can be used to model high dimensional data and produce coherent samples.

First, we model dequantized pixel values rescaled to the unit interval as described in (8). Moreover, we also model the MNIST digits through a logit transformation of pixel values. That is, we take the dequantized pixel values in the range $[0, 256]$, y and model: $x = \text{logit}\left(\lambda + (1 - \lambda)\frac{y}{256}\right)$, with $\lambda = 0.05$. This transformation will lessen boundary of effects and keep pixel values inside a valid range.

We ran experiments on MNIST using the two models (`L RNN+4xAdd+Re` & `LAM` and `L RNN` & `RAM`) that consistently appear in the top-10 in our previous experiments (see Tables 8-14 in Appendix). We observe test set average log-likelihoods and samples reported in bits per pixel in Table 3. Furthermore, we plot samples in Figure 4. We see that our models are able to capture the structure of MNIST digits, with very few artifacts in samples. This is also reflected in the likelihoods, which are comparable or better than state-of-the-art.

5 Discussion

Below we discuss several conclusions stemming from our comprehensive empirical study of transformations and conditional models.

NICE (8) (Unit)	Real NVP (9) (Logit)	MADE (16) (Logit)	L RNN+4xAdd+Re & LAM (Unit)	L RNN & RAM (Unit)	L RNN+4xAdd+Re & LAM (Logit)	L RNN & RAM (Logit)
4.47 ± 0.021	1.93 ± 0.01	1.41 ± 0.01	2.27 ± 0.013	1.60 ± 0.007	2.12 ± 0.01	$\mathbf{1.19 \pm 0.005}$

Table 3: Bits per pixel for models (lower is better). "(Unit)" denotes model with unit scale on pixels, and "(Logit)" denotes model with logit transformation on pixels.

(a) LAM (Unit) (b) RAM (Unit) (c) LAM (Logit) (d) RAM (Logit)

Figure 4: Samples from L RNN+4xAdd+Re & LAM, and L RNN & RAM models on unit scaled, and logit transformed pixels.

The breadth of our proposed methods is worth noting. As mentioned above, previous approaches considered a complex conditional model with simple or no transformation and vice-versa. As such, some previous works have proposed a single new type of transformation, or a single new conditional model. Here, we propose multiple methods for transformations (linear, recurrent, and shift recurrent) and multiple autoregressive conditional models (LAM, and RAM). Furthermore, we consider the various combinations of transformations and autoregressive models, most of which constitute a novel TAN.

We draw several conclusions through our comprehensive empirical study. First, we consider our experiments on synthetic data. Methods that only consider complex transformations or condition models are illustrated in the entire row corresponding to None transformation and the MultiInd and SingleInd columns, respectively. Performance of some of these models, which include None & Tied (NADE), 4xAdd+Re & SingleInd (NICE), can be moderately well on the Markovian data, however these one-prong approaches fail in the star dataset. Overall, LAM and RAM methods provided considerable improvements. This was especially the case in the star dataset, where the flexibility of LAM made it possible to learn the widely different conditional probabilities present in the data.

Similarly, we observe that the best performing models in real-world datasets are those that incorporate a flexible transformation *and* conditional model. In fact, the best model (according to validation dataset) always has LAM or RAM autoregressive components. Hence, validation across models would always select one of these methods. In fact, 95% of top-10 models (aggregated across all datasets) have a LAM and RAM conditional model (see Tables 8-14). It is interesting to see that many of these top models also contain a linear transformation. Of course, linear transformations of variables are common to most parametric models, however they have been under-explored in the context of autoregressive density estimation. Our methodology for efficiently learning linear transformation coupled with our strong empirical analysis encourages their inclusion in autoregressive models.

Finally, we digest results across all real-world datasets by computing the following performance score for each combination of transformation t, conditional model m, and dataset D: $s(t, m, D) = \exp(l_{t,m,D})/\max_{a,b} \exp(l_{a,b,D})$, where $l_{t,m,D}$ is the test log-likelihood for t, m on D. That is, $s(t, m, D)$ is the percentage of the top likelihood achieved by transformation t and conditional model m on dataset D. We then average S over the datasets: $S(t, m) = \frac{1}{T} \sum_D S(t, m, D)$, where T is the total number of datasets. We show this score in Table 7. This table gives a summary of which models performed better (closer to the best performing model per dataset) over multiple datasets. We see that RAM conditional with L RNN transformation, and LAM conditional with L RNN+4xAdd+Re were the two best performers.

Conclusion: In conclusion, this work jointly leverages transformations of variables and autoregressive models, and proposes novel methods for both. We show a considerable improvement with our methods, through a comprehensive study over both real world and synthetic data. Also, we illustrate the utility of our models in outlier detection and digit modeling tasks.

REFERENCES

[1] Outlier Detection DataSets (ODDS). `http://odds.cs.stonybrook.edu`. Accessed: 04-01-2017.

[2] UCI Machine Learning Repository. `http://archive.ics.uci.edu/ml/`. Accessed: 04-01-2017.

[3] word2vec. `https://code.google.com/archive/p/word2vec/`. Accessed: 04-01-2017.

[4] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, et al. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *arXiv preprint arXiv:1603.04467*, 2016.

[5] Thierry Bertin-Mahieux, Daniel PW Ellis, Brian Whitman, and Paul Lamere. The million song dataset. In *ISMIR*, volume 2, page 10, 2011.

[6] Christopher M Bishop. Mixture density networks. *Technical Report*, 1994.

[7] N. Boulanger-Lewandowski, Y. Bengio, and P. Vincent. Modeling temporal dependencies in high-dimensional sequences: Application to polyphonic music generation and transcription. *International Conference on Machine Learning*, 2012.

[8] Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

[9] Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

[10] Mathieu Germain, Karol Gregor, Iain Murray, and Hugo Larochelle. Made: masked autoencoder for distribution estimation. In *Proceedings of the 32nd International Conference on Machine Learning (ICML-15)*, pages 881–889, 2015.

[11] Ian Goodfellow. Nips 2016 tutorial: Generative adversarial networks. *arXiv preprint arXiv:1701.00160*, 2016.

[12] Han Liu, John Lafferty, and Larry Wasserman. The nonparanormal: Semiparametric estimation of high dimensional undirected graphs. *Journal of Machine Learning Research*, 10(Oct):2295–2328, 2009.

[13] Han Liu, Min Xu, Haijie Gu, Anupam Gupta, John Lafferty, and Larry Wasserman. Forest density estimation. *Journal of Machine Learning Research*, 12(Mar):907–951, 2011.

[14] Radford M Neal. Probabilistic inference using markov chain monte carlo methods. 1993.

[15] Aaron van den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. *arXiv preprint arXiv:1601.06759*, 2016.

[16] George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. *arXiv preprint arXiv:1705.07057*, 2017.

[17] B. Uria. Connectionist multivariate density-estimation and its application to speech synthesis., 2015.

[18] Benigno Uria, Marc-Alexandre Côté, Karol Gregor, Iain Murray, and Hugo Larochelle. Neural autoregressive distribution estimation. *Journal of Machine Learning Research*, 17(205):1–37, 2016.

[19] Benigno Uria, Iain Murray, and Hugo Larochelle. A deep and tractable density estimator. In *ICML*, pages 467–475, 2014.

[20] L Wasserman. All of nonparametric statistics, 2007.

[21] Heiga Zen and Andrew Senior. Deep mixture density networks for acoustic modeling in statistical parametric speech synthesis. In *Acoustics, Speech and Signal Processing (ICASSP), 2014 IEEE International Conference on*, pages 3844–3848. IEEE, 2014.

Transformation	LAM	RAM	TIED	MultiInd	SingleInd
None	14.319	−29.950	−0.612	−41.472	− − −
L None	**15.486**[9]	14.538	10.906	5.252	−9.426
RNN	14.777	−37.716	11.075	−30.491	−37.038
L RNN	**15.658**[5]	10.354	10.910	5.370	3.310
2xRNN	14.683	13.698	11.493	−18.448	−34.268
L 2xRNN	**15.474**[8]	**15.752**[3]	12.316	5.385	3.739
4xAdd+Re	15.269	12.257	12.912	12.446	11.625
L 4xAdd+Re	**15.683**[6]	12.594	13.845	12.768	12.069
4xSRNN+Re	14.829	14.381	11.798	11.738	12.932
L 4xSRNN+Re	15.289	**16.202**[1]	12.748	**15.415**[10]	13.908
RNN+4xAdd+Re	15.171	12.991	14.455	11.467	10.382
L RNN+4xAdd+Re	15.078	12.655	14.415	12.886	12.315
RNN+4xSRNN+Re	14.968	**16.216**[2]	12.590	**15.589**[4]	14.231
L RNN+4xSRNN+Re	15.429	**15.566**[7]	14.179	14.528	13.961

Table 4: Held out test log-likelihoods for the Markovian dataset. The superscripts denote rankings of log-likelihoods on the validation dataset.

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	−2.041	2.554	−10.454	−29.485	**0.000**[0]
L None	5.454	8.247	−7.858	−26.988	−38.952
RNN	−1.276	2.762	−6.292	−25.946	−41.275
L RNN	7.775	6.335	−1.157	−25.986	−34.408
2xRNN	3.705	8.032	−0.565	−25.100	−38.490
L 2xRNN	**14.878**[3]	9.946	0.901	−23.772	−33.075
4xAdd+Re	**13.278**[6]	**11.561**[9]	7.146	−16.740	−21.332
L 4xAdd+Re	**15.728**[2]	**12.444**[7]	9.031	−6.091	−11.225
4xSRNN+Re	3.496	8.429	−1.380	−15.590	−23.712
L 4xSRNN+Re	**16.042**[1]	**9.939**[10]	5.598	−12.530	−16.889
RNN+4xAdd+Re	**14.071**[5]	**14.123**[4]	6.868	−14.773	−20.483
L RNN+4xAdd+Re	**11.819**[8]	9.253	2.638	−7.662	−14.530
RNN+4xSRNN+Re	−0.679	3.320	−6.172	−12.879	−19.204
L RNN+4xSRNN+Re	7.433	7.324	3.554	−10.427	−15.243

Table 5: Held out test log-likelihoods for Star dataset. The superscript denotes ranking of log-likelihood on cross validation dataset

APPENDIX

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	15.671	15.895	−83.115	−128.238	**0.000**[0]
L None	57.881	−82.100	−28.206	−123.939	−159.391
RNN	18.766	48.295	−22.485	−113.181	−178.641
L RNN	**66.070**[9]	−49.084	31.136	−107.083	−155.324
2xRNN	27.295	45.834	−11.930	−113.210	−178.331
L 2xRNN	**85.681**[3]	−84.524	30.974	−105.368	−162.635
4xAdd+Re	**77.195**[6]	**61.947**[10]	16.062	−75.206	−111.542
L 4xAdd+Re	**88.837**[1]	−21.882	20.234	−65.694	−96.071
4xSRNN+Re	33.577	−98.796	3.256	−88.912	−98.936
L 4xSRNN+Re	**86.375**[2]	**76.968**[5]	33.481	−85.590	−93.086
RNN+4xAdd+Re	**66.540**[8]	−57.861	−16.277	−75.491	−114.729
L RNN+4xAdd+Re	**80.063**[4]	32.104	21.944	−71.933	−100.384
RNN+4xSRNN+Re	21.719	−87.335	−6.517	−76.459	−85.422
L RNN+4xSRNN+Re	**72.463**[7]	56.201	26.269	−71.843	−91.695

Table 6: Held out test log-likelihood for Star dataset. The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM	RAM	TIED	MultiInd	SingleInd	MAX
None	0.218	0.118	0.006	0.000	0.000	0.218
L None	0.154	0.179	0.026	0.051	0.001	0.179
RNN	0.086	0.158	0.014	0.001	0.000	0.158
L RNN	0.173	**0.**540	0.014	0.040	0.013	0.540
2xRNN	0.151	0.101	0.045	0.001	0.000	0.151
L 2xRNN	0.118	0.330	0.015	0.045	0.025	0.330
4xAdd+Re	0.036	0.047	0.015	0.010	0.006	0.047
L 4xAdd+Re	0.153	0.096	0.025	0.014	0.009	0.153
4xSRNN+Re	0.086	0.051	0.031	0.010	0.008	0.086
L 4xSRNN+Re	0.109	0.143	0.023	0.021	0.018	0.143
RNN+4xAdd+Re	0.121	0.096	0.023	0.011	0.011	0.121
L RNN+4xAdd+Re	0.336	0.165	0.024	0.016	0.013	0.336
RNN+4xSRNN+Re	0.102	0.151	0.017	0.012	0.014	0.151
L RNN+4xSRNN+Re	0.211	0.288	0.024	0.018	0.016	0.288
MAX	0.336	0.540	0.045	0.051	0.025	

Table 7: Average performance percentage score for each model across all datasets. Note that this measure is not over log space.

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	0.751	−1.383	−0.653	−12.824	$\mathbf{0.000^{(0)}}$
L None	1.910	1.834	−0.243	−7.665	−11.062
RNN	1.395	0.053	0.221	−5.130	−15.983
L RNN	$\mathbf{2.189^{(8)}}$	1.747	−0.087	−4.001	−5.807
2xRNN	1.832	1.830	0.448	−6.162	−9.095
L 2xRNN	$\mathbf{2.240^{(6)}}$	$\mathbf{2.432^{(3)}}$	0.264	−3.956	−5.125
4xAdd+Re	1.106	1.430	0.420	−0.021	−0.492
L 4xAdd+Re	2.043	1.979	0.909	0.365	−0.088
4xSRNN+Re	1.178	1.428	0.187	−0.029	−0.212
L 4xSRNN+Re	$\mathbf{2.089^{(9)}}$	$\mathbf{2.061^{(10)}}$	0.611	0.754	0.593
RNN+4xAdd+Re	1.962	$\mathbf{2.226^{(7)}}$	0.857	0.081	0.086
L RNN+4xAdd+Re	$\mathbf{2.389^{(4)}}$	$\mathbf{2.672^{(1)}}$	0.852	0.450	0.251
RNN+4xSRNN+Re	1.599	1.545	0.510	0.182	0.369
L RNN+4xSRNN+Re	$\mathbf{2.297^{(5)}}$	$\mathbf{2.443^{(2)}}$	0.804	0.600	0.480

Table 8: Held out test log-likelihood for `Forest` dataset. The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	$\mathbf{6.923^{(1)}}$	$\mathbf{3.911^{(8)}}$	1.437	−14.138	$\mathbf{0.000^{(0)}}$
L None	$\mathbf{4.104^{(9)}}$	2.911	−2.872	−9.997	−15.617
RNN	$\mathbf{5.464^{(3)}}$	3.273	−1.676	−10.144	−19.719
L RNN	$\mathbf{4.072^{(6)}}$	1.398	−2.299	−10.840	−13.103
2xRNN	$\mathbf{6.376^{(5)}}$	$\mathbf{3.896^{(7)}}$	−4.002	−12.132	−16.576
L 2xRNN	2.987	0.871	−3.977	−10.890	−12.711
4xAdd+Re	−1.924	−3.087	−3.172	−5.010	−6.498
L 4xAdd+Re	−1.796	−1.438	−2.288	−4.951	−7.834
4xSRNN+Re	$\mathbf{5.854^{(2)}}$	2.146	−2.827	−5.970	−7.084
L 4xSRNN+Re	3.758	−1.020	−3.370	−5.885	−12.978
RNN+4xAdd+Re	−2.357	−2.869	−2.187	−5.454	−8.053
L RNN+4xAdd+Re	−2.687	−2.103	−2.185	−4.742	−6.941
RNN+4xSRNN+Re	$\mathbf{5.207^{(4)}}$	2.425	−2.126	−5.147	−8.859
L RNN+4xSRNN+Re	$\mathbf{3.466^{(10)}}$	0.496	−2.761	−7.205	−13.897

Table 9: Held out test log-likelihood for `pendigits` dataset. The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	9.736	−14.821	−5.721	−21.369	**0.000$^{(0)}$**
L None	15.731	**16.930$^{(8)}$**	6.410	−8.846	−17.130
RNN	12.784	3.347	6.114	−18.575	−44.273
L RNN	16.381	**18.389$^{(2)}$**	6.772	−5.744	−11.489
2xRNN	11.052	14.362	3.595	−16.478	−33.126
L 2xRNN	14.523	**17.373$^{(7)}$**	10.687	−6.884	−10.420
4xAdd+Re	9.835	8.033	7.238	6.031	4.245
L 4xAdd+Re	**17.673$^{(3)}$**	**16.500$^{(10)}$**	11.613	10.941	9.034
4xSRNN+Re	8.798	13.235	1.234	6.936	3.378
L 4xSRNN+Re	14.242	**17.870$^{(5)}$**	15.397	12.161	13.413
RNN+4xAdd+Re	15.408	12.480	9.409	7.619	5.446
L RNN+4xAdd+Re	**17.474$^{(6)}$**	16.376	13.765	10.951	8.269
RNN+4xSRNN+Re	14.066	**17.691$^{(4)}$**	9.136	10.088	7.656
L RNN+4xSRNN+Re	**16.627$^{(9)}$**	**18.941$^{(1)}$**	13.469	12.105	12.349

Table 10: Held out test log-likelihood for `susy` dataset.The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	−6.220	−5.848	−13.883	−25.793	**0.000$^{(0)}$**
L None	**−3.798$^{(8)}$**	−10.651	−9.084	−16.025	−36.051
RNN	−5.800	**−2.600$^{(3)}$**	−10.797	−25.760	−66.223
L RNN	**−3.975$^{(9)}$**	**−0.340$^{(1)}$**	−8.574	−18.607	−32.753
2xRNN	−6.456	−4.833	−9.192	−25.398	−60.040
L 2xRNN	−5.866	**−3.222$^{(5)}$**	−8.216	−16.083	−30.730
4xAdd+Re	−6.502	−10.491	−9.356	−13.678	−15.138
L 4xAdd+Re	−5.377	−5.611	−8.006	−12.106	−14.129
4xSRNN+Re	−7.422	−6.863	−11.033	−11.878	−12.182
L 4xSRNN+Re	−5.999	−9.329	−8.474	−8.223	−8.926
RNN+4xAdd+Re	**−4.242$^{(10)}$**	−4.804	−9.187	−12.321	−15.261
L RNN+4xAdd+Re	**−3.396$^{(6)}$**	**−3.049$^{(4)}$**	−8.052	−12.246	−13.765
RNN+4xSRNN+Re	−5.262	**−2.116$^{(2)}$**	−10.105	−12.307	−9.388
L RNN+4xSRNN+Re	**−3.756$^{(7)}$**	−4.773	−8.097	−9.378	−7.721

Table 11: Held out test log-likelihood for `higgs` dataset.The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	2.328	**3.710$^{(6)}$**	−4.948	−19.771	*nan*
L None	**3.570$^{(7)}$**	2.517	−4.052	−9.266	−35.042
RNN	2.088	**4.935$^{(1)}$**	−1.639	−19.851	−47.686
L RNN	**2.869$^{(10)}$**	**5.047$^{(2)}$**	−2.920	−16.032	−30.210
2xRNN	1.774	0.902	−1.909	−15.440	−36.754
L 2xRNN	2.053	**3.680$^{(5)}$**	−2.150	−15.457	−24.079
4xAdd+Re	1.678	1.873	−4.046	−9.117	−11.387
L 4xAdd+Re	1.961	2.543	−2.259	−6.907	−9.275
4xSRNN+Re	1.443	2.156	−2.904	−6.091	−7.186
L 4xSRNN+Re	2.072	2.730	−3.014	−5.747	−6.245
RNN+4xAdd+Re	2.817	0.912	−2.514	−6.003	−9.284
L RNN+4xAdd+Re	**3.906$^{(3)}$**	−1.869	−3.847	−6.339	−9.103
RNN+4xSRNN+Re	2.663	**3.586$^{(8)}$**	−0.863	−7.146	−3.939
L RNN+4xSRNN+Re	**3.759$^{(4)}$**	**3.487$^{(9)}$**	−0.239	−7.522	−6.102

Table 12: Held out test log-likelihood for `hepmass` dataset.The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	**−1.716$^{(9)}$**	**−1.257$^{(3)}$**	−9.296	−50.507	*nan*
L None	−20.164	**−1.079$^{(4)}$**	−2.635	**−1.570$^{(5)}$**	−5.972
RNN	−7.728	−4.949	−5.466	−6.047	−16.521
L RNN	−31.296	**−0.773$^{(2)}$**	−3.944	**−1.824$^{(8)}$**	−2.977
2xRNN	−12.283	**−2.193$^{(7)}$**	−2.137	−5.447	−8.075
L 2xRNN	−20.968	**−0.550$^{(1)}$**	−5.140	**−1.699$^{(6)}$**	**−2.276$^{(10)}$**
4xAdd+Re	−19.931	−7.539	−11.826	−18.901	−17.977
L 4xAdd+Re	−21.128	−9.944	−12.336	−21.677	−24.070
4xSRNN+Re	−7.519	−11.368	−2.549	−7.730	−7.232
L 4xSRNN+Re	−18.170	−7.709	−5.533	−17.085	−15.347
RNN+4xAdd+Re	−19.278	−11.789	−12.837	−21.249	−22.786
L RNN+4xAdd+Re	−20.899	−12.949	−12.867	−26.164	−28.302
RNN+4xSRNN+Re	−13.476	−3.951	−6.284	−15.025	−16.443
L RNN+4xSRNN+Re	−20.179	−12.128	−7.258	−18.065	−18.125

Table 13: Held out test log-likelihood for `satimage2` dataset.The superscript denotes ranking of log-likelihood on crossvalidation dataset

Transformation	LAM FC	RAM FC	TIED FC	MultiInd	SingleInd
None	−57.873	−97.925	−98.047	−113.099	*nan*
L None	**−52.954$^{(4)}$**	−74.220	−72.441	−82.866	−104.287
RNN	**−54.933$^{(10)}$**	−80.436	−74.361	−106.219	−144.735
L RNN	**−52.710$^{(3)}$**	−59.815	−66.536	−82.731	−98.813
2xRNN	−56.958	−85.359	−77.456	−104.440	−133.898
L 2xRNN	**−53.956$^{(8)}$**	−57.611	−65.016	−82.678	−96.542
4xAdd+Re	−56.349	−69.302	−67.064	−73.886	−83.524
L 4xAdd+Re	**−53.169$^{(5)}$**	−59.282	−59.093	−69.887	−79.330
4xSRNN+Re	−57.670	−68.116	−74.006	−78.032	−121.197
L 4xSRNN+Re	**−53.879$^{(7)}$**	−55.665	−63.894	−77.564	−81.188
RNN+4xAdd+Re	**−53.177$^{(6)}$**	−67.377	−63.372	−73.882	−84.032
L RNN+4xAdd+Re	**−51.572$^{(1)}$**	−56.190	−58.885	−69.484	−79.555
RNN+4xSRNN+Re	**−54.065$^{(9)}$**	−61.204	−76.437	−71.814	−81.087
L RNN+4xSRNN+Re	**−52.617$^{(2)}$**	−68.756	−65.061	−83.292	−78.997

Table 14: Held out test log-likelihood for `music` dataset.The superscript denotes ranking of log-likelihood on crossvalidation dataset