Transformer-XH: Multi-hop Question Answering with eXtra Hop Attention

Abstract

Transformers have obtained significant success modeling natural language as a sequence of text tokens. However, in many real world scenarios, textual data inherently exhibits structures beyond a linear sequence such as trees and graphs; an important one being multi-hop question answering, where evidence required to answer questions are scattered across multiple related documents. This paper presents Transformer-XH, which uses eXtra Hop attention to enable the intrinsic modeling of structured texts in a fully data-driven way. Its new attention mechanism naturally "hops" across the connected text sequences in addition to attending over tokens within each sequence. Thus, Transformer-XH better answers multi-hop questions by propagating information between multiple documents, constructing global contextualized representations, and jointly reasoning over multiple pieces of evidence. This leads to a simpler multi-hop QA system which outperforms previous state-of-the-art on the HotpotQA FullWiki setting by large margins.

1 Introduction

Transformers effectively model natural language in *sequential* form (Vaswani et al., 2017; Dai et al., 2019; Devlin et al., 2019; Yang et al., 2019). Nevertheless, in many NLP tasks, text does not simply appear as a linear sequence of tokens but rather carries meaningful structure in the form of paragraphs, headings, and hyperlinks. These structures can be abstracted into trees or graphs with nodes and edges. Multi-hop question answering (Yang et al., 2018) is one such task in which structure plays an important role, since the evidence required to formulate the answer is scattered across multiple documents, requiring systems to jointly reason across links between them.

Recent approaches leverage pre-trained Transformers (e.g., BERT) for multi-hop question answering (QA) by converting the structural reasoning task into sub-tasks that model flat sequences. For example, Min et al. (2019b) decompose a multi-hop question into a series of single-hop questions; Ding et al. (2019) conduct several steps of single-hop reading comprehension to simulate the multi-hop reasoning. The hope is that additional processing to fuse the outputs of the sub-models can recover all the necessary information from the original structure. While pre-trained Transformer language models have shown improvements on multi-hop QA, manipulating the inherent structure of the problem to fit the rigid requirements of out-of-the-box models can introduce problematic assumptions or information loss.

This paper presents Transformer-XH (meaning eXtra Hop), which upgrades Transformers with the ability to natively represent structured texts. Transformer-XH introduces extra hop attention in its layers that connects different text pieces following their inherent structure while also maintaining the powerful pre-trained Transformer abilities over each textual piece individually. Our extra hop attention enables 1) a more global representation of the evidence presented by each piece of text as it relates to the other evidence, and 2) a more natural way to jointly reason over an evidence graph by propagating information along edges necessary to complete the task at hand.

We apply Transformer-XH to HotpotQA, a challenging benchmark for the multi-hop question answering task (Yang et al., 2018). Rather than decomposing the task into a series of sub-tasks to fit the constraints of pre-trained Transformers, Transformer-XH is a solution that fits the problem as it naturally occurs. It is a single model that represents and combines evidence from multiple documents to construct the answer.

(a) Hop attention on the path $d_2 \to d_1 \to d_3$.   (b) Transformer-XH in Multi-hop QA

Figure 1: The eXtra Hop attention in Transformer-XH (a) and its application to multi-hop QA (b).

On HotpotQA's FullWiki setting, which is a more realistic setup and requires stronger multi-hop reasoning ability (Min et al., 2019b; Jiang & Bansal, 2019), Transformer-XH outperforms CogQA (Ding et al., 2019), the previous start-of-the-art, by 12 points on answer F1. It also beats the contemporary BERT based pipeline SR-MRS (Nie et al., 2019), by 3 points. The results follow from our simple yet effective design, with one unified model operating over the inherent structure of the task, rather than melding the outputs from disparate sub-tasks adapted to the sequential constraints of pre-trained Transformer. Our ablation analysis demonstrates Transformer-XH's efficacy on questions that are known to require multi-hop reasoning (Min et al., 2019b), and that the source of this success is due to the eXtra Hop attention mechanism's ability to combines information from multiple documents.

2 MODEL

This section first discusses preliminaries on sequential Transformers, then we show how we incorporate eXtra hop attention to create Transformer-XH.

2.1 PRELIMINARIES

Transformers represent a sequence of input text tokens $X = \{x_1, ..., x_i, ..., x_n\}$ into contextualized distributed representations $H = \{h_1, ..., h_i, ..., h_n\}$ (Vaswani et al., 2017). This process involves multiple stacked self-attention layers that converts the input X into $\{H^0, H^1, ..., H^l, ...H^L\}$, starting from H^0, the embeddings, to the final layer of depth L.

The key idea of Transformer is its attention mechanism, which calculates the l-th layer output H^l using the input H^{l-1} from the previous layer:

$$H^l = \text{softmax}(\frac{Q \cdot K^T}{\sqrt{d_k}}) \cdot V^T, \tag{1}$$

$$Q^T; K^T; V^T = W^q \cdot H^{l-1}; W^k \cdot H^{l-1}; W^v \cdot H^{l-1}. \tag{2}$$

It includes three projections on the input H^{l-1}: Query (Q), Key (K), and Value (V).

Specifically, the slices of token h_i^l in Eqn.(2) is:

$$h_i^l = \sum_j \text{softmax}_j(\frac{q_i^T \cdot k_j}{\sqrt{d_k}}) \cdot v_j, \tag{3}$$

which first calculates its attention to all other tokens j in the sequence and then combines the token values v_j into a new representation h_i^l, using the normalized attention weights. Multiple attentions can be used in one Transformer layer and concatenated as multi-head attention (Vaswani et al.,

2017). The architecture is stacked to form rather deep networks, which leads to significant success of large pre-trained Transformer models (Devlin et al., 2019; Liu et al., 2019a).

A challenge of Transformer is that its attention is calculated over all token pairs (Eqn. 3), which is hard to scale to long text sequences. Transformer-XL (eXtra Long) addresses this challenge by breaking down longer texts, e.g., a multi-paragraph document, into a sequence of text segments: $\{X_1, ..., X_\tau, ..., X_\zeta\}$, and propagates the information between adjacent text segments using the following attention:

$$\tilde{H}_\tau^{l-1} = [\text{Freeze}(H_{\tau-1}^{l-1}) \circ H_\tau^{l-1}]. \tag{4}$$

It concatenates ($\circ$) the representation of the previous segment $H_{\tau-1}^{l-1}$ to the current segment as segment level recurrences. The new representation $\tilde{H}_\tau^{l-1}$ includes the information from previous segment and is integrated in the new attention mechanism:

$$\tilde{Q}^T; \tilde{K}^T; \tilde{V}^T = W^q \cdot H_\tau^{l-1}; W^k \cdot \tilde{H}_\tau^{l-1}; W^v \cdot \tilde{H}_\tau^{l-1}. \tag{5}$$

The attention over the previous segment allows Transformer-XL to effectively model long form text data recurrently as a sequence of text chunks (Dai et al., 2019).

Nevertheless, in many scenarios, the text segments are organized in nontrivial structures beyond a linear sequence. For example, documents are connected by hyperlinks in a graphical structure that does not readily simplify to form a linear sequence, prohibiting Transformer-XL's recurrent approach.

2.2 TRANSFORMER-XH WITH EXTRA HOP ATTENTION

Transformer-XH models structured text sequence by linking them with eXtra Hop attention following their original structure. As illustrated in Figure 1a, to model three connected documents $d_2 \rightarrow d_1 \rightarrow d_3$, Transformer-XH uses eXtra Hop attention to propagate information along the graph edges, enabling information sharing between connected text sequence.

Formally, the structured text data includes a set of nodes, $\mathcal{X} = \{X_1, ..., X_\tau, ...X_\zeta\}$, each corresponding to a text sequence, and an edge matrix E, which includes the connections (e.g., links) between them. The goal is to learn representations $\mathcal{H} = \{\tilde{H}_1, ..., \tilde{H}_\tau, ...\tilde{H}_\zeta\}$, that incorporate not only the local information in each sequence X, but also the global contexts on the entire structured text $\{\mathcal{X}, E\}$.

Transformer-XH achieves this by two attention mechanisms: in-sequence attention and eXtra Hop attention. The *in-sequence attention* is the same as vanilla Transformer: in layer l, token i gathers information from other tokens inside the same text piece τ:

$$h_{\tau,i}^l = \sum_j \text{softmax}_j\left(\frac{q_{\tau,i}^T \cdot k_{\tau,j}}{\sqrt{d_k}}\right) \cdot v_{\tau,j}. \tag{6}$$

The *eXtra Hop attention* uses the first token in each sequence – the added special token "[CLS]" – as an "attention hub", which attends on all other connected nodes' hub token. In layer l, the τ-th text sequence attends on other text sequence η if there is an edge between them ($e_{\tau\eta} = 1$):

$$\hat{h}_{\tau,0}^l = \sum_{\eta;e_{\tau\eta}=1} \text{softmax}_\eta\left(\frac{\hat{q}_{\tau,0}^T \cdot \hat{k}_{\eta,0}}{\sqrt{d_k}}\right) \cdot \hat{v}_{\eta,0}. \tag{7}$$

Node τ calculates the attention weight on its neighbor η using hop query $\hat{q}_{\tau,0}$ and key $\hat{k}_{\eta,0}$. Then it uses the weights to combine its neighbors' value $\hat{v}_{\eta,0}$ and forms a globalized representation $\hat{h}_{\tau,0}^l$.

The two attention mechanism are combined to form the new representation of layer l:

$$\tilde{h}_{\tau,0}^l = \text{Linear}([h_{\tau,0}^l \circ \hat{h}_{\tau,0}^l]), \tag{8}$$

$$\tilde{h}_{\tau,i}^l = h_{\tau,i}^l; \forall i \neq 0. \tag{9}$$

Note that the non-hub tokens ($i \neq 0$) still have access to the hop attention in the previous layer through Eqn. (6).

One layer of eXtra Hop attention can be viewed as single-step of information propagation along edges E. For example, in Figure 1a, the document node d_3 updates its representation by gathering information from its neighbor d_1 using the hop attention $d_1 \rightarrow d_3$. When multiple Transformer-XH layers are stacked, this information in d_1 includes both d_1's local contexts from its in-sequence attention, and cross-sequence information from the hop attention $d_2 \rightarrow d_1$ of the $l-1$ layer. Hence, an L-layer Transformer-XH can attend over information from up to L hops away.

Together, three main properties equip Transformer-XH to effectively model raw structured text data: the propagation of information (values) along edges, the importance of that information (hop attention weights), and the balance of in-sequence and cross-sequence information (attention combination). The representations learned in $\mathcal{H}$ can innately express nuances in structured text that are required for complex chains of reasoning in tasks such as multi-hop QA.

3 APPLICATION TO MULTI-HOP QUESTION ANSWERING

This section describes how Transformer-XH applies to multi-hop QA. Given a question q, the task is to find an answer span a in a large open-domain document corpus, e.g. the first paragraph of all Wikipedia pages. By design, the questions are complex and often require information from multiple documents to answer. For example, in the case shown in Figure 1b, the correct answer "Cambridge" requires combining the information from both the Wikipedia pages "Facebook" and "Harvard University". To apply Transformer-XH in the open domain multi-hop QA task, we first construct an evidence graph and then apply Transformer-XH on the graph to find the answer.

Evidence Graph Construction. The first step is to find the relevant candidate documents D for the question q and connect them with edges E to form the graph G. Our set D consists of three sources. The first two sources are from canonical information retrieval and entity linking techniques:

D_{ir}: the top 100 documents retrieved by DrQA's TF-IDF on the question (Chen et al., 2017).

D_{el}: the Wikipedia documents associated with the entities that appear in the question, annotated by entity linking systems: TagMe (Ferragina & Scaiella, 2010) and CMNS (Hasibi et al., 2017).

For better retrieval quality, we use a BERT ranker (Nogueira & Cho, 2019) on the set $D_{ir} \cup D_{el}$ and keep the top two ranked ones in D_{ir} and top one per question entity in D_{el}. Then the third source D_{exp} include all documents connected to or from any top ranked documents via Wikipedia hyperlinks (e.g., "Facebook" $\rightarrow$ "Harvard University").

The final graph comprises all documents from the three sources as nodes $\mathcal{X}$. The edge matrix E is flexible. We experiment with various edge matrix settings, including directed edges along Wikipedia links, i.e. $e_{ij} = 1$ if there is a hyperlink from document i to j, the bidirectional edges along Wiki links, and fully-connected graphs, which rely on Transformer-XH to learns the edge importance.

Similar to previous work (Ding et al., 2019), the textual representation for each node in the graph is the [SEP]-delimited concatenation of the question, anchor text (the text in the hyperlink in parent nodes pointing to the child node), and the paragraph itself. More details on the evidence graph construction are in Appendix A.1.

Transformer-XH on Evidence Graph. Transformer-XH takes the input nodes $\mathcal{X}$ and edges E, and produces the global representation of all text sequences:

$$\mathcal{H}^L = \text{Transformer-XH}(\mathcal{X}, E). \tag{10}$$

Then we add two task-specific layers upon the last layer's representation $\mathcal{H}^L$: one auxiliary layer to predict the relevance score of the evidence node, and one layer to extract the answer span within it:

$$p(\text{relevance}|\tau) = \text{softmax}(\text{Linear}(\tilde{h}^L_{\tau,0})); \tag{11}$$

$$p(\text{start}|\tau, i), p(\text{end}|\tau, j) = \text{softmax}(\text{Linear}(\tilde{h}^L_{\tau,i})), \text{softmax}(\text{Linear}(\tilde{h}^L_{\tau,j})). \tag{12}$$

The final model is trained end-to-end with cross-entropy loss for both tasks in a multi-task setting. During inference, we first select the document with the highest relevance score, and then the start and end positions of the answer within that document.

4 EXPERIMENTAL METHODOLOGIES

Dataset. We conduct our experiments on HotpotQA, the multi-hop question answering benchmark dataset (Yang et al., 2018). It includes 112k crowd-sourced questions designed to require multiple pieces of textual evidence, which are the first paragraphs of Wikipedia pages. It has two type of questions: bridge question require hopping via an outside entity, and comparison question compare a property of two entities. There are two settings in HotpotQA. The Distractor setting provides golden evidence paragraphs together with TF-IDF retrieved negatives. The FullWiki setting requires systems to retrieve evidence paragraphs from the full Wikipedia.

We focus on FullWiki setting since previous research found that the negative documents in Distractor may be too weak and mitigate the needs of multi-hop reasoning (Min et al., 2019b). There are 90k Train, 7k Dev and 7k Test questions. The ground truth answer and supporting evidence sentences in Train and Dev sets are provided. Test labels are hidden; only one submission is allowed to the leaderboard per 30 days[1]. We evaluate our final model on Test and conduct ablations on Dev.

Metrics. We use official evaluation metrics of HotpotQA: exact match (EM) and F1 on answer (Ans), supporting facts (Supp), and the combination (Joint). The supporting facts prediction is an auxiliary task that evaluates model's ability to find the evidence sentences. Joint EM is the product of the two EM result. Joint F1 first multiplies the precision and recall from Ans and Supp, then combines the Joint precision and recall to F1.

Baseline. The main baselines include Cognitive QA (CogQA, Ding et al. (2019)) and Semantic Retrieval MRS (SR-MRS, Nie et al. (2019)). CogQA uses several fine-tuned BERT machine reading comprehension (MRC) models to find hop entities and candidate spans, and then uses a BERT based Graph Convolution Network to rank the candidate spans. SR-MRS is a contemporary work and was the previous leaderboard rank one. It is a BERT based pipeline and uses fine-tuned BERT models to first rank the documents (twice), then to rank sentences to find supporting facts, and finally conducts BERT MRC on the concatenated evidence sentences.

We also re-implement CogQA and upgrade its IR with our BERT IR model (BERT on $D_{ir} \cup D_{el}$, same as Transformer-XH), for fair comparisons. We include other approaches on the FullWiki setting: Official Baseline (Yang et al., 2018), MUPPET (Feldman & El-Yaniv, 2019), QFE (Nishida et al., 2019), and DecompRC (Min et al., 2019a),

Implementation Details. The in-sequence attention and other standard Transformer components in Transformer-XH are initialized by the pre-trained BERT base model (Devlin et al., 2019). The extra hop attention parameters are initialized randomly and trained from scratch. The final model uses three hop steps. For bridge questions, we build the evidence graph described in Section 3. And for comparison questions, we build the fully-connected graph on the set $D_{ir} \cup D_{el}$ and train Transformer-XH separately. We leave more implementation details in the Appendix.

5 EVALUATION RESULTS

This section presents the evaluation results, ablation studies, and analyses on Hotpot QA.

5.1 OVERALL RESULT

Table 1 presents HotpotQA FullWiki results. Transformer-XH outperforms all previous methods by significant margins. The only exception is Supp F1, where SR-MRS performs slightly better, perhaps due to our different ways of Supp extraction. We only select supporting facts from the inference path to the answer, which fits the task purpose but may hurt the recall (more in Appendix).

Besides strong results, Transformer-XH's ability to natively represent structured data leads to much simpler QA system. Previously, in order to utilize pre-trained BERT, Hotpot QA approaches adapted the multi-hop reasoning task to comprise multiple sub-tasks. For example, given the retrieved documents, CogQA (w. BERT IR) first leverages one BERT MRC model to find hop entities and then another BERT MRC to find candidate answer spans. After that, it ranks the candidate spans

---

[1]https://hotpotqa.github.io/

	Dev						Test					
	Ans		Supp		Joint		Ans		Supp		Joint	
	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1
Official Baseline (Yang et al., 2018)	23.9	32.9	5.1	40.9	47.2	40.8	24.0	32.9	3.9	37.7	1.9	16.2
DecompRC (Min et al., 2019a)	-	43.3	-	-	-	-	30.0	40.7	-	-	-	-
QFE (Nishida et al., 2019)	-	-	-	-	-	-	28.7	38.1	14.2	44.4	8.7	23.1
MUPPET (Feldman & El-Yaniv, 2019)	31.1	40.4	17.0	47.7	11.8	27.6	30.6	40.3	16.7	47.3	10.9	27.0
CogQA (Ding et al., 2019)	37.6	49.4	23.1	58.5	12.2	35.3	37.1	48.9	22.8	57.7	12.4	34.9
SR-MRS* (Nie et al., 2019)	46.5	58.8	39.9	71.5	26.6	49.2	45.3	57.3	38.7	**70.8**	25.1	47.6
CogQA (w. BERT IR) [Ours]	44.8	57.7	29.2	62.8	18.5	43.4	-	-	-	-	-	-
Transformer-XH	**50.2**	**62.4**	**42.2**	**71.6**	**27.4**	**50.9**	**49.0**	**60.8**	**41.7**	70.0	**27.1**	**49.6**

Table 1: Results (%) on HotpotQA FullWiki Setting. Dev results of previous methods are reported in their papers. Test results are from the leaderboard. Contemporary method is marked by *.

	Question Type				Reasoning Type			
	Comparison (1487)		Bridge (5918)		Single-Hop (3426)		Multi-Hop (3979)	
	EM	F1	EM	F1	EM	F1	EM	F1
CogQA	43.3	51.1	36.1	49.0	45.1	61.1	31.1	39.4
SR-MRS*	62.0	68.9	42.4	56.1	52.3	68.4	41.3	50.3
CogQA (w. BERT IR)	54.1	60.9	42.4	56.9	52.0	69.3	38.6	47.8
Transformer-XH (w. BERT IR)	55.9	61.8	**48.7**	**62.6**	57.4	74.0	43.3	52.2
Transformer-XH (w. SR-MRS)	**64.3**	**70.7**	47.9	62.3	**58.1**	**74.3**	**45.3**	**55.2**

Table 2: Dev Ans (%) on different scenarios. Reasoning Types are estimated by Min et al. (2019b) via whether single-hop BERT has non-zero Ans F1. The numbers of questions are shown in brackets.

using a BERT based GAT, which is the only structure modeling step. In comparison, Transformer-XH is a unified model which directly represents structured texts and integrates BERT weights.

Table 2 further inspects model performances on the Dev set by question types and reasoning types. Transformer-XH significantly outperforms all baselines on bridge questions which require more multi-hop reasoning. And on the "multi-hop" questions, Transformer-XH has higher relative gains (39% over CogQA on EM) than the "single-hop" questions (27%), demonstrating its stronger multi-hop reasoning capability. We further study this in Section 5.3.

The gains of SR-MRS on comparison questions are mainly from its better retrieval on Comparison questions. For fair comparison of Transformer-XH's reasoning ability, we use the top retrieved documents from SR-MRS to construct Transformer-XH's evidence graph. The result system, Transformer-XH (w. SR-MRS), outperforms SR-MRS's multi-step BERT based reasoning on all metrics and question types. Transformer-XH's effectiveness is robust with multiple IR systems.

5.2 ABLATION STUDIES

Model Variations. We show the results of different model variations on the top left of Table 3. *Single-Hop BERT* uses BERT MRC model on each document individually, which significantly decreases the accuracy, confirming the importance of multi-hop reasoning in FullWiki setting (Min et al., 2019a). *GAT + BERT* first uses Graph Attention Network (Veličković et al., 2017) on the evidence graph to predict the best node; then it uses BERT MRC on the best document. It is 10% worse than Transformer-XH since the MRC model has no access to the information from other documents. *No Node Prediction* eliminates the node prediction task and only trains on span prediction task; the accuracy difference shows node prediction task helps the model training.

Graph Structures. We show Transformer-XH's performance with different graph structures on the bottom left of Table 3. *Bidirectional Edges* adds reverse edges along the hyperlinks; *Fully Connected Graph* connects all document pairs; *Node Sequence* randomly permutes the documents and connects them into a sequence to simulate the Transformer-XL setting. Both *Bidirectional Links* and *Fully Connected Graph* have comparable performance with the original graph structure. Transformer-XH is able to learn meaningful connections using its hop attentions and is less dependent on the pre-existing graph structural. The fully connected graph can be used if there is no strong

Model Ablation	Dev Ans		Hop Steps	Dev Ans	
	EM	F1		EM	F1
Single-Hop BERT MRC on Individual Documents	31.3	42.2	One Hop	46.9	60.7
GAT (Node Prediction) + BERT (MRC on Best Node)	45.3	58.8	Two Hops	47.9	62.1
No Node Prediction Multi-Task	42.1	54.4	Four Hops	48.0	61.9
Bidirectional Edges on Hyperlinks	47.9	62.2	Five Hops	47.4	61.6
Fully Connected Graph	48.3	62.4	Six Hops	46.7	60.7
Node Sequence (Bidirectional Transformer-XL)	14.1	20.7	Transformer-XH	**48.7**	**62.6**

Table 3: Ablation studies on the bridge questions on Dev answer accuracy (%), including model components (top left), graph structures (bottom left), and hop steps (right). Transformer-XH's full model uses three hop step and unidirectional Wiki link graph.

(a) First Hop Attentions. (b) Second Hop Attentions. (c) Third Hop Attentions.

Figure 2: Distributions of learned attention weights of three hops on three groups: From All (Node) → (to) All, All → (to) Ans (ground truth answer node), and Supp (nodes with the supporting facts) → (to) Ans. X-axes are attention values scaled by number of nodes.

edge patterns available in the task. However, the performance drops significantly on *Node Sequence*, showing that structured texts cannot be treated as a linear sequence which cuts off many connections.

Hop Steps. Recall that a Transformer-XH layer with extra hop attention corresponds to one information propagation (hop) step in the graph. Thus Transformer-XH with last K layers conducts K-step attention hops in the graph. We show results with different K on the right side of Table 3. Transformer-XH reaches its peak performance with three hops (our full-model). This is expected as most Hotpot QA questions can be answered by two documents (Yang et al., 2018).

5.3 HOP ATTENTION ANALYSIS

This experiment analyzes the hop attentions using our full-model (three-hop) on the fully connected graph to study their behavior without pre-defined structure. Figure 2 plots the distributions of the learned hop attentions on the Dev set. It shows a strong shift away from the normal distribution with more hops. Transformer-XH learns to distinguish different nodes after multi-hop attention: the attention score becomes a bimodal distribution after three hops, ignoring some non-useful nodes. Transformer-XH also learns to focus on meaningful edges: the score is higher on the path Supp→Ans than All→Ans. And the margin is larger as the hop step increases from one to three.

5.4 CASE STUDY

Table 4 lists two examples from Transformer-XH and CogQA (w. BERT IR). The first case has a clear evidence chain "2011/S/S"→"Winner"→"YG Entertainment"; both methods find the correct answer. However, the second case has too many distractors in the first document. Without additional clues from document 2, it is likely that the single-hop hop entity extraction component in CogQA (w. BERT IR) misses the correct answer document in its candidate sets; and the later structural reasoning component can not recover from this cascade error. In comparison, Transformer-XH finds the correct answer by combining the evidence with the hop attentions between the two evidence pieces. We leave more positive and negative cases in Appendix A.5.

| **Q**: 2014 S/S is the debut album of a South Korean boy group that was formed by who?
Document 1: 2014 S/S is the debut album of South Korean group Winner.
Document 2: Winner is a South Korean boy group formed in 2013 by **YG Entertainment**.
Prediction:
   Transformer-XH: YG Entertainment ✓
   CogQA (w. BERT IR): YG Entertainment ✓ | **Q**: Which man who presented 2022 FIFA World Cup bid was born on October 22, 1930?
Document 1: 2022 FIFA World Cup bid was presented by Frank Lowy, Ben Buckley, Quentin Bryce and Elle Macpherson.
Document 2: **Frank Lowy** (born 22 October 1930), is an Australian-Israeli businessman and Chairman of Westfield Corporation.
Prediction:
   Transformer-XH: Frank Lowy ✓
   CogQA (w. BERT IR): Quentin Bryce ✗ |
|---|---|

Table 4: Examples of Transformer-XH and BERT pipeline results in Hotpot QA.

6 RELATED WORK

Machine reading comprehension is an important task of natural language processing (Rajpurkar et al., 2016; Bajaj et al., 2016). The initial MRC questions are mostly single-hop, which only require single evidence sentence to answer (Min et al., 2018). One direction to make the task more realistic is open-domain question answering (QA), in which the evidence paragraph has to be retrieved from a large corpus (Chen et al., 2017). The other direction is multi-hop QA, where the questions require multiple pieces of evidence to answer (Welbl et al., 2018; Yang et al., 2018).

HotpotQA's FullWiki setting is a combination of open-domain QA and multi-hop QA (Yang et al., 2018): the questions are designed to require multiple pieces of evidence and these evidence pieces are documents to retrieve from the entire Wikipedia. The combination makes this setting challenging: The retrieved documents are inevitably noisy and include much stronger distractors than the TF-IDF retrieved documents in the Distractor setting (Min et al., 2019a; Jiang & Bansal, 2019).

Various solutions have been proposed for Hotpot QA (Min et al., 2019b; Feldman & El-Yaniv, 2019; Nishida et al., 2019). These solutions often use complicated pipelines to adapt the multi-hop task into a combination of single-hop tasks, in order to leverage the advantage of pre-trained models. For example, CogQA (Ding et al., 2019) uses two BERT based MRC model to find candidate spans and then another BERT initialized Graph Neural Network (GNN) to rank spans; SR-MRS (Nie et al., 2019) uses three BERT based rankers to find supporting sentences, and then another BERT MRC model on the concatenated sentences to get the answer span. Transformer-XH is a simpler model that directly represents and reasons with multiple pieces of evidence using extra hop attentions.

In addition to Transformer-XL (Dai et al., 2019), Transformer-XH is also inspired by GNN (Kipf & Welling, 2017; Schlichtkrull et al., 2017; Veličković et al., 2017), which leverages neural networks to model graph structured data. The key difference is that a "node" in Transformer-XH is a text sequence, and modeling of the structure is conducted jointly with the representation of the text. Transformer-XH combines the advantages Transformer has in understanding text with the power that GNN has in modeling structure.

7 CONCLUSION

Transformer-XH and its eXtra Hop attention mechanism is a simple yet powerful adaptation of Transformer to learn better representations of structured text data as it naturally occurs. It innately integrates with pre-trained language models to allow for complex reasoning across many hops of a textual evidence graph, where clues to the correct answer of a question are split across multiple documents. When applied to HotpotQA, Transformer-XH significantly shrinks the typical multi-hop QA pipeline, eliminating many cascading errors that arise from the linear sequence input constraints of pre-trained Transformers. Compared to previous SOTA baselines that use pipelines of BERT models to mimic multi-hop reasoning, one Transformer-XH model is all we need to obtain a much stronger answer accuracy. With its simplicity and efficacy, we envision Transformer-XH will benefit many applications in the near future.

REFERENCES

Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*, 2016.

Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. Reading wikipedia to answer open-domain questions. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1870–1879, 2017.

Zihang Dai, Zhilin Yang, Yiming Yang, William W Cohen, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Ming Ding, Chang Zhou, Qibin Chen, Hongxia Yang, and Jie Tang. Cognitive graph for multi-hop reading comprehension at scale. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2694–2703, Florence, Italy, July 2019. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P19-1259.

Yair Feldman and Ran El-Yaniv. Multi-hop paragraph retrieval for open-domain question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2296–2309, Florence, Italy, July 2019. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P19-1222.

Paolo Ferragina and Ugo Scaiella. Tagme: on-the-fly annotation of short text fragments (by wikipedia entities). In *Proceedings of the 19th ACM international conference on Information and knowledge management*, pp. 1625–1628. ACM, 2010.

Faegheh Hasibi, Krisztian Balog, and Svein Erik Bratsberg. Entity linking in queries: Efficiency vs. effectiveness. In *European Conference on Information Retrieval*, pp. 40–53. Springer, 2017.

Yichen Jiang and Mohit Bansal. Avoiding reasoning shortcuts: Adversarial evaluation, training, and model development for multi-hop QA. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2726–2736, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1262. URL https://www.aclweb.org/anthology/P19-1262.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. 2017.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019a.

zhenghao Liu, Chenyan Xiong, and Maosong Sun. Kernel graph attention network for fact verification. *arXiv preprint*, 2019b.

Sewon Min, Victor Zhong, Richard Socher, and Caiming Xiong. Efficient and robust question answering from minimal context over documents. In *ACL*, 2018.

Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. Compositional questions do not necessitate multi-hop reasoning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4249–4257, Florence, Italy, July 2019a. Association for Computational Linguistics. doi: 10.18653/v1/P19-1416. URL https://www.aclweb.org/anthology/P19-1416.

Sewon Min, Victor Zhong, Luke Zettlemoyer, and Hannaneh Hajishirzi. Multi-hop reading comprehension through question decomposition and rescoring. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 6097–6109, Florence, Italy, July 2019b. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P19-1613.

Yixin Nie, Songhe Wang, and Mohit Bansal. Revealing the importance of semantic retrieval for machine reading at scale. *arXiv preprint arXiv:1909.08041*, 2019.

Kosuke Nishida, Kyosuke Nishida, Masaaki Nagata, Atsushi Otsuka, Itsumi Saito, Hisako Asano, and Junji Tomita. Answering while summarizing: Multi-task learning for multi-hop QA with evidence extraction. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2335–2345, Florence, Italy, July 2019. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/P19-1225.

Rodrigo Nogueira and Kyunghyun Cho. Passage re-ranking with bert. *arXiv preprint arXiv:1901.04085*, 2019.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2383–2392, 2016.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. *arXiv preprint arXiv:1703.06103*, 2017.

James Thorne, Andreas Vlachos, Oana Cocarascu, Christos Christodoulopoulos, and Arpit Mittal. The fact extraction and verification (fever) shared task. In *Proceedings of the First Workshop on Fact Extraction and VERification (FEVER)*, pp. 1–9, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Minjie Wang, Lingfan Yu, Da Zheng, Quan Gan, Yu Gai, Zihao Ye, Mufei Li, Jinjing Zhou, Qi Huang, Chao Ma, Ziyue Huang, Qipeng Guo, Hao Zhang, Haibin Lin, Junbo Zhao, Jinyang Li, Alexander J Smola, and Zheng Zhang. Deep graph library: Towards efficient and scalable deep learning on graphs. *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019. URL https://arxiv.org/abs/1909.01315.

Johannes Welbl, Pontus Stenetorp, and Sebastian Riedel. Constructing datasets for multi-hop reading comprehension across documents. *Transactions of the Association for Computational Linguistics*, 6:287–302, 2018.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*, 2019.

Jie Zhou, Xu Han, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Gear: Graph-based evidence aggregating and reasoning for fact verification. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, Volume 1 (Long Papers)*, 2019.

A   APPENDIX

The appendix includes details of the evidence graph construction for Hotpot QA, ablation studies in the BERT IR component, more details and results on Hotpot QA, and results on the FEVER fact verification task.

A.1   HOTPOTQA EVIDENCE GRAPH CONSTRUCTION DETAILS

The evidence graph construction includes two stages. The first stage is BERT IR, which extract related documents directly from question. The second stage expands the related documents along Wikipedia links. The first is applied on all questions while the second is only required by Bridge questions.

The first stage uses two methods to find documents. The first method uses DrQA's retrieval system (Chen et al., 2017), which is unsupervised TF-IDF. We keep the top 100 DrQA retrieved ones D_{ir} for each question. The second method uses TagMe (Ferragina & Scaiella, 2010) and CMNS (Hasibi et al., 2017), two commonly used entity linkers, to annotate questions. We keep the TagMe output entity and three highest scored entities per surface form (a phrase in the question linked with entities) from CMNS, and use its corresponding Wikipedia document as D_{el}.

We use BERT ranker (Nogueira & Cho, 2019) to re-rank the initial set $D_{ir} \cup D_{el}$. The input to the BERT is the concatenation of question and first paragraph of document:

```
[CLS] Question [SEP] First Paragraph of Document.
```

Then a linear layer is added on the last layer's [CLS] representation to score the relevance of the document. We use BERT base and fine-tune it using the relevance label (from supporting facts) with cross-entropy loss. The top two highest scored documents from D_{ir} and the top one document per entity position (surface form) in D_{el} are kept as the first stage BERT IR documents.

The second stage expands the first stage BERT IR documents by Wikipedia hyperlinks to obtain D_{exp}. A document is included if it is linked to or links to a document in the first stage. We use the same BERT ranker to rank D_{exp} and keep the top 15 documents in D_{exp}.

The final evidence graph nodes per question includes the top two highest ranked documents in D_{ir}, top one per entity name in D_{el}, and top 15 from the expanded documents D_{exp}.

The comparison questions only require information from two question entities; thus when building the evidence graph we do not expand them (i.e. there is no D_{exp}).

The retrieval pipeline is a multi-stage retrieval enhanced with entity linking. It is close to the retrieval system used in SR-MRS (Nie et al., 2019). When using SR-MRS retrieved documents for documents, we use top 10 documents on bridge questions and top two documents on comparison questions.

In the next section, we show that Transformer-XH is robust to different number of documents kept in the evidence graph and performs similarly using the documents retrieved from SR-MRS.

A.2   ABLATION STUDIES ON DOCUMENT RETRIEVAL

This experiment studies the effectiveness and influence of different retrieval settings. We use different numbers of top K ranked documents from the BERT ranker, run Transformer-XH in the corresponding evidence graph, and evaluate its performance on Bridge questions in the Dev set. We also evaluate the Supporting facts Recall and Answer Recall. Supp Recall evaluates whether the document with the supporting fact is included in the first stage retrieved documents. Ans Recall evaluates whether their exists a document in the evidence graph that includes the ground truth answer. The results are in Table 5.

Our BERT IR system performs better than CogQA's TF-IDF and on par with SR-MRS, as expected. The latter uses a similar retrieval pipeline with our BERT IR system; Transformer-XH is robust on different retrieval settings and keeps its effectiveness when applied on Top 10 documents from SR-MRS (including both stages).

Method	Supp Recall	Ans Recall	Dev Ans EM	Dev Ans F1
Top 10 TFIDF (CogQA)	70.8	n.a.	-	-
Top 2 w. BERT IR + Q Entites	72.3	88.1	**48.7**	**62.6**
Top 5 w. BERT IR + Q Entites	76.5	89.6	47.1	60.8
Top 10 w. BERT IR + Q Entites	**78.9**	**91.1**	46.6	60.3
SR-MRS Top 10 (All Together)	n.a.	86.1	47.9	62.3

Table 5: Ablation study on the retrieval systems. Top-10 TFIDF is the one used by CogQA (Ding et al., 2019). BERT IR is the retrieval system used by CogQA (w. BERT IR) and Transformer-XH. Top K refers to using the 2/5/10 highest ranked documents from the BERT ranker in the first stage. SR-MRS Top 10 uses the 10 retrieved documents per question provided by Nie et al. (2019). All retrieval methods include entities linked in the question and are expanded along Wiki links, except when evaluating the 1st stage Supp Recall.

A.3 Other Hotpot QA components

This section describes the other components for HotpotQA dataset. The whole QA system starts with question type classification. We train transformer-XH separately on each type of questions over their evidence graph. Besides answer prediction, we also adopt BERT based model for predicting supporting sentences.

A.3.1 Question classification

The first component of our system is to classify the question to bridge and comparison types. We adopt BERT classification fine-tuning setting on HotpotQA questions using the question type labels provided in HotpotQA. The classifier achieves 99.1% accuracy on the dev set. We use the classifier to split the questions into Comparison and Bridge.

A.3.2 Supporting facts classification

The supporting facts prediction task is to extract all sentences that help get the answer. For bridge question, these sentences usually cover different pieces of questions. And for comparison questions, the supporting facts are the properties of two question entities. We design one model architecture for this task, but we train two models on each type to reflect the inherent difference.

We use BERT as our base model and on top of BERT, we conduct multi-task learning scheme. The first task is document relevance prediction, similar as Transformer-XH, we add a linear layer on the [CLS] token of BERT to predict the relevance score. The other task is sentence binary classification, we concatenate the first and last token representation of each sentence in the document through a linear layer, the binary output decides whether this sentence is supporting sentence.

Bridge question supporting facts prediction   For bridge questions, we predict supporting facts after answer prediction from Transformer-XH to resume the inference chain. We start by predicting supporting facts in the answer document. The other document is chosen from the parents of the answer document in the evidence graph. [2]. Compare with the contemporary model Nie et al. (2019), which does not limit the search space along the inference chain (i.e., the answer document may not be relevant to the other supporting page), our method more naturally fits the task purpose.

Comparison question supporting facts prediction   For comparison questions, after extracting the first step documents D, we simply run this supporting facts prediction model to select the top-2 documents, and predict the corresponding supporting facts.

A.3.3 Training details

We use DGL (Wang et al., 2019) for implementing Transformer-XH and CogQA (w. BERT IR) with batch size 1 (i.e., one graph for each batch), and keep the other parameters same as default BERT setting. We train Transformer-XH separately on two different types of questions, following previous

---

[2]If the answer document does not have parent node, we choose from all documents

research (Ding et al., 2019). We train Transformer-XH and the GNN of CogQA (w. BERT IR) for 2 epochs. All other BERT based models use the default BERT parameters and train the model for 1 epoch.

A.4   Implementation Details of CogQA (W. BERT IR)

This section discusses our implementation of CogQA (W. BERT IR). We start with the same documents from BERT IR, the one used by Transformer-XH, and then implement the following steps:

A.4.1   Hop entity extraction

For each document from the previous step, we run BERT MRC model and limit the span candidates as hyperlinked entities for hop entity extraction (e.g., in Figure 1, "Harvard University" is a hop entity). Following Ding et al. (2019), we predict the top three entities that above the relative threshold that is the start span probability of [CLS] position.

A.4.2   Answer span Extraction

For each document (add the hop entity document), following Ding et al. (2019), we run BERT MRC model to extract spans (e.g., "Combridge" in Figure 1.). We predict the top one span that above the threshold that is the start span probability of [CLS] position.

We train both hop entity extraction and span extraction tasks with same BERT model but different prediction layers. For each training example, we extract the link between two given supporting pages. The page includes the link (e.g., "Harvard University" in Figure 1.) is the supporting page for hop entity extraction, while the other page is the answer page (e.g., "Combridge" in Figure 1.) for answer span extraction.

A.4.3   GAT modeling

All the entities and answer spans form the final graph. The nodes are the entities and spans, and edges are the connections from the entities to the extracted hop entities or spans.

We use BERT for each node representation with question, anchor sentences and context, following Ding et al. (2019). We run GAT (Veličković et al., 2017) on top of BERT to predict the correct answer span node.

A.4.4   Comparison Questions

After predicting supporting facts, we concatenate the sentences and follow Min et al. (2019b) to run a BERT MRC model to predict either span or yes/no as the answer.

A.5   Additional case study

We provide addition case studies in Table 6.

A.6   Evaluation on FEVER Fact Extraction and Verification Task

This section evaluates Transformer-XH in the FEVER Fact Extraction and Verification Task (Thorne et al., 2018), the other task SR-MRS was evaluated on (Nie et al., 2019).

A.6.1   FEVER Task

Dataset and Metrics. The FEVER task provides a claim sentence and requires the system to classify it into three categories: SUPPORTS, REFUTES, and NOT ENOUGH INFO, using the Wikipedia corpus as the evidence source. It provides 185,455 claims with manual labels and uses the Wikipedia dump in June 2017 which includes 5.4 million documents.

There are two official evaluation metrics in FEVER: Label Accuracy (LA), which evaluates the classification accuracy of the verification labels, and FEVER Score, which evaluates both the correctness

id	Example	Explanation
1(+)	**Q**: In which year was the King who made the 1925 Birthday Honours born?
P: 1865 ✓
Document 1: The 1925 Birthday Honours were appointments by King George V to various orders and honours.
Document 2: George V (3 June 1865 – 20 January 1936) was King of the United Kingdom.	With necessary evidence available, Transformer-XH conducts multi-hop reasoning, and extracts the correct span.
2(-)	**Q**: Where was the world cup hosted that Algeria qualified for the first time into the round of 16?
A: Brazil   **P**: Spain ✗
Document 1 (Algeria at the FIFA World Cup): In 2014, Algeria qualified for the first time into the round of 16.
Document 2 (2014 FIFA CUP): It took place in Brazil from 12 June to 13 July 2014, after the country was awarded the hosting rights in 2007.	Transformer-XH does not predict the correct answer, since document 1 does not link to any other documents. Thus, the information does not propagate to the correct answer document 2014 FIFA CUP.
3(-)	**Q**: What government position was held by the woman who portrayed Corliss Archer in the film Kiss and Tell?
A: Chief of Protocol   **P**: ambassador ✗
Document 1: Kiss and Tell is a 1945 American comedy film starring then 17-year-old Shirley Temple as Corliss Archer.
Document 2: As an adult, Shirley Temple was named United States ambassador to Ghana and to Czechoslovakia, and also served as Chief of Protocol of the United States.	Transformer-XH predicts the correct answer document Shirley Temple. However it could not distinguish from the wrong answer ambassador which she was named but not held that position.

Table 6: Additional examples for model prediction on HotpotQA dataset, the first example is the correct prediction (+), the other two examples are the wrong predictions (-).

of the evidence sentences used in verification and the LA. The latter is close to Joint EM in Hotpot QA and is the main metric. We use the official evaluation scripts[3] from FEVER task and we refer to Thorne et al. (2018) for more details of this task.

Evidence Graph Construction. Most top performance FEVER systems on the leaderboard first retrieve the evidence sentences for the claim and then reason upon the evidence sentences to verify the claim (Nie et al., 2019; Zhou et al., 2019). The first step is similar as the retrieval stage in Hotpot QA. And the second step is a multi-evidence reasoning task, where Transformer-XH is applied.

We keep the evidence sentence retrieval step consistent with previous methods. The sentence retrieval results of SR-MRS is not yet released at the time of our experiments, thus we instead use the BERT-based retrieval results from another contemporary work (Liu et al., 2019b) in the FEVER leaderboard[4].

We construct the evidence graph using the top five sentences from Liu et al. (2019b) as the nodes $\mathcal{X}$ and fully connected edges E. Following Liu et al. (2019b), the representation of each node is the concatenation of the claim, the Wiki title (entity name) of the document which includes the sentence, and the evidence sentence.

A.6.2   TRANSFORMER-XH ON FEVER

Transformer-XH takes the evidence graph $\{X, E\}$ and learns to verify the claim to three categories: $y \in \{$SUPPORT, REFUSE, and NOT ENOUGH EVIDENCE$\}$. Similar to the application in Hotpot

---

[3] https://github.com/sheffieldnlp/fever-scorer
[4] https://competitions.codalab.org/competitions/18814#results

	Dev		Test		Single Evidence		Multi Evidence	
	LA	FEVER	LA	FEVER	LA	FEVER	LA	FEVER
BERT Concat (Liu et al., 2019b)	73.67	68.89	71.01	65.64	-	-	-	-
GEAR/GAT (Zhou et al., 2019)	74.84	70.69	71.60	67.10	79.79	77.42	66.12	38.21
SR-MRS* (Nie et al., 2019)	75.12	70.18	72.56	67.26	-	-	-	-
KGAT* (Liu et al., 2019b)	78.02	**75.88**	**72.81**	**69.40**	80.33	78.07	65.92	39.23
Transformer-XH	**78.05**	74.98	72.39	69.07	**81.84**	**81.31**	**86.58**	**58.47**

Table 7: FEVER Results. Contemporary work is marked by *. Single and Multi Evidence are results on Dev claims on which one or multiple sentences are labeled as evidence.

QA, it first produces the global representation of the graph:

$$\mathcal{H}^L = \text{Transformer-XH}(\mathcal{X}, E). \tag{13}$$

Then two task-specific layers are added upon the last layer. The first layer conducts the fact prediction per node using the "[CLS]" token:

$$p(y|\tau) = \text{softmax}(\text{Linear}(\tilde{h}^L_{\tau,0})). \tag{14}$$

The second layer learns to measure the importance of each node in the graph:

$$p(s|\tau) = \text{softmax}(\text{Linear}(\tilde{h}^L_{\tau,0})), \tag{15}$$

The node level predictions and node importance are combined to the final prediction for the claim:

$$p(y|\mathcal{X}, E) = \sum_\tau p(s|\tau) \cdot p(y|\tau). \tag{16}$$

Similar as in Hotpot QA, we use multi-task learning that combines the node prediction task and the claim verification task. The first uses the evidence sentence label provided by FEVER and cross-entropy loss on Eqn. 15. The second is the final verification label with cross-entropy loss on Eqn. 16.

A.6.3 EXPERIMENTS ON FEVER

Experimental Setups. We follow the experiment settings used by previous research in FEVER 1.0 shared task, i.e. Nie et al. (2019), Zhou et al. (2019), and Liu et al. (2019b). Similar as Liu et al. (2019b), we also split the data into single and multi evidence categories and evaluate Transformer-XH on the two splits.

Baselines. The baselines include GEAR (Zhou et al., 2019) and two contemporary work, SR-MRS (Nie et al., 2019) and KGAT (Liu et al., 2019b). SR-MRS uses similar adaptations as Transformer-XH from Hotpot QA to FEVER. GEAR is a graph attention network based approach specially designed for fact verification. KGAT further improves GEAR's GAT by adding the kernel information, and is the best method on the current leaderboard with BERT base or smaller parameter sizes. (The better entries use Bert large or XL-NET.) We also include the BERT Concat baseline listed in Liu et al. (2019b) which concatenates the evidence sentences to a text sequence and applies BERT on it.

Evaluation Results. The results on FEVER are shown in Table 7. Transformer-XH outperforms SR-MRS by 4 FEVER score on Dev and 1.8 on Test. It performs on par with KGAT. The effectiveness of Transformer-XH is also more observed on claims that require multiple evidence to verify: it outperforms the contemporary work KGAT by 20 FEVER scores on the multi-evidence claims, a 49% relative improvement. Compared to KGAT, Transformer-XH mainly loses on the "not enough evidence" category which is not single nor multi evidence. This is a unique property of the fact verification task which our system is not specifically designed for.

This result further demonstrates Transformer-XH's effectiveness on tasks with multiple text inputs not in sequential formats. We simply adapt Transformer-XH to the FEVER dataset by only changing the last (linear) task specific layer; it leads to similar or better performances over contemporary approaches that were specifically designed for the fact verification task.