CHARACTERIZING AUDIO ADVERSARIAL EXAMPLES USING TEMPORAL DEPENDENCY

ABSTRACT

Recent studies have highlighted adversarial examples as a ubiquitous threat to different neural network models and many downstream applications. Nonetheless, as unique data properties have inspired distinct and powerful learning principles, this paper aims to explore their potentials towards mitigating adversarial inputs. In particular, our results reveal the importance of using the temporal dependency in audio data to gain discriminate power against adversarial examples. Tested on the automatic speech recognition (ASR) tasks and three recent audio adversarial attacks, we find that (i) input transformation developed from image adversarial defense provides limited robustness improvement and is subtle to advanced attacks; (ii) temporal dependency can be exploited to gain discriminative power against audio adversarial examples and is resistant to adaptive attacks considered in our experiments. Our results not only show promising means of improving the robustness of ASR systems, but also offer novel insights in exploiting domain-specific data properties to mitigate negative effects of adversarial examples.

1 INTRODUCTION

Deep Neural Networks (DNNs) have been widely adopted in a variety of machine learning applications (Krizhevsky et al., 2012; Hinton et al., 2012; Levine et al., 2016). However, recent work has demonstrated that DNNs are vulnerable to adversarial perturbations (Szegedy et al., 2014; Goodfellow et al., 2015). An adversary can add negligible perturbations to inputs and generate adversarial examples to mislead DNNs, first found in image-based machine learning tasks (Goodfellow et al., 2015; Carlini & Wagner, 2017a; Liu et al., 2017; Chen et al., 2017b;a; Su et al., 2018).

Beyond images, given the wide application of DNN-based audio recognition systems, such as Google Home and Amazon Alexa, audio adversarial examples have also been studied recently (Carlini & Wagner, 2018; Alzantot et al., 2018; Cisse et al., 2017; Kreuk et al., 2018). Comparing between image and audio learning tasks, although their state-of-the-art DNN architectures are quite different (i.e., convolutional v.s. recurrent neural networks), the attacking methodology towards generating adversarial examples is fundamentally unanimous - finding adversarial perturbations through the lens of maximizing the training loss or optimizing some designed attack objectives. For example, the same attack loss function proposed in (Cisse et al., 2017) is used to generate adversarial examples in both visual and speech recognition models. Nonetheless, different types of data usually possess unique or domain-specific properties that can potentially be used to gain discriminative power against adversarial inputs. In particular, the temporal dependency in audio data is an innate characteristic that has already been widely adopted in the machine learning models. However, in addition to improving learning performance on natural audio examples, it is still an open question on whether or not the temporal dependency can be exploited to help mitigate negative effects of adversarial examples.

The focus of this paper has two folds. First, we investigate the robustness of automatic speech recognition (ASR) models under *input transformation*, a commonly used technique in the image domain to mitigate adversarial inputs. Our experimental results show that four implemented transformation techniques on audio inputs, including waveform quantization, temporal smoothing, downsampling and autoencoder reformation, provide limited robustness improvement against the recent attack method proposed in (Athalye et al., 2018), which aims to circumvent the gradient obfuscation issue incurred by input transformations. Second, we demonstrate that temporal dependency can be

used to gain discriminative power against adversarial examples in ASR. We perform the proposed temporal dependency method on both the LIBRIS (Graetz et al., 1986) and Mozilla Common Voice datasets against three state-of-the-art attack methods (Carlini & Wagner, 2018; Alzantot et al., 2018; Yuan et al., 2018) considered in our experiments and show that such an approach achieves promising identification of non-adaptive and adaptive attacks. Moreover, we also verify that the proposed method can resist strong proposed adaptive attacks in which the defense implementations are known to an attacker. Finally, we note that although this paper focuses on the case of audio adversarial examples, the methodology of leveraging unique data properties to improve model robustness could be naturally extended to different domains. The promising results also shed new lights in designing adversarial defenses against attacks on various types of data.

Related work An adversarial example for a neural network is an input x^a that is similar to a natural input x but will yield different output after passing through the neural network. Currently, there are two different types of attacks for generating audio adversarial examples: the Speech-to-Label attack and the Speech-to-Text attack. The Speech-to-Label attack aims to find an adversarial example x^a close to the original audio x but yields a different (wrong) label. To do so, Alzantot et al. proposed a genetic algorithm (Alzantot et al., 2018), and Cisse et al. proposed a probabilistic loss function (Cisse et al., 2017). The Speech-to-Text attack requires the transcribed output of the adversarial audio to be the same as the desired output, which has been made possible by Carlini and Wagner (Carlini & Wagner, 2018) using optimization-based techniques operated on the raw waveforms. Iter et al. leveraged extracted audio features called Mel Frequency Cepstral Coefficients (MFCCs) (Iter et al., 2017). Yuan et al. demonstrated practical "wav-to-API" audio adversarial attacks (Yuan et al., 2018). Another line of research focuses on adversarial training or data augmentation to improve model robustness (Serdyuk et al., 2016; Michelsanti & Tan, 2017; Sriram et al., 2017; Sun et al., 2018), which is beyond our scope. Our proposed approach focuses on gaining the discriminative power against adversarial examples through embedded temporal dependency, which is compatible with any ASR model and does not require adversarial training or data augmentation.

2 Do Lessons from Image Adversarial Examples Transfer to Audio Domain?

Although in recent years both image and audio learning tasks have witnessed significant break-throughs accomplished by advanced neural networks, these two types of data have unique properties that lead to distinct learning principles. In images, the pixels entail spatial correlations corresponding to hierarchical object associations and color descriptions, which are leveraged by the convolutional neural networks (CNNs) for feature extraction. In audios, the waveforms possess apparent temporal dependency, which is widely adopted by the recurrent neural networks (RNNs). For the segmentation task in image domain, spatial consistency has played an important role in improving model robustness (Lowe, 1999). However, it remains unknown whether temporal dependency can have a similar effect of improving model robustness against audio adversarial examples. In this paper, we aim to address the following fundamental questions: (a) *do lessons learned from image adversarial examples transfer to the audio domain?*; and (b) *can temporal dependency be used to discriminate audio adversarial examples?* Moreover, studying the discriminative power of temporal dependency in audios not only highlights the importance of using unique data properties towards building robust machine learning models, but also aids in devising principles for investigating more complex data such as videos (spatial + temporal properties) or multimodal cases (e.g., images + texts).

Here we summarize two primary findings concluded from our experimental results in Section 4.

Audio input transformation is not effective against adversarial attacks Input transformation is a widely adopted defense technique in the image domain, owing to its low operation cost and easy integration with the existing network architecture (Luo et al., 2015; Wang et al., 2016; Dziugaite et al., 2016). Generally speaking, input transformation aims to perform certain feature transformation on the raw image in order to disrupt the adversarial perturbations before passing it to a neural network. Popular approaches include bit quantization, image filtering, image reprocessing, and autoencoder reformation (Xu et al., 2017; Guo et al., 2017; Meng & Chen, 2017). However, many existing methods are shown to be bypassed by subsequent or adaptive adversarial attacks (Carlini & Wagner, 2017b; He et al., 2017; Carlini & Wagner, 2017c; Lu et al., 2018). Moreover, Athalye et al. (Athalye et al., 2018) has pointed out that input transformation may cause *obfuscated gradients* when gener-

ating adversarial examples and thus gives a false sense of robustness. They also demonstrated that in many cases this gradient obfuscation issue can be circumvented, making input transformation still vulnerable to adversarial examples. Similarly, in our experiments we find that audio input transformations based on waveform quantization, temporal filtering, signal down sampling or autoencoder reformation suffers from similar weakness: the tested model with input transformation becomes fragile to adversarial examples when one adopts the attack considering gradient obfuscation as in (Athalye et al., 2018).

Temporal dependency possesses strong discriminative power against adversarial examples in automatic speech recognition Instead of input transformation, in this paper we propose to exploit the inherent temporal dependency in audio data to discriminate adversarial examples. Tested on the automatic speech recognition (ASR) tasks, we find that the proposed methodology can effectively detect audio adversarial examples while minimally affecting the recognition performance on normal examples. In addition, experimental results show that an considered adaptive adversarial attack, even when knowing every detail of the deployed temporal dependency method, cannot generate adversarial examples that bypass the proposed temporal dependency based approach.

Combining these two primary findings, we conclude that the weakness of defense techniques identified in the image case is very likely to be transferred to the audio domain. On the other hand, exploiting unique data properties to develop defense methods, such as using temporal dependency in ASR, can lead to promising defense approaches that can resist adaptive adversarial attacks.

3   TEMPORAL DEPENDENCY AND INPUT TRANSFORMATION IN AUDIO DATA

In this section, we will introduce the effect of basic input transformations on audio adversarial examples, and analyze temporal dependency in audio data. We will also show that such temporal dependency can be potentially leveraged to discriminate audio adversarial examples.

3.1   AUDIO ADVERSARIAL EXAMPLES UNDER SIMPLE INPUT TRANSFORMATIONS

Inspired by image input transformation methods and as a first attempt, we applied some primitive signal processing transformations to audio inputs. These transformations are useful, easy to implement, fast to operate and have delivered several interesting findings.

Quantization: By rounding the amplitude of audio sampled data into the nearest integer multiple of q, the adversarial perturbation could be disrupted since its amplitude is usually small in the input space. We choose $q = 128, 256, 512, 1024$ as our parameters.

Local smoothing: We use a sliding window of a fixed length for local smoothing to reduce the adversarial perturbation. For an audio sample x_i, we consider the $K - 1$ samples before and after it, denoted by $[x_{i-K+1}, \ldots, x_i, \ldots, x_{i+K-1}]$, as a local reference sequence and replace x_i by the smoothed value (average, median, etc) of its reference sequence.

Down sampling: Based on sampling theory, it is possible to down-sample an band-limited audio file without sacrificing the quality of the recovered signal while mitigating the adversarial perturbations in the reconstruction phase. In our experiments, we down-sample the original 16kHz audio data to 8kHz and then perform signal recovery.

Autoencoder: In adversarial image defending field, the MagNet defensive method (Meng & Chen, 2017) is an effective way to remove adversarial noises: Implement an autoencoder to project the adversarial input distribution space into the benign distribution. In our experiments, we implement a sequence-to-sequence autoencoder, and the whole audio will be cut into frame-level pieces passing through the autoencoder and concatenate them in the final stage, while using the whole audio passing the autoencoder directly is proved to be ineffective and hard to utilize the underlying information.

3.2   TEMPORAL DEPENDENCY BASED METHOD

Due to the fact that audio sequence has explicit temporal dependency (e.g., correlations in consecutive waveform segments), here we aim to explore if such temporal dependency will be affected by adversarial perturbations. The pipeline of the temporal dependency based method is shown in Figure 1. Given an audio sequence, we propose to select the first k portion of it as input for ASR

Figure 1: Pipeline and example of the proposed temporal dependency (TD) based method for discriminating audio adversarial examples.

to obtain transcribed results as S_k. We will also insert the whole sequence into ASR and select the first k portion of the transcribed result as $S_{\{whole,k\}}$, which has the same length as S_k. We will then compare the consistency between S_k and $S_{\{whole,k\}}$ in terms of temporal dependency distance. Here we adopt the word error rate (WER) as the distance metric (Levenshtein, 1966). For normal/benign audio instance, S_k and $S_{\{whole,k\}}$ should be similar since the ASR model is consistent for different sections of a given sequence due to its temporal dependency. However, for audio adversarial examples, since the added perturbation aims to alter the ASR ouput toward the targeted transcription, it may fail to preserve the temporal information of the original sequence. Therefore, due to the loss of temporal dependency, S_k and $S_{\{whole,k\}}$ in this case will not be able to produce consistent results. Based on such hypothesis, we leverage the the first k portion of the transcribed results and the transcribed k portion to potentially recognize adversarial inputs.

4 EXPERIMENTAL RESULTS

In this section, we will first empirically analyze the effects of input transformation on adversarial audio, inspired by defensive methods in image domain. We show that due to different data properties, such input transformation is less effective in defending adversarial audio than images (such as MagNet (Meng & Chen, 2017)). In addition, even when some input transformation is effective for recovering some adversarial audio data, we find that it is easy to perform adaptive attacks against them. We apply the analysis on both audio classification and speech-to-text tasks by considering three state-of-the-art attacks. Then we will introduce how to leverage the temporal dependency of audio data to potentially distinguish adversarial instances, and we also propose different types of strong adaptive attacks against such temporal dependency based detection. We show that these strong adaptive attacks are not able to generate effective adversarial audio facing the temporal dependency based detection.

4.1 DATASET AND EVALUATION METRICS

In our experiments, we measure the effectiveness on several adversarial audio generation methods. For speech-to-text attack, we benchmark each method on both LibriSpeech and Mozilla Common Voice dataset. For audio classification attack, we used Speech Commands dataset. For Commander Song attack (Yuan et al., 2018), we measure on the generated adversarial audios given by the authors.

Dataset LibriSpeech dataset: LibriSpeech (Panayotov et al., 2015) is a corpus of approximately 1000 hours of 16Khz English speech derived from audiobooks from the LibriVox project. We used samples from its test-clean dataset in their website and the average duration is 4.294s. We generated adversarial examples using the attack method in (Carlini & Wagner, 2018).

Mozilla Common Voice dataset: Common Voice is a large audio dataset provided by Mozilla. This dataset is public and contains samples from human speaking audio files. We used the 16Khz-sampled data released in (Carlini & Wagner, 2018), whose average duration is 3.998s. The first 100 samples from its test dataset is used to mount attacks, which is the same attack experimental setup as in (Carlini & Wagner, 2018).

Speech Commands dataset: Speech Commands dataset (Warden, 2018) is a audio dataset contains 65000 audio files. Each audio is just a single command lasting one second. Commands are "yes", "no", "up", "down", "left", "right", "on", "off", "stop", and "go".

Model For speech-to-text task, we use DeepSpeech speech-to-text transcription network, which is a biRNN based model with beam search to decode text. For audio classification task, we use a convolutional speech commands classification model. For the Command Song attack, we evaluate the performance on Kaldi speech recognition platform.

Evaluation Metrics For input transformation, since it aims to recover the ground truth (original instances) from adversarial instances, we use the word error rate (WER) and character error rate (CER) (Levenshtein, 1966) as evaluation metrics to measure the recovery efficiency. WER and CER are commonly used metrics to measure the error between recovered text and the ground truth in word level or character level. Generally speaking, the error rate (ER) is defined by $ER = \frac{S+D+I}{N}$, where S, D, I is the number of substitutions, deletions and insertions calculated by dynamic string alignment, and N is the total number of word / character in the ground truth text.

The proposed TD method is the first data-specific metric to detect adversarial audio, which focuses on how many adversarial instances are captured (true positive) without affecting benign instances (false positive). Therefore, we report the area under curve (AUC) score to evaluate the detection efficiency. For the proposed TD method, we compare the temporal dependency based on WER, CER, as well as the longest common prefix (LCP). LCP is a commonly used metric to evaluate the similarity between two strings. Given strings s_1 and s_2, the corresponding LCP is defined as $max_{s_1[:k]=s_2[:k]} k$, where $[:k]$ represents the first k portion of a sentence.

4.2 INPUT TRANSFORMATION FOR DIFFERENT TASKS

Currently, there are two types of audio attacks: attacking audio classification and attacking speech-to-text tasks. We will first analyze the effect of various input transformations on different attacks.

Autoencoder transformation method for speech-to-text attack Towards defending against (non-adaptive) adversarial images, MagNet (Meng & Chen, 2017) has achieved promising performance by using an antoencoder to mitigate adversarial perturbation. Inspired by it, here we apply a similar autoencoder structure for audio and test if such input transformation can be applied to defending against adversarial audio. We apply a MagNet-like method for feature-extracted audio spectrum map: we build an encoder to compress the information of origin audio features into latent vector z, then use z for reconstruction by passing through another decoder network under frame level and combine them to obtain the transformed audio (Hsu et al., 2017). We implemented our autoencoder based on convolutional networks evaluated by WER and CER, and the results are shown in Tables S1 and S2 in Appendix. We find that MagNet which gained great effectiveness on defending adversarial images in the oblivious attack setting (Carlini & Wagner, 2017c; Lu et al., 2018), has limited effect on audio defense. We report that the autoencoder works fine for transforming benign instances (57.6 WER in Common Voice compared to 27.5 WER without transformation, 30.0 WER in LIBRIS compared to 12.4 WER without transformation), but fails to recover adversarial audio (76.5 WER in Common Voice and 99.4 WER in LIBRIS). This shows that the non-adaptive additive adversarial perturbation can bypass the MagNet-like autoencoder on audio, which implies different robustness implications of image and audio data.

Primitive transformation for speech-to-text attack In addition to autoencoder, here we study the effects of other general primitive transformations on benign and adversarial audio. In speech-to-text attack, we consider the state-of-the-art audio attack proposed in (Carlini & Wagner, 2018). We separately choose 50 audio files from two audio datasets (Common Voice, LIBRIS) and generate attacks based on the CTC-loss. We evaluate several primitive signal processing methods as input transformation. We then also evaluate the WER and CER to quantify the effectiveness of transformation. The results are shown in Tables S1 and S2 in Appendix. We first report the WER and CER for the translated instance using both ground truth and adversarial target "This is an adversarial example" as references. To fairly evaluate the effectiveness of these transformations, we also report the ratio between transformed instance and corresponding target. For instance, as an controlled experiment, given an instance x we calculate the effectiveness ratio for benign instances as $R_{origin} = \frac{D(T(x),\text{ground truth})}{D(\text{benign},\text{ground truth})}$, where $T(\cdot)$ denotes the result of transformation and $D(\cdot, \cdot)$ characterizes the distance function (WER and CER in our case). R_{origin} are shown in the brackets for the first

two columns in Table S1 and S2. For adversarial audio, we calculate the similar effectiveness ratio as $R_{adv} = \frac{D(T(x),\text{ground truth})}{D(\text{adversarial},\text{ground truth})}$, which is shown in the brackets of last two columns within the tables. Here *benign* and *adversarial* referred to the benign or adversarial audio without transformation.

Here small R_{origin} indicates that transformation has little effect on benign instances, small R_{adv} represents transformation is effective recovering adversarial audio back to benign. From Tables S1 and S2 we showed that most of input transformations (e.g., Median-4, Downsampling and Quantization-256) effectively reduce the adversarial perturbation without affecting the original audio too much.

Commander Song Attack We also evaluate our input transformation method against the Commander Song attack (Yuan et al., 2018), which implemented an Air-to-API adversarial attack. In the paper, the authors reported 91% attack detection rate using some defense techniques. We measured our Quant-256 input transformation on 25 adversarial examples obtained via personal communications. Based on the same detection evaluation metric in (Yuan et al., 2018), Quant-256 attains 100% detection rate for characterizing all the adversarial examples. Although these input transformations show certain effectiveness defending against adversarial audios, we show that it is still possible to generate adversarial audios by adaptive attack in Section 4.3.

Attack targeting on audio classification and recognition For audio classification task, we consider the state-of-the-art attack proposed in (Alzantot et al., 2018). Here an audio classification model is attacked and the audio classes include "yes, no, up, down, etc.". They aimed to attack such a network to misclassify an adversarial instance based on either targeted or untargeted attack.

Primitive transformation method for Audio classification attack Here we perform the primitive input transformation for audio classification targeted attacks and evaluate the corresponding effects. (Due to the space limitation, we defer the results of untargeted attacks to the supplemental materials.) We first evaluate our input transformation against the audio classification attack proposed in (Alzantot et al., 2018). We implemented their attack with 500 iterations and limit the magnitude of adversarial perturbation within 5 (smaller than the quantization we used in transformation) and generated 50 adversarial examples per attack task (more targets in Supplementary Material). The attack success rate is 84% on average. For the ease of illustration, we use Quantization-256 as our input transformation. As observed in Figures 2 and 3, the attack success rates decreased to only 2.1%, and 63.8% of the adversarial instances have been converted back to their original (true) label. We also measure the possible effects on original audio due to our transformation methods: the original audio classification accuracy without our transformation is 89.2%, and the rate decreased to 89.0% after our transformation, which means the effects of input transformation on benign instances are negligible. This shows that for classification tasks, such input transformation is more effective mitigating negative effects of adversarial perturbation. This potential reason could be classification tasks do not rely on audio temporal dependency but focuses on local features, while speech-to-text task will be harder to defend based on the tested input transformations.

Figure 2: Attack success rates (%)

Figure 3: Attack success (%) after transformation

4.3 ADAPTIVE ATTACKS AGAINST INPUT TRANSFORMATIONS

Here we apply adaptive attacks against the preceding input transformations and therefore evaluate the robustness of the input transformation as defenses. We implemented our adaptive attack based on three input transformation methods: Quantization, Local smoothing, and Downsampling. For these transformation, we leverage a gradient-masking aware approach to generate adaptive attacks.

Table 1: The $dB_x(\delta)$ evaluation of adaptive attack

Dataset	Non-adaptive	Downsample	Quantization-256	Median-4	Average-4
LIBRIS	-36.06	-21.42	-11.02	-23.58	-25.64
CommmonVoice	-35.65	-20.91	-9.48	-23.42	-25.12

In the optimization based attack (Carlini & Wagner, 2018), the attack achieved by solving the optimization problem: $\min_\delta \|\delta\|_2^2 + c \cdot l(x + \delta, t)$, where δ is referred as the perturbation, x the benign audio, t the target phrase, and $l(\cdot)$ the CTC-loss. Parameter c is iterated to trade off the importance of being adversarial and remaining close to the original instance.

For quantization transformation, we assume the adversary knows the quantization parameter q. We then change our attack targeted optimization function to: $\min_\delta \|q\delta\|_2^2 + c \cdot l(x + q\delta, t)$. After that, all the adversarial audios can be resistant against quantization transformations and it only increased a small magnitude of adversarial perturbation, which can be ignored by human ears. When q is large enough, the distortion would increase but the transformation process is also ineffective due to too much information loss.

For downsampling transformation, the adaptive attack is conducted by performing the attack on the sampled elements of origin audio sequence. Since the whole process is differentiable, we can do adaptive attack through gradient directly and all the adversarial audios are able to attack.

For local smoothing transformation, it is also differentiable in case of average smoothing transformation, so we can pass the gradient effectively. To attack against median smoothing transformation, we can just convert the gradient back to the median and update its value, which is similar to the max-pooling layer's back propagation process. By implementing the adaptive attack, all the smoothing transformation is shown to be ineffective.

We chose our samples randomly from LIBRIS and Common Voice audio dataset with 50 audio samples each. We implemented our adaptive attack on the samples and passed them through the corresponding input transformation. We use down-sampling from 16kHZ to 8kHZ, median / average smoothing with one-sided sequence length $K = 4$, quantization method with $q = 256$ as our input transformation methods. In (Carlini & Wagner, 2018), Decibels (a logarithmic scale that measures the relative loudness of an audio sample) is applied as the measurement of magnitude of perturbation: $dB(x) = \max_i 20 \cdot \log_{10}(x_i)$, which x referred as adversarial audio sampled sequence. The relative perturbation is calculated as $dB_x(\delta) = dB(\delta) - dB(x)$, where δ is the crafted adversarial noise.

We measured our adaptive attack based on the same criterion. We show that all the adaptive attacks become effective with reasonable perturbation, as shown in Table 1. As suggested in (Carlini & Wagner, 2018), almost all the adversarial audios have distortion $dB_x(\delta)$ from -15dB to -45dB which is tolerable to human ears. From Table 1, the added perturbation are mostly within this range.

4.4 TEMPORAL DEPENDENCY BASED METHOD

Here we show the empirical performance of distinguishing adversarial audios by leveraging the temporal dependency of audio dataset. In the experiments, we use these three metrics, WER, CER and LCP, to measure the inconsistency between S_k and $S_{\{whole, k\}}$. As a baseline, we also directly train a one layer LSTM with 64 hidden feature dimension based on the collected adversarial and benign audio instances for classification. Some examples of translated results for benign and adversarial audios are shown in Table 2. Here we consider three types of adversarial targets: short – *hey google*; medium – *this is an adversarial example*; and long – *hey google please cancel my medical appointment*. We report the AUC score for these detection results for $k = 1/2$ in Table 3.

Table 2: Examples of the temporal dependency based detection method

Type	Transcribed results
Original	then good bye said the rats and they went home
the first half of Original	then good bye said the raps
Adversarial (short)	hey google
First half of Adversarial	he is
Adversarial (medium)	this is an adversarial example
First half of Adversarial	thes on adequate
Adversarial (long)	hey google please cancel my medical appointment
First half of Adversarial	he goes cancer

Table 3: AUC results of the proposed temporal dependency method

Dataset	LSTM	TD (WER)	TD (CER)	TD (LCP ratio)
Common Voice	0.712	**0.936**	0.916	0.859
LIBRIS	0.645	0.930	**0.933**	0.806

Table 4: AUC of detecting Combination Attack based on TD method

Combination Attack	Detection Parameter k_D	TD metrics		
		WER	CER	LCP
$k_A = \{\frac{1}{2}\}$	1/2	0.607	0.518	0.643
	2/3	0.957	0.965	0.881
	Rand(0.2, 0.8)	0.889	0.882	0.776
$k_A = \{\frac{1}{2}, \frac{2}{3}, \frac{3}{4}\}$	1/2	0.665	0.682	0.604
	2/3	0.653	0.664	0.564
	3/4	0.633	0.653	0.601
	Rand(0.2, 0.8)	0.785	0.832	0.642

We can see that by using WER as the detection metric, the temporal dependency based method can achieve AUC as high as 0.936 on Common Voice and 0.93 on LIBRIS. We also explore different values of k and we observe that the results do not vary too much (detailed results can be found in Table S6 in Appendix). When $k = 4/5$, the AUC score based on CER can reach 0.969, which shows that such temporal dependency based method is indeed promising in terms of distinguishing adversarial instances. Interestingly, these results suggest that the temporal dependency based method would suggest an easy-implemented but effective method for characterizing adversarial audio attacks.

4.5 ADAPTIVE ATTACKS AGAINST TEMPORAL DEPENDENCY BASED METHOD

To thoroughly evaluate the robustness of temporal dependency based method, we also perform strong adaptive attack against it. Notably, even if the adversary knows k, the adaptive attack is hard to conduct due to the fact that this process is non-differentiable. Therefore, we propose three types of strong adaptive attacks here aiming to explore the robustness of the temporal based method.

Segment attack: Given the knowledge of k, we first split the audio into two parts: the first k-portion audio S_k and the rest S_{k-}. We then apply similar attack to add perturbation to only S_k. We hope this audio can be attacked successfully without changing S_{k-} since the second part would not receive gradient updates. Therefore, when performing the temporal based consistency check, $T(S_k)$ would be translated consistently with $T(S_{\{whole,k\}})$.

Concatenation attack: To maximally leverage the information of k, here we propose two ways to attack both S_k and S_{k-} individually, and then concatenate them together.

1. the target of S_k is the first $k-$portion of adversarial target, and S_{k-} is attacked to the rest.

2. the target of S_k is the whole adversarial target, while we attack S_{k-} to be silence, which means S_{k-} transcribing nothing. This is different from segment attack where S_{k-} is not modified at all.

Combination attack: To balance attack success rate for both sections and the whole sentence against TD, we apply the attack objective function as $\min_\delta \|\delta\|_2^2 + c \cdot (l(x + \delta, t) + l((x + \delta)_k, t_k))$, where x refers to the whole sentence.

For segment attack, we found that in most cases the attack cannot succeed, that attack success rate remains as 2% for 50 samples in both LIBRIS and Common Voice dataset, and some of the examples are shown in Appendix. We conjecture the reasons as: 1. S_k alone is not enough to be attacked to the adversarial target due to the temporal dependency; 2. the speech recognition results on S_{k-} cannot be applied to the whole recognition process and therefore break the recognition process for S_k.

For concatenation attack, we also found that the attack itself fails. That is, the transcribed result of $adv(S_k)+adv(S_{k-})$ differs from the translation result of S_k+S_{k-}. Some examples are shown in Appendix. The failure of the concatenation adaptive attack more explicitly shows that the temporal dependency plays an important role in audio. Even if the separate parts are successfully attacked into the target, the concatenated instance will again totally break the perturbation and therefore render the adaptive attack inefficient. On the contrary, such concatenation will have negligible effects on benign audio instances, which provides a promising direction to detect adversarial audio.

For combination attack, we vary the section portion k_D used by TD and evaluate the cases where the adaptive attacker uses the same/different section k_A. We define Rand(a,b) as uniformly sampling from [a,b]. We consider stronger attacker, for whom the k_A can be a set containing random sections. The detection results for different settings are shown in Table 4. From the results we can see that when $|k_A| = 1$, if the attacker uses the same k_A as k_D to perform adaptive attack, the attack can achieve relative good performance and if attacker uses different k_A, the attack will fail with AUC above 85%. We also evaluate the case that defender randomly sample k_D during the detection and find that it's very hard for adaptive attacker to perform attacks, which can improve model robustness in practice. For $|k_A| > 1$, the attacker can achieve some attack success when the set contains k_D. But when $|k_A|$ increases, the attacker's performance becomes worse. The complete results are given in Appendix. Notably, the random sample based TD appears to be robust in all cases.

5 CONCLUSION

This papers proposes to exploit the temporal dependency property in audio data to characterize audio adversarial examples. Our experimental results show that while four primitive input transformations on audio fail to withstand adaptive adversarial attacks, temporal dependency is shown to be resistant to these attacks. We also demonstrate the power of temporal dependency for characterizing adversarial examples generated by three state-of-the-art audio adversarial attacks. The proposed method is easy to operate and does not require model retraining. We believe our results shed new lights in exploiting unique data properties toward adversarial robustness.

REFERENCES

Moustafa Alzantot, Bharathan Balaji, and Mani Srivastava. Did you hear that? adversarial examples against automatic speech recognition. *arXiv preprint arXiv:1801.00554*, 2018.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *arXiv preprint arXiv:1802.00420*, 2018.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy, 2017*, 2017a.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *ACM Workshop on Artificial Intelligence and Security*, pp. 3–14, 2017b.

Nicholas Carlini and David Wagner. Magnet and" efficient defenses against adversarial attacks" are not robust to adversarial examples. *arXiv preprint arXiv:1711.08478*, 2017c.

Nicholas Carlini and David Wagner. Audio adversarial examples: Targeted attacks on speech-to-text. *arXiv preprint arXiv:1801.01944*, 2018.

Hongge Chen, Huan Zhang, Pin-Yu Chen, Jinfeng Yi, and Cho-Jui Hsieh. Show-and-fool: Crafting adversarial examples for neural image captioning. *arXiv preprint arXiv:1712.02051*, 2017a.

Pin-Yu Chen, Yash Sharma, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. Ead: elastic-net attacks to deep neural networks via adversarial examples. *arXiv preprint arXiv:1709.04114*, 2017b.

Moustapha Cisse, Yossi Adi, Natalia Neverova, and Joseph Keshet. Houdini: Fooling deep structured prediction models. *arXiv preprint arXiv:1707.05373*, 2017.

Gintare Karolina Dziugaite, Zoubin Ghahramani, and Daniel M Roy. A study of the effect of jpg compression on adversarial images. *arXiv preprint arXiv:1608.00853*, 2016.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

RD Graetz, Roger P Pech, MR Gentle, and JF O'Callaghan. The application of landsat image data to rangeland assessment and monitoring: the development and demonstration of a land image-based resource information system (libris). *Rangeland Journal*, 1986.

Chuan Guo, Mayank Rana, Moustapha Cissé, and Laurens van der Maaten. Countering adversarial images using input transformations. *arXiv preprint arXiv:1711.00117*, 2017.

Warren He, James Wei, Xinyun Chen, Nicholas Carlini, and Dawn Song. Adversarial example defenses: Ensembles of weak defenses are not strong. *arXiv preprint arXiv:1706.04701*, 2017.

Geoffrey Hinton, Li Deng, Dong Yu, George E Dahl, Abdel-rahman Mohamed, Navdeep Jaitly, Andrew Senior, Vincent Vanhoucke, Patrick Nguyen, Tara N Sainath, et al. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 29(6):82–97, 2012.

Wei Ning Hsu, Yu Zhang, and James Glass. Unsupervised domain adaptation for robust speech recognition via variational autoencoder-based data augmentation. *arXiv preprint arXiv:1707.06265*, 2017.

Dan Iter, Jade Huang, and Mike Jermann. Generating adversarial examples for speech recognition. *Techcical Report*, 2017.

Felix Kreuk, Yossi Adi, Moustapha Cisse, and Joseph Keshet. Fooling end-to-end speaker verification by adversarial examples. *arXiv preprint arXiv:1801.03339*, 2018.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet classification with deep convolutional neural networks. In *NIPS*, pp. 1097–1105, 2012.

V. I Levenshtein. Binary codes capable of correcting deletions, insertions and reversals. *Soviet Physics Doklady*, 10(1):845ndash;848, 1966.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *JMLR*, 17(39):1–40, 2016.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. In *ICLR*, 2017.

David G Lowe. Object recognition from local scale-invariant features. In *Computer vision, 1999. The proceedings of the seventh IEEE international conference on*, volume 2, pp. 1150–1157. Ieee, 1999.

Pei-Hsuan Lu, Pin-Yu Chen, Kang-Cheng Chen, and Chia-Mu Yu. On the limitation of MagNet defense against L_1-based adversarial examples. *arXiv preprint arXiv:1805.00310*, 2018.

Yan Luo, Xavier Boix, Gemma Roig, Tomaso Poggio, and Qi Zhao. Foveation-based mechanisms alleviate adversarial examples. *arXiv preprint arXiv:1511.06292*, 2015.

Dongyu Meng and Hao Chen. Magnet: a two-pronged defense against adversarial examples. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, pp. 135–147. ACM, 2017.

Daniel Michelsanti and Zheng-Hua Tan. Conditional generative adversarial networks for speech enhancement and noise-robust speaker verification. *arXiv preprint arXiv:1709.01703*, 2017.

V. Panayotov, G. Chen, D. Povey, and S. Khudanpur. Librispeech: An asr corpus based on public domain audio books. In *2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5206–5210, 2015.

Dmitriy Serdyuk, Kartik Audhkhasi, Philémon Brakel, Bhuvana Ramabhadran, Samuel Thomas, and Yoshua Bengio. Invariant representations for noisy speech recognition. *arXiv preprint arXiv:1612.01928*, 2016.

Anuroop Sriram, Heewoo Jun, Yashesh Gaur, and Sanjeev Satheesh. Robust speech recognition using generative adversarial networks. *arXiv preprint arXiv:1711.01567*, 2017.

Dong Su, Huan Zhang, Hongge Chen, Jinfeng Yi, Pin-Yu Chen, and Yupeng Gao. Is robustness the cost of accuracy?–a comprehensive study on the robustness of 18 deep image classification models. *arXiv preprint arXiv:1808.01688*, 2018.

Sining Sun, Ching-Feng Yeh, Mari Ostendorf, Mei-Yuh Hwang, and Lei Xie. Data augmentation with adversarial examples for robust speech recognition. *ResearchGate*, 2018.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Qinglong Wang, Wenbo Guo, II Ororbia, G Alexander, Xinyu Xing, Lin Lin, C Lee Giles, Xue Liu, Peng Liu, and Gang Xiong. Using non-invertible data transformations to build adversarial-robust neural networks. *arXiv preprint arXiv:1610.01934*, 2016.

Pete Warden. Speech commands: A dataset for limited-vocabulary speech recognition. *arXiv preprint arXiv:1804.03209*, 2018.

Weilin Xu, David Evans, and Yanjun Qi. Feature squeezing: Detecting adversarial examples in deep neural networks. *arXiv preprint arXiv:1704.01155*, 2017.

Xuejing Yuan, Yuxuan Chen, Yue Zhao, Yunhui Long, Xiaokang Liu, Kai Chen, Shengzhi Zhang, Heqing Huang, Xiaofeng Wang, and Carl A Gunter. Commandersong: A systematic approach for practical adversarial voice recognition. *arXiv preprint arXiv:1801.08535*, 2018.

APPENDIX

5.1 RESULTS ON "AUTOENCODER TRANSFORMATION METHOD FOR SPEECH-TO-TEXT ATTACK" AND "PRIMITIVE TRANSFORMATION FOR SPEECH-TO-TEXT ATTACK"

Table S1: Evaluation on Common Voice with language model

Transformation Methods	OriginWER(%)	OriginCER(%)	AdvWER(%)	AdvCER(%)
Without transformations	27.5	14.3	95.9	80.1
Autoencoder	57.6 (2.09)	34.1 (2.38)	76.5 (0.80)	49.8 (0.62)
Median-4	27.0 (0.98)	14.6 (1.02)	73.6 (0.77)	42.4 (0.53)
Downsample	31.2 (1.13)	17.6 (1.23)	69.6 (0.73)	41.2 (0.51)
Quant-128	34.4 (1.25)	21.3 (1.49)	75.9 (0.79)	45.3 (0.57)
Quant-256	42.9 (1.56)	26.7 (1.87)	70.7 (0.74)	41.8 (0.52)
Quant-512	52.4 (1.90)	37.1 (2.59)	68.5 (0.71)	45.0 (0.56)
Quant-1024	62.4 (2.27)	47.2 (3.3)	70 (0.73)	51.2 (0.64)

Table S2: Evaluation on LIBRIS with language model

Transformation Methods	OriginWER(%)	OriginCER(%)	AdvWER(%)	AdvCER(%)
Without transformations	3.05	1.46	102.8	86.5
Autoencoder	30.0 (9.84)	15.1 (10.34)	99.4 (0.97)	58.1 (0.67)
Median-4	3.6 (1.18)	1.7 (1.16)	35.1 (0.34)	19.0 (0.22)
Downsample	11.8 (3.87)	5.7 (3.90)	41.2 (0.40)	21.8 (0.25)
Quant-128	3.2 (1.04)	1.5 (1.03)	49.7 (0.48)	28.2 (0.33)
Quant-256	**3.5 (1.13)**	**1.7 (1.16)**	**29.1 (0.28)**	**15.4 (0.18)**
Quant-512	12.0 (3.93)	6.6 (4.52)	25.1 (0.24)	13.3 (0.15)
Quant-1024	30.7 (10.06)	20.3 (13.90)	36.6 (0.36)	24.1 (0.28)

Table S3: Evaluation on Common Voice without passing through language model

Transformation Methods	OriginWER(%)	OriginCER(%)	AdvWER(%)	AdvCER(%)
Without transformations	37.7	18.5	95.8	83.0
Median-4	43.4 (1.15)	20.4 (1.10)	83.0 (0.87)	46.5 (0.56)
Down sampling	47.2 (1.25)	23.3 (1.26)	77.6 (0.81)	43.9 (0.53)
Quantization-128	47.3 (1.25)	25.7 (1.39)	80.7 (0.84)	49.0 (0.59)
Quantization-256	52.5 (1.39)	29.2 (1.58)	73.4 (0.77)	43.6 (0.53)
Quantization-512	64.1 (1.70)	37.5 (2.03)	73.7 (0.77)	44.2 (0.53)
Quantization-1024	72.1 (1.91)	50.4 (2.72)	76.9 (0.80)	53.0 (0.64)

Table S4: Evaluation on LIBRIS without passing through language model

Transformation Methods	OriginWER(%)	OriginCER(%)	AdvWER(%)	AdvCER(%)
Without transformations	12.4	7.05	105.3	91.7
Median-4	16.4 (1.32)	8.0 (1.13)	57.9 (0.55)	27.5 (0.30)
Downsample	24.2 (1.95)	13.0 (1.84)	60.9 (0.58)	31.2 (0.34)
Quantization-128	13.4 (1.08)	7.6 (1.08)	66.1 (0.63)	37.1 (0.40)
Quantization-256	**16.3 (1.31)**	**8.9 (1.26)**	**48.6 (0.46)**	**24.0 (0.26)**
Quantization-512	27.5 (2.21)	13.8 (1.96)	47.0 (0.45)	23.0 (0.25)
Quantization-1024	46.8 (3.77)	25.4 (3.60)	52.3 (0.50)	30.0 (0.33)

5.2 MORE RESULTS ON PRIMITIVE TRANSFORMATION METHOD FOR AUDIO CLASSIFICATION ATTACK

Figure S1: Successful attack rates

Figure S2: Unchanged label rates

Figure S3: Successful attack rates after transformation Figure S4: Unchanged label rates after transformation

5.3 MORE RESULTS ON ADAPTIVE ATTACKS AGAINST TEMPORAL DEPENDENCY BASED METHOD

Table S5: Examples of Segment Attack and Concatenation attack

Type	Transcribed results
Original	and he leaned against the wa lost in reveriey
the first half of Original	and he leaned against the wa
Adaptive attack target	this is an adversarial example
Adaptive attack result	this is an adversarial losin ver
the first half of Adv.	this is a agamsa
Adaptive attack target	okay google please cancel my medical appointment
Adaptive attack result	okay google please cancel my medcalosinver
the first half of Adv.	okay go please
Original	why one morning there came a quantity of people and set to work in the loft
Attack target	this is an adversarial example
S_k	this is an
S_{k-}	adversarial example
S_k+S_{k-}	this is a quantity of people and set to work in a lift
S_k	this is an adversarial example
S_{k-}	sil
S_k+S_{k-}	this is an adernari eanquatete of pepl and sat to work in the loft

Table S6: AUC scores of different k

k	WER	CER	LCP
1/2	0.930	0.933	0.806
2/3	0.930	0.948	0.826
3/4	0.933	0.938	0.839
4/5	0.955	**0.969**	0.880
5/6	0.941	0.962	0.858

Table S7: AUC of detecting Combination Attack based on TD method

Combination Attack	Detection Parameter k_D	TD metrics		
		WER	CER	LCP
$k_A = \{\frac{1}{2}\}$	1/2	0.607	0.518	0.643
	2/3	0.957	0.965	0.881
	3/4	0.943	0.951	0.875
	Rand(0.2, 0.8)	0.889	0.882	0.776
$k_A = \{\frac{2}{3}\}$	1/2	0.932	0.912	0.860
	2/3	0.611	0.543	0.604
	3/4	0.956	0.944	0.872
	Rand(0.2, 0.8)	0.879	0.890	0.762
$k_A = \{\frac{1}{2}, \frac{2}{3}\}$	1/2	0.633	0.690	0.552
	2/3	0.536	0.615	0.524
	3/4	0.942	0.974	0.934
	Rand(0.2, 0.8)	0.801	0.880	0.664
$k_A = \{\frac{1}{2}, \frac{2}{3}, \frac{3}{4}\}$	1/2	0.665	0.682	0.604
	2/3	0.653	0.664	0.564
	3/4	0.633	0.653	0.601
	Rand(0.2, 0.8)	0.785	0.832	0.642
$k_A = \{\frac{1}{2}, \frac{2}{3}, \frac{3}{4}, \frac{4}{5}\}$	1/2	0.701	0.712	0.615
	2/3	0.684	0.701	0.583
	3/4	0.681	0.693	0.613
	Rand(0.2, 0.8)	0.742	0.811	0.623
$k_A = \{\frac{1}{2}, \frac{2}{3}, \frac{3}{4}, \frac{4}{5}, \frac{5}{6}\}$	1/2	0.736	0.784	0.601
	2/3	0.723	0.763	0.612
	3/4	0.715	0.755	0.584
	Rand(0.2, 0.8)	0.734	0.801	0.620