Responses to Reviewers

on Paper *Beyond Classical Diffusion: Ballistic Graph Neural Network*

Referee #3 and #2:

More experiments to demonstrate the power of ballistic comparing to classical ones.
Classification on different DATASETs(accuracy %)

Name of dataset	Classical Diffusion based ([1])	Classical Diffusion based ([2])	Ballistic (this paper)
CIFAR-10	93.65	93.49	***94.73***
CIFAR-100	60.30	59.51	***61.24***
STL-10	55.28	58.87	***63.32***

[1] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[2] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *Advances in neural information processing systems*, pp. 3844–3852, 2016.

Referee #1:

If the contribution is only a new kind of random walk on a graph, is ICLR the good targeted venue ?

Response: Answer: Yes, random walk on graph is a very important problem. In GCN, random walk is the way you collect the information. The traditional pipeline is show attached.

The Feature Extraction lies as the __cornerstone__ of the GCN problem:
For almost all previous papers, the methods used are based on a random walk (Laplacian matrix), resulting in the over-smooth problem as **Referee #3** *mentioned. The method we propose in this paper is inspired by quantum diffusion and is completely different from the previous one. Our method also achieves better performance.*

Referee #1 and #2:

- The proposed algorithm is not clear.

Response: In light of the reviewer's recommendation, we now present the algorithm in one-dimensional condition for better understanding and ballistic concept.

- **The ballistic concept is not introduced at all in section 4. Referee #1**

   Response: The **ballistic** concept is taken from Condensed Matter physics.(please see the introduction in this link http://asdn.net/asdn/electronics/transport.php).
   For Electron Transport in Semiconductors. There are three types of transportation behaviour: Diffusive, quasi- Ballistic and Ballistic. Please see the attached figure. The 'Ballistic' means transportation is exponentially accelerated.

- **The proposed algorithm.**
   Response: Here we demonstrate the algorithm in one-dimensional case, this algorithm is also called quantum walk, for one-dimensional case, please see here: Section

   Discrete Time Quantum Walks https://en.wikipedia.org/wiki/Quantum_walk
   There are two operators, a "coin flip" operator and a conditional shift operator, which are applied repeatedly.
   1. First, the distribution on one-dimensional line (9 nodes: $x = -4 \, to \, 4$) is:

$$\{0,0,0,0,1,0,0,0,0\}$$

The state on the middle node (x=0) is $\frac{1}{\sqrt{2}}$ ($|left\rangle + i\,|right\rangle$). The left state means go left and the right state means go right, the state is in the coin Hilbert space. $|left\rangle$ corresponds to $\binom{1}{0}$ and $|left\rangle$ corresponds to $\binom{0}{1}$.

2. ***(Coin space operation)*** Then we apply the coin operator, in one-dimensional case the coin operator is the Hadamard Gate. $H = \frac{1}{\sqrt{2}}\begin{pmatrix}1 & 1 \\ 1 & -1\end{pmatrix}$, apply coin operator on the state

$H\frac{1}{\sqrt{2}}$ ($|left\rangle + i\,|right\rangle$) $= \frac{1}{\sqrt{2}} H\binom{1}{i} = \frac{1}{2}\binom{1+i}{1-i} = \frac{1}{2}$ ($(1+i)|left\rangle + \frac{1}{2}$ $(1-i)|right\rangle$

(Spatial space operation) Now the line is $\{0,0,0,0,1,0,0,0,0\}$ with a state $\frac{1}{2}$ $(1+i)|left\rangle + \frac{1}{2}$ $(1-i)|right\rangle$ on $x = 0$. For every node, move the $|left\rangle$ ==state amplitude== to left node and $|right\rangle$ to right node.

Now the line is $\{0,0,0,\frac{1}{2}$ $(1+i), 0, \frac{1}{2}$ $(1-i), 0,0,0\}$, with pure state $|left\rangle$ on $x = -1$ and pure state $|right\rangle$ on $x = 1$.

The probability is the norm (multiply the conjugate complex number) of the ==state amplitude==: the distribution on a line becomes:

$$\{0,0,0,\tfrac{1}{2}\ 0, \tfrac{1}{2}, 0,0,0\}$$

with pure state $|left\rangle$ on $x = -1$ and pure state $|right\rangle$ on $x = 1$.

3. ***Coin space operation:*** the amplitude distribution on a line last moment: $\{0,0,0,\frac{1}{2}$ $(1+i), 0, \frac{1}{2}$ $(1-i), 0,0,0\}$

Using coin operator :$H\frac{(1+i)}{2}\binom{1}{0} = \frac{1+i}{2\sqrt{2}}\binom{1}{1}$ on $x = -1$ and $H\frac{(1-i)}{2}\binom{0}{1} = \frac{1-i}{2\sqrt{2}}\binom{1}{-1}$. For $x = -1$, $\frac{1+i}{2\sqrt{2}}\binom{1}{1} = \frac{1+i}{2\sqrt{2}}|left\rangle + \frac{1+i}{2\sqrt{2}}|right\rangle$, moves the $|left\rangle$ ==state amplitude== to left node and $|right\rangle$ to right node. Same as For $x = 1$.

(Spatial space operation) the amplitude on the line becomes

$$\{0,0,\tfrac{1+i}{2\sqrt{2}}|left\rangle, 0, \tfrac{1+i}{2\sqrt{2}}|left\rangle + \tfrac{1-i}{2\sqrt{2}}|right\rangle, 0, \tfrac{1-i}{2\sqrt{2}}|right\rangle, 0,0,0\} =$$
$$\{0,0,\tfrac{1+i}{2\sqrt{2}}, 0, \tfrac{1}{\sqrt{2}}, 0, \tfrac{1-i}{2\sqrt{2}}, 0,0,0\}$$

With $|left\rangle$ at $x = -2, \frac{1}{2}\big((1+i)|left\rangle + (1-i)|right\rangle\big)$ at $x = 0$ and $|right\rangle$ at $x = 2$.

The probability is the norm (multiply the conjugate complex number)
$$\{0,0,\tfrac{1}{4}, 0, \tfrac{1}{2}, 0, \tfrac{1}{4}, 0,0\}$$

Repeat the two operation again and again.

Here we plot ***Probability*** (not amplitude) evolution on a line with 21 nodes.

Referee #3 the over smooth problem:

The smooth problem means after apply traditional Laplacian-based matrix on a manifold; the distribution will become more and more **'flat'** on the spatial domain, as shown in the figure below:

small steps

large steps

The nodes within this region are indistinguishable
Because of the flat distribution result from the classical diffusion

But the ballistic diffusion avoids this problem, see the attached figure:

The nodes within this region are distinguishable
Because the ballistic distribution

Spatial Domain