LEARNING TO ACTIVELY LEARN: A ROBUST APPROACH

ABSTRACT

This work proposes a procedure for designing algorithms for specific adaptive data collection tasks like active learning and pure-exploration multi-armed bandits. Unlike the design of traditional adaptive algorithms that rely on concentration of measure and careful analysis to justify the correctness and sample complexity of the procedure, our adaptive algorithm is learned via adversarial training over equivalence classes of problems derived from information theoretic lower bounds. In particular, a single adaptive learning algorithm is learned that competes with the best adaptive algorithm learned for each equivalence class. Our procedure takes as input just the available queries, set of hypotheses, loss function, and total query budget. This is in contrast to existing meta-learning work that learns an adaptive algorithm relative to an explicit, user-defined subset or prior distribution over problems which can be challenging to define and be mismatched to the instance encountered at test time. This work is particularly focused on the regime when the total query budget is very small, such as a few dozen, which is much smaller than those budgets typically considered by theoretically derived algorithms. We perform synthetic experiments to justify the stability and effectiveness of the training procedure, and then evaluate the method on tasks derived from real data including a noisy 20 Questions game and a joke recommendation task.

1 INTRODUCTION

Closed-loop learning algorithms use previous observations to inform what measurements to take next in a closed-loop in order to accomplish inference tasks far faster than any fixed measurement plan set in advance. For example, active learning algorithms for binary classification have been proposed that under favorable conditions require exponentially fewer labels than passive, random sampling to identify the optimal classifier (Hanneke et al., 2014). And in the multi-armed bandits literature, adaptive sampling techniques have demonstrated the ability to identify the "best arm" that optimizes some metric with far fewer experiments than a fixed design (Garivier & Kaufmann, 2016; Fiez et al., 2019). Unfortunately, such guarantees often either require simplifying assumptions that limit robustness and applicability, or appeal to concentration inequalities that are very loose unless the number of samples is very large (e.g., web-scale).

The aim of this work is a framework that achieves the best of both worlds: algorithms that learn through simulated experience to be as effective as possible with a tiny measurement budget (e.g., 20 queries), while remaining robust due to adversarial training. Our work fits into a recent trend sometimes referred to as *learning to actively learn* (Konyushkova et al., 2017; Bachman et al., 2017; Fang et al., 2017; Boutilier et al., 2020; Kveton et al., 2020) which tunes existing algorithms or learns entirely new active learning algorithms by policy optimization. Previous works in this area learn a policy by optimizing with respect to data observed through prior experience (e.g., meta-learning or transfer learning) or an assumed explicit prior distribution of problem parameters (e.g. the true weight vector for linear regression). In contrast, our approach makes no assumptions about what parameters are likely to be encountered at test time, and therefore produces algorithms that do not suffer from a potential mismatch of priors. Instead, our method learns a policy that attempts to mirror the guarantees of frequentist algorithms with *instance dependent sample complexities*: if the problem is hard you will suffer a large loss, if it is easy you will suffer little.

The learning framework is general enough to be applied to many active learning settings of interest and is intended to be used to produce novel and robust high performing algorithms. It is directly inspired by how one theoretically justifies an instance dependent sample complexity of a given algorithm using information theoretic lower bounds machinery. The difference is that instead of hand-crafting hard instances that witness the difficulty of the problem, we use adversarial training inspired by the robust reinforcement learning literature to automatically train minimax policies. Embracing the use of a simulator allows our learned policies to be very aggressive while maintaining robustness. Indeed, this work is particularly useful in the setting where relatively few rounds of querying can be made, where concentration inequalities of existing algorithms are vacuous. To demonstrate the efficacy of our approach we implement the framework for the (transductive) linear bandit problem. This paradigm includes pure-exploration combinatorial bandits (e.g., shortest path, matchings) as a special case which itself reduces to active binary classification. We empirically validate our framework on a simple synthetic experiment before turning our attention to datasets derived from real data including a noisy 20 questions game and a joke recommendation task.

2 Proposed Framework for Robust Learning to Actively Learn

Whether learned or defined by an expert, any algorithm for active learning can be thought of as a policy from the perspective of reinforcement learning. At time t, based on an internal state s_t, the policy takes action x_t and receives observation y_t, which then updates the state and the process repeats. In our work, at time t the state $s_t \in \mathcal{S}$ is a function of the history $\{(x_i, y_i)\}_{i=1}^{t-1}$ such as its sufficient statistics. Without loss of generality, a policy takes a state as input and defines a probability distribution over $\mathcal{X}$ so that at time t we have $x_t \sim \pi(s_t)$. Fix a horizon T. For $t = 1, 2, \ldots, T$

- state $s_t \in \mathcal{S}$ is a function of the history, $\{(x_i, y_i)\}_{i=1}^{t-1}$,
- action $x_t \in \mathcal{X}$ is drawn at random from the distribution $\pi(s_t)$ defined over $\mathcal{X}$, and
- next state $s_{t+1} \in \mathcal{S}$ is constructed by taking action x_t in state s_t and observing $y_t \sim f(\cdot|\theta_*, s_t, x_t)$

until the game terminates at time $t = T$ and the policy receives loss L_T. Note that L_T is a random variable that depends on the tuple $(\pi, \{(x_i, y_i)\}_{i=1}^T, \theta_*)$. We assume that f is a distribution of known parameteric form to the policy (e.g., $f(\cdot|\theta, s, x) \equiv \mathcal{N}(\langle x, \theta \rangle, 1)$) but the parameter θ is unknown to the policy. Let $\mathbb{P}_{\pi,\theta}, \mathbb{E}_{\pi,\theta}$ denote the probability and expectation under the probability law induced by executing policy π in the game with $\theta_* = \theta$ to completion. Note that $\mathbb{P}_{\pi,\theta}$ includes any internal randomness of the policy π and the random observations $y_t \sim f(\cdot|\theta, s_t, x_t)$. Thus, $\mathbb{P}_{\pi,\theta}$ assigns a probability to any trajectory $\{(x_i, y_i)\}_{i=1}^T$. For a given policy π and $\theta_* = \theta$, the metric of interest we wish to minimize is the expected loss $\ell(\pi, \theta) := \mathbb{E}_{\pi,\theta}[L_T]$ where L_T as defined above is the loss observed at the end of the episode. For a fixed policy π, $\ell(\pi, \theta)$ defines a loss surface over all possible values of θ. This loss surface captures the fact that some values of θ are just intrinsically harder than others, but also that a policy may be better suited for some values of θ versus others.

Example: In active binary classification, T is a label budget, $\mathcal{X}$ could be a set of images such that we can query the label of example image $x_t \in \mathcal{X}$, $y_t \in \{-1, 1\}$ is the requested binary label, and the loss L_T is the classification error of a trained classifier on these collected labels. Finally, $\theta_x = p(y = 1|x)$ for all $x \in \mathcal{X}$. More examples can be found in Appendix A.

2.1 Instance dependent performance metric

We now define the sense in which we wish to evaluate a particular policy. For any fixed value of θ one could clearly design an algorithm that would maximize performance on θ, but then it might have very poor performance on some other value $\theta' \neq \theta$. Thus, we would ideally like π to perform uniformly well over a set of θ's that are all equivalent in a certain sense. Define a positive function $\mathcal{C} : \Theta \to (0, \infty)$ that assigns a score to each $\theta \in \Theta$ that intuitively captures the "difficulty" of a particular θ, and can be used as a partial ordering of Θ. Ideally, $\mathcal{C}(\theta)$ is a monotonic transformation of $\ell(\widetilde{\pi}, \theta)$ for some "best" policy $\widetilde{\pi}$ that we will define shortly. For any $r \in \mathbb{R}$ define

$$J(\pi, r) := \sup_{\theta : \mathcal{C}(\theta) \leq r} \ell(\pi, \theta).$$

The quantity $J(\pi, r) - \inf_{\pi'} J(\pi', r)$ is a function of r that describes the sub-optimality gap of a given policy π relative to an r-dependent baseline policy trained specifically for each r.

For a fixed $r_k > 0$, a policy π that aims to minimize just $J(\pi, r_k)$ might focus just on the hard instances (i.e., those with $\mathcal{C}(\theta)$ close to r_k) and there may exist a different policy π' that performs far better than π on easier instances (i.e., those with $\mathcal{C}(\theta) \ll r_k$). To avoid this, assuming $\sup_t J(\pi, r) - \inf_{\pi'} J(\pi', r) < \infty$, we define

$$\pi_* := \arg \inf_\pi \sup_{r>0} J(\pi, r) - \inf_{\pi'} J(\pi', r) \qquad (1)$$

as the policy that minimizes the worst case sub-optimality gap over all $r > 0$. Figure 1 illustrates these definitions. Instead of computing $\inf_{\pi'} J(\pi', r)$ for all r, in practice we define a grid with an increasing sequence $\{r_k\}_{k=1}^K$, to find an approximation to π_*, defined as

$$\widehat{\pi} := \arg \inf_\pi \max_{k \leq K} J(\pi, r_k) - \inf_{\pi'} J(\pi', r_k) \qquad (2)$$

$$= \arg \inf_\pi \max_{k \leq K} J(\pi, r_k) - J(\pi_k, r_k) \qquad (3)$$

Figure 1: The r-dependent baseline defines a different policy for each value of r, thus, the blue curve may be unachievable with just a single policy. π_* is the single policy that minimizes the maximum gap to this r-dependent baseline policy.

where by definition $\pi_k \in \arg \inf_\pi \sup_{\theta:\mathcal{C}(\theta) \leq r_k} \ell(\pi, \theta)$. We first compute π_k for all $k \in [K]$ to obtain our benchmarks $J(\pi_k, r_k)$, and then use these benchmarks to train $\widehat{\pi}$. The policy $\widehat{\pi}$ is a 3-approximation to π_*. The proof of this result can be found in Appendix B.

Proposition 1. *Let $\pi_*, \widehat{\pi}$ be defined as above. Fix $\epsilon > 0$, $K \in \mathbb{N}$ and set $r_k = (1 + \epsilon)^k$ for all $k \in [K]$. If $J(\pi, r)$ is differentiable on $r > r_1$ then*

$$\lim_{\epsilon \to 0, K \to \infty} \sup_r [J(\widehat{\pi}, r) - \inf_{\pi'} J(\pi', r)] \leq 3 \cdot \sup_r [J(\pi_*, r) - \inf_{\pi'} J(\pi', r)].$$

We define an optimal policy in terms of a function $\mathcal{C}(\theta)$ that determines a partial ordering over instances θ. This function can come from an intuitive heuristic or from information theoretic lower bounds that describe a general ordering but are typically very loose relative to empirical performance. We define one for our particular experiments of interest, others are given in Appendix A. The bottom line is that any function $\mathcal{C}(\theta)$ works, but if it happens to correspond to an information theoretic lower bound, the resulting policy will match the lower bound if it is achievable.

2.2 DIFFERENTIABLE POLICY OPTIMIZATION

The first step in learning the policy $\widehat{\pi}$ defined in Equation 2 is to learn each $\pi_k := \inf_\pi \sup_{\theta:\mathcal{C}(\theta) \leq r_k} \ell(\pi, \theta)$ for all $k = 1, \ldots, K$. Once all π_k are defined, $\widehat{\pi}$ of (2) is an optimization of the same form after shifting the loss by the scalar $J(\pi_k, r_k)$. Consequently, to learn $\widehat{\pi}$ it suffices to develop a training procedure to solve $\inf_\pi \sup_{\theta \in \Omega} \ell'(\pi, \theta)$ for an arbitrary set Ω and generic loss function $\ell'(\pi, \theta)$. To parameterize the objective for optimization, we have

$$\inf_\pi \sup_{\theta \in \Omega} \ell(\pi, \theta) = \inf_\pi \sup_{\widetilde{\theta}_{1:N} \subset \Omega} \max_{i \in [N]} \ell(\pi, \widetilde{\theta}_i) \qquad (4)$$

$$= \inf_\pi \sup_{w \in \mathbb{R}^N, \widetilde{\theta}_{1:N} \subset \Omega} \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi, \widetilde{\theta}_i) \right] \qquad (5)$$

$$\approx \inf_\psi \sup_{w \in \mathbb{R}^N, \widetilde{\theta}_{1:N} \subset \Omega} \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right] \qquad (6)$$

which follows from parameterizing the policy by ψ and a generating distribution over problem instances $\theta \in \Omega$ by a set of N points $\widetilde{\Theta} := \{\widetilde{\theta}_i\}_{i=1}^N \subset \Omega$ weighted by weights $w \in \mathbb{R}^N$. To motivate (6), starting from the left hand side of (4), observe that a small change in π may result in a large change in $\arg\sup_{\theta \in \Omega} \ell(\pi, \theta)$. Therefore, with the goal of covering the entire Ω, we optimize N points so that when π changes a bit, there is at least one $\widetilde{\theta}_i$ close to the optimal $\arg\sup$. In addition, to cover the entire space of Ω, N is very large in practice. However, to optimize the objective effectively, we can only evaluate on M particles ($M \ll N$) in each iteration. Instead of naively sampling M points uniformly at random from the N points, in (5), we optimize an extra multinomial distribution, $\text{SOFTMAX}(w)$, over the N points so that the points around the $\arg\sup$ are sampled more often. The final approximation in (6) comes from parameterizing the policy by a neural network.

To solve the saddle point optimization problem in (6), we use an instance of the Gradient Descent Ascent (GDA) algorithm as shown in Algorithm 1. The gradient estimates are unbiased estimates of the true gradients with respect to ψ, w and $\widetilde{\Theta}$ (shown in Appendix C). We choose N large enough to avoid *mode collapse*, and M, L as large as possible to reduce variance in gradient estimates while fitting the memory constraint. We use Adam optimization (Kingma & Ba, 2014) in taking gradient updates and regularize some of the parameters (an example will be presented in the next section).

Algorithm 1: Gradient Based Optimization of (6)

---

1   **Input**: partition Ω, loss function L_T

2   **Initialization**: w, $\widetilde{\Theta}$ and ψ

3   **for** $t = 1, ..., N_{it}$ **do**

4   Sample M problem indices $I_1, ..., I_M \overset{i.i.d.}{\sim} \text{SOFTMAX}(w)$

5   **for** $m = 1, ..., M$ **do**

6   Collect L independent rollout trajectories, denoted as $\tau_{m,1:L}$, by the policy π^ψ for problem instant θ_{I_m} and observe losses $\forall 1 \leq l \leq L, L_T(\pi^\psi, \tau_{m,l}, \widetilde{\theta}_{I_m})$.

7   **end**

8   Update the generating distribution by taking ascending steps on gradient estimates:

$$w \leftarrow w + \frac{1}{ML} \sum_{m=1}^{M} \nabla_w \log(\text{SOFTMAX}(w)_{I_m}) \cdot (\sum_{l=1}^{L} L_T(\pi^\psi, \tau_{m,l}, \widetilde{\theta}_{I_m})) \qquad (7)$$

$$\widetilde{\Theta} \leftarrow \widetilde{\Theta} + \frac{1}{ML} \sum_{m=1}^{M} \sum_{l=1}^{L} \left(\nabla_{\widetilde{\Theta}} \mathcal{L}_{\text{barrier}}(\widetilde{\theta}_{I_m}, \Omega) + \nabla_{\widetilde{\Theta}} L_T(\pi^\psi, \tau_{m,l}, \widetilde{\theta}_{I_m}) \right.$$
$$\left. + L_T(\pi^\psi, \tau_{m,l}, \widetilde{\theta}_{I_m}) \cdot \nabla_{\widetilde{\Theta}} \log(\mathbb{P}_{\pi^\psi, \widetilde{\theta}_{I_m}}(\tau_{m,l})) \right) \qquad (8)$$

     where $\mathcal{L}_{\text{barrier}}$ is a differentiable barrier loss that heavily penalizes the $\widetilde{\theta}_{I_m}$'s outside Ω.

9   Update the policy by taking descending step on gradient estimate:

$$\psi \leftarrow \psi - \frac{1}{ML} \sum_{m=1}^{M} \sum_{l=1}^{L} L_T(\pi^\psi, \tau_{m,l}, \widetilde{\theta}_{I_m}) \cdot \nabla_\psi \log(\mathbb{P}_{\pi^\psi, \widetilde{\theta}_{I_m}}(\tau_{m,l})) \qquad (9)$$

10   **end**

Note the decomposition for $\log(\mathbb{P}_{\pi^\psi, \theta'}(\tau))$ in (8) and (9), where rollout $\tau = \{(x_t, y_t)\}_{t=1}^T$, and

$$\log(\mathbb{P}_{\pi^\psi, \theta'}(\{(x_t, y_t)\}_{t=1}^T)) = \log\left(\pi^\psi(x_1) \cdot f(y_1|\theta', s_1) \cdot \prod_{t=2}^T \pi^\psi(s_t, x_t) \cdot f(y_t|\theta', s_t, x_t) \right).$$

Here π^ψ and f are only dependent on ψ and $\widetilde{\Theta}$ respectively. During evaluation of a fixed policy π, we are interested in solving $\sup_{\theta \in \Omega} \ell(\pi, \theta)$ by gradient ascent updates like (8). The decoupling of π^ψ and f thus enables us to optimize the objective without differentiating through a policy π, which could be non-differentiable policies like deterministic algorithms.

Finally, we make a few remarks on the parameterization of (6). As given in (6), we represent the generating distribution $\mathcal{P}$ as a simple finite number of weighted particles, analogous to a particle filter. Our policy parameterization π^ψ could be modelled by multi-layer perceptrons, recurrent neural networks, etc. We note that when using alternative generator parameterization like GANs (Goodfellow et al., 2014), an unbiased gradient can also be derived similarly.

3   IMPLEMENTATION FOR LINEAR BANDITS AND CLASSIFICATION

We now apply the general framework of the previous section to a specific problem: transductive linear bandits. As described in Sections 5 and Appendix A this setting generalizes standard multi-armed bandits, linear bandits, and all of binary classification through a simple reduction to combinatorial bandits. We are particularly motivated to look at classification because the existing agnostic active learning algorithms are very inefficient (see Section 5). Indeed when applied to our setting of $T = 20$ they never get past their first stage of uniform random sampling. Consider the game:

Input: Policy π, $\mathcal{X} \subset \mathbb{R}^d$, $\mathcal{Z} \subset \mathbb{R}^d$, time horizon $T \in \mathbb{T}$
Initialization: Nature chooses $\theta_* \in \mathbb{R}^d$ (hidden from policy)
for $t = 1, 2, \ldots, T$
• Policy π selects $x_t \in \mathcal{X}$ using history $\{(x_s, y_s)\}_{s=1}^{t-1}$
• Nature reveals $y_t \sim f(\cdot|\theta_*, x_t)$ with $\mathbb{E}[y_t|\theta_*, x_t] = \langle x_t, \theta_* \rangle$
Output: Policy π recommends $\widehat{z} \in \mathcal{Z}$ as an estimate for $z^\star(\theta_*) := \mathrm{argmax}_{z \in \mathcal{Z}} \langle z, \theta_* \rangle$ and
suffers loss $L_T = \begin{cases} \langle z^\star(\theta_*) - \widehat{z}, \theta_* \rangle & \text{if SIMPLE REGRET} \\ \mathbf{1}\{z^\star(\theta_*) \neq \widehat{z}\} & \text{if BEST IDENTIFICATION} \end{cases}$

The observation distribution $f(\cdot|\theta, x)$ is domain specific but typically taken to be either a Bernoulli distribution for binary data, or Gaussian for real-valued data. We are generally interested in two objectives: BEST IDENTIFICATION which attempts to exactly identify the vector $z^\star \in \mathcal{Z}$ that is most aligned with θ_*, and SIMPLE REGRET which settles for an approximate maximizer.

Defining $\mathcal{C}(\theta)$ Recalling the discussion of Section 2.1, $\mathcal{C}(\theta)$ should ideally be monotonically increasing in the intrinsic difficulty of minimizing the loss with respect to a particular θ. For arbitrary $\mathcal{X} \subset \mathbb{R}^d$ and $\mathcal{Z} \subset \mathbb{R}^d$, it is shown in Fiez et al. (2019) that the sample complexity of identifying $z^\star(\theta) = \arg\max_{z \in \mathcal{Z}} \langle z, \theta \rangle$ with high probability is proportional to a quantity $\rho_\star(\theta)$, the value obtained by an optimization program. Another complexity term that appears in the combinatorial bandits literature (Cao & Krishnamurthy, 2017) where $\mathcal{X} = \{\mathbf{e}_i : i \in [d]\}$ and $\mathcal{Z} \subset \{0,1\}^d$ is

$$\widetilde{\rho}(\theta) = \sum_{i=1}^{d} \max_{z : z_i \neq z_i^\star(\theta)} \frac{\|z - z^\star(\theta)\|_2^2}{\langle z - z^\star(\theta), \theta \rangle^2}. \tag{10}$$

One can show $\rho_\star(\theta) \leq \widetilde{\rho}(\theta)$ and in many cases track each other. Because $\widetilde{\rho}(\theta)$ is closed-form and much faster to compute relative to $\rho_\star(\theta)$, we use $\mathcal{C}(\theta) = \widetilde{\rho}(\theta)$ in our experiments.

Algorithm 2: Training Workflow

---

1 **Input**: sequence $\{r_k\}_{k=1}^K$, $\mathcal{C}$, $\mathcal{X}$, $\mathcal{Z}$, and $obj \in \{\text{SIMPLE REGRET, BEST IDENTIFICATION}\}$
2 **Define** $r(\theta) \in [K]$ such that $r_{k(\theta)-1} < \mathcal{C}(\theta) \leq r_{k(\theta)}$ for all θ with $\mathcal{C}(\theta) \leq r_K$
3 For each $k \in [K]$, obtain policy $\widetilde{\pi}_k$ by Algorithm 1 with $\Omega = \{\theta : \mathcal{C}(\theta) \leq r_k\}$ and SIMPLE REGRET loss
4 **if** obj is BEST IDENTIFICATION **then**
5   For each $k \in [K]$, warm start $\pi_k = \widetilde{\pi}_k$; optimize π_k by Algorithm 1 with $\Omega = \{\theta : \mathcal{C}(\theta) \leq r_k\}$ and BEST IDENTIFICATION loss; compute $J(\pi_k, r_k)$
6   Warm start $\pi_* = \pi_{\lfloor K/2 \rfloor}$; optimize π_* by Algorithm 1 with $\Omega = \{\theta : \mathcal{C}(\theta) \leq r_K\}$ and objective in (2), i.e., $L_T = \mathbf{1}\{z^\star(\theta) \neq \widehat{z}\} - J(\pi_{k(\theta)}, r_{k(\theta)})$
7 **else**
8   For each $k \in [K]$, compute $J(\widetilde{\pi}_k, r_k)$ // In this case, $\pi_k = \widetilde{\pi}_k$.
9   Warm start $\pi_* = \widetilde{\pi}_{\lfloor K/2 \rfloor}$; optimize π_* by Algorithm 1 with $\Omega = \{\theta : \mathcal{C}(\theta) \leq r_K\}$ and objective in (2), i.e., $L_T = \langle z^\star(\theta) - \widehat{z}, \theta \rangle - J(\widetilde{\pi}_{k(\theta)}, r_{k(\theta)})$
10 **end**

Training. When training our policies, we follow the following procedure in Algorithm 2. Note that even when we are training for BEST IDENTIFICATION, we still warm start the training with optimizing SIMPLE REGRET. This is because a random initialized policy performs so poorly that BEST IDENTIFICATION is nearly always 1, making it difficult to improve the policy. In addition, our generating distribution parameterizations exactly follows from Section 2.2, while detailed state representations, policy parametrization and hyperparamters can be found in Appendix D, E.

Loss functions. Instead of optimizing the approximated quantity from (6) directly, we add regularizers to the losses for both the policy and generator. First, we choose the $\mathcal{L}_{\text{barrier}}$ in (8) to be $\lambda_{\text{barrier}} \cdot \max\{0, \log(\mathcal{C}(\mathcal{X}, \mathcal{Z}, \theta)) - \log(r_k)\}$, for some large constant λ_{barrier}. To discourage the policy from over committing to a certain action and/or the generating distribution from covering only a small subset of particles (i.e., mode collapse), we also add negative entropy penalties to both policy's output distributions and SOFTMAX(w) with scaling factors $\lambda_{\text{Pol-reg}}$ and $\lambda_{\text{Gen-reg}}$.

4 EXPERIMENTS

We now evaluate the approach described in the previous section for combinatorial bandits with $\mathcal{X} = \{\mathbf{e}_i : i \in [d]\}$ and $\mathcal{Z} \subset \{0,1\}^d$. We stress that the framework implemented here can be applied to *any* $\mathcal{X}, \mathcal{Z} \subset \mathbb{R}^d$ and any appropriate f–just plug and play to learn a new policy. In our experiments we take particular instances of combinatorial bandits with Bernoulli observations.

Algorithms. We compare against a number of baseline active learning algorithms (see Section 5 for a review). UNCERTAINTY SAMPLING at time t computes the empirical maximizer of $\langle z, \widehat{\theta} \rangle$ and the runner-up, and samples an index uniformly from their symmetric difference; if either are not unique, an index is sampled from the region of disagreement of the winners (see Appendix G for details). The greedy methods are represented by soft generalized binary search (SGBS) (Nowak, 2011) which maintains a posterior distribution over $\mathcal{Z}$ and samples to maximize information gain. A hyperparameter $\beta \in (0, 1/2)$ of SGBS determines the strength of the likelihood update. We plot or report a range of performance over $\beta \in \{.01, .03, .1, .2, .3, .4\}$. The agnostic algorithms for classification (Dasgupta, 2006; Hanneke, 2007b;a; Dasgupta et al., 2008; Huang et al., 2015; Jain & Jamieson, 2019) or combinatorial bandits (Chen et al., 2014; Gabillon et al., 2016; Chen et al., 2017; Cao & Krishnamurthy, 2017; Fiez et al., 2019; Jain & Jamieson, 2019) are so conservative that given just $T = 20$ samples, they are all exactly equivalent to uniform sampling and hence represented by UNIFORM. To represent a policy based on learning to actively learn (LAL), we employ the method of Kveton et al. (2020) with a fixed prior $\widetilde{\mathcal{P}}$ constructed by drawing a z uniformly at random from $\mathcal{Z}$ and defining $\theta = 2z - 1 \in [-1, 1]^d$ (details in Appendix H). When evaluating each policy, we use the successive halving algorithm (Li et al., 2017; 2018) for optimizing our non-convex objective with randomly initialized gradient descent and restarts (details in Appendix F).

Thresholds. We begin with a very simple instance to demonstrate the instance-dependent performance achieved by our learned policy. For $d = 25$ let $\mathcal{X} = \{\mathbf{e}_i : i \in [d]\}$, $\mathcal{Z} = \{\mathbf{0} + \sum_{i=1}^k \mathbf{e}_i : k = 0, 1, \ldots, d\}$, and $f(\cdot|\theta, x)$ is a Bernoulli distribution over $\{-1, 1\}$ with mean $\langle x, \theta \rangle \in [-1, 1]$. Note this is a binary classification task in one-dimension where the set of classifiers are thresholds on a line. We trained baseline policies $\{\pi_k\}_{k=1}^9$ for the BEST IDENTIFICATION metric with $\mathcal{C}(\theta) = \widetilde{\rho}(\mathcal{X}, \mathcal{Z}, \theta)$ and $r_k = 2^{3+i/2}$ for $i \in \{0, \ldots, 8\}$.

First we compare the base policies π_k to π_*. Figure 2 presents $J(\pi, r) = \sup_{\theta:\rho_*(\theta) \leq r} \ell(\pi, \theta) = \sup_{\theta:\rho_*(\theta) \leq r} \mathbb{P}_{\pi,\theta}(\widehat{z} \neq z_*(\theta))$ as a function of r for our base policies $\{\pi_k\}_k$ and the global policy π_*, each as an individual curve. Figure 3 plots the same information in terms of gap: $J(\pi, r) - \min_{k:r_{k-1} < r \leq r_k} J(\pi_k, r_k)$. We observe that each π_k

Figure 2: Learned policies, lower is better

Figure 3: Sub-optimality of individual policies, lower is better

Figure 4: Max $\{\theta : \widetilde{\rho}(\theta) \leq r\}$, lower is better

Figure 5: Average $\mathbb{E}_{\theta \sim \mathcal{P}_h}[\cdot]$, lower is better

performs best in a particular region and π_* performs almost as well as the r-dependent baseline policies over the range of r. *This plot confirms that our optimization objective of* (2) *was successful.* Under the same conditions as Figure 2, Figure 4 compares the performance of π_* to the algorithm benchmarks. Since SGBS and LAL are deterministic, the adversarial training finds a θ that tricks them into catastrophic failure. Figure 5 trades adversarial evaluation for evaluating with respect to a parameterized prior: For each $h \in \{0.5, 0.6, \ldots, 1\}$, $\theta \sim \mathcal{P}_h$ is defined by drawing a z uniformly at random from $\mathcal{Z}$ and then setting $\theta_i = (2z_i - 1)(2\alpha_i - 1)$ where $\alpha_i \sim \text{Bernoulli}(h)$. Thus, each sign of $2z - 1$ is flipped with probability h. We then compute $\mathbb{E}_{\theta \sim \mathcal{P}_h}[\mathbb{P}_{\pi,\theta}(\widehat{z} = z_*(\theta))] = \mathbb{E}_{\theta \sim \mathcal{P}_h}[\ell(\pi, \theta)]$. While SGBS now performs much better than uniform and uncertainty sampling, our policy π_* is still

superior to these policies. However, LAL is best overall which is expected since the support of $\mathcal{P}_h$ is basically a rescaled version of the prior used in LAL.

20 Questions. We now address an instance constructed from the real data of Hu et al. (2018). Summarizing how we used the data from Hu et al. (2018) (see Appendix I for details), 100 yes/no questions were considered for 1000 celebrities. Each question $i \in [100]$ for each person $j \in [1000]$ was answered by sev-

Figure 6: Max $\{\theta : \widetilde{\rho}(\theta) \leq r\}$

Table 1: Average $\mathbb{E}_{\theta \sim \widehat{\mathcal{P}}}[\cdot]$

Method	Accuracy (%)
π^* (Ours)	17.9
SGBS	$\{26.5, 26.2,$
	$27.2, 26.5,$
	$21.4, 12.8\}$
Uncertainty	14.3
LAL	4.1
Uniform	6.9

eral annotators to construct an empirical probability $\bar{p}_i^{(j)} \in [0, 1]$ denoting the proportion of annotators that answered "yes." To construct our instance, we take $\mathcal{X} = \{\mathbf{e}_i : i \in [100]\}$ and $\mathcal{Z} = \{z^{(j)} : [z_i^{(j)}] = \mathbf{1}\{\bar{p}_i^{(j)} > 1/2\}\} \subset \{0,1\}^{1000}$. Just as before, we trained $\{\pi_k\}_{k=1}^4$ for the BEST IDENTIFICATION metric with $\mathcal{C}(\theta) = \widetilde{\rho}(\mathcal{X}, \mathcal{Z}, \theta)$ and $r_i = 2^{3+i/2}$ for $i \in \{1, \ldots, 4\}$.

Figure 6 is analogous to Figure 4 but for this 20 questions instance. Uncertainty sampling performs remarkably well on this instance. A potential explanation is that on a noiseless instance (e.g., $\theta = 2z - 1$ for some $z \in \mathcal{Z}$), our implementation of uncertainty sampling is equivalent to CAL (Cohn et al., 1994) and is known to have near-optimal sample complexity (Hanneke et al., 2014). Uncertainty sampling even outperforms our r-dependent baseline by a bit which in theory should not occur–we conjecture this is due to insufficient convergence of our policies or local minima. Our second experiment constructs a distribution $\widehat{\mathcal{P}}$ based on the dataset: to draw a $\theta \sim \widehat{\mathcal{P}}$ we uniformly at random select a $j \in [1000]$ and sets $\theta_i = 2\bar{p}_i^{(j)} - 1$ for all $i \in [d]$. As shown in Table 1, SGBS and π_* are the winners. *Although not trained for the objective, our policy still performs relatively well compare to the best algorithm for this case.* LAL performs much worse in this case, potentially because of the distribution shift from $\widetilde{\mathcal{P}}$ (prior we train on) to $\widehat{\mathcal{P}}$ (prior at test time). The strong performance of SGBS may be due to the fact that $\text{sign}(\theta_i) = 2z_\star(\theta)_i - 1$ for all i and $\theta \sim \widehat{\mathcal{P}}$, a realizability condition under which SGBS has strong guarantees (Nowak, 2011).

Jester Joke Recommendation We now turn our attention away from best identification of the last two experiments $\ell(\pi, \theta) = \mathbb{P}_{\pi,\theta}(\widehat{z} \neq z_\star(\theta))$, to simple regret $\ell(\pi, \theta) = \mathbb{E}_{\pi,\theta}[\langle z_\star(\theta) - \widehat{z}, \theta \rangle]$. We consider the Jester jokes dataset of Goldberg et al. (2001) that contains jokes ranging innocent puns to grossly of-

Figure 7: Max $\{\theta : \widehat{\rho}(\theta) \leq r\}$

Table 2: Average $\mathbb{E}_{\theta \sim \widehat{\mathcal{P}}}[\cdot]$

Method	Average Regret
π^* (Ours)	3.209
SGBS	$\{3.180, 3.224,$
	$3.278, 3.263,$
	$3.153, 3.090\}$
Uncertainty	3.027
LAL	3.610
Uniform	3.877

fensive jokes. We filter the dataset to only contain users that rated all 100 jokes, resulting in 14116 users. A rating of each joke was provided on a $[-10, 10]$ scale which was rescaled to $[-1, 1]$ and observations were simulated as Bernoulli's like above. We then clustered the ratings of these users (see Appendix J for details) to 10 groups to obtain $\mathcal{Z} = \{z^{(k)} : k \in [10], z^{(k)} \in \{0,1\}^{100}\}$ where $z_i^{(k)} = 1$ corresponds to recommending the ith joke in user cluster $z^{(k)} \in \mathcal{Z}$. Figure 7 shows the same style plot as Figures 4,6 but for this jokes dataset, with our policy alone nearly achieving the r-dependent baseline for all r. Mirroring the construction of the 20Q prior, we construct $\widehat{P}$ by uniformly sampling a user and employing their θ to answer queries. Table 2 shows that despite our policy not being trained for this setting, its performance is still among the top.

5 RELATED WORK

Learning to actively learn. Previous works vary in how the parameterize the policy, ranging from parameterized mixtures of existing expertly designed active learning algorithms (Baram et al., 2004; Hsu & Lin, 2015; Agarwal et al., 2016), parameterizing hyperparameters (e.g., learning rate, rate of

forced exploration, etc.) in an existing popular algorithm (e.g, EXP3) (Konyushkova et al., 2017; Bachman et al., 2017; Cella et al., 2020), and the most ambitious, policies parameterized end-to-end like in this work (Boutilier et al., 2020; Kveton et al., 2020; Sharaf & Daumé III, 2019; Fang et al., 2017; Woodward & Finn, 2017). These works take an approach of defining a prior distribution either through past experience (meta-learning) or expert created (e.g., $\theta \sim \mathcal{N}(0, \Sigma)$), and then evaluate their policy with respect to this prior distribution. Defining this prior can be difficult, and moreover, if the θ encountered at test time did not follow this prior distribution, performance could suffer significantly. Our approach, on the other hand, takes an adversarial training approach and can be interpreted as learning a parameterized least favorable prior (Wasserman, 2013), thus gaining a much more robust policy as an end result.

Robust and Safe Reinforcement Learning: Our work is also highly related to the field of robust and safe reinforcement learning, where our objective can be considered as an instance of *minimax criterion under parameter uncertainty* (Garcıa & Fernández, 2015). Widely applied in applications such as robotics (Mordatch et al., 2015; Rajeswaran et al., 2016), these methods train a policy in a simulator like Mujoco (Todorov et al., 2012) to minimize a defined loss objective while remaining robust to uncertainties and perturbations to the environment (Mordatch et al., 2015; Rajeswaran et al., 2016). Ranges of these uncertainty parameters are chosen based on potential values that could be encountered when deploying the robot in the real world. In our setting, however, defining the set of environments is far less straightforward and is overcome by the adoption of the $\mathcal{C}(\theta)$ function.

Active Binary Classification Algorithms. The literature on active learning algorithms can be partitioned into *model-based heuristics* like uncertainty sampling, query by committee, or model-change sampling (Settles, 2009), *greedy binary-search* like algorithms that typically rely on a form of bounded noise for correctness (Dasgupta, 2005; Kääriäinen, 2006; Golovin & Krause, 2011; Nowak, 2011), and *agnostic* algorithms that make no assumptions on the probabilistic model (Dasgupta, 2006; Hanneke, 2007b;a; Dasgupta et al., 2008; Huang et al., 2015; Jain & Jamieson, 2019). Though the heuristics and greedy methods can perform very well for some problems, it is typically easy to construct counter-examples (e.g., outside the assumptions) in which they catastrophically fail (as demonstrated in our experiments). The agnostic algorithms have strong robustness guarantees but rely on concentration inequalities, and consequently require at least hundreds of labels to observe any deviation from random sampling (see Huang et al. (2015) for comparison). Therefore, they were not included in our experiments explicitly but were represented by uniform.

Pure-exploration Multi-armed Bandit Algorithms. In the linear structure setting, for sets $\mathcal{X}, \mathcal{Z} \subset \mathbb{R}^d$ known to the player, pulling an "arm" $x \in \mathcal{X}$ results in an observation $\langle x, \theta_* \rangle +$ zero-mean noise, and the objective is to identify $\arg \max_{z \in \mathcal{Z}} \langle z, \theta_* \rangle$ for a vector θ_* unknown to the player (Soare et al., 2014; Karnin, 2016; Tao et al., 2018; Xu et al., 2017; Fiez et al., 2019). A special case of linear bandits is combinatorial bandits where $\mathcal{X} = \{\mathbf{e}_i : i \in [d]\}$ and $\mathcal{Z} \subset \{0, 1\}^d$ (Chen et al., 2014; Gabillon et al., 2016; Chen et al., 2017; Cao & Krishnamurthy, 2017; Fiez et al., 2019; Jain & Jamieson, 2019). Active binary classification is a special case of combinatorial pure-exploration multi-armed bandits (Jain & Jamieson, 2019), which we exploit in the threshold experiments. While the above works have made great theoretical advances in deriving algorithms and information theoretic lower bounds that match up to constants, the constants are so large that these algorithms only behave well when the number of measurements is very large. When applied to the instances of our paper (only 20 queries are made), these algorithms behave no differently than random sampling.

6   DISCUSSION AND FUTURE DIRECTIONS

We see this work as an exciting but preliminary step towards realizing the full potential of this general approach. From a practical perspective, training a π_* can take many hours of computational resources for even these small instances. Scaling these methods to larger instances is an important next step. While training time scales linearly with the horizon length T, we note that one can take multiple samples per time step with minimal computational overhead enabling problems that require larger sample complexities. In our implementation we hard-coded the decision rule for $\widehat{z}$ given s_T, while it could also be learned as in (Luedtke et al., 2020). Likewise, the parameterization of the policy and generator worked well for our purposes but was chosen somewhat arbitrarily–are there more natural choices? Finally, while we focused on stochastic settings, this work naturally extends to constrained fully adaptive adversarial sequences which is an interesting direction of future work.

FUNDING DISCLOSURE

Removed for anonymization purposes.

ACKNOWLEDGEMENT

Removed for anonymization purposes.

REFERENCES

Alekh Agarwal, Haipeng Luo, Behnam Neyshabur, and Robert E Schapire. Corralling a band of bandit algorithms. *arXiv preprint arXiv:1612.06246*, 2016.

VM Aleksandrov, VI Sysoyev, and SHEMENEV. VV. Stochastic optimization. *Engineering Cybernetics*, (5): 11–+, 1968.

Philip Bachman, Alessandro Sordoni, and Adam Trischler. Learning algorithms for active learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 301–310. JMLR. org, 2017.

Yoram Baram, Ran El Yaniv, and Kobi Luz. Online choice of active learning algorithms. *Journal of Machine Learning Research*, 5(Mar):255–291, 2004.

Craig Boutilier, Chih-Wei Hsu, Branislav Kveton, Martin Mladenov, Csaba Szepesvari, and Manzil Zaheer. Differentiable bandit exploration. *arXiv preprint arXiv:2002.06772*, 2020.

Tongyi Cao and Akshay Krishnamurthy. Disagreement-based combinatorial pure exploration: Efficient algorithms and an analysis with localization. *stat*, 2017.

Alexandra Carpentier and Andrea Locatelli. Tight (lower) bounds for the fixed budget best arm identification bandit problem. In *Conference on Learning Theory*, pp. 590–604, 2016.

Leonardo Cella, Alessandro Lazaric, and Massimiliano Pontil. Meta-learning with stochastic linear bandits. *arXiv preprint arXiv:2005.08531*, 2020.

Lijie Chen, Anupam Gupta, Jian Li, Mingda Qiao, and Ruosong Wang. Nearly optimal sampling algorithms for combinatorial pure exploration. In *Conference on Learning Theory*, pp. 482–534, 2017.

Shouyuan Chen, Tian Lin, Irwin King, Michael R Lyu, and Wei Chen. Combinatorial pure exploration of multi-armed bandits. In *Advances in Neural Information Processing Systems*, pp. 379–387, 2014.

David Cohn, Les Atlas, and Richard Ladner. Improving generalization with active learning. *Machine learning*, 15(2):201–221, 1994.

Sanjoy Dasgupta. Analysis of a greedy active learning strategy. In *Advances in neural information processing systems*, pp. 337–344, 2005.

Sanjoy Dasgupta. Coarse sample complexity bounds for active learning. In *Advances in neural information processing systems*, pp. 235–242, 2006.

Sanjoy Dasgupta, Daniel J Hsu, and Claire Monteleoni. A general agnostic active learning algorithm. In *Advances in neural information processing systems*, pp. 353–360, 2008.

Meng Fang, Yuan Li, and Trevor Cohn. Learning how to active learn: A deep reinforcement learning approach. *arXiv preprint arXiv:1708.02383*, 2017.

Tanner Fiez, Lalit Jain, Kevin G Jamieson, and Lillian Ratliff. Sequential experimental design for transductive linear bandits. In *Advances in Neural Information Processing Systems*, pp. 10666–10676, 2019.

Victor Gabillon, Alessandro Lazaric, Mohammad Ghavamzadeh, Ronald Ortner, and Peter Bartlett. Improved learning complexity in combinatorial pure exploration bandits. In *Artificial Intelligence and Statistics*, pp. 1004–1012, 2016.

Javier Garcıa and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(1):1437–1480, 2015.

Aurélien Garivier and Emilie Kaufmann. Optimal best arm identification with fixed confidence. In *Conference on Learning Theory*, pp. 998–1027, 2016.

Ken Goldberg, Theresa Roeder, Dhruv Gupta, and Chris Perkins. Eigentaste: A constant time collaborative filtering algorithm. *information retrieval*, 4(2):133–151, 2001.

Daniel Golovin and Andreas Krause. Adaptive submodularity: Theory and applications in active learning and stochastic optimization. *Journal of Artificial Intelligence Research*, 42:427–486, 2011.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Steve Hanneke. A bound on the label complexity of agnostic active learning. In *Proceedings of the 24th international conference on Machine learning*, pp. 353–360, 2007a.

Steve Hanneke. Teaching dimension and the complexity of active learning. In *International Conference on Computational Learning Theory*, pp. 66–81. Springer, 2007b.

Steve Hanneke et al. Theory of disagreement-based active learning. *Foundations and Trends® in Machine Learning*, 7(2-3):131–309, 2014.

Botao Hao, Tor Lattimore, and Csaba Szepesvari. Adaptive exploration in linear contextual bandit. *arXiv preprint arXiv:1910.06996*, 2019.

Wei-Ning Hsu and Hsuan-Tien Lin. Active learning by learning. In *Twenty-Ninth AAAI conference on artificial intelligence*, 2015.

Huang Hu, Xianchao Wu, Bingfeng Luo, Chongyang Tao, Can Xu, Wei Wu, and Zhan Chen. Playing 20 question game with policy-based reinforcement learning. *arXiv preprint arXiv:1808.07645*, 2018.

Tzu-Kuo Huang, Alekh Agarwal, Daniel J Hsu, John Langford, and Robert E Schapire. Efficient and parsimonious agnostic active learning. In *Advances in Neural Information Processing Systems*, pp. 2755–2763, 2015.

Lalit Jain and Kevin G Jamieson. A new perspective on pool-based active classification and false-discovery control. In *Advances in Neural Information Processing Systems*, pp. 13992–14003, 2019.

Matti Kääriäinen. Active learning in the non-realizable case. In *International Conference on Algorithmic Learning Theory*, pp. 63–77. Springer, 2006.

Zohar Karnin, Tomer Koren, and Oren Somekh. Almost optimal exploration in multi-armed bandits. In *International Conference on Machine Learning*, pp. 1238–1246, 2013.

Zohar S Karnin. Verification based solution for structured mab problems. In *Advances in Neural Information Processing Systems*, pp. 145–153, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ksenia Konyushkova, Raphael Sznitman, and Pascal Fua. Learning active learning from data. In *Advances in Neural Information Processing Systems*, pp. 4225–4235, 2017.

Branislav Kveton, Martin Mladenov, Chih-Wei Hsu, Manzil Zaheer, Csaba Szepesvari, and Craig Boutilier. Differentiable meta-learning in contextual bandits. *arXiv preprint arXiv:2006.05094*, 2020.

Tor Lattimore and Csaba Szepesvari. The end of optimism? an asymptotic analysis of finite-armed linear bandits. *arXiv preprint arXiv:1610.04491*, 2016.

Liam Li, Kevin Jamieson, Afshin Rostamizadeh, Ekaterina Gonina, Moritz Hardt, Benjamin Recht, and Ameet Talwalkar. Massively parallel hyperparameter tuning. *arXiv preprint arXiv:1810.05934*, 2018.

Lisha Li, Kevin Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. Hyperband: A novel bandit-based approach to hyperparameter optimization. *The Journal of Machine Learning Research*, 18(1): 6765–6816, 2017.

Alex Luedtke, Marco Carone, Noah Simon, and Oleg Sofrygin. Learning to learn from data: Using deep adversarial learning to construct optimal statistical procedures. *Science Advances*, 6(9), 2020. doi: 10.1126/sciadv.aaw2140. URL https://advances.sciencemag.org/content/6/9/eaaw2140.

Shie Mannor and John N Tsitsiklis. The sample complexity of exploration in the multi-armed bandit problem. *Journal of Machine Learning Research*, 5(Jun):623–648, 2004.

Igor Mordatch, Kendall Lowrey, and Emanuel Todorov. Ensemble-cio: Full-body dynamic motion planning that transfers to physical humanoids. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5307–5314. IEEE, 2015.

Robert D Nowak. The geometry of generalized binary search. *IEEE Transactions on Information Theory*, 57 (12):7893–7906, 2011.

Jungseul Ok, Alexandre Proutiere, and Damianos Tranos. Exploration in structured reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 8874–8882, 2018.

Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. Epopt: Learning robust neural network policies using model ensembles. *arXiv preprint arXiv:1610.01283*, 2016.

Burr Settles. Active learning literature survey. Technical report, University of Wisconsin-Madison Department of Computer Sciences, 2009.

Amr Sharaf and Hal Daumé III. Meta-learning for contextual bandit exploration. *arXiv preprint arXiv:1901.08159*, 2019.

Max Simchowitz and Kevin G Jamieson. Non-asymptotic gap-dependent regret bounds for tabular mdps. In *Advances in Neural Information Processing Systems*, pp. 1151–1160, 2019.

Max Simchowitz, Kevin Jamieson, and Benjamin Recht. The simulator: Understanding adaptive sampling in the moderate-confidence regime. *arXiv preprint arXiv:1702.05186*, 2017.

Marta Soare, Alessandro Lazaric, and Rémi Munos. Best-arm identification in linear bandits. In *Advances in Neural Information Processing Systems*, pp. 828–836, 2014.

Chao Tao, Saúl Blanco, and Yuan Zhou. Best arm identification in linear bandits with linear dimension dependency. In *International Conference on Machine Learning*, pp. 4877–4886, 2018.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Alexandre B Tsybakov. *Introduction to nonparametric estimation*. Springer Science & Business Media, 2008.

Bart Van Parys and Negin Golrezaei. Optimal learning for structured bandits. 2020.

Larry Wasserman. *All of statistics: a concise course in statistical inference*. Springer Science & Business Media, 2013.

Mark Woodward and Chelsea Finn. Active one-shot learning. *arXiv preprint arXiv:1702.06559*, 2017.

Liyuan Xu, Junya Honda, and Masashi Sugiyama. Fully adaptive algorithm for pure exploration in linear bandits. *arXiv preprint arXiv:1710.05552*, 2017.

A Instance dependent sample complexity

Identifying forms of $\mathcal{C}(\theta)$ is not as difficult a task as one might think due to the proliferation of tools for proving lower bounds for active learning (Mannor & Tsitsiklis, 2004; Tsybakov, 2008; Garivier & Kaufmann, 2016; Carpentier & Locatelli, 2016; Simchowitz et al., 2017; Chen et al., 2014). One can directly extract values of $\mathcal{C}(\theta)$ from the literature for regret minimization of linear or other structured bandits (Lattimore & Szepesvari, 2016; Van Parys & Golrezaei, 2020), contextual bandits (Hao et al., 2019), and tabular as well as structured MDPs (Simchowitz & Jamieson, 2019; Ok et al., 2018). Moreover, we believe that even reasonable surrogates of $\mathcal{C}(\theta)$ should result in a high quality policy π_*.

We review some canonical examples:

- **Multi-armed bandits.** In the best-arm identification problem, there are $d \in \mathbb{N}$ Gaussian distributions where the ith distribution has mean $\theta_i \in \mathbb{R}$ for $i = 1, \dots, d$. In the above formulation, this problem is encoded as action $x_t = i_t$ results in observation $y_t \sim \text{Bernoulli}(\theta_{i_t})$ and the loss $\ell(\pi, \theta) := \mathbb{E}_{\pi,\theta}[\mathbf{1}\{\widehat{i} \neq i_\star(\theta)\}]$ where $\widehat{i}$ is π's recommended index and $i_\star(\theta) = \arg\max_i \theta_i$. It's been shown that there exists a constant $c_0 > 0$ such that for any sufficiently large $\nu > 0$ we have

$$\inf_\pi \sup_{\theta : \mathcal{C}_{MAB}(\theta) \leq \nu} \ell(\pi, \theta) \geq \exp(-c_0 T/\nu) \quad \text{where} \quad \mathcal{C}_{MAB}(\theta) := \sum_{i \neq i_\star(\theta)} (\theta_{i_\star(\theta)} - \theta_i)^{-2}$$

  Moreover, for any $\theta \in \mathbb{R}^d$ there exists a policy $\widetilde{\pi}$ that achieves $\ell(\widetilde{\pi}, \theta) \leq c_1 \exp(-c_2 T/\mathcal{C}_{MAB}(\theta))$ where c_1, c_2 capture constant and low-order terms (Carpentier & Locatelli, 2016; Karnin et al., 2013; Simchowitz et al., 2017; Garivier & Kaufmann, 2016).

The above correspondence between the lower bound and the upper bound suggests that $\mathcal{C}_{MAB}(\theta)$ plays a critical role in determining the difficult of identifying $i_\star(\theta)$ for *any* θ. This exercise extends to more structured settings as well:

- **Content recommendation / active search.** Consider n items (e.g., movies, proteins) where the ith item is represented by a feature vector $x_i \in \mathcal{X} \subset \mathbb{R}^d$ and a measurement $x_t = x_i$ (e.g., preference rating, binding affinity to a target) is modeled as a linear response model such that $y_t \sim \mathcal{N}(\langle x_i, \theta \rangle, 1)$ for some unknown $\theta \in \mathbb{R}^d$. If $\ell(\pi, \theta) := \mathbb{E}_{\pi,\theta}[\mathbf{1}\{\widehat{i} \neq i_\star(\theta)\}]$ as above then nearly identical results to that of above hold for an analogous function of $\mathcal{C}_{MAB}(\theta)$ (Soare et al., 2014; Karnin, 2016; Fiez et al., 2019).

- **Active binary classification.** For $i = 1, \dots, d$ let $\phi_i \in \mathbb{R}^p$ be a feature vector of an unlabeled item (e.g., image) that can be queried for its binary label $y_i \in \{-1, 1\}$ where $y_i \sim \text{Bernoulli}(\theta_i)$ for some $\theta \in \mathbb{R}^d$. Let $\mathcal{H}$ be an arbitrary set of classifiers (e.g., neural nets, random forest, etc.) such that each $h \in \mathcal{H}$ assigns a label $\{-1, 1\}$ to each of the items $\{\phi_i\}_{i=1}^d$ in the pool. If items are chosen sequentially to observe their labels, the objective is to identify the true risk minimizer $h_\star(\theta) = \arg\min_{h \in \mathcal{H}} \sum_{i=1}^d \mathbb{E}_\theta[\mathbf{1}\{h(\phi_i) \neq y_i\}]$ using as few requested labels as possible and $\ell(\pi, \theta) := \mathbb{E}_{\pi,\theta}[\mathbf{1}\{\widehat{h} \neq h_\star(\theta)\}]$ where $\widehat{h} \in \mathcal{H}$ is π's recommended classifier. Many candidates for $\mathcal{C}(\theta)$ have been proposed from the agnostic active learning literature (Dasgupta, 2006; Hanneke, 2007b;a; Dasgupta et al., 2008; Huang et al., 2015; Jain & Jamieson, 2019) but we believe the most granular candidates come from the combinatorial bandit literature (Chen et al., 2017; Fiez et al., 2019; Cao & Krishnamurthy, 2017; Jain & Jamieson, 2019). To make the reduction, for each $h \in \mathcal{H}$ assign a $z^{(h)} \in \{0, 1\}^d$ such that $[z^{(h)}]_i := \mathbf{1}\{h(\phi_i) = 1\}$ for all $i = 1, \dots, d$ and set $\mathcal{Z} = \{z^{(h)} : h \in \mathcal{H}\}$. It is easy to check that $z_\star(\theta) := \arg\max_{z \in \mathcal{Z}} \langle z, \theta \rangle$ satisfies $z_\star(\theta) = z^{(h_\star(\theta))}$. Thus, requesting the label of example i is equivalent to sampling from $\text{Bernoulli}(\langle \mathbf{e}_i, \theta \rangle) \in \{-1, 1\}$, completing the reduction to combinatorial bandits: $\mathcal{X} = \{\mathbf{e}_i : i \in [d]\}$, $\mathcal{Z} \subset \{0, 1\}^d$. We then apply the exact same $\mathcal{C}(\theta)$ as above for linear bandits.

B Proof of Proposition 1

Proposition 1. *Let $\pi_*, \widehat{\pi}$ be defined as in* (1) *and* (2)*. Fix $\epsilon > 0$, $K \in \mathbb{N}$ and set $r_k = (1 + \epsilon)^k$ for all $k \in [K]$. If $J(\pi, r)$ is differentiable on $r > r_1$ then*

$$\lim_{\epsilon \to 0, K \to \infty} \sup_r [J(\widehat{\pi}, r) - \inf_{\pi'} J(\pi', r)] \leq 3 \cdot \sup_r [J(\pi_*, r) - \inf_{\pi'} J(\pi', r)].$$

Proof. We begin by noting that

$$\sup_r J(\widehat{\pi}, r) - J(\pi_*, r)$$

$$= \sup_r \sup_{\theta:\mathcal{C}(\theta)\leq r} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq r} \ell(\pi_*, \theta)$$

$$\leq \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^{k-1}} \ell(\pi_*, \theta)$$

$$= \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta)$$

$$+ \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^{k-1}} \ell(\pi_*, \theta)$$

$$\leq \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta)$$

$$+ \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta) - \inf_{\pi'} J(\pi', (1+\epsilon)^{k-1})$$

$$\leq \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta)$$

$$+ \sup_r \left[\sup_{\theta:\mathcal{C}(\theta)\leq r} \ell(\pi_*, \theta) - \inf_{\pi'} J(\pi', r/(1+\epsilon)) \right]$$

$$= \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}_k, \theta)$$

$$+ \underbrace{\sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}_k, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta)}_{\leq 0}$$

$$+ \sup_r \left[J(\pi_*, r) - \inf_{\pi'} J(\pi', r/(1+\epsilon)) \right]$$

and

$$\max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}_k, \theta)$$

$$= \inf_\pi \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi, \theta) - \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\widehat{\pi}_k, \theta)$$

$$= \inf_\pi \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi, \theta) - \inf_{\pi'} J(\pi', (1+\epsilon)^k)$$

$$\leq \max_k \sup_{\theta:\mathcal{C}(\theta)\leq(1+\epsilon)^k} \ell(\pi_*, \theta) - \inf_{\pi'} J(\pi', (1+\epsilon)^k)$$

$$\leq \sup_r \left[J(\pi_*, r) - \inf_{\pi'} J(\pi', r) \right].$$

Here the last equality follows from the fact that $\inf_{\pi'} J(\pi', r)$ is non-decreasing in r and for all r there exists a k such that $(1+\epsilon)^{k-1} \leq r \leq (1+\epsilon)^k$. Additionally, by differentiability of J, we note that $J(\pi_*, r/(1+\epsilon)) = J(\pi_*, r)$ as $\epsilon \to 0$. Therefore by combining the above ineqalities, we get:

$$\lim_{\epsilon\to 0, K\to\infty} \sup_r [J(\widehat{\pi}, r) - J(\pi_*, r)] \leq 2 \cdot \sup_r [J(\pi_*, r) - \inf_{\pi'} J(\pi', r)].$$

To complete the proof, we further expand the terms:

$$\lim_{\epsilon\to 0, K\to\infty} \sup_r [J(\widehat{\pi}, r) - \inf_{\pi'} J(\pi', r)]$$

$$= \sup_r [J(\widehat{\pi}, r) - J(\pi_*, r) + J(\pi_*, r) - \inf_{\pi'} J(\pi', r)]$$

$$\leq \sup_r [J(\widehat{\pi}, r) - J(\pi_*, r)] + \sup_r [J(\pi_*, r) - \inf_{\pi'} J(\pi', r)]$$

$$\leq 3 \cdot \sup_r [J(\pi_*, r) - \inf_{\pi'} J(\pi', r)].$$

$\square$

C GRADIENT ESTIMATE DERIVATION

Here we derive the unbiased gradient estimates (7), (8) and (9) in Algorithm 1. Since each the gradient estimates in the above averages over $M \cdot L$ identically distributed trajectories, it is therefore sufficient to show that our gradient estimate is unbiased for a single problem $\widetilde{\theta}_i$ and its rollout trajectory $\{(x_t, y_t)\}_{t=1}^T$.

For a feasible w, using the score-function identity (Aleksandrov et al., 1968)

$$\nabla_w \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right] = \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \cdot \nabla_w \log(\text{SOFTMAX}(w)_i) \right].$$

Observe that if $i \sim \text{SOFTMAX}(w)$ and $\{(x_t, y_t)\}_{t=1}^T$ is the result of rolling out a policy π^ψ on $\widetilde{\theta}_i$ then

$$g^w := L_T(\pi^\psi, \{(x_t, y_t)\}_{t=1}^T, \widetilde{\theta}_i) \cdot \nabla_w \log(\text{SOFTMAX}(w)_i)$$

is an unbiased estimate of $\nabla_w \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right]$.

For a feasible set $\widetilde{\Theta}$, by definition of $\ell(\pi, \theta)$,

$$\nabla_{\widetilde{\Theta}} \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right] = \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\nabla_{\widetilde{\Theta}} \mathbb{E}_{\pi, \widetilde{\theta}_i} \left[L_T(\pi, \{(x_t, y_t)\}_{t=1}^T, \widetilde{\theta}_i) \right] \right]$$

$$= \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\mathbb{E}_{\pi, \widetilde{\theta}_i} \left[\nabla_{\widetilde{\Theta}} L_T(\pi, \{(x_t, y_t)\}_{t=1}^T, \widetilde{\theta}_i) \right. \right. \tag{11}$$

$$\left. \left. + L_T(\pi, \{(x_t, y_t)\}_{t=1}^T, \widetilde{\theta}_i) \cdot \nabla_{\widetilde{\Theta}} \log(\mathbb{P}_{\pi^\psi, \widetilde{\theta}_i}(\{(x_t, y_t)\}_{t=1}^T)) \right] \right]$$

where the last equality follows from chain rule and the score-function identity (Aleksandrov et al., 1968). The quantity inside the expectations, call it $g^{\widetilde{\Theta}}$, is then an unbiased estimator of $\nabla_{\widetilde{\Theta}} \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right]$ given i and $\{(x_t, y_t)\}_{t=1}^T$ are rolled out accordingly. Note that if $\mathcal{L}_{\text{barrier}} \neq 0$, $\nabla_{\widetilde{\Theta}} \mathcal{L}_{\text{barrier}}(\widetilde{\theta}_i, \Omega)$ is clearly an unbiased gradient estimator of $\mathbb{E}_{i \sim \text{SOFTMAX}(w)} [\mathbb{E}_{\pi, \widetilde{\theta}_i} [\mathcal{L}_{\text{barrier}}(\widetilde{\theta}_i, \Omega)]]$ given i and rollout are sampled accordingly.

Likewise, for policy,

$$g^\psi := L_T(\pi^\psi, \{(x_t, y_t)\}_{t=1}^T, \widetilde{\theta}_i) \cdot \nabla_\psi \log(\mathbb{P}_{\pi^\psi, \widetilde{\theta}_i}(\{(x_t, y_t)\}_{t=1}^T))$$

is an unbiased estimate of $\nabla_\psi \mathbb{E}_{i \sim \text{SOFTMAX}(w)} \left[\ell(\pi^\psi, \widetilde{\theta}_i) \right]$.

D LINEAR BANDIT PARAMETERIZATION

D.1 STATE REPRESENTATION

We parameterize our state space $\mathcal{S}$ as a flattened $|\mathcal{X}| \times 3$ matrix where each row represents a distinct $x \in \mathcal{X}$. Specifically, at time t the row of s_t corresponding to some $x \in \mathcal{X}$ records the number of times that action x has been taken $\sum_{s=1}^{t-1} \mathbf{1}\{x_s = x\}$, its inverse $(\sum_{s=1}^{t-1} \mathbf{1}\{x_s = x\})^{-1}$, and the sum of the observations $\sum_{s=1}^{t-1} \mathbf{1}\{x_s = x\} y_s$.

D.2 POLICY MLP ARCHITECTURE

Our policy π^ψ is a multi-layer perceptron with weights ψ. The policy take a $3|\mathcal{X}|$ sized state as input and outputs a vector of size $|\mathcal{X}|$ which is then pushed through a soft-max to create a probability distribution over $\mathcal{X}$. At the end of the game, regardless of the policy's weights, we set $\widehat{z} = \text{argmax}_{z \in \mathcal{Z}} \langle z, \widehat{\theta} \rangle$ where $\widehat{\theta}$ is the minimum ℓ_2 norm solution to $\text{argmin}_\theta \sum_{s=1}^T (y_s - \langle x_s, \theta \rangle)^2$.

Our policy network is a simple 6-layer MLP, with layer sizes $\{3|\mathcal{X}|, 256, 256, 256, 256, |\mathcal{X}|\}$ where $3|\mathcal{X}|$ corresponds to the input layer and $|\mathcal{X}|$ is the size of the output layer, which is then pushed through a Softmax function to create a probability over arms. In addition, all intermediate layers are activated with the leaky ReLU activation units with negative slopes of .01. For the experiments for 1D thresholds and 20 Questions, they share the same network structure as mentioned above with $|\mathcal{X}| = 25$ and $|\mathcal{X}| = 100$ respectively.

E HYPER-PARAMETERS

In this section, we list our hyperparameters. First we define λ_{binary} to be a coefficient that gets multiplied to binary loses, so instead of $\mathbf{1}\{z^\star(\theta_*) \neq \widehat{z}\}$, we receive loss $\lambda_{\text{binary}} \cdot \mathbf{1}\{z^\star(\theta_*) \neq \widehat{z}\}$. We choose λ_{binary} so that the recieved rewards are approximately at the same scale as SIMPLE REGRET. During our experiments, all of the optimizers are Adam. All budget sizes are $T = 20$. For fairness of evaluation, during each experiment (1D thresholds or 20 Questions), all parameters below are shared for evaluating all of the policies. To elaborate on training strategy proposed in Algorithm 2 more, we divide our training into four procedures, as indicated in Table 3:

- **Init.** The initialization procedure takes up a rather small portion of iterations primarily for the purpose of optimizing for $\mathcal{L}_{\text{barrier}}$ so that the particles converge into the constrained difficulty sets. In addition, during the initialization process we initialize and freeze $w = \vec{0}$, thus putting an uniform distribution over the particles. This allows us to utilize the entire set of particles without w converge to only a few particles early on. To initialize $\widetilde{\Theta}$, we sample $2/3$ of the N particles uniformly from $[-1, 1]^{|\mathcal{X}|}$ and the rest $1/3$ of the particles by sampling, for each $i \in [|\mathcal{Z}|]$, $\frac{N}{3|\mathcal{Z}|}$ particles uniformly from $\{\theta : \operatorname{argmax}_j \langle \theta, z_j \rangle = i\}$. We initialize our policy weights by Xavier initialization with weights sampled from normal distribution and scaled by .01.
- **Regret Training,** $\widetilde{\pi}_i$ Training with SIMPLE REGRET objective usually takes the longest among the Procedures. The primary purpose for this process is to let the policy converge to a reasonable warm start that already captures some essence of the task.
- **Fine-tune** π_i. Training with BEST IDENTIFICATION objective run multiple times for each π_i with their corresponding complexity set Θ_i. During each run, we start with a warm started policy, and reinitialize the rest of the models by running the initialization procedure followed by optimizing the BEST IDENTIFICATION objective.
- **Fine-tune** $\widehat{\pi}$ This procedure optimizes (2), with baselines $\min_k J(\pi_k, t_k)$ evaluated based on each π_i learned from the previous procedure. Similar to fine-tuning each individual π_i, we warm start a policy $\pi_{\lfloor K/2 \rfloor}$ and reinitialize w and Θ by running the initialization procedure again.

Table 3: Number of Iterations and Learning Rates

Procedure	Hyper-parameter	1D Threshold $|\mathcal{X}| = 25$	20 Questions $|\mathcal{X}| = 100$	Jester Joke $|\mathcal{X}| = 100$
Init	N_{it}		20000 (all)	
	ψ learning rate		10^{-4} (all)	
	$\widetilde{\Theta}$ learning rate		10^{-3} (all)	
	w learning rate		0 (all)	
Regret Training	N_{it}		480000 (all)	
	ψ learning rate		10^{-4} (all)	
	$\widetilde{\Theta}$ learning rate		10^{-3} (all)	
	w learning rate		10^{-3} (all)	
Fine-tune π_i	N_{it}		200000 (all)	
	ψ learning rate		10^{-4} (all)	
	$\widetilde{\Theta}$ learning rate		10^{-3} (all)	
	w learning rate		10^{-3} (all)	
Fine-tune π_*	N_{it}	500000	300000	500000
	ψ learning rate		10^{-4} (all)	
	$\widetilde{\Theta}$ learning rate		10^{-3} (all)	
	w learning rate		10^{-3} (all)	
Adam Optimizer	β_1		.9 (all)	
	β_2		.999 (all)	

Table 4: Parallel Sizes and Regularization coefficients

		Experiment	
		1D Threshold	20 Questions
Procedure	Hyper-parameter	$|\mathcal{X}| = 25$	$|\mathcal{X}| = 100$
	N	$1000 \times |\mathcal{Z}|$	$300 \times |\mathcal{Z}|$
	M	1000	500
	L	10	30
Init +	λ_{binary}	7.5	30
Train +	$\lambda_{\text{Pol-reg}}(\text{regret})$	.2	.8
Fine-tune	$\lambda_{\text{Pol-reg}}(\text{fine-tune})$	.3	.8
	$\lambda_{\text{Gen-reg}}$	.05	.1
	λ_{barrier}	10^3	

To provide a general strategy of choosing hyper-parameters, we note that L, firstly, λ_{binary}, $\lambda_{\text{Pol-reg}}$ are primarily parameters tuned for $|\mathcal{X}|$ as the noisiness and scale of the gradients, and entropy over the arms $\mathcal{X}$ grows with the size $|\mathcal{X}|$. Secondly, $\lambda_{\text{Gen-reg}}$ is primarily tuned for $|\mathcal{Z}|$ as it penalizes the entropy over the N arms, which is a multiple of $|\mathcal{Z}|$. Thirdly, learning rate of θ is primarily tuned for the convergence of constraint ρ^* into the restricted class, thus $\mathcal{L}_{\text{barrier}}$ becoming 0 after the specified number of iterations during initialization is a good indicator. Finally, we choose N and M by memory constraint of our GPU. The hyper-parameters for each experiment was tuned with less than 20 hyper-parameter assignments, some metrics to look at while tuning these hyper-parameters includes but are not limited to: gradient magnitudes of each component, convergence of each loss and entropy losses for each regularization term (how close it is to the entropy of a uniform probability), etc.

F   POLICY EVALUATION

When evaluating a policy, we are essentially solving the following objective for a fixed policy π:

$$\max_{\theta \in \Omega} \ell(\pi, \theta)$$

where Ω is a set of problems. However, due to non-concavity of this loss function, gradient descent initialized randomly may converge to a local maxima. To reduce this possibility, we randomly initialize many initial iterates and take gradient steps round-robin, eliminating poorly performing trajectories. To do this with a fixed amount of computational resource, we apply the successive halving algorithm from Li et al. (2018). Specifically, we choose hyperparamters: $\eta = 4$, $r = 100$, $R = 1600$ and $s = 0$. This translates to:

- Initialize $|\widetilde{\Theta}| = 1600$, optimize for 100 iterations for each $\widetilde{\theta}_i \in \widetilde{\Theta}$
- Take the top 400 of them and optimize for another 400 iterations
- Take the top 100 of the remaining 400 and optimize for an additional 1600 iterations

We take gradient steps with the Adam optimizer (Kingma & Ba, 2014) with learning rate of 10^{-3} $\beta_1 = .9$ and $\beta_2 = .999$.

G UNCERTAINTY SAMPLING

We define the symmetric difference of a set of binary vectors, $\text{SymDiff}(\{z_1, ..., z_n\}) = \{i : \exists j, k \in [n] \ s.t., z_j^{(i)} = 1 \wedge z_k^{(i)} = 0\}$, as the dimensions where inconsistencies exist.

Algorithm 3: Uncertainty sampling in very small budget setting

---
1   Input: $\mathcal{X}, \mathcal{Z}$
2   **for** $t = 1, ..., T$ **do**
3      $\widehat{\theta}_{t-1} = \text{argmin}_\theta \sum_{s=1}^{T} (y_s - \langle x_s, \theta \rangle)^2$
4      $\widehat{\mathcal{Z}} = \{z \in \mathcal{Z} : \max_{z' \in \mathcal{Z}} \langle z', \widehat{\theta}_{t-1} \rangle = \langle z, \widehat{\theta}_{t-1} \rangle\}$
5   **if** $|\widehat{\mathcal{Z}}| = 1$ **then**
6          $\widehat{\mathcal{Z}}_t = \widehat{\mathcal{Z}} \bigcup \{z \in \mathcal{Z} : \max_{z' \in (\mathcal{Z} \setminus \widehat{\mathcal{Z}})} \langle z', \widehat{\theta}_{t-1} \rangle = \langle z, \widehat{\theta}_{t-1} \rangle\}$
7   **else**
8          $\widehat{\mathcal{Z}}_t = \widehat{\mathcal{Z}}$
9   **end**
10   Uniformly sample I_t from $\text{SymDiff}(\widehat{\mathcal{Z}}_t)$
11   Pull x_{I_t} and observe y_t
12   **end**

H LEARNING TO ACTIVELY LEARN ALGORITHM

To train a policy under the learning to actively learn setting, we aim to solve for the objective

$$\min_\psi \mathbb{E}_{\theta \sim \widehat{\mathcal{P}}} [\ell(\pi^\psi, \theta)]$$

where our policy and states are parameterized the same way as Appendix D for a fair comparison. To optimize for the parameter, we take gradient steps like (9) but with the new sampling and rollout where $\widetilde{\theta}_i \sim \widehat{\mathcal{P}}$. This gradient step follows from both the classical policy gradient algorithm in reinforcement learning as well as from recent LAL work by Kveton et al. (2020).

Moreover, note that the optimal policy for the objective must be deterministic as justified by deterministic policies being optimal for MDPs. Therefore, it is clear that, under our experiment setting, the deterministic LAL policy will perform poorly in the adversarial setting (for the same reason why SGBS performs poorly).

I 20 QUESTIONS SETUP

Hu et al. (2018) collected a dataset of 1000 celebrities and 500 possible questions to ask about each celebrity. We chose 100 questions out of the 500 by first constructing $\bar{p}'$, $\mathcal{X}'$ and $\mathcal{Z}'$ for the 500 dimensions data, and sampling without replacement 100 of the 500 dimensions from a distribution derived from a static allocation. We down-sampled the number of questions so our training can run with sufficient M and L to de-noise the gradients while being prototyped with a single GPU.

Specifically, the dataset from Hu et al. (2018) consists of probabilities of people answering *Yes / No / Unknown* to each celebrity-question pair collected from some population. To better fit the linear bandit scenario, we re-normalize the probability of getting *Yes / No*, conditioning on the event that these people did not answer *Unknown*. The probability of answering *Yes* to all 500 questions for each celebrity then constitutes vectors $\bar{p}'^{(1)}, ..., \bar{p}'^{(1000)} \in \mathbb{R}^{500}$, where each dimension of a give $\bar{p}'^{(j)}_i$ represents the probability of yes to the ith question about the jth person. The action set $\mathcal{X}'$ is then constructed as $\mathcal{X}' = \{\mathbf{e}_i : i \in [500]\}$, while $\mathcal{Z}' = \{z^{(j)} : [z^{(j)}_i] = \mathbf{1}\{\bar{p}^{(j)}_i > 1/2\}\} \subset \{0, 1\}^{1000}$ are binary vectors taking the majority votes.

To sub-sample 100 questions from the 500, we could have uniformly at random selected the questions, but many of these questions are not very discriminative. Thus, we chose a "good" set of queries based on the design recommended by $\rho_\star$ of Fiez et al. (2019). If questions were being answered noiselessly in response to a particular $z \in \mathcal{Z}'$, then equivalently we have that for this setting

$\theta = 2z - 1$. Since $\rho_\star$ optimizes allocations λ over $\mathcal{X}'$ that would reduce the number of required queries as much as possible (according to the information theoretic bound of (Fiez et al., 2019)) if we want to find a single allocation for all $z' \in \mathcal{Z}$ simultaneously, we can perform the optimization problem

$$\min_{\lambda \in \Delta^{(|X|-1)}} \max_{z' \in \mathcal{Z}'} \max_{z \neq z'} \frac{\|z' - z\|^2_{(\sum_i \lambda_i x_i x_i^T)^{-1}}}{((z' - z)^T (2z' - 1))^2}.$$

We then sample elements from $\mathcal{X}'$ according to this optimal λ without replacement and add them to $\mathcal{X}$ until $|\mathcal{X}| = 100$.

J   JESTER JOKE RECOMMENDATION SETUP

We consider the Jester jokes dataset of Goldberg et al. (2001) that contains jokes ranging from pun-based jokes to grossly offensive. We filter the dataset to only contain users that rated all 100 jokes, resulting in 14116 users. A rating of each joke was provided on a $[-10, 10]$ scale which was shrunk to $[-1, 1]$. Denote this set of ratings as $\hat{\Theta} = \{\theta_i : i \in [14116], \theta_i \in [-1, 1]^{100}\}$, where θ_i encodes the ratings of all 100 jokes by user i. To construct the set of arms $\mathcal{Z}$, we then clustered the ratings of these users to 10 groups to obtain $\mathcal{Z} = \{z_i : i \in [10], z_i \in \{0, 1\}^{100}\}$ by minimizing the following metric:

$$\min_{\mathcal{Z}:|\mathcal{Z}|=10} \sum_{i=1}^{14116} \max_{z_* \in \{0,1\}^{100}} \langle z_*, \theta_i \rangle - \max_{z \in \mathcal{Z}} \langle z, \theta_i \rangle.$$

To solve for $\mathcal{Z}$, we adapt the $k-means$ algorithm, with the metric above instead of the $L-2$ metric used traditionally.