# DEEP HIERARCHICAL-HYPERSPHERICAL LEARNING (DH²L)

## ABSTRACT

Regularization is known to be an inexpensive and reasonable solution to alleviate over-fitting problems arising in inference models, including deep neural networks. In this paper, we propose a hierarchical regularization which preserves the semantic structure of a sample distribution. At the same time, this regularization promotes diversity by imposing distance between parameter vectors enlarged within semantic structures. To generate evenly distributed parameters which is considered less redundant, we constrain them to lie on *hierarchical hyperspheres*. To define a hierarchical parameter space, we propose to reformulate the topology space with multiple hyperspheres. On each hypersphere, a projection is parameterized by two individual parameters. Since maximizing a groupwise and pairwise distance between points on hypersphere is nontrivial (generalized Thomson problem), we propose a new discrete metric integrated with continuous angular metric. The proposed method shows improved generalization performance on extensive experiments using publicly available datasets (CIFAR-10, CIFAR-100, CUB200-2011, and Stanford Cars), especially when the number of super-classes is large.

## 1 INTRODUCTION

Diversity promoting learning has been widely adopted via enlarging pairwise distances (Xie et al., 2018; 2017a; Liu et al., 2018), increasing orthogonality (Xie et al., 2018), reducing covariance between parameters (Xie et al., 2017b), or reducing correlation on feature (Cogswell et al., 2016) to improve generalization performance. Among them, *diversity promoting regularization* (Xie et al., 2017a;b; Liu et al., 2018) by enforcing large diversity between projection parameters achieves a reasonable performance without modifying the model structure. Optimizing the objective function with a covariance matrix in (Xie et al., 2017a;b) is nontrivial. In different circumstances, the diversity promoting regularization via minimizing energy of parameters of deep neural networks has been proposed (Liu et al., 2018). By minimizing a pairwise distance between parameters on hypersphere with the known metric, they achieved the improved generalization performance.

Following an efficient regularization on hypersphere space, we explore further this direction with three main concepts (hierarchical and hyperspherical learning with discrete metrics).
1) *Why hierarchical learning?* Hierarchical inference explains *human intelligence*. In (Kurzweil, 2013), it states that "the neocortex contains about 300 million very general pattern recognizers, arranged in a hierarchy". Applying a hierarchy of multiple classes based on semantic taxonomy is a natural choice to devise *machine intelligence*. Effectiveness of the hierarchical learning can be found in (Verma et al., 2012).

2) *Why hyperspherical learning?* Hypersphere can be represented by a centroid and a radius. Due to the denominator in the unit-length normalization ($\frac{w}{\|w\|}$), the distance defined on the hypersphere converges when the magnitude of $w$ goes infinity while Euclidean distance goes infinity. Due to this bounded property, a hierarchical structure with multiple separated hyperspheres can be defined.

3) *Why discrete metric learning?* If the vector points form discontinuous series with discrete representation (e.g. multi-dimensional binary or ternary), they are isolated from each other with a certain margin. This property may fit with a disconnected manifold or a groupwise space problem. Moreover, to make points to be equidistributed where a pairwise distance is maximized is a nontrivial

Figure 1: Multiple (hyper)spheres as quotient spaces of a topology space on Euclidean space might be found by gluing process with identifying points. Those separated hyperspheres are assumed to be under the quotient space conditions (Tu, 2010). Within an individual (hyper)sphere, projection parameters in deep neural networks preserve a hierarchical structure. The space can be formed in a series: (a), (b), (c), and (d)

task. Because of finite and isolated points, this metric may reduce search efforts to satisfy those constraints using a set of pairwise distance.

In this paper, we propose to apply hierarchical structure to parameter regularization on the multiple groupwise hyperspherical spaces. In order to find an appropriate metric on this space, we explore a discrete angular metric. We examine the proposed method on extensive experimental setups in terms of datasets and deep network models.

## 2 MULTIPLE SEPARATED HYPERSPHERES

Samples observed from the real world may be on disconnected manifolds. In other words, disjoint union of those manifolds could generate the global manifold (Lee, 2000). In this section, we decompose the one space into multiple spaces (manifolds) and re-define the space in terms of hierarchical point of view.

### 2.1 DISCONNECTED MANIFOLD VIA EQUIVALENT RELATIONS

Since it is not suitable to measure a pairwise distance between high dimensional vectors which have the hierarchical structure in the same space, we construct another identification space which includes isolated spaces, from the original space (via equivalence relation (Tu, 2010)). Denote $d$-sphere $\mathbb{S}^d$ to be the set of points that satisfies $\mathbb{S}^d = \{\boldsymbol{w} \in \mathbb{R}^{d+1} : \|\boldsymbol{w}\| = 1\}$. We construct multiple separated hyperspheres using multiple identifying relations. In Figure 1, we use a center vector $\boldsymbol{w}_c$ and a surface vector $\boldsymbol{w}_s$ to define a hypershpere space and a projection parameter $\boldsymbol{w}$.

### 2.2 PRIOR DISTRIBUTION AND REGULARIZATION

To make parameter vectors uniformly distributed on the unit hypersphere, parameters are sampled from the Gaussian normal distribution (Muller, 1959; Harman & Lacko, 2010). This is because the normal distribution is spherically symmetric (Muller, 1959). In a Bayesian point of view, neural networks with Gaussian priors are known to induce an $l^2$-norm regularization (Vladimirova et al., 2019). From two evidences, we know that enforcing the parameters to have the Gaussian prior is important in hyperspherical learning in neural networks. Note that a parameter which is calculated from the difference arithmetic operation with two parameters on the normal Gaussian distribution is on the *normal difference distribution*.

## 3 METHOD

In deep neural networks, the objective function $\mathcal{J}$ with regularization $\mathcal{R}$ in addition to a loss $\mathcal{L}$, $\mathcal{J}_{\mathcal{R}(\mathbf{W})} = \mathcal{L}(\boldsymbol{x}, \mathbf{W}) + \lambda \mathcal{R}(\mathbf{W})$, is optimized to find the optimal $\mathbf{W}$ having a near minimum loss $\mathcal{L}$, $\arg\min_{\mathbf{W}} \mathcal{J}_{\mathcal{R}(\boldsymbol{x}, \mathbf{W})}$, where $\boldsymbol{x} \in \mathbb{R}^{d_0}$ denotes an input vector, $\mathbf{W} = \{\boldsymbol{W}_i \in \mathbb{R}^{d_{i-1} \times c_i} : \boldsymbol{W}_i = \{\boldsymbol{w}_j \in \mathbb{R}^{d_{i-1}}\}, j = 1, \ldots, c_i, i = 1, \ldots, L\}$ denotes a set of parameter matrices (i.e. neurons/kernels), $L$ denotes the number of layers, and $\lambda > 0$ is to control the degree of the regularization. For a classification task, the cross entropy loss is used for the loss function $\mathcal{L}$. We propose a new regularization formulation $\mathcal{R}$ preserving a hierarchical parameter structure in Section 3.1.

(a)       (b)       (c)

Figure 2: (a) A radius of global area converges to $\frac{r_0}{1-\delta}$ ($= \sum_l^\infty r_0\delta^l$: the sum of radius series, assuming $\delta$: constant) as $l$ goes to infinity where $r_0$ is their initial radius and the constant $\delta$ is the ratio between radiuses $\frac{r_l}{r_{l-1}}$ which the absolute value is less than one. (b) The radius of global area is bounded to the initial radius $r_0$ of a series of spheres. This bears a resemblance to the process of repeat of *Hypersphere packing* which arranges non-overlapping spheres within a containing space. (c) Since a bounded space shown in (b) is better to model a hierarchical structure, 2-sphere is defined following (b) and can be generalized to a higher dimensional sphere, hypersphere ($\mathbb{S}^d$, $d \geq 3$).

## 3.1 REGULARIZATION FOR HIERARCHICAL HYPERSPHERICAL HYPOTHESES

Denote $w$ a parameter vector (called a projection parameter, an element of $W$ at a single layer) to transform a given input into an embedding space defined in a Euclidean metric space: $x \in \mathbb{R}^{d+1} \mapsto w^T x \in \mathbb{R}$. By the definition of unit-length projection $\frac{w}{\|w\|}$, a new parameter vector $\hat{w}$ can be defined on $d$-sphere: $\mathbb{S}^d = \{\hat{w} \in \mathbb{R}^{d+1} : \|\hat{w}\| = 1\}$ where $\|\cdot\|$ denotes $l^2$-norm and the center is zero. In other word, the parameter vector $\hat{w}$ can be defined by a center point vector $w_c \in \mathbb{R}^{d+1}$ and a surface vector $w_s \in \mathbb{R}^{d+1}$ using an arithmetic operation: $\hat{w} := w_s - w_c$. We define the $d$-sphere with center and surface vectors: $\mathbb{S}^d_{w_c} = \{w_s - w_c \in \mathbb{R}^{d+1} : \|w_s - w_c\| = 1\}$. For a notation simplicity, we use $w$ instead of $\hat{w}$ hereafter. While we consider a radius equals to 1 for simplicity, the parameter vector can have a radius $r > 0$.

### 3.1.1 HIERARCHICAL PARAMETERS DERIVED FROM LEVELWISE AND GROUPWISE CENTROID VECTORS

We assume that the hierarchical structure consists of levelwise structure with a notation $(l)$ and groupwise structure with a notation $g$ below. We explain these two terms to define parameter vectors serially.

**Levelwise structure** The above parameter vector on $\mathbb{S}^d_{w_c}$ can be defined with the levelwise notation $(l)$ as follows,

$$w^{(l)} := w_s^{(l)} - w_c^{(l)} \tag{1}$$

where the parameter is defined on $l$-th $d$-sphere, $\mathbb{S}^d_{w_c^{(l)}}$. In Figure 2, an example is provided in a lower dimensional space. In this paper, we define the hierarchical parameter in a higher dimensional space than that in (b) and (c) in Figure 2.

In a levelwise setting, $w_s^{(l)}$ and $w_c^{(l)}$ are additively represented based on the center parameter (centroid) calculated from the previous level: $w_c^{(l-1)} + \overrightarrow{\Delta w}^{(l)} \mapsto w_c^{(l)}$, where $w_c^{(l-1)} = \sum_i^{l-1} \overrightarrow{\Delta w}^{(i)}$ is the accumulated center vector and $\overrightarrow{\Delta w}^{(l)}$ denotes a newly connected parameter vector from $w_c^{(l-1)}$ to $w_c^{(l)}$. By denoting $\overrightarrow{\Delta w}^{(l)}$ as $w^{(l,l-1)}$, the center vector at the $l$-level is defined as, $w_c^{(l)} := w_c^{(l,l-1)} + w_c^{(l-1)}$, and the surface vector $w_s^{(l)} := w_s^{(l,l-1)} + w_c^{(l-1)}$. Both the center vector and the surface vector at the current level are based on the center vector at the previous level[1]. Hence, Eq. 1 is equivalent to

$$w^{(l)} = w_s^{(l,l-1)} - w_c^{(l,l-1)}. \tag{2}$$

Note that we use $(l, l-1)$ to denote a connecting parameter from the center parameter at the $(l-1)$th level to parameters at the $(l)$th level.

**Groupwise structure** With a group notation $g_k$, the center parameter in Eq. 2 can be rephrased as $w_{c,g_k}^{(l,l-1)}$, on $\mathbb{S}^d_{w_{c,g_k}^{(l,l-1)}}$ which denotes $d$-sphere of $g_k$ group at $l$-th level, $g^{(l)} := \{g_k\}_{k=1}^{|g^{(l)}|}$.

---

[1] As not every sample has a child sample, it might be more reasonable to branch from representative parameter or center parameter rather than from individual projection parameters.

$g^{(l)} \subseteq \mathbb{G}^{(l)}$ is a group set at the $l$th level, and $|\cdot|$ denotes the cardinality. A group $g^{(l)}$ at the $l$-th level is conditioned on a group at a parent $(l-1)$-th level, $g^{(l-1)} := \{g_{k'}\}_{k'=1}^{|g^{(l-1)}|}$ where $g^{(l-1)} \subseteq \mathbb{G}^{(l-1)}$. With their groupwise relation over levels, an adjacency indication[2] $P^{(l,l-1)}(\{\mathbb{G}^{(l-1)}, \mathbb{G}^{(l)}\}) \in \{0,1\}^{|\mathbb{G}^{(l-1)}| \times |\mathbb{G}^{(l)}|}$ is given. Hence, the parameter vector at the $l$-th level is determined as: $\boldsymbol{w}_{g_k,i}^{(l)} := \boldsymbol{w}_{s,g_k,i}^{(l,l-1)} - \boldsymbol{w}_{c,g_k}^{(l,l-1)}$ on $\mathbb{S}_{\boldsymbol{w}_{c,g_k}^{(l,l-1)}}^d$ where $i = 1, \ldots, |g_k|$, $\{\boldsymbol{w}_{s,g_k,i}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}\} \forall i$ is calculated based on $\boldsymbol{w}_{c,g^{(l-1)}}^{(l-1)}$ referring to the adjacency indication.

A representative vector of the group $g_k$ at the $l$-th level is the center vector $\boldsymbol{w}_{c,g_k}^{(l)}$ and it is equivalent to a mean vector of $\boldsymbol{w}_{s,g_k,i}^{(l)} \forall i$: $\mu(\boldsymbol{w}_{s,g_k,i}^{(l)}) = \frac{1}{|g_k|} \sum_i^{|g_k|} \boldsymbol{w}_{s,g_k,i}^{(l)}$ [3].

### 3.1.2 HIERARCHICAL REGULARIZATION

In this section, we define a regularization term of the hierarchical parameter vectors defined above. A set of parameters $\{\boldsymbol{W}_{s,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k'}^{(l-1)}\} \in \boldsymbol{W} \ \forall g_k, \ \forall g_{k'}$ where $\boldsymbol{W}_{s,g_k}^{(l,l-1)} := \{\boldsymbol{w}_{s,g_k,i}^{(l,l-1)}\}_{i=1}^{|g_k|}$, is an optimizing target of hierarchical regularization term as follows:

$$\mathcal{R}(\boldsymbol{W}) := \sum_l \lambda_l \mathcal{R}_l(\boldsymbol{W}_{s,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}; P^{(l,l-1)}) + \sum_l \mathcal{C}_l(\boldsymbol{w}_{c,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k'}^{(l-1)}; P^{(l,l-1)}) \quad (3)$$

where $\mathcal{R}_l$ works on individual spheres $\mathbb{S}_{\boldsymbol{w}_{c,g_k}^{(l,l-1)}}^d$, $\lambda_l > 0$, and $\mathcal{C}_l$ aims to apply geometry-aware constraints across spheres. $\mathcal{R}_l$ consists of two parts of regularization terms with: 1) $\mathcal{R}_{l,p}$ for projection parameter vectors in the same group $g_k$ on $\mathbb{S}_{\boldsymbol{w}_{c,g_k}^{(l,l-1)}}^d$ and 2) $\mathcal{R}_{l,c}$ for center parameter vectors across the groups in the same level on $\mathbb{S}_{\boldsymbol{w}_{c,g_k'}^{(l-1)}}^d$,

$$\mathcal{R}_l(\boldsymbol{W}_{s,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}) := \mathcal{R}_{l,p}(\boldsymbol{W}_{s,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}) + \mathcal{R}_{l,c}(\boldsymbol{w}_{c,g_k}^{(l,l-1)}), \quad (4)$$

where

$$\mathcal{R}_{l,p}(\boldsymbol{W}_{s,g_k}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}) := \frac{1}{|g^{(l)}|} \frac{2}{|\mathbb{G}|(|\mathbb{G}|-1)} \sum_{\{g_k \in g^{(l)}\}} \sum_{\{i \neq j \in g_k\}} d(\boldsymbol{w}_{g_k,i}^{(l,l-1)}, \boldsymbol{w}_{g_k,j}^{(l,l-1)}), \quad (5)$$

$$\mathcal{R}_{l,c}(\boldsymbol{w}_{c,g_k}^{(l,l-1)}) := \frac{2}{|\mathbb{C}|(|\mathbb{C}|-1)} \sum_{\mathbb{M}} d(\boldsymbol{w}_{c,g_i}^{(l,l-1)}, \boldsymbol{w}_{c,g_j}^{(l,l-1)}), \quad (6)$$

where $\boldsymbol{w}_{g_k,i}^{(l,l-1)} := \boldsymbol{w}_{s,g_k,i}^{(l,l-1)} - \boldsymbol{w}_{c,g_k}^{(l,l-1)}$, ($\boldsymbol{w}_{g_k,j}^{(l,l-1)}$ is similarly defined), $\mathbb{G} = \{i \neq j \in g_k\}$, $\mathbb{C} = \{g_i \neq g_j \in g^{(l)}\}$, and $d(\cdot, \cdot)$ denotes a distance metric between the parameter vectors. The distance metric is defined in Section 3.2. We explain these parameter vectors and pairwise distances formulating regularization terms in Figure 4 in Appendix. When a mini-batch of inputs ($m_x$: a set of inputs $\{\boldsymbol{x}_i\}$ ) is given, the regularization term becomes: $\mathbb{E}(\mathcal{R}(\boldsymbol{W})) = \frac{1}{|m_x|} \sum_{m_x} \mathcal{R}(\boldsymbol{W}; m_x)$.

The constraint term help construct geometry-aware relational parameters between different spheres on the same level and on the across levels. Multiple constraints are defined as $\mathcal{C}_l := \sum_k \lambda_k \mathcal{C}_{l,k}$, where $\mathcal{C}_{l,k}$ is $k$th constraint between parameters at $l$th and $(l-1)$th, and $\lambda_k > 0$ is a Lagrange multiplier. We apply three constraints in a geometric point of view. The detailed formulation is defined in appendix.

### 3.2 DISCRETE AND CONTINUOUS ANGULAR DISTANCE METRIC

Discrete (code) product metric might be a good fit with the above group-wise definition. We expect that a projected point from the parameters formed in a discrete metric space, are isolated from each other. In Figure 3, discrete distance helps a distribution of pairs having the same angle distance to be diversified. In order to maximize the distance between the parameters, maximization of discrete distance could help the distribution of parameters diverse.

---

[2]This can be replaced with a probability model.

[3]The center vector for the group $g_k$ can be determined by a parameter vector at the $(l-1)-th$ level using an adjust factor ($\epsilon$, $|\epsilon| < 1$): $\boldsymbol{w}_{c,g_k}^{(l,l-1)} = \epsilon \cdot \boldsymbol{w}_{g_{k'},i}^{(l-1)}$, where $\boldsymbol{w}_{g_{k'},i}^{(l-1)} \in \mathbb{S}_{\boldsymbol{w}_{c,g_k'}^{(l-1)}}^d$.

Using parameter vectors $\boldsymbol{w}_i$ and $\boldsymbol{w}_j$ in $\mathbb{R}^{d+1}$, we define a discrete distance metric using a sign function as follows:

$$D_h := \frac{1}{d}\sum_k^d sign(\boldsymbol{w}_i(k)) \cdot sign(\boldsymbol{w}_j(k)), \tag{7}$$

where $sign(x) := \begin{cases} 1, & \text{if } x \geq 0 \\ -1, & \text{otherwise} \end{cases}$, $-1 \leq D_h \leq 1$, and $\boldsymbol{w} = \{\boldsymbol{w}(k) \mid \forall k = 1,\ldots,d\} \in \mathbb{R}^{d+1}$. This is a normalized version of Hamming distance. For a ternary discrete, $\{-1,0,1\}$ is used. In order to consider the discrete distance as an angle distance within $[0,1]$, normalized one is defined as $D_{h01} := \frac{-D_h+1}{2}, 0 \leq D_{h01} \leq 1$. The angle distance based on the above product can be rephrased as $\theta_{D_h} = D_{h01}$[4] where $0 \leq \theta_{D_h} \leq 1$.

Figure 3: While the pairwise angle distances $D_a$ between a pair of vectors $\{\boldsymbol{w}_1,\boldsymbol{w}_2\}$ and $\{\boldsymbol{w}_2,\boldsymbol{w}_3\}$ are the same, the pairwise discrete product distances $D_h$ between vectors are different. To diversify a parameter space, the space with sign could be effective to recognize their difference.

As the discrete distance could underestimate to approximate the model distribution, we merge the above discrete distance metric with continuous angle distance metric ($\theta = \frac{1}{\pi}\arccos\big(\frac{\boldsymbol{w}_i \cdot \boldsymbol{w}_j}{\|\boldsymbol{w}_i\|\|\boldsymbol{w}_j\|}\big), 0 \leq \theta \leq 1$) into the single metric. We simply use the definition of Pythagorean means which consist of the arithmetic mean (AM), the geometric mean (GM), and the harmonic mean (HM). Pythagorean means using the above angle pair is defined as follows:

$$D_{\text{AM}} := \frac{\theta_{D_h}+\theta}{2}, \quad D_{\text{GM}} := \theta_{D_h}\theta, \quad D_{\text{HM}} := \frac{4\theta_{D_h}\theta}{\theta_{D_h}+\theta}. \tag{8}$$

In the angular distance[5] using $\{\theta_{D_h},\theta\}$, a reversed form $1 - D_{\{\theta_{D_h},\theta\}}$ is adopted to maximize an angle in optimization formulation as a form of minimization instead of $(\cdot)^{-s}$ where $s = 1,2,\ldots$ which is used in Thomson problem that utilizes $s$-energy (Brauchart & Grabner, 2015). The cosine similarity of these angles can be defined as follows:

$$D_{\cos(\text{AM})} := \cos\big(\frac{\theta_{D_h}+\theta}{2}\pi\big), D_{\cos(\text{GM})} := \cos\big(\theta_{D_h}\theta\pi\big), D_{\cos(\text{HM})} := \cos\big(\frac{4\theta_{D_h}\theta}{\theta_{D_h}+\theta}\pi\big), \tag{9}$$

then the cosine similarity functions are normalized with $\frac{\cos(\cdot)+1}{2}$ to have a distance value within $[0,1]$. Finally, Pythagorean means of each cosine similarity can be calculated as follows:

$$D_{\text{AM}_{\cos}} := \frac{\cos\theta_{D_h}\pi+\cos\theta\pi+2}{4}, D_{\text{GM}_{\cos}} := \frac{(\cos\theta_{D_h}\pi+1)(\cos\theta\pi+1)}{4}, D_{\text{HM}_{\cos}} := \frac{(\cos\theta_{D_h}\pi+1)(\cos\theta\pi+1)}{\cos\theta_{D_h}+\cos\theta+2}.$$
$$\tag{10}$$

The above metric functions defined in (8), (9), and (10) satisfy the metric conditions: non-negativity, symmetry, and triangle inequality. The distance using the above metric functions between any two points is bounded, because the hypersphere is a compact manifold.

### 3.3 GRADIENTS AND BACKPROPAGATION

As the sign function is not differentiable at the value 0, we adopt alternative backpropagation function. We adopt straight-through estimator (STE) (Bengio et al., 2013) in the backward path of the neural networks for the sign function in the discrete metric. The derivative of the sign function is substituted with $1_{|w|\leq 1}$ in the backward pass, known as the saturated STE. As the derivative of $\arccos(x)$ ($\frac{-1}{\sqrt{1-x^2}}$) is undefined at the value $x = \pm 1$, we apply clamping to the cosine function to have $x \in [-0.99, 0.99]$[6] where $x = \cos(\theta\pi), 0 \leq \theta \leq 1$.

## 4 EXPERIMENTS

### 4.1 EXPERIMENTAL SETUP

**Datasets** We conduct experiments using four publicly available datasets including small size images (CIFAR-10 and CIFAR-100) and large size images (CUB200-2011 (Wah et al., 2011) and

---

[4]On the other hand, the angle can be considered as a cosine similarity directly, $D_h := \cos\theta_{D_h}\pi$. So as to get the angle distance, it needs an arccosine function $\theta_{D_h} = \frac{1}{\pi}\arccos D_h$. In summary, for the angle distance $\theta_{D_h}$, either "$D_{h01}$" or "$D'_{h01} = \frac{1}{\pi}\arccos D_h$" where $0 \leq D_{h01} \leq 1$, can be adopted.

[5]In $0 \leq \theta \leq 1$, the angle and its cosine value show an inverse relationship:$0 \leq \theta \leq 1 \rightarrow 1 \geq \cos\theta\pi \geq -1$.

[6]$x = \{0.99 \cdot 1_{x>0.99}, x, -0.99 \cdot 1_{x<-0.99}\}$

Stanford-Cars (Krause et al., 2013b), shortly CUB200 and Cars respectively). CIFAR-10 dataset is used to validate effectiveness of the proposed metric without hierarchical information. Except CIFAR-10, we use two-level hierarchy pairs $\{parent, child\}$ for the proposed hierarchical regularization on three datasets. In Table 7 at Appendix, statics of datasets in detail is provided.

**Deep neural network models and training setting**   We used the deep residual neural networks (*resnet*) (He et al., 2016) with different sizes of parameters (weights) dependent on an image size of datasets. For a small size input ($32 \times 32$ pixels) such on CIFAR-10 and CIFAR-100, we used *resnet* with smaller number of parameters (light models, resnet-20 (0.29M) and resnet-110 (1.73 M)) so as not to have redundant parameters leading to over-fitting. For a fine-grained input ($224 \times 224$ pixels) such on CUB200 and Cars, The original resnet with larger number of parameters (heavy models[7], Resnet-18 (11.28M) and Resnet-50 (23.91M)).

In training with the hierarchical regularization, we assume that the global hierarchical structure is not given. Instead, stochastic or partial hierarchical structure is shown within each mini-batch by the hierarchy pairs. Mini-batches, 512 for light models and 256 for heavy models, are used in the SGD optimizer. We applied hierarchical regularization in the FC layer of the resnet. Even though SGD is known as an unbiased estimation, a stochastic hierarchical structure could affect the overall approximation performance upon the class distribution within the minibatch. Settings in more detail are provided in Appendix.

**Baseline setting**   In terms of the regularization, we used three settings, called 'baseline', 'baseline+$l^2$', and 'E' for a reference. First, in 'baseline', we examine neural networks without regularization. Then, in 'baseline+$l^2$', we adopt $l^2$-norm minimization regularization (which is equivalent to a weight decay in SGD setting (Zhang et al., 2019)) via $\lambda_f \sum_k \|\boldsymbol{w}_k\|$, where $\boldsymbol{w}_k \in \boldsymbol{W}$ and $\lambda_f > 0$ in addition to 'baseline'. Lastly, in 'E', energy minimization (Liu et al., 2018), diversity promoting regularization without hierarchical information, via $\lambda_e \sum_{i \neq j} d(\boldsymbol{w}_i, \boldsymbol{w}_j)$, where $d(\cdot, \cdot)$ is a pairwise distance and $\lambda_e > 0$, is added to baseline+$l^2$. When the proposed hierarchical regularization (Eq. 4) is applied on the FC layer, we named it as 'H'. Hence, the regularization is incrementally adopted to the baseline: $l^2$+'E'+'H'. In terms of a distance metric, we compared the proposed metric with other continuous metrics such as Euclidean distance with the unit-length projection ('N-euclidean2', $\sum_{i \neq j} \|\frac{\boldsymbol{w}_i}{\|\boldsymbol{w}_i\|} - \frac{\boldsymbol{w}_i}{\|\boldsymbol{w}_i\|}\|^{-2}$)[8], angular distance ('angular2', $\sum_{i \neq j} \arccos{(\frac{\boldsymbol{w}_i \cdot \boldsymbol{w}_j}{\|\boldsymbol{w}_i\|\|\boldsymbol{w}_j\|})}^{-2}$) where '2' is from Riesz $s$-energy shown higher accuracy, and cosine distance ('cosine', $1 - \sum_{i \neq j} \frac{\boldsymbol{w}_i \cdot \boldsymbol{w}_j}{\|\boldsymbol{w}_i\|\|\boldsymbol{w}_j\|}$).

## 4.2   RESULTS

**Low resolution object classification**   In Table 1, we showed test accuracy (%) using different metrics with energy minimization regularization without hierarchical regularization[9] along a weight decay ($l^2$-norm) using CIFAR-10 and resnet-20. 'baseline' method is examined without or with the weight decay. The discrete angular metric based regularization ($D_h^{ter}$ (ternary code), $D_h^{bin}$ (binary code), $D_{\cos{(\text{HM})}}$, and $D'_{\text{HM}_{\cos}}$) on the baseline can improve the generalization performance in term of test accuracy compared to the other continuous metrics such as N-euclidean2, angular2, and cosine. Due to the unit-length projection in N-euclidean2, their performance is comparable to that other angular metrics. $D'$ denotes a distance used $D'_h$ from footnote 4 in Section 3.2. The regularization terms are applied over all layers except the Batch Normalization (BN) layers. As explained in (van Laarhoven, 2017; Zhang et al., 2019), $l^2$-norm minimization based regularization (weight decay) showed much improvement due to their effective learning rate in SGD.

As shown in Table 2, the regularization with proposed metrics shows better accuracy performance than that of the baseline on both resnet-20 and resnet-110 using CIFAR-100 dataset. Comparing to the baseline+$l^2$, with energy minimization 'E' regularization, metrics such as $D_h^{ter}$, $D_{\cos(\text{AM})}$, and $D'_{\cos(\text{HM})}$ showed better performance than other metrics. If the proposed hierarchical 'H' regularization is applied, the generalization performance is improved further in most metric cases on both

---

[7]which is available at the pytorch library

[8]$= \sum_{i \neq j} (2 - 2 \frac{\boldsymbol{w}_i \cdot \boldsymbol{w}_j}{\|\boldsymbol{w}_i\|\|\boldsymbol{w}_j\|})^{-1}$

[9]This is because that hierarchy information is not included in CIFAR-10.

Table 1: Test accuracy (%) using different metrics with energy minimization without hierarchy information along $l^2$-norm minimization (weight decay) on CIFAR-10 and resnet-20.

| metric \ $l^2$ | $\times$ | $\circ$ |
|---|---|---|
| baseline | 90.34 | 92.21 |
| N-euclidean2 | 90.93 | 92.35 |
| angular2 | 90.47 | 92.38 |
| cosine | 90.53 | 92.40 |
| $D_h^{ter}$ | 90.67 | 92.48 |
| $D_h^{bin}$ | 90.67 | 92.48 |
| $D_{\cos(HM)}$ | 90.84 | 92.93 |
| $D'_{HM_{\cos}}$ | 90.94 | 92.69 |

Table 2: Test accuracy (%) using different metrics with energy minimization ('E') and hierarchical regularization ('H') on CIFAR-100: 'E' / 'E+H' respectively.

| metric \ db | resnet-20 | resnet-110 |
|---|---|---|
| baseline | 63.86 | 62.02 |
| baseline+$l^2$ | 68.03 | 72.90 |
| N-euclidean2 | 67.59 / 68.65 | 73.95 / 73.96 |
| angular2 | 67.83 / 67.76 | 74.40 / 73.89 |
| cosine | 68.11 / 68.45 | 73.37 / 73.37 |
| $D_h^{ter}$ | 68.44 / 68.68 | 73.73 / 73.97 |
| $D_h^{bin}$ | 68.52 / 68.69 | 73.97 / 74.26 |
| $D_{AM}$ | 68.58 / 68.86 | 73.43 / 73.50 |
| $D_{\cos(AM)}$ | 68.58 / 68.60 | 73.14 / 73.65 |
| $D'_{\cos(AM)}$ | 67.57 / 68.36 | 73.14 / 73.72 |
| $D'_{\cos(HM)}$ | 68.62 / 68.65 | 73.07 / 73.65 |

Table 3: Test accuracy (%) using different metrics with energy minimization ('E') and hierarchical regularization ('H') on CUB200: 'E' / 'E+H' respectively.

| metric \ db | Resnet-18 | Resnet-50 |
|---|---|---|
| baseline | 72.17 | 74.21 |
| baseline+$l^2$ | 72.29 | 74.05 |
| N-euclidean2 | 72.61 / 75.99 | 73.49 / 76.14 |
| angular2 | 72.43 / 76.11 | 73.55 / 76.66 |
| cosine | 72.12 / 75.64 | 73.26 / 76.85 |
| $D_h^{ter}$ | 72.58 / 75.99 | 73.57 / 76.37 |
| $D_h^{bin}$ | 72.55 / 76.21 | 73.57 / 76.99 |
| $D_{AM}$ | 73.04 / 76.02 | 73.88 / 75.95 |
| $D_{AM_{\cos}}$ | 72.31 / 76.14 | 73.59 / 77.32 |
| $D'_{AM_{\cos}}$ | 72.28 / 75.37 | 72.42 / 74.12 |
| $D_{GM}$ | 72.90 / 76.35 | 74.16 / 75.30 |
| $D'_{HM_{\cos}}$ | 72.55 / 76.11 | 74.64 / 76.94 |
| $D'_{\cos(HM)}$ | 72.55 / 76.32 | 72.86 / 76.56 |

Table 4: Test accuracy (%) using different metrics with energy minimization ('E') and hierarchical regularization ('H') on Cars: 'E' / 'E+H' respectively.

| metric \ db | Resnet-18 | Resnet-50 |
|---|---|---|
| baseline | 85.10 | 87.99 |
| baseline+$l^2$ | 85.58 | 87.92 |
| N-euclidean2 | 85.48 / 85.56 | 87.96 / 87.97 |
| angular2 | 85.11 / 85.13 | 88.34 / 87.85 |
| cosine | 85.57 / 85.73 | 88.01 / 87.86 |
| $D_h^{ter}$ | 85.35 / 85.99 | 85.35 / 88.07 |
| $D_h^{bin}$ | 86.22 / 85.99 | 88.32 / 88.14 |
| $D_{AM}$ | 85.66 / 85.66 | 88.39 / 88.11 |
| $D_{AM_{\cos}}$ | 85.52 / 86.05 | 87.92 / 88.57 |
| $D'_{AM_{\cos}}$ | 85.76 / 86.43 | 88.07 / 87.96 |
| $D'_{\cos(AM)}$ | 85.54 / 85.52 | 88.22 / 88.13 |

resnet-20 and resnet-110. As the binary metric shows a better performance than that ternary, we adopt binary discretization for proposed angular metrics ($D_\bullet$, $D_{\cos(\bullet)}$, and $D_{\bullet_{\cos}}$) in experiments.

**Fine-grained visual categorization** In this experiment, we used two large size image datasets with a fine-grained category. One is with birds (CUB200) and another is with cars (Cars) that focus on single species of objects. A hierarchy of CUB200 is defined by the academic expert on birds whereas that of Cars is categorized manually based on a name of cars by a non-expert. The rate between the number of superclass (parent) per subclass of CUB200 (0.35) is much larger than that of Cars (0.0459) (as shown in Table 7 at Appendix). That rate of Cars is even smaller than that of CIFAR-100.

As shown in Table 3, the proposed hierarchical regularization significantly improve the test accuracy over all metrics on both Resnet-18 and Resnet-50. Compared to CUB200, as shown in Table 4, the improvement of the proposed method is not that significant using Cars dataset. This might be because CUB200 dataset has not only better the hierarchical categorization by the expert but also more dirversitified pairs between the superclass and the subclass.

**Ablation study** In Table 5, we showed how the metrics affect the generalization performance using resnet-20 and CIFAR-100 dataset.. The proposed method showed significantly improved performance compared to the baseline+$l^2$. Individual averaging settings (AM, GM, and HM) show different improvement patterns.

In Table 6, we showed how heterogeneous metrics between convolutional (conv.) layers (with the energy minimization, 'E') and fully connected (FC) layers (with the hierarchical 'H' regularization, 'H') affect the generalization performance using resnet-20 and CIFAR-100 dataset. The cases applying hierarchical regularization showed better performance than that the baseline applying only energy minimization regularization. In this experiment, a combination GM and HM shows a better improvement than that other combinations.

Table 5: Test accuracy (%) using different metrics with energy minimization ('E') and hierarchical regularization ('H') on CIFAR-100 and resnet-20.

| metric | |
|---|---|
| baseline+$l^2$ | 68.03 |
| $D'_{AM}$ | 68.64 |
| $D'_{GM}$ | 68.70 |
| $D'_{HM}$ | 68.80 |
| $D_{AM_{cos}}$ | 69.24 |
| $D_{GM_{cos}}$ | 68.55 |
| $D_{HM_{cos}}$ | 68.77 |
| $D'_{AM_{cos}}$ | 68.96 |
| $D'_{GM_{cos}}$ | 69.00 |
| $D'_{GM_{cos}}$ | 68.83 |

Table 6: Test accuracy (%) using heterogeneous metrics on Conv. layers and FC layer respectively, with energy minimization ('E') and hierarchical regularization ('H') on CIFAR-100 and resnet-20.

| metrics (in conv., in FC) | |
|---|---|
| baseline+$l^2$ | 68.03 |
| $(D_{GM}, \text{null})$ | 68.22 |
| $(D_{GM}, D_{AM})$ | 68.58 |
| $(D_{GM}, D_{GM})$ | 68.62 |
| $(D_{GM}, D_{HM})$ | 69.04 |
| $(D_{GM}, D_{AM})$ | 68.62 |
| $(D_{GM}, D_{GM})$ | 68.65 |
| $(D_{GM}, D_{HM})$ | 68.70 |

## 5 RELATED WORKS

Promoting of diversity on embedding space or model parameters is widely adopted concept in machine learning related area to improve the generalization performance (Cogswell et al., 2016; Yang et al., 2019; Li et al., 2012; Ratzlaff & Fuxin, 2019; Xie et al., 2017b; 2018; 2017a; Liu et al., 2018). The diversity exists at a variety of levels such as in a feature level (Cogswell et al., 2016; Xie et al., 2018), in a projection parameter level (Xie et al., 2017a; Liu et al., 2018), in a model ensemble level (Zhou et al., 2018; Ratzlaff & Fuxin, 2019), in a latent space model level (Ratzlaff & Fuxin, 2019; Liu et al., 2018), or in a generative model level (Yang et al., 2019; Ratzlaff & Fuxin, 2019). Among the above approaches, enlarging pairwise distance between features (Xie et al., 2018) requires computational efforts due to their covariance matrix. In (Xie et al., 2017b), to optimize the solution, unit-eigenvalue is utilized via singular value decomposition. To optimize a direction and magnitude of the parameter vector alternatively, an alternating direction method of multipliers (ADMM) (Xie et al., 2017a) is used.

In terms of learning on hyperspherical space, (Liu et al., 2017) proposed that hyperspherical convolution (SphereCov) replaces the traditional inner-product based convolution in order to conduct learning angular representation on hyperspheres. To maximize distances between parameters, Minimum Hyperspherical Energy (Liu et al., 2018), is proposed to regularization methods to make parameters equidistributed globally.

In terms of hierarchical learning, (Nickel & Kiela, 2017) and (Ganea et al., 2018) proposed to apply hyperbolic spaces to embed the data in deep neural networks. They showed that learning representations in the hyperbolic space is effective to the data preserving a latent hierarchy compared to non-Euclidean space. Different from these works for representation learning, our proposed method is focused on regularization learning using explicit (predefined) hierarchy information.

## 6 CONCLUSION

We proposed the regularization method, which maximize pairwise distance between parameters preserving hierarchical structure. To define a hierarchical parameter space, we reformulated the topology space with multiple hypersphere spaces. On each hypersphere, a projection is parameterized by the surface parameter with the center parameter. By imposing maximum a pairwise angular distance between the projection parameters, diversity of parameters preserving semantic structure was promoted. For the angular distance metric in multiple separated spaces, we proposed a discrete metric integrated with a continuous metric. Extensive experiments using publicly available datasets, the deep neural network with our proposed regularization method showed superior classification performance, especially when the number of super-classes is large. For further exploration in future, our proposed method can be combined with hierarchical representation learning such as hyperbolic (or Poincaré) embeddings.

## REFERENCES

Y. Bengio, Nicholas Lonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv*, Aug. 2013.

Johann S. Brauchart and Peter J. Grabner. Distributing many points on spheres. *J. Complex.*, 31(3): 293–326, June 2015.

Michael Cogswell, Faruk Ahmed, Ross B. Girshick, Larry Zitnick, and Dhruv Batra. Reducing Overfitting in Deep Networks by Decorrelating Representations. In *International Conference on Learning Representations*, 2016.

Octavian Ganea, Gary Becigneul, and Thomas Hofmann. Hyperbolic neural networks. In *Advances in Neural Information Processing Systems 31*, pp. 5345–5355. 2018.

Radoslav Harman and Vladimr Lacko. On decompositional algorithms for uniform sampling from n-spheres and n-balls. *Journal of Multivariate Analysis*, 101(10):2297 – 2304, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pp. 770–778, 2016.

Jonathan Krause, Jun Deng, Michael Stark, and Li Fei-Fei. Collecting a large-scale dataset of fine-grained cars. In *Second Workshop on Fine-Grained Visual Categorization (FGVC2)*, 2013a.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *4th International IEEE Workshop on 3D Representation and Recognition (3dRR-13)*, Sydney, Australia, 2013b. Ddataset available at `http://imagenet.stanford.edu/internal/car196/`.

Ray Kurzweil. *How to Create a Mind: The Secret of Human Thought Revealed*. Penguin Books, New York, NY, USA, 2013.

J.M. Lee. *Introduction to Topological Manifolds*. Graduate texts in mathematics. Springer, 2000.

Nan Li, Yang Yu, and Zhi-Hua Zhou. Diversity regularized ensemble pruning. In *Proceedings of the 2012th European Conference on Machine Learning and Knowledge Discovery in Databases - Volume Part I*, ECMLPKDD'12, pp. 330–345, 2012.

Weiyang Liu, Yan-Ming Zhang, Xingguo Li, Zhiding Yu, Bo Dai, Tuo Zhao, and Le Song. Deep hyperspherical learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 3950–3960, 2017.

Weiyang Liu, Rongmei Lin, Zhen Liu, Lixin Liu, Zhiding Yu, Bo Dai, and Le Song. Learning towards minimum hyperspherical energy. In *Proceedings of the 32Nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 6225–6236, USA, 2018. Curran Associates Inc.

Mervin E. Muller. A note on a method for generating points uniformly on n-dimensional spheres. *Commun. ACM*, 2(4):19–20, April 1959.

Maximillian Nickel and Douwe Kiela. Poincaré embeddings for learning hierarchical representations. In *Advances in Neural Information Processing Systems 30*, pp. 6338–6347. 2017.

Neale Ratzlaff and Li Fuxin. HyperGAN: A generative model for diverse, performant neural networks. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97, pp. 5361–5369, 09–15 Jun 2019.

L.W. Tu. *An Introduction to Manifolds*. Universitext. Springer New York, 2010.

Twan van Laarhoven. L2 regularization versus batch and weight normalization. *arXiv preprint*, arXiv:1706.05350, 2017.

N. Verma, D. Mahajan, S. Sellamanickam, and V. Nair. Learning hierarchical similarity metrics. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2280–2287, June 2012.

Mariia Vladimirova, Jakob Verbeek, Pablo Mesejo, and Julyan Arbel. Understanding priors in Bayesian neural networks at the unit level. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6458–6467, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical Report CNS-TR-2011-001, California Institute of Technology, 2011. Dataset available at `http://www.vision.caltech.edu/visipedia-data/CUB-200-2011/`.

Pengtao Xie, Yuntian Deng, Yi Zhou, Abhimanu Kumar, Yaoliang Yu, James Zou, and Eric P. Xing. Learning latent space models with angular constraints. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, pp. 3799–3810, 2017a.

Pengtao Xie, Aarti Singh, and Eric P. Xing. Uncorrelation and evenness: A new diversity-promoting regularizer. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 3811–3820. JMLR.org, 2017b.

Pengtao Xie, Wei Wu, Yichen Zhu, and Eric P. Xing. Orthogonality-promoting distance metric learning: Convex relaxation and theoretical analysis. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, pp. 5399–5408, 2018.

Dingdong Yang, Seunghoon Hong, Yunseok Jang, Tiangchen Zhao, and Honglak Lee. Diversity-sensitive conditional generative adversarial networks. In *International Conference on Learning Representations*, 2019.

Guodong Zhang, Chaoqi Wang, Bowen Xu, and Roger Grosse. Three mechanisms of weight decay regularization. In *International Conference on Learning Representations*, 2019.

Tianyi Zhou, Shengjie Wang, and Jeff A Bilmes. Diverse ensemble evolution: Curriculum data-model marriage. In *Advances in Neural Information Processing Systems 31*, pp. 5905–5916. Curran Associates, Inc., 2018.

## APPENDIX

**Dataset acquisition details**  CIFAR-100 dataset provides their labels. In CUB200 dataset, the pairs can be extracted from their filename. In Cars dataset, we parsed each fine label to one of nine coarse vehicle types, such as "Sedan", "SUV", "Van" and etc., following (Krause et al., 2013a).

Table 7: Statistics of benchmark datasets

| Dataset | #classes $\{pa, ch\}$ | #train | #test | input size | #samples /class | #super /subclass |
|---------|----------|--------|-------|------------|---------|---------|
| CIFAR-10 | $\{1, 10\}$ | 50,000 | 10,000 | $32 \times 32$ | 5000.00 | 0.1000 |
| CIFAR-100 | $\{20, 100\}$ | 50,000 | 10,000 | $32 \times 32$ | 500.00 | 0.2000 |
| CUB200 | $\{70, 200\}$ | 5,994 | 5,794 | $224 \times 224$ | 29.97 | 0.3500 |
| Cars | $\{9, 196\}$ | 8,144 | 8,041 | $224 \times 224$ | 41.55 | 0.0459 |

**Deep neural network models and training details**  First, resnet-20 (0.29M) and resnet-110 (1.73 M), which include a combination of Basic blocks with output channels $[16, 30, 64]$ are adopted for light models. An input dimensionality of the fully connected (FC) layer (a classier) is 64 for both resnet-20 and resnet-110. Second, heavy models are adopted such as Resnet-18 (11.28M[10]) and Resnet-50 (23.91M) which consists of the basic blocks (Resnet-18) or the bottleneck blocks with

---

[10]Dependent on the number of classes and the corresponding center parameters, the size could variate (e.g. 11.42M for CUB200, 11.31M for Cars).

output channels [64, 128, 256, 512] in Conv. layers. An input dimensionality of the FC layer is 512 for Resnet-18 and 2048 for Resnet-50.

The networks are optimized with SGD for both light and heavy models: we fixed 1) the weight initialization with Random-Seed number 0 in pytorch, 2) learning rate schedule [0.1, 0.01, 0.001], 3) with momentum 0.9, 4) regularization: $l^2$-norm minimization with $\lambda_f = 0.0005$, 5) orthogonalization $\lambda_o = 0.0001$, energy minimization $\lambda_e = \{0.1, 1\}$, and hierarchical minimization $\lambda_l = 0.1 \times \{1, 5\}$. All the regularization is not applied to the parameters of Batch Normalization (BN) layers, since BN is also a regularization function. A bias term in the FC layer is not used. The images in training and test, images are resized to 256 size. The images is cropped with $224 \times 224$ size at random location in training and at center location in test. Horizontal flipping is applied in training. The light models are trained from scratch without the pretrained weights for 300 epochs. The heavy model is trained using pretrained model provided by pytorch library[11] with 100 epochs. The experiments are conduced using GPU "NVIDIA TESLA P40".

Figure 4: $\mathcal{R}_{l,p}(\boldsymbol{W}_{s,g_i}^{(l,l-1)}, \boldsymbol{w}_{c,g_i}^{(l,l-1)}) = d(\boldsymbol{w}_{g_i,n}^{(l,l-1)}, \boldsymbol{w}_{g_i,m}^{(l,l-1)}) + d(\boldsymbol{w}_{g_i,m}^{(l,l-1)}, \boldsymbol{w}_{g_i,k}^{(l,l-1)}) + d(\boldsymbol{w}_{g_i,k}^{(l,l-1)}, \boldsymbol{w}_{g_i,n}^{(l,l-1)}) + \ldots$ corresponds to Eq (5) and $\mathcal{R}_{l,c}(\boldsymbol{w}_{c,g_k}^{(l,l-1)}) = d(\boldsymbol{w}_{c,g_i}^{(l,l-1)}, \boldsymbol{w}_{c,g_j}^{(l,l-1)}) + d(\boldsymbol{w}_{c,g_j}^{(l,l-1)}, \boldsymbol{w}_{c,g_k}^{(l,l-1)}) \ldots$ corresponds to Eq (6)

***Constraints* in Eq. 3**   $\mathcal{C}_l := \sum_k \lambda_k \mathcal{C}_{l,k}$ can be given as follows:

1. *Constraint 1* ($\mathcal{C}_1$): This constraint describes that a radius of an inner sphere must be smaller than that of its outer sphere.
   $$r^{(l-1)} - r^{(l)} \geq 0 \Rightarrow \|\boldsymbol{w}^{(l-1)} - \boldsymbol{w}^{(l)}\| = \|\boldsymbol{w}_s^{(l-1)} - \boldsymbol{w}_c^{(l-1)}\| - \|\boldsymbol{w}_s^{(l)} - \boldsymbol{w}_c^{(l)}\| \geq 0.$$

2. *Constraint 2* ($\mathcal{C}_2$): This constraint describes that a center of an inner sphere must be located in its outer sphere.
   $$r^{(l-1)} - (\|\boldsymbol{w}_c^{(l,l-1)}\| + r^{(l)}) \geq 0 \Rightarrow r^{(l-1)} - (\|\boldsymbol{w}_c^{(l-1,0)} - \boldsymbol{w}_c^{(l,0)}\| + r^{(l)}) = \|\boldsymbol{w}_s^{(l-1,0)} - \boldsymbol{w}_c^{(l-1)}\| - (\|\boldsymbol{w}_c^{(l-1)} - \boldsymbol{w}_c^{(l)}\| + \|\boldsymbol{w}_s^{(l)} - \boldsymbol{w}_c^{(l)}\|) \geq 0.$$

3. *Constraint 3* ($\mathcal{C}_3$): This constraint describes that a margin between spheres must be larger than zero.
   $$\|\boldsymbol{w}_c^{(l,l-1)}\|(2 - 2\cos\theta)^{0.5} - 2r^{(l)} \geq 0 \Rightarrow \|\boldsymbol{w}_c^{(l)}\|(2 - 2\frac{\sum_{i \neq j} \boldsymbol{w}_c^{(l),i} \cdot \boldsymbol{w}_c^{(l),j}}{\|\boldsymbol{w}_c^{(l)}\|^2})^{0.5} -$$

---

[11]from https://download.pytorch.org/models/resnet18-5c106cde.pth, https://download.pytorch.org/models/resnet50-19c8e357.pth respectively

$2\|\boldsymbol{w}_s^{(l)} \quad - \quad \boldsymbol{w}_c^{(l)}\|,$ where $\|\boldsymbol{w}_c^{(l,l-1)}\|(2 - 2\cos\theta)^{0.5} \quad =$
$\|\boldsymbol{w}_c^{(l,l-1)}\|(r^{(l-1)}\sin\theta^2 - (r^{(l-1)} - r^{(l-1)}\cos\theta)^2)^{0.5}.$