SIC-GAN: A Self-Improving Collaborative GAN for Decoding Variational RNNs

Abstract

Variational RNNs are proposed to output "creative" sequences. Ideally, a collection of sequences produced by a variational RNN should be of both high quality and high variety. However, existing decoders for variational RNNs suffer from a trade-off between quality and variety. In this paper, we seek to learn a variational RNN that decodes high-quality *and* high-variety sequences. We propose the *Self-Improving Collaborative GAN* (SIC-GAN), where there are two generators (variational RNNs) collaborating with each other to output a sequence and aiming to trick the discriminator into believing the sequence is of good quality. By deliberately *weakening* one generator, we can make another *stronger* in balancing quality and variety. We conduct experiments using the QuickDraw dataset and the results demonstrate the effectiveness of SIC-GAN empirically.

1 Introduction

Recurrent Neural Networks (RNNs) are popular models designed for sequence prediction problems. They have made significant impact on tasks related to Natural Language Processing (NLP), speech recognition, image captioning, and many other time-series analysis tasks. Traditionally, RNN decoding methods (Gu et al. (2017a); Boulanger-Lewandowski et al. (2013); Sutskever et al. (2014); Graves (2012); Cho (2016); Graves (2013); Gu et al. (2017b); Li et al. (2016)) focus on how to generate *high-quality* sequences. For example, in a language translation task, an RNN decoder aims to output a sequence that best expresses the input sequence in the target language. However, recent applications, such as Sketch drawing (Jongejan et al. (2016)), may expect an RNN to produce a *variety* of output sequences so to be "creative." Thus when drawing a firetruck, which is an output sequence of strokes, the RNN is expected to achieve both high quality (i.e., the sequence looks like a firetruck) and variety (i.e., different outputs looks different).

The above reasoning motivates the creation of *variational RNNs* that are able to output different sequences given the same input. There are two well-known ways to create the variety, namely *output sampling* (Graves (2013)) and *noise injection* (Cho (2016)), which are presented in Figures 1(b) and 1(c), respectively. For output sampling, to produce a point in a sequence, the decoder first outputs parameters of a predefined distribution, and then samples a point from the parametrized distribution. The process of sampling generates variety. While for *noise injection,* assuming that a small perturbation in the hidden space will not change a lot the semantic meaning in the input space, the decoder adds noises into the hidden representations h_i at each time step i, which in turn creates variety by changing the input slightly.

However, in practice, the variational RNNs usually generate outputs with low quality (Graves (2013)). Figure 2(a) shows some examples of output sequences, which are sketches of firetrucks, produced by a variational RNN using output sampling.[1] As we can see, many sequences are *not* recognizable as firetrucks. Similarly, the outputs of variational RNNs using noise injection also lack quality when the noise level is high.

To solve the problem, one can employ decoding techniques that improve the quality. Ha & Eck (2017) introduce a *temperature* parameter in the model that controls the level of randomness in output sampling (Figure 1(b)) or in hidden noises (Figure 1(c)). This concentrates around the mean

---

[1]For more details about the settings and training process, please refer to Section 5.

the distribution of points that can be output at each time. In beam search (Graves (2012); Boulanger-Lewandowski et al. (2013); Sutskever et al. (2014)), the decoder saves several output points into a tree-structural buffer at each time step, and finds out from the tree the best combination of points (one point at a time step) that will constitute as the output sequence. In effect, this concentrates the distribution of the sequences to be output by an RNN to its mean. Unfortunately, these decoding methods, when applied to variational RNNs, create a trade-off between quality and variety. Figures 2(b) and 2(c) illustrate some examples of sequences produced using the temperature method and beam search method, respectively. It can be seen that the quality is improved but at the cost of limited variety.

Figure 2(d) displays human-drawn sketches of fire trucks which demonstrate that producing sequences–in this case sketches–with both quality and variety is definitely achievable in real-world applications. The challenge is to come up with an algorithm that can produce the same (if not better) quality and variety of outputs as humans can.

In this paper, we seek to learn variational RNNs that output high-quality and high-variety sequences. We found out that the reason why variational RNNs give low quality is mainly because of the *error propagation* effect—a "bad" point output at the current time step by randomness will create a negative impact on the future points. On the other hand, *it is the "bad" points that create variety*. So instead of avoiding such a bad point, as in most existing work try to do, our key idea is to allow a bad point to occur but with the expectation that its negative impact in the future may be "covered" by some mechanism later on.

In line with this, we propose the *Self-Improving Collaborative GAN* (SIC-GAN), where there are two generators (variational RNNs) collaborating with each other to generate an output sequence and aiming to trick the discriminator into believing the sequence is of good quality. We deliberately let one generator, which we call the *weak* generator, produce bad points. This forces another generator, we refer as the *strong* generator, to learn to cover the bad points created by its partner in order to successfully fool the discriminator. After training SIC-GAN, we keep the strong generator only. This final variational RNN (the strong generator) will have the ability to conceal inadvertently bad points made by itself, and will output sequences of both high quality and variety.

To the best of our knowledge, this is the first work that improved the outputs of variational RNN in terms of both quality and variety. Following summarizes our contributions:

- We propose a novel collaborative GAN model that guides a variational RNN to learn to cover the creative points and to preserve the quality of an output sequence.

- The proposed collaborative GAN opens up some new research directions. For example, how the collaboration is done? How to weaken one generator to make another strong? We provide initial steps toward these directions.

- The collaborative GAN has an interesting extension in that the strong and weak generator can *share their weights*. So, every time the strong generator improves, so does the weak learner. Intuitively, this creates a *self-improving* effect during the training process. While the self-improving ability has been seen in an Reinforcement Learning agent such as AlphaGo (Silver et al. (2016)), we believe this is new to the GAN field.

- We conduct experiments using the QuickDraw dataset (Jongejan et al. (2016)) released by Google, and the results show that SIC-GAN achieves the state-of-the art performance in striking the balance between quality and variety.

2 RELATED WORK

There are some techniques other than the beam search and temperature method that improves the quality of RNN decoding. Li et al. (2016) observe that beam search decoding often sticks in a few branches. They modify the beam search algorithm to penalize siblings. This method helps find the high-quality sequences more efficiently, but it is still subject to the same problem as the beam search—there is no guarantee that the found sequences are diverse. Greedy decoding (Germann (2003); Langlais et al. (2007)) outputs a sequence by choosing the most likely point at each local step. It is a special case of the temperature method or beam search (where the beam size equals 1), and subject to the same quality-variety trade-off.

Figure 1: RNN models. (a) Vanilla RNNs. (b) Variational RNNs based on output sampling. (c) Variational RNNs based on noise injection.

Figure 2: Firetrucks drawn by (a) variational RNN; (b) tempered variational RNN parameter (top: high temperature, bottom: low temperature); (c) variational RNN with bean search; (d) human beings; (e) variational RNN trained by Naive GAN; (f) variational RNN trained by SIC-GAN.

Recently, studies (Yu et al. (2017); Che et al. (2017); Kusner & Hernández-Lobato (2016); Zhang et al. (2016)) start to apply GANs to generate the sequential output. In particular, there are some GAN-based approaches that helps RNN decoding. The professor forcing (Goyal et al. (2016)) uses GANs to reduce the mismatch between the training and testing distributions of the RNN output. The goal is different from ours. The Gumbel-greedy decoding (Gu et al. (2017b)) uses GANs to fine-tune a variational RNN to the one that outputs better-quality sequences. This provides another way than the beam search to find high-quality sequences, but is still subject to the same problem as the beam search.

Some studies use the Reinforcement Learning to improve the RNN decoding. SeqGAN (Yu et al. (2017)) uses a discriminator to guide the RNN decoding based on the policy gradients. The goal is to solve the gradient passing problem in GANs on discrete output and is different from that of this paper. Trainable Greedy Decoding (TGD) (Gu et al. (2017a)) extends the idea of nose-injected variational RNNs (Cho (2016)) by formulating the decoding as a Reinforcement Learning problem. TGD learns an agent to decide what noise to inject, and directly uses the BLEU score (Papineni et al. (2002)) as its reward function to guide the agent. Note that BLEU is a quality measure thus TGD improves the quality of the output sequences only. To improve the variety simultaneously, one has to define a reward function for the variety. Unfortunately, there is no existing study about such a reward function. SIC-GAN differs from the Reinforcement Learning-based approaches in that it does *not* require any variety reward/measure to train, which we believe is a significant advantage for

Figure 3: Model architecture. (a) Naive GAN. (b) The Strong-Week Collaborative GAN.

applications (such as drawing and image data synthesis tasks) whose output is in a high dimensional space and/or in an unknown manifold of that space.

3   STRONG-WEAK COLLABORATIVE GAN

In this section, we introduce a novel GAN setting, called the *strong-weak collaborative GAN*, which our SIC-GAN is based on. We then present SIC-GAN in Section 4.

The output of vanilla variational RNNs lacks quality because of the error propagation; that is, a creative point generated at a time step for variety prevents the points at later time steps from forming a high quality sequence. Most existing decoding methods improve the quality of the output sequences by reducing the variation of points, but this creates a trade-off between the quality and variety. To avoid such a trade-off, we do *not* limit the variation of a point. Instead, we let the later points learn to *cover* the negative effect of the variation.

To achieve our goal, one naive way is to use a GAN to improve a variational RNN, as shown in Figure 3(a). Given a (pre-trained) variational RNN, we can use it as the generator in GAN that output sequences aiming to trick the discriminator into believing they are real. In the presence of variation of a point s_i at time step i, the generator would learn to cover the error (in terms of quality) of s_i when generating later points s_j's, $j > i$, during the GAN training process in order to successfully fool the discriminator. Note that the discriminator performs the discrimination *at the sequence level*, so the generator has a chance to output high quality sequences without sacrificing the variety of each generated point. Figure 2(e) shows some example sequences output by this naive GAN approach. We can see that it improves *both* the quality and variety of the output sequences to a certain degree.

However, the naive GAN approach has a subtle drawback—it does *not* always preserve the variety of a variational RNN. This is because that, during the GAN training, there is another way for the generator to fool the discriminator. At each time step, the generator can choose to reduce the variation and output a more probable point that leads to a high quality sequence in order to fool the discriminator easily. In this case, the variety is limited.

To avoid such a problem, we propose the strong-weak collaborative GAN where there are strong and weak generators *collaborate* to generate an output sequence aiming to fool the discriminator, as shown in Figure 3(b). We deliberately *weaken* the weak generator by letting it output "bad" (variational) points. Thus, the strong generator is forced to learn to cover the variation during the GAN training process. After the training, we discard the weak generator and keep the strong one as the final variational RNN.

The strong-weak collaborative GAN is a general architecture and there are different ways to define the collaboration and weakening. For the collaboration, one can let the weak generator generate the first half of a sequence and then let the strong one generate the second half. Here, we choose to let the two generators take turns to generate points in a sequence, so the strong generator can see the "bad" points right after they are generated and learn to take actions to recover the quality immediately. The detailed architecture of our collaboration design is shown in Figure 4(a). As compared to standard

Figure 4: Collaboration between the strong and weak generators for outputting a sequence in (a) strong-weak collaborative GAN; (b) SIC-GAN.

RNNs, the strong generator has an additional input coming from the weak generator at each time step. This allows the strong generator to see the points output by the weak generator.

For the weakening, we simply set the weak generator to the original variational RNN used as the input to the strong-weak collaborative GAN. We fix the weights of the weak generator during the GAN training process and update the weights of the strong generator only.[2] Since the weak generator is not updated and could generate "bad" points from time to time by its nature, the strong generator is now forced to learn to cover the negative impact of the variety of input variational RNN.

4 SIC-GAN: SELF-IMPROVING COLLABORATIVE GAN

The strong-weak collaborative GAN has an interesting extension in making the strong generator *self-improving*. Note that the strong generator is a variational RNN that still could generate "bad" points. Is it possible to learn an *even stronger* generator that covers these points? One way to do so is to train the strong-weak collaborative GAN multiple times, and at each time we set the weak generator as the strong one we get from the previous GAN training. This allows the strong generator to learn to cover its own variety and gradually improve itself in quality.

Although viable, training a long series of GANs could be time consuming. Here, we propose the *Self-Improving Collaborative GAN* (SIC-GAN) that improves the strong generator in a single GAN training process. The idea is to simply *tie the weights of the strong and weak generators together*, as shown in Figure 4(b). Every time the strong generator improves, so does the weak generator. This allows the strong generator to learn to cover the quality errors made by itself over the training iterations.

The design of collaboration and weakening needs to be adapted for the SIC-GAN. As shown in Figure 4(b), the weak generator takes extra input at each time step now, and it functions the same as the strong generator in terms of input/output so that we can tie the weights of the two generators together. The weakening design needs a special care since the weak generator *may change* during the training and the strong and weak generators may together choose to ignore the variety and focus only on the quality in order to fool the discriminator easily. To avoid this issue, we deliberately add a random noise δ_i to the point output by the weak generator at time step i (see Figure 4(b)). The precise definition of δ_i depends on the application. For example, in the case of firetruck drawing, δ_i can be a random translation/rotation/scaling of a stroke (point) on the canvas.

In addition to time efficiency, the SIC-GAN offers some advantages over the strong-weak collaborative GAN. First, the self-improving ability could lead the strong generator to *learn beyond the human knowledge* (provided by the training dataset and could be limited) in striking the balance between quality and variety. The self-improving ability has been discussed in some Reinforcement Leaning work such as the AlphaGo (Silver et al. (2016; 2017)). By playing Go with and beating itself iteratively, the agent is able to learn what was *not* in the playbooks written by humans. Note that the SIC-GAN requires only the measure of quality (used by the discriminator) while a Rein-

---

[2] As in the naive GAN approach, we can initialize the weights of the strong generator using those of the input variational RNN.

forcement Learning-based agent would require the reward functions of both quality and variety to train.

Another advantage is that, by adding the $\boldsymbol{\delta}_i$'s explicitly, we are able to control the degree of weakening and improve the learning. For example, we can gradually increase the $\boldsymbol{\delta}_i$'s during the training process by following the *curriculum learning* strategy (Bengio et al. (2009; 2015)). This makes the generators easier to learn in the beginning (with small $\boldsymbol{\delta}_i$'s) and more capable of covering the variety in the end (with large $\boldsymbol{\delta}_i$'s).

5 EXPERIMENTS

Next, we conduct experiments using the QuickDraw (Jongejan et al. (2016)) dataset and evaluate the effectiveness of SIC-GAN in terms of both quality and variety.

The QuickDraw dataset[3] consists of 50 million hand-drawn sketches in 345 classes. Each sketch in turn consists of multiple pen strokes. A stroke is recorded in the form $(\Delta x, \Delta y, p_1, p_2, p_3)$, where $(\Delta x, \Delta y)$ denotes the ending position of the stroke relative to that of the previous stroke, and (p_1, p_2, p_3) represents a one-hot vector of 3 possible states. The state p_1 indicates if the pen is currently touching the canvas. The state p_2 tells if the pen will be lifted from the canvas after the current stroke. While the state p_3 indicates whether the sketch drawing has ended.

Settings. To set up a GAN, we use a CNN consisting of a 1D convolution layer, a max-pooling layer, and a fully-connected output layer as the discriminator. In the convolution layer, we use the filters proposed by Kim (2014) that scan the n-grams of the real and generated sequences. The layer scans 1- to 30-grams, each with a 128 filters. The generator is a variational RNN consisting of 1-layer LSTM with 512 hidden units. At each time step, the generator outputs parameters of a mixture of 20 two-dimensional Gaussian distributions and also parameters of a Categorical distribution of three categories. The parametrized Gaussian mixture model is then used to sample the $(\Delta x, \Delta y)$ part of a generated point, and the parametrized Categorical distribution is used to sample the (p_1, p_2, p_3) part. To set up SIC-GAN, we add a random noise $\boldsymbol{\delta}_i \in \mathbb{R}^2$ to the $(\Delta x, \Delta y)$ part of the point generated by the weak generator at each time step i. Each dimension of $\boldsymbol{\delta}_i$ falls within $[-\alpha, \alpha]$, where α is set to 0 in the beginning of the GAN training process and enlarged gradually till 0.2 in the end. We use SIC-GAN to improve the decoding of a variational RNN pre-trained by labeled examples aiming to draw a sketch of firetruck given an initial stroke. We use the improved WGAN (Gulrajani et al. (2017)) as the training algorithm. We update the generator every batch and the discriminator every 5 batches. We implement SIC-GAN using TensorFlow 1.2 and our code is based on that of the *sketch rnn* (Ha & Eck (2017)).[4]

Baseline Methods. We compare SIC-GAN against the several baseline decoding methods, including the ordinary decoder (Vanilla) of a variational RNN using output sampling (Graves (2013)), the decoder with a lowered temperature (Low Temp) by Ha & Eck (2017) where the temperature parameter is set to 0.2, beam search (Beam) by Graves (2012); Boulanger-Lewandowski et al. (2013); Sutskever et al. (2014) which samples 10 points and keep the top-5 points ranked by their respective probability at each time step, and the naive GAN (GAN) described in Section 3. Note that the SIC-GAN has a plausible simplification that uses only *one* generator with a random noise $\boldsymbol{\delta}_i$ added to the output point at every one another time step, $i = 1, 3, 5, \cdots$. We also implement this approach (Noisy GAN) and use it as a baseline.

5.1 QUALITY

Measures. To evaluate the quality of the sequences produced by a variational RNN, we need to have quality measures first. However, there is no existing quality measure defined in the literature for sketch drawing. Here, we propose two new measures, namely the *typicalness* and *details*, for this task. We find that the strokes in a sketch can usually be divided into two groups serving different purposes. One contains the strokes for the main contour and the other includes the strokes for the details. For example, when drawing a firetruck, we can usually see strokes for the body and wheels, as shown in Figure 5(a), that defines the main contour. We can also see strokes for the

---

[3]https://github.com/googlecreativelab/quickdraw-dataset
[4]https://github.com/tensorflow/magenta/tree/master/magenta/models/sketch_rnn

bell and ladder, as shown in Figure 5(b), that adds details. To quantify the typicalness, we train a CNN with 4 convolution layers and 4 fully connected layers that classifies 5 carefully chosen classes—the airplanes, bicycles, firetrucks, helicopters, and submarines. These classes define very different main contours, so the classifier tends to capture the difference between the main contours of the input sequences when making predictions. We use the CNN to obtain a *typicalness score* of outputs of a variational RNN drawing firetrucks. Given 1000 sequences generated by the RNN, the typicalness score is defined as the times the CNN classifies the sequences into the firetruck class. Similarly, for quantifying the details measure, we train another CNN of the same architecture using the examples in 5 carefully chosen classes, namely the ambulances, buses, firetrucks, pickup trucks, and police cars. This time, sketches in these classes share the main contours but are different from each other in details. Therefore, the classifier tends to distinguish the details of input sequences when making predictions. Given 1000 sequences generated by the RNN, the *details score* is defined as the times the CNN classifies the sequences into the firetruck class. Note that the above two CNNs are trained using the rectified images (in pixels) so to ensure that the scores are derived purely from the appearance of the sketches.

Base variety. To see how different decoding approaches balance quality and variety, we evaluate the typicalness and details scores at different levels of *base variety*. We create the base variety at degree $1/i$ by replacing the points with random noises at every i time steps when a model is generating a sequence at the test time. Here, we take $i = 3, 5, 10$ into account.

	Vanilla	Low Temp	Beam	GAN	Noisy GAN	SIC-GAN
Typicalness@0	0.995	**0.998**	0.973	0.993	0.99	0.986
Details@0	0.793	0.813	0.546	0.854	**0.885**	0.845
Typicalness@(1/10)	0.872	0.808	0.901	0.897	0.869	**0.913**
Details@(1/10)	0.573	0.483	0.508	0.78	0.773	**0.784**
Typicalness@(1/5)	0.644	0.557	0.804	0.681	0.738	**0.823**
Details@(1/5)	0.495	0.388	0.442	0.669	0.686	**0.701**
Typicalness@(1/3)	0.425	0.428	**0.706**	0.537	0.529	0.651
Details@(1/3)	0.539	0.474	0.440	0.609	0.609	**0.664**

Table 1: Typicalness and details scores at (@) different base variety.

Results. Table 1 lists the typicalness and details scores of different approaches at different degrees of base variety. When there is no base variety, all the models perform roughly the same. The only exception is Beam, which gives a particularly low details score. This implies that it can only generate firetrucks of typical contours, as we have seen in Figure 2(c). As the degree of base variety increases, SIC-GAN starts to outperform other methods in *both* typicalness and details. Figures 6 also shows that some non-GAN-based methods tend to confuse the firetrucks with some other classes. Figure 2(f) shows the firetrucks drawn by SIC-GAN. We can clearly see that the firetrucks contains more details than those output by GAN. Note that the Noisy GAN outperforms SIG-GAN when the base variety is low, but degrades dramatically when the base variety goes up. The two-generator design is advantageous because at each time step, the final generator in SIC-GAN takes the points in the previous two steps as the input. If the previous point contains an error, it can use the input coming before the previous point to "recover" the error and then decide what to output next.

5.2 VARIETY

We quantify the variety of a model by directly calculating the sample variance of 100 output sequences. To calculate the sample variance, we need a distance measure between the sketches. One way is to use the 1-norm, as shown in Figure 7(a), where the distance is the sum of differences between the RGB values of the pixels in rectified images. Note that the standard 1-norm does not take into account the translation, rotation, scaling, and other perturbations of an image that would not change the semantic distance. So, we walk around this problem by either adding a Gaussian blur to the rectified sketches first or using the soft 1-norm, i.e., the sum of the differences between the RGB values of the nearby pixels in rectified images, as shown in Figure 7(b). Table 2 shows the variety scores achieved by different approaches. SIC-GAN consistently gives the highest variety in all measures. This can be seen more specifically in Figure 2(f), where SIC-GAN generates more

Figure 5: Two type of strokes. (a) Main contour. (b) Details.

Figure 6: Distributions of the predictions of typicalness and details CNNs over 1000 output sequences.

Figure 7: Difference between standard and soft 1-norm.

	Vanilla	Low Temp	Beam	GAN	Noisy GAN	SIC-GAN
1-Norm	135.88	115.18	109.01	122.29	115.56	**145.28**
Gaussian Blur + 1-Norm	43.33	37.02	35.88	36.76	34.11	**48.81**
Soft 1-Norm	3.99	1.38	2.30	4.59	4.14	**6.43**

Table 2: Variety scores given different similarity measures.

diverse results than GAN. Furthermore, some of the firetrucks it generates do not bear a resemblance to any training example, implying that SIC-GAN can learn beyond the provided knowledge.

6 CONCLUSIONS

We propose the strong-weak collaborative GAN and SIC-GAN that fine-tune a variational RNN to the one capable of generating high-quality and high-variety sequences. We conduct experiments using a real-world dataset and the results shows that SIC-GAN can achieve the state-of-the-art performance in balancing quality and variety. These work opens up several interesting research directions. For example, as the strong-weak collaborative GAN is a general architecture, there could be other ways to define the collaboration between the strong and weak generators as well as the weakening mechanism for the weak generator. Also, it is possible to apply the SIC-GAN to other applications such as the Natural Language Processing (NLP) tasks. These are the matters of our future exploration.

REFERENCES

Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In *NIPS*, pp. 1171–1179, 2015.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *ICML*, volume 382 of *ACM International Conference Proceeding Series*, pp. 41–48. ACM, 2009.

Nicolas Boulanger-Lewandowski, Yoshua Bengio, and Pascal Vincent. High-dimensional sequence transduction. In *ICASSP*, pp. 3178–3182. IEEE, 2013.

Tong Che, Yanran Li, Ruixiang Zhang, R. Devon Hjelm, Wenjie Li, Yangqiu Song, and Yoshua Bengio. Maximum-likelihood augmented discrete generative adversarial networks. *CoRR*, abs/1702.07983, 2017.

Kyunghyun Cho. Noisy parallel approximate decoding for conditional recurrent language model. *CoRR*, abs/1605.03835, 2016.

Ulrich Germann. Greedy decoding for statistical machine translation in almost linear time. In *HLT-NAACL*. The Association for Computational Linguistics, 2003.

Anirudh Goyal, Alex Lamb, Ying Zhang, Saizheng Zhang, Aaron C. Courville, and Yoshua Bengio. Professor forcing: A new algorithm for training recurrent networks. In *NIPS*, pp. 4601–4609, 2016.

Alex Graves. Sequence transduction with recurrent neural networks. *CoRR*, abs/1211.3711, 2012.

Alex Graves. Generating sequences with recurrent neural networks. *CoRR*, abs/1308.0850, 2013.

Jiatao Gu, Kyunghyun Cho, and Victor O. K. Li. Trainable greedy decoding for neural machine translation. In *EMNLP*, pp. 1958–1968. Association for Computational Linguistics, 2017a.

Jiatao Gu, Daniel Jiwoong Im, and Victor O. K. Li. Neural machine translation with gumbel-greedy decoding. *CoRR*, abs/1706.07518, 2017b.

Ishaan Gulrajani, Faruk Ahmed, Martín Arjovsky, Vincent Dumoulin, and Aaron C. Courville. Improved training of wasserstein gans. *CoRR*, abs/1704.00028, 2017.

David Ha and Douglas Eck. A neural representation of sketch drawings. *CoRR*, abs/1704.03477, 2017.

J. Jongejan, H. Rowley, T. Kawashima, J. Kim, and N. Fox-Gieg. The quick, draw! - a.i. experiment. https://quickdraw.withgoogle.com/, 2016.

Yoon Kim. Convolutional neural networks for sentence classification. In *EMNLP*, pp. 1746–1751. ACL, 2014.

Matt J. Kusner and José Miguel Hernández-Lobato. GANS for sequences of discrete elements with the gumbel-softmax distribution. *CoRR*, abs/1611.04051, 2016.

Philippe Langlais, Alexandre Patry, and Fabrizio Gotti. A greedy decoder for phrase-based statistical machine translation. *Proc. of TMI*, 2007.

Jiwei Li, Will Monroe, and Dan Jurafsky. A simple, fast diverse decoding algorithm for neural generation. *CoRR*, abs/1611.08562, 2016.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *ACL*, pp. 311–318. ACL, 2002.

David Silver, Aja Huang, Chris J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Vedavyas Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy P. Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 2017.

Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks. In *NIPS*, pp. 3104–3112, 2014.

Lantao Yu, Weinan Zhang, Jun Wang, and Yong Yu. Seqgan: Sequence generative adversarial nets with policy gradient. In *AAAI*, pp. 2852–2858. AAAI Press, 2017.

Yizhe Zhang, Zhe Gan, and Lawrence Carin. Generating text via adversarial training. In *NIPS Workshop on Adversarial Training*, 2016.

APPENDIX

To help understand the distribution of the output sequences of different methods, we include more generated sketches here.

Figure 8: Firetrucks by Vanilla.

Figure 9: Firetrucks by Low Temp.

Figure 10: Firetrucks by Beam.

Figure 11: Firetrucks by GAN.

Figure 12: Firetrucks by Noisy GAN.

Figure 13: Firetrucks by SIC-GAN.