Boosting Data-Driven Mirror Descent with Randomization, Equivariance, and Acceleration

Abstract

Learning-to-optimize (L2O) is an emerging research area in large-scale optimization with applications in data science. Recently, researchers have proposed a novel L2O framework called learned mirror descent (LMD), based on the classical mirror descent (MD) algorithm with learnable mirror maps parameterized by input-convex neural networks. The LMD approach has been shown to significantly accelerate convex solvers while inheriting the convergence properties of the classical MD algorithm. This work proposes several practical extensions of the LMD algorithm, addressing its instability, scalability, and feasibility for high-dimensional problems. We first propose accelerated and stochastic variants of LMD, leveraging classical momentum-based acceleration and stochastic optimization techniques for improving the convergence rate and per-iteration computational complexity. Moreover, for the particular application of training neural networks, we derive and propose a novel and efficient parameterization for the mirror potential, exploiting the equivariant structure of the training problems to significantly reduce the dimensionality of the underlying problem. We provide theoretical convergence guarantees for our schemes under standard assumptions and demonstrate their effectiveness in various computational imaging and machine learning applications such as image inpainting, and the training of support vector machines and deep neural networks.

1 Introduction

Large-scale optimization plays a key role in modern data science applications. In such applications, we typically seek to infer a collection of parameters $x \in \mathbb{R}^n$ from m i.i.d. data samples of a random variable $\{z_i\}_{i=1}^m$, by solving optimization problems of the form:

$$x^\star \in \underset{x \in \mathbb{R}^n}{\arg\min} f(x) := \frac{1}{m} \sum_{i=1}^m [f_i(x; z_i) + R(x)], \tag{1}$$

where each f_i is a fidelity function associated with the i-th data sample z_i, while $R(x)$ is a regularizer containing the prior knowledge of x. In the context of machine learning applications, x would contain the parameters of some models such as SVMs and neural networks, while z_i contains a pair of of training data samples and labels. For signal/image processing and inverse problems, z_i is usually referred to as a pair of measurement operators and measurement data, with the measurement operator appearing in the fidelity f_i. Many classical variational image reconstruction models can also take the form of (1), with a simple example being total variation regularization (Rudin et al., 1992). In this case, we have $m = 1$, where f_1 depends only on the corrupted image, and the total variation regularizer $R(x) = \lambda \|\nabla x\|_1$ is the ℓ_1 norm of the discrete differences of x. In modern applications, the dimension of the optimization problems and the number of data samples involved are often large, leading to heavy demands on the development of computationally efficient optimization algorithms.

Throughout the past decade, we have witnessed tremendous successes by researchers in the field of optimization in data science. In particular, efficient first-order algorithms utilizing momentum-based acceleration (Nesterov, 1983; Beck & Teboulle, 2009) and stochastic approximation (Robbins & Monro, 1951; Zhang,

2004) have been proposed, with applications including sparse signal recovery and convex programming (Bubeck, 2015; Ghadimi & Lan, 2016). Recently, stochastic gradient algorithms with theoretically optimal convergence rates for solving generic classes of problems were developed (Lan, 2012; Lan & Zhou, 2015; Defazio, 2016; Allen-Zhu, 2017; Chambolle et al., 2018; Tang et al., 2018; Zhou et al., 2018b; Driggs et al., 2021), matching complexity lower bounds for convex (Woodworth & Srebro, 2016) or non-convex problems (Arjevani et al., 2023).

Despite being theoretically optimal for generic optimization problem classes, stochastic gradient methods result in poor performance when applied to problems with particular structures. Tang et al. (2020) demonstrate that while optimal stochastic gradient methods perform very well in terms of convergence rates for certain imaging inverse problems such as X-ray CT, they perform poorly for some other problems such as image deblurring and compressed sensing. One important aspect is the fact that these methods are designed for some wide generic class of problems, while in practice, each practitioner may be only interested in a very narrow subclass of problems with a specific structure. The optimal algorithms for generic problems may still perform suboptimally for the specific subclasses of interest.

1.1 Learning-to-Optimize

Learning-to-optimize (L2O), sometimes referred to as meta-learning in the machine learning literature, aims to overcome this limitation when dealing with more specialized problem classes, such as natural image reconstruction as a subset of all imaging problems. An underlying idea is to utilize the intrinsic structure of the optimization problems to converge faster on tasks from the same distribution. This has been shown to be effective for problems such as linear regression, training neural networks, and tomographic reconstruction, beating standard analytic methods (Andrychowicz et al., 2016; Li & Malik, 2016; Li et al., 2019; Banert et al., 2020). The aim is to generate optimizers that (1) optimize in-distribution functions at a faster rate, and (2) possibly return a higher quality solution given the same computing budget (Chen et al., 2022).

The L2O framework can be formally described as follows (Chen et al., 2022). Given a learnable mapping function g with parameters θ, as well as a set $\mathcal{F}$ of training sample optimization problems $\min_x f(x)$ for $f \in \mathcal{F}$, the optimizer is learned to generate updates of the form $x_{k+1} = x_t - g_\theta(I_t)$. Here, I_t represents previous information, such as the iterates $x_t, x_{t-1}, ...$ or their gradients $\nabla f(x_t), \nabla f(x_{t-1})$ etc. For example, gradient descent with can be formulated as $g_\theta(I_t) = \eta \nabla f(x_t)$, with a learnable step-size parameter η. This formulation of L2O is flexible in the sense that all previous information is available, which should theoretically allow for better informed steps. The parameters are usually learned by minimizing an objective of the form

$$\min_\theta \mathbb{E}_{f \in \mathcal{F}} \left[\sum_{i=1}^{T} w_t f(x_t) \right], \quad x_{t+1} = x_t - g_\theta(I_t). \tag{2}$$

This can be interpreted as minimizing the objective value of the evolved iterates, with weights w_t. Some standard choices include $w_t \equiv 1$, or $w_T = 1, w_{T-1} = ... = w_1 = 0$ (Zhou et al., 2018a; Andrychowicz et al., 2016).

Learning-to-optimize frameworks broadly fall into two categories: fully learned "model-free" methods, and "model-based" methods based on classical algorithms (Chen et al., 2022). Model-free methods directly parameterize the optimizer updates $g_\theta(I_t)$ using neural networks, formulating fast optimization as an unrolled loss objectives of the form Equation (2) (Andrychowicz et al., 2016; Li & Malik, 2016). Recent advances for this paradigm include improving the generalization performance of both the optimizers and final optimization objective when used to train neural networks (Almeida et al., 2021; Yang et al., 2023), and more stable computation (Metz et al., 2019). However, major drawbacks include lack of convergence guarantees, as well as requiring many training samples.

Model-based L2O methods instead inherit structure from classical optimization algorithms such as PDHG-like proximal splitting algorithms, where certain optimizer parameters such as step-sizes or momentum parameters are learned (Banert et al., 2020; Almeida et al., 2021; Banert et al., 2021; Gregor & LeCun, 2010). These methods are typically applied to convex problems rather than non-convex problems such as neural network training, which also allows for theoretical convergence analysis of the learned schemes. One

advantage of building a L2O model from a classical optimization model is that convergence of the learned model can usually be derived by slightly modifying existing convergence results. A more in-depth overview of L2O can be found in Chen et al. (2022).

A provable learning-to-optimize framework called learned mirror descent (LMD) (Tan et al., 2023b;a) was recently proposed based on the classical mirror descent (MD) algorithm by Nemirovski & Yudin (1983). By using neural networks to implicitly learn and model the geometry of the underlying problem class via mirror maps, LMD can achieve significantly faster convergence on certain convex problem classes, including model-based image inpainting and training support vector machines. Moreover, the LMD framework proposes approximate convergence results based on the accuracy of the mirror map inversion.

Building upon the vanilla LMD framework by Tan et al. (2023b), we make the following contributions:

1. **Learned accelerated mirror descent and its theoretical analysis.** Our first contribution is developing the learned accelerated mirror descent (LAMD) scheme, which was initially proposed in the preliminary work of Tan et al. (2023a) without convergence analysis. In this work, we complete the theoretical analysis of the LAMD scheme under standard assumptions, demonstrating improved convergence rates over vanilla LMD. In particular, we demonstrate in Theorem 1 that we obtain convergence to the minimum, as opposed to a constant above the minimum as found in Tan et al. (2023b).

2. **Learned stochastic mirror descent and its acceleration.** We propose the learned stochastic mirror descent (LSMD) and the accelerated version (LASMD) in the spirit of stochastic optimization, which is crucial for the scalability of the LMD framework in large-scale problems prevalent in modern data science applications. We also provide theoretical convergence analysis of these schemes and demonstrate their effectiveness using numerical experiments including image processing, training of SVMs, and training neural networks for classification.

3. **Efficient mirror map parameterization by utilizing the equivariant structure.** For the training of deep neural networks, we utilize the equivariant structure of the training problems to significantly simplify the parameterization of the mirror map, further improving the efficiency and practicality of the LMD framework. We provide a derivation of this scheme, showing theoretically that LMD trained under certain group invariance and equivariance assumptions will also satisfy a group invariance property, removing redundant parameters and reducing the problem dimensionality. We additionally utilize this to extend the LMD framework to the task of training deep and convolutional neural networks, achieving competitive performance with widely used and empirically powerful optimizers such as Adam.

1.2 Mirror Descent and Learned Mirror Descent

Mirror descent (MD) was originally proposed by Nemirovski & Yudin (1983) as a method of generalizing gradient descent to general infinite-dimensional Banach spaces. The lack of Hilbert space structure and isomorphisms between $\mathcal{X}$ and their duals $\mathcal{X}^*$ prevents the use of gradient descent, which usually identifies the formal derivative $Df \in \mathcal{X}^*$ with the corresponding Riesz element $\nabla f \in \mathcal{X}$, satisfying $\langle Df, x \rangle_{\mathcal{X}^*, \mathcal{X}} = \langle \nabla f, x \rangle_{\mathcal{X}, \mathcal{X}}$. MD proposes to address this by directly updating elements in the dual space $\mathcal{X}^*$, and 'tying' the dual space updates in $\mathcal{X}^*$ to corresponding primal space updates in $\mathcal{X}$ using a "mirror map", satisfying various conditions.

Generalizing the classical Euclidean structure used for gradient descent to more general Bregman divergences, such as those induced by L^p norms, can improve the dimensionality scaling of the Lipschitz constant. Having a smaller Lipschitz constant with respect to another norm compared to the Euclidean norm directly impacts the step size for which the methods converge, as well as the convergence rates. For example, for minimizing a convex function f on the n-simplex $\Delta^n = \{x \in \mathbb{R}^n \mid x_i \geq 0, \sum_{i=1}^n x_i\}$, MD is able to achieve rates of $\mathcal{O}(\sqrt{\log n} \|f'\|_\infty / \sqrt{k})$, as opposed to (sub-)gradient descent which has rate $\mathcal{O}(\|f'\|_2 / \sqrt{k})$ (Beck & Teboulle, 2003; Ben-Tal et al., 2001). The ratio $\|f'\|_2 / \|f'\|_\infty$ can be as large as $\sqrt{n}$, leading to $(n/\log n)^{1/2}$ asymptotic speedup by using MD.

Gunasekar et al. (2021) demonstrate further that mirror descent corresponds to a Riemannian gradient flow in the limiting case, and further generalize mirror descent to general Riemannian geometries. Moreover,

the mirror descent framework is amenable to modifications similar to gradient descent, with extensions such as ergodicity (Duchi et al., 2012), composite optimization (Duchi et al., 2010), stochasticity (Lan et al., 2012; Zhou et al., 2017) and acceleration (Krichene et al., 2015; Hovhannisyan et al., 2016). In summary, the mirror descent algorithm allows us to utilize non-Euclidean geometry for optimization, which has been shown to accelerate convergence in applications including online learning and tomography (Srebro et al., 2011; Raskutti & Mukherjee, 2015; Allen-Zhu & Orecchia, 2014; Ben-Tal et al., 2001; Orabona et al., 2015; Zimmert & Lattimore, 2019).

We present the MD algorithm as given in Beck & Teboulle (2003), as well as the data-driven version of which this work is based, LMD (Tan et al., 2023b). The LMD framework serves as a base for the accelerated and stochastic extensions that will be presented in this work. LMD aims to speed up convergence on a class of "similar" functions, which are taken to be qualitatively similar, such as image denoising on natural images or CT imaging (Banert et al., 2020). By using data to generate functions from the target function class, the geometry of the class can be learned using these sample functions. Mirror descent then exploits this learned geometry for faster convergence. Follow-up works additionally suggest that the learned geometry can be transferred to other mirror-descent-type algorithms without the need for retraining. Moreover, the learned mirror maps are robust to small perturbations in the forward operator such as from the identity to a blur convolution, as well as change of data sets (Tan et al., 2023a).

We begin with some notation and definitions that will be used for mirror descent, as well as more standard assumptions for the MD framework.

Let $\mathcal{X}$ be the finite dimensional normed space $(\mathbb{R}^n, \|\cdot\|)$. Denote by $\mathcal{X}^* = ((\mathbb{R}^n)^*, \|\cdot\|_*)$ the dual space, where the dual norm is defined as $\|p\|_* = \sup_x\{\langle p, x\rangle \mid \|x\| \leq 1\}$, and the bracket notation denotes evaluation $\langle p, x\rangle = p(x) \in \mathbb{R}$. Let $\overline{\mathbb{R}} := \mathbb{R} \cup \{+\infty\}$ denote the extended real line. Let $f : \mathcal{X} \to \overline{\mathbb{R}}$ be a proper, convex, and lower-semicontinuous function with well-defined subgradients. For a differentiable convex function $h : \mathcal{X} \to \mathbb{R}$, define the *Bregman divergence* as $B_h(x,y) = h(x) - h(y) - \langle h'(y), x - y\rangle$. Let $g : \mathcal{X} \to \mathcal{X}^*$ be a function such that $g(x) \in \partial f(x)$ for all $x \in \mathcal{X}$. We denote a (possibly noisy) stochastic approximation to g by

$$\mathsf{G}(x,\xi) = g(x) + \Delta(x,\xi) + U(x),$$

where $\mathbb{E}_\xi[\Delta(x,\xi)] = 0$, and $U(x) : \mathcal{X} \to \mathcal{X}^*$ represents dual noise. One standard assumption that we will use is that G has bounded second moments.

While we have defined $\mathcal{X}$ to be a vector space, this is not necessary. Indeed, suppose instead that $\mathcal{X}$ were a (proper) closed convex subset of $\mathbb{R}^n$. Assuming that the inverse mirror function maps into $\mathcal{X}$, i.e., $\nabla\psi^* : (\mathbb{R}^n)^* \to \mathcal{X}$, such as when $\nabla\psi(x) \to \infty$ as $x \to \partial\mathcal{X}$, then the proposed algorithms will still hold. We will restrict our exposition in this work to the simpler case where $\mathcal{X} = \mathbb{R}^n$ to avoid these technicalities, but the results can be extended.

Definition 1. *We define a* mirror potential *to be an α-strongly convex $\mathcal{C}^1$ function $\psi : \mathcal{X} \to \mathbb{R}$ with $\alpha > 0$. We define a* mirror map *to be the gradient of a mirror potential $\nabla\psi : \mathcal{X} \to \mathcal{X}^*$.*

We further denote the convex conjugate of ψ by $\psi^* : \mathcal{X}^* \to \mathbb{R}$. Note that under these assumptions, we have that $\nabla\psi^* = (\nabla\psi)^*$ on $\mathrm{dom}\,\psi$. Moreover, ψ^* is α^{-1}-smooth with respect to the dual norm, or equivalently, $\nabla\psi^*$ is α^{-1}-Lipschitz (Azé & Penot, 1995).

For a mirror potential ψ and step-sizes $(t_k)_{k=0}^\infty$, the mirror descent iterations of Beck & Teboulle (2003) applied to an initialization $x^{(0)} \in \mathcal{X}$ are

$$x^{(k+1)} = \nabla\psi^*(\nabla\psi(x^{(k)}) - t_k\nabla f(x^{(k)})). \tag{3}$$

The roles of $\nabla\psi : \mathcal{X} \to \mathcal{X}^*$ and $\nabla\psi^* : \mathcal{X}^* \to \mathcal{X}$ are to *mirror* between the primal and dual spaces such that the gradient step is taken in the dual space. A special case is when $\Psi(x) = \frac{1}{2}\|x\|_2^2$, whereby $\nabla\psi$ and $\nabla\psi^*$ are the canonical isomorphisms between $\mathcal{X}$ and $\mathcal{X}^*$, and the MD iterations (3) reduce to gradient descent. In the case where f is L-Lipschitz and ψ has strong convexity parameter $\alpha > 0$, mirror descent is able to achieve regret bounds of the following form (Beck & Teboulle, 2003):

$$\min_{1 \leq k \leq s} f(x^{(k)}) - f(x^*) \leq \frac{B_\psi(x^*, x^{(1)}) + (2\alpha)^{-1}\sum_{k=1}^s t_k^2\|\nabla f(x^{(k)})\|_*^2}{\sum_{k=1}^s t_k}.$$

LMD arises when we replace ψ and ψ^* with neural networks, which we can then learn from data. We denote learned variants of ψ and ψ^* by $M_\theta : \mathcal{X} \to \mathbb{R}$ and $M_\vartheta^* : \mathcal{X}^* \to \mathbb{R}$ respectively. Note that M_θ and M_ϑ^* are not necessarily convex conjugates of each other due to the lack of a closed-form convex conjugate for general neural networks – we change the subscript to remind the reader of this subtlety. Equipped with this new notation for learned mirror maps, the learned mirror descent algorithm arises by directly replacing the mirror maps $\nabla\psi$ and $\nabla\psi^*$ with learned variants M_θ and M_ϑ^* respectively, where ∇M_ϑ^* is enforced to be approximately $(\nabla M_\theta)^{-1}$ during training (Tan et al., 2023b):

$$x^{(k+1)} = \nabla M_\vartheta^*(\nabla M_\theta(x^{(k)}) - t_k \nabla f(x^{(k)})). \tag{4}$$

The mismatch between ∇M_ϑ^* and $(\nabla M_\theta)^{-1}$, also called the *forward-backward inconsistency*, necessarily arises as the convex conjugate of a neural network is generally intractable. Tan et al. (2023b) consider analyzing LMD as an approximate mirror descent scheme, where the error bounds depend on the distance between the computed (approximate) iterates (4) and the true mirror descent iterates (3). Under certain conditions on the target function f and the mirror potential $\psi = M_\theta$, they show convergence in function value up to a constant over the minimum (Tan et al., 2023b, Thm. 3.1, 3.6). A sufficient condition for this convergence is that the LMD iterations x_i with inexact mirror maps given by Equation (4) is close to the exact MD iterations $\hat{x}^{(k+1)} = (\nabla M_\theta)^{-1}(\nabla M_\theta(x^{(k)}) - t_k \nabla f(x^{(k)}))$, in the sense that $\langle \nabla\Psi(\hat{x}_i) - \nabla\Psi(\tilde{x}_i), x - \tilde{x}_i \rangle$ and $\langle \nabla f(\hat{x}_i), \tilde{x}_i - \hat{x}_i \rangle$ are uniformly bounded for a given minimizer x.

This work proposes to address two current restrictions of LMD. The first restriction is the approximate convergence and instability that arises due to the forward-backward inconsistency, such that the function values are only minimized up to a constant above the minimum. This is demonstrated in Tan et al. (2023a, Thm. 3.1), where LMD is also shown to diverge in later iterations as the forward-backward inconsistencies accumulate. Section 2 presents an algorithm through which the constant can vanish if the forward-backward inconsistency is uniformly bounded. The second drawback is the computational cost of training LMD, which is prohibitive for expensive forward operators such as CT or neural network parameters. Sections 3 and 4 present stochastic and accelerated stochastic extensions of LMD that show convergence in expectation even with possibly unbounded stochastic approximation errors. We demonstrate these extensions with function classes considered in previous works in Section 5, utilizing pre-trained neural networks on tasks such as image denoising, image inpainting and training support vector machines (Tan et al., 2023b;a).

Section 6 introduces a method of reducing the dimensionality of the mirror maps without affecting the expressivity, by exploiting the symmetries in the considered functions, with applications to training mirror maps on neural networks. Moreover, the lower dimensionality allows us to consider parameterizations of mirror maps with exact inverses, bypassing the forward-backward inconsistency problem. We utilize equivariance to extend a simple version of LMD to train deep neural networks in Section 7, where we demonstrate competitive performance with Adam on non-convex problem classes.

2 Learned Accelerated MD

In this section, we first present a mirror descent analog to the Nesterov accelerated gradient descent scheme (Nesterov, 1983). The resulting scheme, named accelerated mirror descent (AMD), can be considered as a discretization of a coupled ODE. Krichene et al. (2015) show accelerated convergence rates of the ODE, which translate to a discrete-time algorithm after a particular discretization. The analysis and convergence rates of AMD are similar to the ODE formulation for Nesterov accelerated gradient descent given in Su et al. (2014), where both papers show $\mathcal{O}(1/k^2)$ convergence rate of function value.

By considering the discrete AMD iterations with inexact mirror maps, we then generalize this algorithm to the approximate case, given in Algorithm 1, and provide the corresponding convergence rate bound. This can then be applied in the case where the forward and backward mirror maps are given by neural networks, leading to convergence results for learned accelerated mirror descent (LAMD). Our main contribution in this section is Theorem 1, which shows convergence of the function value to the minimum, rather than to the minimum plus a constant.

Step 3 of Algorithm 1 is the mirror descent step of AMD, where $\tilde{z}^{(k)}$ represents a (computable) approximate mirror descent iteration. The additional step in Step 4 arises as a correction term to allow for convergence

---

Algorithm 1 Accelerated mirror descent (AMD) with approximate mirror updates

---

Require: $\tilde{x}^{(0)} = \tilde{z}^{(0)} = x^{(0)}$, step-sizes t_k, parameter $r \geq 3$

1: **for** $k \in \mathbb{N}$ **do**
2:      $x^{(k+1)} = \lambda_k \tilde{z}^{(k)} + (1 - \lambda_k)\tilde{x}^{(k)}$ with $\lambda_k = \frac{r}{r+k}$
3:      $\tilde{z}^{(k+1)} = \nabla M_\vartheta^* (\nabla M_\theta(\tilde{z}^{(k)}) - \frac{kt_k}{r}\nabla f(x^{(k+1)}))$
4:      $\tilde{x}^{(k+1)} = \arg\min_{\tilde{x} \in \mathbb{R}^n} \gamma t_k \left\langle \nabla f(x^{(k+1)}), \tilde{x} \right\rangle + R(\tilde{x}, x^{(k+1)})$
5: **end for**

---

analysis (Krichene et al., 2015). Here, R is a regularization function where there exists $0 < \ell_R \leq L_R$ such that for all $x, x' \in \mathcal{X}$, we have

$$\frac{\ell_R}{2}\|x - x'\|^2 \leq R(x, x') \leq \frac{L_R}{2}\|x - x'\|^2.$$

For practical purposes, R can be taken to be the Euclidean distance $R(x, x') = \frac{1}{2}\|x - x'\|^2$, in which case $\ell_R = L_R = 1$. Taking R of this form reduces Step 4 to the following gradient descent step:

$$\tilde{x}^{(k+1)} = x^{(k+1)} - \gamma t_k \nabla f(x^{(k+1)}).$$

Similarly to Tan et al. (2023b), we additionally define a sequence $\hat{z}^{(k)}$ that comprises the true mirror descent updates, applied to the intermediate iterates $\tilde{z}^{(k)}$:

$$\hat{z}^{(k+1)} = (\nabla M_\theta)^{-1}\left(\nabla M_\theta(\tilde{z}^{(k)}) - \frac{kt_k}{r}\nabla f(x^{(k+1)})\right). \tag{5}$$

This additional variable will allow us to quantify the approximation error, with which we will show the approximate convergence. For ease of notation, we will denote the forward mirror potential by $\psi = M_\theta$. With this notation, ψ^* is the convex conjugate, satisfying $\nabla \psi^* = (\nabla \psi)^{-1}$. The true mirror descent iterates can be written as $\hat{z}^{(k+1)} = \nabla \psi^* \left(\nabla \psi(\tilde{z}^{(k)}) - \frac{kt_k}{r}\nabla f(x^{(k+1)})\right)$. We begin with the following lemma, which bounds the difference between consecutive energies to be the sum of a negative term and an approximation error term.

Lemma 1. *Consider the approximate AMD iterations from Algorithm 1, and let $\hat{z}^{(k)}$ be the exact MD iterates given by Equation 5. Assume ψ^* is L_{ψ^*}-smooth with respect to a reference norm $\|\cdot\|_*$ on the dual space, i.e. $B_{\psi^*}(z, y) \leq \frac{L_{\psi^*}}{2}\|z - y\|_*^2$, or equivalently that $\nabla \psi^*$ is L_{ψ^*}-Lipschitz. Assume further that there exists $0 < \ell_R \leq L_R$ such that for all $x, x' \in \mathcal{X}$, $\frac{\ell_R}{2}\|x - x'\|^2 \leq R(x, x') \leq \frac{L_R}{2}\|x - x'\|^2$. Define the energy $\tilde{E}^{(k)}$ for $k \geq 0$ as follows (where $t_{-1} = 0$):*

$$\tilde{E}^{(k)} := \frac{k^2 t_{k-1}}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) + rB_{\psi^*}\left(\nabla \psi(\tilde{z}^{(k)}), \nabla \psi(x^*)\right). \tag{6}$$

Assume the step-size conditions $\gamma \geq L_R L_{\psi^*}$, and $t_k \leq \frac{l_R}{L_f \gamma}$. Then the difference between consecutive energies satisfies the following:

$$\tilde{E}^{(k+1)} - \tilde{E}^{(k)} \leq \frac{(2k + 1 - rk)t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) - \frac{k^2(t_{k-1} - t_k)}{r}\left(f(\tilde{x}^{(k)}) - f^*\right)$$
$$+ r\left\langle \nabla \psi(\tilde{z}^{(k+1)}) - \nabla \psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle.$$

Proof. The proof closely follows that of Lemma 2 in Krichene et al. (2015). We will use the following lemmas, which will be stated without proof. The proofs of these results can be found in the supplementary material of Krichene et al. (2015).

Lemma 2. *Let f be convex with L_f-Lipschitz gradient with respect to $\|\cdot\|$. Then for all x, x', x^+,*

$$f(x^+) \leq f(x') + \langle \nabla f(x), x^+ - x' \rangle + \frac{L_f}{2}\|x^+ - x\|^2.$$

Lemma 3. *For any differentiable convex ψ^* and $u, v, w \in \operatorname{dom} \psi^*$,*

$$B_{\psi^*}(u, v) - B_{\psi^*}(w, v) = -B_{\psi^*}(w, u) + \langle \nabla\psi^*(u) - \nabla\psi^*(v), u - w \rangle.$$

Lemma 4. *If ψ^* has L_{ψ^*}-Lipschitz gradient, then for all $u, v \in (\mathbb{R}^n)^*$,*

$$\frac{1}{2L_{\psi^*}}\|\nabla\psi^*(u) - \nabla\psi^*(v)\|^2 \leq B_{\psi^*}(u, v) \leq \frac{L_{\psi^*}}{2}\|u - v\|_*^2.$$

We begin our analysis with these lemmas in place. Let $x^* = z^*$ be some minimizer. We begin by bounding the difference in Bregman divergence.

$$B_{\psi^*}\left(\nabla\psi(\tilde{z}^{(k+1)}), \nabla\psi(x^*)\right) - B_{\psi^*}\left(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(x^*)\right)$$

$$\overset{\text{(a)}}{=} -B_{\psi^*}\left(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(\tilde{z}^{(k+1)})\right) + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\tilde{z}^{(k)}), \tilde{z}^{(k+1)} - x^* \right\rangle$$

$$\overset{\text{(b)}}{\leq} -\frac{1}{2L_{\psi^*}}\|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\tilde{z}^{(k)}), \tilde{z}^{(k+1)} - x^* \right\rangle$$

$$\overset{\text{(c)}}{\leq} -\frac{1}{2L_{\psi^*}}\|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 + \left\langle -\frac{kt_k}{r}\nabla f(x^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle.$$
(7)

In Step (a) above, we used $\nabla\psi^* \circ \nabla\psi = I$ and $z^* = x^*$ together with Lemma 3. In Step (b), we use Lemma 4 to bound the first term. In Step (c), we decomposed the right-hand side of the inner product using

$$\nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}) + \nabla\psi(\hat{z}^{(k+1)}) - \nabla\psi(\tilde{z}^{(k)}) = \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}) - \frac{kt_k}{r}\nabla f(x^{(k+1)}),$$

which follows directly from Equation 5. Recall Step 4 of Algorithm 1:

$$\tilde{x}^{(k+1)} = \arg\min_{\tilde{x}\in\mathbb{R}^n} \left\langle \nabla f(x^{(k+1)}), \tilde{x} \right\rangle + \frac{1}{\gamma t_k} R(\tilde{x}, x^{(k+1)}),$$

where $\frac{l_R}{2}\|x - y\|^2 \leq R(x, y) \leq \frac{L_R}{2}\|x - y\|^2$. From the definition of $\tilde{x}^{(k+1)}$, we have that for any $x \in \mathbb{R}^n$,

$$R(x, x^{(k+1)}) \geq R(\tilde{x}^{(k+1)}, x^{(k+1)}) + \gamma t_k \langle \nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - x \rangle.$$
(8)

Recalling the step for $x^{(k+1)}$ in Step 2 of Algorithm 1, we can write

$$\tilde{z}^{(k+1)} - \tilde{z}^{(k)} = \frac{1}{\lambda_k}\left(\lambda_k\tilde{z}^{(k+1)} + (1-\lambda_k)\tilde{x}^{(k)} - x^{(k+1)}\right) = \frac{1}{\lambda_k}\left(d^{(k+1)} - x^{(k+1)}\right),$$

where we define $d^{(k+1)} := \lambda_k\tilde{z}^{(k+1)} + (1-\lambda_k)\tilde{x}^{(k)}$. We then compute

$$\|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 = \frac{1}{\lambda_k^2}\|d^{(k+1)} - x^{(k+1)}\|^2 \geq \frac{2}{L_R\lambda_k^2}R(d^{(k+1)}, x^{(k+1)}), \text{ since } R(x, x') \leq \frac{L_R}{2}\|x - x'\|^2.$$

$$\implies \|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 \geq \frac{2}{L_R\lambda_k^2}\left(R(\tilde{x}^{(k+1)}, x^{(k+1)}) + \gamma t_k\left\langle \nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - d^{(k+1)} \right\rangle\right),$$

by setting $x = d^{(k+1)}$ in Equation 8. Now, using $R(\tilde{x}^{(k+1)}, x^{(k+1)}) \geq \frac{l_R}{2}\|\tilde{x}^{(k+1)} - x^{(k+1)}\|^2$, we have:

$$\|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 \geq \frac{2}{L_R\lambda_k^2}\left(\frac{l_R}{2}\|\tilde{x}^{(k+1)} - x^{(k+1)}\|^2 + \gamma t_k\left\langle \nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - d^{(k+1)} \right\rangle\right).$$

By replacing $d^{(k+1)} = \lambda_k\tilde{z}^{(k+1)} + (1-\lambda_k)\tilde{x}^{(k)}$ and multiplying both sides by $\lambda_k\frac{kL_R}{2r\gamma}$, we get

$$\lambda_k\frac{kL_R}{2r\gamma}\|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 \geq \frac{kl_R}{2r\lambda_k\gamma}\|\tilde{x}^{(k+1)} - x^{(k+1)}\|^2$$

$$+ \left\langle \frac{kt_k}{r}\nabla f(x^{(k+1)}), \frac{1}{\lambda_k}\tilde{x}^{(k+1)} - \tilde{z}^{(k+1)} - \frac{1-\lambda_k}{\lambda_k}\tilde{x}^{(k)} \right\rangle. \quad (9)$$

Subtracting Equation 9 from Equation 7:

$$B_{\psi^*}(\nabla\psi(\tilde{z}^{(k+1)}), \nabla\psi(x^*)) - B_{\psi^*}(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(x^*)) \leq -\alpha_k \|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2 - \frac{kl_R}{2r\lambda_k\gamma}\|\tilde{x}^{(k+1)} - x^{(k+1)}\|^2$$
$$+ \left\langle \frac{-kt_k}{r}\nabla f(x^{(k+1)}), -x^* + \frac{1}{\lambda_k}\tilde{x}^{(k+1)} - \frac{1-\lambda_k}{\lambda_k}\tilde{x}^{(k)} \right\rangle + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle,$$

where $\alpha_k = \frac{1}{2L_{\psi^*}} - \frac{k\lambda_k L_R}{2r\gamma}$. Defining $D_1^{(k+1)} = \|\tilde{x}^{(k+1)} - x^{(k+1)}\|^2$ and $D_2^{(k+1)} = \|\tilde{z}^{(k+1)} - \tilde{z}^{(k)}\|^2$, we rewrite the last inequality as

$$B_{\psi^*}(\nabla\psi(\tilde{z}^{(k+1)}), \nabla\psi(x^*)) - B_{\psi^*}(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(x^*))$$
$$\leq -\alpha_k D_2^{(k+1)} - \frac{kl_R}{2r\lambda_k\gamma}D_1^{(k+1)} + \frac{kt_k}{r}\left\langle -\nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - x^* \right\rangle$$
$$+ \frac{1-\lambda_k}{\lambda_k}\frac{kt_k}{r}\left\langle -\nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - \tilde{x}^{(k)} \right\rangle + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle.$$

Using Lemma 2 with x, x^+, x' as follows, we bound the inner products:

$$\left\langle -\nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - \tilde{x}^{(k)} \right\rangle \leq f(\tilde{x}^{(k)}) - f(\tilde{x}^{(k+1)}) + \frac{L_f}{2}D_1^{(k+1)}, \ (x = x^{(k+1)}, \ x^+ = \tilde{x}^{(k+1)}, \text{ and } x' = \tilde{x}^{(k)});$$
$$\left\langle -\nabla f(x^{(k+1)}), \tilde{x}^{(k+1)} - x^* \right\rangle \leq f^* - f(\tilde{x}^{(k+1)}) + \frac{L_f}{2}D_1^{(k+1)}, \ (x = x^{(k+1)}, \ x^+ = \tilde{x}^{(k+1)}, \text{ and } x' = x^*).$$

Combining the inequalities and using $\frac{1-\lambda_k}{\lambda_k} = \frac{k}{r}$, we obtain

$$B_{\psi^*}(\nabla\psi(\tilde{z}^{(k+1)}), \nabla\psi(x^*)) - B_{\psi^*}(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(x^*))$$
$$\leq -\alpha_k D_2^{(k+1)} + \frac{k^2 t_k}{r^2}\left(f(\tilde{x}^{(k)}) - f(\tilde{x}^{(k+1)}) + \frac{L_f}{2}D_1^{(k+1)} \right) + \frac{kt_k}{r}\left(f^* - f(\tilde{x}^{(k+1)}) + \frac{L_f}{2}D_1^{(k+1)} \right)$$
$$- \frac{kl_R}{2r\lambda_k\gamma}D_1^{(k+1)} + \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle$$
$$= \frac{k^2 t_k}{r^2}\left(f(\tilde{x}^{(k)}) - f(\tilde{x}^{(k+1)}) \right) + \frac{kt_k}{r}\left(f^* - f(\tilde{x}^{(k+1)}) \right) - \alpha_k D_2^{(k+1)} - \beta_k D_1^{(k+1)}$$
$$+ \left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle,$$

where $\beta_k := \frac{kl_R}{2r\lambda_k\gamma} - \frac{L_f k^2 t_k}{2r^2} - \frac{L_f kt_k}{2r}$. Re-introducing the energy function for $k \geq 1$,

$$\tilde{E}^{(k)} := \frac{k^2 t_{k-1}}{r}(f(\tilde{x}^{(k)}) - f^*) + rB_{\psi^*}(\nabla\psi(z^{(k)}), \nabla\psi(x^*)),$$

we can compute the difference $\tilde{E}^{(k+1)} - \tilde{E}^{(k)}$:

$$
\begin{aligned}
\tilde{E}^{(k+1)} - \tilde{E}^{(k)} &= \frac{(k+1)^2 t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) - \frac{k^2 t_{k-1}}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) \\
&\quad + r(B_{\psi^*}(\nabla\psi(\tilde{z}^{(k+1)}), \nabla\psi(x^*)) - B_{\psi^*}(\nabla\psi(\tilde{z}^{(k)}), \nabla\psi(x^*))) \\
&= \frac{k^2 t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) + \frac{(2k+1)t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) \\
&\quad - \frac{k^2 t_k}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) - \frac{k^2 t_{k-1} - k^2 t_k}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) \\
&\quad + \frac{k^2 t_k}{r}\left(f(\tilde{x}^{(k)}) - f(\tilde{x}^{(k+1)})\right) + k t_k\left(f^* - f(\tilde{x}^{(k+1)})\right) - r\alpha_k D_2^{(k+1)} - r\beta_k D_1^{(k+1)} \\
&\quad + r\left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^*\right\rangle \\
&= \frac{(2k+1-rk)t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) - \frac{k^2(t_{k-1} - t_k)}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) - r\alpha_k D_2^{(k+1)} - r\beta_k D_1^{(k+1)} \\
&\quad + r\left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^*\right\rangle.
\end{aligned}
$$

For the desired inequality to hold, it suffices that $\alpha_k, \beta_k \geq 0$. Recalling their definitions (and λ_k), we want

$$
\frac{1}{2L_{\psi^*}} - \frac{kL_R}{2(r+k)\gamma} \geq 0 \text{ and } \frac{k(r+k)l_R}{2r^2\gamma} - \frac{L_f k^2 t_k}{2r^2} - \frac{L_f k t_k}{2r} \geq 0,
$$

which are equivalent to

$$
\gamma \geq \frac{kr}{kr+r^2}L_R L_{\psi^*} \text{ and } t_k \leq \frac{l_R}{L_f \gamma}.
$$

It thus suffices to have

$$
\gamma \geq L_R L_{\psi^*}, \quad t_k \leq \frac{l_R}{L_f \gamma}.
$$

Under these conditions, we get the bound as required

$$
\begin{aligned}
\tilde{E}^{(k+1)} - \tilde{E}^{(k)} &\leq \frac{(2k+1-rk)t_k}{r}\left(f(\tilde{x}^{(k+1)}) - f^*\right) - \frac{k^2(t_{k-1} - t_k)}{r}\left(f(\tilde{x}^{(k)}) - f^*\right) \\
&\quad + r\left\langle \nabla\psi(\tilde{z}^{(k+1)}) - \nabla\psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^*\right\rangle.
\end{aligned}
$$

$\square$

Lemma 1 gives us a way of telescoping the energy $\tilde{E}$. To turn this into a bound on the objective values $f(\tilde{x}^{(k)}) - f^*$, we need the initial energy. The following proposition gives a bound on the energy $\tilde{E}^{(1)}$, which when combined with telescoping with Lemma 1, will be used to derive bounds on the objective.

Proposition 1. *Assume the conditions as in Lemma 1. Then*

$$
\tilde{E}^{(1)} \leq rB_{\psi^*}(\nabla\psi(x^{(0)}), \nabla\psi(x^*)) + \frac{t_0}{r}(f(x^{(0)}) - f^*) + r\left\langle \nabla\psi(\tilde{z}^{(1)}) - \nabla\psi(\hat{z}^{(1)}), \tilde{z}^{(1)} - x^*\right\rangle \tag{10}
$$

Proof. The proof relies on bounding $f(\tilde{x}^{(1)}) - f^*$, which is done identically to that in Krichene et al. (2015). From Lemma 1 applied with $k = 0$, we have

$$
\begin{aligned}
\tilde{E}^{(1)} &\leq \tilde{E}^{(0)} + \frac{t_0}{r}\left(f(\tilde{x}^{(1)}) - f^*\right) + r\left\langle \nabla\psi(\tilde{z}^{(1)}) - \nabla\psi(\hat{z}^{(1)}), \tilde{z}^{(1)} - x^*\right\rangle \\
&= rB_{\psi^*}\left(\nabla\psi(z^{(0)}), \nabla\psi(x^*)\right) + \frac{t_0}{r}\left(f(\tilde{x}^{(1)}) - f^*\right) + r\left\langle \nabla\psi(\tilde{z}^{(1)}) - \nabla\psi(\hat{z}^{(1)}), \tilde{z}^{(1)} - x^*\right\rangle.
\end{aligned}
$$

By definition, $\tilde{x}^{(1)} = \arg\min_{\tilde{x} \in \mathbb{R}^n} \gamma t_0 \langle \nabla f(x^{(1)}), \tilde{x} \rangle + R(\tilde{x}, x^{(1)})$, thus (since $R(x, x) = 0$)

$$\gamma t_0 \left\langle \nabla f(x^{(1)}), \tilde{x}^{(1)} \right\rangle + R(\tilde{x}^{(1)}, x^{(1)}) \leq \gamma t_0 \left\langle \nabla f(x^{(1)}), x^{(1)} \right\rangle. \tag{11}$$

Therefore, we get

$$
\begin{aligned}
f(\tilde{x}^{(1)}) - f^* &\leq \left\langle \nabla f(x^{(1)}), \tilde{x}^{(1)} - x^* \right\rangle + \frac{L_f}{2} \|\tilde{x}^{(1)} - x^{(1)}\|^2 && \text{by Lemma 2} \\
&\leq \left\langle \nabla f(x^{(1)}), \tilde{x}^{(1)} - x^* \right\rangle + \frac{L_f}{l_R} R(\tilde{x}^{(1)}, x^{(1)}) && \text{by assumption on } R \\
&\leq \left\langle \nabla f(x^{(1)}), \tilde{x}^{(1)} - x^* \right\rangle + \frac{1}{\gamma t_0} R(\tilde{x}^{(1)}, x^{(1)}) - \frac{L_f}{l_R} R(\tilde{x}^{(1)}, x^{(1)}) && \text{using } \frac{2L_f}{l_R} \leq \frac{1}{\gamma t_0} \\
&\leq \left\langle \nabla f(x^{(1)}), x^{(1)} - x^* \right\rangle - \frac{L_f}{l_R} R(\tilde{x}^{(1)}, x^{(1)}) && \text{using Equation 11} \\
&\leq f(x^{(1)}) - f^* + \frac{L_f}{2} \|x^{(1)} - x^*\|^2 - \frac{L_f}{l_R} R(\tilde{x}^{(1)}, x^{(1)}) && \text{using Lemma 2} \\
&\leq f(x^{(1)}) - f^* && \text{by assumption on } R.
\end{aligned}
$$

Now recalling that $x^{(1)} = \lambda_0 \tilde{z}^{(0)} + (1 - \lambda_0)\tilde{x}^{(0)}$ and $\lambda_0 = 1$, we have $x^{(1)} = \tilde{x}^{(0)} = x^{(0)}$. Therefore, we have $f(\tilde{x}^{(1)}) - f^* \leq f(x^{(0)}) - f^*$. Further using $\tilde{z}^{(0)} = x^{(0)}$ shows the desired inequality. $\qquad\square$

Putting together Lemma 1 and Proposition 1, we get the following theorem that bounds the objective value of the approximate AMD iterates.

Theorem 1. *Assume the conditions as in Lemma 1. Assume also that the step-sizes $(t_k)_{k=0}^{\infty}$ are non-increasing, and that the approximation error term, given by*

$$\left\langle \nabla \psi(\tilde{z}^{(k+1)}) - \nabla \psi(\hat{z}^{(k+1)}), \tilde{z}^{(k+1)} - x^* \right\rangle, \tag{12}$$

is uniformly bounded by a constant $M > 0$. If our step-sizes are chosen as $t_k = \Theta(k^{-c})$ for $c \in [0, 1)$, then we get $\mathcal{O}(k^{c-1})$ convergence in objective value.

Proof. Summing the expression in Lemma 1, noting the first two terms are non-positive for $k \geq 1$ since t_k is non-increasing and $r \geq 3$, and noting that the final term is bounded by rM,

$$\tilde{E}^{(k+1)} \leq \tilde{E}^{(1)} + krM.$$

By definition of $\tilde{E}$ and non-negativity of B_{ψ^*}, we also have

$$f(\tilde{x}^{(k+1)}) - f^* \leq \frac{r}{(k+1)^2 t_k} \tilde{E}^{(k+1)} \leq \frac{r}{(k+1)^2 t_k} [\tilde{E}^{(1)} + krM] = \mathcal{O}(k^{c-1}). \tag{13}$$

$\qquad\square$

This theorem shows that we are actually able to obtain convergence to the function objective minimum by using acceleration, as opposed to the minimum plus a constant given in Tan et al. (2023b). There are two main ideas at play here. One is that the acceleration makes the function value decrease fast enough, as seen by the energy given in Equation 6 growing as $\mathcal{O}(k)$, while having a $k^2 t_k$ factor in front of the objective difference term. The second idea is that the λ_k factor in Step 2 of Algorithm 1 decreases the importance of the mirror descent step, which thus reduces the effect of the forward-backward inconsistency.

3 Learned Stochastic MD

Stochastic mirror descent (SMD) arises when we are able to sample gradients $\mathsf{G}(x^k, \xi^k)$ such that the expectation of G is equal to a subgradient of our convex objective f. For example, in large-scale imaging applications such as CT, computing the forward operator may be expensive, and a stochastic gradient may consist of computing a subset of the forward operator. Another example would be neural network training over large data sets, where there is insufficient memory to keep track of the gradients of the network parameters over all of the given data. Therefore, we wish to extend the analysis for approximate mirror descent to the case where we only have access to stochastic gradients.

While it may be tempting to put the stochastic error into the approximation error terms of the previous analyses, stochastic errors may be unbounded, violating the theorem assumptions. This section will extend approximate MD to the case where the approximation error is now the sum of a bounded term and a zero-mean term with finite second moments. In particular, Theorem 2 shows an expected regret bound depending on the stochastic noise based on bounded variance and bounded error assumptions.

We base the analysis of this section on the robust stochastic approximation approach (Nemirovski et al., 2009). We require two additional assumptions in this setting as follows:

Assumption 1. *We can draw i.i.d. samples $\xi^{(0)}, \xi^{(1)}, \dots$ of a random vector $\xi \in \Xi$.*

Assumption 2. *An oracle G exists for which, given an input $(x, \xi) \in \mathcal{X} \times \Xi$, returns a vector $\mathsf{G}(x, \xi)$ such that $g(x) \coloneqq \mathbb{E}_\xi[\mathsf{G}(x, \xi)]$ is well defined and satisfies $g(x) \in \partial f(x)$.*

If f can be written as an expectation $f(x) = \mathbb{E}[\mathsf{F}(x, \xi)]$, where $\mathsf{F}(\cdot, \xi)$ is convex with f having finite values in a neighborhood of a point x, then we can interchange the subgradient with the expectation (Strassen, 1965),

$$\partial f(x) = \mathbb{E}[\partial_x \mathsf{F}(x, \xi)].$$

Stochastic MD thus generalizes MD by replacing the subgradient ∇f at each step with this gradient oracle G, which can be written as follows

$$x^{(k+1)} = \nabla \psi^* \left(\nabla \psi(x^{(k)}) - t_k \mathsf{G}(x^{(k)}, \xi^{(k)}) \right). \tag{14}$$

Observe that under this formulation, we can additionally encode a noise component that arises as a result of inexact mirror descent computation. Therefore, we may redefine $\mathsf{G}(x, \xi)$ as an inexact stochastic oracle as in the introduction, having two components

$$\mathsf{G}(x, \xi) = g(x) + \Delta(x, \xi) + U(x),$$

where $\Delta(\cdot, \xi)$ signifies stochastic noise satisfying $\mathbb{E}[\Delta(x)] = \mathbf{0}$, and $U(x)$ is a deterministic error to model the approximation error of computing MD steps. We will use the notation $\Delta_k = \Delta(x^{(k)}, \xi^{(k)})$, $U_k = U(x^{(k)})$ to signify these values at each iteration.

Algorithm 2 Stochastic mirror descent (SMD) (Nemirovski et al., 2009)

Require: $x^{(0)} \in \mathcal{X}$, step-sizes $t_k > 0$, stochastic oracle G, random i.i.d. $\xi^{(k)}$
1: **for** $k \in \mathbb{N}$ **do**
2:      $x^{(k+1)} = \nabla \psi^*(\nabla \psi(x^{(k)}) - t_k \mathsf{G}(x^{(k)}, \xi^{(k)}))$
3: **end for**

We first reformulate the MD iterates into a "generalized proximal" form. In particular, a small modification of the argument in Beck & Teboulle (2003) shows that the SMD iterations given in Equation (14) can be written as follows:

$$x^{(k+1)} = \underset{x' \in \mathcal{X}}{\arg\min} \left\{ \left\langle \mathsf{G}(x^{(k)}, \xi^{(k)}), x' \right\rangle + \frac{1}{t_k} B_\psi(x', x^{(k)}) \right\}. \tag{15}$$

This can be written in terms of the *prox-mapping* $P_x : (\mathbb{R}^n)^* \to \mathcal{X}$, defined as follows:

$$P_x(y) = \underset{x' \in \mathcal{X}}{\arg\min} \left\{ \langle y, x' \rangle + B_\psi(x', x) \right\}, \tag{16a}$$

$$x^{(k+1)} = P_{x^{(k)}} \left(t_k \mathsf{G}(x^{(k)}, \xi^{(k)}) \right). \tag{16b}$$

The following lemma characterizes the effect of a mirror step on the Bregman divergence. We use this lemma to show a regret bound on SMD with the inexact stochastic oracle $\mathsf{G}(x, \xi)$ similarly to Nemirovski et al. (2009), where the bound depends on the variance of the stochastic component $\Delta(x, \xi)$ and the norm of the inexactness $U(x)$.

Lemma 5 (Nemirovski et al. 2009, Lem. 2.1). *For any $u, x \in \mathcal{X}$ and $y \in (\mathbb{R}^n)^*$, we have (where ψ is α-strongly convex),*

$$B_\psi(u, P_x(y)) \leq B_\psi(u, x) + \langle y, u - x \rangle + \frac{\|y\|_*^2}{2\alpha}. \tag{17}$$

Applying Equation 17 with $x = x^{(k)}$, $y = t_k \mathsf{G}(x^{(k)}, \xi^{(k)})$, given any point $u \in \mathcal{X}$, we have

$$t_k \langle \mathsf{G}(x^{(k)}, \xi^{(k)}), x^{(k)} - u \rangle \leq B_\psi(u, x^{(k)}) - B_\psi(u, x^{(k+1)}) + \frac{t_k^2}{2\alpha} \|\mathsf{G}(x^{(k)}, \xi^{(k)})\|_*^2. \tag{18}$$

Using the definition of G, we can expand

$$\begin{aligned} t_k \langle g(x^{(k)}), x^{(k)} - u \rangle &\leq B_\psi(u, x^{(k)}) - B_\psi(u, x^{(k+1)}) + \frac{t_k^2}{2\alpha} \|\mathsf{G}(x^{(k)}, \xi^{(k)})\|_*^2 \\ &\quad - t_k \langle \Delta_k, x^{(k)} - u \rangle - t_k \langle U_k, x^{(k)} - u \rangle. \end{aligned} \tag{19}$$

Observe that since f is convex and $g(x) \in \partial f(x)$, we have $\langle g(x^{(k)}), x^{(k)} - u \rangle \geq f(x^{(k)}) - f(u)$. Using this, summing Equation 19 from 1 to k, and noting that $B_\psi \geq 0$, we have

$$\sum_{i=0}^k t_i[f(x^{(i)}) - f(u)] \leq B_\psi(u, x^{(0)}) + \sum_{i=0}^k \frac{t_i^2}{2\alpha} \|\mathsf{G}(x^{(i)}, \xi^{(i)})\|_*^2 - \sum_{i=0}^k t_i \langle \Delta_i, x^{(i)} - u \rangle - \sum_{i=0}^k t_i \langle U_i, x^{(i)} - u \rangle. \tag{20}$$

Observing that $\mathbb{E}[\Delta_i | \xi_0, ..., \xi_{i-1}] = 0$ and that $x^{(i)}$ lives in the σ-algebra defined by $\xi_0, ..., \xi_{i-1}$, we have that for any i,

$$\mathbb{E}[\langle \Delta_i, x^{(i)} - u \rangle] = \mathbb{E}\left[\mathbb{E}\left[\langle \Delta_i, x^{(i)} - u \rangle \mid \xi_0, ..., \xi_{i-1}\right]\right] = 0.$$

We can take expectations over ξ to get

$$\mathbb{E}\left[\sum_{i=0}^k t_i[f(x^{(i)}) - f(u)]\right] \leq B_\psi(u, x^{(0)}) + \sum_{i=0}^k \frac{t_i^2}{2\alpha} \mathbb{E}\left[\|\mathsf{G}(x^{(i)}, \xi^{(i)})\|_*^2\right] - \sum_{i=0}^k t_i \mathbb{E}\left[\langle U_i, x^{(i)} - u \rangle\right].$$

Assuming that the stochasticity is bounded

$$\mathbb{E}[\|\mathsf{G}(x, \xi)\|_*^2] \leq \sigma^2 \quad \forall x \in \mathcal{X},$$

this gives a regret bound, which can be extended to convergence of the ergodic average.

If f were μ-strongly convex, then we can remove the uniform boundedness assumption since this allows us to control $\|x^{(i)} - u\|$, using the fact that $\langle g(x^{(k)}), x^{(k)} - u \rangle \geq f(x^{(k)}) - f(u) + \mu \|x^{(k)} - u\|^2/2$. Equation 20 instead becomes

$$\begin{aligned} \sum_{i=0}^k t_i[f(x^{(i)}) - f(u)] &\leq B_\psi(u, x^{(0)}) + \sum_{i=0}^k \frac{t_i^2}{2\alpha} \|\mathsf{G}(x^{(i)}, \xi^{(i)})\|_*^2 \\ &\quad - \sum_{i=0}^k t_i \langle \Delta_i, x^{(i)} - u \rangle - \sum_{i=0}^k t_i \left[\langle U_i, x^{(i)} - u \rangle + \frac{\mu}{2} \|x^{(i)} - u\|^2\right]. \end{aligned} \tag{21}$$

Taking expectations as before and using Young's inequality on the final term, we get

$$\mathbb{E}\left[\sum_{i=0}^{k} t_i[f(x^{(i)}) - f(u)]\right] \leq B_\psi(u, x^{(0)}) + \sum_{i=0}^{k} \frac{t_i^2}{2\alpha} \mathbb{E}\left[\|\mathsf{G}(x^{(i)}, \xi^{(i)})\|_*^2\right] + \sum_{i=0}^{k} \frac{t_i}{2\mu}\|U_i\|_*^2.$$

Putting everything together, we get the following theorem that bounds the expected regret of the approximate SMD iterations.

Theorem 2. *Consider the approximate SMD iterations $x^{(i)}$ generated by Equation 14. Suppose that the stochastic oracle satisfies $\mathbb{E}[\|\mathsf{G}(x, \xi)\|_*^2] \leq \sigma^2$ for all $x \in \mathcal{X}$ for some $\sigma \geq 0$. Let x^* be some minimizer of f.*

1. If $\langle U_i, x^{(i)} - x^* \rangle$ is uniformly bounded by C, then the expected loss satisfies

$$\mathbb{E}\left[\sum_{i=0}^{k} t_i[f(x^{(i)}) - f^*]\right] \leq B_\psi(x^*, x^{(0)}) + \frac{\sigma^2}{2\alpha}\sum_{i=0}^{k} t_i^2 + C\sum_{i=0}^{k} t_i. \tag{22}$$

2. If f is μ-strongly convex and $\|U_i\|_*^2$ is uniformly bounded by C', the expected loss satisfies

$$\mathbb{E}\left[\sum_{i=0}^{k} t_i[f(x^{(i)}) - f^*]\right] \leq B_\psi(x^*, x^{(0)}) + \frac{\sigma^2}{2\alpha}\sum_{i=0}^{k} t_i^2 + \frac{C'}{2\mu}\sum_{i=0}^{k} t_i. \tag{23}$$

In particular, the ergodic average defined by

$$\tilde{x}_0^k = \sum_{i=0}^{k} \gamma_i x^{(i)}, \quad \gamma_i = \frac{t_i}{\sum_{i=0}^{k} t_i}$$

satisfies respectively

$$\mathbb{E}\left[f(\tilde{x}_0^k) - f^*\right] \leq \left(B_\psi(x^*, x^{(0)}) + \frac{\sigma^2}{2\alpha}\sum_{i=0}^{k} t_i^2\right) \Big/ \left(\sum_{i=0}^{k} t_i\right) + C, \tag{24}$$

$$\mathbb{E}\left[f(\tilde{x}_0^k) - f^*\right] \leq \left(B_\psi(x^*, x^{(0)}) + \frac{\sigma^2}{2\alpha}\sum_{i=0}^{k} t_i^2\right) \Big/ \left(\sum_{i=0}^{k} t_i\right) + \frac{C'}{2\mu}. \tag{25}$$

$\square$

Remark 1. *A stronger assumption to condition (1) in Theorem 2 is to assume uniformly bounded iterates, as well as uniformly bounded deterministic errors U_i. In LMD, deterministic errors arise due to mismatches in the learned mirror maps $\nabla M_\vartheta^* \approx (\nabla M_\theta)^{-1}$, which can be controlled using a soft penalty.*

We observe in Equations (24) and (25) that ℓ_2–ℓ_1 summability (where $\sum t_i^2 < +\infty$ but $\sum t_i = +\infty$) is a sufficient condition to remove the contribution of the first term to the ergodic average error. This is consistent with the empirical observation in Tan et al. (2023a) that extending the learned step-sizes using a reciprocal rule $t_k = c/k$ gives the best convergence results.

4 Learned Accelerated Stochastic MD

In the previous sections, we considered accelerated and stochastic variants of mirror descent and presented results pertaining to the convergence of these algorithms with noisy mirror maps. These two variants improve different parts of MD, with acceleration improving the convergence rates, while stochasticity improves the computational dependency on the gradient. Indeed, one of the drawbacks of SMD is the slow convergence rate of $\mathcal{O}(1/\sqrt{k})$ in expectation, where the constant depends on the Lipschitz constant of f. Acceleration as a tool to counteract this decrease in convergence rate for SMD has recently been explored, with convergence results such as convergence in high probability (Ene & Nguyen, 2022; Lan, 2020) and in expected function

value (Xu et al., 2018; Lan, 2012). These approaches decouple the gradient and stochastic noise, resulting in $\mathcal{O}(L/k^2 + \sigma/\sqrt{k})$ convergence rate, where C depends on the Lipschitz constant of ∇f, and σ^2 is the variance of the stochastic gradient.

We note that it is possible to extend Algorithm 1 (approximate AMD) to the stochastic case by directly replacing the gradient ∇f with a stochastic oracle G, albeit currently without convergence guarantees. In this section, we consider another version of approximate accelerated SMD that comes with convergence guarantees, using a slightly different proof technique.

For our analysis, we follow the accelerated SMD setup in Xu et al. (2018), in particular of Algorithm 2, replicated as below. Suppose that f is differentiable and has L_f-Lipschitz gradient, and let $\mathsf{G}(x, \xi) = \nabla_x \mathsf{F}(x, \xi)$ be a stochastic gradient satisfying

$$\mathbb{E}\left[\mathsf{G}(x^{(k)}, \xi^{(k)})\right] = \nabla f(x^{(k)}), \ \mathbb{E}\left[\|\mathsf{G}\|_*^2 \mid x^{(k)}\right] \le \sigma^2.$$

For simplicity, we let $\Delta_k = \mathsf{G}(x^{(k)}, \xi^{(k)}) - \nabla f(x^{(k)})$ denote the zero mean stochastic component.

Algorithm 3 Accelerated stochastic mirror descent (ASMD) (Xu et al., 2018, Alg. 2)

Require: Inputs $x^{(0)} \in \mathcal{X}, y^{(0)} = \nabla \psi(x^{(0)}) \in \mathcal{X}^*, A_0 = s_0 = 1/2$,
1: **for** $k \in \mathbb{N}$ **do**
2: $\quad A_{k+1} = (k+1)(k+2)/2, \ \tau_k = (A_{k+1} - A_k)/A_k, \ s_k = (k+1)^{3/2}$
3: $\quad x^{(k+1)} = \frac{\tau_k}{\tau_k + 1} \nabla \psi^*(y^{(k)}) + \frac{1}{\tau_k + 1} x^{(k)}$
4: $\quad y^{(k+1)} = y^{(k)} - \frac{A_{k+1} - A_k}{s_k} \mathsf{G}(x^{(k+1)}, \xi^{(k+1)})$
5: **end for**

An inexact convex conjugate can be modeled using a noise term in Step 3. With a noise term U, the step would instead read

$$x^{(k+1)} = \frac{\tau_k}{\tau_k + 1}\left[\nabla \psi^*(y^{(k)}) + U(y^{(k)})\right] + \frac{1}{\tau_k + 1} x^{(k)}. \tag{26}$$

The corresponding optimality conditions become

$$\nabla \psi^*(y^{(k)}) = x^{(k+1)} + \frac{A_k}{A_{k+1} - A_k}(x^{(k+1)} - x^{(k)}) - U^{(k)}, \tag{27}$$

$$y^{(k+1)} - y^{(k)} = -\frac{A_{k+1} - A_k}{s_k} \mathsf{G}(x^{(k+1)}, \xi^{(k+1)}). \tag{28}$$

We can perform a similar convergence analysis using the energy function given in Xu et al. (2018). Let $\mathcal{E}^{(k)} = \mathbb{E}[A_k(f(x^{(k)}) - f(x^*)) + s_k B_\psi(x^*, \nabla \psi^*(y^{(k)}))]$. We require a bound on the diameter of the optimization domain, as stated in the following assumption.

Assumption 3. *There exists a constant $M_\psi > 0$ such that $M_\psi = \sup_{x, x' \in \mathcal{X}} B_\psi(x, x')$.*

Using the following identity (which can be shown by expanding the Bregman distances using their definitions and using $\nabla \psi^* = (\nabla \psi)^{-1}$)

$$B_\psi(x^*, \nabla \psi^*(y^{(k+1)})) - B_\psi(x^*, \nabla \psi^*(y^{(k)})) - B_\psi(\nabla \psi^*(y^{(k)}), \nabla \psi^*(y^{(k+1)})) = \langle y^{(k)} - y^{(k+1)}, x^* - \nabla \psi^*(y^{(k)})\rangle,$$

we compute the difference in energy

$$
\begin{aligned}
\mathcal{E}^{(k+1)} - \mathcal{E}^{(k)} &= \mathbb{E}[A_{k+1}(f(x^{(k+1)}) - f(x^*)) - A_k(f(x^{(k)}) - f(x^*))] + \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla \psi^*(y^{(k+1)}))] \\
&\quad + s_k \mathbb{E}[B_\psi(x^*, \nabla \psi^*(y^{(k+1)})) - B_\psi(x^*, \nabla \psi^*(y^{(k)}))] \\
&= \mathbb{E}[A_{k+1}(f(x^{(k+1)}) - f(x^*)) - A_k(f(x^{(k)}) - f(x^*))] + \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla \psi^*(y^{(k+1)}))] \\
&\quad + s_k \mathbb{E}[B_\psi(\nabla \psi^*(y^{(k)}), \nabla \psi^*(y^{(k+1)})) + \langle y^{(k)} - y^{(k+1)}, x^* - \nabla \psi^*(y^{(k)})\rangle] \\
&= \mathbb{E}[A_{k+1}(f(x^{(k+1)}) - f(x^*)) - A_k(f(x^{(k)}) - f(x^*))] + \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla \psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[s_k B_\psi(\nabla \psi^*(y^{(k)}), \nabla \psi^*(y^{(k+1)})) + (A_{k+1} - A_k)\langle \mathsf{G}(x^{(k+1)}, \xi^{(k+1)}), x^* - \nabla \psi^*(y^{(k)})\rangle]
\end{aligned}
$$

where the second equality comes from the above identity, and the third equality from the definition of $y^{(k)}$. We further compute using the optimality conditions in Equations (27) and (28) and expanding $\mathsf{G}(x^{(k+1)}, \xi^{(k+1)}) = \nabla f(x^{(k+1)}) + \Delta_{k+1}$:

$$
\begin{aligned}
\mathcal{E}^{(k+1)} - \mathcal{E}^{(k)} &= \mathbb{E}[A_{k+1}(f(x^{(k+1)}) - f(x^*)) - A_k(f(x^{(k)}) - f(x^*))] + \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla\psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[s_k B_\psi(\nabla\psi^*(y^{(k)}), \nabla\psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\nabla f(x^{(k+1)}), x^* - x^{(k+1)}\rangle - A_k\langle\nabla f(x^{(k+1)}), x^{(k+1)} - x^{(k)}\rangle] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\Delta_{k+1}, x^* - \nabla\psi^*(y^{(k)})\rangle] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\mathsf{G}(x^{(k+1)}, \xi^{(k+1)}), U^{(k)}\rangle] \\
&\leq \mathbb{E}[A_{k+1}(f(x^{(k+1)}) - f(x^*)) - A_k(f(x^{(k)}) - f(x^*))] + \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla\psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[s_k B_\psi(\nabla\psi^*(y^{(k)}), \nabla\psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)(f(x^*) - f(x^{(k+1)})) + A_k(f(x^{(k)}) - f(x^{(k+1)}))\rangle] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\Delta_{k+1}, x^* - \nabla\psi^*(y^{(k)})\rangle] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\mathsf{G}(x^{(k+1)}, \xi^{(k+1)}), U^{(k)}\rangle] \\
&= \mathbb{E}[(s_{k+1} - s_k)B_\psi(x^*, \nabla\psi^*(y^{(k+1)}))] + \mathbb{E}[s_k B_\psi(\nabla\psi^*(y^{(k)}), \nabla\psi^*(y^{(k+1)}))] \\
&\quad + \mathbb{E}[(A_{k+1} - A_k)\langle\nabla f(x_{k+1}), U^{(k)}\rangle]
\end{aligned}
$$

where the second inequality follows from convexity of f, and the final equality from zero mean of Δ_{k+1} and independence with $y^{(k)}, U^{(k)}$.

Recalling that since ψ is α-strongly convex, we have that ψ^* is $1/\alpha$-strongly smooth. Using this, we have the following bound on the Bregman divergence:

$$
\begin{aligned}
B_\psi(\nabla\psi^*(y^{(k)}), \nabla\psi^*(y^{(k+1)})) = B_{\psi^*}(y^{(k+1)}, y^{(k)}) &\leq \frac{1}{2\alpha}\|y^{(k+1)} - y^{(k)}\|_*^2 \\
&\leq \frac{8L_f^2 M_\psi + 2\alpha\sigma^2 + 4\|\nabla f(x^*)\|_*^2}{\alpha}\frac{(A_{k+1} - A_k)^2}{2\alpha s_k^2},
\end{aligned}
$$

where the final iterate comes from the fact that for any $x \in \mathcal{X}$, $\|\nabla f(x)\|_* \leq \frac{L_f\sqrt{2M_\psi}}{\sqrt{\alpha}} + \|\nabla f(x^*)\|_*$, which is derived from the smoothness of f, strong convexity of ψ and bounded domain assumption. Furthermore, we have $B_\psi(x^*, \nabla\psi^*(y^{(k+1)})) \leq M_\psi$. Further assume that $\langle\nabla f(x^{(k+1)}), U^{(k)}\rangle$ is bounded, say by K. Substituting back we have

$$
\mathcal{E}^{(k+1)} - \mathcal{E}^{(k)} \leq M_\psi(s_{k+1} - s_k) + \frac{4L_f^2 M_\psi + \alpha\sigma^2 + 2\|\nabla f(x^*)\|_*^2}{\alpha^2}\frac{(A_{k+1} - A_k)^2}{s_k} + |A_{k+1} - A_k|K.
$$

Assuming that A_k is monotonically increasing (which will be justified later), we can sum from 0 to $k - 1$ and get

$$
\mathcal{E}^{(k)} \leq \mathcal{E}^{(0)} + M_\psi s_k + \frac{4L_f^2 M_\psi + \alpha\sigma^2 + 2\|\nabla f(x^*)\|_*^2}{\alpha^2}\sum_{j=0}^{k-1}\frac{(A_{j+1} - A_j)^2}{s_j} \\
+ A_k K.
$$

Taking $A_j = j(j+1)/2$ (which is monotonically increasing) and $s_j = (j+1)^{3/2}$, we get

$$
\mathcal{E}^{(k)} \leq \mathcal{E}^{(0)} + M_\psi(k+1)^{3/2} + \frac{4L_f^2 M_\psi + \alpha\sigma^2 + 2\|\nabla f(x^*)\|_*^2}{\alpha^2}\sum_{j=0}^{k-1}\sqrt{j+1} + A_k K
$$

$$
\leq \mathcal{E}^{(0)} + M_\psi(k+1)^{3/2} + \frac{8L_f^2 M_\psi + 2\alpha\sigma^2 + 4\|\nabla f(x^*)\|_*^2}{\alpha^2}(k+1)^{3/2} + A_k K.
$$

where we use the following lemma for divergent series for the final inequality.

Lemma 6 (Chlebus 2009). *For $p < 0$,*

$$1 + \frac{k^{1-p} - 1}{1 - p} \leq \sum_{j=1}^{k} j^{-p} \leq \frac{(k+1)^{1-p} - 1}{1 - p} \qquad (29)$$

Dividing throughout by A_k, we get

$$\mathbb{E}[f(x^{(k)}) - f(x^*)] \leq \mathcal{E}^{(0)}/A_k + \frac{(k+1)^{3/2}}{A_k} \left[M_\psi + \frac{8L_f^2 M_\psi + 2\alpha\sigma^2 + 4\|\nabla f(x^*)\|_*^2}{\alpha^2} \right] + K \qquad (30)$$

$$= K + \mathcal{O}(k^{-2} + k^{-1/2}).$$

Putting everything together, we get the following theorem.

Theorem 3. *Suppose f has L_f-Lipschitz gradient, the mirror map is α-strongly convex, the approximation error $U^{(k)}$ is bounded, and that the stochastic oracle is otherwise unbiased with bounded second moments. Assume Assumption 3 holds, that is, there exists a constant $M_\psi > 0$ such that*

$$M_\psi = \sup_{x,x' \in \mathcal{X}} B_\psi(x, x').$$

Suppose further that there exists a constant K such that for every iterate $x^{(k)}$, we have

$$\langle \nabla f(x^{(k)}), U^{(k)} \rangle \leq K.$$

Then the convergence rate of approximate ASMD is (where the right hand side is also given by Equation 30),

$$\mathbb{E}[f(x^{(k)}) - f(x^*)] \leq K + \mathcal{O}(k^{-2} + k^{-1/2}).$$

$\square$

Theorem 3 thus extends the classical $\mathcal{O}(k^{-2} + k^{-1/2})$ convergence rate for accelerated stochastic mirror descent to the approximate case, up to a constant depending on the approximation error. We note that f having bounded gradients is sufficient to satisfy the second assumption that $\langle \nabla f(x^{(k)}), U^{(k)} \rangle$ is bounded, as we have also assumed that $U^{(k)}$ is bounded.

5 Experiments

In this section, we demonstrate the performance of the proposed algorithms on image reconstruction and various training tasks. As we will be using neural networks to model the mirror potentials, we refer to the three proposed algorithms as learned AMD (LAMD), learned SMD (LSMD), and learned ASMD (LASMD) for the algorithms proposed in Sections 2 to 4 respectively with the learned mirror potentials. We will primarily consider GD, Nesterov accelerated GD, and the Adam optimizer as benchmarks for these tasks, with SGD where stochasticity is applicable. For fairness, we use pre-trained mirror maps as given in Tan et al. (2023b;a), and replicate selected experiments from these works to review the convergence behavior as compared to LMD.

The mirror maps were trained to minimize a loss function of the form

$$\tilde{L}(\theta, \vartheta) = \left[\sum_{k=1}^{N} f(\tilde{x}_k^{(i)}) + s_k \|(\nabla M_\vartheta^* \circ \nabla M_\theta - I)(\tilde{x}_k^{(i)})\| \right], \qquad (31)$$

where $\tilde{x}_k^{(i)}$ are the approximate MD iterations as in Equation (4), and the mirror maps are tied across each iteration. The loss $\tilde{L}$ is averaged over a family of training objectives f, such as TV-regularized image reconstruction or SVM hinge losses, and the regularization parameter s_k is increased as training progresses. The maximum unrolled iterations is set to $N = 10$, and the LMD step-sizes are also learned for these iterations (Tan et al., 2023b).

All implementations were done in PyTorch, and training was done on Quadro RTX 6000 GPUs with 24GB of memory (Paszke et al., 2019).

5.1 Numerical Considerations and Implementation

For numerical stability, we additionally store the dual variables $\nabla M_\theta(x^{(k)})$, similarly to ASMD in Algorithm 3. This avoids computing $\nabla M_\theta \circ \nabla M_\vartheta^*$, which would be the identity in the exact MD case where M_ϑ^* is the convex conjugate of M_θ, and appears to be a source of instability. For example, the current LMD scheme (with step-size t) computes

$$x^{(k+1)} = \nabla M_\vartheta^* \left(\nabla M_\theta(x^{(k)}) - t\nabla f(x^{(k)}) \right). \tag{32}$$

We propose to replace this with updates in the dual

$$y^{(k+1)} = y^{(k)} - t\nabla f(\nabla M_\vartheta^*(y^{(k)})), \; y^{(k)} = \nabla M_\theta(x^{(k)}). \tag{33}$$

In the case where $\nabla M_\vartheta^* = (\nabla M_\theta)^{-1}$, both schemes correspond exactly to mirror descent. The key difference is that the inconsistency is now within the ∇f which would heuristically be close to 0 around the minimum, instead of on the entire dual term. To put this in terms of forward-backward error, let $\hat{x}^{(k+1)} = \nabla M_\theta^{-1} \left(\nabla M_\theta x^{(k)} - t\nabla f(x^{(k)}) \right)$ be the exact mirror update on $x^{(k)}$ with mirror potential M_θ. The forward-backward inconsistencies $\nabla M_\theta(x^{(k+1)}) - \nabla M_\theta(\hat{x}^{(k+1)})$ for Equation (32) and Equation (33) would then be given respectively as

$$\nabla M_\theta(x^{(k+1)}) - \nabla M_\theta(\hat{x}^{(k+1)}) = \left(\nabla M_\vartheta^* - (\nabla M_\theta)^{-1}\right)\left(\nabla M_\theta x^{(k)} - t\nabla f(x^{(k)})\right) \quad \text{for the primal update,} \tag{34}$$

$$\nabla M_\theta(x^{(k+1)}) - \nabla M_\theta(\hat{x}^{(k+1)}) = t\nabla f(x^{(k)}) - t\nabla f(\nabla M_\vartheta^* \nabla M_\theta x^{(k)}) \qquad \text{for the dual update.} \tag{35}$$

By pulling the difference between ∇M_ϑ^* and $(\nabla M_\theta)^{-1}$ into the dual term, we empirically observe a much lower forward-backward error, which would correspond to smaller constants and tighter convergence bounds for our presented theorems. We formalize the proposed learned AMD (LAMD) with $R(x, x') = \frac{1}{2}\|x - x'\|^2$, learned SMD (LSMD), and learned ASMD (LASMD) algorithms with this dual update modification in the following Algorithms 4 to 6.

Since the original pre-trained models only have step-sizes available up to $N = 10$, we need to choose step-sizes to continue optimizing. We consider running LAMD, LSMD and LASMD for 2000 iterations with various choices of step-size. In particular, we consider three constant step-sizes $t_k = \tilde{c}$, as well as step-size regimes of the form and $t_k = c/k$ and $t_k = c'/\sqrt{k}$ for LAMD and LSMD. These step-sizes were derived from step-sizes given from the pre-trained models, given for the image denoising, image inpainting and SVM experiments in Tan et al. (2023b;a). In particular, for the constant step-size extensions, we consider taking $\tilde{c}$ to be the mean, minimum and final learned step-size, i.e. $c = \sum_{i=1}^{10} t_i/10$, $c = \min_{1 \leq i \leq 10} t_i$, $c = t_{10}$ respectively. For the reciprocal step-size extensions $t_k = c/k$, we compute c by taking the average $c = \sum_{i=1}^{10} it_i$. For root-reciprocal extensions $t_k = c'/k$, we similarly take $c' = \sum_{i=1}^{10} i\sqrt{t_i}$. These extensions act as best-fit constants for the given learned step-sizes.

Recall that the conditions of convergence for AMD and SMD desire a non-increasing step-size condition. Moreover, convergence of the ergodic average for SMD requires a ℓ_2–ℓ_1 summability condition, which is satisfied by the $t_k = c/k$ extension. We will demonstrate the behavior of these algorithms under both constant, reciprocal and root-reciprocal step-size regimes.

We note that while ASMD does not have a step-size in its definition, we can artificially introduce a step-size by adding a step-size in the dual update step in Step 4 of Algorithm 3, as

$$y^{(k+1)} = y^{(k)} - t_k \frac{A_{k+1} - A_k}{s_k} \mathsf{G}(x^{(k+1)}, \xi^{(k+1)}).$$

In the case where $t_k = t$ is constant, this can be interpreted as instead running ASMD without this step-size modification on the scaled function tf. Therefore, we still get convergence guarantees, up to a constant multiple factor.

Algorithm 4 Learned AMD (LAMD)

Require: Input $\tilde{x}^{(0)} = \tilde{z}^{(0)} = x^{(0)} \in \mathcal{X}$, parameter $r \geq 3$, step-sizes t_k, number of iterations K
1: $z^{(0)} = \nabla M_\theta(\tilde{z}^{(0)})$
2: **for** $k = 0, ..., K$ **do**
3:      $x^{(k+1)} = \lambda_k \nabla M_\vartheta^*(z^{(k)}) + (1 - \lambda_k)\tilde{x}^{(k)}$ with $\lambda_k = \frac{r}{r+k}$
4:      $z^{(k+1)} = z^{(k)} - \frac{kt_k}{r}\nabla f(x^{(k+1)})$
5:      $\tilde{x}^{(k+1)} = x^{(k+1)} - \gamma t_k \nabla f(x^{(k+1)})$
6: **end for**
7: **return** $x^{(K+1)} = \lambda_K \nabla M_\vartheta^*(z^{(K)}) + (1 - \lambda_K)\tilde{x}^{(K)}$

Algorithm 5 Learned SMD (LSMD)

Require: Input $x^{(0)} \in \mathcal{X}$, step-sizes t_k, number of iterations K, stochastic gradient oracle G
1: $y^{(0)} = \nabla M_\theta(x^{(0)})$
2: **for** $k = 0, ..., K$ **do**
3:      $y^{(k+1)} = y^{(k)} - t_k \mathsf{G}(\nabla M_\vartheta^*(y^{(k)}), \xi^{(k)})$
4: **end for**
5: **return** $x^{(K+1)} = \nabla M_\vartheta^*(y^{(K+1)})$

Algorithm 6 Learned ASMD (LASMD)

Require: Input $x^{(0)} \in \mathcal{X}$, $A_0 = s_0 = 1/2$, step-sizes t_k, number of iterations K
1: $y^{(0)} = \nabla M_\theta(x^{(0)})$
2: **for** $k = 0, ..., K$ **do**
3:      $A_{k+1} = (k+1)(k+2)/2$, $\tau_k = (A_{k+1} - A_k)/A_k$, $s_k = (k+1)^{3/2}$
4:      $x^{(k+1)} = \frac{\tau_k}{\tau_k+1}\nabla M_\vartheta^*(y^{(k)}) + \frac{1}{\tau_k+1}x^{(k)}$
5:      $y^{(k+1)} = y^{(k)} - t_k \frac{A_{k+1}-A_k}{s_k}\mathsf{G}(x^{(k+1)}, \xi^{(k+1)})$
6: **end for**
7: **return** $x^{(K+1)} = \frac{\tau_K}{\tau_K+1}\nabla M_\vartheta^*(y^{(K)}) + \frac{1}{\tau_K+1}x^{(K)}$

(a) Clean phantom

(b) Noisy phantom

(c) True TV reconstruction

Figure 1: Example of the ellipse phantom data, as well as the reconstruction gained by using gradient descent on the TV function.

5.2 Image Denoising

We consider image denoising on an ellipse data set, with images of size 128×128, where we apply LAMD, LSMD and LASMD with pre-trained mirror maps given in Tan et al. (2023a). The mirror maps $M_\theta : \mathcal{X} \to \mathcal{X}^*, M_\vartheta^* : \mathcal{X}^* \to \mathcal{X}$ are modelled using input-convex neural networks (ICNNs) (Amos et al., 2017), and are trained to minimize the function values while also minimizing the *forward-backward inconsistency*, which is defined to be $(M_\vartheta^* \circ M_\theta - I)(x^{(k)})$. The training data used for the pre-trained mirror map are noisy ellipse phantoms in X-ray CT, generated using the Deep Inversion Validation Library (DIVal) (Wang & Zhou, 2006; Leuschner et al., 2019). The phantoms were generated in the same manner as in Tan et al. (2023a). The target functions to optimize were given by TV model-based denoising,

$$\mathcal{F} = \left\{ f(x) = \|x - y\|_2^2 + \lambda \|\nabla x\|_1 \right\},$$

where y are noisy phantoms, and ∇x is the pixel-wise discrete gradient, with the regularization parameter $\lambda = 0.15$.

Figure 1 presents some of the noisy ellipse data that we aim to reconstruct using a TV model. We observe that the noise artifacts are non-Gaussian and have some ray-like artifacts. We model the stochasticity by artificially adding Gaussian noise to the gradient $\mathsf{G}(x, \xi) - g(x) = \Delta(x, \xi) \sim \mathcal{N}(0, \sigma^2 I_{n \times n})$, with $\sigma = 0.05$.

Figure 2 demonstrates the effect of extending the learned step-sizes for LMD, LAMD, LSMD and LASMD, compared to the baseline optimization algorithms GD, Nesterov accelerated GD, and Adam. We observe that step-sizes following $t_k = c/k$ perform well for LAMD and LSMD, which is consistent with observations made in Tan et al. (2023a), Theorem 2. For LASMD, we observe that a constant step-size extension choice is optimal. We also observe the poor performance of Adam, for which various non-convergence results are known for convex setting (Reddi et al., 2018; Zou et al., 2019). We will use the aforementioned optimal step-size extensions as found in Figure 2 to extend step-sizes for the following experiments.

(a) LAMD

(b) LSMD

(c) LASMD.

Figure 2: Evolution of losses for the proposed LAMD, LSMD and LASMD methods with various step-size extensions, evaluated over 2000 iterations for TV model-based denoising of noisy ellipse phantoms. We observe that reciprocal step sizes generally work well for LAMD and LSMD, with larger step-sizes (given by the "mean" plot) resulting in non-convergence to minima. Constant step-sizes work better for LASMD, which can be attributed to the already decaying step-sizes in LASMD.

Figure 3: Comparison of LAMD, LSMD and LASMD against the classical GD, Nesterov accelerated GD, and Adam methods. We observe that the learned MD methods exhibit similar convergence behavior, which may be due to the relative strong convexity of the underlying optimization problem.

5.3 Image Inpainting

We additionally consider the image inpainting setting in Tan et al. (2023b). The images to reconstruct are STL-10 images, which are 96×96 color images. The images are corrupted with a fixed 20% missing pixel mask Z, then 5% Gaussian noise is added to all color channels to get the noisy image. The function class we optimize over is the class of TV-regularized variational forms, with regularization parameter $\lambda = 0.15$ as chosen in Tan et al. (2023b), given by

$$\mathcal{F} = \left\{ f(x) = \|Z \circ (x - y)\|_2^2 + \lambda \|\nabla x\|_1 \right\},$$

where y are images corrupted with mixing pixels. We use mirror maps that are pre-trained with the training regime given in Tan et al. (2023b), and measure their performance when applied with LAMD, LSMD and LASMD as compared to MD.

We first note that this setting does not admit a stochastic interpretation, and thus we set the artificial noise in LSMD and LASMD to zero. Notice that in this case, LSMD updates revert to mirror descent updates. The main difference between the LSMD that we will present here with the LMD used in Tan et al. (2023b) is that in this work's computations, the dual iterates are saved, as described at the start of Section 5.

In addition to the the three methods proposed in this work, we compare gradient descent, its accelerated version Nesterov accelerated gradient descent (Nesterov, 1983), and Adam (Kingma & Ba, 2015). These methods were used to optimize a function that arises from TV-based variational model for a single noisy masked image from the STL-10 test data set. The step-sizes were chosen by considering the best step-size extension out of those described at the start of Section 5, which were reciprocal step-size extensions for LAMD, LSMD and LMD, and constant step-size for LASMD given by the mean of the learned step-sizes. To compute the global minimum of the optimization problem, we run gradient descent for 15000 iterations with a step-size of 5×10^{-4}, followed by another 5000 iterations with a step-size of 1×10^{-4}. Nesterov accelerated GD was run with step-size 5×10^{-4} and momentum parameter $r = 3$. The Adam optimizer was run with learning rate 10^{-2} and default momentum parameters.

Figure 4 demonstrates approximately that LAMD and LASMD are able to achieve $\mathcal{O}(k^{-2})$ convergence. Moreover, we see the effect of storing the dual iterates instead of the primal iterates, as the LSMD con-

Reconstruction Loss

Figure 4: Plot of the function optimality gap $f(x^{(k)}) - f^*$ for 2000 iterations of various MD methods for image inpainting. The step-size regime is reciprocal for LAMD, LSMD and LMD, and constant for LASMD. We observe that each of LAMD, and LASMD both exhibit approximately $\mathcal{O}(k^{-2})$ convergnce. LMD and LSMD exhibit approximately $\mathcal{O}(k^{-1})$ convergence, with instability around iteration 100 for LMD causing the increase in function value. As we are not applying added stochastic noise in this setting, the only difference between LSMD and LMD is that the dual variables are stored as described in Section 5, which allows the LSMD iterates to stay bounded.

verges without the divergent behavior of LMD. Moreover, the convergence rate of LAMD is faster than is suggested by Theorem 1 for step-size $t_k = \Theta(k^{-1})$. This suggests that the approximation error term given in Equation (12),

$$\left\langle \tilde{z}^{(k+1)} - x^*, \nabla \psi(\tilde{z}^{(k+1)}) - \nabla \psi(\hat{z}^{(k+1)}) \right\rangle,$$

is decaying as well. This could be attributed to the iterate approaching the global minimum such that the first term $\tilde{z}^{(k+1)} - x^*$ is decaying. We additionally observe the speedup of LAMD compared to Nesterov accelerated GD in the earlier iterates, coming from the learned mirror maps.

5.4 SVM Training

To demonstrate an application of stochasticity, we consider training a support vector machine (SVM) over a dataset with many samples. Similarly to Tan et al. (2023b), the task is to classify the digits 4 and 9 from the MNIST data set. A 5-layer neural network was used to compute feature vectors $\phi_i \in \mathbb{R}^{50}$ from the MNIST images for classification. The SVM training problem in this case is to find weights $\mathbf{w} \in \mathbb{R}^{50}$ and a bias b such that for a given set of features and targets $(\phi_i, y_i)_{i \in \mathcal{I}} \in \mathbb{R}^{50} \times \{\pm 1\}$, the prediction $\text{sign}(\mathbf{w}^\top \phi_i + b)$ matches y_i for most samples. This can be reformulated into a variational problem as follows, where $C > 0$ is some positive constant,

$$\min_{\mathbf{w}, b} \frac{1}{2} \mathbf{w}^\top \mathbf{w} + \frac{C}{|\mathcal{I}|} \sum_{i \in \mathcal{I}} \max(0, 1 - y_i(\mathbf{w}^\top \phi_i + b)). \tag{36}$$

Using the pre-trained neural network, we train SVMs using the training fold of MNIST using the 4 and 9 classes, which consists of 11791 images. For testing the generalization accuracy of these methods, we use the 4 and 9 classes in the testing fold, which consists of 1991 images. For the stochastic methods, we consider

(a) SVM hinge loss

(b) Test prediction error

Figure 5: Plots of the SVM hinge loss and test accuracy for the various optimization methods tested. We observe that LSMD is able to outperform both GD, Nesterov accelerated GD and SGD in terms of hinge loss. Interestingly, the test error for LAMD is lower than that of LSMD despite having a higher hinge loss. This suggests that the optimization algorithm additionally plays a role in the performance of the optimized results.

using a batch-size of 500 random samples from the testing fold, and the same for stochastic gradient descent. To train the SVMs, full-batch gradient is used for LAMD, LMD, GD and Nesterov accelerated GD. Batched gradients with batch-size 500 were used for LSMD, LASMD and SGD. We consider the same number of optimization for both the full-batch methods and the stochastic variants. This is slightly different from typical learned schemes where if the data is batched, then more training iterations have to be taken to keep the number of "epochs" the same.

The optimization problem and initialization was taken to be the same as in Tan et al. (2023b), where 100 SVMs are initialized using $(\mathbf{w}, b) \sim \mathcal{N}(0, I_{50+1})$. Each SVM has its parameters optimized with respect to the hinge loss Equation (36) using the various optimization methods. As in the previous section, we consider running each of the methods with all the step-size choices, and present the best choice for comparison.

Figure 5 compares the losses on the entire training set, as well as the generalization error of the computed SVMs on the test set. The step-size regimes chosen are reciprocal for LAMD, LSMD and LMD, and constant for LASMD and LSGD. LSMD is able to outperform the compared methods despite only having access to stochastic gradients, and overall less information. LAMD is able to converge faster than other methods initially, but eventually has its function value settle at a constant above the minimum after around 100 iterations. We are able to clearly see the effect of having an inexact gradient in this case, as the loss stabilizes at a constant above the minimum. Another possible explanation for this gap is that the step-sizes chosen may be too large.

Looking at the generalization error plots for the various optimization algorithms, we see some interesting behavior when we compare with the hinge loss. In particular, if we consider LSMD and SGD, we observe that in later iterations, LSMD has a lower hinge loss but SGD has a lower test error. Considering LASMD and LAMD as well shows that the relationship between the hinge loss and test error are inconclusive, at least on these small scales. This mismatch suggests that the both the stochasticity and optimization algorithm are important in determining the generalization accuracy, which could be an interesting direction for future work.

6 Equivariant MD for NNs

In the previous sections, we demonstrated some applications of LMD for convex optimization. However, the mirror map models used still require hundreds of thousands of parameters. Compared to classical optimizers

such as SGD or Adam with less than 10 hyperparameters, this is a significant limitation in scaling LMD to complex problems such as training neural networks. In this section, we propose to remedy this by reducing the number of learnable parameters for LMD while retaining expressiveness. This is done by exploiting symmetries of the problems at hand, sometimes known as *equivariance* in the literature.

Equivariance is a group-theoretic concept, where a group action commutes with a function application. In practical terms, symmetries can be exploited to reduce problem complexity. For example, translations and rotations of medical histopathology or electron microscopy images can also be considered as images from the same distribution. Bekkers et al. (2018) exploit this to construct convolutional neural networks exploiting this symmetry to achieve improved performance on various medical imaging segmentation tasks.

In the context of L2O, we aim to exploit symmetries to construct simpler or faster optimizers. Equivariance for neural networks have recently been explored, from both an external viewpoint of optimization or training losses, as well as the internal viewpoint of learned filters. Lenc & Vedaldi (2015) consider using equivariance to interpret the filters learned in a convolutional neural network. Chen et al. (2021) consider using equivariance in the unsupervised learning setting, using known equivariance properties to construct virtual operators and drastically increase the reconstruction quality. A major field is the usage of equivariant neural networks that enforce some type of group symmetry by using specific network architectures and activations, used in inverse problems and graph learning problems (Celledoni et al., 2021; Cohen & Welling, 2016; Worrall et al., 2017). By strictly enforcing symmetry, the resulting networks are more measurement-consistent and have better reconstruction quality. We focus on the use of equivariance for dimensionality reduction, provably demonstrating "weight-tying" when using LMD for neural networks.

To simplify the process of training LMD for neural networks, we consider exploiting the architecture of a neural network. In particular, the weights of a neural network typically carry permutation symmetries, which are exploited in works such as the Neural Tangent Kernel or Neural Network Gaussian Processes (Jacot et al., 2018; Lee et al., 2018). For example, a neural network with a dense layer and layer-wise activations between two feature layers will be invariant to permutations of the weights and feature indices. Another example is convolutional networks, where permuting the kernels will result in a permuted feature layer. In this section, we aim to formalize equivariance in the context of neural networks, and eventually show that we can MD methods that are equivariant stay equivariant along their evolution. This means that we can replace parameterizations of MD with equivariant parameterizations, reducing the number of learnable parameters while retaining the expressivity.

Let us first formalize the notion of symmetry that we aim for equivariance with. Let G be a group of symmetries acting linearly on a real Hilbert parameter space $(\mathcal{Z}, \langle \cdot, \cdot \rangle)$. In other words, G acts on $\mathcal{Z}$ via the binary operator $\cdot : G \times \mathcal{Z} \to \mathcal{Z}$, and moreover, for any $z, z' \in \mathcal{Z}$, $\lambda \in \mathbb{R}$, we have

$$g \cdot (z + z') = g \cdot z + g \cdot z', \ g \cdot (\lambda z) = \lambda g \cdot z.$$

Assume further that G has an adjoint in the inner product, i.e. $\langle g \cdot z, z' \rangle = \langle z, g^{-1} \cdot z' \rangle$. One example is when $\mathcal{Z} = \mathbb{R}^n$ equipped with the standard inner product, and G is a subset of the orthogonal group $O(n)$ (the group of $n \times n$ orthonormal matrices) with the natural action (matrix multiplication).

Let $L : \mathcal{Z} \to \mathbb{R}$ be a loss function for our parameters. Suppose $x^{(0)}$ is initialized with some distribution $x^{(0)} \sim (\mathcal{Z}, p)$ that is stable under G, i.e., $p(x^{(0)}) = p(g \cdot x^{(0)}) \ \forall g \in G$, and further that L is stable under the permutations $L(g \cdot x) = L(x)$. For example, for a feature vector $x \in \mathbb{R}^n$, the loss function $L(x) = \|x\|_2$ and initialization distribution $\mathcal{N}(0, I_n)$ are invariant under the orthogonal group $G = O(n)$. The loss functions $L(x) = \|x\|_1, \|x\|_\infty$ and any component-wise i.i.d. distribution are invariant under the permutation group $G = \text{Sym}(n)$.

Recall that the objective of LMD is to minimize the loss after some number of optimization iterations (Tan et al., 2023b). To this end, let $\Omega : \mathcal{Z} \to \mathcal{Z}$ be an optimization iteration. For example, gradient descent on L can be written as $\Omega(z) = z - \eta \nabla L(z)$. The objective of LMD can be written, for example, as

$$\min_{\Omega} \mathbb{E}\left[\sum_{i=1}^{N} L(z_i) \right].$$

Suppose that we optimize Ω using some sort of gradient descent (in, say, the Sobolev space $H^1(\mathcal{Z})$ of L^2 functions with L^2 derivative), and further that Ω_0 satisfies

$$\Omega_0(g \cdot z) = g \cdot [\Omega_0(z)], \quad \forall g \in G, z \in \mathcal{Z}.$$

This reads that Ω_0 is G-invariant under conjugation, where the conjugation action of G on functions $F : \mathcal{Z} \to \mathcal{Z}$ is $(g \cdot F)(z) = g \cdot (F(g^{-1} \cdot z))$. We equivalently denote this as G-equivariance, as g commutes with Ω_0. For a sanity check, consider the case where Ω_0 is gradient descent with on the objective function L. The following proposition says that Ω_0 is indeed G-equivariant under these conditions.

Proposition 2. *If Ω_0 is gradient descent on the G-invariant objective function L, then it is G-equivariant, i.e. $\Omega_0(g \cdot z) = g \cdot [\Omega_0(z)]$ for all $g \in G, z \in \mathcal{Z}$.*

Proof. We first check that ∇L commutes with g actions. For any $y \in \mathcal{Z}$, the derivative operator $DL : \mathcal{Z} \to \mathcal{Z}^*$ satisfies

$$
\begin{aligned}
DL(g \cdot z)(y) &= \lim_{t \to 0} \frac{L(g \cdot z + ty) - L(g \cdot z)}{t} \\
&= \lim_{t \to 0} \frac{L(z - tg^{-1} \cdot y) - L(z)}{t} \\
&= DL(z)(g^{-1}y),
\end{aligned}
$$

where the second inequality holds since $L(g \cdot z) = L(z)$, applied with g^{-1} and linearity of g actions. Let ι denote the canonical isomorphism $\iota : \mathcal{Z}^* \to \mathcal{Z}$. For any $y \in \mathcal{Z}$,

$$
\begin{aligned}
\langle \iota^{-1} \nabla L(g \cdot z), y \rangle &= DL(g \cdot z)(y) \\
&= DL(z)(g^{-1} \cdot y) \\
&= \langle \iota^{-1} \nabla L(z), g^{-1} \cdot y \rangle \\
&= \langle g \cdot \iota^{-1} \nabla L(z), y \rangle.
\end{aligned}
$$

Hence, G commutes with $\iota^{-1} \nabla L = DL$. We now have that

$$
\begin{aligned}
\Omega_0(g \cdot z) &= g \cdot z - \eta (\nabla L)(g \cdot z) \\
&= g \cdot z - \eta g \cdot \nabla L(z) \\
&= g \cdot (z - \eta g \nabla L(z)) \\
&= g \cdot \Omega_0(z),
\end{aligned}
$$

where the first equality comes from the fact that g trivially commutes with ι (and thus ι^{-1}) using the induced group action, and the second and third equality comes from the linearity of g actions. Since this is true for all $y \in \mathcal{Z}$, by the Riesz representation theorem, we have $\nabla L(g \cdot z) = g \cdot \nabla L(z)$. $\qquad\square$

Suppose first that $N = 1$, so that we want to minimize (initialized at a G-invariant $\Omega = \Omega_0$)

$$\mathcal{L}(\Omega) := \mathbb{E}_{z_0 \sim p}\left[L(z_1)\right] = \mathbb{E}_{z_0 \sim p}\left[L(\Omega(z_0))\right]. \tag{37}$$

We wish to show that after optimization, Ω commutes with g (i.e. Ω stays invariant under the conjugation action of G on functions $\mathcal{Z} \to \mathcal{Z}$). To do this, we observe that the discrete differences as computed by autograd are invariant under the group action of g. Assume further $\Omega_0 \in L^2(\mathcal{Z}, \mathcal{Z}, p)$ where p is the initialization probability measure. The corresponding inner product is

$$\langle \Omega, \Xi \rangle_{L^2(\mathcal{Z}, \mathcal{Z}, p)} = \mathbb{E}_{z \sim p}[\langle \Omega(z), \Xi(z) \rangle_{\mathcal{Z}}].$$

G naturally acts on $L^2(\mathcal{Z}, \mathcal{Z}, p)$ by the conjugation action

$$(g \cdot \Omega)(z) = g \cdot [\Omega(g^{-1} \cdot z)].$$

To check that this conjugation is an action, first note that the action by g is isotropic since $G \leq O(n)$:

$$\int \|(g \cdot \Omega)(z)\|^2 dp(z) = \int \|(g \cdot \Omega)(z)\|^2 dp(z)$$

$$= \int \|g \cdot (\Omega(g^{-1}(z)))\|^2 dp(g \cdot z)$$

$$= \int \|\Omega(z)\|^2 dp(z).$$

Here, we used invariance of g under p, and also that $\|g \cdot y\|^2 = \langle g \cdot y, g \cdot y \rangle = \langle y, y \rangle = \|y\|^2$ from the adjoint. The required composition and identity properties of the action are clear. Moreover, the action is linear, and we have the adjoint property

$$\langle g \cdot \Omega, \Xi \rangle_{L^2(p)} = \int \langle g \cdot \Omega(g^{-1} \cdot z), \Xi(z) \rangle dp(z)$$

$$= \int \langle \Omega(g^{-1} \cdot z), g^{-1} \cdot \Xi(z) \rangle dp(z)$$

$$= \int \langle \Omega(z), g^{-1} \Xi(g \cdot z) \rangle dp(z)$$

$$= \langle \Omega, g^{-1} \cdot \Xi \rangle.$$

Assume that Ω_0 is G-equivariant. Then the next iterate satisfies the following

$$\Omega_1 = \Omega_0 - \eta \frac{d\mathcal{L}}{d\Omega}(\Omega_0). \tag{38}$$

But we also have for any g and Ω,

$$\mathcal{L}(\Omega) = \mathbb{E}_{z_0 \sim p}[L(\Omega(z_0))]$$

$$= \mathbb{E}_{z_0 \sim p}[L(g \cdot \Omega(z_0))] \qquad \text{since } L(z) = L(g \cdot z)$$

$$= \mathbb{E}_{z_0 \sim p}[L(g \cdot \Omega(g^{-1} \cdot z_0))] \quad \text{since } p(z) = p(g \cdot z)$$

$$= \mathbb{E}_{z_0 \sim p}[L((g \cdot \Omega)(z_0))]$$

$$= \mathcal{L}(g \cdot \Omega).$$

Hence if $\Omega_0 = g \cdot \Omega_0$ for all g, then

$$\frac{d}{d\Omega}\mathcal{L}(\Omega_0) = \frac{d}{d(g \cdot \Omega)}\mathcal{L}(\Omega_0) \tag{39}$$

Since the variation of the Ω and $g \cdot \Omega$ is the same at Ω_0, we have that $g \cdot \Omega_1 = \Omega_1$, i.e. Ω_1 is G-equivariant. This argument can be repeated to get that Ω_n is G-equivariant (under conjugation) for all $n \in \mathbb{N}$. This is summarized in the following proposition.

Proposition 3. *Let $(\mathcal{Z}, \langle \cdot, \cdot \rangle)$ be a Hilbert parameter space. Suppose the following hold:*

1. *G a group acting linearly on $\mathcal{Z}$ with an adjoint;*

2. *The loss function $L : \mathcal{Z} \to \mathbb{R}$ and are stable under G, that is, $L(g \cdot z) = L(z)$ for any $g \in G$ and $z \in \mathcal{Z}$;*

3. *The initialization distribution $z^{(0)} \sim (\mathcal{Z}, p)$ is stable under G, that is, the laws $p(z^{(0)})$ and $p(g \cdot z^{(0)})$ coincide for any $g \in G$.*

Let $\Omega_0 : \mathcal{Z} \to \mathcal{Z}$ be an optimization iteration that is G-equivariant, such that $\Omega_0(g \cdot z) = g \cdot \Omega_0(z)$ for all $z \in \mathcal{Z}, g \in G$. If Ω_0 is evolved using a gradient step (with step-size η) to minimize

$$\mathcal{L}(\Omega) = \mathbb{E}_{z_0 \sim p}[L(z_1)],$$

then the evolved optimizer $\Omega_1 = \Omega_0 - \eta d\mathcal{L}/d\Omega(\Omega_0)$ is also G-equivariant.

6.1 Application: Deep Neural Networks

For the sake of exposition with a concrete example, let us consider a two-hidden-layer dense neural network of the form

$$N(x; A_i, b_i) = A_3 \sigma_2 (A_2 \sigma_1 (A_1 x + b_1) + b_2) + b_3,$$

where $x \in \mathbb{R}^{d_0}$, σ_i are coordinate-wise or otherwise permutation-invariant activation functions such as softmax, and $A_i \in \mathbb{R}^{d_i \times d_{i-1}}$, $b_i \in \mathbb{R}^{d_i}$ are the weights and biases. In this case, the parameter space will be

$$\mathcal{Z} = \mathbb{R}^d, \, d = \sum_{i=1}^{3} (d_{i-1} d_i + d_i) .$$

Let us consider a least-squares regression problem with data (x_j, y_j), $j = 1, ..., k$, which can be written as minimizing the loss

$$L(z) = \sum_{j=1}^{k} [N(x_j; z) - y_j]^2 .$$

Suppose that the weights are initialized entry-wise i.i.d. for each A_i, b_i, such as in common initializations where $A_i \sim \mathcal{N}(0, \eta_i^2 I_{d_{i-1} d_i \times d_{i-1} d_i})$ or $A_i \sim \text{Uniform}(-d_{i-1}^{-1/2}, d_{i-1}^{-1/2})$. Consider the symmetry group $G \simeq \text{Sym}(d_1) \times \text{Sym}(d_2)$, consisting of permutations of the intermediate feature maps with appropriate permutations on the weights and biases, i.e. of permutations ρ_1, ρ_2 on $[d_1], [d_2]$ respectively with the group action as

$$g_{\rho_1, \rho_2}(z)[A_1]_{p,q} = (A_1)_{p, \rho_1(q)},$$
$$g_{\rho_1, \rho_2}(z)[A_2]_{p,q} = (A_2)_{\rho_1(p), \rho_2(q)},$$
$$g_{\rho_1, \rho_2}(z)[A_3]_{p,q} = (A_3)_{\rho_2(p), q}$$
$$g_{\rho_1, \rho_2}(z)[b_1]_q = (b_1)_{\rho_1(q)},$$
$$g_{\rho_1, \rho_2}(z)[b_2]_q = (b_2)_{\rho_2(q)},$$
$$g_{\rho_1, \rho_2}(z)[b_3]_q = (b_3)_q.$$

We can check directly that this group action satisfies the requirements of Proposition 3:

- (*Linearity*) Permutation of elements is linear.

- (*Initialization Invariance*) Follows from i.i.d. property of entries of A_i, b_i.

- (*Loss Equivariance*) Follows from σ_i acting coordinatewise and invariance of sums under permutation.

Consider the simple approach of scaling each component of the gradient by a learned constant, i.e. MD with a mirror map of the form $\psi = x^\top D x$ for some learned positive definite diagonal D. Notice that starting with $D = I$ yields gradient descent, which is equivariant under G. Using Proposition 3, we find that D will continue to be G-equivariant. In other words, each of the components of D must be fixed under permutation actions of the form $(\rho_1, \rho_2) \in G$.

We can explicitly demonstrate this experimentally on a small-scale neural network. In particular, we consider training a classifier using a three-layer neural network with fully connected layers on the 2D moons data set. We arbitrarily choose 50 dimensions for the middle feature layer. The neural network takes the form

$$N(x; A_i, b_i) = \sigma_2 (A_2 \sigma_1 (A_1 x + b_1) + b_2),$$

where $A_i \in \mathbb{R}^{d_i \times d_{i-1}}$, $b_i \in \mathbb{R}^{d_i}$, $d_0 = 2, d_1 = 50, d_2 = 1$. In this case, we choose σ_1 to be a ReLU activation and σ_2 to be a log-softmax. We train using the binary cross-entropy loss. Note that in the case of a log-softmax, which takes the form

$$\text{LogSoftmax(x)}_i = \log \left(\frac{\exp(x_i)}{\sum_j \exp(x_j)} \right),$$

Figure 6: Componentwise gradient weightings learned for a two layer neural network on 2D moons data. Each band consists of 50 datapoints, corresponding to elements of the weight matrix D for each neural network parameter group. We observe strong grouping of the weightings within each parameter group. In particular, we find that the weightings of A_1 are split into two groups, which correspond to the two input dimensions.

the activation is still equivariant under permutations in G, as the sum of the exponentials stays the same. Therefore, loss equivariance holds and the above theory given by Proposition 3 applies.

Using the diagonal quadratic LMD introduced above, we thus expect from the equivariance theory that the diagonal weights in D will be invariant under the effect of any permutations (ρ_1) on $[d_1]$. Using superscripts to denote the weights corresponding to each learnable neural network component, we thus have that for any indices $i \in [d_1] = [2], j, j' \in [d_2] = [50], k \in [d_3] = [1]$:

$$(D^{A_1})_{i,j} = (D^{A_1})_{i,j'}$$
$$(D^{b_1})_j = (D^{b_1})_{j'}$$
$$(D^{A_2})_{j,k} = (D^{A_2})_{j',k}.$$

Therefore, from G-equivariance of LMD with diagonal weighting D, we have that the weights are constant across the orbits of ρ_1, and are thus fully determined by the weights $(D^{A_1})_{1,1}, (D^{A_1})_{2,1}, (D^{b_1})_1, (D^{A_2})_{1,1}, (D^{b_2})_1$. This reduces the number of variables that need to be learned from $\dim(D) = 201$ to only 5. The equivariance effect can be clearly seen in Figure 6, which empirically demonstrates what happens if we train all the variables of D without directly enforcing equivariance. By initializing D to be the identity, the initial mapping $\Omega_0 : \mathcal{Z} \to \mathcal{Z}$ induced by D is gradient descent, which we have shown before to be equivariant under permutations of the intermediate feature layer. The theory presented thus suggests that the optimization path of Ω (or in this case, of D), will continue to be equivariant under such permutations. Indeed, at the end of the optimization for D, we observe that the weights do indeed satisfy approximate equivariance, as demonstrated by the tight grouping phenomenon of the weights. We observe that the weights D^{A_1} become two groups, and D^{b_1}, D^{A_2} becoming one group each, which supports the theory that if the initial map Ω_0 is equivariant, then so are subsequent maps after training.

We note that this analysis can be used to partially explain the existing heuristic method of applying mirror maps to neural networks layer-wise, such as using p-norms (D'Orazio et al., 2021; Gunasekar et al., 2018), or projections such as the hyperbolic tangent or softmax function (Ajanthan et al., 2021). In these cases, the learned components are applied componentwise to dense neural networks, which satisfy the required assumptions above.

7 Experiments: Neural Network Training using Equivariance

We consider the problem of training LMD on neural networks, based on the group equivariance demonstrated in Section 6. This is a challenging non-convex optimization task, where the approximate theory for LMD (and its extensions) does not apply, due to significant errors that may occur from small perturbations in the parameters. This motivates us to consider simpler yet exact mirror maps to learn, which can be done layer-wise by the analysis in Section 6. We demonstrate competitive performance with Adam, one of the most widely used optimizers for neural network training (Kingma & Ba, 2015).

7.1 Deep Fully Connected Neural Network

We first consider training a classifier neural network on the MNIST image dataset. Neural networks are usually trained using minibatched gradients, as computing gradients over the whole dataset is infeasible. This is a prime use case for the stochastic variants of LMD. The neural network to train as well as the LSMD parameterization are detailed as follows.

Algorithm 7 Learned AMD with minibatched gradients (LAMD*)

Require: Input $\tilde{x}^{(0)} = \tilde{z}^{(0)} = x^{(0)} \in \mathcal{X}$, parameter $r \geq 3$, step-sizes t_k, number of iterations K

1: $z^{(0)} = \nabla M_\theta(\tilde{z}^{(0)})$
2: **for** $k = 0, ..., K$ **do**
3: $\quad x^{(k+1)} = \lambda_k \nabla M_\vartheta^*(z^{(k)}) + (1 - \lambda_k)\tilde{x}^{(k)}$ with $\lambda_k = \frac{r}{r+k}$
4: $\quad z^{(k+1)} = z^{(k)} - \frac{kt_k}{r}\nabla f_k(x^{(k+1)})$
5: $\quad \tilde{x}^{(k+1)} = x^{(k+1)} - \gamma t_k \nabla f_k(x^{(k+1)})$
6: **end for**
7: **return** $x^{(K+1)} = \lambda_K \nabla M_\vartheta^*(z^{(K)}) + (1 - \lambda_K)\tilde{x}^{(K)}$

Neural network architecture. The number of features in each layer of the neural network is 784–50–40–30–20–10, with dense linear layers with bias between the layers and ReLU activations, for a total of 43350 parameters. The MNIST images are first flattened (giving $28 \times 28 = 784$ features), before being fed into the network. The function objective corresponding to a neural network is the cross-entropy loss for classification over the MNIST dataset. For LSMD, we associate each layer with two splines – one for the weight matrix and one for the bias vector. This results in a total of 10 learned splines, a total of 410 learnable parameters for LSMD.

LMD parameterization. Utilizing the reduced parameterization as suggested by Section 6, we can consider only layer-wise mirror maps Ψ. This allows us to use more complicated mirror maps from $\mathbb{R} \to \mathbb{R}$. One parameterization is to use *monotonic splines* as mirror maps, as induced by convex mirror potentials (given by the integrals of the monotonic splines). We use a similar knot-based spline parameterization as Goujon et al. (2022), where knots are defined at pre-determined locations, and the spline is (uniquely) determined by the change of slope at each knot. We note that since the monotonic spline $\sigma : \mathbb{R} \to \mathbb{R}$ is continuous, the corresponding mirror potential given by the integral $\psi(x) = \int_0^x \sigma(t)\,\mathrm{d}t$ is $\mathcal{C}^1$. For these experiments, we use 41 knots equispaced on the interval $[-1, 1]$, with gap 0.05. Each spline can thus be parameterized using 41 parameters.

The goal of LSMD is to train neural networks with architecture faster, given MNIST data. The function class that we wish to optimize over is thus

$$\mathcal{F} = \left\{ \sum_{k=1}^{N} \mathcal{L}(\mathcal{N}_k) \,\middle|\, \text{neural networks } \mathcal{N}_0 \right\}, \tag{40}$$

where $\mathcal{L}$ is the cross-entropy of a neural network (on an image mini-batch), and $\mathcal{N}_k$ is the neural network after evolving the parameters through LSMD for k iterations. Note that the number of iterations that we can unroll is significantly higher than in the image processing examples, due to the dimensionality reduction from the equivariant theory. The minibatching process means that we are training using SMD instead of

(a) Train accuracy

(b) Cross-entropy loss

Figure 7: Spline-based LMD applied to training a 4-hidden-layer dense neural network for MNIST classification. We observe a significant acceleration of LAMD as compared to LMD. There is a slight performance gap between LAMD and Adam on this task.

the MD framework, similarly to how SGD is used instead of GD to train neural networks on large datasets. We are allowed to use three epochs of MNIST to train, which we find to be sufficient for these experiments. The MNIST batch-size is taken to be 500, resulting in unrolling $N = 360$ steps. The neural networks $\mathcal{N}_0$ are initialized using the default PyTorch initialization, where a dense layer from C_{in}–C_{out} features has the entries of its weight matrix A and bias matrix b initialized from $\text{Uniform}(-C_{\text{in}}^{-1}, C_{\text{in}}^{-1})$. We use 20 such neural network initializations as a batch for each LMD training iteration, and average the cross-entropy over each neural network as our loss function.

Figure 7 shows the performance of LSMD on this task, as well as minibatched LAMD* Algorithm 7 applied with the spline-based mirror maps learned using the LSMD framework. LMD and LAMD* are compared against: SGD with learning rate 1×10^{-1}, and Adam with learning rate 1×10^{-2}, where other parameters are kept as default. The values are averaged over 20 neural network initializations. We observe that Adam with this learning rate is able to train this network architecture very rapidly. LAMD* is able to almost match the performance of Adam at the end of the 3 training epochs, while both LAMD* and LMD significantly outperform SGD.

7.2 Convolutional Neural Network

We additionally consider LMD to train a 2-layer convolutional neural network. We impose a diagonal quadratic LMD prior on the weights, similarly to Section 6.1. The CNN is taken to have a single convolutional layer with 8 channels and kernel size 3, a max pooling layer with window size 2, followed by a dense layer from 288 features to 10 output features. The inputs of the CNN are MNIST images that have been downscaled to have dimension 14×14. The target is to minimize the cross-entropy loss of the CNN after 2 epochs of MNIST, with mini-batch size 1000, resulting in a total unrolling count of $N = 120$.

The equivariance here is due to the permutation invariance of each of the eight 3×3 kernels. Therefore, we can reduce the number of parameters of LMD by tying the diagonal weights across the channels, reducing the number of parameters for this layer from $8 \times (9 + 1) = 72$ to only 10, with 9 from the sliding window weights and 1 from the bias term. While not strictly induced by the training problem[1], we additionally impose equivariance on the dense layer by tying the 288 features together, reducing the number of parameters from $288 \times 10 + 10$ to $1 \times 10 + 10$. In total, we learn 30 parameters.

Figure 8 shows the performance of LMD and LAMD* when averaged over training 20 randomly initialized CNN problems, trained for 2 epochs of MNIST. We observe competitive performance with Adam for both LAMD* and LMD. Interestingly, we observe that the testing accuracy of the training result of LAMD* is marginally higher than that of Adam. This distinctly highlights the potential of learning the geometry for

---

[1]Since the layer before the dense layer is a convolutional layer (followed by max-pooling), the features in this intermediate layer still contain local information. Therefore, we do not have permutation invariance of the features.

(a) Test accuracy   (b) Cross-entropy loss

Figure 8: Diagonal LMD and LAMD applied to training one-hidden-layer convolutional neural networks with 2 epochs of MNIST, averaged over 20 runs. We observe that LAMD can achieve higher test accuracy and lower training loss by the end of the 2 training epochs. Both LMD and LAMD are competitive with Adam in this example.

gradient-based methods, as we achieve significant acceleration with only 30 parameters to the point of being competitive with Adam, while retaining a principled approach to learning the model.

We note that the size of the CNN is limited due to the memory constraints of LMD. To train one iteration of LMD, all the intermediate activations of the neural network need to be stored. In the case of a convolutional layer, the intermediate layer is also image-like, which results in very high memory usage.

8 Conclusions

In this work, we present multiple extensions of the learned mirror descent method introduced in a recent work on learning to optimize (Tan et al., 2023b;a). In particular, we introduce accelerated and stochastic versions, as well as a new training paradigm that reduces the number of learnable parameters while maintaining the *expressivity* of the mirror maps by exploiting symmetries. Numerical experiments demonstrate that the learned accelerated and stochastic MD methods are able to outperform their corresponding GD counterparts as well as previous LMD with the same mirror maps, and we empirically improve on the constant optimization gap by utilizing the dual domain during mirror steps. These experiments additionally demonstrate that mirror maps trained using LMD as in (Tan et al., 2023b;a) are able to successfully generalize to different LMD-type optimization schemes. We empirically show that mirror maps respect group invariances under training to support our equivariant theory, and exploit this to train LMD on the non-convex problems of training deep and convolutional neural networks.

This work presented results as well as techniques for developing L2O schemes for large-scale applications. Given the various modifications to LMD presented, the mirror maps were pretrained using a basic scheme that penalizes the objective function as well as the forward-backward inconsistency for a fixed number of unrolled iterates (Tan et al., 2023b). One consideration is the modification of the training scheme to instead use the accelerated or stochastic mirror descent rather than full-batch mirror descent, which could help in large-scale applications. Another possible direction would be to consider convergence properties of the approximate MD methods for non-convex functions, similarly to the non-mirrored cases presented in Berahas et al. (2017); Jin et al. (2017).

This work additionally presented an application of equivariance for dimensionality reduction of LMD, reducing the total number of parameters required to train. We demonstrated that the reduced parameterization arises naturally from common training scenarios, and that the resulting LMD is able to perform competitively with Adam. While we limit our equivariance to simple gradient-based methods, interesting future directions could consider equivariance under the scope of other optimization algorithms utilizing techniques such as scaling, momentum, or using proximal operators. Another direction to continue pushing LMD is to address the current limitations caused by needing to store intermediate activations, allowing for this method to be used for larger and more practical neural networks.

References

Thalaiyasingam Ajanthan, Kartik Gupta, Philip Torr, Richad Hartley, and Puneet Dokania. Mirror descent view for neural network quantization. In *International conference on artificial intelligence and statistics*, pp. 2809–2817. PMLR, 2021.

Zeyuan Allen-Zhu. Katyusha: The first direct acceleration of stochastic gradient methods. *The Journal of Machine Learning Research*, 18(1):8194–8244, 2017.

Zeyuan Allen-Zhu and Lorenzo Orecchia. Linear coupling: An ultimate unification of gradient and mirror descent. *arXiv preprint arXiv:1407.1537*, 2014.

Diogo Almeida, Clemens Winter, Jie Tang, and Wojciech Zaremba. A generalizable approach to learning optimizers. *arXiv preprint arXiv:2106.00958*, 2021.

Brandon Amos, Lei Xu, and J. Zico Kolter. Input convex neural networks. In *International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 146–155. PMLR, 2017.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in neural information processing systems*, pp. 3981–3989, 2016.

Yossi Arjevani, Yair Carmon, John C Duchi, Dylan J Foster, Nathan Srebro, and Blake Woodworth. Lower bounds for non-convex stochastic optimization. *Mathematical Programming*, 199(1-2):165–214, 2023.

Dominique Azé and Jean-Paul Penot. Uniformly convex and uniformly smooth convex functions. In *Annales de la Faculté des sciences de Toulouse: Mathématiques*, volume 4, pp. 705–730, 1995.

Sebastian Banert, Axel Ringh, Jonas Adler, Johan Karlsson, and Ozan Oktem. Data-driven nonsmooth optimization. *SIAM Journal on Optimization*, 30(1):102–131, 2020.

Sebastian Banert, Jevgenija Rudzusika, Ozan Öktem, and Jonas Adler. Accelerated forward-backward optimization using deep learning. *arXiv preprint arXiv:2105.05210*, 2021.

A. Beck and M. Teboulle. Fast gradient-based algorithms for constrained total variation image denoising and deblurring problems. *IEEE Transactions on Image Processing*, 18(11):2419–2434, 2009.

Amir Beck and Marc Teboulle. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.

Erik J Bekkers, Maxime W Lafarge, Mitko Veta, Koen AJ Eppenhof, Josien PW Pluim, and Remco Duits. Roto-translation covariant convolutional networks for medical image analysis. In *Medical Image Computing and Computer Assisted Intervention–MICCAI 2018: 21st International Conference, Granada, Spain, September 16-20, 2018, Proceedings, Part I*, pp. 440–448. Springer, 2018.

Aharon Ben-Tal, Tamar Margalit, and Arkadi Nemirovski. The ordered subsets mirror descent optimization method with applications to tomography. *SIAM Journal on Optimization*, 12(1):79–108, 2001.

Albert S Berahas, Raghu Bollapragada, and Jorge Nocedal. An investigation of newton-sketch and subsampled newton methods. *arXiv preprint arXiv:1705.06211*, 2017.

Sébastien Bubeck. Convex optimization: Algorithms and complexity. *Foundations and Trends® in Machine Learning*, 8(3-4):231–357, 2015.

Elena Celledoni, Matthias J Ehrhardt, Christian Etmann, Brynjulf Owren, Carola-Bibiane Schönlieb, and Ferdia Sherry. Equivariant neural networks for inverse problems. *Inverse Problems*, 37(8):085006, 2021.

Antonin Chambolle, Matthias J Ehrhardt, Peter Richtarik, and Carola-Bibiane Schonlieb. Stochastic primal-dual hybrid gradient algorithm with arbitrary sampling and imaging applications. *SIAM Journal on Optimization*, 28(4):2783–2808, 2018.

Dongdong Chen, Julián Tachella, and Mike E Davies. Equivariant imaging: Learning beyond the range space. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4379–4388, 2021.

Tianlong Chen, Xiaohan Chen, Wuyang Chen, Zhangyang Wang, Howard Heaton, Jialin Liu, and Wotao Yin. Learning to optimize: A primer and a benchmark. *The Journal of Machine Learning Research*, 23 (1):8562–8620, 2022.

Edward Chlebus. An approximate formula for a partial sum of the divergent p-series. *Applied Mathematics Letters*, 22(5):732–737, 2009.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999. PMLR, 2016.

Aaron Defazio. A simple practical accelerated method for finite sums. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 676–684. Curran Associates, Inc., 2016.

Ryan D'Orazio, Nicolas Loizou, Issam Laradji, and Ioannis Mitliagkas. Stochastic mirror descent: Convergence analysis and adaptive variants via the mirror stochastic polyak stepsize. *arXiv preprint arXiv:2110.15412*, 2021.

Derek Driggs, Junqi Tang, Jingwei Liang, Mike Davies, and Carola-Bibiane Schönlieb. A stochastic proximal alternating minimization for nonsmooth and nonconvex optimization. *SIAM Journal on Imaging Sciences*, 14(4):1932–1970, 2021.

John C Duchi, Shai Shalev-Shwartz, Yoram Singer, and Ambuj Tewari. Composite objective mirror descent. In *COLT*, volume 10, pp. 14–26. Citeseer, 2010.

John C Duchi, Alekh Agarwal, Mikael Johansson, and Michael I Jordan. Ergodic mirror descent. *SIAM Journal on Optimization*, 22(4):1549–1578, 2012.

Alina Ene and Huy L Nguyen. High probability convergence for accelerated stochastic mirror descent. *arXiv preprint arXiv:2210.00679*, 2022.

Saeed Ghadimi and Guanghui Lan. Accelerated gradient methods for nonconvex nonlinear and stochastic programming. *Mathematical Programming*, 156(1-2):59–99, 2016.

Alexis Goujon, Sebastian Neumayer, Pakshal Bohra, Stanislas Ducotterd, and Michael Unser. A neural-network-based convex regularizer for image reconstruction. *arXiv preprint arXiv:2211.12461*, 2022.

Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proceedings of the 27th international conference on international conference on machine learning*, pp. 399–406, 2010.

Suriya Gunasekar, Jason Lee, Daniel Soudry, and Nathan Srebro. Characterizing implicit bias in terms of optimization geometry. In *International Conference on Machine Learning*, pp. 1832–1841. PMLR, 2018.

Suriya Gunasekar, Blake Woodworth, and Nathan Srebro. Mirrorless mirror descent: A natural derivation of mirror descent. In *International Conference on Artificial Intelligence and Statistics*, pp. 2305–2313. PMLR, 2021.

Vahan Hovhannisyan, Panos Parpas, and Stefanos Zafeiriou. MAGMA: Multilevel accelerated gradient mirror descent algorithm for large-scale convex composite minimization. *SIAM Journal on Imaging Sciences*, 9 (4):1829–1857, 2016.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in Neural Information Processing Systems*, 31, 2018.

Kyong Hwan Jin, Michael T McCann, Emmanuel Froustey, and Michael Unser. Deep convolutional neural network for inverse problems in imaging. *IEEE Transactions on Image Processing*, 26(9):4509–4522, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 2015.

Walid Krichene, Alexandre Bayen, and Peter L Bartlett. Accelerated mirror descent in continuous and discrete time. *Advances in Neural Information Processing Systems*, 28, 2015.

Guanghui Lan. An optimal method for stochastic composite optimization. *Mathematical Programming*, 133 (1-2):365–397, 2012.

Guanghui Lan. *First-order and stochastic optimization methods for machine learning*, volume 1. Springer, 2020.

Guanghui Lan and Yi Zhou. An optimal randomized incremental gradient method. *arXiv preprint arXiv:1507.02000*, 2015.

Guanghui Lan, Arkadi Nemirovski, and Alexander Shapiro. Validation analysis of mirror descent stochastic approximation method. *Mathematical programming*, 134(2):425–458, 2012.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as Gaussian processes. In *International Conference on Learning Representations*, 2018.

Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 991–999, 2015.

Johannes Leuschner, Maximilian Schmidt, and David Erzmann. Deep inversion validation library. *Software available from https://github.com/jleuschn/dival*, 2019.

Ke Li and Jitendra Malik. Learning to optimize. In *International Conference on Learning Representations*, 2016.

Yanjun Li, Kai Zhang, Jun Wang, and Sanjiv Kumar. Learning adaptive random features. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4229–4236, 2019.

Luke Metz, Niru Maheswaranathan, Jeremy Nixon, Daniel Freeman, and Jascha Sohl-Dickstein. Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*, pp. 4556–4565. PMLR, 2019.

Arkadi Nemirovski and David Berkovich Yudin. *Problem Complexity and Method Efficiency in Optimization / translated by E.R. Dawson.* Wiley-Interscience series in discrete mathematics. Wiley, Chichester, 1983. ISBN 0471103454.

Arkadi Nemirovski, Anatoli Juditsky, Guanghui Lan, and Alexander Shapiro. Robust stochastic approximation approach to stochastic programming. *SIAM Journal on Optimization*, 19(4):1574–1609, 2009.

Yurii Evgen'evich Nesterov. A method of solving a convex programming problem with convergence rate $O(1/k^2)$. In *Doklady Akademii Nauk*, volume 269, pp. 543–547. Russian Academy of Sciences, 1983.

Francesco Orabona, Koby Crammer, and Nicolo Cesa-Bianchi. A generalized online mirror descent with applications to classification and regression. *Machine Learning*, 99:411–435, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Garvesh Raskutti and Sayan Mukherjee. The information geometry of mirror descent. *IEEE Transactions on Information Theory*, 61(3):1451–1457, 2015.

Sashank J Reddi, Satyen Kale, and Sanjiv Kumar. On the convergence of adam and beyond. In *International Conference on Learning Representations*, 2018.

Herbert Robbins and Sutton Monro. A stochastic approximation method. *The Annals of Mathematical Statistics*, 22(3):400–407, 1951.

Leonid I Rudin, Stanley Osher, and Emad Fatemi. Nonlinear total variation based noise removal algorithms. *Physica D: nonlinear phenomena*, 60(1-4):259–268, 1992.

Nati Srebro, Karthik Sridharan, and Ambuj Tewari. On the universality of online mirror descent. *Advances in Neural Information Processing Systems*, 24, 2011.

Volker Strassen. The existence of probability measures with given marginals. *The Annals of Mathematical Statistics*, 36(2):423–439, 1965.

Weijie Su, Stephen Boyd, and Emmanuel Candes. A differential equation for modeling Nesterov's accelerated gradient method: theory and insights. *Advances in neural information processing systems*, 27, 2014.

Hong Ye Tan, Subhadip Mukherjee, Junqi Tang, Andreas Hauptmann, and Carola-Bibiane Schönlieb. Robust data-driven accelerated mirror descent. In *2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 1–5. IEEE, 2023a.

Hong Ye Tan, Subhadip Mukherjee, Junqi Tang, and Carola-Bibiane Schönlieb. Data-driven mirror descent with input-convex neural networks. *SIAM Journal on Mathematics of Data Science*, 5(2):558–587, 2023b.

Junqi Tang, Mohammad Golbabaee, Francis Bach, and Mike E Davies. Rest-Katyusha: Exploiting the solutions' structure via scheduled restart schemes. In *Advances in Neural Information Processing Systems*, pp. 427–438. Curran Associates, Inc., 2018.

Junqi Tang, Karen Egiazarian, Mohammad Golbabaee, and Mike Davies. The practicality of stochastic optimization in imaging inverse problems. *IEEE Transactions on Computational Imaging*, 6:1471–1485, 2020.

Yang Wang and Haomin Zhou. Total variation wavelet-based medical image denoising. *International Journal of Biomedical Imaging*, 2006, 2006.

Blake E Woodworth and Nati Srebro. Tight complexity bounds for optimizing composite objectives. In *Advances in Neural Information Processing Systems*, pp. 3639–3647, 2016.

Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5028–5037, 2017.

Pan Xu, Tianhao Wang, and Quanquan Gu. Accelerated stochastic mirror descent: From continuous-time dynamics to discrete-time algorithms. In *International Conference on Artificial Intelligence and Statistics*, pp. 1087–1096. PMLR, 2018.

Junjie Yang, Tianlong Chen, Mingkang Zhu, Fengxiang He, Dacheng Tao, Yingbin Liang, and Zhangyang Wang. Learning to generalize provably in learning to optimize. In *International Conference on Artificial Intelligence and Statistics*, pp. 9807–9825. PMLR, 2023.

Tong Zhang. Solving large scale linear prediction problems using stochastic gradient descent algorithms. In *International Conference on Machine learning*, pp. 116. ACM, 2004.

Joey Tianyi Zhou, Kai Di, Jiawei Du, Xi Peng, Hao Yang, Sinno Jialin Pan, Ivor Tsang, Yong Liu, Zheng Qin, and Rick Siow Mong Goh. Sc2net: Sparse lstms for sparse coding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018a.

Kaiwen Zhou, Fanhua Shang, and James Cheng. A simple stochastic variance reduced algorithm with fast convergence rates. In *International Conference on Machine Learning*, pp. 5975–5984, 2018b.

Zhengyuan Zhou, Panayotis Mertikopoulos, Nicholas Bambos, Stephen Boyd, and Peter W Glynn. Stochastic mirror descent in variationally coherent optimization problems. *Advances in Neural Information Processing Systems*, 30, 2017.

Julian Zimmert and Tor Lattimore. Connections between mirror descent, Thompson sampling and the information ratio. *Advances in Neural Information Processing Systems*, 32, 2019.

Fangyu Zou, Li Shen, Zequn Jie, Weizhong Zhang, and Wei Liu. A sufficient condition for convergences of Adam and RMSprop. In *Proceedings of the IEEE/CVF Conference on computer vision and pattern recognition*, pp. 11127–11135, 2019.