A New Constructive Criterion for Markov Equivalence of MAGs

Abstract

Ancestral graphs are an important tool for encoding causal knowledge as they represent uncertainty about the presence of latent confounding and selection bias, and they can be inferred from data. As for other graphical models, several maximal ancestral graphs (MAGs) may encode the same statistical information in the form of conditional independencies. Such MAGs are said to be *Markov equivalent*. This work concerns graphical characterizations and computational aspects of Markov equivalence between MAGs. These issues have been studied in past years leading to several criteria and methods to test Markov equivalence. The state-of-the-art algorithm, provided by Hu and Evans [UAI 2020], runs in time $O(n^5)$ for instances with n vertices. We propose a new constructive graphical criterion for the Markov equivalence of MAGs, which allows us to develop a practically effective equivalence test with worst-case runtime $O(n^3)$. Additionally, our criterion is expressed in terms of natural graphical concepts, which is of independent value.

1 INTRODUCTION

Graphical causal models represent random variables as vertices of a graph and express causal effects of one variable on another with edges. Using the graphical approach allows an intuitive formalism to explore complex causal phenomena Spirtes et al. [2000], Pearl [2009], Koller and Friedman [2009]. Another strength of this approach is the ability to tackle causal problems using algorithmic tools, paving the way towards automated causal inference and data science.

A popular and commonly used model to encode causal knowledge, which can be inferred from data, is a *directed acyclic graph* (DAG). A DAG can be learned from conditional independence (CI) statements, if one assumes faithful-

Figure 1: DAG G_1 encodes the CIs $X_a \perp\!\!\!\perp \{X_c, X_d\}$ and $X_c \perp\!\!\!\perp \{X_a, X_b\}$ among observed variables (u is a latent variable). G_2 is a MAG which encodes the same CIs. The example is from [Richardson and Spirtes, 2002, Fig. 10].

ness, that is, if the CIs among the variables are equal to those expressed through d-separations in the DAG Spirtes et al. [2000]. However, multiple DAGs can imply the same CI statements. For instance, if for the variables X_a, X_b, X_c the only CI relationship is $X_a \perp\!\!\!\perp X_c \mid X_b$, then there are three DAGs $a \to b \to c$, $a \leftarrow b \to c$, and $a \leftarrow b \leftarrow c$, which encode the CI. We say that such DAGs are *Markov equivalent* and belong to the same *Markov equivalence class* (MEC). Thus, Markov equivalent DAGs encode the same CIs via d-separations and, in consequence, they are indistinguishable on the basis of observational CIs alone.

Key results for these concepts are the graphical criterion for two DAGs to be Markov equivalent [Verma and Pearl, 1990, Frydenberg, 1990] and the graph-theoretic characterization of MECs as so-called CPDAGs [Andersson et al., 1997]. Subsequent work in this field resulted in further achievements, e. g., regarding causal structure identification from data [Meek, 1997, Spirtes et al., 2000, Chickering, 2002a,b] or causal inference and analysis based on Markov equivalence classes [Maathuis et al., 2009, Wienöbst et al., 2021b]. However, things are more complicated when hidden and selective variables emerge, as is often the case in practice. Useful in this setting are (maximal) ancestral graphs (AGs, MAGs) introduced by Richardson and Spirtes [2002], which can represent uncertainty about the presence of latent confounding and selection bias, and which can be inferred from data. A variable is latent if it is not measured or recorded. For example, the DAG G_1 in Fig. 1 shows a causal structure

over four observed variables represented as vertices a, b, c, d and a latent variable represented as u. G_1 implies the independence relations $X_a \perp\!\!\!\perp \{X_c, X_d\}$ and $X_c \perp\!\!\!\perp \{X_a, X_b\}$ over the observed variables, i. e., after marginalizing variable X_u out. However, there is no DAG over a, b, c, d representing precisely these CIs, which shows that DAGs are not closed under marginalization. One can represent the CIs using MAGs as shown by G_2 in Fig. 1. Additionally, DAGs are not expressive enough for selection variables, which are unmeasured variables determining whether a measured unit is included in the data (variables which are conditioned on). Hence, DAGs are also not closed under conditioning, while the class of independence models associated with AGs is the smallest class that contains the DAG independence models and is closed under marginalizing and conditioning (see [Richardson and Spirtes, 2002] for details).

Despite many advances, a number of fundamental problems concerning the properties and algorithmic aspects of this important causal model remain to be explored. We investigate the Markov equivalence of MAGs – one of the basic problems in this field. Similarly, as in the case of DAGs, different MAGs may encode the same conditional independencies, in which case they are Markov equivalent. In graphical language, we express CIs via *m-separations*, an extended form of d-separation in DAGs (for definitions, see Section 2).

An effective polynomial-time algorithm to test if two MAGs are Markov equivalent has been the subject of intense research. A naïve implementation of the definition requires testing m-separation relations over all pairs of vertices and all subsets of vertices, which takes exponential time. The first graphical criterion was given by Spirtes and Richardson [1996]. The Spirtes and Richardson Criterion (SRC) extends the conditions by Verma and Pearl [1990] and Frydenberg [1990] for DAGs and is based on the useful concept of *discriminating paths*. The SRC is intuitive and forms the basis of subsequent work. However, testing the SRC naively requires exponential time since one has to inspect all discriminating paths, which may be exponentially many. Zhao et al. [2005] proposed another characterization using the concept of minimal collider paths, which also did not lead to polynomial time. The first criterion that can be checked in polynomial time has been proposed by Ali et al. [2009]. The complexity of their method is bounded by $O(n \cdot m^4)$ for MAGs with n vertices and m edges. Recently a criterion based on parametrizing sets was proposed by Hu and Evans [2020]. These sets can be generated in time $O(n \cdot m^2)$ ($O(n^5)$ for dense graphs with $m \in O(n^2)$) and lead to a significantly faster algorithm. However, the criterion is quite involved and verifying its satisfiability with pencil and paper, even for small instances, is not simple.

The main contribution of this paper is a new criterion for the Markov equivalence of MAGs. It is a simple and constructive variant of the SRC and allows us to develop an algorithm for equivalence testing in cubic time. This breaks the previous $O(n^5)$ worst-case time barrier. Our criterion, coined *constructive-SRC*, is based on discriminating paths, but avoids searching potentially exponentially many paths and boils down to a simple graphical condition. The constructive-SRC is intuitive and checking it by hand is convenient. For sparse graphs, which are common in causal modeling, the expected time is $O(n \cdot \Delta^2)$ for graphs with maximal degree Δ. We compare our algorithm experimentally with the algorithm by Hu and Evans [2020] and show that the theoretical improvements lead to better practical performance.

Obtaining the cubic runtime raises the question of whether further improvements are possible, e. g., whether a runtime of $O(n^2)$ can be attained. We discuss this issue by relating it to the Markov equivalence of DAGs, where such a runtime is achievable using the CPDAG representation of Markov equivalence classes. We uncover obstacles in translating this approach towards the MAG setting, while also highlighting the open research questions in this area.

2 PRELIMINARIES

General Backgrounds. A (mixed) graph $G = (V, E)$ consists of a set of vertices V and a set of edges E between pairs of vertices. We consider three different edge types: directed edges $a \rightarrow b$ (or $a \leftarrow b$), bidirected edges $a \leftrightarrow b$, and undirected edges $a - b$. Vertices linked by an edge (of any type) are called *adjacent* or *neighbors*. The *degree* of a vertex is the number of its neighbors, and the maximum degree of a graph is the maximum degree of any of its vertices. We call vertices connected by a bidirected edge *siblings*, and say that u is a *parent* of v if $u \rightarrow v$ (then v is a *child* of u). A path π between two vertices v_1 and v_p in G is a sequence of distinct vertices $\pi = \langle v_1, \ldots, v_p \rangle$ with $p \geq 2$ such that each vertex v_i is adjacent to v_{i+1} for $i = 1, \ldots, p - 1$. A path of the form $v_1 \rightarrow v_2 \rightarrow \ldots \rightarrow v_p$ is directed, or causal. If there is a directed path from u to v, then u is called an *ancestor* of v and v a *descendant* of u. For a vertex v, the set of all of its ancestors is written as $An_G(v)$. The descendant set $De_G(v)$ is analogously defined. $Dis_G(v)$ is the set of vertices in the same district as v, i. e., the ones connected to v via bidirected edges. Also, we denote by $Pa_G(v), Ch_G(v), Ne_G(v), Si_G(v)$ the set of parents, children, neighbors, siblings of v in G, respectively. If G is clear from the context, we omit it as subscript. These notations generalize to sets of vertices in the natural way. We denote the subgraph induced by vertex set S as $G[S]$. A graph is *acyclic* if there is no directed path from a vertex u to v with $v \rightarrow u$. An acyclic graph with only directed edges is called a DAG. The *skeleton* of G is the graph obtained by replacing every edge with an undirected one. A *v-structure*, also called an *unshielded collider*, is an ordered triple of vertices (u, c, v) that induces the subgraph $u \rightarrow c \leftarrow v$. A vertex c on a path π is called a *collider* if two arrowheads of π meet at c, e. g. if π contains $u \leftrightarrow c \leftarrow v$. Two vertices are *collider connected* if there is

$$x \ast\!\!\rightarrow \quad \overset{\frown}{\leftarrow\!\!\ast} \cdots \leftarrow\!\!\ast\, b \ast\!\!\rightarrow y$$

Figure 2: A discriminating path from x to y for b. The $\ast$ indicates that multiple edge marks are possible. For the last three vertices, $\overset{\frown}{\leftarrow\!\!\rightarrow}\, b \leftrightarrow y$, $\overset{\frown}{\leftarrow\!\!\rightarrow}\, b \longrightarrow y$, and $\overset{\frown}{\longleftarrow}\, b \longrightarrow y$ are possible configurations (see Fact 4.1). In the first one b is a collider, in the other two a non-collider.

a path (a *collider path*) between them on which all internal vertices are colliders; hence, adjacent vertices are collider connected. Vertices are m-*connected* by a set Z if there is a path π between them on which every collider is in $An(Z)$ and every node that is not a collider is not in Z. Such a π is called an m-*connecting path given* Z. If vertices u, v are not m-connected by Z, written as $(u \perp\!\!\!\perp v \mid Z)_G$, we say that Z m-*separates* them. Two sets X, Y are m-separated by Z if all their nodes are pairwise m-separated by Z. In DAGs, m-separation is equivalent to d-separation [Pearl, 2009].

Ancestral Graphs. A graph $G = (V, E)$ is called *ancestral* (AG) if *(i)* it is acyclic, *(ii)* for every bidirected edge $a \leftrightarrow b$ vertex a is not an ancestor of b (and vice versa), and *(iii)* for every undirected edge $a - b$ vertex a (and vertex b) have no parents or siblings [Richardson and Spirtes, 2002]. Consequently, ancestral graphs contain at most one edge type between two vertices. An AG is a *maximal ancestral graph* (MAG) if for every pair of nonadjacent vertices a and b, there exists a set Z such that a and b are m-separated by Z. Every AG can be turned into a MAG by adding bidirected edges between vertices that cannot be m-separated [Richardson and Spirtes, 2002]. Syntactically, all DAGs are MAGs and all AGs that contain only directed edges are DAGs.

Markov Equivalence. Two ancestral graphs G_1 and G_2 with the same vertex set V are said to be *Markov equivalent* if we have for all pairwise disjoint sets $A, B, Z \subseteq V$ with $A \neq \emptyset$ and $B \neq \emptyset$ that A and B are m-separated given Z in G_1 if, and only if, A and B are m-separated given Z in G_2 [Richardson and Spirtes, 2002]. The following definition is central for the study of Markov equivalence of MAGs:

Definition 2.1 ([Richardson and Spirtes, 2002])**.** *A path* $\pi = \langle x, q_1, \ldots, q_p, b, y \rangle$, $p \geq 1$, *is called* discriminating *for vertex* b *in a MAG* G *if*

(i) x *is not adjacent to* y *and*
(ii) *any* $q_i, 1 \leq i \leq p,$ *is a collider on* π *and a parent of* y.

A discriminating path is illustrated in Fig. 2. For vertices b, y in G denote by $Discr_G(b, y)$ the set of all discriminating paths $\pi = \langle x, q_1, \ldots, q_p, b, y \rangle$ for b. Our focus lies on the computational complexity of the following problem:[1]

---

[1] We first deal with the problem for MAGs *without undirected edges*. We later discuss in Section 7 how these can be included with minor modifications (our main theorem holds as is).

Problem 2.2 (MAG-EQUIVALENCE)**.**

Instance: *Two MAGs G_1 and G_2.*
Question: *Are G_1 and G_2 Markov equivalent?*

3 HISTORY

A graphical criterion for Markov equivalence of DAGs was provided by Verma and Pearl [1990] and Frydenberg [1990]:

Theorem 3.1 ([Verma and Pearl, 1990, Frydenberg, 1990])**.** *Two DAGs G_1 and G_2 are Markov equivalent if, and only if,*

(i) G_1 and G_2 have the same adjacencies and

(ii) G_1 and G_2 have the same unshielded colliders.

The first graphical criterion for two MAGs to be Markov equivalent was given by Spirtes and Richardson [1996]:

Theorem 3.2 (Spirtes and Richardson Criterion (SRC))**.** *Two MAGs G_1 and G_2 are Markov equivalent if, and only if,*

(i) G_1 and G_2 have the same adjacencies,

(ii) G_1 and G_2 have the same unshielded colliders, and

(iii) if π forms a discriminating path for b in G_1 and G_2, then b is a collider on the path π in G_1 if, and only if, it is a collider on the path π in G_2.

Note that it is indeed possible that G_1 contains a discriminating path for b and y, which is not present in G_2, even in the case of Markov equivalence (see examples 2 and 3 in Fig. 3). Therefore, testing property *(iii)* naively requires exponential time as one has to consider all discriminating paths for variable b (which may be exponentially many).[2]

On the quest of finding a *polynomial-time*-checkable criterion for the Markov equivalence of MAGs, Zhao et al. [2005] proposed the following characterization:

Theorem 3.3 ([Zhao et al., 2005])**.** *Two MAGs G_1 and G_2 are Markov equivalent if, and only, if G_1 and G_2 have the same minimal collider paths*[3].

However, this characteristic also does not lead to a polynomial-time algorithm as there can be exponentially many minimal collider paths. Subsequently, significant effort has been made to develop an algorithm that tests whether two MAGs are Markov equivalent and that runs in polynomial time [Ali et al., 2009, Hu and Evans, 2020]. To achieve this, the natural formulation in the style of Theorem 3.2 has been abandoned and more involved criteria without an intuitive graphical interpretation were introduced.

---

[2] Spirtes and Richardson [1996] claimed that the criterion is testable in time $n^{O(1)}$, which was later withdrawn [Ali et al., 2009].

[3] $\pi = \langle v_1, \ldots, v_p \rangle$ is minimal if there is no order preserving subsequence $\langle v_1 = v_{i_1}, \ldots, v_t = v_{i_t} \rangle$ that forms a collider path.

Ali et al. [2009] used *triples with order* (if the triple forms a collider, it is called a *collider with order*). The idea behind this approach is to consider only the discriminating paths that are present in any Markov equivalent MAG. While this was an important contribution towards characterizing Markov equivalence classes of MAGs [Ali et al., 2005], the recursive definition of such triples lacks the graphical intuitiveness of, e. g, the SRC. With significant technical effort, the following criterion was developed:

Theorem 3.4 (Theorem 3.7 in [Ali et al., 2009])**.** *Two MAGs G_1 and G_2 are Markov equivalent if, and only if, they have the same adjacencies and the same colliders with order.*

This criterion led to the sought polynomial-time algorithm, as the authors showed that it can be checked in polynomial time. However, the dependency is $O(n \cdot m^4)$ for MAGs with n vertices and m edges, which is $O(n^9)$ for dense graphs.

Another criterion was proposed by Hu and Evans [2020] based on so-called *parametrizing sets*. As we compare our algorithm with this approach, we give a brief overview. For a vertex set $W \subseteq V$, the *barren subset* of W is defined as $\mathrm{barren}(W) = \{w \in W \mid De(w) \cap W = \{w\}\}$. A vertex set H is called a *head* if *(i)* $\mathrm{barren}(H) = H$ and *(ii)* H is contained in a single district in $G[An(H)]$. Let $\mathcal{H}(G)$ be the set of heads and define the *tail* of a head as $\mathrm{tail}(H) = (Dis_{G[An(H)]}(H) \setminus H) \cup Pa_G(Dis_{G[An(H)]}(H))$. The parametrizing set of MAG G is defined as the set $\mathcal{S}(G) = \{H \cup A \mid H \in \mathcal{H}(G) \text{ and } \emptyset \subseteq A \subseteq \mathrm{tail}(H)\}$. Hu and Evans [2020] showed that MAGs G_1 and G_2 are Markov equivalent if, and only if, they have the same parametrizing sets. However, generating these sets is costly as they may have exponential size. Hence, they consider $\tilde{\mathcal{S}}_3 \subseteq \mathcal{S}$, which only includes sets S of cardinality 2 and 3, with the vertices in S having 1 or 2 adjacencies.

Theorem 3.5 (Corollary 3.2.1 in Hu and Evans [2020])**.** *Two MAGs G_1 and G_2 are Markov equivalent if, and only if, $\tilde{\mathcal{S}}_3(G_1) = \tilde{\mathcal{S}}_3(G_2)$.*

The sets $\tilde{\mathcal{S}}_3(G)$ can be generated in time $O(nm^2)$, which is significantly faster than the algorithm by Ali et al. [2009] (for dense graphs with $m \in O(n^2)$ the runtime equates to $O(n^5)$). However, the criterion in this form is not very intuitive in graphical terms and checking such a criterion by hand, respectively using it for a graphical characterization of Markov equivalent MAGs, appears to be inconvenient.

4 A SIMPLE CRITERION FOR THE MARKOV EQUIVALENCE OF MAGS

We propose a *constructive* variant of the Spirtes and Richardson Criterion (SRC) for the Markov equivalence of MAGs. This allows us to develop an efficient equivalence test, improving upon the previous $O(n^5)$ runtime by Hu and Evans

[2020]. Additionally, our criterion has a natural graphical characterization, which is of independent value.

We begin with the following fact observed before in Fig. 2.

Fact 4.1. *Let $\pi = \langle x, \ldots, q, b, y \rangle$ be a discriminating path in a MAG G. Then b and y are connected either via $b \leftrightarrow y$ or $b \rightarrow y$ and in the former case b is a collider on π, in the latter a non-collider.*

Proof. Recall that q is collider and a parent of y and, thus, the edge $q \rightarrow y$ is present and the edge between q and b is either $q \leftarrow b$ or $q \leftrightarrow b$.

To prove the claim, we first show that $b \leftarrow y$ cannot occur and distinguish the two ways the edge between q and b is oriented. If $q \leftarrow b$, then we have a directed cycle $q \rightarrow y \rightarrow b \rightarrow q$; if $q \leftrightarrow b$ we would have q as an ancestor of b, which violates the ancestrality property.

For the second part, note that b is always a non-collider if $b \rightarrow y$. In case of $b \leftrightarrow y$, the edge $q \leftarrow b$ cannot occur as b would be an ancestor of y, violating the ancestrality property. Hence, b is a collider in this case. □

We are ready to state our criterion for the Markov equivalence of MAGs, which we will refer to as constructive-SRC:

Theorem 4.2 (Constructive-SRC)**.** *Two MAGs G_1 and G_2 are Markov equivalent if, and only if,*

(I) G_1 *and* G_2 *have the same adjacencies,*

(II) G_1 *and* G_2 *have the same unshielded colliders, and*

(III) for all edges $b \leftrightarrow y \in G_1$ with $Discr_{G_1}(b, y) \neq \emptyset$ we have $b \rightarrow y \notin G_2$ and vice versa.

Proof. We show two directions: If G_1 and G_2 fulfill the three conditions listed in the constructive-SRC, then they are Markov equivalent. We show this by arguing that in this case SRC is satisfied.

The first two conditions are identical. Assume the third one holds for the constructive-SRC. Then there is no discriminating path for (x, b, y) with $b \leftrightarrow y$ in G_1 (for the argument we only consider G_1 w.l.o.g.) such that $b \rightarrow y$ in G_2. Hence, it cannot happen that we have a discriminating path π in G_1 and G_2 such that b is a collider in G_1 and a non-collider in G_2 (this is *(iii)* in the SRC). This is because in that case G_2 would have $b \rightarrow y$ by Fact 4.1.

For the second direction: Assume G_1 and G_2 violate one of the three conditions *(I)*, *(II)* or *(III)*. We show that they are not Markov equivalent. By the SRC, this is obvious for *(I)* and *(II)*. Now consider that *(III)* is violated but *(I)* and *(II)* are true. Then, w.l.o.g., assume that for some $b \leftrightarrow y$ in G_1 there is a discriminating path $\pi = \langle x, q_1, \ldots, q_p, b, y \rangle$ in G_1 and the edge $b \rightarrow y \in G_2$. It follows by the maximality of G_1 and the fact that x and y are nonadjacent that there is

Figure 3: Three examples to illustrate the constructive-SRC. Example 2 is from [Ali et al., 2009] and Example 3 is a modification of another example therein.

a set Z such that $(x \perp\!\!\!\perp y \mid Z)_{G_1}$. One can easily verify that $q_1, \dots, q_p \in Z$ and $b \notin Z$. Due to the former observation it holds that $(x \not\perp\!\!\!\perp b \mid Z)_{G_1}$.

On the other hand, one can see that $(x \perp\!\!\!\perp y \mid Z)_{G_2}$ and $(x \not\perp\!\!\!\perp b \mid Z)_{G_2}$ cannot both hold in G_2. This is due to the fact that $(x \not\perp\!\!\!\perp b \mid Z)_{G_2}$ immediately implies $(x \not\perp\!\!\!\perp y \mid Z)_{G_2}$ as b is a non-collider not contained in Z. Hence, G_1 and G_2 are not Markov equivalent. □

To illustrate the constructive-SRC, we give three examples (see Fig. 3) and discuss why or why not Markov equivalence holds (as all considered pairs of graphs have the same adjacencies and unshielded colliders, we focus on whether *(iii)* of the SRC and *(III)* of the constructive-SRC are satisfied).

Example 1. In the first example of Fig. 3, the graphs are not Markov equivalent as the left one contains a discriminating path from x to y with $b \leftrightarrow y$ and the right graph contains the edge $b \to y$, which violates condition *(III)* of the constructive-SRC. In the SRC, condition *(iii)* is not satisfied as the discriminating path $\pi = \langle x, q, b, y \rangle$ exists in both graphs with b being a collider in the left one and a non-collider in the right one.

Example 2. The graphs in the second example of Fig. 3 are Markov equivalent. There is a discriminating path $\langle x, q, b, y \rangle$ in the left graph and it includes the edge $b \leftrightarrow y$, but the right graph also contains the edge $b \leftrightarrow y$ and, hence, *(III)* does not apply. Accordingly, condition *(iii)* of the SRC does not apply as $\langle x, q, b, y \rangle$ is not a discriminating path. An advantage of the constructive-SRC is that one does not have to check for every path π whether it exists in both graphs. It is sufficient to check for the existence of such a path with collider b in one graph, in combination with the edge $b \to y$ in the other graph.

Example 3. The graphs in the third example of Fig. 3 are Markov equivalent as well. There is no discriminating path in the left graph, but one in the right graph, namely

$\langle x, q, b, y \rangle$. This path contains the edge $b \to y$ and, hence, *(III)* does not apply (here, the discriminating path needs to contain the edge $b \leftrightarrow y$ and the *other* graph needs to contain $b \to y$). Also, *(iii)* does not apply because, as stated above, there is no discriminating path in the left graph.

This third example is interesting, because it highlights that *(III)* indeed only refers to discriminating paths with $b \leftrightarrow y$. If then $b \to y$ in the other graph, one can conclude that Markov equivalence does not hold. If we have a discriminating path with $b \to y$, even if $b \leftrightarrow y$ in the other graph, we cannot conclude the same. However, as we have seen above, condition *(III)* is not only necessary for Markov equivalence, it is, together with *(I)* and *(II)*, also sufficient. This is because *(iii)* in the SRC could only be violated if we have a discriminating path with a collider in one graph (hence $b \leftrightarrow y$) and a non-collider in the other (hence $b \to y$) and, consequently, *(III)* would be violated as well. Hence, for the constructive-SRC, it is not necessary to consider discriminating paths with non-colliders b. This entails a simplification, which makes *(III)* easier to check by hand compared to previous formulations (we discuss the algorithmic advantages of the constructive-SRC in the subsequent section) as one only has to look for discriminating path with collider b. Moreover, it also allows to simplify the notion of a discriminating path as *a collider path between non-adjacent x and y for which every vertex but the one before y is a parent of y.*

We note that *(III)* is a generalization of the unshielded collider condition *(ii)*. To see this, we reformulate the criterion for Markov equivalence of DAGs (Theorem 3.1):

Corollary 4.3 ([Verma and Pearl, 1990, Frydenberg, 1990]). *Two DAGs G_1 and G_2 are Markov equivalent if, and only if,*

(a) G_1 and G_2 have the same adjacencies and

(b) if in G_1 there is an unshielded collider $x \to b \leftarrow y$, then the other does not contain $b \to y$ and vice versa.

Proof. We argue that *(b)* is true if, and only if, G_1 and G_2 have the same unshielded colliders (implying that Corollary 4.3 is equivalent to Theorem 3.1). The first direction is immediate: if one graph contains the unshielded collider $x \to b \leftarrow y$ while the other graph orients $b \to y$, then clearly (x, b, y) is an unshielded collider in only one them.

For the other direction assume w.l.o.g. that G_1 contains an unshielded collider (u, v, w), but G_2 does not. Then G_2 has either $u \leftarrow v$ or $v \to w$. In both cases *(b)* is violated (set $b = v$ and either $x = w, y = u$ or $x = u, y = w$). □

Corollary 4.4. *Two MAGs G_1 and G_2 are Markov equivalent if, and only if,*

(A) G_1 and G_2 have the same adjacencies,

(B) if there is a collider path $\langle x, \dots, b, y \rangle$ between non-adjacent x and y with every vertex but x, b and y being

a parent of y in G_1, then G_2 does not contain the edge $b \to y$ and vice versa.

Proof. The collider path $\langle x, \ldots, b, y \rangle$ may only consist of three vertices, i.e., it could be an unshielded collider. If the other graph were to contain the edge $b \to y$, then it would not have that same collider, meaning the graphs are not Markov equivalent by *(II)*. If the collider path consists of more than three vertices, the formulation equals *(III)*. $\square$

We remark that this corollary applies only to MAGs without undirected edges (in contrast to the constructive-SRC). However, only minor modifications are necessary to handle undirected edges as well. We discuss this in Section 7.

5 TESTING MARKOV EQUIVALENCE OF MAGS ALGORITHMICALLY

In the previous section, we derived a simple characterization of Markov equivalence for MAGs. In this section, we deal with the computational side of the problem and discuss how this new characterization can be tested. The algorithm we propose has a worst-case runtime of $O(n^3)$, thus being significantly faster than previous approaches. Moreover, for sparse graphs, which are very common in causal modeling, we even report linear time in the number of vertices.

We check the conditions *(I)* and *(II)* naively. For checking the third condition *(III)*, we need to test for each $b \leftrightarrow y$ in G_k with $k \in \{1, 2\}$, for which $b \to y$ is an edge in the other graph $G_{k'}$ (with $k' = 3 - k$), whether there is a discriminating path for b and y. We do this by considering the vertices y consecutively. For each y, we compute the bidirected connected components of its parents (we term these the *parent districts*), which aid our computations.

Definition 5.1. *Given a MAG $G = (V, E)$ and a vertex y, the bidirected connected components of $G[Pa(y)]$ are termed the parent districts of y and denoted as $\mathcal{D}(y)$.*

This notion is useful as the middle part of a discriminating path consists solely of such vertices $q_1, \ldots, q_p$ in a single parent district of y. Once the parent districts have been computed, one can check if, for a certain district $D \in \mathcal{D}(y)$, there is a vertex x non-adjacent to y and a parent or sibling of D, which can function as the start of the discriminating path. If this is the case, it remains to consider all vertices b which are siblings of D and y. For these, we can conclude that they are part of a discriminating path $x \ast\!\!\to q_1 \leftrightarrow \ldots \leftrightarrow q_p \leftrightarrow b \leftrightarrow y$. If $b \to y$ in the other graph, the graphs are not Markov equivalent. Figure 4 illustrates this approach and Algorithm 1 gives an implementation.

Theorem 5.2. *Algorithm 1 checks whether two MAGs are Markov equivalent in time $O(n^3)$ for general graphs and expected time $O(n \cdot \Delta^2)$ for graphs with maximal degree Δ.*

Figure 4: Algorithm 1 checking vertex $\boxed{y}$ in G_1 (line 5) with $\mathcal{D}(y) = \{\ \{q_3\}\ ,\ \{q_1, q_2\}\ \}$. For $D = \{q_3\}$, the set $Pa_{G_1}(D) \cup Si_{G_1}(D) \setminus Ne_{G_1}(y)$ is empty as x is a child of D. Hence, Algorithm 1 does not consider D further (line 8). For $D = \{q_1, q_2\}$, the set $Pa_{G_1}(D) \cup Si_{G_1}(D) \setminus Ne_{G_1}(y)$ contains x, which is a parent of D but not a neighbor of y. Moreover, b_1 is a sibling of both D and y. Hence, we obtain the discriminating path $x \to q_2 \leftrightarrow q_1 \leftrightarrow b_1 \leftrightarrow y$. As $b_1 \to y$ in G_2, the algorithm reports that the graphs are not Markov equivalent. Note that for SRC *(iii)* is violated due to the discriminating path x, q_2, q_1, y in both graphs with G_1 containing non-collider $q_2 \leftrightarrow q_1 \to y$ and G_2 containing collider $q_2 \leftrightarrow q_1 \leftrightarrow y$. The discriminating path for $q_1 \leftrightarrow y$ in G_2 and the corresponding edge $q_1 \to y$ would also be detected by Algorithm 1. Note that here $\{q_2\}$ is a parent district of y (q_1 is not part of this district as it is not a parent of y in G_2).

Proof. For the correctness of Algorithm 1, we need to show that *(III)* of the constructive-SRC is correctly checked. If the algorithm returns *Not Markov equivalent* in line 13, then there exists a b and y such that $b \leftrightarrow y$ in one graph and $b \to y$ in the other. Moreover, in the former graph there exists a parent district $D \in \mathcal{D}(y)$ such that there is a $x \in Pa_{G_k}(D) \cup Si_{G_k}(D) \setminus Ne_{G_k}(y)$ (this set is non-empty in line 8) and it is guaranteed that b is not only a sibling of y, but also of D. Hence, there is a discriminating path $x \ast\!\!\to q_1 \leftrightarrow \ldots \leftrightarrow q_p \leftrightarrow b \leftrightarrow y$, with $q_1, \ldots, q_p \in D$ and q_1 being the sibling/child of x and q_p being the sibling of b. The collider path from q_1 to q_p exists by the definition of D. For the same reason, we have that $q_1, \ldots, q_p$ are parents of y. Note, in particular, that $b \neq x$ and both are not in D. Thus, *(III)* is violated and the output is correct.

For the other direction, if the graph contains a violation of *(III)*, then there is a discriminating path for $b \leftrightarrow y$ (while the other graph contains $b \to y$). The existence of such a path is detected as all discriminating paths for $b \leftrightarrow y$ have the form $x \ast\!\!\to q_1 \leftrightarrow \ldots \leftrightarrow q_p \leftrightarrow b \leftrightarrow y$ with $q_1, \ldots, q_p$ being parents of y. Thus, there is a parent district of y, which has x as parent/sibling and b as a sibling. Hence, the algorithm outputs *Not Markov equivalent* in line 13.

Regarding the runtime, note that checking *(I)* and *(II)* in line 1 is possible in time $O(n^2)$, resp. $O(n^3)$. If the graph is sparse the runtimes $O(n\Delta)$, resp. $O(n\Delta^2)$ follow (in the latter case one can consider for each vertex all pairs of its parents and test whether they are adjacent.[4])

---

[4] We can perform adjacency tests in $O(1)$ by storing the graph

For checking *(III)*, there are n vertices y considered per graph at line 5. Computing the parent districts for one y can be done in time $O(n^2)$ or $O(\Delta^2)$ if Δ is the maximal degree of the graph, as finding the connected components of a (sub)graph with s vertices takes $O(s^2)$ time in the worst-case. Hence, this step can be performed in time $O(n^3)$ or $O(n \cdot \Delta^2)$. Also the neighbors/parents/siblings of y and all its parent districts may be precomputed in this phase as well. There are two nested for loops, one over the parent districts (there are at most $O(n)$ or $O(\Delta)$ many) and one over b (again there are $O(n)$ or $O(\Delta)$ choices for b)[5]. Finally line 11 can be performed in (expected) time $O(1)$ (see footnote 4). Hence, we obtain the claimed runtimes. $\square$

---

input : Two MAGs $G_1 = (V_1, E_1)$, $G_2 = (V_2, E_2)$.
output : Whether G_1 and G_2 are Markov equivalent.

1 **if** *(I) or (II) of the constructive-SRC is violated* **then**
2   **return** Not Markov equivalent.
3 **end**
4 **foreach** $G_k = (V_k, E_k)$ *with* $k \in \{1, 2\}$ **do**
5   **foreach** $y \in V_k$ **do**
6   **foreach** $D \in \mathcal{D}(y)$ **do**
7   Compute $Pa_{G_k}(D)$ and $Si_{G_k}(D)$.
8   **if** $Pa_{G_k}(D) \cup Si_{G_k}(D) \setminus Ne_{G_k}(y) \neq \emptyset$ **then**
9   **foreach** $b \in Si_{G_k}(D) \cap Si_{G_k}(y)$ **do**
10   Let $G_{k'}$ be the other graph, i. e., $k' = 3 - k$.
11   **if** $b \rightarrow y$ *in* $G_{k'}$ **then**
12   **return** Not Markov equivalent.
13   **end**
14   **end**
15   **end**
16   **end**
17   **end**
18 **end**
19 **return** Markov equivalent.

Algorithm 1: Checking the constructive-SRC.

We conclude that for graphs with maximal degree Δ the expected runtime can be written as $O(n \cdot \Delta^2)$, which is linear in the number of vertices for a constant Δ. We note that this is a crucial improvement over Hu and Evans [2020], who reported time $O(m^2) = O(n^2)$ for sparse random graphs.

6 A DIFFERENT APPROACH TO MARKOV EQUIVALENCE TESTING

The continued improvement of algorithms for testing the Markov equivalence of MAGs from exponential time (the naive testing of the SRC) over $O(n^9)$ (Ali et al. [2009]) and $O(n^5)$ (Hu and Evans [2020]) to $O(n^3)$ begs the question of what the best achievable runtime is. Is it possible to test Markov equivalence of MAGs in $O(n^2)$? A natural comparison is the one to the Markov equivalence of DAGs. Here, the *naïve* test of Theorem 3.1 can be done in $O(n^3)$: List all triples that are unshielded colliders. This approach cannot lead to faster algorithms, as we may have $\Omega(n^3)$ unshielded colliders (this obstacle exists for MAGs as well). This indicates that a whole new approach is necessary.

For DAGs, such an approach using *completed partially directed acyclic graph* (CPDAGs) [Andersson et al., 1997] was recently given by Wienöbst et al. [2021a]. A CPDAG is a compact and unique representation of a Markov equivalence class. To test whether two DAGs D_1 and D_2 are Markov equivalent, one may compute the corresponding CPDAGs C_1 and C_2 and simply check whether $C_1 = C_2$. The complexity of this approach hinges on the complexity of converting DAGs to CPDAGs. There are two algorithmic strategies for this task:

1. The first one imitates the PC algorithm for learning the CPDAG from observational data [Spirtes et al., 2000, Kalisch and Bühlman, 2007]. First, initialize C as the skeleton of D. Second, set all v-structures of D in C. Third, orient further edges by repeated application of the first three Meek rules [Meek, 1995].

2. The second strategy directly constructs the CPDAG from D based on a topological ordering of D while utilizing the characterizations of CPDAGs and Markov equivalence classes of DAGs [Andersson et al., 1997]. This approach was used by [Chickering, 1995], who proposed a clever linear-time (i. e., $O(n + m)$) algorithm for the DAG-to-CPDAG task.

Hence, based on the second approach, testing Markov equivalence of DAGs can be done in linear time $O(n + m)$. Coming back to MAGs, we note that the first approach for DAGs can be used as well. For a MAG G, one can imitate the FCI algorithm Spirtes et al. [2000], which is the counterpart of the PC algorithm under latent confounding/selection bias, to obtain its corresponding *partial ancestral graph* (PAG) [Zhang, 2008a], which is, analogously to the CPDAG for DAGs, a compact and unique representation of an equivalence class. This is done by first initializing P as the skeleton of G, then, setting the unshielded colliders according to G and, finally, applying the 10 completion rules given by Zhang [2008b] (see also Ali et al. [2005]). This approach yields a polynomial-time algorithm for testing Markov equivalence of MAGs, but with a rather large polynomial:[6] One can compute the PAGs P_1, P_2 for the

---

as adjacency matrix. For sparse graphs we may avoid $O(n^2)$ space by using hash tables, which yields expected time $O(1)$.

[5] Forming $Si_{G_k}(D) \cap Si_{G_k}(y)$ can be done in $O(n)$. To do it in expected time $O(\Delta)$ we may again use hash tables.

[6] The time is a polynomial of order roughly $O(m^3 \cdot n)$ as for every undirected edge we have to check whether global conditions hold (Zhang [2008b] briefly discussed the runtime, mentioning $O(n \cdot m)$ for checking the fourth rule for a single edge).

given MAGs G_1, G_2 and check whether they are identical[7].

The second strategy currently cannot be translated to MAGs as there is no counterpart to the DAG-to-CPDAG algorithm for directly transforming a MAG to a PAG. Reasons for this are that (i) MAGs cannot be topologically ordered in a meaningful way as easily as DAGs due to the additional bidirected edges, and (ii) it is significantly harder to obtain concise and constructive characterizations for PAGs compared to CPDAGs. We therefore believe that further improvements in the design of algorithms for the Markov equivalence test of MAGs will be tightly related to a better understanding of compact characterizations of Markov equivalence classes.

7 RELATED PROBLEMS

So far, our focus lied on the problem of testing Markov equivalence of maximal ancestral graph (MAGs) without undirected edges. In this section, we discuss the connection to more general formulations of the problem.

First, we note that the constructive-SRC and Algorithm 1 work also for MAGs with undirected edges. This is because the SRC also holds in this setting and that there cannot be an undirected edge in a discriminating path (in particular, the edge between b and y cannot be undirected).

For Corollary 4.4 a modification is necessary: condition *(II)* has to be changed to "If there is a collider path $x, \ldots, b, y$ between non-adjacent x and y with every vertex but x and b being a parent of y in one graph, then the other graph does neither contain the edge $b \rightarrow y$ nor the edge $b - y$." This is necessary as a collider $u \ast\!\!\rightarrow v \leftarrow\!\!\ast w$ in one graph might correspond to a non-collider $u - v - w$ in the other graph – and these graphs are, of course, not Markov equivalent.

Further related problems are obtained by removing the maximality or the ancestrality requirement (or both). In that case, we deal with general *acyclic directed mixed graphs* (ADMGs). These are graphs that may contain directed and bidirected edges with the only requirement that there may be no directed cycle. The SRC and constructive-SRC do not apply for ADMGs as they explicitly uses those properties. However, one can transform ADMGs into equivalent MAGs and, thus, test the Markov equivalence of ADMGs using the algorithms for MAGs. As it turns out, the currently fasted algorithm for the ADMG-to-MAG transformation (Algorithm 2 in Hu and Evans [2020]) requires time $O(n^4)$ and is, thus, the bottleneck in this approach (testing the equivalence of MAGs is in $O(n^3)$ by Theorem 5.2).

It is unclear whether this transformation can be performed in $O(n^3)$. A central part of it involves the computation of so-called *inducing paths*, where it has to be checked

for every pair of vertices (x, y) whether there is a collider path between x and y via vertices in $\mathrm{An}(x, y)$. Since we have $O(n^2)$ such pairs and since, further, graph traversal is in $\Omega(n + m)$, this direct approach necessarily produces a workload of $O(m \cdot n^2)$. We believe that it will be central for the developement of faster ADMGs equivalence tests to better understand the complexity of ADMG-to-MAG and deem this as an important question for further work.

8 EXPERIMENTS

To emphasize the practical effectiveness of the constructive-SRC and, in particular, Algorithm 1, we compared an implementation of it to the previously fastest approach by Hu and Evans [2020] on synthetic data. We base our experimental setup on the approach given in the latter paper, all specifics and the detailed results can be found in Appendix A and the figures therein. We compared the algorithms for sparse and for slightly denser graphs. We report that Algorithm 1 is faster by a significant margin (up to a factor 50), needing only fractions of seconds for the considered inputs. One of the main practical advantages of the algorithm (in addition to the improved worst-case runtime) is that it only needs to consider, for each vertex y, its parents and their siblings/parents, whereas Hu and Evans [2020] need to look at all ancestors of v and w for every edge $v \leftrightarrow w$. In most causal models, the number of parents is a small constant, while the number of ancestors might even be in $O(n)$.

9 CONCLUSIONS

We proposed the constructive-SRC – a new graphical criterion for the Markov equivalence of MAGs. It is expressed in terms of natural graphical concepts, can easily be checked by hand for smaller graphs, and leads to the first cubic-time Markov equivalence test for MAGs.

For further work, it remains an open problem whether the runtime can be reduced to $O(n^2)$, as is possible for DAGs. We argued that, for this, a different approach is necessary as any approach, which explicitly considers all unshielded colliders has a complexity of $\Omega(n^3)$. Generally, a better understanding of Markov equivalence classes of MAGs may facilitate the translation of further research from the DAG setting, e. g., regarding active learning [Hauser and Bühlmann, 2012] or the question of computing the size of Markov equivalence classes [Wienöbst et al., 2021b], which could add to recent papers in this direction [Kocaoglu et al., 2019, Wang and Zhou, 2021].

Finally, due to the improved runtime for equivalence testing of MAGs, the ADMG-to-MAG transformation is currently the bottleneck for the problem on acyclic mixed graphs. We thus deem the design of a faster transformation algorithm an important task for further work.

---

[7]This strategy has some parallels to Ali et al. [2009], due to the fact that colliders with order also play a key role in the completeness of the FCI rules Ali et al. [2005].

References

R Ayesha Ali, Thomas S Richardson, Peter Spirtes, and Jiji Zhang. Towards characterizing markov equivalence classes for directed acyclic graphs with latent variables. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI '05*, pages 10–17, 2005.

R Ayesha Ali, Thomas S Richardson, and Peter Spirtes. Markov equivalence for ancestral graphs. *The Annals of Statistics*, 37(5B):2808–2837, 2009.

Steen A Andersson, David Madigan, and Michael D Perlman. On the Markov equivalence of chain graphs, undirected graphs, and acyclic digraphs. *Scandinavian Journal of Statistics*, 24(1):81–102, 1997.

Jeff Bezanson, Alan Edelman, Stefan Karpinski, and Viral B Shah. Julia: A fresh approach to numerical computing. *SIAM review*, 59(1):65–98, 2017. URL https://doi.org/10.1137/141000671.

David Maxwell Chickering. A transformational characterization of equivalent Bayesian network structures. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI '95*, pages 87–98, 1995.

David Maxwell Chickering. Learning equivalence classes of Bayesian-network structures. *Journal of Machine Learning Research*, 2:445–498, 2002a.

David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of Machine Learning Research*, 3:507–554, 2002b.

Morten Frydenberg. The chain graph Markov property. *Scandinavian Journal of Statistics*, pages 333–353, 1990.

Alain Hauser and Peter Bühlmann. Characterization and greedy learning of interventional markov equivalence classes of directed acyclic graphs. *The Journal of Machine Learning Research*, 13(1):2409–2464, 2012.

Zhongyi Hu and Robin Evans. Faster algorithms for markov equivalence. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI '20*, pages 739–748. PMLR, 2020.

Markus Kalisch and Peter Bühlman. Estimating high-dimensional directed acyclic graphs with the pc-algorithm. *Journal of Machine Learning Research*, 8(3), 2007.

Murat Kocaoglu, Amin Jaber, Karthikeyan Shanmugam, and Elias Bareinboim. Characterization and learning of causal graphs with latent variables from soft interventions. *Advances in Neural Information Processing Systems*, 32, 2019.

Daphne Koller and Nir Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.

Marloes H Maathuis, Markus Kalisch, and Peter Bühlmann. Estimating high-dimensional intervention effects from observational data. *The Annals of Statistics*, 37(6A): 3133–3164, 2009.

Christopher Meek. Causal inference and causal explanation with background knowledge. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI 95*, pages 403–410, 1995.

Christopher Meek. *Graphical Models: Selecting Causal and Statistical Models*. PhD thesis, Carnegie Mellon University, 1997.

Judea Pearl. *Causality*. Cambridge University Press, 2nd Ed., 2009. ISBN 0-521-77362-8.

Thomas Richardson and Peter Spirtes. Ancestral graph markov models. *The Annals of Statistics*, 30(4):962–1030, 2002.

Peter Spirtes and Thomas Richardson. A polynomial time algorithm for determining DAG equivalence in the presence of latent variables and selection bias. In *Proc. of the 6th International Workshop on Artificial Intelligence and Statistics*, pages 489–500, 1996.

Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

Thomas Verma and Judea Pearl. Equivalence and synthesis of causal models. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI '90*, pages 255–270, 1990.

Tian-Zuo Wang and Zhi-Hua Zhou. Actively identifying causal effects with latent variables given only response variable observable. *Advances in Neural Information Processing Systems*, 34, 2021.

Marcel Wienöbst, Max Bannach, and Maciej Liśkiewicz. Extendability of causal graphical models: Algorithms and computational complexity. In *Proc. of the Conference on Uncertainty in Artificial Intelligence, UAI '21*. AUAI Press, 2021a.

Marcel Wienöbst, Max Bannach, and Maciej Liśkiewicz. Polynomial-time algorithms for counting and sampling Markov equivalent DAGs. In *Proc. of the 35th Conference on Artificial Intelligence, AAAI*, pages 294–321, 2021b.

Jiji Zhang. Causal reasoning with ancestral graphs. *Journal of Machine Learning Research*, 9:1437–1474, 2008a.

Jiji Zhang. On the completeness of orientation rules for causal discovery in the presence of latent confounders and selection bias. *Artificial Intelligence*, 172(16-17): 1873–1896, 2008b.

Hui Zhao, Zhongguo Zheng, and Baijun Liu. On the Markov equivalence of maximal ancestral graphs. *Science in China Series A: Mathematics*, 48(4):548–562, 2005.

A FULL EXPERIMENTS

We compare an implementation of Algorithm 1 on synthetic data with the algorithm proposed by Hu and Evans [2020]. Both algorithms were implemented in the Julia programming language [Bezanson et al., 2017] and we ran the experiments on a desktop computer with an Intel(R) Core(TM) i7-8565U CPU and 16GBs of RAM. The code to reproduce the experiments is provided in the supplementary material. Synthetic MAGs were generated with the process described in [Hu and Evans, 2020]: Fix a topological ordering τ of the vertices, then add k edges uniformly at random, and finally direct each edge with probability $1/2$ according to τ. Replacing remaining undirected edges with bidirected edges yields an ADMG, which can in turn be transformed into a MAG, as discussed in Section 7.

For a fair comparison with the experiments in [Hu and Evans, 2020], we run a modified version of Algorithm 1. It generates for *a single MAG* a set of all adjacencies A (for checking *I*), a set of all v-structures V (for checking *II*), and the set C of all $b \leftrightarrow y$ that are part of a discriminating path, as well as the set N of all $b \rightarrow y$ (for checking *III*). Clearly, if one were to generate these sets for two MAGs G_1 and G_2, testing Markov equivalence would reduce to the simple task of checking whether $A_1 = A_2$, $V_1 = V_2$, $C_1 \cap Ne_2 = \emptyset$, and $C_2 \cap Ne_1 = \emptyset$.

This approach provides a finer control over the experiments as it avoids the possibility of an "early stopping" at line 1 or line 13 of Algorithm 1 (which can happen if the given MAGs are not equivalent and would give an unfair advantage to our algorithm). It also enables us to consider single MAGs, which are simpler to generate randomly than, e. g, two random Markov equivalent MAGs. The reported runtimes can be viewed, for our algorithm as well as for [Hu and Evans, 2020], as essentially half the time occurring when two Markov equivalent DAGs are compared (because these steps have to be performed for both graphs and there is no early stopping in this case).

For the choice of the parameter k (the number of edges), we follow, on the one hand, Hu and Evans [2020] and set it to $k = 3n$ (see the top part of Fig. 5) and, on the other hand, also consider denser graphs with $k = 10n$ (bottom part of Fig. 5). Note that k is the number of edges in the generated ADMG, and not in the MAGs on which the algorithms run. The transformation of an ADMG into a MAG might generate new edges, see Table 1. For $k = 3n$, one usually only sees a small increase, while a significant amount of edges is added for $k = 10n$. The proportion of directed and bidirected edges also changes in the latter case, the graphs usually contain more directed edges than bidirected ones.

For our experiments, we ran both algorithms on the same 250 randomly generated graphs for each choice of parameters and report the average time they used in Fig. 5.

Table 1: Distribution of directed edges ($\rightarrow$) and bidirected edges ($\leftrightarrow$) in the randomly generated ADMGs and in the corresponding MAGs. For every row we generated 250 random ADMGs with n vertices and k edges, and show the average of directed or bidirected edges they contain.

		ADMG			MAG		
n	k	$\rightarrow$	$\leftrightarrow$	$\rightarrow/\leftrightarrow$	$\rightarrow$	$\leftrightarrow$	$\leftarrow/\leftrightarrow$
250	3n	373.844	376.156	0.9962	394.38	401.88	0.9840
500	3n	752.536	747.464	1.0081	772.148	771.456	1.0022
750	3n	1125.812	1124.188	1.0023	1146.012	1147.944	0.9991
1000	3n	1500.308	1499.692	1.0010	1519.616	1523.628	0.9980
1250	3n	1873.564	1876.436	0.9990	1892.58	1899.968	0.9966
1500	3n	2251.344	2248.656	1.0016	2270.228	2272.872	0.9992
1750	3n	2627.564	2622.436	1.0023	2647.156	2646.568	1.0005
2000	3n	3002.328	2997.672	1.0018	3021.66	3021.5	1.0003
25	10n	124.392	125.608	0.9984	246.432	49.544	5.4013
50	10n	250.912	249.088	1.0113	824.804	306.212	2.7741
75	10n	374.312	375.688	0.9989	1639.868	796.848	2.0995
100	10n	498.536	501.464	0.9962	2684.468	1501.252	1.8099
125	10n	625.692	624.308	1.0038	3902.696	2456.212	1.6067
150	10n	749.684	750.316	1.0006	5314.2	3632.024	1.4762
175	10n	874.788	875.212	1.0007	6926.444	4999.7	1.3952
200	10n	1002.088	997.912	1.0051	8662.34	6582.824	1.3236

It can be seen that Algorithm 1 is faster for all choices of n and k. We can also observe that for ever larger graphs, the advantage over the algorithm by Hu and Evans [2020] increases – which implies that the algorithm in fact has a better asymptotic behaviour. This phenomenon becomes even more significant on the dense (and, thus, more difficult) instances. Finally, the absolute runtime of Algorithm 1 is generally extremely low (for the considered inputs only fractions of a second[8]).

This shows that the theoretical improvement in worst-case time complexity from $O(n^5)$ to $O(n^3)$ also translates to practical settings. One reason, also mentioned in the main paper, is that Algorithm 1 acts locally: for each y it only has to check its parents and their neighbors (this amounts to a constant number of vertices for most causal models in practice), whereas the algorithm by Hu and Evans [2020] needs to look at all ancestors of v and w for every edge $v \leftrightarrow w$, and these may be $O(n)$ many.

---

[8]Generating significantly harder instances is not a trivial task as the random generation process relies on the ADMG-to-MAG task, which currently cannot be performed faster than $O(n^4)$.

n	Algorithm HE		Algorithm C-SRC		Random graphs with $n =$
	Avg. Time	Std. Dev.	Avg. Time	Std. Dev.	250 500 750 1000 1250 1500 1750 2000
250	0.0487s	0.0101	0.0015s	0.0009	
500	0.1058s	0.0388	0.0032s	0.0051	
750	0.1605s	0.0279	0.0049s	0.0065	
1000	0.2587s	0.0594	0.0062s	0.0058	
1250	0.3579s	0.0684	0.0085s	0.0081	
1500	0.4629s	0.0789	0.0091s	0.0058	
1750	0.5373s	0.0626	0.0106s	0.0021	
2000	0.6794s	0.0778	0.0119s	0.0024	

Advantage of C-SRC / HE

0.0472s 0.10258s 0.15556s 0.2525s 0.34938s 0.45377s 0.52664s 0.66751s

n	Algorithm HE		Algorithm C-SRC		Random graphs with $n =$
	Avg. Time	Std. Dev.	Avg. Time	Std. Dev.	25 50 75 100 125 150 175 200
25	0.0011	0.0007	0.0004	0.0004	
50	0.0169	0.0028	0.0028	0.0007	
75	0.0912	0.0246	0.0092	0.0014	
100	0.4004	0.1037	0.0263	0.0129	
125	1.0339	0.2283	0.0466	0.0091	
150	2.3356	0.4349	0.0808	0.0084	
175	4.7182	0.8741	0.1303	0.0106	
200	8.9285	1.5242	0.2033	0.0129	

Advantage of C-SRC / HE

0.00067s 0.01414s 0.0826s 0.37418s 0.98724s 2.25485s 4.58789s 8.72528s

Figure 5: *Advantage plots* that compare our implementation (C-SRC) with the algorithm by Hu and Evans (HE). Each bar corresponds to an experiment on random graphs with n vertices (denoted above the bars) and $k = 3n$ (top image) or $k = 10n$ (bottom image) edges, respectively. For each experiment we measured the average time needed by both algorithms over 250 instances. If C-SRC uses t_1 seconds and HE took t_2 seconds, then the *advantage* of C-SRC over HE is defined by $t_2 - t_1$ (i. e., the advantage is positive iff C-SRC is faster). The advantage (in seconds) is shown below the bars.