Partial Rejection Control for Robust Variational Inference in Sequential Latent Variable Models

Abstract

Effective variational inference crucially depends on a flexible variational family of distributions. Recent work has explored sequential Monte-Carlo (SMC) methods to construct variational distributions, which can, in principle, approximate the target posterior arbitrarily well, which is especially appealing for models with inherent sequential structure. However, SMC, which represents the posterior using a weighted set of particles, often suffers from particle weight degeneracy, leading to a large variance of the resulting estimators. To address this issue, we present a novel approach that leverages the idea of *partial* rejection control (PRC) and enables us to develop a robust variational inference framework. Although PRC constructs a low variance estimator of the marginal likelihood, unbiased estimators are not available in the literature for arbitrary variational posteriors. We solve this issue by employing a *dice-enterprise*: a generalization of the *Bernoulli factory* to construct unbiased estimators for SMC-PRC. The resulting variational lower bound can be optimized efficiently with respect to the variational parameters. We show theoretical properties of the lower bound and report experiments on various sequential models, such as the Gaussian state-space model and variational RNN, on which our approach outperforms existing methods.

1 Introduction

Exact inference in latent variable models is usually intractable. Markov Chain Monte-Carlo (MCMC) (Andrieu et al., 2003) and variational methods (Blei et al., 2017), are commonly employed in such models to make inference tractable. While MCMC has been the traditional method of choice, often with provable guarantees, optimization based variational inference (VI) methods have also enjoyed considerable recent interest due to their excellent scalability on large-scale datasets. VI, in particular, is based on maximizing a lower bound constructed through a marginal likelihood estimator. However, for latent variable models with sequential structure, sequential Monte Carlo (SMC) (Doucet & Johansen, 2009) returns a much lower variance estimator for the log marginal likelihood than importance sampling (IS) (Bérard et al., 2014; Cérou et al., 2011). In this work, we focus our attention on designing a low variance, *unbiased*, and computationally efficient estimator of the marginal likelihood.

The performance of SMC based methods is strongly dependent on the choice of the proposal distribution. Inadequate proposal distributions propose values in areas of low probability under the target, leading to particle depletion (Doucet & Johansen, 2009). An effective solution is to use rejection control (Liu et al., 1998; Peters et al., 2012) which is based on an *approximate* rejection sampling step within SMC to reject samples with low importance weights.

In this work, we leverage the idea of *partial* rejection control within the framework of SMC based VI for sequential latent variable models. To this end, we construct a novel lower bound VSMC-PRC and propose an efficient optimization strategy. As compared to other recently proposed SMC based VI approaches (Naesseth et al., 2017; Maddison et al., 2017; Le et al., 2017), our approach consists of an inbuilt accept-reject mechanism within SMC to prevent particle depletion and obtain an *unbiased* marginal likelihood estimator. To the best of our knowledge, there are no unbiased estimators

available for SMC-PRC for arbitrary proposal distributions (but see Kudlicka et al., 2020, for when the proposal is the prior density itself).

Although the idea of combining VI with an inbuilt accept-reject mechanism is not new (Salimans et al., 2015; Ruiz & Titsias, 2019; Grover et al., 2018), a key distinction of our approach is to incorporate a *partial* accept-reject mechanism. In contrast to standard sampling algorithms that may reject the *entire* stream of particles, we use accept-reject on the most recent update, increasing the sampling efficiency. Another key distinction is that, while existing approaches using PRC (Liu et al., 1998; Peters et al., 2012) construct a biased marginal likelihood estimator, we leverage insights from dice-enterprise (Morina et al., 2019) and Bernoulli factory (Asmussen et al., 1992) to obtain an *unbiased* estimator.

The rest of the paper is organized as follows: In Section 2, we provide a brief review on SMC, partial rejection control, and dice enterprise. In Section 3, we introduce our VSMC-PRC bound and provide new theoretical insights into the Monte-Carlo estimator and design efficient ways to optimize it. Finally, we discuss related work and present experiments on the Gaussian state-space model (SSM) and variational recurrent neural networks (RNN).

2 BACKGROUND

We denote a sequence of T real-valued observations as $x_{1:T} = (x_1, x_2, \ldots, x_T)$, and assume that there is an associated sequence of latent variables $z_{1:T} = (z_1, z_2, \ldots, z_T)$. We further assume that the joint density $p_\theta(x_{1:t}, z_{1:t})$ factorizes as follows for $t \in \{2, 3, \ldots, T\}$

$$p_\theta(x_{1:t}, z_{1:t}) = p_\theta(x_{1:t-1}, z_{1:t-1})p_\theta(x_t, z_t | x_{1:t-1}, z_{1:t-1}). \tag{1}$$

We are interested in inferring the posterior distribution of the latent variables, i.e., $p(z_{1:T}|x_{1:T})$. The task is, in general, intractable.

2.1 SEQUENTIAL MONTE CARLO WITH PARTIAL REJECTION CONTROL

A SMC sampler approximates a sequence of densities $(p_\theta(z_{1:t}|x_{1:t}))_{t=1}^T$ through a set of N weighted samples generated from a proposal distribution. Let the proposal density be

$$q_\phi(z_{1:T}|x_{1:T}) = \prod_{t=1}^{T} q_\phi(z_t | x_{1:t}, z_{1:t-1}). \tag{2}$$

Consider time $t-1$ at which we have uniformly weighted samples $\{N^{-1}, z_{1:t-1}^i, A_{t-1}^i\}_{i=1}^N$ estimating $p_\theta(z_{1:t-1}|x_{1:t-1})$. We want to estimate $p_\theta(z_{1:t}|x_{1:t})$ such that particles with a low importance weight are automatically rejected. PRC achieves this by using an *approximate* rejection sampling step (Liu et al., 1998; Peters et al., 2012). The overall procedure is as follows:

- Generate $z_t^i \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$ where $i = 1, 2, \ldots, N$.
- Accept z_t^i with probability

$$a_{\theta,\phi}(z_t^i | z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) = \left(1 + \frac{M(i, t-1)q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})}\right)^{-1}, \tag{3}$$

  where $M(i, t-1)$ is a hyperparameter controlling the acceptance rate. Note that PRC applies accept-reject only on z_t^i, not on the entire trajectory.
- The new incremental importance weight of the accepted sample is

$$\alpha_t(z_{1:t}^i) = c_t^i \int a_{\theta,\phi}(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})dz_t, \tag{4}$$

  where c_t^i is

$$c_t^i = \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})}{q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}. \tag{5}$$

- Compute Monte-Carlo estimator of $\alpha_t(.)$:

$$\widetilde{w}_t^i = \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i}) \frac{1}{K} \sum_{k=1}^{K} a_{\theta,\phi}(\delta_t^{i,k} | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) a_{\theta,\phi}(z_t^i | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}, \qquad (6)$$

  where $\delta_t^{i,k} \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$ and $k = 1, 2, \dots, K$.

- Generate ancestor variables A_t^i through *dice-enterprise* and set new weights $w_t^i = N^{-1}$ for $i = 1, 2, \dots, N$:

$$A_t^i \sim \text{Categorical}\left(\frac{\alpha_t(z_{1:t}^1)}{\sum_{j=1}^N \alpha_t(z_{1:t}^j)}, \frac{\alpha_t(z_{1:t}^2)}{\sum_{j=1}^N \alpha_t(z_{1:t}^j)}, \dots, \frac{\alpha_t(z_{1:t}^N)}{\sum_{j=1}^N \alpha_t(z_{1:t}^j)}\right). \qquad (7)$$

2.2 DICE ENTERPRISE

Simulation of ancestor variables in Eq. (7) is non-trivial due to intractable normalization constants in the incremental importance weight (see Eq. (4)). Vanilla Monte-Carlo estimation yields biased estimators. To address this issue, we leverage a generalization of *Bernoulli factory* (Asmussen et al., 1992), called *dice-enterprise* (Morina et al., 2019).

Suppose we can simulate Bernoulli(p_t^i) outcomes where p_t^i is intractable. Bernoulli factory problem simulates an event with probability $f(p_t^i)$, where $f(.)$ is some desired function. In our case, the intractable coin probability p_t^i is the intractable normalization constant,

$$p_t^i = \int a_{\theta,\phi}(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) dz_t. \qquad (8)$$

Since $p_t^i \in [0, 1]$ and we can easily simulate this coin, we obtain the *dice-enterprise* algorithm below.

1. Required: Constants $\{c_t^i\}_{i=1}^N$ see (5).

2. Sample $C \sim \text{Categorical}\left(\frac{c_t^1}{\sum_{j=1}^N c_t^j}, \frac{c_t^2}{\sum_{j=1}^N c_t^j}, \dots, \frac{c_t^N}{\sum_{j=1}^N c_t^j}\right)$

3. If $C = i$, generate $U_i \sim U[0, 1]$ and $z_t \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$

   - If $U_i < a_{\theta,\phi}(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$ output i
   - Else go to step 2

The *dice-enterprise* produces unbiased ancestor variables. For details on efficiency and correctness, please refer to Section 3.1. Our proposed VSMC-PRC bound is constructed through a marginal likelihood estimator obtained by combining the SMC sampler with a PRC step and *dice-enterprise*. The variance of estimators obtained through SMC-PRC particle filter is usually low (Kudlicka et al., 2020; Peters et al., 2012). Therefore, we expect VSMC-PRC to be a tighter bound compared to the standard SMC based bounds used in recent works (Maddison et al., 2017; Naesseth et al., 2017; Le et al., 2017). Algorithm (1) summarizes the generative process to simulate the VSMC-PRC bound.

3 PARTIAL REJECTION CONTROL BASED VI FOR SEQUENTIAL LATENT VARIABLE MODELS

We now show how to leverage PRC to develop a robust VI framework for sequential latent variable models. Our framework is based on the VSMC-PRC bound presented below. The complete sampling distribution of Algorithm (1) is as follows.

$$Q_{\text{VSMC-PRC}}\left(z_{1:T}^{1:N}, A_{1:T-1}^{1:N}, \delta_{1:T}^{1:N,1:K}\right) = \left(\prod_{k=1}^{K}\prod_{i=1}^{N} q_\phi(\delta_1^{i,k}|x_1) \prod_{t=2}^{T}\prod_{i=1}^{N}\prod_{k=1}^{K} q_\phi(\delta_t^{i,k}|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})\right) \times$$

$$\left(\prod_{i=1}^{N}\frac{q_\phi(z_1^i|x_1)a_{\theta,\phi}(z_1^i|x_1)}{Z(x_1, M(i,0))}\prod_{t=1}^{T-1}\prod_{i=1}^{N}\text{Discrete}(A_t^i|\alpha_t)\frac{q_\phi(z_{t+1}^i|x_{1:t+1}, z_{1:t}^{A_t^i})a_{\theta,\phi}(z_{t+1}^i|z_{1:t}^{A_t^i}, x_{1:t+1})}{Z(z_{1:t}^{A_t^i}, x_{1:t+1}, M(i,t))}\right)$$

$$\tag{9}$$

Algorithm 1 Estimating the VSMC-PRC lower bound

1: **Required**: N, K, and M
2: **for** $t \in \{1, 2, \ldots, T\}$ **do**
3:    **for** $i \in \{1, 2, \ldots, N\}$ **do**
4:      $z_t^i, c_t^i, \widetilde{w}_t^i \sim \textbf{PRC}\,(q, p, M(t-1, i))$
5:      $z_{1:t}^i = (z_{1:t-1}^{A_{t-1}^i}, z_t^i)$
6:    **end for**
7:    **for** $i \in \{1, 2, \ldots, N\}$ **do**
8:      $A_t^i = \textbf{DICE-ENT}\left(\{c_t^i, z_{1:t}^i\}_{i=1}^N\right)$
9:    **end for**
10: **end for**
11: **return** $\log \prod_{t=1}^T \left(\frac{1}{N}\sum_{i=1}^N \widetilde{w}_t^i\right)$
12:
13: **PRC** $(q, p, M(t-1, i))$
14: **while** sample not accepted **do**
15:    Generate $z_t^i \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$
16:    Accept z_t^i with probability
   $a_{\theta,\phi}(z_t^i | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$

17: **end while**
18: Sample $\{\delta_t^{i,k}\}_{k=1}^K \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$
19: Calculate $\widetilde{w}_t^i$ from (6)
20: Calculate c_t^i from (5)
21: **return** $\left(z_t^i, c_t^i, \widetilde{w}_t^i\right)$
22:
23: **DICE-ENT** $\left(\{c_t^i, z_{1:t}^i\}_{i=1}^N\right)$
24: Sample $C \sim \text{Multinoulli}\left(\frac{c_t^i}{\sum_{j=1}^N c_t^j}\right)_{i=1}^N$
25: **if** $C == i$ **then**
26:    Sample $U_i \sim U[0, 1]$
27:    $z_t^i \sim q_\phi(z_t | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$
28: **end if**
29: **if** $U_i < a_{\theta,\phi}(z_t^i | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$ **then**
30:    **return** (i)
31: **else**
32:    return **DICE-ENT** $\left(\{c_t^i, z_{1:t}^i\}_{i=1}^N\right)$
33: **end if**

The normalization constants $Z(.)$ in Eq. 9 are intractable and have to be estimated while calculating the weights. Therefore, we introduce an extra parameter K, denoting the number of Monte-Carlo samples used to estimate $Z(.)$. The Monte-Carlo estimator of VSMC-PRC bound is

$$\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K) = \sum_{t=1}^T \log\left(\frac{1}{N}\sum_{i=1}^N \widetilde{w}_t^i\right). \tag{10}$$

We maximize the VSMC-PRC bound with respect to model parameters θ and variational parameters ϕ. This requires estimating the gradient the details of which are provided in Section (3.2).

3.1 THEORETICAL PROPERTIES

We now present properties of the Monte-Carlo estimator $\hat{\mathcal{L}}_{\text{VSMC-PRC}}$. The key variables that affect this bound are N (number of samples), hyper-parameter M, and the number of Monte-Carlo samples used to compute the normalization constant $Z(.)$, i.e., K. As discussed by Bérard et al. (2014); Naesseth et al. (2017), as N increases, we expect the VSMC-PRC bound to get tighter. Hence, we will focus our attention on M and K. All the proofs can be found in the appendix.

Proposition 1. *Dice-enterprise produces unbiased ancestor variables. Further, let Λ_t be the number of iterations required for generating one ancestor variable, then $\Lambda_t \sim \text{Geom}\left(\mathbb{E}[\Lambda_t]^{-1}\right)$ where*

$$\mathbb{E}[\Lambda_t] = \frac{\sum_{i=1}^N c_t^i}{\sum_{i=1}^N c_t^i Z(z_{1:t-1}^{A_{t-1}^i}, x_{1:t}, M(i, t-1))}.$$

As evident from Proposition (1), the computational efficiency of the *dice-enterprise* clearly relies on the normalization constant $Z(.)$. Note that the value of $Z(.)$ could be interpreted as the average acceptance rate of PRC which depends on the hyper-parameter $M(i, t-1)$. If the average acceptance rate for PRC for all particles is γ, then we can express the expected number of iterations as $\mathbb{E}[\Lambda_t^i] = \gamma^{-1}$. Therefore, the computational efficiency of *dice-enterprise* is similar to the PRC step and depends crucially on the hyper-parameter M.

Proposition 2. *For all K, $\exp(\hat{\mathcal{L}}_{\text{VSMC-PRC}})$ is unbiased, i.e., $\mathbb{E}\left[\exp(\hat{\mathcal{L}}_{\text{VSMC-PRC}})\right] = p_\theta(x_{1:T})$. Further, $\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}]$ is non-decreasing in K.*

The use of Monte-Carlo estimator in place of the true value of $Z(.)$ creates an inefficiency, as depicted by Proposition (2). The bound monotonically increases as we increase K despite the use of resampling operation. It is important to note that Algorithm (1) produces an unbiased estimator of the marginal likelihood for all values of K.

(a) VSMC-PRC (b) IWAE (c) FIVO

Figure 1: Comparison of VSMC-PRC with IWAE (Burda et al., 2015) and FIVO (Maddison et al., 2017) (a) The blue arrows represent the resampling step, We then generate multiple samples from parametrized proposal $z_t^i | z_{1:t-1}^i$ out of which one sample is accepted via PRC, depicted via green arrows. (b) In IWAE, there is no resampling step and no PRC step (c). In FIVO, there is a resampling step (blue arrows) but no PRC step.

Proposition 3. *Let the sampling distribution of the i^{th} particle (generated via PRC) at time t be $r_{\theta,\phi}(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$, then*

$$KL\left(r_{\theta,\phi}(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) \,\|\, p_\theta(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})\right) \leq KL\left(q_\phi(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) \,\|\, p_\theta(z_t | z_{1:t-1}^{A_{t-1}^i}, x_{1:t})\right).$$

Proposition (3) implies that the use of the accept-reject mechanism within SMC refines the sampling distribution. Instead of accepting all samples, the PRC step ensures that only high-quality samples are accepted, leading to a tighter bound for VSMC in general (not always). We show in the appendix that when $M(i, t-1) \to \infty$, the PRC step reduces to pure rejection sampling (Robert & Casella, 2013). On the other hand, $M(i, t-1) \to 0$ implies that all samples are accepted from the proposal. Recall, $M(i, t-1)$ is a hyperparameter that can be tuned to control the acceptance rate. For more details on tuning M, see Section (3.3).

3.2 GRADIENT ESTIMATION

For tuning the variational parameters, we use stochastic optimization. Algorithm (1) produces the marginal likelihood estimator by sequentially sampling the particles, ancestor variables, and particles for the normalization constant $(z_{1:T}^{1:N}, A_{1:T-1}^{1:N}, \delta_{1:T}^{1:N,1:K})$.

When the variational distribution $q_\phi(.)$ is reparameterizable, we can make the sampling of $\delta_t^{i,k}$ independent of the model and variational parameters. However, the generated particles z_t^i are not reparametrizable due to the PRC step. Finally, the ancestor variables are discrete and, therefore, cannot be reparameterized. The complete gradient can be divided into three core components (assuming $q_\phi(.)$ is reparametrizable):

$$\nabla_{\theta,\phi}\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}] = \mathbb{E}_{Q_{\text{VSMC-PRC}}}\left[\nabla_{\theta,\phi}\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K)\right] + g_{\text{PRC}} + g_{\text{RSAMP}} \quad (11)$$

$$\approx \mathbb{E}_{Q_{\text{VSMC-PRC}}}\left[\nabla_{\theta,\phi}\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K)\right]. \quad (12)$$

Note that g_{PRC} and g_{RSAMP} denote the score gradient of PRC and resampling step, respectively. Due to high variance, we have ignored these terms for the optimization. We have derived the full gradient and explored the gradient variance issues in the appendix. Please see Figure (2) (*left*) comparing the convergence of biased gradient vs. unbiased gradients on a toy Gaussian SSM.

3.3 LEARNING THE M MATRIX

We use M as a hyperparameter for the PRC step which controls the acceptance rate of the sampler. The basic scheme of tuning M is as follows:

- Define a new random variable $F(z_{t+1} | z_{1:t}^{A_t^i}, x_{1:t+1}) = \log\left(\frac{q_\phi(z_{t+1} | x_{1:t+1}, z_{1:t}^{A_t^i})}{p_\theta(x_{t+1}, z_{t+1} | x_{1:t}, z_{1:t}^{A_t^i})}\right)$.

- Draw $z_{t+1}^j \sim q_\phi(z_{t+1}|x_{1:t+1}, z_{1:t}^{A_t^i})$ for $j = 1, 2, \ldots, J$.
- Evaluate $\gamma \in [0, 1]$ quantile value of $\{F(z_{t+1}^j | z_t^{A_t^i}, x_{1:t+1})\}_{j=1}^J$. In general for this case the acceptance rate would be around γ for all particles.

$$\log M(i, t) = -\mathcal{Q}_{F(z_{t+1}|z_{1:t}^{A_t^i}, x_{1:t+1})}(\gamma). \tag{13}$$

- If M matrix is very large then use a common $\{M(., t)\}_{t=1}^T$ for every time-step. In general, for this configuration, the acceptance rate would be *greater* than equal to γ for all particles:

$$\log M(., t) = \min\left\{-\mathcal{Q}_{F(z_{t+1}|z_{1:t}^{A_t^i}, x_{1:t+1})}(\gamma)\right\}_{i=1}^N. \tag{14}$$

Through γ, we can directly control the acceptance rate. For example, if $\gamma = 0.5$ then the acceptance rate would be around (greater than) 50% for (Eq. 13) (see Eq. (14)). Note that a similar scheme was employed in Grover et al. (2018). We update $\{\{M(i, t-1)\}_{i=1}^N\}_{t=1}^T$ dynamically once every F epochs to save time. To learn more on setting hyper-parameter M, see Liu et al. (1998); Peters et al. (2012).

4   RELATED WORK AND SPECIAL CASES

There is significant recent interest in developing more expressive variational posteriors for latent variable models. There are two basic schemes for constructing tighter bounds on the log marginal likelihood: sampling-based methods (MCMC, rejection sampling) (Salimans et al., 2015; Ruiz & Titsias, 2019; Hoffman, 2017; Grover et al., 2018) or multiple samples from VI distributions to increase the flexibility (IS, SMC) (Burda et al., 2015; Maddison et al., 2017; Lawson et al., 2018; Naesseth et al., 2015). In this work, we present a unified framework for combining these two approaches, utlizing the best of both worlds. Although applying sampling-based methods on VI is useful, the density ratio between the true posterior and the improved density is often intractable. Therefore, we cannot take advantage of variance-reducing schemes like resampling, which is crucial for sequential models. We solve this issue through *dice-enterprise*: an extension of the *Bernoulli factory*.

Recently, *Bernoulli factory* has amassed a great interest in the area of Bayesian inference (Gonçalves et al., 2017a;b; Vats et al., 2020). Although *Bernoulli factory* is theoretically valuable, its applicability is severely limited due to a high rejection rate. In this paper, we have presented an approach that combines SMC with *dice-enterprise* in a practically meaningful manner. A closely related work is Schmon et al. (2019), which also uses *Bernoulli factory* to implement unbiased resampling. However, the work is mostly focused on partially observed diffusions and likely limited to low-dimensional models (unlike our approach). Another closely related work is Kudlicka et al. (2020), which also produces an unbiased estimator for SMC-PRC; however, the approach is only applicable when the proposal is the prior distribution itself.

To provide more clarity, we will consider some special cases of VSMC-PRC bound and relate it with existing work: For the special case of $N = 1$ and $T = 1$, our method reduces to variational rejection sampling (VRS) (Grover et al., 2018). For $N, T > 1$, if we remove the PRC step, our bound reduces to FIVO (Maddison et al., 2017). Finally, if we remove both the PRC step and resampling, then our method effectively reduces to IWAE (Burda et al., 2015). Please refer to Figure (1) for more details.

5   EXPERIMENTS

In this section, we evaluate our proposed algorithm on synthetic as well as real-world datasets and compare them with relevant baselines. For the synthetic data experiment, we implement our method on a *Gaussian SSM* and compare our approach with VSMC (Naesseth et al., 2017). For the real data experiment, we train a *VRNN* (Chung et al., 2015) on the polyphonic music dataset.

5.1   GAUSSIAN STATE SPACE MODEL

In this experiment, we study the linear Gaussian state space model. Consider the model

Figure 2: (*Left*) The figures compares the bound value for VSMC-PRC with full gradient and biased gradient (equation 12) as a function of iterations. (*Left*) The Table compares the bound value for VSMC (Naesseth et al., 2017) and VSMC-PRC for 80% and 40% acceptance rate. (*Right*) We compare VSMC, VSMC-PRC (40% acceptance rate), and $\log p_\theta(x_{1:T})$ as a function of iterations.

$$z_t = Az_{t-1} + e_z,$$
$$x_t = Cz_t + e_x,$$

where $e_z, e_x \sim \mathcal{N}(0, I)$ and $z_0 = 0$. We are interested in learning a good proposal for the above model. The latent variable is denoted by z_t and the observed data by x_t. Let the dimension of z_t be d_z and dimension of x_t be d_x. The matrix A has the elements $(A)_{i,j} = \alpha^{|i-j|+1}$, for $\alpha = 0.42$. We explore different settings of d_z, d_x, and matrix C. A sparse version of C matrix measures the first d_x components of z_t, on the other hand a dense version of C is normally distributed i.e $C_{i,j} \sim \mathcal{N}(0, 1)$. We consider four different configurations for the experiment. For more details please refer to Figure (2).

The variational distribution is a multivariate Gaussian with unknown mean vector $\mu = \{\mu_d\}_{d=1}^{d_z}$ and diagonal covariance matrix $\{\log \sigma_d^2\}_{d=1}^{d_z}$. We set $N = 4$ and $T = 10$ for all the cases:

$$q(z_t|z_{t-1}) \sim \mathcal{N}\left(z_t|Az_{t-1} + \mu, \text{diag}(\sigma^2)\right).$$

The $\{\{M(i, t-1)\}_{i=1}^N\}_{t=1}^T$ matrix (see (13)) for approximate rejection sampling is updated once every 10 epochs with acceptance rate $\gamma \in \{0.8, 0.4\}$. For estimating the intractable normalization constants, we generate $K = 3$ samples. Figure (2): (*left*) compares the convergence of biased gradient vs unbiased gradients. Note that we get a much tighter bound as compared to VSMC (Naesseth et al., 2017).

5.2 VARIATIONAL RNN

VRNN (Chung et al., 2015) comprises of three core components: the observation x_t, stochastic latent state z_t, and a deterministic hidden state $h_t(z_{t-1}, x_{t-1}, h_{t-1})$, which is modeled through a RNN. For the experiments, we use a single-layer LSTM for modeling the hidden state. The conditional distributions $p_t(z_t|.)$ and $q_t(z_t|.)$ are assumed to be factorized Gaussians, parametrized by a single layer neural net. The output distribution $g_t(x_t|.)$ depends on the dataset. For a fair comparison, we use the same model setting as employed in FIVO (Maddison et al., 2017). We evaluate our model on four polyphonic music datasets: `Nottingham`, `JSB chorales`, `Musedata`, and `Piano-midi.de`.

Each observation x_t is represented as a binary vector of 88 dimensions. Therefore, we model the observation distribution $g_t(x_t|.)$ by a set of 88 factorized Bernoulli variables. We split all four datasets into the standard train, validation, and test sets. For tuning the learning rate, we use the validation

test set. For a fair comparison, we use the same learning rate and iterations for all the models. Let the dimension of hidden state (learned by single layer LSTM) be d_h and dimension of latent variable be d_z. We choose the setting $d_z = d_h = 64$ for all the data-sets except JSB. For modeling JSB, we use $d_z = d_h = 32$. For VSMC-PRC we have considered $N \in \{4, 6\}$ Further, for each N, we consider four settings $(K, \gamma) \in \{(1, 0.9), (1, 0.8), (3, 0.9), (3, 0.8)\}$. The M hyper-parameter for PRC step is learned from (14) due to large size. We have updated M value once every 50 epoches. Note that in this scenario, the acceptance rate for all particles would be *greater* than equal to γ. For more details on experiments, please refer to the appendix.

As discussed in Section (3.1), the PRC step and dice-enterprise have time complexity $\mathcal{O}(N/\gamma)$ for producing N samples (assuming average acceptance rate γ). Therefore, we consider $\lceil N\gamma^{-1} \rceil$ particles for IWAE and FIVO to ensure effectively the same number of particles, where $N \in \{4, 6\}$ and $\gamma = 0.8$. Note, however, that the acceptance rate is $\geq \gamma$, so this adjustment actually favors the other approaches more. For FIVO, we perform resampling when ESS falls below $N/2$. Table (1) summarizes the results which show whether rejecting samples provide us with any benefit or not, and as the results show, our approach, even with the aforementioned adjustment, outperforms the other approaches in terms of test log-likelihoods, while still having a similar computational cost.

Table 1: We report Test log-likelihood for models trained with FIVO, IWAE, ELBO, and VSMC-PRC. For VSMC-PRC $N = (4, 6)$ and $(K, \gamma) \in \{(1, 0.9), (1, 0.8), (3, 0.9), (3, 0.8)\}$ (results are in this order). The results for pianoroll data-sets are in nats per timestep.

N	Data	ELBO	IWAE	FIVO	N	VSMC-PRC			
	Nott	-3.87	-3.12	-3.07		**-2.96**	-2.98	-2.99	-2.96
	jsb	-8.69	-8.01	-7.51		-7.41	**-7.28**	-7.37	-7.36
5	Piano	-7.99	-7.97	-7.85	4	-7.82	-7.86	**-7.80**	-7.85
	Muse	-7.48	-7.45	-6.75		-6.61	-6.63	-6.66	**-6.58**
N	Data	ELBO	IWAE	FIVO	N	VSMC-PRC			
	Nott	-3.87	-3.87	-2.99		-2.93	-2.93	**-2.90**	-2.91
	jsb	-8.69	-8.32	-7.40		-7.29	-7.21	-7.16	**-7.14**
8	Piano	-7.99	-8.04	-7.80	6	-7.78	-7.77	-7.79	**-7.77**
	Muse	-7.48	-7.41	-6.67		-6.60	**-6.57**	-6.61	-6.60
Avg. Rank		6.87 ± 0.33	6.12 ± 0.33	4.87 ± 0.33		2.87 ± 1.05	2.62 ± 1.21	2.87 ± 1.26	$\mathbf{1.75 \pm 0.66}$

In Sec. (3.1), we discussed the effect of K and PRC rejection rate on VSMC-PRC bound. We expect a performance improvement when K and the rejection rate is increased. Although the results for VSMC-PRC's different configurations are almost the same, we still get the best average ranking for $(K = 3, \gamma = 0.8)$. Overall, for most cases, VSMC-PRC bound performs better than FIVO (Maddison et al., 2017) and IWAE (Burda et al., 2015) for a variety of configurations.

In VSMC-PRC, improvement in the bound value comes at the cost of estimating the normalization constant $Z(.)$, i.e., K. Therefore, the proposed bound uses more particles (PRC step and *dice-enterprise*) than existing approaches like FIVO and IWAE due to intractability. Table (1) signifies that rejecting samples with low importance weight is better instead of keeping a large number of particles (at least for a reasonably high acceptance rate γ). Future work aims at designing a scalable implementation for VSMC-PRC bound that consumes fewer particles.

6 CONCLUSION

We introduced VSMC-PRC, a novel bound that combines SMC and *partial* rejection sampling with VI in a synergistic manner. This results in a robust VI procedure for sequential latent variable models. Instead of using standard sampling algorithms, we have employed a partial sampling scheme suitable for high dimensional sequences. Our experimental results clearly demonstrate that VSMC-PRC outperforms existing bounds like IWAE (Burda et al., 2015) and standard particle filter bounds (Maddison et al., 2017; Naesseth et al., 2017; Le et al., 2017). The future work aims at designing a parallel implementation of dice-enterprise (Schmon et al., 2019) for faster resampling and to explore *partial* versions of powerful sampling algorithms like Hamiltonian Monte Carlo (Neal et al., 2011) instead of rejection sampling.

REFERENCES

Christophe Andrieu, Nando De Freitas, Arnaud Doucet, and Michael I Jordan. An introduction to mcmc for machine learning. *Machine learning*, 50(1-2):5–43, 2003.

Søren Asmussen, Peter W Glynn, and Hermann Thorisson. Stationarity detection in the initial transient problem. *ACM Transactions on Modeling and Computer Simulation (TOMACS)*, 2(2): 130–157, 1992.

Jean Bérard, Pierre Del Moral, Arnaud Doucet, et al. A lognormal central limit theorem for particle approximations of normalizing constants. *Electronic Journal of Probability*, 19, 2014.

David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American Statistical Association*, 112(518):859–877, 2017.

Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders. *arXiv preprint arXiv:1509.00519*, 2015.

Frédéric Cérou, Pierre Del Moral, and Arnaud Guyader. A nonasymptotic theorem for unnormalized feynman-kac particle models. In *Annales de l'IHP Probabilités et statistiques*, volume 47, pp. 629–649, 2011.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In *Advances in neural information processing systems*, pp. 2980–2988, 2015.

Arnaud Doucet and Adam M Johansen. A tutorial on particle filtering and smoothing: Fifteen years later. *Handbook of nonlinear filtering*, 12(656-704):3, 2009.

Flávio B Gonçalves, Krzysztof Łatuszyński, Gareth O Roberts, et al. Barker's algorithm for bayesian inference with intractable likelihoods. *Brazilian Journal of Probability and Statistics*, 31(4): 732–745, 2017a.

Flávio B Gonçalves, Krzysztof G Łatuszyński, and Gareth O Roberts. Exact monte carlo likelihood-based inference for jump-diffusion processes. *arXiv preprint arXiv:1707.00332*, 2017b.

Aditya Grover, Ramki Gummadi, Miguel Lazaro-Gredilla, Dale Schuurmans, and Stefano Ermon. Variational rejection sampling. *arXiv preprint arXiv:1804.01712*, 2018.

Matthew D Hoffman. Learning deep latent gaussian models with markov chain monte carlo. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1510–1519. JMLR. org, 2017.

Jan Kudlicka, Lawrence M Murray, Thomas B Schön, and Fredrik Lindsten. Particle filter with rejection control and unbiased estimator of the marginal likelihood. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5860–5864. IEEE, 2020.

Dieterich Lawson, George Tucker, Christian A Naesseth, Chris J Maddison, Ryan P Adams, and Yee Whye Teh. Twisted variational sequential monte carlo. In *Third workshop on Bayesian Deep Learning (NeurIPS)*, 2018.

Tuan Anh Le, Maximilian Igl, Tom Rainforth, Tom Jin, and Frank Wood. Auto-encoding sequential monte carlo. *arXiv preprint arXiv:1705.10306*, 2017.

Jun S Liu, Rong Chen, and Wing Hung Wong. Rejection control and sequential importance sampling. *Journal of the American Statistical Association*, 93(443):1022–1031, 1998.

Chris J Maddison, John Lawson, George Tucker, Nicolas Heess, Mohammad Norouzi, Andriy Mnih, Arnaud Doucet, and Yee Teh. Filtering variational objectives. In *Advances in Neural Information Processing Systems*, pp. 6573–6583, 2017.

Giulio Morina, Krzysztof Latuszynski, Piotr Nayar, and Alex Wendland. From the bernoulli factory to a dice enterprise via perfect sampling of markov chains. *arXiv preprint arXiv:1912.09229*, 2019.

Christian A Naesseth, Fredrik Lindsten, and Thomas B Schön. Nested sequential monte carlo methods. *arXiv preprint arXiv:1502.02536*, 2015.

Christian A Naesseth, Scott W Linderman, Rajesh Ranganath, and David M Blei. Variational sequential monte carlo. *arXiv preprint arXiv:1705.11140*, 2017.

Christian A Naesseth, Fredrik Lindsten, and Thomas B Schön. Elements of sequential monte carlo. *arXiv preprint arXiv:1903.04797*, 2019.

Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of markov chain monte carlo*, 2(11):2, 2011.

Gareth W Peters, Yanan Fan, and Scott A Sisson. On sequential monte carlo, partial rejection control and approximate bayesian computation. *Statistics and Computing*, 22(6):1209–1222, 2012.

Christian Robert and George Casella. *Monte Carlo statistical methods*. Springer Science & Business Media, 2013.

Francisco JR Ruiz and Michalis K Titsias. A contrastive divergence for combining variational inference and mcmc. *arXiv preprint arXiv:1905.04062*, 2019.

Tim Salimans, Diederik Kingma, and Max Welling. Markov chain monte carlo and variational inference: Bridging the gap. In *International Conference on Machine Learning*, pp. 1218–1226, 2015.

Sebastian M Schmon, Arnaud Doucet, and George Deligiannidis. Bernoulli race particle filters. *arXiv preprint arXiv:1903.00939*, 2019.

Dootika Vats, Flávio Gonçalves, Krzysztof Łatuszyński, and Gareth O Roberts. Efficient bernoulli factory mcmc for intractable likelihoods. *arXiv preprint arXiv:2004.07471*, 2020.

A   PROOF OF THEORETICAL RESULTS

Proof of proposition (1): Dice-enterprise produces unbiased ancestor variables. Let's evaluate the probability that Dice-enterprise would output i as the ancestor index. Assume that the algorithm terminates after r steps where $r \in \{1, 2, \ldots, \infty\}$, then the probability of output i is given as follows:

$$
\begin{aligned}
\Pr(\text{output} = i) &= \sum_{r=1}^{\infty} \Pr(\text{output} = i | \text{after } r \text{ steps}) \\
&= \frac{c_t^i Z(z_{1:t-1}^{A_{t-1}^i}, x_{1:t}, M(i, t-1))}{\sum_{m=1}^{N} c_t^m} \sum_{r=1}^{\infty} \left(\sum_{j=1}^{N} \frac{c_t^j (1 - Z(z_{1:t-1}^{A_{t-1}^j}, x_{1:t}, M(j, t-1)))}{\sum_{m=1}^{N} c_t^m} \right)^{r-1} \\
&= \frac{c_t^i Z(z_{1:t-1}^{A_{t-1}^i}, x_{1:t}, M(i, t-1))}{\sum_{j=1}^{N} c_t^j Z(z_{1:t-1}^{A_{t-1}^j}, x_{1:t}, M(j, t-1))} .
\end{aligned}
$$

It is easy to see that Λ_t is geometrically distributed with success probability given by

$$
\Pr(\text{getting output in a loop}) = \frac{\sum_{i=1}^{N} c_t^i Z(z_{1:t-1}^{A_{t-1}^i}, x_{1:t}, M(i, t-1))}{\sum_{m=1}^{N} c_t^m}
$$

Proof of proposition (2): Algorithm 1 is producing an unbiased estimator of the marginal likelihood. We will first integrate out $\delta_{1:T}^{1:N,1:K}$ from the marginal likelihood estimator.

$$
\begin{aligned}
&\mathbb{E}_{Q_{\text{VSMC-PRC}}} \left[\exp(\hat{\mathcal{L}}_{\text{VSMC-PRC}}) \right] \\
&= \sum_{A_{1:T-1}^{1:N}} \int \prod_{t=1}^{T} \frac{1}{N} \sum_{i=1}^{N} \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i}) \widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; K)}{q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) a_{\theta,\phi}(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})} \\
&\quad Q_{\text{VSMC-PRC}} \left(z_{1:T}^{1:N}, A_{1:T-1}^{1:N}, \delta_{1:T}^{1:N,1:K} \right) dz_{1:T}^{1:N} d\delta_{1:T}^{1:N,1:K} \\
&= \sum_{A_{1:T-1}^{1:N}} \int \prod_{t=1}^{T} \frac{1}{N} \sum_{i=1}^{N} \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i}) Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}{q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) a_{\theta,\phi}(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})} Q_{\text{VSMC-PRC}} \left(z_{1:T}^{1:N}, A_{1:T-1}^{1:N} \right) dz_{1:T}^{1:N} \\
&= \sum_{A_{1:T-1}^{1:N}} \int \prod_{t=1}^{T} \frac{1}{N} \sum_{i=1}^{N} \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})}{r_{\theta,\phi}(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})} Q_{\text{VSMC-PRC}} \left(z_{1:T}^{1:N}, A_{1:T-1}^{1:N} \right) dz_{1:T}^{1:N} . \quad (15)
\end{aligned}
$$

Note that $r_{\theta,\phi}(z_t^i | .)$ is the sampling density of PRC. It is easy to show that equation (15) is an unbiased estimator of the marginal likelihood $p_\theta(x_{1:T})$. For more details, please refer to (Naesseth et al., 2017; 2019). Using Jensen inequality we can easily show that VSMC-PRC bound is smaller then log marginal likelihood.

$$
\mathbb{E} \left[\hat{\mathcal{L}}_{\text{VSMC-PRC}}; K \right] = \int \sum_{t=1}^{T} \log \left[\frac{1}{N} \sum_{i=1}^{N} \frac{p_\theta(x_t, z_t^i | x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i}) \widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; K, M(i, t-1))}{q_\phi(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) a_{\theta,\phi}(z_t^i | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})} \right]
$$

$$
Q_{\text{VSMC-PRC}} \left(z_{1:T}^{1:N}, A_{1:T-1}^{1:N}, \delta_{1:T}^{1:N,1:K} \right) dz_{1:T}^{1:N} d\delta_{1:T}^{1:N,1:K} dA_{1:T-1}^{1:N} \leq \log p_\theta(x_{1:T}) . \quad (16)
$$

We will show that $\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}; K]$ is non-decreasing with K. Let's define a collection of subsets $\{\{I_{i,t}\}_{i=1}^N\}_{t=1}^T \subset \{1, 2, \ldots, K\}$ having elements $\{i_1, i_2, \ldots, i_m\}$ randomly drawn from the set $\{1, 2, \ldots, K\}$ having length $m \leq K$. We can easily show the following expectation:

$$
\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; K) = \mathbb{E}_{I_{i,t} = \{i_1, i_2, \ldots, i_m\}} \left[\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; m) \right] = \frac{1}{K} \sum_{k=1}^{K} a_{\theta,\phi}(\delta_t^{i,k} | x_{1:t}, z_{1:t-1}^{A_{t-1}^i})
$$

$$
(17)
$$

Substitute the values of above expectation in equation 16. Use Jensen's inequality i.e $\mathbb{E}[\log X] \leq \log \mathbb{E}[X]$ to complete the proof .

$$\mathbb{E}\left[\hat{\mathcal{L}}_{\text{VSMC-PRC}}; K\right]$$

$$= \mathbb{E}\left[\sum_{t=1}^{T} \log \mathbb{E}_{\{\{I_{i,t}\}_{i=1}^{N}\}_{t=1}^{T}}\left(\frac{1}{N}\sum_{i=1}^{N}\frac{p_\theta(x_t, z_t^i|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; m)}{q_\phi(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right]$$

$$\geq \mathbb{E}\left[\mathbb{E}_{\{\{I_{i,t}\}_{i=1}^{N}\}_{t=1}^{T}}\sum_{t=1}^{T} \log\left(\frac{1}{N}\sum_{i=1}^{N}\frac{p_\theta(x_t, z_t^i|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; m)}{q_\phi(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right]$$

$$\geq \mathbb{E}\left[\hat{\mathcal{L}}_{\text{VSMC-PRC}}; m\right]$$

Now we will see what happens when the limit $K \rightarrow \infty$. Using *dominated convergence theorem* we can write down the estimator as follows:

$$\lim_{K \rightarrow +\infty}\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}]$$

$$= \lim_{K \rightarrow +\infty}\mathbb{E}\left[\sum_{t=1}^{T} \log\left(\frac{1}{N}\sum_{i=1}^{N}\frac{p_\theta(x_t, z_t^i|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; K)}{q_\phi(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right]$$

$$= \mathbb{E}\left[\sum_{t=1}^{T} \log\left(\frac{1}{N}\sum_{i=1}^{N}\frac{p_\theta(x_t, z_t^i|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})\lim_{K \rightarrow +\infty}\widehat{Z}(x_{1:t}, z_{1:t-1}^{A_{t-1}^i}; K)}{q_\phi(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right]$$

$$= \mathbb{E}\left[\sum_{t=1}^{T} \log\left(\frac{1}{N}\sum_{i=1}^{N}\frac{p_\theta(x_t, z_t^i|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}{q_\phi(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})a_{\theta,\phi}(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right] \leq \log p_\theta(x_{1:T})$$

Proof of proposition (3) : We will show that PRC step refines the learned distribution.

$$KL\left(r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})||p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})\right)$$

$$= \int \log\left(\frac{r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}\right)r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})dz_t$$

$$= \int \log\left(\frac{q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})a(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})dz_t$$

$$\leq \int \log\left(\frac{q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})a(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})dz_t$$

$$\leq KL\left(q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})||p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})\right) +$$

$$\int \log\left(\frac{a(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})dz_t$$

$$\leq KL\left(q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})||p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})\right)$$

First, we will use the property of negatively correlated random variables. Note that the following two random variables

$$X = \log\left(\frac{r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}{p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})}\right) \text{ and } Y = a(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t}),$$

are negatively correlated. We know that for negatively correlated variables following identity holds $\mathbb{E}[XY] \leq \mathbb{E}[X]\mathbb{E}[Y]$. Further we have used Jensen's inequality to show that

$$\mathbb{E}[\log a(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})] \leq \log Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})$$

Case 1: $M(i, t-1) \to 0$ implies $r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) \to q(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$

In this situation all samples would be accepted. Hence, we can express the sampling distribution as:

$$r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) = q(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i}), \tag{18}$$

Case 2: $M(i, t-1) \to \infty$ implies $r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) \to p(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t})$

In this case, the acceptance probability would reduce to standard rejection sampling. Therefore, the sampling distribution would become equal to the true posterior.

$$
\begin{aligned}
r(z_t|z_{1:t-1}^{A_{t-1}^i}, x_{1:t}) &= \frac{q(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) \frac{p(z_t^i, x_t|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})}{M(i,t-1)q(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}}{\int q(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i}) \frac{p(z_t^i, x_t|x_{1:t-1}, z_{1:t-1}^{A_{t-1}^i})}{M(i,t-1)q(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})} dz_t^i} \\
&= p(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})
\end{aligned}
$$

B GRADIENT ESTIMATION

Figure 3: Convergence rate for biased gradient vs. unbiased gradient on toy Gaussian SSM. We compared g_{rep} (blue), $g_{\text{rep}} + g_{\text{PRC}}$ (orange), and unbiased gradient (green) for optimization.

In this section, we will derive the unbiased gradients for the Monte-Carlo estimate $\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}]$. Note that we can express the complete gradient into three core components (assuming $q()$ is reparametrizable):

$$
\begin{aligned}
\nabla_{\theta,\phi}\mathbb{E}[\hat{\mathcal{L}}_{\text{VSMC-PRC}}] &= g_{\text{rep}} + g_{\text{PRC}} + g_{\text{RSAMP}} \\
g_{\text{rep}} &= \mathbb{E}_{Q_{\text{VSMC-PRC}}}\left[\nabla_{\theta,\phi}\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K)\right], \\
g_{\text{PRC}} &= \mathbb{E}_{Q_{\text{VSMC-PRC}}}\left[\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K)\nabla_{\theta,\phi}\left(\sum_{i=1}^{N}\sum_{t=1}^{T}\log\frac{a(z_t^i|x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}{Z(x_{1:t}, z_{1:t-1}^{A_{t-1}^i})}\right)\right], \\
g_{\text{RSAMP}} &= \mathbb{E}_{Q_{\text{VSMC-PRC}}}\left[\hat{\mathcal{L}}_{\text{VSMC-PRC}}(\theta, \phi; x_{1:T}, K)\nabla_{\theta,\phi}\sum_{i=1}^{N}\sum_{t=1}^{T-1}A_t^i\log\alpha_t\right]
\end{aligned}
$$

Note that for both g_{PRC} and g_{RSAMP} unbiased score gradient estimates are **not available** due to intractability. Therefore, we have used Monte-Carlo samples to estimate the log density for figure (3).

C EXPERIMENTAL SETUP

For the real data experiment, we train a *VRNN* (Chung et al., 2015) on the polyphonic music dataset. Polyphonic music comprises of four datasets: : Nottingham, JSB chorales, Musedata, and Piano-midi.de. Each dataset was divided into standard train, validation, and test datset.

The validation data was used to tune the learning rate: we picked the learning rate from the following set: $\{3 \times 10^{-4}, 1 \times 10^{-4}, 3 \times 10^{-5}, 1 \times 10^{-5}\}$, instead of optimizing for each method, we picked the learning rate at which FIVO (Maddison et al., 2017) validation performance is the best. Once the learning rate is decided, we ran every method for the same number of iterations to ensure uniformity. We use a single-layer LSTM for modeling the hidden state having dimension d_h. For a length T sequence, the variational distribution and joint data likelihood are defined as follows

$$r(z_{1:T}|x_{1:T}) = \frac{\prod_{t=1}^{T} q_t(z_t|h_t(z_{t-1}, x_{t-1}, h_{t-1}), x_t) a_t(z_t|h_t(z_{t-1}, x_{t-1}, h_{t-1}), x_t)}{\prod_{t=1}^{T} Z_t(h_t(z_{t-1}, x_{t-1}, h_{t-1}), x_t)}$$

Note that $a_t(z_t|.)$ is the acceptance probability for the PRC step and $Z_t(.)$ is the intractable normalization constant. Similarly, we can write down the joint data likelihood as

$$p(z_{1:T}, x_{1:T}) = \prod_{t=1}^{T} p_t(z_t|h_t(z_{t-1}, x_{t-1}, h_{t-1}), x_t) g_t(x_t|h_t(z_{t-1}, x_{t-1}, h_{t-1}), z_t)$$

The conditional distributions $p_t(z_t|.)$ and $q_t(z_t|.)$ are assumed to be factorized Gaussians, where dimension of the latent variable z_t is d_z. Note that the conditional densities are parametrized by fully connected neural networks with a single layer having size d_h. The output distribution $g_t(x_t|.)$ is modeled by a set of 88 iid Bernoulli variables. Please see Table (2) for more details regarding implementation details. The unknown weights and biases are initialized using a Xavier initialization. For setting up the optimization we used a batch size of 4 with adam optimizer. The unknown hyperparameter M is updated once every 50 epoches through (14) to save time.

Table 2: Training parameters used for VSMC-PRC, FIVO, and IWAE.

Parameters	Datasets			
	Piano-mid	**Muse**	**jsb**	**Nott**
Optimizer	Adam	Adam	Adam	Adam
Learning Rate	0.00003	0.0001	0.00003	0.0001
Batch-size	4	4	4	4
d_h	64	64	32	64
d_z	64	64	32	64
num-iteration	50,000	1,00,000	1,00,000	1,00,000