Caption generation in Cultural Heritage: Crowdsourced Data and Tuning Multimodal Large Language Models

Abstract

Automated caption generation for paintings enables enhanced access and understanding of visual artworks. This work introduces a novel caption dataset, obtained by manual annotation of about 7500 images from the publicly available DEArt dataset for object detection and pose estimation. Unlike prior captioning datasets, our focus remains squarely on the visual scenes. The dataset is the result of a crowdsourcing initiative spanning 13 months, with volunteers adhering to explicit captioning guidelines reflecting our requirements. We aimed to provide each artwork in the dataset with five captions, created independently by volunteers to ensure diversity of interpretation and increase the robustness of the captioning model.

In addition, we explore using the crowdsourced dataset for fine-tuning Large Language Models with vision encoders (multimodal LLM) for domain-specific caption generation. The goal is to improve the performance of multimodal LLMs in the context of cultural heritage, a domain with "small data" which often struggles with the nuanced visual analysis and interpretation required for cultural objects such as paintings. The use of crowdsourced data in the domain adaptation process enables us to incorporate the collective perceptual insights of diverse annotators, resulting in an exploration of visual narratives and a reduction in hallucinations otherwise created by these large language models.

1 Introduction

Among the numerous forms of cultural heritage, visual arts hold a unique place, serving as an easily accessible window into artistic, societal and historical contexts. To offer innovative methods for engaging with and understanding visual artefacts at scale, many systems rely on rich metadata - for instance, in the form of captions or descriptions.

Having access to good captions of artworks not only facilitates broader public access to these artifacts but also fosters a deeper appreciation for their cultural significance. However, the automatic generation of captions is not without challenges. Artworks often present scenes with intricate symbolism and complex narratives, where the most important elements can be hard to identify and demand nuanced description beyond simple object recognition.

In this paper we introduce a novel dataset and showcase how it can help in the domain adaptation of state-of-art approaches such as Multimodal Large Language Models (mLLMs) (Liu et al., 2023) for the task of caption generation. The image dataset was sourced from the publicly available DEArt object detection and pose estimation dataset (Reshetnikov et al., 2022b), a curated assemblage of paintings spanning diverse European cultures, centuries and artistic movements.

The model adaptation work was motivated by the experiments we ran that used mMMLs to generate caption for cultural heritage artifacts; the results underlined some apparent shortcomings, on the one hand, content unrelated to the visual scene (i.e., mistaken identity for both objects and relationships between objects), and on the other, missing elements. Our hypothesis was that these models could effectively leverage domain knowledge from datasets like ours, to overcome some of their apparent limitations.

In an effort to train a robust model, capable of generating rich visual descriptions, we set out to gather a caption dataset that is not only accurate for the job - describing only the visual content, as recommended by our guidelines - but also diverse - 5 captions per image. The crowdsourcing campaign was hosted on the Zooniverse platform and involved volunteers from various backgrounds and expertise levels, who created detailed caption annotations for about 7500 DEArt paintings dur-

ing a year-long period. Given that a high percentage of the images are non-iconic (Berg and Berg, 2009), gathering 5 different annotations per image allows for a diversity of perspectives and interpretations, which can make the trained model more robust. Based on our crowdsourced data, we explore fine-tuning mLLM by employing parameter-efficient fine-tuning techniques(Xu et al., 2023) and we demonstrate the possibility of mitigating hallucinations in LLM-generated captions.

2 Related work

Caption generation for visual content has garnered attention across diverse domains such as video captioning, assistive technologies and social media and user-generated content. Early efforts in image captioning, such as (Vinyals et al., 2015), laid the groundwork for later advancements. While these newer approaches have shown proficiency in generic image captioning, the distinctive challenges posed by cultural heritage artworks demand specialized solutions due to several important features not present in everyday pictures. Several works have made significant contributions in the area captioning for cultural heritage, of which we briefly present those directly related to our task - visual content captioning.

(Cetinic, 2021) addresses the challenge of generating accurate and meaningful textual descriptions of artwork images. The paper highlights the complexity of describing artworks, which can include multiple levels of interpretation. The author used a large-scale dataset of artwork images annotated with concepts from the Iconclass classification system to develop a captioning model. The model was fine-tuned using a transformer-based vision-language pre-trained model. The results suggest that the model could generate meaningful captions that exhibit a stronger relevance to the visual art context than those generated by the baseline (pre-trained) model.

(Bai et al., 2021) present a framework to bring art closer to people by generating comprehensive descriptions of fine-art paintings. The authors introduce a multi-topic and knowledgeable art description framework (Bai et al., 2021), which models the generated sentences according to three artistic perspectives and enhances each description with external knowledge (from Wikipedia). The framework is validated through an exhaustive analysis, both quantitative and qualitative, as well as a comparative human evaluation.

(Stefanini et al., 2019) addresses the problem of cross-modal retrieval of images and sentences coming from the artistic domain. The authors collected and manually annotated the Artpedia dataset that contains paintings and textual sentences describing both the visual content of the paintings and other (contextual) information. They then devised a visual-textual model that jointly addresses the challenge of the retrieval of images and sentences by exploiting the visual and textual chunks.

The DEArt dataset(Reshetnikov et al., 2022a) focuses on object detection and pose estimation for 15,000 images of European artwork between the XIIth and the XVIIIth centuries. It includes 69 object classes, many of which are specific to cultural heritage, as well as 12 distinct pose annotations for human-like figures. However, the dataset does not include caption annotations. Recognizing this gap, and considering the rich variety of non-iconic images in DEArt, we decided to leverage a subset of DEArt to create a caption generation dataset.

Recent advances in the field of Large Language Models (LLMs) (OpenAI, 2023) have seen the successful integration of visual information into these models, giving rise to a new generation of mLLMs. Notable among these is LLaVA (Liu et al., 2023), which, along with other models such as Mini-GPT4 (OpenAI, 2023) and Instruct-BLIP (Dai et al., 2023), have shown impressive image captioning and question-answering capabilities.

Different from these works - with the exception of LLMs - our approach relies on crowdsourcing data. This has the advantage of training the model with a variety of interpretations of paintings, coming from volunteers with different levels of expertise in cultural heritage. Due to this, we believe that the descriptions our model generates can be both more flexible and accurate, and can thus further enrich the knowledge about cultural heritage.

Other works in metadata generation for cultural heritage exist, but they usually don't focus on the generation of visual descriptions.

3 Guidelines for caption generation

To create effective guidelines, we drew inspiration from established practices - such as the "Guidelines for image descriptions from the Cooper Hewitt museum" (Starr, 2022) - and we discussed our proposal with several cultural heritage experts. After deciding to use Zooniverse as a crowdsourcing

platform, we received expert advice from one of the platform´s shepherds.

Our guidelines emphasize the requirements of clarity, simplicity, and objectivity. We encourage annotators to start descriptions with the most crucial elements, progressing from foreground to background. We recommend avoiding assumptions, e.g., the identity of characters, events or places, assumptions about time periods (which, for instance, may bias the choice of object names), or professional jargon. The focus should always be on what is visually present in the image, avoiding implications or intentions. Named entities should be identified, but only if they are clearly recognizable or convey important information. Guidelines rules provide specific instructions for spatial orientation, using absolute positioning and limiting the use of "background/foreground" to essential details. The guidelines also advocate for concise annotations, restricting descriptions to 250 characters, while encouraging multiple sentences for clarity and simplicity. The language should be straightforward and avoid comparative constructs (e.g. larger, smallest), pronouns, and unnecessary punctuation. The annotation interface included examples to illustrate the preferred style and promote clear and informative annotations in a standardized manner.

4 Crowdsourcing process and preprocessing of the annotated data

After a thorough assessment of various platforms, which included short tests for quality of annotations, we decided to use the Zooniverse platform. Zooniverse's established reputation in supporting citizen science projects with quality metadata, the possibility of hosting caption annotation tasks, and the reality that volunteers make for better annotators (possibly due to the inherent interest in the project), were decisive factors in our decision.

The crowdsourcing campaign was initiated with the design of a user-friendly interface (UI) to facilitate efficient interaction between volunteers and the paintings. We ran the campaign in batches to try to get 4-5 good annotations per image for increasingly larger subsets of DEArt, while at the same time keeping a balance between diversity and thematic consistency.

Concretely, we included images with different styles and from different time periods, while excluding most portraits and other iconic images with limited interest from a captioning perspective (e.g.images that weren't iconographic or that had low expected variability for the descriptions). This process was iterative and involved:

1. the gradual decrease of the size of the batches to increase the motivation of the volunteers to complete the work

2. the adaptation of the image selection process to propose paintings of complexity that had lead to good captions in previous batches

The multiple captions generated for each painting by the different volunteers reflect diverse artistic interpretations and visual insights and thus help us train a more robust captioning model.

At the end of each batch annotation process, we ran a data health check; rigorous quality control mechanisms were applied to manually verify the adherence of captions to guidelines and to maintain thematic alignment. Corrections and clarifications were incorporated into our guidelines and User Interface to enhance annotation accuracy. This iterative batch approach enabled us to capitalize on the collective contributions of volunteers while preserving dataset integrity.

The total number of uploaded images was 7543. The original plan was to collect five captions per image, resulting in a total of 38539 captions. The dataset health check was based on several rules:

1. Filter out captions with fewer than two tokens.

2. Filter out captions containing specific words. One such (very specific) case is given by the images included in the guidelines. When presented with an image to annotate, some users introduced a description of a guideline image rather than the one that corresponds to the dataset image. Another (general) case was due to our campaign not allowing volunteers to skip images they didn't want to annotate, which resulted in descriptions with expressions such as "I don't see", "I don't want", "n/a", etc.

3. Eliminate annotations by users who either didn't read the guidelines properly or intentionally chose not to follow them. Some examples we identified that fall in this class are:

   • "aN oLd DrAwInG!!!!!!!!!!!!!!!!!!!!!!"
   • "bad example"
   • "MAN LOOKS MAD"

	Images	Captions per image	Captions
Our dataset	7543	**4,57**	**34535**
SemArt	**21383**	1	21383
ArtPedia	2930	3,1	9173

Table 1: Dataset evaluation metrics: Our dataset vs state of the art caption datasets in CH

- "pretty freaky"
- "looks like some commie ***** to me"

4. Maybe not unexpectedly, users seem to be remarkably consistent in providing useless, or high-quality, annotations. This provided us with yet another criteria to eliminate all captions from specific users.

Following the dataset health check, 34535 captions were retained.

Our crowdsourced dataset stands out for its richness (i.e. number of annotations per images and total annotations) and diversity (i.e. different annotator views, given by the number of annotations per image) in comparison to the datasets that are the largest and most relevant in cultural heritage, as indicated by the metrics in Table 1. While it contains fewer images than SemArt, our dataset offers an average of 4.57 captions per image. The higher caption diversity is crucial to train more nuanced models, as it reflects how a visual scene can be described differently - which increases the power of generalization. In contrast, SemArt provides only one caption per image (although of museum-expert quality), which limits the range of insights available for each artwork. Although ArtPedia offers a moderate number of captions per image (3.1 on average), its total image count is significantly lower, leading to a smaller pool of captions overall (9173).

This comparative analysis highlights the balance achieved in our dataset between the quantity of images and the variety of annotations. The emphasis on obtaining multiple captions per image enriches the dataset by incorporating a variety of descriptive styles, subjective interpretations, and visual details, thus providing a comprehensive base for fine-tuning models. The iterative process of data collection and quality checks ensures that our dataset maintains both breadth and depth, making it uniquely positioned for generating high-quality, diverse painting captions.

We will release the caption dataset and the detailed guidelines after publication.

5 Model architecture and training process

For model training and caption generation experiments, we chose an open sourced model, the LLAVA (Large Language and Vision Assistant) llava-v1.5-7b. LLAVA is a novel end-to-end large multimodal model that combines a vision encoder and an LLM for general-purpose visual and language understanding. It represents a significant advancement in the field of multimodal AI, demonstrating impressive multimodal chat capabilities - sometimes of similar quality of captions as those generated by the multimodal GPT-4 - and setting a new state-of-the-art accuracy standard for QA(Rodrigues et al., 2024).

The LLAVA pre-trained visual encoder and the LLM connect using a simple projection matrix. This setup allows the model to convert images into a word embedding space, while textual input is also transformed into the same space. The image and word tokens are then passed to a LLaMA (Touvron et al., 2023) decoder, which produces output.

Retraining or even fine-tuning LLMs typically demands extensive datasets and significant GPU hours. This process not only consumes considerable computational resources but also carries the risk of catastrophic forgetting, where the model loses the knowledge it previously acquired when too many layers of the network update their weights. To address these challenges, one of the parameter-efficient fine-tuning (PEFT) approaches (Xu et al., 2023) has been used for domain adaptation of the LLAVA model. PEFT methods are designed to adjust only a small subset of the model's parameters while keeping the majority of them fixed. This makes the fine-tuning process more efficient and less resource-intensive. By focusing on a limited number of parameters, PEFT techniques significantly reduce the computational load and the amount of data required, enabling quicker and more cost-effective adaptation to new domains. This can lead to a more agile and scalable deployment of LLMs for specialized application domains, ensuring that the model remains both accurate and efficient.

LoRA (Low-Rank Adaptation of Large Language Models) (Hu et al., 2021) is one of the PEFT techniques to train LLMs on specific tasks or domains. This technique introduces trainable rank decomposition matrices into each layer of transformer architecture and also reduces the number of trainable parameters for downstream tasks while keeping the pre-trained weights frozen.

To further optimize resource usage and fine-tuning efficiency, we employed QLoRA (Quantized Low-Rank Adaptation) instead of traditional LoRA. QLoRA was the most optimal choice because it reduces the memory footprint even further by leveraging 4-bit quantization, allowing for the fine-tuning of LLMs on consumer-grade hardware without sacrificing model performance. The use of QLoRA enables efficient memory utilization, allowing us to fine-tune larger models with fewer hardware resources, significantly lowering both the cost and time required for adaptation (Han et al., 2024).

Our QLoRA configuration is characterized by several key parameters such as the rank and the alpha value, which contribute to better convergence and scalability. Additionally, the use of mixed-precision training with bfloat16 (BF16) and TensorFlow32 (TF32) enables faster computation while minimizing memory requirements. To ensure effective utilization of resources, the data loading process is optimized with lazy preprocessing and efficient parallelism (Rasley et al., 2020) using multiple dataloader workers. The LLAVA architecture we implement utilizes Vicuna-7B as LLM (Zheng et al., 2023) and the ViT vision transformer (Dosovitskiy et al., 2021) from OpenAI's CLIP model (Dai et al., 2023), which incorporates advanced features like multimodal projection layers and gradient checkpointing (See Figure1).

6 Evaluation

We employed multiple evaluation metrics to assess the quality of the image captions generated by the baseline (LLAVA) and fine-tuned models, including Rouge1 (R1), Rouge2 (R2), RougeL (RL), and RougeLsum (RLsum), which measure n-gram overlap between generated and reference captions. Additionally, we included Meteor, Cider, and the ClipScore, providing a more comprehensive view of the captioning performance. Rouge metrics are particularly useful for evaluating fluency and structure through n-gram and subsequence overlaps, while Meteor and Cider provide insights into the semantic accuracy; ClipScore assesses the alignment between the generated captions and the visual content.

Table 2 presents the results of our evaluation, which compares the baseline LLAVA model and its fine-tuned version using QLoRA - for our dataset and the SemArt dataset. Fine-tuning on our dataset led to significant improvements over the baseline; for instance, the Rouge1 score increased from 0.31 to 0.43, and Rouge2 rose from 0.09 to 0.18, indicating a stronger overlap with reference captions. RougeL and RougeLsum similarly improved from 0.21 to 0.31 and 0.21 to 0.32, respectively, reflecting enhanced structural consistency and coherence of generated captions.

The fine-tuned LLAVA model also demonstrated notable gains in Meteor and Cider scores, with Cider improving from 0.28 to 0.48, suggesting a better match with the overall reference data. Additionally, ClipScore increased from 0.31 to 0.42, indicating a higher alignment between captions and the visual content of the images.

However, the results on the SemArt dataset were more modest. Fine-tuning improved Rouge1 from 0.19 to 0.21 and Rouge2 from 0.027 to 0.11, while the gains in RougeL and RougeLsum were similarly limited (0.14 to 0.16). The lower ClipScore of 0.315 for the fine-tuned LLAVA on SemArt, compared to 0.42 on our dataset, indicates that the captions generated for SemArt images were less contextually aligned with the visual content. This disparity suggests that the model's ability to generate highly relevant captions is influenced by the characteristics of the dataset used for training, with our dataset providing a better foundation for capturing the nuanced relationship between text and imagery.

Overall, the evaluation demonstrates that fine-tuning using QLoRA can significantly improve the performance of mMMLs when training for specific domains, especially when these domains do not (or cannot) have extensive datasets. Moreover, the richer and more diverse the manual annotations are, the higher the quality of the generated captions, as reflected by the lower ClipScore.

7 Limitations and discussion

Given the widespread excitement surrounding LLM capabilities and despite the improvements our fine-tuned model brings, we questioned whether

Figure 1: Architecture of LLAVA model with QLoRA layer

	R1*	R2*	RL*	RLsum*	Meteor	Cider	ClipScore
Baseline LLAVA (our dataset)	0.31	0.09	0.21	0.21	0.25	0.28	0.31
Fine-tuned LLAVA (our dataset)	0.43	0.18	0.31	0.32	0.31	0.48	0.42
Baseline LLAVA (SemArt)	0.19	0.027	0.14	0.14	0.12	0.19	0.21
Fine-tuned LLAVA (SemArt)	0.21	0.11	0.16	0.16	0.19	0.24	0.315

Table 2: Evaluation metrics, fine-tuned model using QLoRA, * R = Rouge

these quantitative results also reflect a better quality of the generated captions from a human viewpoint. We thus embarked on an empirical exploration to assess LLAVA's performance in visual art description.

Our experiments with the baseline LLAVA model and the improvements that the fine-tuned LLAVA model achieved point to limitations in terms of the effectiveness of general-purpose mLLMs in the absence of domain-specific adaptations.

1. Hallucinations: One of the most notable limitation we observed was the baseline model's tendency to hallucinate (invent details not present in the actual artwork). For example, in the description of "Palas Athena in Fight against Centaurs" (Figure 4), the baseline LLAVA model generated incorrect elements, such as a dog and a bird, which do not exist in the painting. Similarly, for "Jupiter and Bellerophon" (Figure 2), it inaccurately describes a scene involving angels when the painting actually features a man and a winged horse. This may also be interpreted to some extent as a case of mistaken identity in the case of the winged horse, whose wings made the baseline model believe it is an angel. On the other hand, the man on the left does not have wings, and the baseline model hallucinates angel instead. Finally, in "Annunciation" (Figure 3), the basic model hallucinates a baby and a potted plant; this last could can also be interpreted as mistaken identity since we assume the wings are interpreted as greenery. Both models hallucinate a man in white.

2. Incompleteness and mistaken identity: In several instances, the model produced captions that lacked crucial details. For example, in "Annunciation" (Figure 3), the baseline model's description mentions a woman and a child, omitting - or making the mistake - that the second figure is an angel and he is holding a flower; the baseline model does not see the wings, nor the flower. Both aspects are part of a significant religious interaction that is central to the meaning of the painting. Likewise, in Figure 4, the centaurs are interpreted by the baseline model as horses; in Figure 2, the model does not identify a horse at all.

The baseline model also mistakenly identifies crucial actions. In Figure 2, the man *falls* rather than *being lifted*, while in Figure 4, the woman is *killing* a beast rather than *standing* on it. Both these actions are critical for understanding the true meaning embedded in the artpiece, and their symbolic

Figure 2: Generated captions for "Jupiter and Bellerophon" by unknown artist.

Baseline LLAVA: *The image depicts a painting of a man being lifted into the air by two angels. The man is positioned in the center of the scene, with one angel on his left side and the other on his right side. The angels are holding the man, and he appears to be flying through the sky. In the background, there are two people standing, possibly observing the scene or waiting for their turn to be lifted. The painting captures a moment of wonder and awe, as the man is lifted above the earth by the divine beings.*

Fine-tuned LLAVA: *The image features a painting of a man and a winged horse flying through the sky. The man falls from the horse, which is positioned towards the right side of the scene. The painting captures the dynamic and dramatic moment of the man and the horse soaring through the air. In the background, there is another man visible, on the left side of the painting. The scene appears to be set in a mountainous landscape, with a mountain visible in the background. The overall atmosphere of the painting is one of adventure and freedom.*

Figure 3: Generated captions for "Annunciation" by Domenico Ghirlandaio.

Baseline LLAVA: *The image depicts a scene from a painting, featuring a woman and a child. The woman is kneeling down, holding a baby, while the child is standing nearby. The woman appears to be dressed in a yellow gown, and the child is wearing a white gown. The painting is set in a room with a window in the background. In the room, there is a chair positioned towards the right side of the scene, and a potted plant is located on the left side. Additionally, there is a bowl placed on the floor, close to the woman and the child.*

Fine-tuned LLAVA: *The image features a painting of a woman sitting in front of an angel, who is kneeling and holding a white flower. They appear to be engaged in a conversation or a religious ceremony. The woman is wearing a yellow dress, while the man is dressed in white. In the background, there is a window with a curtain, which adds to the atmosphere of the scene. The painting is likely a religious or historical depiction, as it captures the interaction between the two individuals.*

meaning.

These limitations suggest that foundation models like LLAVA struggle with both accuracy and completeness in complex visual art contexts. Developing a domain-specific dataset and fine-tuning mLLM models like LLAVA for art interpretation is a more reliable approach. This adaptation could address hallucinations, improve caption completeness, and ensure a better understanding of iconographic details in visual artworks.

8 Conclusion

In conclusion, this work introduces a novel dataset for caption generation of paintings sourced from a publicly available dataset. Our caption dataset was created through a year-long crowdsourcing campaign on Zooniverse, with volunteers adhering to explicit captioning guidelines. We have shown that this dataset is a valuable resource for research and development in the field of automated caption generation for paintings and other forms of visual art. It can be used to fine-tune mLLMs - such as LLAVA - for domain adaptation, resulting in significant improvements in the quality of generated captions compared to the baseline models. The LoRA approach to fine-tuning mLLMs appears to be particularly effective in enhancing the model's ability

Figure 4: Generated captions for "Palas Athena in Fight against Centaurs" by Milan Thomka Mitrovský.

Baseline LLAVA: *The image features a woman dressed in a warrior costume, standing on a horse and holding a shield. She appears to be engaged in a battle or a mock fight. The horse is positioned in the center of the scene, with the woman standing on its back. There are two other people in the background, one on the left side and the other on the right side of the image. The scene also includes a dog, which is located on the left side of the image, and a bird, which is flying in the sky above the woman and the horse.*

Fine-tuned LLAVA: *The image depicts a painting of a woman killing a centaur. The woman is wearing a helmet and is holding a shield, while the man appears to be holding a sword. The scene takes place in a lush green field, with a body of water in the background. There are several other centaurs in the painting, some of whom are closer to the water and others further away. The overall atmosphere of the painting suggests a battle or a moment of intense action.*

to generate captions that are more coherent, contextually aligned, and better capture the nuances of artistic interpretation. We believe that this research will contribute to further advancements in automated caption generation for paintings and other forms of visual art, ultimately enhancing accessibility and understanding of these cultural artifacts.

9 Ethical and broader impact of the work

Participation in the annotation campaign (on the public platform Zenodo) was on voluntary basis. Annotators were informed about the purpose, benefits, risks, and funding behind the study before participating.

The dataset we used as a source of images (DEArt) already has a Creative Commons license and is openly available.

We pseudoanonymized the collected data based on identifiers. We did not collect and personally identifiable data beyond the user name on the Zenodo platform.

We recognize no additional potential for harm in our work beyond those already incurred by LLMs (e.g. bias), and our approach fine-tunes one such mMML model to make it more accurate for the cultural heritage domain.

AI assistants ware not used in this work.

Upon publication, we will be releasing the dataset and the guidelines publicly for research uses. Using the dataset is classified as a "not high-risk" application according to the EU Artificial Intelligence Act.

To the best of our knowledge, we are not aware of any other possible ethical consequences of the proposed dataset and fine-tuned model.

References

Zechen Bai, Yuta Nakashima, and Noa Garcia. 2021. Explain me the painting: Multi-topic knowledgeable art description generation. *Preprint*, arXiv:2109.05743.

Tamara L. Berg and Alexander C. Berg. 2009. Finding iconic images. *2009 IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, pages 1–8.

Eva Cetinic. 2021. Towards generating and evaluating iconographic image captions of artworks. *Journal of Imaging*, 7:123.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. 2023. Instructblip: Towards general-purpose vision-language models with instruction tuning. *Preprint*, arXiv:2305.06500.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. 2021. An image is worth 16x16 words: Transformers for image recognition at scale. *Preprint*, arXiv:2010.11929.

Zeyu Han, Chao Gao, Jinyang Liu, Jeff Zhang, and Sai Qian Zhang. 2024. Parameter-efficient fine-tuning for large models: A comprehensive survey. *Preprint*, arXiv:2403.14608.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *Preprint*, arXiv:2106.09685.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. *Preprint*, arXiv:2304.08485.

OpenAI. 2023. Gpt-4v(ision) system card.

Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. 2020. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '20, page 3505–3506, New York, NY, USA. Association for Computing Machinery.

Artem Reshetnikov, Maria-Cristina Marinescu, and Joaquim More Lopez. 2022a. Deart: Dataset of european art. *Preprint*, arXiv:2211.01226.

Artem Reshetnikov, Sergio Mendoza, and Maria-Cristina Marinescu. 2022b. Deart: Dataset of european art.

Luiz Rodrigues, Filipe Dwan Pereira, Luciano Cabral, Dragan Gašević, Geber Ramalho, and Rafael Ferreira Mello. 2024. Assessing the quality of automatic-generated short answers using gpt-4. *Computers and Education: Artificial Intelligence*, 7:100248.

Ruth Starr. 2022. Cooper hewitt guidelines for image description.

Matteo Stefanini, Marcella Cornia, Lorenzo Baraldi, Massimiliano Corsini, and Rita Cucchiara. 2019. Artpedia: A new visual-semantic dataset with visual and contextual sentences in the artistic domain.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. Llama: Open and efficient foundation language models. *Preprint*, arXiv:2302.13971.

Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. 2015. Show and tell: A neural image caption generator. *Preprint*, arXiv:1411.4555.

Lingling Xu, Haoran Xie, Si-Zhao Joe Qin, Xiaohui Tao, and Fu Lee Wang. 2023. Parameter-efficient fine-tuning methods for pretrained language models: A critical review and assessment. *Preprint*, arXiv:2312.12148.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Preprint*, arXiv:2306.05685.