Trusted Aggregation (TAG): Backdoor Defense in Federated Learning

Abstract

Federated learning is a framework for training machine learning models from clients with multiple local data sets without access to the data in its aggregate. Instead, a shared model is jointly learned through an interactive process between a centralized server that combines locally learned model gradients or weights from the client. However, the lack of data transparency naturally raises concerns about model security. Recently, several state-of-the-art backdoor attacks have been proposed, which achieve high attack success rates while simultaneously being difficult to detect, leading to compromised federated learning models. In this paper, motivated by differences in the logits of models trained with and without the presence of backdoor attacks, we propose a defense method that can prevent backdoor attacks from influencing the model while maintaining the accuracy of the original classification task. TAG leverages a small validation data set to estimate the most considerable change a benign client's local training can make to the shared model, which can be used to filter clients from updating the shared model. Experimental results on multiple data sets show that TAG defends against backdoor attacks even when 40 percent of user submissions to update the shared model are malicious.

1 Introduction

Federated learning (FL) is a promising solution for constructing machine learning models from numerous local data sources that cannot be directly exchanged or aggregated (Yang et al., 2019; Kairouz et al., 2021). These limitations become particularly crucial in contexts where data privacy and security are prominent concerns (Li et al., 2020), with healthcare being a prime example. Additionally, FL has garnered significant attention from companies that opt to offload computing workloads onto local devices. Furthermore, FL allows for non-independent and non-identically distributed local data sets. Hence, a shared and robust global model is often unattainable without collaborative learning. Within this FL framework, local entities, called clients, contribute their locally acquired model gradients or weights to be intelligently combined by some centralized entity, the server, resulting in a shared machine-learning model.

However, concerns have arisen regarding the potential vulnerabilities inherent in FL. The lack of control or knowledge concerning the local training procedures opens doors for malicious users to craft updates that compromise the global model for all participating clients. One insidious threat is the backdoor attack, in which malicious actors seek to manipulate the global model into associating specific input data manipulations (known as triggers) with particular outcomes (the target). While various methods have been proposed to detect triggers and defend against backdoor attacks (Kurita et al., 2020; Qi et al., 2020; Li et al., 2021), these approaches often rely on having access to the training data itself, which is not feasible within the FL paradigm. Moreover, the limited information available to detect and prevent such malicious intent within FL makes backdoor attacks easier to execute and more challenging to identify.

In this article, we shed light on an approach to detect and mitigate backdoor attacks in FL. Our primary observation centers on the substantial divergence between the logits of classification models created by malicious users and those produced by benign users. This discrepancy is most pronounced for the class label targeted by the backdoor attack. Leveraging this stark contrast, we propose a method that employs a small,

clean data set to generate a backdoor-free, locally trained model, which we term the "trusted user". We then compare other user models against this trusted user model on the same clean data to identify models with unusual outputs. Suspicious users are removed from participating in the update of the global model.

To identify unusual outputs, we propose comparing user and trusted models by the distributional difference between their outputs and those of the most recent global model to identify malicious updates. We use the trusted user to estimate the most considerable distributional difference a benign user's local training could produce and eliminate other returning user models that exceed this distance cutoff. We show that robust aggregation is insufficient for defense against backdoor attacks and that our framework is more effective than similar proposed backdoor defenses. In FL, there is the potential for multiple attackers to simultaneously attempt to attack the shared model with either the same or different malicious objectives. Our proposed method demonstrates its effectiveness against backdoor attacks with multiple attackers, even in scenarios where 40% of clients are part of an attack. Remarkably, our approach consistently outperforms existing methods and remains robust even when backdoor attacks persist throughout the entirety of federated training. Importantly, our method does not compromise the global model's performance on clean data, ensuring that the accuracy of the original classification task remains intact. We provide experimental evidence across multiple data sets to underscore the consistency and reliability of our results.

The rest of the paper is organized as follows: Section 2 briefly summarizes related work from federated learning, backdoor attack, and defense. We introduce the proposed framework for excluding malicious users from participating in the update of the global model in Section 3. Finally, Section 4 gives empirical evidence for performance improvements over other considered defense options.

2 Related Work

Federated Learning Federated learning (FL) is an emerging machine learning paradigm with great success in many fields (Bonawitz et al., 2019; Hard et al., 2018; Ryffel et al., 2018). At its core, FL operates through iterative rounds of model improvement where in each round, the global model is distributed to participating users, with a subset of these users selected to update a local copy of the model. These chosen users train their models on their respective local data sets, and to safeguard data privacy, the resulting models are shared back and aggregated to construct a new global model.

Backdoor Attack Recently, the FL setting has become a target for various backdoor attacks. In Xie et al. (2020), the authors highlighted how the multi-user nature of FL could be exploited to create more potent and persistent backdoor attacks. By distributing the backdoor trigger across a few malicious users, they effectively induced the desired behavior in the global model at higher rates and for more extended periods after the attack had ceased. Another notable contribution in this domain is the projection method known as Neurotoxin (Zhang et al., 2022). This approach projects the attacker's updates onto dimensions with small absolute weight vector values, claiming that benign users update such weights less frequently, leading to longer-lasting successful attacks. Our research rigorously evaluates the effectiveness of our proposed method against both the aforementioned attacks.

Defense While FedAvg (McMahan et al., 2017) remains the most prevalent aggregation method in FL, the field has since introduced robust aggregation rules. In particular, Median and Trim-mean, two such methods, were proposed in Yin et al. (2018). The Median operation computes the coordinate-wise median among the weight vectors of selected users, while the Trim-mean procedure aggregates weight vectors by calculating the coordinate-wise mean, after excluding the largest and smallest k elements in that coordinate. Our experiments show that these robust aggregation methods are not alone sufficient against backdoor attacks.

Defending against backdoor attacks in FL has been a relatively unexplored area in the literature. Many previously proposed defenses, such as Neural Cleanse (Wang et al., 2019), are infeasible for FL, as they jeopardize data privacy. While prior work (Shejwalkar et al., 2022) suggested that norm clipping (Sun et al., 2019) could be effective against backdoor attacks in FL, it has been shown to be vulnerable to the Neurotoxin attack. Other works pertaining to federated learning include DeepSight (Rieger et al., 2022), Baffle (Andreina et al., 2020), and FLAME (Nguyen et al., 2021). We focus on comparison with FLTrust (Cao et al., 2020), as

it (similar to our proposal) requires an additional small, clean data set. Although the original FLTrust paper showcased its effectiveness against adaptive attacks involving around half of the clients being malicious, our research demonstrates its failure even against the most basic backdoor attacks considered in our experiments. Thus, our work addresses a critical gap in the field of federated learning and contributes to the enhancement of similar defense methodologies.

3 Trusted Aggregation (TAG)

This section begins with an observation in Section 3.1 that model performance on clean data changes depending on whether the model was backdoor attacked. Next, Section 3.2 introduces our framework for excluding users from updating the global model depending on their local model's performance on some clean data. Finally, Section 3.3 provides a smoothing procedure to strengthen our defense further.

3.1 Motivation

Figure 1: Output distributions (kernel density estimation based) conditional on the class label for a backdoor model (black) and a clean model (red). Note the obvious difference between the distributions of the backdoor and clean models for the target label class.

Our proposed method, Trusted Aggregation (TAG), is motivated by observing that the distributions of model logits generated by malicious users, significantly differ from those produced by benign users. We use the term logits to refer to the output of a classification model before the softmax operation is used to produce probabilities. Note that each element of the logit vector corresponds to precisely one class, establishing a specific node-class association unique to the logits.

In targeted backdoor attacks, malicious users aim to create an additional learned association between a particular manipulation of input data (the trigger) and a specific class label (the target). This effectively transforms the task into a $(m + 1)$-way classification problem. We intuitively believe this difference in the model's task can be exploited to identify models trained with a backdoor attack. In Figure 1, we demonstrate that this learned association can lead to a distributional change in the logits on non-attacked inputs, particularly for the target class. Our insight suggests that models containing a backdoor may produce distinct distributions of logits when provided with clean data. Consequently, if we have a model that is believed to be trained without a backdoor attack, we can potentially identify whether another candidate model exhibits signs of a backdoor attack by comparing their logits on the same clean data.

3.2 Detection Framework

Our detection framework assumes the presence of a small clean validation data set, which serves as the gatekeeper for updates to the global model. This data set can either belong to a trusted existing user or be collected by the centralized server and treated as a new user. We will refer to this trustworthy validation data set as the "trusted user".

Our detection method leverages the trusted user to evaluate incoming model weights and determine whether each contribution can participate in the global model update process. The core idea is to detect user models with unusually distributed outputs using a clean data set from the trusted user. Our method can be easily

extended when multiple trustworthy data sets or users are available. Refer to Figure 2 for an overview of our proposed detection framework.

Figure 2: Diagram representation of our trusted aggregation detection framework. A distance score ($\mathbf{v}^{(j)}$) is calculated for each selected user's model ($U^{(j)}$) based on the distributional distances between the user's model and the global model. A threshold (τ) is computed based on the distributional distances between the trusted user's model ($U^{(T)}$) and the global model (G). If the distance score of a user is greater than the threshold, it will be excluded from the aggregation. See more details in Section 3.2.

In each communication round, the trusted user performs the following steps to establish a threshold for detecting malicious users:

1. The validation data is utilized to update a copy of the global model concurrently with the local training of other users.

2. When models are returned by the subset of users selected to potentially participate in the shared model update, logits are generated and stored for the validation data. These logits are denoted as $\mathbf{o}^{(G)}$, $\mathbf{o}^{(T)}$, and $\mathbf{o}^{(j)}$ for the global, validation, and j-th user models, respectively.

3. Subsequently, we compute the distance between each user from the previous global model. Specifically, for each class c, we calculate the class-conditional distributional distance $\mathcal{D}$ between empirical distributions for the previous global model's logits and the user's logits using some distributional difference function.

4. Given m total classes, the process generates a distance vector $\mathbf{v}$ for each user, including the trusted user. These distance vectors then dictate which users can participate in the model. See Algorithm 1 for additional details.

We aim to estimate the maximum change a non-malicious user can introduce in communication round r, defined below in Equation 1:

$$\tau_r = \max_j \left(\max_c \left[\mathcal{D} \left(\mathbf{o}_c^{(j)}, \mathbf{o}_c^{(G)} \right) \right] \right) \tag{1}$$

Users with distance values surpassing this threshold should be excluded from the update process. For estimation of τ_r, we compute $\max_c \left[\mathcal{D} \left(\mathbf{o}_c^{(T)}, \mathbf{o}_c^{(G)} \right) \right]$ for our trusted user. Note τ_r involves the maximum of all benign users. Since the validated user is non-malicious, their distance vector serves as a good representation

---

Algorithm 1 Trusted Aggregation (TAG)

Let $\mathcal{S}$ denote the subset of users selected to update the global model for a given round r.

Input: Global model G, user models $\left\{U^{(j)}\right\}_{j \in \mathcal{S}}$, trusted model $U^{(T)}$ and data $\mathbf{X}^{(T)}$, and scaling coefficient $\theta \geq 1$.

1: Generate logits $\mathbf{o}^{(G)} = G(\mathbf{X}^{(T)})$, $\mathbf{o}^{(j)} = U^{(j)}(\mathbf{X}^{(T)})$ for $j \in \mathcal{S}$, and $\mathbf{o}^{(T)} = U^{(T)}(\mathbf{X}^{(T)})$
2: **for** Each class $c \in [1, \ldots, m]$ **do**
3:     Compute distributional distances between each user and the global model $\mathbf{v}_c^{(j)} = \mathcal{D}\left(\mathbf{o}_c^{(j)}, \mathbf{o}_c^{(G)}\right)$ for $j \in \mathcal{S}$ and $\mathbf{v}_c^{(T)} = \mathcal{D}\left(\mathbf{o}_c^{(T)}, \mathbf{o}_c^{(G)}\right)$
4: **end for**
5: Compute threshold for communication round r
    $\hat{\tau}_r = \theta \times \max_c\left[\mathbf{v}_c^{(T)}\right]$
6: Exclude suspicious users
    $\mathcal{S}_r = \left\{j \in \mathcal{S} \mid \max_c\left[\mathbf{v}_c^{(j)}\right] \leq \hat{\tau}_r\right\} \subseteq \mathcal{S}$
7: **return** Update G with $\left\{U^{(j)}\right\}_{j \in \mathcal{S}_r}$

---

of other non-malicious users. However, we scale by $\theta \geq 1$ since the true maximum will be at least as large as our observed trusted user. A user with a maximum distance smaller than the threshold $\hat{\tau}_r = \theta \times \max_c\left[\mathcal{D}\left(\mathbf{o}_c^{(T)}, \mathbf{o}_c^{(G)}\right)\right]$ is considered a benign user, while a user with a maximum distance larger than or equal to the threshold will be removed. However, this naive threshold is very unstable, and a lucky malicious user can get past it in some rounds due to the instability. To overcome this limitation, we propose a specific smoothing procedure in Section 3.3

If the distributions of $\mathbf{v}_j = \mathcal{D}\left(\mathbf{o}_c^{(j)}, \mathbf{o}_c^{(G)}\right)$ can be assumed, the ranges of plausible θ's can be better determined.

Proposition 1. *If $v_c \sim Uniform(0, b_c)$ for all classes $c \in [1, \ldots, m]$ and for all benign users, then $\mathbb{E}[v] \leq b \leq E[2v]$ where $v = \max_c[v_c]$ and $b = \max_c[b_c]$.*

For example, when $\mathbf{v}_c^{(j)}$ are each uniformly distributed for all users, Proposition 1 suggests that, on average, $\hat{\tau} = \theta \times \max_c\left[\mathbf{v}_c^{(T)}\right]$, should equal $\tau = b$ for some $\theta \in [0, 1]$. However, we acknowledge that it may be unreasonable to assume that class conditional distances are Uniform as many training hyper-parameters and even model choice will impact the distance distributions. We present these results to assist in understanding reasonable magnitudes for θ as many distributions may not require large scaling values.

We recommend choosing θ based on the setting's prevalence of backdoor attacks (potentially unknown) and the cost of a successful attack to interested parties. Relatively large values for θ will allow more users to update the global model but increase the risk of a successful backdoor attack. Conversely, using our threshold $\hat{\tau}_r$ without scaling would help to prevent stronger backdoor attacks, but with the potential loss of denying benign users from updating the global model. The goal is to choose the smallest θ that allows benign users to create a robust shared machine learning model sufficiently.

3.3 Global-Min Mean Smoothing (GMMS)

Stabilizing the threshold value is essential for maintaining the security of our method. While a straightforward approach to achieving this stability is through a smoothing technique, such as a moving average, it comes with its own set of challenges. In the early communication rounds, the naive threshold value experiences rapid fluctuations as the model learns quickly to relate inputs and output classes. We need to understand when past behavior of $\hat{\tau}_r$ is relevant while ensuring stability throughout the process.

Conventional smoothing methods, which rely on several previous values, can lead to an overly high threshold in the initial rounds. This, in turn, could create vulnerabilities that attackers could exploit. To address this

concern, we introduce our Global-Min Mean Smoothing approach, which combines the benefits of both a stable threshold and a rapidly adjusting threshold, early in training.

The foundation of our approach lies in using the lowest observed value of $\hat{\tau}_r$ (Global Min) as the starting point for the (Mean) smoothing window. Here, $\hat{\tau}_r$ represents the naive threshold estimation up to round n. The smoothed threshold $\tilde{\tau}_n$ for round n is determined using Algorithm 2.

Algorithm 2 Global-Min Mean Smoothing (GMMS)

Input: Threshold history $\hat{\tau}_1, \ldots, \hat{\tau}_r$

1: Identify the start of the smoothing window

$s = \arg\min_{i=2,\ldots,r} = \hat{\tau}_i$

2: **return** Smooth estimate $\tilde{\tau}_r = \dfrac{1}{r-s+1} \sum_{i=s}^{r} \hat{\tau}_i$

In scenarios where $\hat{\tau}$ exhibits rapid initial decreases, we should observe new global minimums, which serve as a re-set point for the threshold smoothing. This allows us to maintain the decreasing behavior of the original threshold sequence. However, when the original sequence is not experiencing a decline, previous values are utilized to smooth the threshold, effectively preventing lucky malicious users from evading a volatile threshold.

Figure 3 visually compares our Global-Min Mean Smoothing with the base (naive) threshold and various conventional smoothing methods. It is evident that our Global Min-Mean Smoothing not only captures the early behavior of the naive threshold but also significantly improves stability, rendering it a robust choice for safeguarding the global model against backdoor attacks.

Figure 3: Comparison of the global min-mean smoothing with the naive threshold and various smoothing methods.

4 Experiments

In this section, we present a series of experiments that offer valuable insights into the effectiveness of Trusted Aggregation (TAG) as a defense mechanism against strong backdoor attacks in federated learning. In Section 4.2, we observe that robust aggregation is insufficient to prevent backdoor attacks and that TAG outperforms the backdoor defense FLTrust, which also requires additional clean data. Additionally, Section 4.4 shows that the TAG is robust to changes in the data distribution of clients or the trusted data set.

4.1 Setting

To ensure the reproducibility of our experiments, this section provides a comprehensive breakdown of the parameters used throughout our study, as summarized in Table 1. When used in conjunction with the code available on our GitHub repository [1], this detailed information serves readers seeking to recreate our results and further investigate our work.

Model Our experiments primarily employ the ResNet18 model (He et al., 2016), a well-established classi-fier. Additionally, to showcase the robustness and generalizability of our approach, we reproduce the main results using the VGG16 model (Simonyan & Zisserman, 2014) in Section B. Importantly, we assume that all users, including potential malicious actors, have complete control over various aspects of local training. However, for simplicity, we use two sets of hyper-parameters for benign and malicious users. The malicious

---

[1]Our repo will later be made public.

	Hyperparameter	Variable Name	CIFAR10	CIFAR100	STL10
Federated Learning	Users	n_users	100	100	20
	Local Data Size	n_user_data	500	500	400
	User Subset Proportion	p_report	.1	.1	.5
Data Augmentation	Padding		4	4	12
	Random Horizontal Flip	NA	.5	.5	.5
	Random Crop Size		32	32	96
All Users	Batch Size	n_batch	64	64	128
	Weight Decay	wd	5e-4	5e-4	5e-4
Benign Users	Local Epochs	n_epochs	10	10	10
	Learning Rate	lr	.01	.01	.01
Malicious Users	Local Epochs	n_epochs_pois	20 (15)	15	25 (15)
	Learning Rate	lr_pois	.01	.01	.005 (.01)
Data Poisoning	Poisoning Proportion	p_pois	.1	.1	.1
	Stamp Pixel Height	row_size	4	4	24
	Stamp Pixel Width	col_size	4	4	24
Backdoor Defense	TAG Scaling (θ)	d_scale	2	2	1.1
	Trim Mean	$beta$	.2	.2	.2

Table 1: Default arguments for all experiments unless otherwise specified. For all experiments, alternative values for β did not seem to prevent the backdoor attacks. Any values modified for Neurotoxin attacks are shown in parentheses.

users will poison (add their backdoor trigger) and change the training label to the target class for a given proportion of their local data. They intend their model to associate the trigger with the target class and transfer such behavior to future global models.

Attack and Defense To assess the effectiveness of TAG, we operate in a scenario where the backdoor attack is particularly potent. We mandate that the *same* set of malicious users are included *every* round in the subset of selected users responsible for updating the global model. Moreover, all attacks start in the first communication round. This approach circumvents the randomness associated with selecting users, allowing malicious users to influence the global model repeatedly. Furthermore, the guaranteed benign validation user is excluded from participating in any global model updates. These decisions are made to showcase TAG's ability to thwart even backdoor attacks against the global model in the strongest attack settings.

In our experiments, we compare the performance of the TAG method with robust aggregation methods, including Median and Trim-mean (Yin et al., 2018), as well as the backdoor defense FLTrust (Cao et al., 2020). Regarding TAG, in our experiments, we exclusively use the Kolmogorov-Smirnov (KS) distance between distributions due to its ease of computation for estimated cumulative distribution functions. However, we acknowledge that other distance functions, and even divergences, may be suitable. We assess these methods against two state-of-the-art backdoor attacks in federated learning: Neurotoxin (Zhang et al., 2022) and Distributed Backdoor Attacks (DBA) (Xie et al., 2020). To evaluate the strength of the considered defenses, we vary the proportion of malicious attackers from 10%, 20%, and 40% of the selected users.

Data The experiments are conducted on three distinct datasets: CIFAR10 and CIFAR100 (Krizhevsky & Hinton, 2009), and STL10 (Coates et al., 2011). A specific adjustment worth noting pertains to our use of STL10, where we have inverted the conventional train and test data splits. Since we are using only labeled data, we swap train and test to have the larger of the two for training purposes. User datasets are constructed by random sampling from the training data splits. These samples are generated using a Dirichlet distribution that determines the class frequency. In our experiments, we ensure the creation of balanced local data sets by applying a scaling factor, $\alpha = 10000$, to a vector consisting of ones, with the dimensionality equal to the total number of classes. When investigating imbalanced user (and trusted) data sets, we modify α to a value

of 1 to create the desired imbalance. Further details, including experiment specifics and hyperparameters, can be found in Table 1.

We split the test set into two parts, to evaluate the global model. The first half is used to determine classification accuracy. In the second half, we introduce the backdoor trigger to the images, remove any observations related to the target class, and report the attack success rate. The attack success rate measures the extent to which the backdoor attack has compromised the model by determining the proportion of the poisoned half predicted as the target class. An effective defense method will exhibit a low attack success rate while maintaining a high classification accuracy, indicating that the attack is unsuccessful and the defense does not negatively impact classification performance.

4.2 Comparison of Defense Methods Against Backdoor Attacks

To thoroughly evaluate the performance of TAG, we explore settings where 10%, 20%, and 40% of the returning user models are malicious in each communication round. Figure 4 provides a visual representation of the performance of various methods against backdoor attacks on three different data sets. We assess the success of each method in terms of model classification accuracy and attack success rate. For our primary results, we use scaling coefficients (θ) of 2, 2, and 1 for the CIFAR10, CIFAR100, and STL10 data sets, respectively. Our findings reveal that TAG effectively neutralizes the backdoor attack in each case, without significantly compromising the classification accuracy of the original task. Conversely, other methods, such as coordinate-wise Median, Trim-mean, and FLTrust, fail to thwart backdoor attacks, with or without Neurotoxin, at all considered strength levels. FLTrust, while capable of delaying attack success in some settings, ultimately falls short in preventing backdoor attacks. We assert that the direction taken by FLTrust is not pertinent to strong backdoor attacks, which aim to preserve benign behavior on non-manipulated inputs. In contrast, TAG consistently thwarts backdoor attacks across the initial rounds, safeguarding the model's integrity. In summary, our method significantly outperforms existing defense techniques for federated learning.

Our supplemental experiment, detailed in Section A, supports that TAG does not hinder performance for the original classification task, even in the absence of backdoor attacks. This comparison with FedAvg highlights the minimal impact on the classification task's performance when using TAG as a defense mechanism. Furthermore, Section B demonstrates that our primary results, which were obtained using ResNet18, are not model-dependent by reproducing them using VGG16. This emphasizes that TAG enhances model security without negatively affecting the classification task, even without an attack. In conclusion, Trusted Aggregation (TAG) is a crucial advancement in bolstering model security within the federated learning framework.

4.3 Necessity Of Threshold Smoothing

We revisit the last attack on the STL10 data set to highlight the importance of our proposed global-min mean smoothing technique. Recall that our smoothing is intended to improve the stability of our estimated threshold while preserving its behavior in the initial rounds, not conserved by other smoothing techniques. Suppose we repeat the backdoor attack where 40% of the user subset is malicious each iteration and omit the global-min mean smoothing. In that case, our method can no longer prevent the backdoor attack with Neurotoxin projection on STL10. Please see Figure 5. We do remark that this was the only attack in our main results that became successful without including smoothing. Regardless, without smoothing, we conclude that malicious users may be able to get past a less stable cutoff.

4.4 Extending Results To Imbalanced User Data Sets

In federated learning, user data sets may not adhere to the assumption of being independent and identically distributed. This section explores TAG's effectiveness in the context of imbalanced user data sets, specifically focusing on the CIFAR10 data set. We investigate this scenario under the most potent attack setting, where 40% of user submissions are malicious in each round. In Section C, we include our analysis on the weaker attack settings, revealing that TAG remains highly effective in defending against backdoor attacks, even

Figure 4: Model performance under DBA without and with Neurotoxin (NT) with 10%, 20%, and 40% malicious users on several data sets. Column names indicate attack setting while rows correspond to data sets. The proposed method, TAG, performs well in defending against backdoor attacks as the attack success rates are low. Furthermore, it does not generally affect the model's classification performance on clean data. Most importantly, the other methods do not work well against any backdoor attacks

Figure 5: Model performance under DBA without and with Neurotoxin (NT) with 40% malicious users on STL-10 without using global-min mean smoothing. Column names indicate attack setting. TAG fails to defend against the backdoor attack with Neurotoxin without the improved stability of our estimate from our proposed smoothing technique.

without fine-tuning the scaling coefficient (θ). These results are consistent across imbalanced user data sets, irrespective of whether the trusted data set is imbalanced.

In these experiments, we employ the m-dimensional Dirichlet distribution with parameter $\alpha\mathbf{1}_m$ to determine the proportion for each class label in the data set, introducing an imbalance. The choice of θ plays a critical role in the performance of TAG. With appropriate tuning, TAG can successfully neutralize 40% of malicious backdoor attacks. See Figure 6. However, a trade-off exists between backdoor attack prevention and original classification task performance. Smaller scaling values may reduce original classification accuracy in the early communication rounds, as fewer users contribute to model updates. Nonetheless, as the global model converges, TAG's round-to-round accuracy stabilizes and matches or surpasses the baseline methods. In conclusion, TAG can mitigate backdoor attacks on imbalanced data without compromising the original task's accuracy, underscoring its utility in a wide range of federated learning applications.

Figure 6: Model performance under DBA without and with Neurotoxin (NT) backdoor attacks with 40% malicious users on CIFAR-10 under imbalanced local data sets with tuned θ. Column names indicate whether the trusted user (Trusted) is also imbalanced. The proposed method, TAG, performs well against backdoor attacks, even when the local user data sets are imbalanced. Again, the other defense methods do not prevent any backdoor attack under imbalanced data.

When obtaining a balanced, trusted data set is challenging, TAG still exhibits its efficacy. Even when the trusted user's data set is imbalanced, and 40% of user updates are malicious, TAG effectively prevents backdoor attacks. These experiments reaffirm TAG's ability to serve as a potent defense mechanism, regardless of the balanced representation within the trusted data set. TAG remains a powerful tool for backdoor defense, even when obtaining a balanced trusted data set proves difficult. Furthermore, Section C illustrates that significantly reducing the size of the trusted data set relative to other users also does not impact the success of TAG as a defense method. Even when FLTrust operates with a full-sized, representative trusted user data set, it is outperformed by TAG. These findings underscore the robustness and versatility of TAG in handling backdoor attacks in federated learning, making it a valuable addition to the security toolkit.

5   Limitations

While Trusted Aggregation (TAG) demonstrates substantial success as a defense mechanism against backdoor attacks in federated learning, several limitations must be considered:

Extreme Non-IID Distribution   Our experiments do include non-independent and non-identically distributed (non-IID) data sets. However, more extreme cases of non-IID data sets remain unexplored. For instance, we do not test TAG in scenarios where each user possesses the entirety of only a few of the total classes. In such cases, the assumption of learning a single shared model for all users, which is the primary objective of this work, may not be reasonable.

Limited Application Scope   While our framework is conceptually extendable to various machine learning models, such as regression and natural language processing (NLP), our experimental results are confined to standard classification computer vision models and databases. Future work may be needed to adapt our method and demonstrate its effectiveness in other applications.

Figure 7: Comparison of TAG under adaptive attack with baseline defense methods not under adaptive attack for various attack settings on CIFAR10. Adaptive attacks are successful against TAG and are a limitation of our proposed defense. However, even under adaptive attack, TAG exhibits lower attack success rates at termination than baseline defenses, not under adaptive attack.

Adaptive Attacks We do not claim that TAG can successfully defend against adaptive attacks. Adaptive attacks occur when malicious attackers are aware that our defense is in use, and they strive to return a model with output distributions similar to a benign model while still exhibiting backdoor behavior. This can be achieved by creating two copies of the global model: one trained on original, unmodified local data to produce a benign model (copy A) and the other (copy B) backdoor attacked with the poisoned data set. The attacker enforces similarity between the outputs of these two copies using techniques like L2 regularization as shown in Equation 2

$$\mathcal{L}\left(x, y\right) = \mathcal{L}\left(B(x), y\right) + \frac{\mu}{2}||B(x) - A(x)||_2^2 \tag{2}$$

Regardless, TAG outperforms other considered defense methods even under adaptive attack. See Figure 7. However, the effectiveness of TAG diminishes when faced with strong adaptive attacks.

In summary, while TAG offers a valuable defense mechanism for backdoor attacks in federated learning, there are scenarios and attack types where its efficacy may be compromised. These limitations should guide further research in the field of federated learning security.

6 Conclusion

In this study, we introduced Trusted Aggregation (TAG), a robust defense mechanism against backdoor attacks in the federated learning framework. Our extensive experimentation and analysis have led us to several key conclusions:

Defense Efficacy TAG has proven to be a highly effective defense method, showcasing its ability to thwart state-of-the-art backdoor attacks in challenging settings. While existing defense techniques falter even under mild attack conditions, TAG consistently prevails against powerful adversaries.

Heterogeneous Data TAG's adaptability and resilience are evident when dealing with federated learning scenarios where users have heterogeneous and imbalanced data. Importantly, it accomplishes this without sacrificing classification accuracy for the original task, a testament to its versatility and broad applicability. Furthermore, our method's performance remains stable regardless of the size or distribution of the trusted data it relies on.

Compatibility TAG can be seamlessly integrated with other filtering methods or modifications to the aggregation process, enhancing its compatibility with a wide range of defense strategies. This flexibility empowers federated learning systems to adopt a multi-layered approach to security, further safeguarding against adversarial threats.

In summary, TAG stands as a pivotal advancement in the realm of model security for federated learning. It raises the bar for similar defenses against backdoor attacks with adaptability, robustness, and potential as part of a holistic defense strategy. As the field of federated learning continues to evolve, TAG represents a valuable tool for maintaining model integrity and trust in collaborative machine-learning environments.

References

Sebastien Andreina, Giorgia Azzurra Marson, Helen Möllering, and Ghassan Karame. Baffle: Backdoor detection via feedback-based federated learning, 2020. URL `https://arxiv.org/abs/2011.02167`.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečný, Stefano Mazzocchi, Brendan McMahan, et al. Towards federated learning at scale: System design. *Proceedings of Machine Learning and Systems*, 1:374–388, 2019.

Xiaoyu Cao, Minghong Fang, Jia Liu, and Neil Zhenqiang Gong. Fltrust: Byzantine-robust federated learning via trust bootstrapping, 2020. URL `https://arxiv.org/abs/2012.13995`.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223, 2011.

Andrew Hard, Kanishka Rao, Rajiv Mathews, Swaroop Ramaswamy, Françoise Beaufays, Sean Augenstein, Hubert Eichner, Chloé Kiddon, and Daniel Ramage. Federated learning for mobile keyboard prediction. *arXiv preprint arXiv:1811.03604*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1–2):1–210, 2021.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Keita Kurita, Paul Michel, and Graham Neubig. Weight poisoning attacks on pretrained models. pp. 2793–2806, July 2020. doi: 10.18653/v1/2020.acl-main.249. URL `https://aclanthology.org/2020.acl-main.249`.

Li Li, Yuxi Fan, Mike Tse, and Kuo-Yi Lin. A review of applications in federated learning. *Computers & Industrial Engineering*, 149:106854, 2020. ISSN 0360-8352. doi: https://doi.org/10.1016/j.cie.2020.106854. URL `https://www.sciencedirect.com/science/article/pii/S0360835220305532`.

Linyang Li, Demin Song, Xiaonan Li, Jiehang Zeng, Ruotian Ma, and Xipeng Qiu. Backdoor attacks on pre-trained models by layerwise weight poisoning. pp. 3023–3032, November 2021. doi: 10.18653/v1/2021.emnlp-main.241. URL `https://aclanthology.org/2021.emnlp-main.241`.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Thien Duc Nguyen, Phillip Rieger, Huili Chen, Hossein Yalame, Helen Möllering, Hossein Fereidooni, Samuel Marchal, Markus Miettinen, Azalia Mirhoseini, Shaza Zeitouni, Farinaz Koushanfar, Ahmad-Reza Sadeghi, and Thomas Schneider. Flame: Taming backdoors in federated learning, 2021. URL `https://arxiv.org/abs/2101.02281`.

Fanchao Qi, Yangyi Chen, Mukai Li, Yuan Yao, Zhiyuan Liu, and Maosong Sun. Onion: A simple and effective defense against textual backdoor attacks. *arXiv preprint arXiv:2011.10369*, 2020.

Phillip Rieger, Thien Duc Nguyen, Markus Miettinen, and Ahmad-Reza Sadeghi. DeepSight: Mitigating backdoor attacks in federated learning through deep model inspection. In *Proceedings 2022 Network and Distributed System Security Symposium.* Internet Society, 2022. doi: 10.14722/ndss.2022.23156. URL `https://doi.org/10.14722%2Fndss.2022.23156`.

Theo Ryffel, Andrew Trask, Morten Dahl, Bobby Wagner, Jason Mancuso, Daniel Rueckert, and Jonathan Passerat-Palmbach. A generic framework for privacy preserving deep learning. *arXiv preprint arXiv:1811.04017*, 2018.

Virat Shejwalkar, Amir Houmansadr, Peter Kairouz, and Daniel Ramage. Back to the drawing board: A critical evaluation of poisoning attacks on production federated learning. In *2022 IEEE Symposium on Security and Privacy (SP)*, pp. 1354–1371. IEEE, 2022.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2014. URL `https://arxiv.org/abs/1409.1556`.

Ziteng Sun, Peter Kairouz, Ananda Theertha Suresh, and H Brendan McMahan. Can you really backdoor federated learning? *arXiv preprint arXiv:1911.07963*, 2019.

Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. pp. 707–723, 05 2019. doi: 10.1109/SP.2019.00031.

Chulin Xie, Keli Huang, Pin-Yu Chen, and Bo Li. Dba: Distributed backdoor attacks against federated learning. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rkgyS0VFvr`.

Qiang Yang, Yang Liu, Tianjian Chen, and Yongxin Tong. Federated machine learning: Concept and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 10(2):1–19, 2019.

Dong Yin, Yudong Chen, Ramchandran Kannan, and Peter Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 5650–5659. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/yin18a.html`.

Zhengming Zhang, Ashwinee Panda, Linyue Song, Yaoqing Yang, Michael Mahoney, Prateek Mittal, Ramchandran Kannan, and Joseph Gonzalez. Neurotoxin: Durable backdoors in federated learning. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 26429–26446. PMLR, 17–23 Jul 2022.

Appendix

A   TAG Classification Accuracy Without Attackers

A successful backdoor defense can prevent attackers while best preserving the model's performance on the original task. The model ability for the original task must also be maintained in the absence of an attack. In addition to successfully preventing attacks when present, we observe in Figure 8 that our defense does not hinder the classification accuracy of the original task on STL10 compared to the FedAvg procedure. This supports the overall usefulness of our proposed method as the shared model will have improved security with our defense without cost if attacks do not threaten the system.

Figure 8: Model classification accuracy on STL10 in the absence of backdoor attacks without (*left*) and with (*right*) TAG defense.

B   Model Generalizability

In this section, we demonstrate that our results are not architecture dependent by repeating our main experiment results on CIFAR10 for another off-the-shelf image classification model. The following results are obtained using VGG16 with batch normalization, originally proposed in Simonyan & Zisserman (2014). In this experiment, Trim Mean is parameterized by $\beta = 0.1$. However, other values for β did not impact defense.

Recall that we attempt to choose the smallest scaling coefficient θ such that the global model obtains desirable classification accuracy. For CIFAR10, $\theta = 2$ is successful for the ResNet18 architecture both for preventing backdoor attacks and for good classification accuracy for the original task. However, VGG required $\theta = 2.5$ to train a sufficient global model under Neurotoxin attacks. We observe that the choice of θ may depend on many hyperparameters of various parts of the federated learning procedure. In all attack settings, as presented in our main results, Section 4.2, our proposed defense TAG is the only method successful in preventing backdoor attacks. We again note that the successful defense of TAG is not associated with a meaningful change in global model performance on the original classification task. We conclude that TAG can be an effective backdoor defense for federated learning for various model choices.

C   Extending Results To Imbalanced User Data Sets (Continued)

In this subsection, we provide additional figures that complement Section 4.4, to assist in understanding the effectiveness of backdoor attacks when local user data sets exhibit imbalanced distributions. We would expect with imbalanced data, more variety in the change a user can make to the output distributions. Intuitively, our defense should be less effective as malicious behavior should become more difficulty to differentiate from

Figure 9: VGG model performance under DBA without and with Neurotoxin (NT) with 10% malicious users on CIFAR-10. Column names indicate attack setting. Results are the same as when using ResNet18. TAG is the only method to prevent backdoor attacks, as shown by low attack success rates, while maintaining desirable classification accuracy.

Figure 10: VGG model performance with 20% malicious users. See above for further details.

Figure 11: VGG model performance with 40% malicious users. See above for further details.

benign. This section's results help us understand how different backdoor defense is under other local user data distributions, TAG scaling coeficients, and the validation data distribution and size.

Figure 12 and Figure 13 show that even without tuning TAG's scaling coefficient θ, our proposed defense is effective for imbalanced user data regardless of whether the trusted user has imbalanced data as well. Note that we are using $\theta = 2$ as obtained from tuning our defense method on balanced local user data sets for CIFAR10. Similar to other experimentation results, TAG is the only method to prevent our backdoor attacks without changing model performance for the original classification task.

Figure 12: Model performance under DBA without and with Neurotoxin (NT) backdoor attacks with 10% malicious users under imbalanced local data sets without tuned θ. Column names indicate whether the trusted user (Trusted) is imbalanced as well. The proposed method, TAG, performs well in defending against backdoor attacks, even when the local user data sets are imbalanced. Again, the other defense methods do not prevent any backdoor attack under imbalanced data.

Figure 13: Model performance under DBA without and with Neurotoxin (NT) backdoor attacks with 20% malicious users under imbalanced local data sets without tuned θ. See above for further details.

Figure 14: Model performance under DBA without and with Neurotoxin (NT) backdoor attacks with 40% malicious users under imbalanced local data sets without tuned θ. See above for further details.

Consistently TAG scaling is robust to changes under weaker attacks but needs application-specific tuning to offer its best backdoor defense. If θ is not modified from the previous experiments, all but one considered backdoor attacks are successful at 40% prevalence, see Figure 14. However, in Section 4.4, we observe that

with proper tuning of θ, even with imbalanced user data, TAG can prevent the powerful attack where 40% of returning user updates are malicious. TAG is a good choice for a defense method regardless of the data distribution of its users.

D Size of Trusted Data Set

Additionally, we want to determine whether our method depends on the size of the trusted data set. Hence we revisit the most substantial attack setting for the CIFAR10 data set but only allow the validation user to have a data set that is 20% of the size of the other local users. Note that for this experiment, all users have balanced and representative data. This experiment is most applicable to the case where the centralized server must collect data, especially for problems where the data is expensive. Here the validation set is now only allowed 100 images, yet TAG prevents the backdoor attack and can achieve improved accuracy compared to the baseline robust aggregation methods. Hence, we additionally conclude we do not need validation data of the same quantity as other local users to discriminate between benign and malicious returning models.

Figure 15: Model performance under DBA and Neurotoxin backdoor attacks with 40% malicious users on CIFAR10 where the validation data set is 20% the size of the local users. Still, the proposed method TAG performs well, and the other three aggregation methods do not work well in preventing any backdoor attack.

E Proof of Proposition 1

Proof. Let v_c denote the distribution of distances between logits produced for class c on a given data set by the previous global model and the locally updated copy of a benign user. Assume that each element has the Uniform distribution, $v_c \sim \text{Uniform}(0, b_c)$, from zero to some class-specific constant, b_c, for all benign users.

Define $v = \max_c [v_c]$ and $j = \arg\max_c [b_c]$.

$$v_j \leq v \Rightarrow \mathbb{E}[v_j] \leq \mathbb{E}[v]$$
$$\Rightarrow \frac{b_j}{2} \leq \mathbb{E}[v]$$
$$\Rightarrow b_j \leq 2\mathbb{E}[v]$$

$$v \leq b_j \Rightarrow \mathbb{E}[v] \leq \mathbb{E}[b_j]$$
$$\Rightarrow \mathbb{E}[v] \leq b_j$$

Therefore $\mathbb{E}[v] \leq b_j \leq 2\mathbb{E}[v]$. Moreover $\theta \times \mathbb{E}[v] = b_j$ for some $\theta \in [0,1]$. $\square$