Fair Bayes-Optimal Classifiers Under Predictive Parity

Abstract

Increasing concerns about disparate effects of AI have motivated a great deal of
work on fair machine learning. Existing works mainly focus on independence
and separation-based measures (e.g., demographic parity, equality of opportunity,
equalized odds), while sufficiency-based measures such as predictive parity are
much less studied. This paper considers predictive parity, which requires the
same probability of success given a positive prediction, among different protected
groups. We prove that, if the overall performances of different groups vary only
moderately, all fair Bayes-optimal classifiers under predictive parity are group-wise
thresholding rules. Perhaps surprisingly, this may not hold if group performance
levels vary widely; in which case we find that predictive parity among protected
groups may lead to within-group unfairness. We then propose an algorithm we call
FairBayes-DPP, aiming to ensure predictive parity when our condition is satisfied.
FairBayes-DPP is an adaptive thresholding algorithm that aims to achieve predictive
parity, while also seeking to maximize test accuracy. We provide supporting
experiments conducted on synthetic and empirical data.

1 Introduction

Due to an increasing ability to handle massive data with extraordinary model accuracy, machine
learning (ML) algorithms have achieved remarkable success in many applications, such as computer
vision [43, 45, 23, 46] and natural language processing [44, 48, 12, 54]. However, empirical studies
have also revealed that ML algorithms may incorporate bias from the training data into model
predictions. Due to historical biases, vulnerable groups are often under-represented in available data
[26, 59, 47]. As a consequence, without fairness considerations, ML algorithms can be systematically
biased against certain groups defined by protected attributes such as race and gender.

As algorithmic decision-making systems are now widely integrated in high-stakes decision- making
processes, such as in healthcare [21] and criminal prediction [26], fair machine learning has grown
rapidly over the last few years into a key area of trustworthy AI. A main task in fair machine learning
is to design efficient algorithms satisfying fairness constraints with a small sacrifice in model accuracy.
This field has made substantial progress in recent years, as many effective approaches have been
proposed to mitigate algorithmic bias [56, 32, 3, 51, 4, 9, 34, 10, 24, 5, 57].

An important fundamental benchmark for fair classification is provided by fair Bayes-optimal
classifiers, which maximize accuracy subject to fairness [35, 57]. A key class of classifiers is
group-wise thresholding rules (GWTRs) over the feature-conditional probabilities of the target label,
for each protected group (e.g., probability of repaying a loan given income). Intuitively, being
a GWTR is a minimal requirement for within-group fairness: the most qualified individuals are
selected in every group. [8, 35, 7, 1, 42, 57] have studied fair Bayes-optimal classifiers under various
fairness constraints and proved that, for many fairness metrics, the optimal fair classifiers are GWTRs.
Moreover, the associated thresholds can be learned efficiently [35, 57].

Current literature on Bayes-optimality focuses mainly on the independence- and separation-based fairness measures (e.g., demographic parity, equality of opportunity, equalized odds; see Section 2.1 for definitions and a review). However, sufficiency-based measures such as predictive parity are less commonly considered, possibly due to the complexity of their constraints. Sufficiency-based measures are often applied to assess recidivism prediction instruments [19, 13, 6]. [30] show that a particular sufficiency-based measure, group calibration, is implicitly favored by unconstrained optimization: calibration error is bounded by the excess risk over the unconstrained Bayes-optimal classifier. For selective classification, [29] find that sufficiency-based representation learning leads to fairness. Despite these findings, little is known about (1) what are the optimal fair classifiers under sufficiency-based measures and (2) how to learn them. In this paper, we aim to answer these two questions. We consider predictive parity, which requires that the positive predictive value (probability of a successful outcome given a positive prediction) be similar among protected groups. In credit lending, for example, predictive parity requires that, for individuals who receive the loans, the repayment rates in different protected groups are the same.

We study fair Bayes-optimal classifiers under predictive parity. Perhaps surprisingly, our theoretical results reveal that the optimal fair classifiers may or may not be a GWTR, depending on the data distribution. We identify a sufficient condition under which all fair Bayes-optimal classifier are GWTRs. Without this condition, we show that fair Bayes-optimal classifiers may not be a GWTR when the minority group is more qualified than the majority group. In these cases, predictive parity may have limitations as a fairness measure, as it can lead to within-group unfairness for the minority group. Our findings are a reminder that the improper use of fairness measures may result in severe unintended consequences. Careful analysis before applying fairness measures is necessary.

We then develop an algorithm, FairBayes-DPP, aiming for predictive parity. Our method is a two-stage plug-in method. In the first step, we use standard learning algorithms to estimate group-wise conditional probabilities of the labels. In the second step, we first check our sufficient condition. If the sufficient condition holds, we apply a plug-in method for estimating the optimal thresholds under fairness for each protected group.

We summarize our contributions as follows.

- We show that Bayes-optimal classifiers satisfying predictive parity may or may not be group-wise thresholding rules (GWTRs), depending on the data distribution.

- We identify a sufficient condition under which all fair Bayes-optimal classifiers are GWTRs. However, when the sufficient condition is not satisfied, the fair Bayes-optimal classifier may lead to within-group unfairness for the minority group.

- We propose the FairBayes-DPP algorithm for binary fair classification. The proposed FairBayes-DPP is computationally efficient, showing a solid performance in our experiments.

2 Related Literature

2.1 Fairness Measures

Various fairness metrics have been proposed to measure aspects of disparity in ML. Group fairness [2, 15, 22] targets statistical parity across protected groups, while individual fairness [25, 28, 40] aims to provide nondiscriminatory predictions for similar individuals. In general, group fairness measures can be categorized into three categories.

The first group consists of independence-based measures, which require independence between predictions and protected attributes; this includes demographic parity [27, 56] and conditional statistical parity [8, 1]. In credit lending, independence means that the proportion of approved candidates is the same across different protected groups. However, as discussed in [22], independence-based measures have limitations; and applying them often leads to a substantial loss of accuracy.

The second group consists of separation-based measures, which require conditional independence between predictions and protected attributes, given label information. Typical examples in this group are equality of opportunity [22, 58] and equalized odds [22, 55]. In credit lending, separation-based measures require, that the individuals who will pay back (or default on) their loan have an equal probability of getting the loan, despite their race or gender. Compared to independence-based measures, separation-based measures take label information into account, allowing for perfect

predictions that equal the label. However, these measures are hard to validate in certain applications as the label information is often unknown for some groups. For example, the repayment status is missing for individuals whose loan application is declined.

As a result, measuring predictive bias is more widely applicable. This leads to the third class, sufficiency-based measures [38, 6, 30], where the label is required to be conditionally independent of the protected attributes, given the prediction. In credit lending, this requires that among the approved applications, the proportion of individuals who pay back the loan is equal across different groups. Unlike independence- and separation-based measures that are well studied with solid theoretical benchmarks and efficient algorithms, sufficiency-based measures are less commonly investigated. A possible reason is that conditioning on the prediction leads to a complex constraint, which is thus challenging to study and enforce algorithmically.

2.2 Algorithms Aimed at Fairness

Literature on algorithms for fairness has grown explosively over the past decade. Existing algorithms for fairness can be categorized broadly into three categories. The first category is pre-processing algorithms aiming to remove biases from the training data. Examples include transformations [17, 33, 3, 24], fair representation learning [56, 32, 34, 10] and fair data generation [52, 41, 53, 39]. The second group is in-processing algorithms, which handle fairness constraints during the training process. Two common strategies are penalized optimization [20, 37, 9, 5] and adversarial training [58, 49, 51, 4]. The former incorporates fairness measures as a regularization term into the optimization objective and the later tries to minimize the predictive ability of the model with respect to the protected attribute.

The third group is post-processing algorithms, aiming to remove disparities from the model output. The most common post-processing algorithm is the thresholding method [18, 35, 1, 42, 57], adjusting thresholds for every protected group to achieve fairness. In this paper, we propose a post-processing algorithm, FairBayes-DPP, to estimate the fair Bayes-optimal classifier under predictive parity.

3 Problem Formulation and Notations

In this paper, we consider classification problems where two types of feature are observed: the usual feature $X \in \mathcal{X}$, and the protected feature $A \in \mathcal{A}$. For example, in loan applications, X may refer to common features such as education level and income, and A may correspond to the race or gender of a candidate. As multiclass protected attributes are often encountered in practice, we allow $\mathcal{A}$ to have any number $|\mathcal{A}| \geq 1$ of classes, and let $\mathcal{A} = \{1, 2, ..., |\mathcal{A}|\}$. We denote by Y the ground truth label. In credit lending, Y may correspond to the status of repayment or defaulting on a loan. The output $\hat{Y}$ of the classifier aims to predict Y based on observed features. We consider randomized classifiers defined as follows:

Definition 3.1 (Randomized classifier). *A randomized classifier is a measurable function[1] f : $\mathcal{X} \times \mathcal{A} \to [0, 1]$, indicating the probability of predicting $\hat{Y} = 1$ when observing $X = x$ and $A = a$. We denote by $\hat{Y}_f = \hat{Y}_f(x, a)$ the prediction induced by the classifier f.*

Group-wise thresholding rules (GWT rules/classifiers or GWTRs) over conditional probabilities are of special importance. Consider an appropriate dominating sigma-finite measure μ on $\mathcal{X}$ (such as the Lebesgue measure for measurable subsets of $\mathbb{R}^d$, $d \geq 1$, or the uniform measure for finite sets), and suppose that for all $a \in \mathcal{A}$ and $y \in \mathcal{Y}$, the features X have a conditional distribution $P_{X|a,y}$ given $A = a, Y = y$ with a density $dP_{X|a,y}$ with respect to μ. For all[2] $x \in \mathcal{X}$ and $a \in \mathcal{A}$, let $\eta_a(x) = P(Y = 1 | X = x, A = a)$.

Definition 3.2 (GWT classifier). *A classifier f is a GWTR if there are constants t_a, $a \in \mathcal{A}$, and functions $\tau_a : \mathcal{X} \to [0, 1]$, $a \in \mathcal{A}$, such that for all $x \in \mathcal{X}$ and $a \in \mathcal{A}$*

$$f(x, a) = I(\eta_a(x) > t_a) + \tau_a(x)I(\eta_a(x) = t_a), \tag{1}$$

---

[1]We assume that, whenever needed, the sets considered are endowed with appropriate sigma-algebras, and all functions considered are measurable with respect to the appropriate sigma-algebras.

[2]To be precise, this conditional density is defined for μ-almost every $x \in \mathcal{X}$; however for simplicity we say for all $x \in \mathcal{X}$. We use this convention without further mentioning through the paper.

where $I(\cdot)$ is the indicator function.

Clearly, GWTRs choose individuals with the highest conditional probability in each group. This property is a minimal requirement for within-group fairness. For example, a GWT recruitment tool ensures that the most qualified candidates are approved in every protected group.

We consider predictive parity, which aims to ensure the same positive predictive value among protected groups:

Definition 3.3 (Predictive Parity). *A classifier f satisfies predictive parity if for all $a \in \mathcal{A}$,*

$$P(Y = 1|\widehat{Y}_f = 1, A = a) = P(Y = 1|\widehat{Y}_f = 1).$$

We follow [5, 57] to use the difference between positive predictive values to measure the degree of unfairness, defining the Difference in Predictive Parities (DPP) of a classifier f as

$$\text{DPP}(f) = \sum_{a \in \mathcal{A}} |P(Y = 1|\widehat{Y}_f = 1, A = a) - P(Y = 1|\widehat{Y}_f = 1)|.$$

4 Fair Bayes-optimal Classifiers under Predictive Parity

Since predictive parity is commonly considered under the scenarios where false positives are particularly harmful [29], we study cost-sensitive classification. For a cost parameter $c \in [0, 1]^3$, the cost-sensitive 0-1 risk of the classifier f is defined as

$$R_c(f) = c \cdot P(\hat{Y}_f = 1, Y = 0) + (1 - c) \cdot P(\hat{Y}_f = 0, Y = 1).$$

An unconstrained Bayes-optimal classifier for the cost-sensitive risk is any minimizer $f^\star \in \text{argmin}_f R_c(f)$. A classical result is that all Bayes-optimal classifiers have the form $f^\star(x, a) = I(\eta_a(x) > c) + \tau I(\eta_a(x) = c)$, where $\tau \in [0, 1]$ is arbitrary [16, 35]. Taking predictive parity into account, a fair Bayes-optimal classifier is any minimizer of the cost-sensitive risk among fair classifiers:

$$f^\star_{PPV} \in \underset{f:\text{DPP}(f)=0}{\text{argmin}} \ R_c(f). \tag{2}$$

4.1 GWT Fair Bayes-Optimal Classifiers under Predictive Parity

We first identify a sufficient condition under which all fair Bayes-optimal classifier under predictive parity are GWTRs.

Condition 4.1 (Sufficient condition for Bayes-optimal classifiers to be GWTRs).

$$\min_{a \in \mathcal{A}} P(Y = 1| \eta_a(X) \geq c, A = a) \geq \max_{a \in \mathcal{A}} P(Y = 1|A = a).$$

The sufficient condition 4.1 requires that the minimal group-wise positive predictive value $P(Y = 1| \eta_a(X) \geq c, A = a)$ of the unconstrained Bayes-optimal classifier is lower bounded by the maximal proportion of positive labels $P(Y = 1|A = a)$ among groups. In other words, the performances of different groups vary only moderately: the average performance of the most qualified class of each group—the points with x such that $\eta_a(x) \geq c$—should be better than the overall performance $P(Y = 1|A = a)$ of any of the other groups. Condition 4.1 holds if $P(Y = 1|A = a) \leq c$ for all $a \in \mathcal{A}$, because $P(Y = 1| \eta_a(X) \geq c, A = a) \geq c$.

These conditions are applicable in settings where c is large, such as in credit lending where false positives are more harmful than false negatives, or if $p_{Y|a}, a \in \mathcal{A}$ are small, such as in job recruitment or school admissions where the number of slots is much smaller than the number of applications. Under this condition, we present our main result.

Theorem 4.2 (Main result). *Consider the cost-sensitive 0-1 risk with cost parameter c. If Condition 4.1 holds, then all fair Bayes-optimal classifiers under predictive parity are GWTRs. Thus, for all $f^\star_{PPV}$ from (2), there are $(t_a)_{a=1}^{|\mathcal{A}|} \in [0, 1]^{|\mathcal{A}|}$ and functions $\tau_a(x) : \mathcal{X} \to [0, 1]$ such that (1) holds.*

---

[3]When $c = 1/2$, cost-sensitive risk reduces to the usual zero-one risk.

Unlike for demographic parity or for equality of opportunity, where the fairness constraint is linear with respect to the probability predictions of the classifier f [35], the DPP constraint is non-linear with respect to f. As a consequence, previously used theoretical tools such as the Neyman-Pearson argument from hypothesis testing [57] are no longer valid in this case. Instead, we prove the result using a novel constructive argument. When Condition 4.1 is satisfied, for any classifier satisfying predictive parity, which is not a GWTR, we construct a GWTR that satisfies predictive parity and achieves a smaller classification error. As a result, under Condition 4.1, all fair Bayes-optimal classifiers are GWTRs. Overall, the proof of Theorem 4.2 is quite involved, and requires a lot of careful casework and analysis.

4.2 Fair Bayes-optimal Classifiers under Predictive Parity do not Need to be Thresholding Rules

Next, we consider the case when the sufficient condition 4.1 does not hold. For simplicity, we consider a binary protected attribute $a \in \{0, 1\}$ with

$$P(Y = 1 \mid \eta_a(x) \geq c, A = 1) < P(Y = 1 \mid A = 0). \tag{3}$$

Our result shows that, under condition (3), there exist class probabilities p_a, $a \in \mathcal{A}$, such that no Bayes-optimal classifier under predictive parity is a GWTR.

Theorem 4.3. *Suppose that condition* (3) *holds. Denote* $t_1 = \inf\{t : P(Y = 1 \mid \eta_1(X) \geq t, A = 1) > P(Y = 1 \mid A = 0)\}$. *Suppose there exist* $\delta_1, \delta_2 > 0$ *such that* $P(c + \delta_1 < \eta_A(X) < t_1 \mid A = 1) = \delta_2 > 0$. *Then, for all* $p_1 > \frac{2}{2 + \delta_1 \delta_2}$, *no fair Bayes-optimal classifier under predictive parity is a GWTR.*

The condition involving the constants $\delta_1, \delta_2 > 0$ ensures that $\eta_1(X)$ has positive probability to be strictly larger than c, which is a technical condition needed in the proof. Theorem 4.3 shows that predictive parity may lead to within-group unfairness, whereby the most qualified individuals are predicted to be unqualified, for a better overall accuracy. By definition, predictive parity requires that the qualifications of selected individuals are similar across the protected groups. Suppose there exists a highly qualified minority group in which most individuals are qualified. Selecting the most qualified individuals in this group leads to a very high standard. As a result, many qualified individuals in other majority groups may be predicted to be unqualified using this standard, leading to accuracy loss. Conversely, if we select less qualified individuals in the highly qualified group, the lower standard allows more qualified individuals from the other groups to be selected, and increases accuracy.

5 FairBayes-DPP: Adaptive Thresholding for Fair Bayes-optimality

In this section, we propose the FairBayes-DPP algorithm (Algorithm 1) for fair Bayes-optimal classification under predictive parity. As mentioned, the DPP constraint is non-linear with respect to the classifier f, and is also highly non-convex with respect to the model parameters, even if both the classifier f and the risk function are convex with respect to these parameters. In such cases, incorporating fairness constraints as a penalty in the training objective may be hard due to potential local minima. Therefore, we consider a different approach, developing a new two-step plug-in method based on Theorem 4.2. Suppose we observe data points $(x_i, a_i, y_i)_{i=1}^n$ drawn independently and identically from a distribution $\mathcal{D}$ over the domain $\mathcal{X} \times \mathcal{A} \times \mathcal{Y}$.

Step 1. In the first step, we apply standard machine learning algorithms to learn the feature- and group-conditional label probabilities η based on the whole dataset. Consider a loss function $L(\cdot, \cdot)$ and the function class $\mathcal{F} = \{f_\theta : \theta \in \Theta\}$ parametrized by θ. The estimator of η is obtained by minimizing the empirical risk, $\hat{\eta}_a(x) := f_{\hat{\theta}}(x, a)$, where

$$\hat{\theta} \in \underset{\theta \in \Theta}{\operatorname{argmin}} \frac{1}{n} \sum_{i=1}^n L(y_i, f_\theta(x_i, a_i)). \tag{4}$$

Here we use the cross-entropy loss, as minimizing the empirical 0-1 risk is generally not tractable. At the population level, the minimizers of the risks induced by the 0-1 and cross-entropy losses are both the true conditional probability function [36].

Algorithm 1 FairBayes-DPP

Input: Datasets $S = \cup_{a=1}^{|\mathcal{A}|} S_a$ with $S = \{x_i, a_i, y_i\}_{i=1}^n$ and $S_a = \{x_j^{(a)}, y_j^{(a)}\}_{j=1}^{n_a}$. Cost parameter $c \in [0, 1]$.

Step 1: Estimate $\eta_a(x)$ by $\hat{\eta} = f_{\hat{\theta}}$, with $\hat{\theta}$ from (4)

Step 2: Find the optimal thresholds..

Define, for all t, $\quad \widehat{\text{PPV}}_a(t) = \frac{\sum_{j=1}^{n_a} I(y_j^{(a)} = 1, \hat{\eta}_a(x_j^{(a)}) \geq t)}{\sum_{j=1}^{n_a} I(\hat{\eta}_a(x_j^{(a)}) \geq t)}, \quad \hat{P}(Y = 1 | A = a) = \frac{1}{n_a} \sum_{i=1}^{n_a} y_j^{(a)}.$

if $\min_a \widehat{\text{PPV}}_a(c) < \max_a \hat{P}(Y = 1 | A = a)$ **then**

    We recommend considering other fairness measures.

else

    Let $t_{\min} = \min\{t : \widehat{\text{PPV}}_1(t) \geq \max_a \hat{P}(Y = 1 | A = a)\}$.

    for $t \in \mathcal{T} = [t_{\min}, \max_j \hat{\eta}_1(x_j^{(1)})]$ **do**

        for $a \in \mathcal{A} \setminus \{1\}$ **do**

            Find $\hat{t}_a(t)$ such that $\widehat{\text{PPV}}_a(\hat{t}_a(t)) \approx \widehat{\text{PPV}}_1(t)$.

        end for

        Let $\hat{f}(x, a, t) = \tilde{f}\left(x, a; \hat{t}_1(t), \hat{t}_2(t), ..., \hat{t}_{|\mathcal{A}|}(t)\right) = I\left(\hat{\eta}_a(x) \geq \hat{t}_a(t)\right).$

        Let $R_c(t) = \frac{1}{n} \sum_{i=1}^n c^{(1-y_i)}(1-c)^{y_i} I(y_i \neq \hat{f}(x_i, a_i, t)).$

    end for

    Find $\hat{t} = \underset{t \in \mathcal{T}_n}{\text{argmin}} R_c(t)$.

    Output: $\hat{f}_{PP}(x, a) = I(\hat{\eta}_a(x) \geq \hat{t}_a(\hat{t}))$

end if

Step 2. In the second step, we first check the empirical version of Condition 4.1 for the classifier derived in the first step. To be more specific, we divide the data into $|\mathcal{A}|$ parts, according to the value of A: for $a \in \mathcal{A}$, $S_a = \{x_j^{(a)}, y_j^{(a)}\}_{j=1}^{n_a}$, where $a_j^{(a)} = a$. Let, for all t for which it is defined,

$$\widehat{\text{PPV}}_a(t) = \frac{\sum_{j=1}^{n_a} I(y_j^{(a)} = 1, \hat{\eta}_a(x_j^{(a)}) \geq t)}{\sum_{j=1}^{n_a} I(\hat{\eta}_a(x_j^{(a)}) \geq t)} \quad \text{and} \quad \hat{P}(Y = 1 | A = a) = \frac{1}{n_a} \sum_{i=1}^{n_a} y_j^{(a)}.$$

We only divide by nonzero quantities here and below. To ensure that the quantities we divide by are nonzero, we restrict to $t_a \in [0, \max_j(\hat{\eta}_a(x_j^{(a)}))]$ when evaluating $\widehat{\text{PPV}}_a(t_a)$. We check whether $\min_a \widehat{\text{PPV}}_a(c) \geq \max_a \hat{P}(Y = 1 | A = a)$.[4] If this is not satisfied, we recommend considering other fairness measures, as predictive parity may not be appropriate in this case, see the discussion after Theorem 4.3. If it is satisfied, we then adjust the thresholds of the classifier aiming for predictive parity. Based on Theorem 4.2, we consider the following deterministic classifiers:

$$\tilde{f}(x, a; t_1, t_2, ..., t_{|\mathcal{A}|}) = I\left(\hat{\eta}_a(x) \geq t_a\right), \tag{5}$$

where $\hat{\eta}$ is the estimate of η from the first step, and t_a, $a \in \mathcal{A}$, are parameters to learn.

We use the following strategy to estimate t_a, $a \in \mathcal{A}$: First, we fix the threshold for the group with $a = 1$, say t. The positive predictive value for this group can then be estimated by $\widehat{\text{PPV}}_1(t)$. To achieve predictive parity, we need to find thresholds for the other groups such that the positive group-wise predictive values are the same[5], i.e., find t_a, $a = 2, 3, \ldots, |\mathcal{A}|$, such that

$$\widehat{\text{PPV}}_a(t_a) \approx \widehat{\text{PPV}}_1(t), \quad \text{for } a = 2, 3, ..., |\mathcal{A}|. \tag{6}$$

As stated in Lemma A.1, the positive predictive value for each group in the population is always non-decreasing with the thresholds t_a increases. As a consequence, we can search over t_a, $a = $

---

[4]One could modify this to allow some slack; and perform a formal statistical hypothesis test of our sufficient condition.

[5]Since a sample mean $n^{-1} \sum_{i=1}^n Z_i$ of iid random variables Z_i has a variability of order $O_P(n^{-1/2})$, even if the true predictive parities are equal, the empirical versions may differ by $O_P(n^{-1/2})$. However, in our case we simply find the values t_a, t for which they are as close as possible.

Table 1: Classification accuracy and DPP of the true fair Bayes-optimal classifier and our estimator trained via logistic regression on a synthetic data example. See Section 6.1 for details.

| | THEORETICAL VALUE | | | LOGISTIC REGRESSION | | | |
| | FAIR | | UNCONSTRAINED | FAIRBAYES-DPP | | UNCONSTRAINED | |
p	ACC	DPP	ACC	DPP	ACC	DPP	ACC
0.2	0.814	0.000	0.814	0.049 (0.036)	0.813 (0.005)	0.046 (0.037)	0.813 (0.005)
0.3	0.794	0.024	0.794	0.037 (0.029)	0.794 (0.006)	0.040 (0.033)	0.794 (0.005)
0.4	0.781	0.050	0.781	0.035 (0.029)	0.781 (0.006)	0.054 (0.029)	0.782 (0.005)
0.5	0.775	0.078	0.777	0.042 (0.032)	0.775 (0.006)	0.081 (0.036)	0.777 (0.006)
0.6	0.778	0.113	0.781	0.038 (0.031)	0.778 (0.006)	0.113 (0.037)	0.781 (0.006)

$2, 3, \ldots, |\mathcal{A}|$, efficiently via, for instance, the bisection method.[6] Correspondingly, we consider the following range of t: $\mathcal{T} = [t_{\min}, \max_j \eta_1(x_j^{(1)})]$ with

$$t_{\min} = \min\{t : \widehat{\mathrm{PPV}}_1(t) \geq \max_a \hat{P}(Y = 1 | A = a)\}.$$

We denote by $\hat{t}_a(t)$, $a = 2, 3, \ldots, |\mathcal{A}|$, the estimated thresholds given by (6), writing $\hat{t}_1(t) = t$ for convenience. We consider the classifier (5) with these thresholds:

$$\hat{f}(x, a, t) = \tilde{f}\left(x, a; \hat{t}_1(t), \hat{t}_2(t), ..., \hat{t}_{|\mathcal{A}|}(t)\right) = I\left(\widehat{\eta}_a(x) \geq \hat{t}_a(t)\right).$$

Lastly, we find t that minimizes the cost-sensitive risk on the training data by searching over a grid $\mathcal{T}_n$ within $\mathcal{T}$:

$$\hat{t} = \underset{t \in \mathcal{T}_n}{\operatorname{argmin}} \left\{ \frac{1}{n} \sum_{i=1}^{n} c^{(1-y_i)}(1-c)^{y_i} I(y_i \neq \hat{f}(x_i, a_i, t)) \right\}.$$

Our final estimator of the fair Bayes-optimal classifier is $\hat{f}_{PP} = \hat{f}_{\hat{t}}$. The FairBayes-DPP algorithm is related to the algorithms proposed for other fairness measures in [57], where a binary protected attribute is considered and closed-form optimal thresholds are derived. In contrast, FairBayes-DPP can handle multi-class protected attributes and does not rely on closed-form thresholds. Similar to [57], our algorithm enforces fairness only in the fast second step, where no gradient-based technique is applied. Thus, it is computationally efficient and the non-convexity of fairness constraint is no longer problematic. Our experimental results demonstrate that our method removes disparities and preserves accuracy.

6 Experiments

6.1 Synthetic Data

We first study a synthetic dataset to compare our method with the true Bayes-optimal fair classifier derived analytically using the true data distribution.

Statistical model. Let $X = (X_1, X_2) \in \mathbb{R}^2$ be a generic feature, $A \in \{0, 1\}$ be the protected attribute and $Y \in \{0, 1\}$ be the label. We generate A and Y according to the probabilities $P(A = 1)$, $P(Y = 1 | A = 1)$ and $P(Y = 1 | A = 0)$, specified below. Conditional on $A = a$ and $Y = y$, X is generated from a bivariate Gaussian distribution $N((2a - 1, 2y - 1)^\top, 2^2 I_2)$, where I_p is the p-dimensional identity covariance matrix. In this model, $\eta_a(x)$ has a closed form, and we use it to find the true fair Bayes-optimal classifier numerically under the Condition 4.1. More details about this synthetic model can be found in Section C of Appendix.

Experimental setting. We randomly sample $50,000$ training data points and $5,000$ test data points. In the Gaussian case, the Bayes-optimal classifier is linear in x and thus we employ logistic regression to learn $\eta_1(\cdot)$ and $\eta_0(\cdot)$. We then search over a grid with spacings equal to 0.001 over the range we identified in Section 5 for the empirically optimal thresholds under fairness. We denote $\hat{f}$ and $\hat{f}_{PPV}$ the estimators of the unconstrained and fair Bayes-optimal classifiers, respectively.

We first evaluate the FairBayes-DPP algorithm under the Condition 4.1. We set the cost parameter $c = 0.5$, while $P(A = 1) = 0.3$ and $P(Y = 1 | A = 0) = 0.2$. It can be calculated that $P(Y =$

---

[6]The empirical PPV is only approximately monotonic, but this does not cause problems.

Figure 1: Accuracy and difference in predictive parity on the Adult and COMPAS datasets.

$1| \eta_0(X) > 0.5, A = 0) \approx 0.613$, using (23) in the Appendix. To consider settings with varied levels of fairness in the population, we vary $p = P(Y = 1|A = 1)$ from 0.2 to 0.6, with the DPP of unconstrained Bayes-optimal classifier grows from 0 to 0.113.

Table 1 presents the classification accuracy and DPP of the true fair Bayes-optimal classifier and FairBayes-DPP trained via logistic regression over 100 simulations[7]. Our first observation is that, under predictive parity, the accuracy of true unconstrained and fair Bayes-optimal classifiers is almost identical, indicating that predictive parity under Condition 4.1 requires a very small loss of accuracy. This finding is consistent with the results in [30] that sufficiency-based measures are favored by unconstrained learning.

Second, our FairBayes-DPP method closely tracks the behavior of the fair Bayes-optimal classifier, controlling the accuracy metric ACC and unfairness metric DPP on the test data effectively. When $|P(Y = 1|A = 1) - P(Y = 1|A = 0)|$ is small, FairBayes-DPP performs similarly to the unconstrained classifier. However, when the data is biased against protected groups and $|P(Y = 1|A = 1) - P(Y = 1|A = 0)|$ is large, FairBayes-DPP mitigates the disparity of the unconstrained classifier effectively, while preserving model accuracy. We further conduct extensive simulations to evaluate the FairBayes-DPP algorithm with different model and training setups, as shown in the Appendix. In particular, we also consider the multi-class protected attribute case.

6.2 Empirical Data Analysis

Dataset. We test FairBayes-DPP on two benchmark datasets for fair classification: "Adult" [14] and "COMPAS" [26]. For each dataset, we randomly sample (with replacement) 70%, 50% and 30% as the training, validation and test set, respectively. To further test the performance of our algorithm on a large-scale dataset, we conduct experiments on the CelebFaces Attributes (CelebA) Dataset [31].

- *Adult:* The target variable Y is whether the income of an individual is more than \$50,000. Age, marriage status, education level and other related variables are included in X, and the protected attribute A refers to gender.
- *COMPAS:* In the COMPAS dataset, the target is to predict recidivism. Here Y indicates whether or not a criminal will reoffend, while X includes prior criminal records, age and an indicator of misdemeanor. The protected attribute A is the race of an individual, "white-vs-non-white".
- *CelebA:* CelebA dataset is a large-scale dataset with more than 200,000 face images, each with 40 attributes (including protected attribute "gender" and other 39 different attributes for prediction tasks). Our goal is to predict the face attributes Y based on the images X and remove bias with respect to gender A from the output.

Experimental setting. As algorithms for predictive parity are rarely considered in the literature, we use unconstrained learning as a baseline for our experiments. For the "Adult" and "COMPAS" datasets, we adopt the same training setting as in [5, 57]. The conditional probabilities are learned

---

[7]Here, the randomness of the experiment is due to the random generation of the synthetic data.

Table 2: Per-attribute accuracy and DPP of the FairBayes-DPP algorithm and unconstrained optimization.

ATTRIBUTES	PER-ATTRIBUTE ACCURACY		PER-ATTRIBUTE DPP	
	FAIRBAYES-DPP	UNCONSTRAINED	FAIRBAYES-DPP	UNCONSTRAINED
ARCHED EYEBROWS	0.838(0.003)	0.838(0.003)	0.027(0.015)	0.099(0.041)
ATTRACTIVE	0.825(0.002)	0.826(0.003)	0.075(0.011)	0.169(0.016)
BAGS UNDER EYES	0.853(0.002)	0.852(0.002)	0.024(0.015)	0.056(0.034)
BANGS	0.959(0.001)	0.959(0.001)	0.007(0.007)	0.069(0.029)
BIG LIPS	0.706(0.002)	0.717(0.003)	0.023(0.015)	0.115(0.027)
BIG NOSE	0.845(0.002)	0.847(0.003)	0.083(0.020)	0.145(0.023)

via a three-layer fully connected neural network architecture with 32 hidden neurons per layer. For "CelebA", we apply the training setting from [50]. We learn the conditional probabilities by training a ResNet50 model; [23], pretrained on ImageNet [11]. For all the datasets, Over the course of training the model on the training set, we select the one with best performance on the validation set. In addition, we learn the optimal thresholds over the validation set to avoid overfitting. All experiments use PyTorch. We refer readers to the Appendix for more training details, including optimizer, learning rates, batch sizes and training epochs. We repeat the experiment 100 times for the Adult and COMPAS datasets and 10 times for the CelebA dataset.[8]

Figure 1 presents the average performances of FairBayes-DPP and unconstrained learning on the Adult and COMPAS datasets. Our method achieves almost the same accuracy as the unconstrained classifier, and has a smaller disparity. To better compare our fair classifier with the unconstrained one, we use the paired t-test to compare the DPP of the proposed algorithm (DPP_{Fair}) and of unconstrained learning (DPP_{Base}). We consider the following one sided test:

$$\mathcal{H}_0 : \text{DPP}_{fair} = \text{DPP}_{Base} \quad \text{v.s.} \quad \mathcal{H}_1 : \text{DPP}_{fair} < \text{DPP}_{Base}.$$

The p-values of the tests are 3.90×10^{-4} for the Adult dataset and 3.09×10^{-8} for the COMPAS dataset. In both cases, these results provide evidence that our FairBayes-DPP achieves a smaller disparity than unconstrained learning.

Finally, we test FairBayes-DPP on the CelebA dataset, Here, we only consider 27 attributes[9] with $0.01 \leq P(Y = 1|M), P(Y = 1|F) \leq 0.99$ in the training, validation, and test sets to ensure that the training, validation and test sample sizes are large enough for each subgroup. We further identify one attribute, "Young", that violates Condition 4.1. We calculate the per-attribute accuracies and DPPs on the test set. Table 2 presents the results of the first six attributes; the remaining results are in the Appendix. As we can see, even for the large-scale CelebA dataset with high dimensional image features, our algorithm mitigates the gender bias effectively, with almost no loss of accuracy.

7   Summary and Discussion

In this paper, we investigate fair Bayes-optimal classifiers under predictive parity. We prove that when the overall performances of different protected groups vary only moderately, all fair Bayes-optimal classifiers under predictive parity are GWTRs. We further propose a post-processing algorithm to estimate the optimal GWTR. The derived post-processing algorithm removes the disparity in unconstrained classifiers effectively, while preserving a similar test accuracy.

However, when our sufficient condition is not satisfied, the fair Bayes-optimal classifier under predictive parity may lead to within-group unfairness for the minority group. In the current literature, man algorithms directly apply penalized/constrained optimization to impose fairness. Our negative finding, however, is an important reminder that careful analysis is required before employing a fairness measure. The improper use of a measure may result in severe unintended consequences.

---

[8]For the Adult and COMPAS datasets, the randomness of the experiment comes from the random selection of the training, validation and test data, as well as the stochasticity of the batch selection in the optimization algorithm. For the CelebA dataset, the randomness is caused by the stochasticity of the optimization method.

[9]Among the 39 attributes, 12 are heavily skewed with $\min(P(Y = 1|M), P(Y = 1|F)) < 0.01$ or $\max(P(Y = 1|M), P(Y = 1|F)) > 0.99$ (where M represents Male and F represents Female) in the training, validation or test set. They are: "5 o'Clock Shadow", "Bald", "Double Chin", "Goatee", "Gray Hair", "Heavy Makeup", "Mustache", "No Beard", "Rosy Cheeks", "Sideburns", "Wearing Lipstick" and "Wearing Necktie".

References

313 [1] Ibrahim Alabdulmohsin. Fair classification via unconstrained optimization, 2020.

314 [2] Toon Calders, Faisal Kamiran, and Mykola Pechenizkiy. Building classifiers with independency constraints. In *2009 IEEE International Conference on Data Mining Workshops*, pages 13–18, 2009.

318 [3] Flavio Calmon, Dennis Wei, Bhanukiran Vinzamuri, Karthikeyan Natesan Ramamurthy, and Kush R Varshney. Optimized pre-processing for discrimination prevention. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

321 [4] L. Elisa Celis and Vijay Keswani. Improved adversarial learning for fair classification, 2019.

322 [5] Jaewoong Cho, Gyeongjo Hwang, and Changho Suh. A fair classifier using kernel density estimation. In *Advances in Neural Information Processing Systems*, volume 33, pages 15088–15099, 2020.

325 [6] A. Chouldechova. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data*, 5(2):153–163, 2017.

327 [7] Evgenii Chzhen, Christophe Denis, Mohamed Hebiri, Luca Oneto, and Massimiliano Pontil. Leveraging labeled and unlabeled data for consistent fair binary classification. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

330 [8] Sam Corbett-Davies, Emma Pierson, Avi Feller, Sharad Goel, and Aziz Huq. Algorithmic decision making and the cost of fairness. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 797–806. Association for Computing Machinery, 2017.

334 [9] A. Cotter, M. R. Jiang, H.and Gupta, S. Wang, T. Narayan, S. You, and K. Sridharan. Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *Journal of Machine Learning Research*, 20(172):1–59, 2019.

337 [10] Elliot Creager, David Madras, Joern-Henrik Jacobsen, Marissa Weis, Kevin Swersky, Toniann Pitassi, and Richard Zemel. Flexibly fair representation learning by disentanglement. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 1436–1445. PMLR, 2019.

341 [11] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

344 [12] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding, 2018.

346 [13] W. Dieterich, C. Mendoza, and T. Brennan. Compas risk scales: Demonstrating accuracy equity and predictive parity. *Northpointe Inc*, 7(4), 2016.

348 [14] Dheeru Dua and Casey Graff. UCI machine learning repository, 2017.

349 [15] Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference*, ITCS '12, pages 214–226, 2012.

352 [16] Charles Elkan. The foundations of cost-sensitive learning. In *In Proceedings of the Seventeenth International Joint Conference on Artificial Intelligence*, pages 973–978, 2001.

354 [17] Michael Feldman, Sorelle A. Friedler, John Moeller, Carlos Scheidegger, and Suresh Venkatasubramanian. Certifying and removing disparate impact. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 259–268. Association for Computing Machinery, 2015.

[18] Benjamin Fish, Jeremy Kun, and Ádám Dániel Lelkes. A confidence-based approach for balancing fairness and accuracy. In *Proceedings of the 2016 SIAM International Conference on Data Mining, Miami, Florida, USA, May 5-7, 2016*, pages 144–152. SIAM, 2016.

[19] A. W. Flores, K. Bechtel, and C. T. Lowenkamp. False positives, false negatives, and false analyses: A rejoinder to machine bias: There's software used across the country to predict future criminals. and it's biased against blacks. *Fed. Probation*, 80:38, 2016.

[20] Gabriel Goh, Andrew Cotter, Maya Gupta, and Michael P Friedlander. Satisfying real-world goals with dataset constraints. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

[21] Megh Gupta and Qasim Mohammad. Advances in ai and ml are reshaping healthcare, 2017.

[22] Moritz Hardt, , Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

[23] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition, 2015.

[24] J. E. Johndrow and K. Lum. An algorithm for removing sensitive information: application to race-independent recidivism prediction. *The Annals of Applied Statistics*, 13(1):189–220, 2019.

[25] Matthew Joseph, Michael Kearns, Jamie H Morgenstern, and Aaron Roth. Fairness in learning: Classic and contextual bandits. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

[26] Surya Mattu Julia Angwin, Jeff Larson and Lauren Kirchner. Machine bias there's software used across the country to predict future criminals. and it's biased against blacks, 2016.

[27] F. Kamiran and T. Calders. Data preprocessing techniques for classification without discrimination. *Knowledge and Information Systems*, 33(1):1–33, 2012.

[28] Preethi Lahoti, Krishna P. Gummadi, and Gerhard Weikum. ifair: Learning individually fair data representations for algorithmic decision making. In *35th IEEE International Conference on Data Engineering, ICDE 2019, Macao, China, April 8-11, 2019*, pages 1334–1345. IEEE, 2019.

[29] Joshua K Lee, Yuheng Bu, Deepta Rajan, Prasanna Sattigeri, Rameswar Panda, Subhro Das, and Gregory W Wornell. Fair selective classification via sufficiency. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 6076–6086. PMLR, 18–24 Jul 2021.

[30] Lydia T. Liu, Max Simchowitz, and Moritz Hardt. The implicit fairness criterion of unconstrained learning. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 4051–4060. PMLR, 09–15 Jun 2019.

[31] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pages 3730–3738, 2015.

[32] Christos Louizos, Kevin Swersky, Yujia Li, Max Welling, and Richard S. Zemel. The variational fair autoencoder. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016.

[33] Kristian Lum and James Johndrow. A statistical framework for fair predictive algorithms, 2016.

[34] David Madras, Elliot Creager, Toniann Pitassi, and Richard Zemel. Learning adversarially fair and transferable representations. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 3384–3393. PMLR, 10–15 Jul 2018.

[35] Aditya Krishna Menon and Robert C Williamson. The cost of fairness in binary classification. In *Proceedings of the 1st Conference on Fairness, Accountability and Transparency*, volume 81 of *Proceedings of Machine Learning Research*, pages 107–118. PMLR, 23–24 Feb 2018.

[36] John W Miller, Rod Goodman, and Padhraic Smyth. On loss functions which minimize to conditional expected values and posterior probabilities. *IEEE Transactions on Information Theory*, 39(4):1404–1408, 1993.

[37] Harikrishna Narasimhan. Learning with complex loss functions and constraints. In *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*, volume 84 of *Proceedings of Machine Learning Research*, pages 1646–1654. PMLR, 2018.

[38] Geoff Pleiss, Manish Raghavan, Felix Wu, Jon Kleinberg, and Kilian Q Weinberger. On fairness and calibration. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[39] Vikram V. Ramaswamy, Sunnie S. Y. Kim, and Olga Russakovsky. Fair attribute classification through latent space de-biasing. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9297–9306, 2021.

[40] Anian Ruoss, Mislav Balunovic, Marc Fischer, and Martin Vechev. Learning certified individually fair representations. In *Advances in Neural Information Processing Systems 33*, 2020.

[41] P. Sattigeri, S. C. Hoffman, V. Chenthamarakshan, and K. R. Varshney. Fairness gan: Generating datasets with fairness properties using a generative adversarial network. *IBM Journal of Research and Development*, 63(4/5):3:1–3:9, 2019.

[42] Nicolas Schreuder and Evgenii Chzhen. Classification with abstention but without disparities. In *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 1227–1236. PMLR, 27–30 Jul 2021.

[43] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2014.

[44] Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. In *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014.

[45] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2015.

[46] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

[47] Songül Tolan, Marius Miron, Emilia Gómez, and Carlos Castillo. Why machine learning may lead to unfairness: Evidence from risk assessment for juvenile justice in catalonia. In *Proceedings of the Seventeenth International Conference on Artificial Intelligence and Law, ICAIL 2019, Montreal, QC, Canada, June 17-21, 2019*, pages 83–92. ACM, 2019.

[48] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[49] Christina Wadsworth, Francesca Vera, and Chris Piech. Achieving fairness through adversarial learning: an application to recidivism prediction, 2018.

[50] Zeyu Wang, Klint Qinami, Ioannis Karakozis, Kyle Genova, Prem Nair, Kenji Hata, and Olga Russakovsky. Towards fairness in visual recognition: Effective strategies for bias mitigation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[51] Depeng Xu, Yongkai Wu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Achieving causal fairness through generative adversarial networks. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 1452–1458. International Joint Conferences on Artificial Intelligence Organization, 2019.

[52] Depeng Xu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Fairgan: Fairness-aware generative adversarial networks. In *2018 IEEE International Conference on Big Data (Big Data)*, pages 570–575, 2018.

[53] Depeng Xu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Fairgan[+]: Achieving fair data generation and classification through generative adversarial nets. In *2019 IEEE International Conference on Big Data (Big Data)*, pages 1401–1406, 2019.

[54] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

[55] Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rodriguez, and Krishna P. Gummadi. Fairness beyond disparate treatment and disparate impact: Learning classification without disparate mistreatment. In *Proceedings of the 26th International Conference on World Wide Web*, pages 1171–1180. International World Wide Web Conferences Steering Committee, 2017.

[56] Rich Zemel, Yu Wu, Kevin Swersky, Toni Pitassi, and Cynthia Dwork. Learning fair representations. In *Proceedings of the 30th International Conference on Machine Learning*, volume 28 of *Proceedings of Machine Learning Research*, pages 325–333. PMLR, 2013.

[57] Xianli Zeng, Edgar Dobriban, and Guang Cheng. Bayes-optimal classifiers under group fairness, 2022.

[58] Brian Hu Zhang, Blake Lemoine, and Margaret Mitchell. Mitigating unwanted biases with adversarial learning. In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '18, pages 335–340. Association for Computing Machinery, 2018.

[59] Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Men also like shopping: Reducing gender bias amplification using corpus-level constraints. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 2941–2951, 2017.