DBA: Efficient Transformer with Dynamic Bilinear Low-Rank Attention

Abstract

Many studies have been conducted to improve the efficiency of the Transformer from quadric to linear over long sequence conditions. Among them, the low-rank-based methods aim to learn the projection matrices to compress the sequence length, thus achieving efficiency gain. However, the projection matrices are fixed once they have been learned, which compress the sequence length with dedicated coefficients for the tokens in the same position regardless of different sequences. Adopting such input-invariant low-rank projections ignores the fact that the most informative part of a sequence varies from sequence to sequence, thus failing to preserve the most useful information that lies in varied positions of different sequences. In addition, previous efficient Transformers only focus on the influence of sequence length while neglecting the effect of hidden state dimension to achieve further efficiency gain. To address the aforementioned problems, we present an efficient yet effective attention mechanism, namely the **Dynamic Bilinear Low-Rank Attention (DBA)**, which compresses the sequence length by input-sensitive dynamic projection matrices and achieves linear time and space complexity by jointly optimizing the sequence length and hidden state dimension while maintaining state-of-the-art performance. Specifically, we first theoretically demonstrate that the sequence length can be compressed non-destructively from a novel perspective of the information theory, with the compression matrices dynamically determined by the input sequence. Furthermore, we show that the hidden state dimension can be approximated by extending the Johnson–Lindenstrauss lemma and achieves high-order small amount error, optimizing the attention in bilinear form. In addition, theoretical analysis shows that the DBA is proficient in capturing high-order relations in cross-attention problems. Experiments over tasks with diverse sequence length conditions show that the DBA achieves state-of-the-art performance compared with various strong baselines while maintaining less memory consumption with higher speed, demonstrating the effectiveness and efficiency of the DBA.

1 Introduction

The Transformer (Vaswani et al., 2017) has shown immense capabilities in a wide range of areas, including natural language processing (Dai et al., 2019), computer vision (Dosovitskiy et al., 2021; Liu et al., 2021), time series analysis (Zerveas et al., 2021), and multi-modal tasks (Qin et al., 2022a; Yu et al., 2019). Compared with convolutional architecture (He et al., 2016), the Transformer is generally more scalable to different volumes and could learn the correlations between different tokens in a sequence.

However, the Vanilla Transformer architecture suffers quadratic time and memory complexity within the attention mechanism, raising concerns about its further application scenarios. Therefore, several efficient Transformers have been introduced recently to overcome excessive time and space consumption (Tay et al., 2022). Among them, kernel-based methods have drawn much attention due to their optimization-friendly characteristic, which improves the efficiency by using the approximation in the attention mechanism (Katharopoulos et al., 2020; Wang et al., 2020; Ma et al., 2021; Xiong et al., 2021; Qin et al., 2022b; Choromanski et al., 2021). One popular kernel-based technique is the low-rank approximation, which compress the sequence length dimension using the same coefficients

Figure 1: Performance (y-axis, higher is better), speed (x-axis, higher is better), and memory foot-print (circle sizes, smaller is better) of efficient transformers on the Long-Range Arena benchmark (Tay et al., 2021b) compared with Vanilla Transformer (Vaswani et al., 2017) in different sequence length conditions (512 and 4k). **The DBA could achieve state-of-the-art performance with the highest speed and lowest memory consumption over various sequence length conditions.**

for all sequences. For instance, Wang *et al.* (Wang et al., 2020) approximated the stochastic matrix in sequence length dimension by using sets of fixed coefficients learned in the training process to calculate the weighted sum of tokens in different positions. Xiong *et al.* (Xiong et al., 2021) adopted the Nyström method to approximate the attention mechanism to linear complexity, decreasing the sequence length with mean pooling. Both of them have achieved competitive performance compared to the Vanilla Transformer with lower computation costs.

However, the flexibility of low-rank projection in previous methods is limited. The projection matrices are pre-determined or fixed after the training process, which compress the different sequences by using the same coefficients for the tokens in the same position. Such input-invariant low-rank compressions ignore the fact that the informative part of a sequence varies from sequence to sequence. Hence, the compression might fail to preserve the most informative parts lying in different positions and limit the performance over tasks where the most informative parts of inputs change significantly, such as image-related tasks. In addition, previous efficient Transformers only focus on optimizing the sequence length while ignore the influence of hidden state dimension. The hidden state dimension also contributes to the computation cost and becomes more critical to efficiency when processing moderate or short sequences. Previous efficient Transformers that achieve significant memory compression and speed-up rate in long sequence conditions could end up with similar efficiency when processing moderate or short sequences compared with the Vanilla Transformer, as shown in Figure 1.

To address the aforementioned problems, we proposed an efficient yet effective attention mechanism, namely the Dynamic Bilinear Low-Rank Attention (DBA), which compresses the sequence length with input-sensitive dynamic projection matrices and achieves linear computation and memory efficiency with bilinear optimization from both sequence length and hidden state dimension. Specifically, we first theoretically show that the sequence length can be compressed non-destructively from a novel perspective of the information theory, where the projection matrices are dynamically determined by the input sequence to best preserve the most informative parts. Furthermore, we demonstrate that the hidden state dimension can be approximated by extending the Johnson–Lindenstrauss lemma (Arriaga & Vempala, 2006; Lindenstrauss & Johnson, 1984) with high-order small amount error. In addition, theoretical analysis shows that the DBA is able to capture high-order relations in cross-attention problems, which is crucial to the performance in multi-modality tasks.

Extensive experiments over tasks with various sequence length conditions are conducted on three different datasets, including Long-Range Arena (LRA) (Tay et al., 2021b) as the long sequence benchmark, UEA multivariate time series classification archive (Bagnall et al., 2018) to evaluate

the performance of various sequence lengths, VQA-v2 (Goyal et al., 2017) as the illustrations of DBA in capturing the high-order relations. The DBA achieves state-of-the-art performance with impressing speed-up and memory compression rate compared with other competitors over various sequence length conditions, demonstrating the effectiveness and efficiency of DBA in a wide range of applications.

Our main contributions can be summarized as follows:

1) We introduce an efficient and effective attention mechanism, namely the Dynamic Bilinear Low-Rank Attention (DBA), which compresses the sequence length by input-sensitive dynamic projection matrices. The DBA achieves efficiency gain over various sequence length conditions with linear time and space complexity by jointly optimizing the sequence length and hidden state dimension.

2) Theoretical guarantee from information theory and matrix low-rank approximation demonstrates that the DBA has a similar capability to the Vanilla Attention with low expected error. In addition, theoretical analysis shows that the DBA is able to capture high-order inter-relations in cross-attention problems.

3) Extensive experiments on tasks with various sequence length conditions, including Long-Range Arena (LRA) (Tay et al., 2021b) and UEA multivariate time series classification archive (Bagnall et al., 2018), show that the DBA could achieve state-of-the-art performance in a wide range of applications with impressing efficiency gain. In addition, the superior ability to capture high-order relations in cross-attention is validated on the VQA-v2 (Goyal et al., 2017) task, and the DBA outperforms the Vanilla Transformer based MCAN (Yu et al., 2019) with only 12% of parameters in attention layer.

2 BACKGROUND AND RELATED WORK

2.1 VANILLA TRANSFORMER

The Vanilla Transformer (Vaswani et al., 2017) uses Vanilla Attention as its main algorithm, which is calculated via the softmax weighted sum of all values $\boldsymbol{V}$ concerning the weights obtained by the multiplication of $\boldsymbol{Q}$ and $\boldsymbol{K}$:

$$\boldsymbol{P}_\phi(\boldsymbol{K}, \boldsymbol{Q}) = \text{softmax}\left(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}}\right) \tag{1}$$

$$\text{Attention}\left(\boldsymbol{P}_\phi(\boldsymbol{K}, \boldsymbol{Q}), \boldsymbol{V}\right) = \boldsymbol{P}_\phi(\boldsymbol{K}, \boldsymbol{Q})\boldsymbol{V} \tag{2}$$

Here we define the $\boldsymbol{P}_\phi(\boldsymbol{K}, \boldsymbol{Q})$ as attention map, and later, we will abbreviate $\boldsymbol{P}_\phi(\boldsymbol{K}, \boldsymbol{Q})$ as $\boldsymbol{P}_\phi$ for simplicity. The $\boldsymbol{Q} \in \mathbb{R}^{n \times d}$, $\boldsymbol{K} \in \mathbb{R}^{n \times d}$, $\boldsymbol{V} \in \mathbb{R}^{n \times d}$, and $\boldsymbol{P}_\phi \in \mathbb{R}^{n \times n}$, where n is the sequence length and d indicates the hidden state dimension. Notice that the time and memory complexity for the Vanilla Attention is proportional to $O\left(n^2 d\right)$. For the long sequence applications, the impact of n becomes dominant, and the influence of d becomes greater when facing moderate or short sequences.

2.2 EFFICIENT TRANSFORMERS

A lot of studies have been conducted to improve the efficiency of the Transformer. One kind of method is by using sparsity, where each token could only access limited perspective field with fixed or learned patterns, including the local attention (Parmar et al., 2018), Reformer (Kitaev et al., 2020), Sinkhorn (Tay et al., 2020), Routing Transformer (Roy et al., 2021), ALiBi (Press et al., 2022), Learning-to-Hash Attention (LHA) (Sun et al., 2022), YOSO (Zeng et al., 2021), ClusterFormer (Wang et al.), Poolingformer (Zhang et al., 2021), and Big Bird (Zaheer et al., 2020). To make the attention have wider perspective field, some works concentrate on the interactions between the near field and the far field, such as Focal Attention (Yang et al., 2021), FMMformers (Nguyen et al., 2021), Long-Short Transformer (Zhu et al., 2021), and Crossformer (Wang et al., 2022).

Another popular approach is the kernel-based method, which improves the efficiency of the Transformer by rewriting the multiplication in equations 1 and 2, such as Linear Transformer (Parmar et al., 2018), PoNet (Tan et al., 2022), Random Feature Attention (Peng et al., 2021), and LARA (Zheng et al., 2022). In (Choromanski et al., 2021; Qin et al., 2022b; Chen et al., 2021b), the

authors optimize the softmax kernel with faster reweighting functions. Since the kernels are the approximation in the attention matrices, they can also be optimized by low-rank methods, such as Linformer (Wang et al., 2020), Luna (Ma et al., 2021), and Nyströmformer (Xiong et al., 2021). In (Zhuang et al., 2022; Luo et al., 2021; Kreuzer et al., 2021; Zhou et al., 2022), the authors improve the efficiency of the attention kernel by digging into the frequency domain. Some works also focus on the multi-head characteristic in attention mechanism and optimize via reducing the parallel computations, such as FLASH (Hua et al., 2022) and Transformer-MGK (Nguyen et al., 2022).

The proposed DBA is most similar to Linformer, which both approximate features in Vanilla Attention to the low-rank matrices and achieve linear complexity. The main differences are in three folds. First, the low-rank projection matrices in DBA are more flexible than in Linformer, where the weights in the low-rank projection matrices are dynamically determined by the input sequence rather than fixed after training. Therefore, the DBA is able to compress the sequence length with input-sensitive coefficients for the tokens in the same position to best preserve information and process sequences in different lengths without fixed padding. In addition, the DBA considers the hidden-state dimension to the final efficiency and could achieve further efficiency gain over various sequence length conditions. Furthermore, the DBA is proficient in capturing high-order relations with multi-stage interactions, whereas Linformer could only perform one-stage interaction.

3 METHOD

Our goal is to design an efficient attention mechanism with linear complexity, where the analysis starts with the Vanilla Attention defined in equations 1 and 2. In Section 3.1, we will theoretically demonstrate that the input sequence length n can be compressed non-destructively from the perspective of information theory, leading to linear complexity in both time and space. In Section 3.2, we will extend the Johnson–Lindenstrauss lemma to prove that the multiplication between Q and K can be reduced by low-rank approximation with high-order small amount error in the results, mitigating the impact of the hidden state dimension d on efficiency. In Section 3.3, we will present the source of matrices newly introduced to DBA and show that the sequence length compression matrices are dynamically determined by the input features, leading to adaptive coefficients for tokens in the same position. In Section 3.4, we will show that the DBA could capture high-order inter-relations in cross-attention problems and perform multi-stage interactions within a single attention layer.

3.1 OPTIMIZE THE SEQUENCE LENGTH WITH INFORMATION THEORY

In this section, we will optimize the quadric complexity of sequence length to Transformer by analyzing the attention mechanism from the information theory perspective, leading to linear complexity in both time and space. Specifically, we will show that the attention matrix $P_\phi \in \mathbb{R}^{n \times n}$ could be replaced by a set of smaller matrices without information loss.

Note that in the Vanilla Attention, the P_ϕ is deterministic for dedicated QK^T. Hence, we could derive that the conditional extropy between QK^T and P_ϕ is 0.

$$H(P_\phi | QK^T) = H(\text{softmax}\left(\frac{QK^T}{\sqrt{d}}\right) | QK^T) = 0 \tag{3}$$

Therefore, we could obtain the P_ϕ could be reconstructed none-destructively with the based of QK^T and the reconstruction coefficients. Therefore, the conditional extropy between the bases of QK^T with reconstruction coefficients to the P_ϕ is 0.

$$H(P_\phi | \text{ basis}_\text{r}(\text{basis}_\text{c}(QK^T)), W'_r, W'_c) = 0 \tag{4}$$

where basis_r and basis_c calculate the basis of QK^T in the row and column spaces, respectively. W'_r and W'_c are the reconstruction coefficients for row and column.

From the properties of matrix rank in multiplication, we could get the following inequality.

$$\text{Rank}\left(QK^T\right) \leq \max\left(\text{Rank}\left(Q\right), \text{Rank}\left(K\right)\right) \leq \min\left(n, d\right) \tag{5}$$

where $\text{Rank}()$ calculates the rank of a matrix.

Figure 2: Illustration of the algorithm of Vanilla Attention versus DBA. Compared with Vanilla Transformer (Vaswani et al., 2017), the $\boldsymbol{Q}, \boldsymbol{K}$ in DBA are compressed to low-rank alternatives with bilinear form in both sequence length and the hidden state dimension. The DBA has the same input and output as Vanilla Transformer by using the reconstruction matrix $\boldsymbol{W}_r'$, making the DBA plug and play to existing Transformers easily. The labels on the row and column of squares represent the dimension of features.

Hence, the dimension of $\mathrm{basis_r}(\mathrm{basis_c}(\boldsymbol{Q}\boldsymbol{K}^T))$ are no larger than $\mathbb{R}^{\min(n,d)\times\min(n,d)}$. Therefore, with the help of equation 4, a given $\boldsymbol{P}_\phi$ can be represented non-destructively with a matrix $\boldsymbol{P}_\phi' \in \mathbb{R}^{d_p \times d_p}$ ($d_p \leq \min(n,d)$) and reconstruction coefficient $\boldsymbol{W}_r' \in \mathbb{R}^{n \times d_p}$ and $\boldsymbol{W}_c' \in \mathbb{R}^{n \times d_p}$.

$$\boldsymbol{P}_\phi = \boldsymbol{W}_r'\boldsymbol{P}_\phi'\boldsymbol{W}_c'^T \tag{6}$$

In practice, we could project $\boldsymbol{Q} \in \mathbb{R}^{n \times d}, \boldsymbol{K} \in \mathbb{R}^{n \times d}$ to $\boldsymbol{Q}_l \in \mathbb{R}^{d_p \times d}, \boldsymbol{K}_l \in \mathbb{R}^{d_p \times d}$ to generate the $\boldsymbol{P}_\phi'$, with $\boldsymbol{Q}_l$ with $\boldsymbol{K}_l$ as the input for equation 1. Here, we could derive the following equation:

$$\begin{aligned}\boldsymbol{P}_\phi = \boldsymbol{W}_r'\boldsymbol{P}_\phi'\boldsymbol{W}_c'^T &= \boldsymbol{W}_r'\left(\mathrm{softmax}\left(\frac{\boldsymbol{Q}_l\boldsymbol{K}_l^T}{\sqrt{d}}\right)\right)\boldsymbol{W}_c'^T \\ &= \boldsymbol{W}_r'\left(\mathrm{softmax}\left(\frac{(\boldsymbol{W}_r\boldsymbol{Q})(\boldsymbol{K}^T\boldsymbol{W}_c^T)}{\sqrt{d}}\right)\right)\boldsymbol{W}_c'^T\end{aligned} \tag{7}$$

where $\boldsymbol{W}_r \in \mathbb{R}^{d_p \times n}, \boldsymbol{W}_c \in \mathbb{R}^{d_p \times n}, \boldsymbol{W}_r' \in \mathbb{R}^{n \times d_p}$, and $\boldsymbol{W}_c' \in \mathbb{R}^{n \times d_p}$.

By proposing the $\boldsymbol{P}_\phi'$ as the new attention map instead of $\boldsymbol{P}_\phi$, we avoid the quadric complexity in time and space in attention map generation. However, notice that the reconstruction process using $\boldsymbol{W}_r'$ and $\boldsymbol{W}_c'^T$ still brings high complexity. Here, we first merge the $\boldsymbol{W}_c'$ and $\boldsymbol{V}$ first as $\boldsymbol{V}_{DBA}$, then the $\boldsymbol{V}_{DBA}$ is multiplied by $\boldsymbol{P}_\phi'$. The reconstruction process by $\boldsymbol{W}_r'$ is set in the last. By optimizing the calculation order, the DBA achieves linear complexity.

$$\mathrm{DBA}\left(\boldsymbol{K}, \boldsymbol{Q}, \boldsymbol{V}\right) = \boldsymbol{W}_r'(\boldsymbol{P}_\phi'(\boldsymbol{W}_c'^T\boldsymbol{V})) = \boldsymbol{W}_r'\left(\boldsymbol{P}_\phi'\boldsymbol{V}_{DBA}\right) \tag{8}$$

where $\boldsymbol{V}_{DBA} = \boldsymbol{W}_c'^T\boldsymbol{V} \in \mathbb{R}^{d_p \times d}$.

3.2 OPTIMIZE THE HIDDEN STATE DIMENSION WITH MATRIX APPROXIMATION

In Section 3.1, we optimize the sequence length by analyzing from the information theory perspective, leading to linear complexity. In this section, we will further increase the efficiency of DBA by mitigating the impact of hidden state dimension d on efficiency. Specifically, we will extend the Johnson–Lindenstrauss lemma (JS lemma) (Arriaga & Vempala, 2006; Lindenstrauss & Johnson, 1984) to show the multiplication between $\boldsymbol{Q}$ and $\boldsymbol{K}$ can be approximated with high-order small amount error. Here, we will first introduce the JS lemma.

Johnson–Lindenstrauss lemma. *Let $\boldsymbol{R}$ be an $d \times d_{in}$ matrix, $1 \leq d_{in} \leq d$, with i.i.d. entries from $\mathcal{N}(0, 1/d)$. For any $\mathbf{x}, \mathbf{y} \in \mathbb{R}^d$, we have*

$$\mathrm{Pr}\left(\left|\left|\mathbf{x}\boldsymbol{R}\boldsymbol{R}^T\mathbf{y}^T - \mathbf{x}\mathbf{y}^T\right|\right| \leq \epsilon\left|\left|\mathbf{x}\mathbf{y}^T\right|\right|\right) > 1 - 2e^{-\left(\epsilon^2 - \epsilon^3\right)d_{in}/4} \tag{9}$$

Based on the JS lemma, we could obtain:

$$\begin{aligned}&\mathrm{Pr}\left(\left|\left|\boldsymbol{Q}\boldsymbol{R}\boldsymbol{R}^T\boldsymbol{k}_i^T - \boldsymbol{Q}\boldsymbol{k}_i^T\right|\right| \leq \epsilon\left|\left|\boldsymbol{Q}\boldsymbol{k}_i^T\right|\right|\right) \\ &\geq 1 - \sum_{\boldsymbol{q}_i \in \boldsymbol{Q}}\mathrm{Pr}\left(\left|\left|\boldsymbol{q}_i\boldsymbol{R}\boldsymbol{R}^T\boldsymbol{k}_i^T - \boldsymbol{q}_i\boldsymbol{k}_i^T\right|\right| > \epsilon\left|\left|\boldsymbol{q}_i\boldsymbol{k}_i^T\right|\right|\right) > 1 - 2ne^{-\left(\epsilon^2 - \epsilon^3\right)d_{in}/4}\end{aligned} \tag{10}$$

The $\boldsymbol{K}$ contain n rows. Here we could get:

$$
\begin{aligned}
& \Pr\left(\left|\left|\boldsymbol{Q}\boldsymbol{R}\boldsymbol{R}^T\boldsymbol{K}^T - \boldsymbol{Q}\boldsymbol{K}^T\right|\right| \leq \epsilon \left|\left|\boldsymbol{Q}\boldsymbol{K}^T\right|\right|\right) \\
& \geq 1 - \sum_{\boldsymbol{k}_i \in \boldsymbol{K}} \Pr\left(\left|\left|\boldsymbol{Q}\boldsymbol{R}\boldsymbol{R}^T\boldsymbol{k}_i^T - \boldsymbol{Q}\boldsymbol{k}_i^T\right|\right| > \epsilon \left|\left|\boldsymbol{Q}\boldsymbol{k}_i^T\right|\right|\right) > 1 - 2n^2 e^{-\left(\epsilon^2 - \epsilon^3\right)d_{in}/4}
\end{aligned} \tag{11}
$$

Hence,

$$
\begin{aligned}
& \Pr\left(\left|\left|(\boldsymbol{W}_r\boldsymbol{Q})\,\boldsymbol{R}\boldsymbol{R}^T\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right) - (\boldsymbol{W}_r\boldsymbol{Q})\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right)\right|\right| \leq \epsilon \left|\left|(\boldsymbol{W}_r\boldsymbol{Q})\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right)\right|\right|\right) \\
& > 1 - 2d_p^2 e^{-\left(\epsilon^2 - \epsilon^3\right)d_{in}/4}
\end{aligned} \tag{12}
$$

Let $d_{in} \geq 10log\left(d_p\right)/\left(\epsilon^2 - \epsilon^3\right)$, we could obtain:

$$
\begin{aligned}
& \Pr\left(\left|\left|(\boldsymbol{W}_r\boldsymbol{Q})\,\boldsymbol{R}\boldsymbol{R}^T\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right) - (\boldsymbol{W}_r\boldsymbol{Q})\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right)\right|\right| \leq \epsilon \left|\left|(\boldsymbol{W}_r\boldsymbol{Q})\left(\boldsymbol{K}^T\boldsymbol{W}_c^T\right)\right|\right|\right) \\
& > 1 - o\left(1\right)
\end{aligned} \tag{13}
$$

The equation 13 shows that the multiplication between $\boldsymbol{Q}$ and $\boldsymbol{K}$ could be replaced by alternatives with lower hidden state dimension (d vs. d_{in}) and achieves errors in high-order small quantities compared to full-rank multiplication. Therefore, we could further project $\boldsymbol{Q}_l \in \mathbb{R}^{d_p \times d}$, $\boldsymbol{K}_l \in \mathbb{R}^{d_p \times d}$ mentioned in Section 3.1 to $\boldsymbol{Q}_{DBA} \in \mathbb{R}^{d_p \times d_{in}}$, $\boldsymbol{K}_{DBA} \in \mathbb{R}^{d_p \times d_{in}}$, and finally, the DBA could be written as follows:

$$
\begin{aligned}
\mathrm{DBA}\left(\boldsymbol{K}, \boldsymbol{Q}, \boldsymbol{V}\right) &= \boldsymbol{W}_r'\left(\left(\mathrm{softmax}\left(\frac{((\boldsymbol{W}_r\boldsymbol{Q})\boldsymbol{R})(\boldsymbol{R}^T(\boldsymbol{K}^T\boldsymbol{W}_c^T))}{\sqrt{d_{in}}}\right)\right)\left(\boldsymbol{W}_c'^T\boldsymbol{V}\right)\right) \\
&= \boldsymbol{W}_r'\left(\mathrm{softmax}\left(\frac{\boldsymbol{Q}_{DBA}\boldsymbol{K}_{DBA}}{\sqrt{d_{in}}}\right)\boldsymbol{V}_{DBA}\right)
\end{aligned} \tag{14}
$$

The attention mechanism is now compressed with bilinear form in both sequence length and the hidden state dimension, increasing the efficiency for sequences with various lengths. The graphical comparison between Vanilla Attention and DBA is illustrated in Figure 2.

3.3 THE SOURCE OF MATRICES

In this section, we will define the source of the matrices that are newly introduced to DBA in self-attention situation, including the hidden state compression matrix $\boldsymbol{R}$, the sequence compression matrices $\boldsymbol{W}_r$, $\boldsymbol{W}_c$, and the reconstruction matrices $\boldsymbol{W}_r'$, $\boldsymbol{W}_c'$. We will show that the weights in the sequence compression matrices are determined by the input sequence, leading to dynamic coefficients for tokens in the same position between different sequences.

The $\boldsymbol{R}$ compress the hidden state with a fixed dimension. Therefore, it is set as a fully connected layer and learned through training. The $\boldsymbol{W}_r'$, $\boldsymbol{W}_c'$ are set as the input sequences propagate thought the fully connected layers to obtain the expected hidden state dimension. The $\boldsymbol{W}_r$ and $\boldsymbol{W}_c$ are generated by combining the input sequence and an extra input $\boldsymbol{Z} \in \mathbb{R}^{d_p \times d}$ in a shorter length.

$$
\boldsymbol{W}_r = \varphi\left(\boldsymbol{Z}\boldsymbol{Q}^T\right) \tag{15}
$$

$$
\boldsymbol{W}_c = \varphi(\boldsymbol{Z}\boldsymbol{K}^T) \tag{16}
$$

where φ is a normalization function to stabilize the training process.

Therefore, the compression matrices $\boldsymbol{W}_r$ and $\boldsymbol{W}_c$ are dynamically determined by the input sequence, where every coefficient in the $\boldsymbol{W}_r$ and $\boldsymbol{W}_c$ is the linear transformations of the token features in the corresponding position. Each row in $\boldsymbol{W}_r$ and $\boldsymbol{W}_c$ is a set of compression coefficients for all token in the input sequence, and the results of each position in the final compressed sequences $\boldsymbol{W}_r\boldsymbol{Q}$ and $\boldsymbol{K}^T\boldsymbol{W}_c^T$ are the different weighted sum of tokens in the original sequence. The weights in the reconstruction matrices $\boldsymbol{W}_r'$, $\boldsymbol{W}_c'$ are also determined by the input, where the rows also represent different sets of coefficients dynamically determined by the input sequence. Note that the dimensions for both $\boldsymbol{W}_r$, $\boldsymbol{W}_c$ and $\boldsymbol{W}_r'$, $\boldsymbol{W}_c'$ are dynamically determined by the input, making them able to process sequences in various lengths without fixed padding. In practice, we set $\boldsymbol{Z}$ as learnable parameters propagating through different attention layers.

Table 1: Speed and peak memory consumption of different models on byte-level text classification with various sequence lengths (256, 512, 1k, 2k, 3k, and 4k). The average performances on the LRA task are listed on the right. The best model is made bold.

Model	Speed ↑						Peak Memory Usage ↓						Avg. ↑
	256	512	1k	2k	3k	4k	256	512	1k	2k	3k	4k	
Vanilla Transformer	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	58.57
Local Attention	1.0	1.1	1.1	1.7	3.2	5.3	0.94	0.75	0.49	0.29	0.19	0.14	49.51
Linformer	1.0	1.2	1.2	1.9	3.7	5.5	0.90	0.70	0.44	0.21	0.18	0.10	56.47
Reformer	1.0	0.6	0.5	0.4	0.7	0.8	1.21	1.06	0.70	0.37	0.28	0.24	54.59
Sinkhorn Trans.	0.9	1.0	1.1	1.6	2.9	3.8	0.92	0.76	0.55	0.31	0.21	0.16	53.89
Synthesizer	**1.2**	1.2	1.1	1.2	2.9	1.4	1.06	0.91	0.76	0.75	0.74	0.74	57.95
Cosformer	0.9	1.0	1.0	1.5	2.8	3.7	1.24	0.88	0.58	0.28	0.25	0.19	55.23
Linear Transformer	1.0	1.1	1.1	1.9	3.7	5.6	1.16	0.95	0.44	0.22	0.15	0.11	54.35
Performer	1.1	1.2	1.2	1.9	3.8	5.7	0.89	0.74	0.44	0.22	0.15	0.11	55.73
Luna	1.0	1.2	1.2	1.8	3.7	5.5	0.88	0.70	0.44	0.23	0.17	0.10	61.46
DBA	1.1	**1.4**	**1.4**	**2.0**	**4.1**	**6.1**	**0.84**	**0.66**	**0.38**	**0.19**	**0.15**	**0.09**	**62.42**

3.4 CAPTURE HIGH-ORDER RELATIONS IN CROSS-ATTENTION

In this section, we will show that the DBA is able to capture high-order relations with multi-stage interactions within an attention layer in the cross-attention situation. We will first introduce the cross-attention algorithm in Vanilla Transformer and then compare it with the proposed DBA.

The cross-attention in Vanilla Transformer shares the same expression as self-attention in equations 1 and 2. The only difference is the input. In cross-attention, one input X_1 from H_1 is processed as Q_1, and the other input X_2 from H_2 is processed as K_2, V_2, where the subscript 1, 2 indicate the variables in different hierarchies, and H_1, H_2 denote different hierarchies. By leveraging the Vanilla Attention algorithm, the Q_1 is fused with K_2, leading to one-stage interaction within an attention layer.

$$\text{Cross-Attention}\left(\boldsymbol{K}_2, \boldsymbol{Q}_1, \boldsymbol{V}_2\right) = \text{softmax}\left(\frac{\boldsymbol{Q}_1 \boldsymbol{K}_2^T}{\sqrt{d}}\right) \boldsymbol{V}_2 \tag{17}$$

The DBA takes different inputs compared with Vanilla Attention in cross-attention. Instead of taking the full-length features X_2 as K_2, V_2, the DBA takes the compressed sequence $W_{r2}X_2$ as Z_1, K_2, and V_2. Both models take the X_1 as Q_1.

Firstly, we compress the sequence length following Section 3.1. As the $W_{r2}X_2$ formed K_2, V_2 are already been compressed, we only need to compress sequence length in Q_1 using the W_{r1}, which is obtained from Z_1.

$$\boldsymbol{W}_{r1} = \varphi(\boldsymbol{Z}_1 \boldsymbol{Q}_1^T) = \varphi(\text{Linear}(\boldsymbol{W}_{r2}\boldsymbol{X}_2)\boldsymbol{Q}_1^T) \tag{18}$$

where $\text{Linear}()$ denotes the linear transformation in hidden state dimension.

The advantages of using $W_{r2}X_2$ as Z_1 are in two folds. First, the features from two different hierarchies interact when generating the W_{r1}. Second, it compresses the sequence length of Q_1, where the compression coefficients are guided by features in H_2.

After sequence length compression, we optimize the impact of d on efficiency following Section 3.2, and finally, we could get $(\boldsymbol{Q}_{DBA})_1$, $(\boldsymbol{K}_{DBA})_2$, and $(\boldsymbol{V}_{DBA})_2$ to perform second interaction between two features as in equation 14. Therefore, the DBA could capture inter-relations in the sequence compression matrices generation procedure and attention mechanism within a single attention layer, where the compressed feature in H_2 interacts with original and compressed features in H_1, making the DBA able to capture high-order relations and perform multi-stage interactions.

4 EXPERIMENTS

We evaluate the performance of DBA on three datasets, covering the long and diverse sequence conditions with self- and cross-attention tasks, including Long-Range Arena (LRA) (Tay et al., 2021b)

Table 2: Performance on the LRA benchmark. The best model is made bold.

Model	ListOps ↑	Text ↑	Retrieval ↑	Image ↑	Pathfinder ↑	Avg. ↑
Vanilla Transformer (Vaswani et al., 2017)	36.37	64.27	78.38	42.44	71.40	58.57
Local Attention (Parmar et al., 2018)	15.82	52.98	70.65	41.46	66.63	49.51
Sparse Transformer (Child et al., 2019)	17.07	63.58	72.53	44.24	71.71	53.83
Longformer (Beltagy et al., 2020)	35.63	62.85	68.32	42.22	69.71	55.75
Linformer (Wang et al., 2020)	35.70	53.94	77.83	38.56	76.34	56.47
Reformer (Kitaev et al., 2020)	37.27	56.10	73.03	38.07	68.50	54.59
Sinkhorn (Tay et al., 2020)	33.67	61.20	65.88	41.23	67.45	53.89
Synthesizer (Tay et al., 2021a)	36.99	61.68	80.04	41.61	69.45	57.95
Big Bird (Zaheer et al., 2020)	36.05	64.02	76.41	40.83	74.87	58.44
Linear Transformer (Katharopoulos et al., 2020)	16.13	65.90	72.09	42.34	75.30	54.35
Performer (Choromanski et al., 2021)	18.01	65.40	75.43	42.77	77.05	55.73
Fnet (Lee-Thorp et al., 2022)	35.33	65.11	59.61	38.67	77.80	55.30
cosformer (Qin et al., 2022b)	37.90	63.41	61.36	43.17	70.33	55.23
PoNet (Tan et al., 2022)	37.80	69.82	80.35	46.88	70.39	61.05
Luna (Ma et al., 2021)	37.43	65.74	79.38	46.39	78.36	61.46
Pixelfly (Chen et al., 2022)	37.65	66.78	80.55	42.35	72.01	59.87
YOSO (Zeng et al., 2021)	37.40	64.28	77.61	44.67	71.86	59.16
Scatterbrain (Chen et al., 2021a)	**38.60**	64.55	80.22	43.65	69.91	59.39
Nyströmformer (Xiong et al., 2021)	37.15	65.52	79.56	41.58	70.94	58.95
DBA	38.50	**66.30**	**80.65**	**47.00**	**79.66**	**62.42**

as the benchmark on long sequence, UEA multivariate time series classification archive (Bagnall et al., 2018) to evaluate performance on various sequence lengths, VQA-v2 (Goyal et al., 2017) to test the performance of cross-attention. The detailed descriptions of datasets are in Appendix A.1, and the experiment settings are listed in Appendix A.2.

4.1 EFFICIENCY

The efficiency of DBA compared with Vanilla Transformer and other efficient Transformers are illustrated in Figure 1 and Table 1. We report the speed and peak memory usage of different attentions in 256-4k sequence lengths. The DBA achieves state-of-the-art efficiency in terms of speed and peak memory usage, which is faster than the Vanilla Transformer and consumes fewer memories over various sequence conditions. In the long sequence conditions, the DBA is 6.1 times faster than Vanilla Transformer and only uses 9% of memory in 4k sequence length. As for shorter sequence length, the DBA could also achieve the highest efficiency among others, with 1.4 times faster and only uses 66% of memories compared to the Vanilla Attention in 512 sequence length. The DBA only falls behind the Synthesizer when facing the 256-sequence length in terms of speed. However, the DBA uses much less memory with much-suppressed efficiency on the long sequence condition. In addition, the DBA achieves the best among others in terms of average performance on the LRA task, demonstrating the effectiveness and efficiency of DBA.

4.2 PERFORMANCE ON LONG SEQUENCE MODELING

We evaluate the long sequence modeling performance of DBA and the previous methods on the LRA benchmark, as listed in Table 2. The DBA achieves state-of-the-art performance in terms of the average score. By closer observation of each individual task, the DBA achieves the best results on four out of five individual tasks. Notably, the DBA suppresses the Vanilla Transformer and previous low-rank-based methods in all five tasks and is exceptionally proficient in image-related tasks where the most informative parts change significantly for different inputs. Note that the DBA has the fastest speed and lowest memory consumption in all tasks, demonstrating the effectiveness and efficiency of DBA.

4.3 PERFORMANCE ON TIME SERIES SIGNAL IN VARIOUS LENGTH

We use UEA multivariate time series classification archive to evaluate the performance of models in various sequence lengths. The results are illustrated in Table 3. The DBA achieves the best

Table 3: Performance on the UEA multivariate time series classification archive. The best model is made bold.

Task / Model	Transformer	Linear	Performer	Cosformer	Flowformer	DBA
Ethanolconcentration ↑	32.7	31.9	31.2	33.5	33.8	**36.5**
Facedetection ↑	67.3	67.0	67.0	67.1	67.6	**69.0**
Handwriting ↑	32.0	34.7	32.1	34.7	33.8	**35.2**
Heartbeat ↑	76.1	76.6	78.0	75.6	77.6	**79.0**
Japanese vowels ↑	98.7	99.2	98.1	99.2	98.9	**99.7**
Pems-Sf ↑	82.1	82.1	80.9	80.9	83.8	**84.4**
Selfregulationscp1 ↑	92.2	92.5	91.5	91.8	92.5	**93.2**
Selfregulationscp2 ↑	53.9	56.7	56.7	55.6	56.1	**58.3**
Spokenarabicdigits ↑	98.4	98.0	98.4	98.8	98.8	**99.5**
Uwavegesturelibrary ↑	85.6	85.0	85.3	85.0	86.6	**87.5**
Average Accuracy ↑	71.9	72.4	71.9	72.2	73.0	**74.2**

Table 4: Performance on the *val* split of the VQA-v2 dataset. nPara denotes the number of parameters in attention layers. The best model is made bold.

Model	nPara ↓	All ↑	Y.N. ↑	Num. ↑	Other ↑
MCAN (Yu et al., 2019)	44M	67.17	84.82	49.37	58.48
BAN (Kim et al., 2018)	60M	66.00	83.61	47.04	57.62
Linformer (Wang et al., 2020)	39M	66.19	83.77	48.15	57.61
Performer (Choromanski et al., 2021)	38M	65.64	83.27	46.83	57.21
MCAoAN (Rahman et al., 2021)	58M	67.24	84.95	49.51	58.45
DBA	**5.2M**	**68.59**	**85.87**	**49.95**	**60.39**

performance compared with previous methods in all 10 tasks, with 2.3% improvement on the average accuracy compared with the Vanilla Transformer, highlighting the capability of processing sequences in various lengths.

4.4 PERFORMANCE ON CAPTURE CROSS-ATTENTION RELATIONS

We use the VQA-v2 dataset to evaluate the performance of DBA in cross-attention tasks. The results are shown in Table 4. Compared with the previous methods, where the image and question interact once per layer, the DBA could capture high-order relations between hierarchies and perform multi-stage interactions within an attention layer, making the DBA achieve the best results on the VQA-v2 tasks in all four evaluation aspects with only 12% of parameters compared with Vanilla Transformer based MCAN (Yu et al., 2019) in attention layer, highlighting the effectiveness of DBA in capturing cross-attention relations.

5 CONCLUSION

In this paper, we propose Dynamic Bilinear Low-Rank Attention (DBA), an efficient attention mechanism that compresses the sequence length by input-sensitive dynamic projection matrices and achieves linear time and space complexity by jointly optimizing the sequence length and hidden state dimension. Theoretical analysis from the information theory and matrix low-rank approximation perspectives shows that the DBA could achieve a similar function to Vanilla Attention with high-order small amount error. In addition, the DBA is capable of capturing high-order relations in cross-attention problems. Experiments show that the DBA is able to achieve state-of-the-art performance with faster speed and lower memory consumption compared with previous models, highlighting its efficiency and effectiveness.

REFERENCES

Rosa I. Arriaga and Santosh Vempala. An algorithmic theory of learning: Robust concepts and random projection. *Machine Learning*, 63(2):161–182, 2006. ISSN 0885-6125 1573-0565. doi: 10.1007/s10994-006-6265-7.

Anthony Bagnall, Hoang Anh Dau, Jason Lines, Michael Flynn, James Large, Aaron Bostrom, Paul Southam, and Eamonn Keogh. The uea multivariate time series classification archive, 2018. *arXiv e-prints*, pp. arXiv:1811.00075, 2018.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv e-prints*, pp. arXiv:2004.05150, 2020.

Beidi Chen, Tri Dao, Eric Winsor, Zhao Song, Atri Rudra, and Christopher Ré. Scatterbrain: Unifying sparse and low-rank attention. *Advances in Neural Information Processing Systems*, 34: 17413–17426, 2021a.

Beidi Chen, Tri Dao, Kaizhao Liang, Jiaming Yang, Zhao Song, Atri Rudra, and Christopher Re. Pixelated butterfly: Simple and efficient sparse training for neural network models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=Nfl-iXa-y7R.

Yifan Chen, Qi Zeng, Heng Ji, and Yun Yang. Skyformer: Remodel self-attention with gaussian kernel and nystr\"om method. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 2122–2135. Curran Associates, Inc., 2021b. URL https://proceedings.neurips.cc/paper/2021/file/10a7cdd970fe135cf4f7bb55c0e3b59f-Paper.pdf.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv e-prints*, pp. arXiv:1904.10509, 2019.

Krzysztof Marcin Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Quincy Davis, Afroz Mohiuddin, Lukasz Kaiser, David Benjamin Belanger, Lucy J Colwell, and Adrian Weller. Rethinking attention with performers. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=Ua6zuk0WRH.

Z. H. Dai, Z. L. Yang, Y. M. Yang, J. Carbonell, Q. V. Le, and R. Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *57th Annual Meeting of the Association for Computational Linguistics (Acl 2019)*, pp. 2978–2988, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Y. Goyal, T. Khot, D. Summers-Stay, D. Batra, and D. Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6325–6334, 2017. ISBN 1063-6919. doi: 10.1109/CVPR.2017.670.

C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. Del Rio, M. Wiebe, P. Peterson, P. Gerard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant. Array programming with numpy. *Nature*, 585(7825):357–362, 2020. ISSN 1476-4687 (Electronic) 0028-0836 (Linking). doi: 10.1038/s41586-020-2649-2.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. ISBN 1063-6919. doi: 10.1109/CVPR.2016.90.

Weizhe Hua, Zihang Dai, Hanxiao Liu, and Quoc Le. Transformer quality in linear time. In Chaudhuri Kamalika, Jegelka Stefanie, Song Le, Szepesvari Csaba, Niu Gang, and Sabato Sivan (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Series Transformer Quality in Linear Time*, pp. 9099–9117. PMLR, 2022. ISBN ISBN.

Huaizu Jiang, Ishan Misra, Marcus Rohrbach, Erik Learned-Miller, and Xinlei Chen. In defense of grid features for visual question answering. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, Series In Defense of Grid Features for Visual Question Answering, pp. 10264–10273, 2020. ISBN ISBN. doi: 10.1109/cvpr42600.2020.01028.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In III Hal, Daumé and Singh Aarti (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Series Transformers are RNNs: Fast Autoregressive Transformers with Linear Attention*, pp. 5156–5165. PMLR, 2020. ISBN ISBN.

Jin-Hwa Kim, Jaehyun Jun, and Byoung-Tak Zhang. *Bilinear Attention Networks*, volume 31 of *Advances in Neural Information Processing Systems*. 2018. ISBN ****************.

Nikita Kitaev, Lukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkgNKkHtvB.

Devin Kreuzer, Dominique Beaini, Will Hamilton, Vincent Létourneau, and Prudencio Tossou. Rethinking graph transformers with spectral attention. *Advances in Neural Information Processing Systems*, 34:21618–21629, 2021.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1eA7AEtvS.

James Lee-Thorp, Joshua Ainslie, Ilya Eckstein, and Santiago Ontanon. Fnet: Mixing tokens with fourier transforms. Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pp. 4296–4313. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.naacl-main.319.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. In David Fleet, Tomas Pajdla, Bernt Schiele, and Tinne Tuytelaars (eds.), *Computer Vision – ECCV 2014*, pp. 740–755. Springer International Publishing, 2014. ISBN 978-3-319-10602-1.

W Johnson J Lindenstrauss and J Johnson. Extensions of lipschitz maps into a hilbert space. *Contemp. Math*, 26(189-206):2, 1984.

Drew Linsley, Junkyung Kim, Vijay Veerabadran, Charlie Windolf, and Thomas Serre. Learning long-range spatial dependencies with horizontal gated recurrent units. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, Series Learning long-range spatial dependencies with horizontal gated recurrent units, pp. 152–164. Curran Associates Inc., 2018. ISBN ISBN.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, Series Swin Transformer: Hierarchical Vision Transformer using Shifted Windows, pp. 9992–10002, 2021. ISBN ISBN. doi: 10.1109/iccv48922.2021.00986.

Shengjie Luo, Shanda Li, Tianle Cai, Di He, Dinglan Peng, Shuxin Zheng, Guolin Ke, Liwei Wang, and Tie-Yan Liu. Stable, fast and accurate: Kernelized attention with relative positional encoding. *Advances in Neural Information Processing Systems*, 34:22795–22807, 2021.

Xuezhe Ma, Xiang Kong, Sinong Wang, Chunting Zhou, Jonathan May, Hao Ma, and Luke Zettlemoyer. Luna: Linear unified nested attention. *Advances in Neural Information Processing Systems*, 34:2441–2453, 2021.

Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. Learning word vectors for sentiment analysis. Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies, pp. 142–150. Association for Computational Linguistics, 2011.

Nikita Nangia and Samuel Bowman. Listops: A diagnostic dataset for latent tree learning. Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Student Research Workshop, pp. 92–99. Association for Computational Linguistics, 2018. doi: 10.18653/v1/N18-4013.

Tam Minh Nguyen, Tan Minh Nguyen, Dung D. D. Le, Duy Khuong Nguyen, Viet-Anh Tran, Richard Baraniuk, Nhat Ho, and Stanley Osher. Improving transformers with probabilistic attention keys. In Chaudhuri Kamalika, Jegelka Stefanie, Song Le, Szepesvari Csaba, Niu Gang, and Sabato Sivan (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Series Improving Transformers with Probabilistic Attention Keys*, pp. 16595–16621. PMLR, 2022. ISBN ISBN.

Tan Nguyen, Vai Suliafu, Stanley Osher, Long Chen, and Bao Wang. Fmmformer: Efficient and flexible transformer via decomposed near-field and far-field attention. *Advances in neural information processing systems*, 34:29449–29463, 2021.

Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. Image transformer. In Dy Jennifer and Krause Andreas (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Series Image Transformer*, pp. 4055–4064. PMLR, 2018. ISBN ISBN.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. *PyTorch: an imperative style, high-performance deep learning library*, pp. Article 721. Curran Associates Inc., 2019.

Hao Peng, Nikolaos Pappas, Dani Yogatama, Roy Schwartz, Noah Smith, and Lingpeng Kong. Random feature attention. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=QtTKTdVrFBB.

Ofir Press, Noah Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=R8sQPpGCv0.

Bosheng Qin, Haoji Hu, and Yueting Zhuang. Deep residual weight-sharing attention network with low-rank attention for visual question answering. *IEEE Transactions on Multimedia*, pp. 1–1, 2022a. ISSN 1520-9210 1941-0077. doi: 10.1109/tmm.2022.3173131.

Zhen Qin, Weixuan Sun, Hui Deng, Dongxu Li, Yunshen Wei, Baohong Lv, Junjie Yan, Lingpeng Kong, and Yiran Zhong. cosformer: Rethinking softmax in attention. In *International Conference on Learning Representations*, 2022b. URL https://openreview.net/forum?id=Bl8CQrx2Up4.

Dragomir R. Radev, Pradeep Muthukrishnan, Vahed Qazvinian, and Amjad Abu-Jbara. The acl anthology network corpus. *Language Resources and Evaluation*, 47(4):919–944, 2013. ISSN 1574-020X 1574-0218. doi: 10.1007/s10579-012-9211-2.

Tanzila Rahman, Shih-Han Chou, Leonid Sigal, and Giuseppe Carenini. An improved attention for visual question answering. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, Series An Improved Attention for Visual Question Answering, pp. 1653–1662, 2021. ISBN ISBN. doi: 10.1109/cvprw53098.2021.00181.

Aurko Roy, Mohammad Saffar, Ashish Vaswani, and David Grangier. Efficient content-based sparse attention with routing transformers. *Transactions of the Association for Computational Linguistics*, 9:53–68, 2021. ISSN 2307-387X. doi: 10.1162/tacl_a_00353.

Zhiqing Sun, Yiming Yang, and Shinjae Yoo. Sparse attention with learning to hash. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=VGnOJhd5Q1q`.

Chao-Hong Tan, Qian Chen, Wen Wang, Qinglin Zhang, Siqi Zheng, and Zhen-Hua Ling. Ponet: Pooling network for efficient token mixing in long sequences. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=9jInD9JjicF`.

Yi Tay, Dara Bahri, Liu Yang, Donald Metzler, and Da-Cheng Juan. Sparse sinkhorn attention. In III Hal, Daumé and Singh Aarti (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Series Sparse Sinkhorn Attention*, pp. 9438–9447. PMLR, 2020. ISBN ISBN.

Yi Tay, Dara Bahri, Donald Metzler, Da-Cheng Juan, Zhe Zhao, and Che Zheng. Synthesizer: Rethinking self-attention for transformer models. In Meila Marina and Zhang Tong (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Series Synthesizer: Rethinking Self-Attention for Transformer Models*, pp. 10183–10192. PMLR, 2021a. ISBN ISBN.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena : A benchmark for efficient transformers. In *International Conference on Learning Representations*, 2021b. URL `https://openreview.net/forum?id=qVyeW-grC2k`.

Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey. *ACM Computing Surveys*, 2022. ISSN 0360-0300 1557-7341. doi: 10.1145/3530811.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, Series Attention is all you need, pp. 6000–6010. Curran Associates Inc., 2017. ISBN ISBN.

Ningning Wang, Guobing Gan, Peng Zhang, Shuai Zhang, Junqiu Wei, Qun Liu, and Xin Jiang. Clusterformer: Neural clustering attention for efficient and effective transformer. Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 2390–2402. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.170.

Sinong Wang, Belinda Z. Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv e-prints*, pp. arXiv:2006.04768, 2020.

Wenxiao Wang, Lu Yao, Long Chen, Binbin Lin, Deng Cai, Xiaofei He, and Wei Liu. Crossformer: A versatile vision transformer hinging on cross-scale attention. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=_PHymLIxuI`.

Haixu Wu, Jialong Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Flowformer: Linearizing transformers with conservation flows. In Chaudhuri Kamalika, Jegelka Stefanie, Song Le, Szepesvari Csaba, Niu Gang, and Sabato Sivan (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Series Flowformer: Linearizing Transformers with Conservation Flows*, pp. 24226–24242. PMLR, 2022. ISBN ISBN.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn Fung, Yin Li, and Vikas Singh. Nyströmformer: A nyström-based algorithm for approximating self-attention. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(16):14138–14148, 2021.

Jianwei Yang, Chunyuan Li, Pengchuan Zhang, Xiyang Dai, Bin Xiao, Lu Yuan, and Jianfeng Gao. Focal attention for long-range interactions in vision transformers. *Advances in Neural Information Processing Systems*, 34:30008–30022, 2021.

Z. Yu, J. Yu, Y. Cui, D. Tao, and Q. Tian. Deep modular co-attention networks for visual question answering. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6274–6283, 2019. ISBN 2575-7075. doi: 10.1109/CVPR.2019.00644.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, and Li Yang. Big bird: Transformers for longer sequences. *Advances in Neural Information Processing Systems*, 33:17283–17297, 2020.

Zhanpeng Zeng, Yunyang Xiong, Sathya Ravi, Shailesh Acharya, Glenn M Fung, and Vikas Singh. You only sample (almost) once: Linear cost self-attention via bernoulli sampling. In Meila Marina and Zhang Tong (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Series You Only Sample (Almost) Once: Linear Cost Self-Attention Via Bernoulli Sampling*, pp. 12321–12332. PMLR, 2021. ISBN ISBN.

George Zerveas, Srideepika Jayaraman, Dhaval Patel, Anuradha Bhamidipaty, and Carsten Eickhoff. A transformer-based framework for multivariate time series representation learning. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery Data Mining*, Series A Transformer-based Framework for Multivariate Time Series Representation Learning, pp. 2114–2124. Association for Computing Machinery, 2021. ISBN ISBN. doi: 10.1145/3447548.3467401.

Hang Zhang, Yeyun Gong, Yelong Shen, Weisheng Li, Jiancheng Lv, Nan Duan, and Weizhu Chen. Poolingformer: Long document modeling with pooling attention. In Meila Marina and Zhang Tong (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Series Poolingformer: Long Document Modeling with Pooling Attention*, pp. 12437–12446. PMLR, 2021. ISBN ISBN.

Lin Zheng, Chong Wang, and Lingpeng Kong. Linear complexity randomized self-attention mechanism. In Chaudhuri Kamalika, Jegelka Stefanie, Song Le, Szepesvari Csaba, Niu Gang, and Sabato Sivan (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Series Linear Complexity Randomized Self-attention Mechanism*, pp. 27011–27041. PMLR, 2022. ISBN ISBN.

Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. Fedformer: Frequency enhanced decomposed transformer for long-term series forecasting. In Chaudhuri Kamalika, Jegelka Stefanie, Song Le, Szepesvari Csaba, Niu Gang, and Sabato Sivan (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Series FEDformer: Frequency Enhanced Decomposed Transformer for Long-term Series Forecasting*, pp. 27268–27286. PMLR, 2022. ISBN ISBN.

Chen Zhu, Wei Ping, Chaowei Xiao, Mohammad Shoeybi, Tom Goldstein, Anima Anandkumar, and Bryan Catanzaro. Long-short transformer: Efficient transformers for language and vision. *Advances in Neural Information Processing Systems*, 34:17723–17736, 2021.

Yimeng Zhuang, Jing Zhang, and Mei Tu. Long-range sequence modeling with predictable sparse attention. Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 234–243. Association for Computational Linguistics, 2022. doi: 10.18653/v1/2022.acl-long.19.

A APPENDIX

A.1 DATASETS

LRA (Tay et al., 2021b) is a popular benchmark to test the efficiency of transformers in long sequence conditions, containing a suite of tasks (ListOps (Nangia & Bowman, 2018), byte-level text classification (Maas et al., 2011), document retrieval (Radev et al., 2013), pixel-level image classification (Krizhevsky & Hinton, 2009), and Pathfinder (Linsley et al., 2018)) with sequence length ranging from 1k to 4k.

UEA multivariate time series classification archive (Bagnall et al., 2018) is a collection of datasets to evaluate the time series classification algorithms, which contains a wide range of problems in various sequence length conditions.

VQA-v2 (Goyal et al., 2017) is a popular benchmark for multi-modal models, containing 1.1 million human-labeled image-question pairs with around 13 million associated answers on the 200k images from the Microsoft COCO dataset (Lin et al., 2014), and it is split into the *train*, *val*, and *test* set.

Table 5: Summary of experiment benchmarks.

Dataset	Task	Sequence Length
LRA (Tay et al., 2021b)	Long Sequence Modeling	1k-4k
UEA (Bagnall et al., 2018)	Time Series	29-1751
VQA-v2 (Goyal et al., 2017)	Visual Question Answering	5-625

A.2 EXPERIMENT SETTINGS

All the experiments are conducted using PyTorch (Paszke et al., 2019) and Numpy (Harris et al., 2020) with Nvidia GPU. For the experiment on the Long-Range Arena, the DBA follows the configurations as (Ma et al., 2021), where all models use the same data processing strategy and model architecture for fair comparisons. For the experiment on the UEA multivariate time series classification archive, we select 10 multivariate datasets similar to (Wu et al., 2022) and use the same configurations following (Zerveas et al., 2021). For the experiments on the VQA-v2 dataset, we use the ALBERT (Lan et al., 2020) to extract question features, and we use the gird image features (Jiang et al., 2020) obtained from a Resnet-152 model (He et al., 2016) in the vision part. After cross-attention interactions, both language and vision parts perform intra-modality fusion following (Yu et al., 2019), and the final answer is predicted via addition. We set the φ as the softmax function. The detailed settings with hyper-parameters are listed in Tables 6, 7, and 8.

Table 6: Experiment settings on the LRA.

Task	Depth	Heads	d	d_{ffn}	d_p	d_{in}
ListOps	6	8	512	2048	16	24
Text	4	4	256	1024	16	24
Retrieval	4	4	128	512	16	24
Image	1	8	64	128	16	24
Pathfinder	1	4	128	128	16	24

Table 7: Experiment settings on the UEA multivariate time series classification archive.

Task	Depth	Heads	d	d_{ffn}	d_p	d_{in}
Ethanolconcentration	1	8	64	256	16	24
Facedetection	3	8	128	256	16	24
Handwriting	1	8	128	256	16	24
Heartbeat	1	8	64	256	16	24
Japanesevowels	3	8	128	256	16	24
Pems-Sf	1	8	128	512	16	24
Selfregulationscp1	3	8	128	256	16	24
Selfregulationscp2	3	8	128	256	16	24
Spokenarabicdigits	3	8	128	256	16	24
Uwavegesturelibrary	3	16	256	256	16	24

Table 8: Experiment settings on the VQA-v2.

Task	Depth	Heads	d	d_{ffn}	d_p	d_{in}
VQA-v2	3	8	256	1024	24	64