A Closer Look at the Worst-case Behavior of Multi-armed Bandit Algorithms

Abstract

One of the key drivers of complexity in the classical (stochastic) multi-armed bandit (MAB) problem is the difference between mean rewards in the top two arms, also known as the instance gap. The celebrated Upper Confidence Bound (UCB) policy is among the simplest optimism-based MAB algorithms that naturally adapts to this gap: for a horizon of play n, it achieves optimal $\mathcal{O}(\log n)$ regret in instances with "large" gaps, and a near-optimal $\mathcal{O}(\sqrt{n \log n})$ minimax regret when the gap can be arbitrarily "small." This paper provides new results on the *arm-sampling* behavior of UCB, leading to several important insights. Among these, it is shown that arm-sampling rates under UCB are asymptotically deterministic, *regardless* of the problem complexity. This discovery facilitates new sharp asymptotics and a novel alternative proof for the $\mathcal{O}(\sqrt{n \log n})$ minimax regret of UCB. Furthermore, the paper also provides the first complete process-level characterization of the MAB problem in the conventional *diffusion scaling*. Among other things, the "small" gap worst-case lens adopted in this paper also reveals profound distinctions between the behavior of UCB and Thompson Sampling, such as an *incomplete learning* phenomenon characteristic of the latter.

1   Introduction

Background and motivation. The MAB paradigm provides a succinct abstraction of the quintessential *exploration* vs. *exploitation* trade-offs inherent in many sequential decision making problems. This has origns in clinical trial studies dating back to 1933 [23] which gave rise to the earliest known MAB heuristic, Thompson Sampling [1]. Today, the MAB problem manifests itself in various forms with applications ranging from dynamic pricing and online auctions to packet routing, scheduling, e-commerce and matching markets among others (see [8] for a comprehensive survey of different formulations). In the canonical stochastic MAB problem, a decision maker (DM) pulls one of K *arms* sequentially at each time $t \in \{1, 2, ...\}$, and receives a random payoff drawn according to an arm-dependent distribution. The DM, oblivious to the statistical properties of the arms, must balance exploring new arms and exploiting the best arm played thus far in order to maximize her cumulative payoff over the horizon of play. This objective is equivalent to minimizing the *regret* relative to an oracle with perfect ex ante knowledge of the optimal arm (the one with the highest mean reward). The classical stochastic MAB problem is fully specified by the tuple $\left((\mathcal{P}_i)_{1 \leqslant i \leqslant K}, n\right)$, where $\mathcal{P}_i$ denotes the distribution of rewards associated with the i^{th} arm, and n the horizon of play.

The statistical complexity of regret minimization in the stochastic MAB problem is governed by a key primitive called the *gap*, denoted by Δ, which accounts for the difference between the top two arm mean rewards in the problem. For a "well-separated" or "large gap" instance, i.e., a fixed Δ bounded away from 0, the seminal paper [18] showed that the order of the smallest achievable regret

is logarithmic in the horizon. There has been a plethora of subsequent work involving algorithms which can be fine-tuned to achieve a regret arbitrarily close to the optimal rate discovered in [18] (see [5, 12, 11, 2, 3], etc., for a few notable examples). On the other hand, no algorithm can achieve an expected regret smaller than $C\sqrt{n}$ for a fixed n (the constant hides dependence on the number of arms) *uniformly* over all problem instances (also called *minimax* regret); see, e.g., [19], Chapter 15. The *saddle-point* in this minimax formulation occurs at a gap that satisfies $\Delta \asymp 1/\sqrt{n}$. This has a natural interpretation: approximately $1/\Delta^2$ samples are required to distinguish between two distributions with means separated by Δ; at the $1/\sqrt{n}$-scale, it becomes statistically impossible to distinguish between samples from the top two arms within n rounds of play. If the gap is smaller, despite the increased difficulty in the hypothesis test, the problem becomes "easier" from a regret perspective. Thus, $\Delta \asymp 1/\sqrt{n}$ is the statistically "hardest" scale for regret minimization. A number of popular algorithms achieve the $\sqrt{n}$ minimax-optimal rate (modulo constants), see, e.g., [3, 2], and many more do this within poly-logarithmic factors in n. Many of these are variations of the celebrated upper confidence bound algorithms, e.g., UCB1 [6], that achieve a minimax regret of $\mathcal{O}\left(\sqrt{n\log n}\right)$, and at the same time also deliver the logarithmic regret achievable in the instance-dependent setting of [18].

A major driver of the regret performance of an algorithm is its arm-sampling characteristics. For example, in the instance-dependent (large gap) setting, optimal regret guarantees imply that the fraction of time the optimal arm(s) are played approaches 1 in probability, as n grows large. However, this fails to provide any meaningful insights as to the distribution of arm-pulls for smaller gaps, e.g., the $\Delta \asymp 1/\sqrt{n}$ "small gap" that governs the "worst-case" instance-independent setting.

An illustrative numerical example involving "small gap." Consider an A/B testing problem (e.g., a vaccine clinical trial) where the experimenter is faced with two competing objectives: first, to estimate the efficacy of each alternative with the best possible precision given a budget of samples, and second, keeping the overall cost of the experiment low. This is a fundamentally hard task and algorithms incurring a low cumulative cost typically spend little time exploring sub-optimal alternatives, resulting in a degraded estimation precision (see, e.g., [4]). In other words, algorithms tailored for (cumulative) regret minimization may lack *statistical power* [24]. While this trade-off is unavoidable in "well-separated" instances, numerical evidence suggests a plausible resolution in instances with "small" gaps as illustrated below. For example, such a situation might arise in trials conducted using two similarly efficacious vaccines (abstracted away as $\Delta \approx 0$). To illustrate the point more vividly, consider the case where Δ is exactly 0 (of course, this information is not known to the experimenter). This setting is numerically illustrated in Figure 1, which shows the empirical distribution of $N_1(n)/n$ (the fraction of time arm 1 is played until time n) in a two-armed bandit with $\Delta = 0$, under two different algorithms (UCB and Thompson Sampling), and reward configurations.

Figure 1: **Incomplete learning under Thompson Sampling.** A two-armed bandit with arms having Bernoulli(q) rewards each: Histograms show the empirical (probability) distribution of $N_1(n)/n$ for $n = 10,000$ pulls, plotted using 20,000 experiments. Algorithms: UCB1 [6], TS with Beta priors [1].

A desirable property of the outcome in this setting is to have a *linear allocation* of the sampling budget *per arm* on almost every sample-path of the algorithm, as this leads to "complete learning:" an algorithm's ability to discern statistical indistinguishability of the arm-means, and induce a "balanced" allocation in that event. However, despite the simplicity of the zero-gap scenario, it is far from obvious whether the aforementioned property may be satisfied for standard bandit algorithms such as UCB and Thompson Sampling. Indeed, Figure 1 exhibits a striking difference between the two. The concentration around $1/2$ observable in Figure 1(a) indicates that UCB results in an approximately "balanced" sample-split, i.e., the allocation is roughly $n/2$ per arm for large n

(and this is observed for "most" sample-paths). In fact, we will later see that the "bell curve" in Figure 1(a) eventually collapses into the Dirac measure at $1/2$ (Theorem 1). On the other hand, under Thompson Sampling, the allocation of samples across arms *may* be arbitrarily "imbalanced" despite the arms being statistically identical, as seen in Figure 1(b) (see, for contrast, Figure 1(c), where the allocation is perfectly "balanced"). Namely, the distribution of the posterior *may* be such that arm 1 is allocated anywhere from almost no sampling effort all the way to receiving almost the entire sampling budget, as Figure 1(b) suggests. Non-degeneracy of arm-sampling rates is observable also under the more widely used version of the algorithm that is based on Gaussian priors and Gaussian likelihoods (Algorithm 2 in [2]); see Figure 2(a). Such behavior can be detrimental for ex post causal inference in the general A/B testing context, and the vaccine testing problem referenced earlier. This is demonstrated via an instructional example of a two-armed bandit with one deterministic reference arm (aka the "one-armed" bandit paradigm), illustrated in Figure 2, and discussed below.

A numerical example illustrating inference implications. Consider a model where arm 1 returns a constant reward of 0.5, while arm 2 yields rewards distributed as Bernoulli(0.5). In this setup, the estimate of the gap Δ (*average treatment effect* in causal inference parlance) after n rounds of play is given by $\hat{\Delta} = \bar{X}_2(n) - 0.5$, where $\bar{X}_2(n)$ denotes the empirical mean reward of arm 2 at time n. The $\mathcal{Z}$ statistic associated with this gap estimator is given by $\mathcal{Z} = 2\sqrt{N_2(n)}\hat{\Delta}$, where $N_2(n)$ is the visitation count of arm 2 at time n. In the absence of any sample-adaptivity in the arm 2 data, results from classical statistics such as the Central Limit Theorem (CLT) would posit an asymptotically Normal distribution for $\mathcal{Z}$. However, since the algorithms that play the arms are adaptive in nature, e.g., UCB and Thompson Sampling, asymptotic-normality may no longer be guaranteed. Indeed, the numerical evidence in Figure 2(b) strongly points to a significant departure from asymptotic-normality of the $\mathcal{Z}$ statistic associated with the gap estimator under Thompson Sampling (TS). Non-normality of the $\mathcal{Z}$ statistic can be problematic for inferential tasks, e.g., it can lead to statistically unsupported inferences in the binary hypothesis test $\mathcal{H}_0 : \Delta = 0$ vs. $\mathcal{H}_1 : \Delta \neq 0$ performed using confidence intervals constructed as per the conventional CLT approximation. In sharp contrast, our work shows that UCB satisfies a certain "balanced" sampling property (such as that in Figure 1(a)) in instances with "small" gaps, formally stated as Theorem 1, that drives the $\mathcal{Z}$ statistic towards asymptotic-normality in the aforementioned binary hypothesis testing example (asymptotic-normality being a consequence of Theorem 4). Furthermore, since the $\sqrt{n}$-normalized "stochastic" regret (defined in (1) in §2) equals $-\left(\sqrt{N_2(n)/(4n)}\right)\mathcal{Z}$, it follows that this too, satisfies asymptotic-normality under UCB (due to Theorem 4, in conjunction with Theorem 1). These properties are evident in Figure 2(c) below, and signal reliability of ex post causal inference (under classical assumptions like validity of CLT) from "small gap" data collected by UCB vis-à-vis Thompson Sampling (TS). The veracity of inference under TS maybe doubtful even in the limit of infinite data, as Figure 2(b) suggests.

(a) Distribution of $N_1(n)/n$ (b) Departure from CLT   (c) Asymptotic normality per CLT

Figure 2: **Failure of CLT under TS.** A two-armed bandit with $\Delta = 0$: Arm 1 returns a constant reward of 0.5, and arm 2 yields rewards distributed as Bernoulli(0.5). In (a), the histogram shows the empirical (probability) distribution of $N_1(n)/n$. Algorithms: TS (Algorithm 2 in [2]) and UCB (UCB1 in [6]). All histograms have $n = 10{,}000$ pulls, and are plotted using $\aleph = 20{,}000$ experiments.

While traditional literature has focused primarily on the expected regret minimization problem for the stochastic MAB model, there has been recent interest in finer-grain properties of popular MAB algorithms in terms of their arm-sampling behavior. As already discussed, this has significance from the standpoint of ex post causal inference using data collected adaptively by bandit algorithms (see, e.g., [26, 14, 25], etc., and references therein for recent developments), algorithmic fairness in the

broader context of fairness in machine learning (see [21] for a survey), as well as novel formulations of the MAB problem such as [17]. Below, we discuss extant literature relevant to our line of work.

Previous work. The study of "well-separated" instances, or the *large gap* regime, is supported by rich literature. For example, [5] provides high-probability bounds on arm-sampling rates under a parametric family of UCB algorithms. However, as the gap diminishes, leading to the so called *small gap* regime, the aforementioned bounds become vacuous. The understanding of arm-sampling behavior remains relatively under-studied here even for popular algorithms such as UCB and Thompson Sampling. This regime is of special interest in that it also covers the classical *diffusion scaling*[1], where $\Delta \asymp 1/\sqrt{n}$, which as discussed earlier, corresponds to instances that statistically constitute the "worst-case" for hypothesis testing and regret minimization. Recently, a partial diffuion-limit characterization of the arm-sampling distribution under a version of Thompson Sampling with horizon-dependent prior variances[2], was provided in [25] as a solution to a certain stochastic differential equation (SDE). The numerical solution to said SDE was observed to have a non-degenerate distribution on $[0, 1]$. Similar numerical observations on non-degeneracy of the arm-sampling distribution also under standard versions of Thompson Sampling were reported in [9, 17], among others, albeit limited only to the special case of $\Delta = 0$, and absent a theoretical explanation for the aforementioned observations. Thus, outside of the so called "easy" problems, where Δ is bounded away from 0 by an absolute constant, theoretical understanding of the sampling behavior of bandit algorithms remains as such an open area of research.

Contributions. In this paper, we provide the first complete asymptotic characterization of arm-sampling distributions under canonical UCB (Algorithm 1) as a function of the gap Δ (Theorem 1). This gives rise to a fundamental insight: arm-sampling rates are asymptotically deterministic under UCB regardless of the hardness of the instance. We also provide the first theoretical explanation for an "incomplete learning" phenomenon under Thompson Sampling (Algorithm 2) alluded to in Figure 1, as well as a sharp dichotomy between Thompson Sampling and UCB evident therein (Theorem 2). This result earmarks an "instability" of Thompson Sampling in terms of the limiting arm-sampling distribution. As a sequel to Theorem 1, we provide the first *complete* characterization of the worst-case performance of canonical UCB (Theorem 3). One consequence is that the $\mathcal{O}\left(\sqrt{n \log n}\right)$ minimax regret of UCB is strictly unimprovable in a precise sense. Moreover, our work also leads to the first process-level characterization of the two-armed bandit problem under canonical UCB in the classical diffusion limit, according to which a suitably normalized cumulative reward process converges in law to a Brownian motion with fully characterized drift and infinitesimal variance (Theorem 4). To the best of our knowledge, this is the first such characterization of UCB-type algorithms. Theorem 4 facilitates a complete distribution-level characterization of UCB's diffusion-limit regret, thereby providing sharp insights as to the problem's minimax complexity. Such distribution-level information may also be useful for a variety of inferential tasks, e.g., construction of confidence intervals (see the binary hypothesis testing example referenced in Figure 2(c)), among others. We believe our results may also present new design considerations, in particular, how to achieve, loosely speaking, the "best of both worlds" for Thompson Sampling, by addressing its "small gap" instability. Lastly, we note that our proof techniques are markedly different from the conventional methodology adopted in MAB literature ([5, 8, 2]), and may be of independent interest in the study of related learning algorithms.

Organization of the paper. A formal description of the model and the canonical UCB algorithm is provided in §2. All theoretical propositions are stated in §3, along with a high-level overview of their scope and proof sketch; detailed proofs and ancillary results are relegated to the appendices. Finally, concluding remarks and open problems are presented in §4.

2 The model and notation

The technical development in this paper will focus on the two-armed problem purely for expositional reasons; we remark on extensions to the general K-armed setting at the end in §4. The two-armed setting encapsulates the core statistical complexity of the MAB problem, as well as concisely highlights the key novelties in our approach. Before describing the model formally, we introduce the following asymptotic notations.

---

[1]This is a standard technique for performance evaluation of stochastic systems, commonly used in the operations research and mathematics literature, see, e.g., [13].

[2]Assumed to be vanishing in n; standard versions of the algorithm involve fixed (positive) prior variances.

Notations. We say $f(n) = o\left(g(n)\right)$ or $g(n) = \omega\left(f(n)\right)$ if $\lim_{n\to\infty} \frac{f(n)}{g(n)} = 0$. Similarly, $f(n) = \mathcal{O}\left(g(n)\right)$ or $g(n) = \Omega\left(f(n)\right)$ if $\limsup_{n\to\infty} \left|\frac{f(n)}{g(n)}\right| \leqslant C$ for some constant C. If $f(n) = \mathcal{O}\left((g(n))\right)$ and $f(n) = \Omega\left((g(n))\right)$ hold simultaneously, we say $f(n) = \Theta\left(g(n)\right)$, or $f(n) \asymp g(n)$, and we write $f(n) \sim g(n)$ in the special case where $\lim_{n\to\infty} \frac{f(n)}{g(n)} = 1$. If either sequence $f(n)$ or $g(n)$ is random, and one of the aforementioned ratio conditions holds in probability, we use the subscript p with the corresponding Landau symbol. For example, $f(n) = o_p\left(g(n)\right)$ if $f(n)/g(n) \xrightarrow{p} 0$ as $n \to \infty$. Lastly, the notation '$\Rightarrow$' will be used for weak convergence.

The model. The arms are indexed by $\{1, 2\}$. Each arm $i \in \{1, 2\}$ is characterized by a reward distribution $\mathcal{P}_i$ supported on $[0, 1]$ with mean μ_i. The difference between the two mean rewards, aka the *gap*, is given by $\Delta = |\mu_1 - \mu_2|$; as discussed earlier, this captures the *hardness* of an instance. The sequence of rewards associated with the *first m pulls* of arm i is denoted by $(X_{i,j})_{1 \leqslant j \leqslant m}$. The rewards are assumed to be i.i.d. in time, and independent across arms.[3] The number of pulls of arm i up to (and including) time t is denoted by $N_i(t)$. A policy $\pi := (\pi_t)_{t \in \mathbb{N}}$ is an adapted sequence that prescribes pulling an arm $\pi_t \in \mathcal{S}$ at time t, where $\mathcal{S}$ denotes the probability simplex on $\{1, 2\}$. The natural filtration at time t is given by $\mathcal{F}_t := \sigma\left\{(\pi_s)_{s \leqslant t}, \left((X_{i,j})_{j \leqslant N_i(t)} : i = 1, 2\right)\right\}$. The stochastic regret of policy π after n plays, denoted by R_n^π, is given by

$$R_n^\pi := \sum_{t=1}^n \left[\max\left(\mu_1, \mu_2\right) - X_{\pi_t, N_{\pi_t}(t)}\right]. \tag{1}$$

The decision maker is interested in the problem of minimizing the *expected regret*, given by

$$\inf_{\pi \in \Pi} \mathbb{E} R_n^\pi,$$

where Π is the set of policies satisfying the non-anticipation property $\pi_t : \mathcal{F}_{t-1} \to \mathcal{S}$, $1 \leqslant t \leqslant n$, and the expectation is w.r.t. the randomness in reward realizations as well as possible randomness in the policy π. In this paper, we will focus primarily on the canonical UCB policy given by Algorithm 1 below. This policy is parameterized by an exploration coefficient ρ, which controls its arm-exploring rate. The standard UCB1 policy [6] corresponds to Algorithm 1 with $\rho = 2$; the effect of ρ on the expected and high-probability regret bounds of the algorithm is well-documented in [5] for problems with a "large gap." In what follows, $\bar{X}_i(t-1)$ denotes the empirical mean reward from arm $i \in \{1, 2\}$ at time $t - 1$, i.e., $\bar{X}_i(t-1) := \frac{\sum_{j=1}^{N_i(t-1)} X_{i,j}}{N_i(t-1)}$.

Algorithm 1 The canonical UCB policy for two-armed bandits.

1: **Input:** Exploration coefficient $\rho \in \mathbb{R}_+$.
2: At $t = 1, 2$, play each arm $i \in \{1, 2\}$ once.
3: **for** $t \in \{3, 4, ...\}$ **do**
4:     Play arm $\pi_t \in \arg\max_{i \in \{1,2\}} \left(\bar{X}_i(t-1) + \sqrt{\frac{\rho \log(t-1)}{N_i(t-1)}}\right)$.

---

3 Main results

Algorithm 1 is known to achieve $\mathbb{E} R_n^\pi = \mathcal{O}\left(\log n\right)$ in the instance-dependent setting, and $\mathbb{E} R_n^\pi = \mathcal{O}\left(\sqrt{n \log n}\right)$ in the "small gap" minimax setting. The primary focus of this paper is on the distribution of arm-sampling rates, i.e., $N_i(n)/n$, $i \in \{1, 2\}$. Our main results are split across two sub-sections; §3.1 examines the behavior of UCB (Algorithm 1) as well as another popular bandit algorithm, Thompson Sampling (specified in Algorithm 2). §3.2 is dedicated to results on the (stochastic) regret of Algorithm 1 under the $\Delta \asymp \sqrt{(\log n)/n}$ "worst-case" gap and the $\Delta \asymp 1/\sqrt{n}$ "diffusion-scaled" gap.

3.1 Asymptotics of arm-sampling rates

Theorem 1 (Arm-sampling rates under UCB) *Let $i^* \in \arg\max \{\mu_i : i = 1, 2\}$ with ties broken arbitrarily. Then, the following results hold for arm i^* as $n \to \infty$ under Algorithm 1 with $\rho > 1$:*

---

[3]These assumptions can be relaxed in the spirit of [6]; our results also extend to sub-Gaussian rewards.

(I) *"Large gap:" If* $\Delta = \omega\left(\sqrt{\frac{\log n}{n}}\right)$, *then* $N_{i^*}(n)/n \xrightarrow{p} 1$.

(II) *"Small gap:" If* $\Delta = o\left(\sqrt{\frac{\log n}{n}}\right)$, *then* $N_{i^*}(n)/n \xrightarrow{p} 1/2$.

(III) *"Moderate gap:" If* $\Delta \sim \sqrt{\frac{\theta \log n}{n}}$ *for some fixed* $\theta \geqslant 0$, *then* $N_{i^*}(n)/n \xrightarrow{p} \lambda_\rho^*(\theta)$, *where the limit is the unique solution (in* λ*) to*

$$\frac{1}{\sqrt{1-\lambda}} - \frac{1}{\sqrt{\lambda}} = \sqrt{\frac{\theta}{\rho}}, \tag{2}$$

and is monotone increasing in θ, *with* $\lambda_\rho^*(0) = 1/2$ *and* $\lambda_\rho^*(\theta) \to 1$ *as* $\theta \to \infty$.

Remark 1 (Permissible values of ρ in Algorithm 1) *For $\rho > 1$, the expected regret of the policy π given by Algorithm 1 is bounded as $\mathbb{E}R_n^\pi \leqslant C\rho\left(\frac{\log n}{\Delta} + \frac{\Delta}{\rho - 1}\right)$ for some absolute constant C (see [5], Theorem 7). Theorem 1 is restricted to $\rho > 1$ to ensure that $\mathbb{E}R_n^\pi$ remains non-trivially bounded.*

Discussion and intuition. Theorem 1 essentially asserts that the sampling rates $N_i(n)/n$, $i \in \{1, 2\}$ are asymptotically deterministic in probability under canonical UCB; Δ only serves to determine the value of the limiting constant. The "moderate" gap regime offers a continuous interpolation from instances with zero gaps to instances with "large" gaps as θ sweeps over $\mathbb{R}_+$ in that $\lambda_\rho^*(\theta)$ increases monotonically from $1/2$ at $\theta = 0$ to 1 at $\theta = \infty$, consistent with intuition. The special case of $\theta = 0$ is numerically illustrated in Figure 1(a). The tails of $N_{i^*}(n)/n$ decay polynomially fast near the end points of the interval $[0, 1]$ with the best possible rate approaching $\mathcal{O}\left(n^{-3}\right)$, occurring for $\theta = 0$. However, as $N_{i^*}(n)/n$ approaches its limit, convergence becomes slower and is dominated by fatter $\Theta\left(\sqrt{\frac{\log \log n}{\log n}}\right)$ tails. The behavior in this regime is regulated by the $\mathcal{O}\left(\sqrt{n \log \log n}\right)$ envelope of the zero-drift random walk process driving the algorithm's regret (see proof of Theorem 1 for details).

Proof sketch. To provide the most intuitive explanation, we pivot to the special case of $\Delta = 0$. The natural candidate then for the limit of the empirical sampling rate is $1/2$. On a high-level, the proof relies on polynomially decaying bounds in n for ϵ-deviations of the form $\mathbb{P}\left(\left|\frac{N_{i^*}(n)}{n} - \frac{1}{2}\right| \geqslant \epsilon\right)$ derived using the standard trick for bounding the number of pulls of any arm on a given sample-path (see, e.g., [5] for details). This enables a meta-conclusion using the Borel-Cantelli Lemma, that sampling rates are eventually linear in n, almost surely. However, this only achieves half the goal since the aforementioned tail bounds turn vacuous for ϵ outside the vicinity of $1/2$. Extension to the full generality of $\epsilon > 0$ is achieved using the Law of the Iterated Logarithm (see [10], Theorem 8.5.2), together with the previous meta-conclusion. The proof for a general Δ proceeds along similar lines, albeit guessing a candidate limit for $N_{i^*}(n)/n$ is non-trivial; a closed-form expression for $\lambda_\rho^*(\theta)$ is provided in Appendix A. Refer to Appendix D,E,F for the complete proof of Theorem 1. $\qquad\square$

Remark 2 (Possible generalizations of Theorem 1) *A simple extension to the K-armed setting is provided in Appendix B as Theorem 5. The behavior of UCB policies is largely governed by their optimistic bias. While Theorem 1 only covers the generic UCB policy with $\sqrt{\rho \log t}$ bias, results of the form $N_i(n)/n \xrightarrow{p} c_i$ for some $c_i \in (0, 1)$ continue to hold also under smaller $\omega\left(\sqrt{\rho \log \log t}\right)$ bias (driven by the Law of the Iterated Logarithm). We believe this observation will be useful when examining more complicated UCB-inspired policies such as KL-UCB [11], DMED [16], etc.*

What about Thompson Sampling? Results such as those discussed above for other popular adaptive algorithms like Thompson Sampling[4] are only arable in "well-separated" instances where $N_{i^*}(n)/n \xrightarrow{p} 1$ as $n \to \infty$ follows as a trivial consequence of its $\mathcal{O}\left(\sqrt{n}\right)$ minimax regret bound [2]. For smaller gaps, theoretical understanding of the distribution of arm-pulls under Thompson Sampling remains largely absent even for its most widely-studied variants. In this paper, we provide a first result in this direction: Theorem 2 formalizes a revealing observation for classical Thompson

---

[4]This is the version based on Gaussian priors and Gaussian likelihoods, not the classical version based on Beta priors and Bernoulli likelihoods which has a minimax regret of $\mathcal{O}\left(\sqrt{n \log n}\right)$ [2].

Sampling (Algorithm 2) in instances with zero gap, and elucidates its instability in view of the numerical evidence reported in Figure 1(b) and 1(c). This result also offers an explanation for the sharp contrast with the statistical behavior of canonical UCB (Algorithm 1) à la Theorem 1, also evident from Figure 1(a). In what follows, rewards are assumed to be Bernoulli, and S_i (respectively F_i) counts the number of successes/1's (respectively failures/0's) associated with arm $i \in \{1, 2\}$.

Algorithm 2 Thompson Sampling for the two-armed Bernoulli bandit.

1: **Initialize:** Number of successes (1's) and failures (0's) for each arm $i \in \{1, 2\}$, $(S_i, F_i) = (0, 0)$.
2: **for** $t \in \{1, 2, ...\}$ **do**
3:     Sample for each $i \in \{1, 2\}$, $\mathcal{T}_i \sim \text{Beta}(S_i + 1, F_i + 1)$.
4:     Play arm $\pi_t \in \arg\max_{i \in \{1,2\}} \mathcal{T}_i$ and observe reward $r_t \in \{0, 1\}$.
5:     Update success-failure counts: $S_{\pi_t} \leftarrow S_{\pi_t} + r_t$, $F_{\pi_t} \leftarrow F_{\pi_t} + 1 - r_t$.

Theorem 2 (Incomplete learning under Thompson Sampling) *In a two-armed model where both arms yield rewards distributed as Bernoulli(q), the following holds under Algorithm 2 as $n \to \infty$:*

(I) If $q = 0$, then $N_1(n)/n \Rightarrow 1/2$.

(II) If $q = 1$, then $N_1(n)/n \Rightarrow$ Uniform distribution on $[0, 1]$.

Proof sketch. The proof of Theorem 2 relies on a careful application of two subtle properties of the Beta distribution listed in Appendix C as Fact 2 and 3. For part (I), we invoke symmetry to deduce $\mathbb{E}N_1(n) = n/2$, and use Fact 2 to show that the standard deviation of $N_1(n)$ is sub-linear in n, thus proving the stated assertion in (I). In fact, we conjecture that this result holds also with probability 1. The conclusion in part (II) hinges on an application of Fact 3 to show the *stronger* result: $N_1(n)$ is *uniformly distributed* over $\{0, 1, ..., n\}$ for any $n \in \mathbb{N}$. Full proofs are provided in Appendix G. $\square$

More on "incomplete learning." The zero-gap setting is a special case of the "small gap" regime where canonical UCB guarantees a $(1/2, 1/2)$ sample-split in probability (Theorem 1). On the other hand, Theorem 2 suggests that second order factors such as the mean signal strength (magnitude of the mean reward) could significantly affect the nature of the resulting sample-split under Thompson Sampling. Note that even though the result only presupposes deterministic 0/1 rewards, the aforementioned claim is, in fact, borne out by the numerical evidence in Figure 1(b) and 1(c). The sampling distribution seemingly flattens rapidly from the Dirac measure at $1/2$ to the Uniform distribution on $[0, 1]$ as the mean rewards move away from 0. This uncertainty in the limiting sampling behavior has non-trivial implications for a variety of application areas of such learning algorithms. For instance, a uniform distribution of arm-sampling rates on $[0, 1]$ indicates that the sample-split could be arbitrarily imbalanced along a sample-path, despite, as in the setting of Theorem 2, the two arms being statistically identical; this phenomenon is typically referred to as "incomplete learning" (see [22, 20] for the original context). Non-degeneracy in the limiting distribution is also observable numerically up to diffusion-scale gaps of $\mathcal{O}(1/\sqrt{n})$ under other versions of Thompson Sampling (see [25] for examples); our focus on the more extreme zero-gap setting simplifies the illustration of these effects.

3.2 Beyond arm-sampling rates

This part of the paper is dedicated to a more fine-grained analysis of the "stochastic" regret of UCB (defined in (1) in §2). Results are largely facilitated by insights on the sampling behavior of UCB in instances with "small" gaps, attributable to Theorem 1; however, we believe they are of interest in their own right. We commence with an application of Theorem 1 which provides the first complete characterization of the worst-case (minimax) performance of canonical UCB. A full diffusion-limit characterization of the two-armed bandit problem under UCB is provided thereafter in Theorem 4.

Theorem 3 (Minimax regret complexity of UCB) *In the "moderate gap" regime referenced in Theorem 1 where $\Delta \sim \sqrt{\frac{\theta \log n}{n}}$, the regret of the policy π given by Algorithm 1 with $\rho > 1$ satisfies*

$$\frac{R_n^\pi}{\sqrt{n \log n}} \xrightarrow{p} \sqrt{\theta}\left(1 - \lambda_\rho^*(\theta)\right) =: h_\rho(\theta) \quad as \ n \to \infty, \tag{3}$$

where $\lambda_\rho^*(\theta)$ is the (unique) solution to (2).

To the best of our knowledge, this is the first statement predicating an *algorithm-specific* achievability result (sharp asymptotic for regret) that is away from the general $\Omega\left(\sqrt{n}\right)$ information-theoretic lower bound by a horizon-dependent factor.[5]

Discussion. A closed-form expression for $\lambda_\rho^*(\theta)$ and $h_\rho(\theta)$ is provided in Appendix A. The behavior of $h_\rho(\theta)$ is illustrated below in Figure 3. For a fixed ρ, the function $h_\rho(\theta)$ is numerically observed to be uni-modal in θ and admit a global maximum at a unique $\theta_\rho^* = \arg\max_{\theta \geqslant 0} h_\rho(\theta)$, bounded away from 0. Theorem 3 establishes that the worst-case (instance-independent) regret admits the sharp asymptotic $R_n^\pi \sim h_\rho\left(\theta_\rho^*\right)\sqrt{n \log n}$. In standard bandit parlance, this substantiates that the

Figure 3: $h_\rho(\theta)$ vs. θ for different values of the exploration coefficient ρ in Algorithm 1. The graphs exhibit a unique global maximizer θ_ρ^* for each ρ. The $\left(\theta_\rho^*, h_\rho\left(\theta_\rho^*\right)\right)$ pairs for $\rho \in \{1.1, 2, 3, 4\}$ in that order are: $(1.9, 0.2367), (3.5, 0.3192), (5.3, 0.3909), (7, 0.4514)$.

$\mathcal{O}\left(\sqrt{n \log n}\right)$ worst-case (minimax) performance guarantee of canonical UCB cannot be improved in terms of its horizon-dependence. In addition, the result also specifies the precise asymptotic constants achievable in the worst-case setting. This can alternately be viewed as a direct approach to proving the $\mathcal{O}\left(\sqrt{n \log n}\right)$ performance bound for UCB vis-à-vis conventional minimax analyses such as [8].

Proof sketch. Note that there are, in effect, three regimes that exhaustively cover all possibilities for Δ, viz., (i) $\Delta = o\left(\sqrt{(\log n)/n}\right)$, (ii) $\Delta = \omega\left(\sqrt{(\log n)/n}\right)$, and (iii) $\Delta = \Theta\left(\sqrt{(\log n)/n}\right)$. In either of the two so called "easy" regimes for regret minimization; (i) and (ii), we have that $R_n^\pi = o_p\left(\sqrt{n \log n}\right)$. The assertion for (i) is obvious from $\mathbb{E}R_n^\pi \leqslant \Delta n$ and Markov's inequality, while (ii) uses that Algorithm 1 with $\rho > 1$ has its regret bounded as $\mathbb{E}R_n^\pi \leqslant C\rho\left((\log n)/\Delta + \Delta/(\rho-1)\right)$ for some absolute constant C (see [5], Theorem 7), followed by Markov's inequality. This leaves out (iii), and therefore, it must be the case that the multiplicative constant $h_\rho\left(\theta_\rho^*\right)$ obtained in the "moderate gap" regime indeed corresponds to the worst-case performance of the algorithm. $\qquad\square$

Towards diffusion asymptotics. The diffusion scaling is a standard tool for performance evaluation of stochastic systems that is widely used in the operations research literature, with origins in queuing theory (see [13] for a survey). Under this scaling, time is accelerated linearly in n, space contracted by a factor of $\sqrt{n}$, and a sequence of systems indexed by n is considered. In our problem, the n^{th} such system refers to an instance of the two-armed bandit with: n as the horizon of play; a gap that vanishes in the horizon as $\Delta = c/\sqrt{n}$ for some fixed c; and fixed reward variances given by σ_1^2, σ_2^2. This is a natural scaling for MAB experiments in that it "preserves" the hardness of the learning problem as n sweeps over the sequence of systems. Recall also from previous discussion that the "hardest" information-theoretic instances have a $\Theta\left(1/\sqrt{n}\right)$ gap; in short, the diffusion limit is an appropriate asymptotic lens for observing interesting process-level behavior in the MAB problem. However, despite the aforementioned reasons, the diffusion limit behavior of bandit algorithms remains poorly understood and largely unexplored. A recent foray was made in [25], however, standard bandit algorithms such as the ones discussed in this paper remain outside the ambit of their analysis due to the restrictive nature of assumptions used there. In Theorem 4 below, we provide the first full characterization of the diffusion limit performance of canonical UCB.

Theorem 4 (Diffusion asymptotics for canonical UCB) *Suppose that the mean reward of arm $i \in \{1, 2\}$ is given by $\mu_i = \mu + \theta_i/\sqrt{n}$, where n is the horizon of play and $\mu, \theta_1, \theta_2 \geqslant 0$ are fixed constants, and reward variances are σ_1^2, σ_2^2. Define $\Delta_0 := |\theta_1 - \theta_2|$. Denote the cumulative reward*

---

[5]The closest being [2], which established matching $\Theta\left(\sqrt{Kn \log K}\right)$ upper and lower bounds for the minimax *expected* regret of the Gaussian prior-based Thompson Sampling algorithm in the K-armed problem.

earned from arm i until time m by $S_{i,m} := \sum_{j=1}^{N_i(m)} X_{i,j}$, and let $\tilde{S}_{i,m} := S_{i,m} - \mu N_i(m)$. Then, the following process-level convergences hold under the policy π given by Algorithm 1 with $\rho > 1$:

$$(I) \quad \left(\frac{\tilde{S}_{1,\lfloor nt \rfloor}}{\sqrt{n}}, \frac{\tilde{S}_{2,\lfloor nt \rfloor}}{\sqrt{n}} \right) \Rightarrow \left(\frac{\theta_1 t}{2} + \frac{\sigma_1}{\sqrt{2}} B_1(t), \frac{\theta_2 t}{2} + \frac{\sigma_2}{\sqrt{2}} B_2(t) \right),$$

$$(II) \quad \left(\frac{R_{\lfloor nt \rfloor}^{\pi}}{\sqrt{n}} \right) \Rightarrow \left(\frac{\Delta_0 t}{2} + \sqrt{\frac{\sigma_1^2 + \sigma_2^2}{2}} \tilde{B}(t) \right),$$

where the process-level convergence is over $t \in [0, 1]$, and $B_1(t)$ and $B_2(t)$ are independent standard Brownian motions in $\mathbb{R}$, and $\tilde{B}(t) := -\sqrt{\frac{\sigma_1^2}{\sigma_1^2 + \sigma_2^2}} B_1(t) - \sqrt{\frac{\sigma_2^2}{\sigma_1^2 + \sigma_2^2}} B_2(t)$.

Proof sketch. The result hinges on the observation from Theorem 1 that $N_i(n)/n \xrightarrow{p} 1/2$ as $n \to \infty$ under UCB when $\Delta \asymp 1/\sqrt{n}$. This essentially states that a two-armed bandit under UCB behaves in the diffusion limit as a classical system with *independent* samples (sample-adaptivity is washed away in the limit), thereby facilitating a standard "random time-change" argument followed by an application of Donsker's Theorem (see [7], Section 16) in $\mathbb{R}^2$, which leads to the stated assertion. $\square$

Discussion. An immediate observation following Theorem 4 is that the normalized regret $R_n^{\pi}/\sqrt{n}$ is asymptotically Gaussian with mean $\Delta_0/2$ and variance $\left(\sigma_1^2 + \sigma_2^2\right)/2$ under canonical UCB. Apart from aiding in obvious inferential tasks like construction of confidence intervals (see, e.g., the binary hypothesis testing example referenced in Figure 2(c)), etc., such information provides new insights as to the problem's minimax complexity as well. This is because $\Delta \asymp 1/\sqrt{n}$ is known to be the information-theoretic "worst-case" for the problem; the smallest achievable regret in this regime must asymptotically be dominated by that under UCB, i.e., $\Delta_0 \sqrt{n}/2$. It is also noteworthy that while the diffusion limit in Theorem 4 does not itself depend on the exploration coefficient ρ of the algorithm, the rate at which the system converges to said limit indeed depends on ρ. Theorem 4 will continue to hold only as long as $\rho = \omega\left((\log \log n)/\log n\right)$; for smaller ρ, the convergence of $N_i(n)/n$ to $1/2$ may no longer be true (refer to the proof of Theorem 1 in the "small" gap regime in Appendix E).

Comparison with Thompson Sampling. The closest related work in extant literature is [25], which shows that the diffusively re-scaled cumulative reward and arm-pull processes under a version of Thompson Sampling based on Gaussian priors and Gaussian likelihoods converge in law to the unique solution to a certain stochastic differential equation (SDE). However, their version of Thompson Sampling is significantly different from the standard version in that it assumes prior variances to vanish in the horizon of play. It remains a mere conjecture that a similar SDE arises in the limit also under the standard version of the algorithm with fixed prior variances. Furthermore, certain regularity conditions pivotal to the proof in [25] are violated under algorithms such as UCB which consequently remain outside the scope of their analysis. The principal difficulty impeding the diffusion-limit analysis of Thompson Sampling stems from its instability and non-degeneracy of the arm-sampling distribution, i.e., the "incomplete learning" phenomenon referenced in Figure 1 and Theorem 2.

4 Concluding remarks and open problems

Our results for the two-armed problem under canonical UCB (Algorithm 1) may be generalizable to the K-armed setting, leveraging the observations and insights from Theorem 1 (a simple extension is provided in Appendix B). The K-armed problem under UCB is of interest in its own right: we postulate a division of sampling effort within and across clusters of "similar" and "separated" arms, determined by their relative sub-optimality gaps in the spirit of Theorem 1. We expect that similar generalizations are possible also for Theorem 3 and Theorem 4. For Thompson Sampling, on the other hand, things are less obvious even in the two-armed setting. For example, in spite of compelling numerical evidence (refer, e.g., to Figure 1(b)) suggesting a plausibly non-degenerate distribution of arm-sampling rates for bounded rewards in $[0, 1]$ with means away from 0, the proof of Theorem 2 relies heavily on the rewards being deterministic $0/1$, and cannot be extended to the general case. In addition, similar results are conjectured also for the more widely used Gaussian prior-based version of the algorithm. Such results may shed light on several diffusion-limit performance metrics of Thompson Sampling, including the stochastic behavior of its normalized minimax regret, which could prove useful in a variety of application areas. However, since technical difficulty is a major impediment in the derivation of such results, this currently remains an open problem.

References

[1] AGRAWAL, S., AND GOYAL, N. Analysis of thompson sampling for the multi-armed bandit problem. In *Conference on learning theory* (2012), JMLR Workshop and Conference Proceedings, pp. 39–1.

[2] AGRAWAL, S., AND GOYAL, N. Near-optimal regret bounds for thompson sampling. *Journal of the ACM (JACM) 64*, 5 (2017), 1–24.

[3] AUDIBERT, J.-Y., BUBECK, S., ET AL. Minimax policies for adversarial and stochastic bandits. In *COLT* (2009), vol. 7, pp. 1–122.

[4] AUDIBERT, J.-Y., BUBECK, S., AND MUNOS, R. Best arm identification in multi-armed bandits. In *COLT* (2010), pp. 41–53.

[5] AUDIBERT, J.-Y., MUNOS, R., AND SZEPESVÁRI, C. Exploration–exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science 410*, 19 (2009), 1876–1902.

[6] AUER, P., CESA-BIANCHI, N., AND FISCHER, P. Finite-time analysis of the multiarmed bandit problem. *Machine learning 47*, 2-3 (2002), 235–256.

[7] BILLINGSLEY, P. *Convergence of probability measures*. John Wiley & Sons, 2013.

[8] BUBECK, S., AND CESA-BIANCHI, N. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *arXiv preprint arXiv:1204.5721* (2012).

[9] DESHPANDE, Y., MACKEY, L., SYRGKANIS, V., AND TADDY, M. Accurate inference for adaptive linear models. *arXiv preprint arXiv:1712.06695* (2017).

[10] DURRETT, R. *Probability: theory and examples*, vol. 49. Cambridge university press, 2019.

[11] GARIVIER, A., AND CAPPÉ, O. The kl-ucb algorithm for bounded stochastic bandits and beyond. In *Proceedings of the 24th annual conference on learning theory* (2011), pp. 359–376.

[12] GARIVIER, A., LATTIMORE, T., AND KAUFMANN, E. On explore-then-commit strategies. In *Advances in Neural Information Processing Systems* (2016), pp. 784–792.

[13] GLYNN, P. W. Diffusion approximations. *Handbooks in Operations research and management Science 2* (1990), 145–198.

[14] HADAD, V., HIRSHBERG, D. A., ZHAN, R., WAGER, S., AND ATHEY, S. Confidence intervals for policy evaluation in adaptive experiments. *arXiv preprint arXiv:1911.02768* (2019).

[15] HOEFFDING, W. Probability inequalities for sums of bounded random variables. *Journal of the American Statistical Association 58*, 301 (1963), 13–30.

[16] HONDA, J., AND TAKEMURA, A. An asymptotically optimal bandit algorithm for bounded support models. In *COLT* (2010), Citeseer, pp. 67–79.

[17] KALVIT, A., AND ZEEVI, A. From finite to countable-armed bandits. *Advances in Neural Information Processing Systems 33* (2020).

[18] LAI, T. L., AND ROBBINS, H. Asymptotically efficient adaptive allocation rules. *Advances in applied mathematics 6*, 1 (1985), 4–22.

[19] LATTIMORE, T., AND SZEPESVÁRI, C. *Bandit algorithms*. Cambridge University Press, 2020.

[20] MCLENNAN, A. Price dispersion and incomplete learning in the long run. *Journal of Economic dynamics and control 7*, 3 (1984), 331–347.

[21] MEHRABI, N., MORSTATTER, F., SAXENA, N., LERMAN, K., AND GALSTYAN, A. A survey on bias and fairness in machine learning. *arXiv preprint arXiv:1908.09635* (2019).

[22] ROTHSCHILD, M. A two-armed bandit theory of market pricing. *Journal of Economic Theory 9*, 2 (1974), 185–202.

[23] THOMPSON, W. R. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika 25*, 3/4 (1933), 285–294.

[24] VILLAR, S. S., BOWDEN, J., AND WASON, J. Multi-armed bandit models for the optimal design of clinical trials: benefits and challenges. *Statistical science: a review journal of the Institute of Mathematical Statistics 30*, 2 (2015), 199.

[25] WAGER, S., AND XU, K. Diffusion asymptotics for sequential experiments. *arXiv preprint arXiv:2101.09855* (2021).

[26] ZHANG, K. W., JANSON, L., AND MURPHY, S. A. Inference for batched bandits. *arXiv preprint arXiv:2002.03217* (2020).