Toward General Object-level Mapping from Sparse Views with 3D Diffusion Priors

Ziwei Liao   Binbin Xu   Steven L. Waslander
Institute for Aerospace Studies & Robotics Institute
University of Toronto
{ziwei.liao, binbin.xu, steven.waslander}@robotics.utias.utoronto.ca

Abstract: Object-level mapping builds a 3D map of objects in a scene with detailed shapes and poses from multi-view sensor observations. Conventional methods struggle to build complete shapes and estimate accurate poses due to partial occlusions and sensor noise. They require dense observations to cover all objects, which is challenging to achieve in robotics trajectories. Recent work introduces generative shape priors for object-level mapping from sparse views, but is limited to single-category objects. In this work, we propose a **G**eneral **O**bject-level **M**apping system, *GOM*, which leverages a 3D diffusion model as shape prior with multi-category support and outputs Neural Radiance Fields (NeRFs) for both texture and geometry for all objects in a scene. GOM includes an effective formulation to guide a pre-trained diffusion model with extra nonlinear constraints from sensor measurements without finetuning. We also develop a probabilistic optimization formulation to fuse multi-view sensor observations and diffusion priors for joint 3D object pose and shape estimation. GOM demonstrates superior multi-category mapping performance from sparse views, and achieves more accurate mapping results compared to state-of-the-art methods on the real-world benchmarks. We will release our code: https://github.com/TRAILab/GeneralObjectMapping.

Keywords: Mapping, Objects Reconstruction, Pose Estimation, Diffusion

1   Introduction

Object-level mapping [1, 2, 3, 4, 5, 6, 7, 8, 9] builds a 3D map of multiple object instances in a scene, which is critical for scene understanding [10] and has various applications in robotic manipulation [11], semantic navigation [12, 13] and long-term dynamic map maintenance [14]. It addresses two closely coupled tasks: 3D shape reconstruction [15, 16] and pose estimation [17]. Conventional methods [18, 19, 20] approach these tasks from a perspective of state estimation [21], solving an inverse problem where low-dimensional observations (RGB and Depth images) are used to recover high-dimensional unknown variables (3D poses and shapes) through a known observation process (e.g., projection, and differentiable rendering). However, these methods require dense observations (e.g., hundreds of views for NeRF [18]) to fully constrain the problem. In robotics or AR applications, obtaining such dense observations is challenging due to limitations in the robot's or user's observation angle and occlusions in clustered scenarios. Therefore, it is crucial to develop methods that can map from sparse (fewer than 10) or even single observations.

Human vision can infer complete 3D objects from images despite occlusions by using *prior knowledge* of the objects, which represents the *prior distributions* of the shapes of specific categories, such as chairs, based on thousands of instances observed in daily life. We aim to introduce generative models [22] as providers of *prior knowledge* to constrain the 3D object mapping. Generative models have demonstrated impressive abilities to generate high-quality multi-modal data by learning distributions in large-scale datasets, including texts [23], images [24], videos [25], and 3D models [26, 27, 28, 29]. Previously, researchers have explored methods, to introduce generative priors

to constrain inverse problems in the image field, such as restoration [30] and controllable generation [31]. However, applying generative models to 3D inverse problems remains an open problem.

Two types of generative priors have been explored in the context of 3D inverse problem. (1) **Image Generation Models as 2D Priors**. Researchers [32, 33] use image generation models [24] to generate multi-view images to optimize NeRF parameters for shape reconstruction. However, these models suffer from poor 3D consistency (e.g., multi-face problem [32]) as it is difficult to preserve 3D consistency and identity in image generation models. Additionally, they require dense observations, which limit computation efficiency (e.g., taking hours per object). Achieving high-quality results often necessitates complex modifications, such as retraining the generation model [34, 35, 36]. Furthermore, these methods typically focus on shape generation from texts, rather than on reconstruction *and pose estimation* from multi-view real observations. (2) **3D Shape Generation Models as 3D Priors**. Recent object-level mapping systems [3, 4] directly inject 3D priors from a 3D generation model like DeepSDF [27] by jointly optimizing pose and shape (represented in a learned latent space). Compared to 2D priors, which provide only partial and low-dimensional shape information, 3D priors achieve better 3D consistency and completeness. However, limited by the capacity of an autodecoder model [27], they support only single-category objects, and model only the geometries of shapes without textures, limiting the generalization ability.

We aim to propose an object-level mapping system that introduces valuable generative priors for diverse objects in any scene. Our system is therefore designed to be: (1) *General*: It supports multi-category objects by using a pre-trained generative model as shape prior; (2) *Flexible*: It supports multi-view, multi-modality observation signals (e.g., RGB, depth images and pointclouds), without the need for finetuning the generative model. Retraining large-scale 3D generative models is a process that is both time-consuming and resource-intensive. The attributes of being *General* and *Flexible* are essential when integrating into a complex robotics system for downstream tasks.

Recently, diffusion-based 3D generative models trained on millions of 3D objects and supporting multiple object categories have been released [37, 29]. Additionally, new public large-scale 3D object datasets [38, 39] are becoming available. However, employing diffusion-based models to solve inverse problems remains theoretically unsolved, since diffusion models use score functions to model distributions [24] and cannot directly output probability densities like the VAE-variant models [27]. In this paper, we make a key theoretical contribution by proposing an effective formulation to fuse 3D diffusion priors with 3D sensor observations. As far as we know, we are the first to explore 3D object-level mapping with a multi-category 3D diffusion model for both pose and shape estimation. Our contributions are summarized as follows:

- We propose a 3D object-level mapping system from sparse RGB-D observations, leveraging a pre-trained diffusion-based 3D generation model as a multi-category shape prior;

- We propose an effective optimization formulation that jointly fuses information from multi-view sensor observations and diffusion priors;

- We demonstrated our superior multi-category mapping performance over the state-of-the-art baselines through extensive experiments on the real ScanNet dataset.

2 Related Work

2.1 3D Object-level Mapping

3D scene understanding is crucial for robots to perform high-level object-oriented tasks such as navigation and manipulation [10]. Early methods in the field of SLAM and SfM [40] built 3D scene models from dense multi-view observations, leveraging multi-view geometric consistency [41]. However, they used a single model to represent both foreground objects and backgrounds, unaware of separate instances [16, 42, 43]. Object-level mapping addresses the problem of estimating objects' shapes and poses as independent instances. SLAM++ [1] was pioneering in this area but requires a database of CAD models and could not handle unseen objects outside this database. To generalize

to unseen objects, researchers have used compact object representation such as quadrics [6, 7] or cuboids [5], but these approaches lack detailed shape information and texture. Methods [44, 2, 45] produce dense representations, such as Signed Distance Function (SDF) fields, and Neural Radiance Fields (NeRFs) [46]. However, they require dense observations to constrain the high-dimensional shape variables, and struggle to achieve complete and accurate results in the presence of occlusions and noise. Differing from the methods above, we develop our method to address object-level mapping from *sparse* observations, which is more relevant for robotic applications.

2.2 Generative Models as Shape Priors

Introducing generative models as prior constraints for 3D object pose and shape estimation is an open problem. Currently, the literature explores two kinds of priors. (1) Prior for Specific Single-category. Early 3D generative models [27, 28, 47] train separate models for single-category objects. Object-level mapping systems [8, 3, 4, 48, 9] introduce DeepSDF-like [27] generative models as priors to constrain object shapes. They estimate complete shapes and poses from sparse observations under occlusions, however, limited by the shortcomings of these generative priors, they are limited to a single category. (2) General Prior for Multi-categories. Recent research, including DreamFusion [32] and Magic3D [33], optimizes 3D shapes represented by NeRF through multi-view images from an image generation model [49]. However, since the prior is inherently 2D, it has limited 3D consistency, leading to multi-face artifacts and identity-preserving problems [32]. Although they can generate multi-category 3D shapes from texts, they can not reconstruct from real images or estimate object poses to form a map with multiple instances. In contrast to the methods above, we aim to leverage a 3D prior model with multi-category ability for improved 3D consistency. Recently, diffusion-based 3D generative models [37, 29] have become available, such as Shap-E [29] which is trained on millions of objects in thousands of categories. However, unlike VAE-variant models [27], diffusion-based models are not straightforward to integrate into an object-level mapping system. We discuss this further in the next section.

2.3 Pretrained Diffusion Models as Optimization Constraints

Training a diffusion model on millions of 3D objects is time-consuming [37, 29]. We aim to leverage a pre-trained diffusion model without finetuning. One method to control a pre-trained diffusion model is through conditional generation. It introduces extra constraints to guide the original diffusion process, and has been investigated in image generation [31], restoration [30], and 3D human pose generation [50]. However, a conditional generation formulation is not flexible enough to estimate extra variables (i.e. poses) beyond the variable modeled by the diffusion model (i.e. shapes). Another method is to leverage the diffusion model as a constraint in optimization, which is flexible to introduce extra variables and constraints. However, unlike VAE-variant methods that have explicit latent spaces [27, 3, 9], the latent space of diffusion models is still under investigation [51]. Diffusion models output scores instead of densities and require a complex sampling process to generate a sample [24], making it nontrivial to formulate a joint optimization with additional variables. Recently, some work uses optimization with diffusions, in the fields of images [51, 52], 3D human poses [53, 54], and medical CT reconstruction [55]. Most similar to ours, Yang et al. [56] optimized a NeRF with a *single-category* diffusion model, but did not include pose estimation. Differing from the work above, we are the first to use a pre-trained multi-categories diffusion model in an optimization framework for both 3D object pose and shape estimation.

3 Methods

3.1 Framework Overview

Our system, visualized in Figure 1, estimates 3D object shapes and poses in a scene using two information sources: multiple RGB-D observations and a generative shape prior model. Following

Figure 1: Framework overview. We propose an object-level mapping framework that fuses both multi-view observations and a pre-trained diffusion shape prior model. It generalizes to multi-categories objects, and multiple multi-modalities observations without the need of fine-tuning.

Shap-E [29], object shapes are represented as NeRFs with SDFs, modeling both the geometry and texture, which can be rendered into images or generate meshes.

3.2   3D Objects Shapes and Poses Representations

We aim to build a map of the 3D objects $\mathcal{O}$ in a scene. For each object, we estimate its 3D model (a NeRF), $\boldsymbol{Q}_o$, in the object canonical coordinate frame, $\underset{\rightarrow}{\mathcal{F}}_O$, and a relative pose, $\mathbf{T}_{OW}$, from the world coordinate frame, $\underset{\rightarrow}{\mathcal{F}}_W$, to the object coordinate frame $\underset{\rightarrow}{\mathcal{F}}_O$.

Pose Representation. A pose transformation with scale, $\mathbf{T} \in \mathbb{R}^{4\times4}$, is constructed from a translation vector, $\mathbf{t} \in \mathbb{R}^3$, a rotation vector, $\phi \in \mathfrak{so}(3)$, and a scaling vector, $\mathbf{s} \in \mathbb{R}^3$:

$$\mathbf{T} = \begin{bmatrix} \exp\left(\phi^{\wedge}\right) & \mathbf{t} \\ \mathbf{0}^T & 1 \end{bmatrix} \cdot \begin{bmatrix} \operatorname{diag}\left(\mathbf{s}\right) & \mathbf{0} \\ \mathbf{0}^T & 1 \end{bmatrix} \tag{1}$$

where $\exp\left(\cdot\right)$ is the exponential mapping from the Lie Algebra to the corresponding Lie Group. The operator $\left(\cdot\right)^{\wedge}$ converts a vector to a skew-symmetric matrix. Thus, we can represent the pose with a 9-DoF vector: $\xi = [\mathbf{t}, \phi, \mathbf{s}] \in \mathbb{R}^9$. As a mapping system, we assume camera poses, $\mathbf{T}_{WC} \in SE(3)$, are known, e.g., by off-the-shelf SLAM methods [43], or by robot kinematics [57].

Shape Representation. We parameterize the object's shape with a Neural Radiance Field (NeRF) [18] through a neural network $f_{\Theta}(.)$ with weights Θ. For any given 3D point, it outputs its density, σ, color, $\mathbf{c}$, and illumination, i, and can be rendered into RGB and depth images. Following Shap-E [29], it further outputs SDF values, s, and can generate meshes via Marching Cubes:

$$\sigma, \mathbf{c}, i, s = f_{\Theta}(\mathbf{x}, \mathbf{d}) \tag{2}$$

where $\mathbf{x} \in R^3$ is the given 3D coordinate and $\mathbf{d} \in R^3$ is the viewing direction.

3.3   Leveraging Generative Models as Shape Priors

Common 3D objects, such as chairs and tables, exhibit diverse shapes and textures. This translates to high-dimensional NeRF parameters Θ. To further constrain the process, we propose to leverage a generative model with learnable parameters β, denoted by $g_{\beta}(.)$, to learn an approximate posterior distribution $\hat{P}(\Theta|C)$ of the true posterior distribution $P(\Theta|C)$. Here C represents the conditioning information, e.g., an image or a text prompt. The generative model $g_{\beta}(.)$ takes this conditioning information, C, as input and outputs a *conditional* distribution of the NeRF parameters Θ:

$$\hat{P}(\Theta|C) = g_{\beta}(C) \tag{3}$$

Figure 2: An illustration of the gradient fields and optimization process. The gradient fields from two sources, a diffusion prior originally for *Generation*, and multi-view non-linear observation constraints, are effectively fused into a shape and pose optimization formulation for *Mapping*.

Diffusion Models. We leverage Shap-E [29], a pre-trained diffusion model as $g_\beta(.)$, which has been trained on millions of 3D objects. As shown in Figure 2, to generate a sample $\Theta_i \in \hat{P}(\Theta|C)$, we start from a random noise Θ_T and refine it through a series of diffusion steps $\epsilon_\beta(.)$ for timestamp $t = T, ..., 1$, according to a noise schedule. This process produces the final noise-free sample Θ_0:

$$\Theta_{t-1} = \epsilon_\beta(\Theta_t, C, t) \tag{4}$$

3.4 Optimization with Diffusion and Extra Observations

To update Θ with multi-view RGB-D observations and further estimate a new unknown pose variable $\mathbf{T}$, we propose an optimization formulation that integrates additional observations into the pre-trained diffusion model, as shown in Figure 2. We refer $\mathbf{T}$ as $\mathbf{T}_{OW}$ without further notice. Given M observation frames $\{F_i\}_{i=1}^M$ and a condition C, we aim to estimate a Maximum Likelihood Estimation for the unknown variables pose $\mathbf{T}$ and shape Θ, from a joint distribution of $P(\mathbf{T}, \Theta|F_1, \ldots, F_M, C)$. By derivation (Proof provided in Appendix), we get a convenient form for numerical optimization:

$$\hat{\mathbf{T}}, \hat{\Theta} = \arg\max_{\mathbf{T}, \Theta} \sum_i \underbrace{\log P(F_i|\mathbf{T}, \Theta)}_{\text{Observations}} + \underbrace{\log P(\Theta|C)}_{\text{Diffusion Priors}} \tag{5}$$

Diffusion Priors. The term $\log P(\Theta|C)$ measures the likelihood of current Θ under a condition C by the diffusion model. However, diffusion models can not directly output the probability density [24]. We derive a method to calculate gradients from diffusion priors for optimization, following a variational sampler [58], originally designed for controlling image generation. A diffusion model is trained to predict the noise ϵ in a noisy variable Θ_t at timestamp t, under a condition C:

$$\min_\beta = \mathbb{E}_{t,\epsilon} \|\epsilon_\beta(\Theta_t, C, t) - \epsilon\|_2^2, \quad t \in \mathcal{U}(0, T), \quad \epsilon \in \mathcal{N}(0, I_n) \tag{6}$$

We fix the weights β of the pre-trained diffusion model, and use it to get the gradients $\Delta_\Theta \log P(\Theta|C)$ of the current shape Θ. First, we add noise to the current shape parameter Θ to get a noisy Θ_t with the predefined noise schedule of the diffusion model at timestamp t:

$$\Theta_t = \alpha_t \Theta + \sigma_t \epsilon, \quad \epsilon \in \mathcal{N}(0, I_n) \tag{7}$$

where σ_t and α_t are constants of the schedule, and ϵ is a randomly sampled noise. Then, we predict the added noise and evaluate the predicted error $\Delta_\beta(\Theta, C, t)$ with the diffusion model:

$$\Delta_\beta(\Theta, C, t) = \epsilon_\beta(\Theta_t, C, t) - \epsilon \tag{8}$$

$$= \epsilon_\beta(\alpha_t \Theta + \sigma_t \epsilon, C, t) - \epsilon, \quad \epsilon \in \mathcal{N}(0, I_n) \tag{9}$$

To eliminate the timestamps t, we randomly sample K times from a uniform distribution $\mathcal{U}(0, T)$ and take an expectation:

$$\Delta_\beta(\Theta, C) = \frac{1}{K} \sum_{i=1}^K \Delta_\beta(\Theta, C, t_i), \quad t_i \in \mathcal{U}(0, T) \tag{10}$$

| RGB-D Reference View | Rendered View | Novel Views | Mesh | Methods |

Figure 3: Prior Effectiveness: Using priors, GOM (Ours) can render higher-quality 3D consistent views and generate 3D meshes with fewer artifacts compared to vMap. Results are based on 10 RGB-D views.

As illustrated in Figure 2, the predicted noise of a diffusion model naturally models the gradient field [24] of the prior distribution. Thus, we take the predicted error $\Delta_\beta(\Theta, C)$ as the gradient to update Θ under a prior condition C:

$$\nabla_\Theta \log P(\Theta|C) = \Delta_\beta(\Theta, C) \tag{11}$$

We also present ablations with other alternatives in the Appendix.

Observations. The term $\sum \log P(F_i|\mathbf{T}, \Theta)$ measures the geometric and texture consistency from multi-view observations. For each observation $F_i = \{I_i, D_i, \mathbf{P}_{WC_i}\}$, we use differentiable rendering [18] to render an RGB image $\hat{I}_i(\mathbf{T}_{OW}, \Theta, \mathbf{P}_{WC_i})$ and a depth image $\hat{D}_i(\mathbf{T}_{OW}, \Theta, \mathbf{P}_{WC_i})$ with the camera projection matrix $\mathbf{P}_{WC_i}$. We then formulate an L2 loss:

$$\log P(F_i|\mathbf{T}, \Theta) \propto |\hat{I}_i - I_i|^2 + |\hat{D}_i - D_i|^2 \tag{12}$$

This term can propagate gradients to update both poses $\mathbf{T}_{OW}$ and shapes Θ as shown in Figure 2.

Iterative Update. We first coarsely initialize the unknown variables shape Θ_0 and pose $\mathbf{T}_0$. Then, we iteratively refine for J steps considering a prior condition C and observations $\{F_i\}$:

$$\Theta_j, \mathbf{T}_j = Refine(\Theta_{j-1}, \mathbf{T}_{j-1}, C, \{F_i\}), \quad \text{for} \quad j = 1, ..., J \tag{13}$$

The $Refine()$ process has two steps. First, a *Prior Step* to update Θ with diffusion using Eq. 11:

$$\Theta_j^* = \Theta_{j-1} + \lambda_p \nabla_\Theta \log P(\Theta|C)|_{\Theta=\Theta_{j-1}} = \Theta_{j-1} + \lambda_p \Delta_\beta(\Theta_{j-1}, C) \tag{14}$$

where Θ_j^* is a middle shape fused with prior. Then, an *Observation Step* to update both Θ and $\mathbf{T}$:

$$\Theta_j = \Theta_j^* + \lambda_o \sum_i \nabla_\Theta log P(F_i|\mathbf{T}, \Theta)|_{\Theta=\Theta_j^*, \mathbf{T}=\mathbf{T}_{j-1}} \tag{15}$$

$$\mathbf{T}_j = \mathbf{T}_{j-1} + \lambda_o \sum_i \nabla_\mathbf{T} \log P(F_i|\mathbf{T}, \Theta)|_{\Theta=\Theta_j^*, \mathbf{T}=\mathbf{T}_{j-1}} \tag{16}$$

where λ_p and λ_o are hyperparameters to balance the influence of priors and observations. Finally, we obtain the refined $\mathbf{T}_J$ and Θ_J after J steps optimization.

4   Experiments

Datasets. We conducted experiments utilizing the ScanNet [59] dataset, which comprises RGB-D scans of real indoor scenes. It presents significant challenges to object mapping methods due to real-world occlusions, clusters, blurs, and sensor noise. We use ground-truth shape annotations of ShapeNet [60] meshes provided by Scan2CAD [61] for evaluation. We focus on objects that have a

| Reference View | Pointcloud | Shap-E (Text) | Shap-E (Image) | DSP | BundleSDF | vMap | GOM (Ours) |

Figure 4: Mapping Performance: GOM (Ours) outputs 3D object shapes and poses that align with the inputs and further completes the occluded parts. GOM can also generalize to multiple categories. Results are based on 10 RGB-D views.

minimum of 10 available views, where at least 50% of the object is visible in each view. This results in a total of 206 scenes, encompassing 1036 object instances across 7 categories. These categories include chairs, tables, cabinets, sofas, bookshelves, beds, and bathtubs.

Baselines and Metrics. We compared our method against the following state-of-art RGB-D object-level mapping methods: (1) *Shap-E+ICP*, which uses Shap-E [29] to generate a NeRF model conditioned on an input image, and then matches RGB-D inputs with ICP [62]; (2) *DSP* [3], which optimizes objects shapes and poses with DeepSDF [27] as shape priors; (3) *vMap* [45], which optimizes an independent NeRF [18] from scratch with a fixed pose for each 3D object; (4) *BundleSDF* [20], which optimizes objects' NeRF [18] and poses for tracking. To ensure a fair comparison, we utilize the ground truth camera poses, segmentation masks, and data association provided by the dataset across all systems. For pose accuracy, we use Intersection over Union (IoU) to evaluate the bounding boxes of the estimated and ground truth shapes in world coordinates. For shape accuracy, we calculate Chamfer Distance (CD) after transforming objects into world coordinates.

Implementation Details. We optimize for 200 steps, with a fixed learning rate of 0.5. For every 2 steps, we diffuse once with a timestamp randomly sampled from the Shap-E diffusion schedule. We use the text prompt "a {category}" as the condition for Shap-E, where the category comes from the segmentation mask. We randomly initialize the shape variable from a Gaussian distribution and a coarse pose using ICP matching between the input depth point cloud and an average shape of the corresponding category, generated from Shap-E with the prompt "a {category}". The same ICP pose initialization method is applied for DSP and vMap to ensure a fair comparison. To test the potential performance of vMap [45], we replace its iMAP representation with NeRF [18] and run more optimization iterations until it converges. We provide more details in the Appendix.

4.1 Multi-view Mapping Performance

We present the mapping performance with 1, 3, and 10 RGB-D views on chairs in Table 1. We show qualitative results in Figure 3 and Figure 4. Compared to vMap [45], which lacks priors as additional constraints, our approach yields significant improvements. This is particularly evident with fewer views, where observations are compromised by occlusions and noise. In these instances, prior information serves as a valuable additional constraint. Compared to DSP [3], our method produces more detailed shapes with textures, and outperforms it in both 3 and 10 views. DSP achieves better CD in single-view cases due to a smaller latent space with stronger constraints specifically trained on Chairs. However, it can not generalize to other categories. Shap-E can generate reason-

Views	1		3		10	
Methods	IoU ↑	CD ↓	IoU ↑	CD ↓	IoU ↑	CD ↓
Shap-E [29] + ICP	0.337	**0.169**	-	-	-	-
DSP [3]	-	0.202	-	0.173	-	0.171
vMap [45]	0.370	0.282	0.384	0.184	0.413	0.158
GOM (Ours)	**0.401**	0.267	**0.409**	**0.166**	**0.429**	**0.157**

Table 1: Mapping performance from 1, 3, and 10 RGB-D views on ScanNet Chairs dataset. Since Shap-E can only take in one image, we present a single-view result for Shap-E+ICP.

Tasks	Methods	Chairs	Tables	Cabinets	Sofas	Bookshelfs	Beds	Bathtubs	**Average**
Mapping	Shap-E [29] + ICP *	0.169	0.430	0.268	0.162	0.392	0.813	1.91	0.437
	DSP [3]	0.171	-	-	-	-	-	-	-
	vMap [45]	0.158	0.249	0.200	0.220	0.315	0.729	1.53	0.350
	GOM (Ours)	**0.157**	**0.173**	**0.194**	**0.136**	**0.258**	**0.500**	**1.32**	**0.290**
Recon	Shap-E [29] Image *	0.206	0.184	0.101	0.186	**0.084**	0.266	0.139	0.188
	Shap-E [29] Text	0.211	0.189	0.260	0.187	0.143	0.362	0.207	0.211
	GOM (Ours)	**0.102**	**0.119**	**0.096**	**0.137**	0.098	**0.132**	**0.110**	**0.107**

Table 2: Mapping performance on 7 object categories on ScanNet dataset from 10 RGB-D views for DSP, vMap, and GOM (Ours). * Since Shap-E can only take in one image, we present a single-view result for Shap-E+ICP and Shap-E Image for reference. Metrics: Chamfer Distance (CD).

able chairs from image conditions, as shown in Figure 4. When combined with ICP, it exhibits a low CD, but struggles to faithfully reconstruct objects. Its performance decreases significantly for large objects such as tables, beds and bathtubs, as shown in Table 2. GOM (Ours) achieves better IoU and can continue to improve when provided additional observations. We qualitatively compare to BundleSDF [20] in Figure 4 and we see that GOM delivers better mapping results as it better completes the unseen parts of objects with prior information.

4.2 Multi-categories Performance

We benchmark the open-vocabulary mapping performance for objects across 7 categories using 10 RGB-D views in Table 2. Our approach outperforms the naive use of ICP matching with shapes generated from Shap-E. The ICP matching stuck to a local minimum for the pose with a fixed shape. DSP [3] is a single-category system that requires separate network weights for each category, and since only the chair model is officially available, we present its performance solely for this category. This limitation also restricts the system's applicability. Compared to vMap [45], our approach yields an improved average CD and enhancements across most categories. This highlights the efficacy of our optimization formulation in integrating prior information with observations. We further demonstrate the *Reconstruction* performance in Table 2 (Recon), given the ground truth object poses. Our performance significantly improves compared with Mapping, demonstrating the potential for enhanced performance when more accurate initial poses are available. Our approach outperforms both the text and image-conditioned Shap-E model. This underscores that additional observations can enhance a pre-trained generative model for reconstruction tasks. *We present more experiments on the CO3D dataset and analysis in the Supplementary Materials.*

5 Conclusion

We present a General Object-level Mapping system, *GOM*, leveraging a pre-trained diffusion-based 3D generation model as shape priors. We propose an optimization formulation to couple multi-view RGB-D observations, and diffusion priors to constrain shapes and poses for 3D objects. We achieve state-of-the-art mapping performances among multiple categories without further finetuning. Further exploring the diffusion shape priors into inverse problems with more constraints, e.g., temporal constraints for dynamic tracking, and spatial constraints for complete SLAM, and the application to downstream robotics tasks such as robotics manipulation, will be valuable future work directions.

References

[1] R. F. Salas-Moreno, R. A. Newcombe, H. Strasdat, P. H. Kelly, and A. J. Davison. Slam++: Simultaneous localisation and mapping at the level of objects. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1352–1359, 2013.

[2] B. Xu, W. Li, D. Tzoumanikas, M. Bloesch, A. Davison, and S. Leutenegger. Mid-fusion: Octree-based object-level multi-instance dynamic slam. In *2019 International Conference on Robotics and Automation (ICRA)*, 2019.

[3] J. Wang, M. Rünz, and L. Agapito. Dsp-slam: Object oriented slam with deep shape priors. In *2021 International Conference on 3D Vision (3DV)*, pages 1362–1371. IEEE, 2021.

[4] E. Sucar, K. Wada, and A. Davison. Nodeslam: Neural object descriptors for multi-view shape reconstruction. In *2020 International Conference on 3D Vision (3DV)*, pages 949–958. IEEE, 2020.

[5] S. Yang and S. Scherer. Cubeslam: Monocular 3-d object slam. *IEEE Transactions on Robotics*, 35(4):925–938, 2019.

[6] L. Nicholson, M. Milford, and N. Sünderhauf. Quadricslam: Dual quadrics from object detections as landmarks in object-oriented slam. *IEEE Robotics and Automation Letters*, 4(1):1–8, 2018.

[7] Z. Liao, Y. Hu, J. Zhang, X. Qi, X. Zhang, and W. Wang. So-slam: Semantic object slam with scale proportional and symmetrical texture constraints. *IEEE Robotics and Automation Letters*, 7(2):4008–4015, 2022.

[8] M. Runz, K. Li, M. Tang, L. Ma, C. Kong, T. Schmidt, I. Reid, L. Agapito, J. Straub, S. Lovegrove, et al. Frodo: From detections to 3d objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14720–14729, 2020.

[9] Z. Liao, J. Yang, J. Qian, A. P. Schoellig, and S. L. Waslander. Uncertainty-aware 3d object-level mapping with deep shape priors. *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024.

[10] M. Naseer, S. Khan, and F. Porikli. Indoor scene understanding in 2.5/3d for autonomous agents: A survey. *IEEE access*, 7:1859–1887, 2018.

[11] Y. Wu, Y. Zhang, D. Zhu, X. Chen, S. Coleman, W. Sun, X. Hu, and Z. Deng. Object slam-based active mapping and robotic grasping. In *2021 International Conference on 3D Vision (3DV)*, pages 1372–1381. IEEE, 2021.

[12] D. S. Chaplot, D. P. Gandhi, A. Gupta, and R. R. Salakhutdinov. Object goal navigation using goal-oriented semantic exploration. *Advances in Neural Information Processing Systems*, 33: 4247–4258, 2020.

[13] S. Papatheodorou, N. Funk, D. Tzoumanikas, C. Choi, B. Xu, and S. Leutenegger. Finding things in the unknown: Semantic object-centric exploration with an mav. In *2023 IEEE International Conference on Robotics and Automation (ICRA)*, 2023.

[14] J. Qian, V. Chatrath, J. Servos, A. Mavrinac, W. Burgard, S. L. Waslander, and A. P. Schoellig. Pov-slam: Probabilistic object-aware variational slam in semi-static environments. *arXiv preprint arXiv:2307.00488*, 2023.

[15] C. B. Choy, D. Xu, J. Gwak, K. Chen, and S. Savarese. 3d-r2n2: A unified approach for single and multi-view 3d object reconstruction. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part VIII 14*, pages 628–644. Springer, 2016.

[16] S. Izadi, D. Kim, O. Hilliges, D. Molyneaux, R. Newcombe, P. Kohli, J. Shotton, S. Hodges, D. Freeman, A. Davison, et al. Kinectfusion: real-time 3d reconstruction and interaction using a moving depth camera. In *Proceedings of the 24th annual ACM symposium on User interface software and technology*, pages 559–568, 2011.

[17] Y. Hu, P. Fua, W. Wang, and M. Salzmann. Single-stage 6d object pose estimation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 2930–2939, 2020.

[18] B. Mildenhall, P. P. Srinivasan, M. Tancik, J. T. Barron, R. Ramamoorthi, and R. Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *European conference on computer vision*, pages 405–421. Springer, 2020.

[19] Y. Jiang, D. Ji, Z. Han, and M. Zwicker. Sdfdiff: Differentiable rendering of signed distance fields for 3d shape optimization. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1251–1261, 2020.

[20] B. Wen, J. Tremblay, V. Blukis, S. Tyree, T. Müller, A. Evans, D. Fox, J. Kautz, and S. Birchfield. Bundlesdf: Neural 6-dof tracking and 3d reconstruction of unknown objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 606–617, 2023.

[21] T. D. Barfoot. *State estimation for robotics*. Cambridge University Press, 2024.

[22] G. Harshvardhan, M. K. Gourisaria, M. Pandey, and S. S. Rautaray. A comprehensive survey and analysis of generative models in machine learning. *Computer Science Review*, 38:100285, 2020.

[23] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[24] J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

[25] J. Ho, W. Chan, C. Saharia, J. Whang, R. Gao, A. Gritsenko, D. P. Kingma, B. Poole, M. Norouzi, D. J. Fleet, et al. Imagen video: High definition video generation with diffusion models. *arXiv preprint arXiv:2210.02303*, 2022.

[26] P. Achlioptas, O. Diamanti, I. Mitliagkas, and L. Guibas. Learning representations and generative models for 3d point clouds. In *International conference on machine learning*, pages 40–49. PMLR, 2018.

[27] J. J. Park, P. Florence, J. Straub, R. Newcombe, and S. Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 165–174, 2019.

[28] L. Mescheder, M. Oechsle, M. Niemeyer, S. Nowozin, and A. Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4460–4470, 2019.

[29] H. Jun and A. Nichol. Shap-e: Generating conditional 3d implicit functions. *arXiv preprint arXiv:2305.02463*, 2023.

[30] Z. Shi and R. Liu. Conditional velocity score estimation for image restoration. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 179–188, 2024.

[31] C. Meng, Y. He, Y. Song, J. Song, J. Wu, J.-Y. Zhu, and S. Ermon. Sdedit: Guided image synthesis and editing with stochastic differential equations. *arXiv preprint arXiv:2108.01073*, 2021.

[32] B. Poole, A. Jain, J. T. Barron, and B. Mildenhall. Dreamfusion: Text-to-3d using 2d diffusion. *arXiv preprint arXiv:2209.14988*, 2022.

[33] C.-H. Lin, J. Gao, L. Tang, T. Takikawa, X. Zeng, X. Huang, K. Kreis, S. Fidler, M.-Y. Liu, and T.-Y. Lin. Magic3d: High-resolution text-to-3d content creation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 300–309, 2023.

[34] R. Liu, R. Wu, B. Van Hoorick, P. Tokmakov, S. Zakharov, and C. Vondrick. Zero-1-to-3: Zero-shot one image to 3d object. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9298–9309, 2023.

[35] N. Ruiz, Y. Li, V. Jampani, Y. Pritch, M. Rubinstein, and K. Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 22500–22510, 2023.

[36] M. Liu, C. Xu, H. Jin, L. Chen, M. Varma T, Z. Xu, and H. Su. One-2-3-45: Any single image to 3d mesh in 45 seconds without per-shape optimization. *Advances in Neural Information Processing Systems*, 36, 2024.

[37] A. Nichol, H. Jun, P. Dhariwal, P. Mishkin, and M. Chen. Point-e: A system for generating 3d point clouds from complex prompts. *arXiv preprint arXiv:2212.08751*, 2022.

[38] M. Deitke, D. Schwenk, J. Salvador, L. Weihs, O. Michel, E. VanderBilt, L. Schmidt, K. Ehsani, A. Kembhavi, and A. Farhadi. Objaverse: A universe of annotated 3d objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13142–13153, 2023.

[39] M. Deitke, R. Liu, M. Wallingford, H. Ngo, O. Michel, A. Kusupati, A. Fan, C. Laforte, V. Voleti, S. Y. Gadre, E. VanderBilt, A. Kembhavi, C. Vondrick, G. Gkioxari, K. Ehsani, L. Schmidt, and A. Farhadi. Objaverse-xl: A universe of 10m+ 3d objects. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine, editors, *Advances in Neural Information Processing Systems*, volume 36, pages 35799–35813. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/70364304877b5e767de4e9a2a511be0c-Paper-Datasets_and_Benchmarks.pdf.

[40] C. Cadena, L. Carlone, H. Carrillo, Y. Latif, D. Scaramuzza, J. Neira, I. Reid, and J. J. Leonard. Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age. *IEEE Transactions on robotics*, 32(6):1309–1332, 2016.

[41] R. Hartley and A. Zisserman. *Multiple view geometry in computer vision*. Cambridge university press, 2003.

[42] T. Whelan, R. F. Salas-Moreno, B. Glocker, A. J. Davison, and S. Leutenegger. Elasticfusion: Real-time dense slam and light source estimation. *The International Journal of Robotics Research*, 35(14):1697–1716, 2016.

[43] C. Campos, R. Elvira, J. J. G. Rodríguez, J. M. Montiel, and J. D. Tardós. Orb-slam3: An accurate open-source library for visual, visual–inertial, and multimap slam. *IEEE Transactions on Robotics*, 37(6):1874–1890, 2021.

[44] J. McCormac, R. Clark, M. Bloesch, A. Davison, and S. Leutenegger. Fusion++: Volumetric object-level slam. In *2018 international conference on 3D vision (3DV)*, pages 32–41. IEEE, 2018.

[45] X. Kong, S. Liu, M. Taher, and A. J. Davison. vmap: Vectorised object mapping for neural field slam. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 952–961, 2023.

[46] B. Mildenhall, P. P. Srinivasan, M. Tancik, J. T. Barron, R. Ramamoorthi, and R. Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *Communications of the ACM*, 65(1):99–106, 2021.

[47] Z. Erkoç, F. Ma, Q. Shan, M. Nießner, and A. Dai. Hyperdiffusion: Generating implicit neural fields with weight-space diffusion. *arXiv preprint arXiv:2303.17015*, 2023.

[48] B. Xu, A. J. Davison, and S. Leutenegger. Learning to complete object shapes for object-level mapping in dynamic scenes. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022.

[49] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10684–10695, 2022.

[50] H. Ji and H. Li. 3d human pose analysis via diffusion synthesis. *arXiv preprint arXiv:2401.08930*, 2024.

[51] M. Kwon, J. Jeong, and Y. Uh. Diffusion models already have a semantic latent space. *arXiv preprint arXiv:2210.10960*, 2022.

[52] A. Graikos, N. Malkin, N. Jojic, and D. Samaras. Diffusion models as plug-and-play priors. *Advances in Neural Information Processing Systems*, 35:14715–14728, 2022.

[53] Z. Jiang, Z. Zhou, L. Li, W. Chai, C.-Y. Yang, and J.-N. Hwang. Back to optimization: Diffusion-based zero-shot 3d human pose estimation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 6142–6152, 2024.

[54] J. Lu, J. Lin, H. Dou, Y. Zhang, Y. Deng, and H. Wang. Dposer: Diffusion model as robust 3d human pose prior. *arXiv preprint arXiv:2312.05541*, 2023.

[55] Y. Song, L. Shen, L. Xing, and S. Ermon. Solving inverse problems in medical imaging with score-based generative models. In *International Conference on Learning Representations*, 2021.

[56] G. Yang, A. Kundu, L. J. Guibas, J. T. Barron, and B. Poole. Learning a diffusion prior for nerfs. *arXiv preprint arXiv:2304.14473*, 2023.

[57] X. Deng, Y. Xiang, A. Mousavian, C. Eppner, T. Bretl, and D. Fox. Self-supervised 6d object pose estimation for robot manipulation. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3665–3671, 2020. doi:10.1109/ICRA40945.2020.9196714.

[58] M. Mardani, J. Song, J. Kautz, and A. Vahdat. A variational perspective on solving inverse problems with diffusion models. In *The Twelfth International Conference on Learning Representations*, 2023.

[59] A. Dai, A. X. Chang, M. Savva, M. Halber, T. Funkhouser, and M. Nießner. Scannet: Richly-annotated 3d reconstructions of indoor scenes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5828–5839, 2017.

[60] A. X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Q. Huang, Z. Li, S. Savarese, M. Savva, S. Song, H. Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

[61] A. Avetisyan, M. Dahnert, A. Dai, M. Savva, A. X. Chang, and M. Nießner. Scan2cad: Learning cad model alignment in rgb-d scans. In *Proceedings of the IEEE/CVF Conference on computer vision and pattern recognition*, pages 2614–2623, 2019.

[62] S. Rusinkiewicz and M. Levoy. Efficient variants of the icp algorithm. In *Proceedings third international conference on 3-D digital imaging and modeling*, pages 145–152, 2001.

[63] J. Reizenstein, R. Shapovalov, P. Henzler, L. Sbordone, P. Labatut, and D. Novotny. Common objects in 3d: Large-scale learning and evaluation of real-life 3d category reconstruction. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 10901–10911, 2021.

[64] T. Wu, J. Zhang, X. Fu, Y. Wang, J. Ren, L. Pan, W. Wu, L. Yang, J. Wang, C. Qian, et al. Omniobject3d: Large-vocabulary 3d object dataset for realistic perception, reconstruction and generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 803–814, 2023.

[65] Z. Liao and S. L. Waslander. Multi-view 3d object reconstruction and uncertainty modelling with neural shape prior. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 3098–3107, 2024.

[66] S. L. Bowman, N. Atanasov, K. Daniilidis, and G. J. Pappas. Probabilistic data association for semantic slam. In *2017 IEEE international conference on robotics and automation (ICRA)*, pages 1722–1729. IEEE, 2017.

[67] L. Schmid, M. Abate, Y. Chang, and L. Carlone. Khronos: A unified approach for spatio-temporal metric-semantic slam in dynamic environments. *arXiv preprint arXiv:2402.13817*, 2024.

[68] T. Ren, S. Liu, A. Zeng, J. Lin, K. Li, H. Cao, J. Chen, X. Huang, Y. Chen, F. Yan, et al. Grounded sam: Assembling open-world models for diverse visual tasks. *arXiv preprint arXiv:2401.14159*, 2024.

[69] A. Kirillov, E. Mintun, N. Ravi, H. Mao, C. Rolland, L. Gustafson, T. Xiao, S. Whitehead, A. C. Berg, W.-Y. Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4015–4026, 2023.

[70] B. Kerbl, G. Kopanas, T. Leimkühler, and G. Drettakis. 3d gaussian splatting for real-time radiance field rendering. *ACM Transactions on Graphics*, 42(4), July 2023. URL https://repo-sam.inria.fr/fungraph/3d-gaussian-splatting/.