Nearly Optimal Best-of-Both-Worlds Algorithms for Online Learning with Feedback Graphs

Abstract

This study considers online learning with general directed feedback graphs. For this problem, we present best-of-both-worlds algorithms that achieve nearly tight regret bounds for adversarial environments as well as poly-logarithmic regret bounds for stochastic environments. As Alon et al. [2015] have shown, tight regret bounds depend on the structure of the feedback graph: *strongly observable* graphs yield minimax regret of $\tilde{\Theta}(\alpha^{1/2}T^{1/2})$, while *weakly observable* graphs induce minimax regret of $\tilde{\Theta}(\delta^{1/3}T^{2/3})$, where α and δ, respectively, represent the independence number of the graph and the domination number of a certain portion of the graph. Our proposed algorithm for strongly observable graphs has a regret bound of $\tilde{O}(\alpha^{1/2}T^{1/2})$ for adversarial environments, as well as of $O(\frac{\alpha(\ln T)^3}{\Delta_{\min}})$ for stochastic environments, where $\Delta_{\min}$ expresses the minimum suboptimality gap. This result resolves an open question raised by Erez and Koren [2021]. We also provide an algorithm for weakly observable graphs that achieves a regret bound of $\tilde{O}(\delta^{1/3}T^{2/3})$ for adversarial environments and poly-logarithmic regret for stochastic environments. The proposed algorithms are based on the follow-the-perturbed-leader approach combined with newly designed update rules for learning rates.

1 Introduction

In this paper, we consider *online learning with feedback graphs* [Mannor and Shamir, 2011], a common generalization of the multi-armed bandit problem [Lai et al., 1985, Auer et al., 2002a,b] and the problem of prediction with expert advice [Littlestone and Warmuth, 1994, Freund and Schapire, 1997]. This problem is a sequential decision-making problem formulated with a directed *feedback graph* $G = (V, E)$, where $V = [K] := \{1, 2, \ldots, K\}$ is the set of arms or available actions, and $E \subseteq V \times V$ represents the structure of feedback for choosing actions. In each round of $t = 1, 2, \ldots, T$, a player sequentially chooses an action $I_t \in V$ and then incurs the loss of $\ell_t(I_t)$, where $\ell_t : V \to [0, 1]$ is a loss function chosen by the environment. After choosing the action, the player gets feedback of $\ell_t(j)$ for all j such that the feedback graph G has an edge from I_t to j. If G consists of only self-loops, i.e., if $E = \{(i, i) \mid i \in V\}$, the problem corresponds to a K-armed bandit problem. If G is a complete directed graph with self-loops, i.e., $E = V \times V$, then the problem corresponds to a problem of prediction with expert advice.

Alon et al. [2015] have provided a characterization of minimax regrets for the problem of online learning with feedback graphs. They divide the class of all directed graphs into three categories. For the first category, called *strongly observable graphs*, the minimax regret is $\tilde{\Theta}(\alpha^{1/2}T^{1/2})$, where α is the independence number of the graph G, and $\tilde{\Theta}$ ignores poly-logarithmic factors in T and K. For the second category, *weakly observable graphs*, the minimax regret is $\tilde{\Theta}(\delta^{1/3}T^{2/3})$, where δ represents

Table 1: Regret upper bounds for online learning with feedback graphs. Note that regret bounds by Erez and Koren [2021] only apply to a special case of strongly observable graphs with self-loops.

feedback graph	reference	adversarial	stochastic
strongly observable	[Alon et al., 2015]	$\tilde{O}\left(\alpha^{1/2}T^{1/2}\right)$	$\tilde{O}\left(\alpha^{1/2}T^{1/2}\right)$
	[Erez and Koren, 2021]	$\tilde{O}\left(\theta^{1/2}T^{1/2}\right)$	$O\left(\sum_k \frac{(\ln T)^4}{\Delta_k}\right) = O\left(\frac{\theta(\ln T)^4}{\Delta_{\min}}\right)$
	[This work]	$\tilde{O}\left(\alpha^{1/2}T^{1/2}\right)$	$O\left(\frac{\alpha(\ln T)^3}{\Delta_{\min}}\right)$
weakly observable	[Alon et al., 2015]	$\tilde{O}\left(\delta^{1/3}T^{2/3}\right)$	$\tilde{O}\left(\delta^{1/3}T^{2/3}\right)$
	[This work]	$\tilde{O}\left(\delta^{1/3}T^{2/3}\right)$	$O\left(\frac{\delta(\ln T)^2}{\Delta_{\min}^2} + \frac{K' \ln T}{\Delta_{\min}}\right)$

the *weakly dominating number*. For the last category of *unobservable graphs*, it is not possible to achieve sublinear regret, which means that the minimax regret is $\Theta(T)$. The definitions of categories of graphs and α and δ are given in Section 3.

Best-of-both-worlds (BOBW) algorithms [Bubeck and Slivkins, 2012] have been studied for the purpose of going beyond such minimax regret bounds; they achieve sublinear regret for adversarial environments and, as well, have logarithmic regret bounds for stochastic environments. The only BOBW algorithm for online learning with feedback graphs has been proposed by Erez and Koren [2021]. They have focused on the case in which G is symmetric and all vertices have self-loops, i.e., any edge $(i,j) \in E$ is accompanied by its reversed edge $(j,i) \in E$ and $(i,i) \in E$ for any $i \in V$. Note that this is a special case of strongly observable graphs. For this class of problems, they provide an algorithm that achieves a regret bound of $\tilde{O}(\theta^{1/2}T^{1/2})$ for adversarial environments, and of $O\left(\frac{\theta \mathrm{polylog}(T)}{\Delta_{\min}}\right)$ for stochastic environments, where θ ($\geq \alpha$) is the *clique covering number* of the graph G, and $\Delta_{\min}$ is the minimum *suboptimality gap* for the loss distributions. Their algorithm also works well for adversarially-corrupted stochastic environments, achieving $O\left(\frac{\theta \mathrm{polylog}(T)}{\Delta_{\min}} + \left(\frac{C\theta \mathrm{polylog}(T)}{\Delta_{\min}}\right)^{1/2}\right)$-regret, where C represents the total amount of corruption.

As Erez and Koren [2021] have pointed out, however, their results leave room for improvement, which is due to the fact that the clique covering number θ is significantly larger than the independence number α in some cases. Indeed, there is an example such that $\alpha = 1$ while $\theta = K$, as mentioned in Section 3. This means that regret bound depending on θ is not minimax optimal. In response to this issue, they have raised the question of whether it is possible to replace α with θ in their regret bounds. Contributions of this study include a positive solution to this question.

1.1 Contributions of this study

This study provides BOBW algorithms that achieve minimax regret (up to logarithmic factors) for online learning with general feedback graphs. Our contributions can be summarized as follows:

Theorem 1 (strongly observable case, informal). *For the problem with strongly observable graphs, an algorithm achieves $R_T = \tilde{O}(\alpha^{1/2}T^{1/2})$ for adversarial environments, $R_T = O\left(\frac{\alpha(\ln T)^3}{\Delta_{\min}}\right)$ for stochastic environments, and $R_T = O\left(\frac{\alpha(\ln T)^3}{\Delta_{\min}} + \left(\frac{C\alpha(\ln T)^3}{\Delta_{\min}}\right)^{1/2}\right)$ for adversarially-corrupted stochastic environments, where α is the independence number of feedback graphs.*

Theorem 2 (weakly observable case, informal). *For the problem with weakly observable graphs, an algorithm achieves $R_T = \tilde{O}(\delta^{1/3}T^{2/3})$ for adversarial environments, $R_T = O\left(\frac{\delta(\ln T)^2}{\Delta_{\min}^2} + \frac{K' \ln T}{\Delta_{\min}}\right)$ for stochastic environments, and $R_T = O\left(\frac{\delta(\ln T)^2}{\Delta_{\min}^2} + \left(\frac{C^2\delta(\ln T)^2}{\Delta_{\min}^2}\right)^{1/3} + \frac{K' \ln T}{\Delta_{\min}} + \left(\frac{CK' \ln T}{\Delta_{\min}}\right)\right)$ for adversarially-corrupted stochastic environments, where δ is the weakly dominating number of feedback graphs, and $K' (\leq K)$ is the number of vertices not covered by the weakly dominating set.*

Regret bounds for online learning with feedback graphs are summarized in Table 1. Note that the regret bounds by Erez and Koren [2021] apply only to the special case of strongly observable graphs

that have self-loops for all vertices. Their algorithm and regret bounds are stated with *clique cover* $\{V_k\}_{k=1}^K$ of G, which is a partition of all vertices V such that each V_k is a clique. The clique covering number θ of G is the minimum size K of clique covers. Parameters Δ_k in Table 1 are defined to be the minimum suboptimality gap among actions in V_k, and the summation is taken over $k \in [K]$ such that $\Delta_k > 0$. As the clique covering number θ is larger than or equal to the independence number α of G, our adversarial regret bound of $\tilde{O}\left(\alpha^{1/2}T^{1/2}\right)$ for strongly observable cases is superior to that obtained by Erez and Koren [2021] and is minimax optimal up to logarithmic factors. Although our stochastic regret bound is also better than one by Erez and Koren [2021] in many cases, it is not always so. For example, if $\alpha = \theta$ and $\Delta_{\min}$ is much smaller than many Δ_k, their regret may be better.

Our study includes the first BOBW algorithm that can be applied to online learning with weakly observable graphs. As shown in Table 1, the adversarial regret bounds obtained with the proposed algorithm match the minimax regret bound shown by Alon et al. [2015], up to logarithmic factors. Similarly to their algorithm, the proposed algorithm uses a *weakly dominating set* $D \subseteq V$ of G. If D is a weakly dominating set, all elements in the set of vertices not dominated by D, which is denoted by $V_2 \subseteq V$, have self-loops. Parameters δ and K in the regret bounds are given by $\delta = |D|$ and $K' = |V_2|$. The stochastic regret bound obtained with the proposed algorithm is also nearly tight. In fact, Alon et al. [2015] have shown a regret lower bound of $\tilde{\Omega}\left(\frac{\delta}{\Delta_{\min}^2}\right)$ in the proof of Theorem 7 in their paper. Further, if vertices in V_2 are not connected by edges except for self-loops, the problem is at least harder than the K'-armed bandit problem, which leads to a regret lower bound of $\Omega\left(\frac{K'\ln T}{\Delta_{\min}}\right)$.

1.2 Techniques employed in this study

The proposed algorithms are based on the follow-the-regularized-leader (FTRL) framework, similarly to the algorithms by Alon et al. [2015] and Erez and Koren [2021]. The main differences with existing methods are in the definitions of regularization functions and update rules for learning rates.

For strongly observable cases, we employ the Shannon entropy regularizer functions with a newly developed update rule for learning rates. Most FTRL-based BOBW algorithms are realized by setting the learning rate adaptively to t and/or observations. On the other hand, it is well known that FTRL with Shannon-entropy regularization corresponds to Exp3 algorithm [Auer et al., 2002b] as discussed in, e.g., Lattimore and Szepesvári [2019, Example 28.3]. Since Exp3.G by Alon et al. [2015] achieves an independence-number-dependent regret bound for adversarial environments, it is intuitively natural to expect that a variant of Exp3.G with adaptive learning rates can be used to achieve BOBW regret bounds. However, from the theoretical viewpoint, it is necessary to express the regret depending on the arm-selection distribution q_t to apply the *self-bounding technique* [Gaillard et al., 2014, Zimmert and Seldin, 2021], which plays the central role in the BOBW analysis. Such an expression is highly nontrivial for Shannon-entropy regularization and our contribution lies in this derivation, which can also be of interest for other online learning tasks where Exp3-type algorithms are essentially used, e.g., combinatorial bandits [Cesa-Bianchi and Lugosi, 2012], bandits with delayed feedback [Cesa-Bianchi et al., 2016], and partial monitoring [Bartók et al., 2014].

The proposed algorithm for weakly observable graphs uses novel regularization functions consisting of Tsallis-entropy-based and Shannon-entropy-based regularization. Intuitively, we divide the vertices V into the weakly dominated part V_1 and non-dominated part V_2, and apply Shannon-entropy regularization to V_1 and Tsallis-entropy regularization to V_2. We combine the FTRL method with exploration using a uniform distribution over the weakly dominating set, similarly to the approach by Alon et al. [2015]. However, we adjust exploration rates and learning rates in a carefully designed manner, in contrast to the existing approach that employs fixed parameters. The combination of the above techniques leads to an entropy-dependent regret bound. By applying the self-bounding technique to this bound, we obtain improved regret bounds for stochastic environments.

2 Related work

Since Bubeck and Slivkins [2012] initiated the study of best-of-both-worlds (BOBW) algorithms for the multi-armed bandit (MAB) problem, studies on BOBW algorithms have been extended to a variety of problem settings, including the problem of prediction with expert advice [Gaillard et al.,

2014, Luo and Schapire, 2015], combinatorial semi-bandits [Zimmert et al., 2019], linear bandits [Lee et al., 2021], episodic Markov decision processes [Jin and Luo, 2020, Jin et al., 2021], and online learning with feedback graphs [Erez and Koren, 2021], Among these studies, those using the follow-the-regularized-leader framework [McMahan, 2011] are particularly relevant to our work. In an analysis of algorithms in this category, we show regret bounds that depend on output distributions, and we apply the self-bounding technique to derive BOBW regret bounds. In applying this approach to partial feedback problems including MAB, it has been shown that regularization based on the Tsallis entropy [Zimmert and Seldin, 2021, Zimmert et al., 2019] or the logarithmic barrier [Wei and Luo, 2018, Ito, 2021b] is useful. By way of contrast, our study employs regularization based on the Shannon entropy and demonstrates for the first time that the self-bounding approach can be applied even with such regularization.

This study includes the regret bounds for stochastic environments with adversarial corruption [Lykouris et al., 2018, Gupta et al., 2019, Amir et al., 2020], which is an intermediate setting between stochastic and adversarial settings. Zimmert and Seldin [2021] have demonstrated that the self-bounding technique is also useful in deriving regret bounds for corrupted stochastic environments. Typically, when the self-bounding technique yields a regret bound of $O(\mathcal{R})$ for stochastic environments, it also yields a bound of $O(\mathcal{R} + \sqrt{C\mathcal{R}})$ for corrupted stochastic environments, where C represents the amount of corruption. Examples of such results can be found in the literature, e.g., that by Zimmert and Seldin [2021], Erez and Koren [2021], and Ito [2021a]. Our study follows the same strategy as these studies to obtain regret bounds for corrupted stochastic environments.

The problem of online learning with feedback graphs was formulated by Mannor and Shamir [2011], and Alon et al. [2015] have provided a full characterization of minimax regret w.r.t. this problem. Whereas these studies have considered adversarial models, Caron et al. [2012] have considered stochastic settings and proposed an algorithm with an $O(\ln T)$-regret bound. In addition to these, there can be found studies on such various extensions as models with (uninformed) time-varying feedback graphs [Cohen et al., 2016, Alon et al., 2017], non-stationary environments [Lu et al., 2021a], and corrupted environments [Lu et al., 2021b] as well as such improved algorithms as those with problem-dependent regret bounds [Hu et al., 2020].

3 Problem setting and known results

Let $G = (V, E)$ be a directed graph with $V = [K] = \{1, 2, \ldots, K\}$ and $E \subseteq V \times V$, which we refer to as a *feedback graph*. For each $i \in V$, we denote the in-neighborhood and the out-neighborhood of i in G by $N^{\mathrm{in}}(i)$ and $N^{\mathrm{out}}(i)$, respectively, i.e., $N^{\mathrm{in}}(i) = \{j \in V \mid (j, i) \in E\}$ and $N^{\mathrm{out}}(i) = \{j \in V \mid (i, j) \in E\}$.

Before a game starts, the player is given G. For each round $t = 1, 2, \ldots$, the environment selects the loss functions $\ell_t : V \to [0, 1]$, and the player then chooses $I_t \in V$ without knowing ℓ_t, where the value $\ell_t(i)$ represents the loss for choosing $i \in V$ in the t-th round. After that, the player incurs the loss of $\ell_t(I_t)$ and observes $\ell_t(j)$ for all $j \in N^{\mathrm{out}}(I_t)$. Note that the player cannot observe the incurred loss if $I_t \notin N^{\mathrm{out}}(I_t)$. The goal of the player is to minimize the sum of incurred loss. To evaluate performance, we use the regret R_T defined by

$$R_T(i^*) = \mathbf{E}\left[\sum_{t=1}^{T} \ell_t(I_t) - \sum_{t=1}^{T} \ell_t(i^*)\right], \quad R_T = \max_{i^* \in V} R_T(i^*), \tag{1}$$

where the expectation is taken with respect to the randomness of ℓ_t and the algorithm's internal randomness. The *minimax regret* $R(G, T)$ is defined as the minimum over all randomized algorithms, of the maximum of R_T over all loss sequences $\{\ell_t\}$.

Alon et al. [2015] have shown that the minimax regret can be characterized by the notion of observability:

Definition 1 ([Alon et al., 2015]). A graph G is *observable* if $N^{\mathrm{in}}(i) \neq \emptyset$ holds for each $i \in V$. A graph G is *strongly observable* if $\{i\} \subseteq N^{\mathrm{in}}(i)$ or $V \setminus \{i\} \subseteq N^{\mathrm{in}}(i)$ holds for each $i \in V$. A graph G is *weakly observable* if it is observable but not strongly observable.

We further define the independence number $\alpha(G)$ and the weak domination number $\delta(G)$ as follows:

Definition 2. For a graph $G = (V, E)$, an *independent set* $S \subseteq V$ is a set of vertices such that $u, v \in S, u \neq v \implies (u, v) \notin E$. The *independence number* $\alpha(G)$ of G is the size of its largest

independent set. For a graph $G = (V, E)$, a *weakly dominating set* $D \subseteq V$ is a set of vertices such that $\{i \in V \mid i \notin N^{\mathrm{out}}(i)\} \subseteq \bigcup_{i \in D} N^{\mathrm{out}}(i)$. The *weak domination number* $\delta(G)$ of G is the size of its smallest weakly dominating set.

The minimax regret can then be characterized as follows:

Theorem 3 ([Alon et al., 2015])**.** *Let G be a feedback graph with $|V| \geq 2$. Then, the minimax regret for $T \geq |V|^3$ is (i) $R(G, T) = \tilde{\Theta}(\alpha^{1/2}T^{1/2})$ if G is strongly observable; (ii) $R(G, T) = \tilde{\Theta}(\delta^{1/3}T^{2/3})$ if G is weakly observable; (iii) $R(G, T) = \Theta(T)$ if G is not observable.*

Following this statement by Alon et al. [2015], we assume $T \geq |V|^3 = K^3$ in this paper.

Regret bounds by Erez and Koren [2021] listed in Table 1 depend on the *clique covering number* $\theta(G)$ of the feedback graph. The clique covering number $\theta(G)$ is the minimum value of N such that there exists a *clique cover* $\{V_k\}_{k=1}^N$ for G of size N. A clique cover is a partition of vertices V such that each V_k is a clique, i.e., $V_k \cap V_{k'} = \emptyset$ for all $k \neq k'$, $\bigcup_{k=1}^\theta V_k = V$, and $V_k \times V_k \subseteq E$ holds for any k. While there exists an example such that $K = \theta(G) > \alpha(G) = 1$,[1] we always have $\theta(G) \geq \alpha(G)$, that is, the clique covering number is at least the independence number. In fact, for any clique cover $\{V_k\}_{k=1}^N$ and any independence set $S \subseteq V$, two distinct elements in S can never be in a single clique V_k, which implies that $N \geq |S|$.

In this work, we consider the *stochastically constrained adversarial regime*, a comprehensive regime including stochastic settings, adversarial settings, and adversarially corrupted stochastic settings.

Definition 3 (stochastically constrained adversarial regime [Zimmert and Seldin, 2021])**.** Let $\Delta : V \to [0, 1]$ and $C \geq 0$. The environment is in an *adversarial regime with a (Δ, C, T) self-bounding constraint* if it holds for any algorithm that

$$R_T \geq \mathbf{E}\left[\sum_{t=1}^T \Delta(I_t) - C\right]. \tag{2}$$

As has been shown by Zimmert and Seldin [2021], this regime includes (adversarially corrupted) stochastic settings. Indeed, if ℓ_t follows a distribution $\mathcal{D}$ independently for $t = 1, 2, \ldots, T$ we have $R_T = \max_{i^* \in V} \mathbf{E}\left[\sum_{t=1}^T (\ell_t(I_t) - \ell_t(i^*))\right] = \mathbf{E}\left[\sum_{t=1}^T \Delta(I_t)\right]$, where we define Δ by $\Delta(i) = \mathbf{E}_{\ell \sim \mathcal{D}}[\ell(i)] - \min_{i^* \in V} \mathbf{E}_{\ell \sim \mathcal{D}}[\ell(i^*)]$. This means that the environment is in an adversarial regime with a $(\Delta, 0, T)$ self-bounding constraint. Further, if ℓ_t satisfies $\sum_{t=1}^T \max_{i \in [N]} |\ell_t(i) - \ell_t'(i)| \leq C$ for some $\ell_t' \sim \mathcal{D}$, the environment is in an adversarial regime with a (Δ, C, T) self-bounding constraint. Note also that, for any $\Delta : V \to [0, 1]$, the adversarial regime with a $(\Delta, 2T, T)$ self-bounding constraint includes all the adversarial environments since (2) clearly holds when $C = 2T$.

In this paper, we assume that there exists $i^* \in V$ such that $\Delta(i^*) = 0$ and that $\Delta_{\min} := \min_{i \in V \setminus \{i^*\}} \Delta_i > 0$. This implies that the optimal arm i^* is assumed to be unique. Similar assumptions were also made in previous works using the self-bounding technique [Gaillard et al., 2014, Luo and Schapire, 2015, Wei and Luo, 2018, Zimmert and Seldin, 2021, Erez and Koren, 2021].

4 Preliminary

The proposed algorithms are based on the follow-the-regularized-leader approach. In this approach, we define a probability distribution p_t over V as follows:

$$q_t \in \arg\min_{p \in \mathcal{P}(V)} \left\{ \sum_{s=1}^{t-1} \left\langle \hat{\ell}_s, p \right\rangle + \psi_t(p) \right\}, \quad p_t = (1 - \gamma_t)q_t + \gamma_t\mu_U, \tag{3}$$

where $\mathcal{P}(V) = \{p : V \to [0, 1] \mid \sum_{i \in V} p(i) = 1\}$ expresses the set of all probability distributions over V, $\hat{\ell}_s$ is an unbiased estimator for ℓ_s, $\langle \ell, p \rangle = \sum_{i \in V} \ell(i)p(i)$ represents the inner product, $\psi_t : \mathcal{P} \to \mathbb{R}$ is a convex regularizer function, $\gamma_t \in [0, 0.5]$ is a parameter, and μ_U is the uniform

---

[1]For example, consider the graph $G = (V, E)$ given by $V = [K]$ and $E = \{(i, j) \in V \times V \mid i \geq j\}$.

distribution over a nonempty subset $U \subseteq V$, i.e., $\mu_U(i) = 1/|U|$ for $i \in U$ and $\mu_U(i) = 0$ for $i \in V \setminus U$. After computing p_t defined by (3), we choose I_t following p_t so that $\Pr[I_t = i|p_t] = p_t(i)$. We then observe $\ell_t(j)$ for each $j \in N^{\text{out}}(I_t)$. Based on these observations, we set the unbiased estimator $\hat{\ell}_t : V \to \mathbb{R}$ by

$$\hat{\ell}_t(i) = \frac{\ell_t(i)}{P_t(i)} \mathbf{1}[i \in N^{\text{out}}(I_t)], \quad P_t(i) = \sum_{j \in N^{\text{in}}(i)} p_t(j). \tag{4}$$

Let D_t denote the *Bregman divergence* with respect to ψ_t, i.e.,

$$D_t(p, q) = \psi_t(p) - \psi_t(q) - \langle \nabla \psi_t(q), p - q \rangle. \tag{5}$$

We then have the following regret bounds:

Lemma 1. *If I_t is chosen by the above procedure, the regret is bounded by*

$$R_T \leq \mathbf{E}\left[\sum_{t=1}^{T}\left(\gamma_t + \left\langle \hat{\ell}_t, q_t - q_{t+1} \right\rangle - D_t(q_{t+1}, q_t) + \psi_t(q_{t+1}) - \psi_t(q_{t+1})\right)\right] + \psi_{T+1}(\mu_{i^*}) - \psi_1(q_1), \tag{6}$$

where $\mu_{i^*}(i) = 1$ if $i = i^*$ and $\mu_{i^*}(i) = 0$ for $i \in V \setminus \{i^*\}$.

This lemma can be shown by the standard analysis technique for FTRL, e.g., given in Exercise 28.12 of the book by Lattimore and Szepesvári [2019], combined with the fact that $\hat{\ell}_t$ defined by (4) is an unbiased estimator of ℓ_t. All omitted proofs will be given in the appendix.

We also introduce the following parameters $Q(i^*)$ and Q, which will be used when applying self-bounding technique:

$$Q(i^*) = \sum_{t=1}^{T}(1 - q_t(i^*)), \quad \bar{Q}(i^*) = \mathbf{E}\left[Q(i^*)\right], \quad \bar{Q} = \min_{i^* \in V} \bar{Q}(i^*). \tag{7}$$

We note that these values are clearly bounded as $0 \leq \bar{Q} \leq \bar{Q}(i^*) \leq T$ for any $i^* \in V$. In an adversarial regime with a self-bounding constraint, the regret can be bounded from below, as follows:

Lemma 2. *In an adversarial regime with a self-bounding constraint given in Definition 3, the regret is bounded as $R_T \geq \frac{\Delta_{\min}}{2}\bar{Q} - C$.*

This lemma will be used to show poly-logarithmic regret in adversarial regime with a self-bounding constraint.

5 Strongly observable case

This section provides an algorithm achieving regret bounds in Theorem 1. We set $U = V$ and define ψ_t using the Shannon entropy $H(p)$ as follows:

$$\psi_t(p) = -\beta_t H(p), \quad \text{where} \quad H(p) = \sum_{i \in V} p(i) \ln \frac{1}{p(i)}, \tag{8}$$

where $\beta_t > 0$ will be defined later. If we choose $\gamma_t = \min\left\{\left(\frac{1}{\alpha T}\right)^{1/2}, \frac{1}{2}\right\}$ and $\beta_t = \frac{1}{2\gamma_t}$ for all t, the FTRL algorithm (3) with (8) coincides with the Exp3.G algorithm with the parameter setting given in Theorem 2 (i) by Alon et al. [2015]. As shown by them, this round-independent parameter setting leads to a regret bound of $R_T = O(\alpha^{1/2}T^{1/2}\ln(KT))$.

In this work, we modify the update rule of β_t and γ_t as follows: We set $\beta_1 = c_1 \geq 1$ and update β_t and γ_t by

$$\beta_{t+1} = \beta_t + \frac{c_1}{\sqrt{1 + (\ln K)^{-1}\sum_{s=1}^{t} a_s}}, \quad \gamma_t = \frac{1}{2\beta_t}, \tag{9}$$

where a_s is defined by $a_s = H(q_s)$. In the following, we will show the following regret bounds:

Theorem 4. *If the feedback graph G is strongly observable and has the independent number $\alpha = \alpha(G)$, the FTRL algorithm (3) with $U = V$ and ψ_t defined by (8) and (9) enjoys a regret bound of*

$$R_T \leq \hat{c} \cdot \max\left\{\bar{Q}^{1/2}, 1\right\}, \text{ where } \hat{c} = O\left(\left(\frac{\alpha \ln T \cdot \ln(c_1 K T)}{c_1 \sqrt{\ln K}} + c_1 \sqrt{\ln K}\right)\sqrt{\ln(KT)}\right). \quad (10)$$

Consequently, we have $R_T = O\left(\hat{c}\sqrt{T}\right)$ in adversarial regimes and $R_T = O\left(\frac{\hat{c}^2}{\Delta_{\min}} + \sqrt{\frac{C\hat{c}^2}{\Delta_{\min}}}\right)$ in adversarial regimes with self-bounding constraints.

When we set $c_1 = \Theta\left(\sqrt{\frac{\alpha \ln T \cdot \ln(KT)}{\ln K}}\right)$, $\hat{c}$ in this theorem is at most $O\left(\sqrt{\alpha \ln T \cdot (\ln(KT))^2}\right)$, which leads to the regret bounds in Theorem 1. In the rest of this section, we provide proof for Theorem 4.

Let us start with the following lemma:

Lemma 3. *If ψ_t is given by (8) with $\beta_t \geq 1$ and $\gamma_t \geq 1/(2\beta_t)$, the regret for the FTRL algorithm (3) with $U = V$ is bounded as*

$$R_T \leq \mathbf{E}\left[\sum_{t=1}^{T}\left(\gamma_t + \frac{2}{\beta_t}\left(1 + 4\alpha \ln \frac{K^2}{4\gamma_t}\right) + (\beta_{t+1} - \beta_t)a_{t+1}\right)\right] + \beta_1 \ln K, \quad (11)$$

where $a_t = H(q_t)$ is the value of the Shannon entropy for q_t.

This lemma follows from Lemma 1 and the technique used in the proof of Alon et al. [2015, Theorem 2]. We note that $0 \leq a_t \leq \ln K$ and $a_1 = \ln K$. From Lemma 3 and the update rules of parameters given by (9), we obtain the following entropy-dependent regret bound:

Proposition 1. *Suppose (11) holds. If β_t and γ_t are given by (9), $R_T \leq \tilde{c}\,\mathbf{E}\left[\sqrt{\sum_{t=1}^{T} a_t}\right]$, where $a_t = H(q_t)$ and $\tilde{c} = O\left(\frac{\alpha \ln T \cdot \ln(c_1 K T)}{c_1 \sqrt{\ln K}} + c_1 \sqrt{\ln K}\right)$.*

Proof. We will show the following two inequalities:

$$\sum_{t=1}^{T}\left(\gamma_t + \frac{2}{\beta_t}\left(1 + 4\alpha \ln \frac{K^2}{4\gamma_t}\right)\right) = O\left(\frac{\alpha \ln T \cdot \ln(c_1 K^2 T)}{c_1 \sqrt{\ln K}}\sqrt{\sum_{t=1}^{T} a_t}\right), \quad (12)$$

$$\sum_{t=1}^{T}(\beta_{t+1} - \beta_t)a_{t+1} = O\left(c_1 \sqrt{\ln K}\sqrt{\sum_{t=1}^{T} a_t}\right). \quad (13)$$

Let us first show (12). From the definition of γ_t given in (9), we have [LHS of (12)] $\leq \sum_{t=1}^{T}\frac{1}{\beta_t}\left(3 + 8\alpha \ln \frac{c_1 K^2 t}{2}\right) \leq \left(3 + 8\alpha \ln \frac{c_1 K^2 T}{2}\right)\sum_{t=1}^{T}\frac{1}{\beta_t}$. From the definition of β_t given by (9), β_t is bounded as $\beta_t = c_1 + \sum_{u=1}^{t-1}\frac{c_1}{\sqrt{1 + (\ln K)^{-1}\sum_{s=1}^{u} a_s}} \geq \frac{c_1 t}{\sqrt{1 + (\ln K)^{-1}\sum_{s=1}^{t} a_s}}$. We hence have $\sum_{t=1}^{T}\frac{1}{\beta_t} \leq \sum_{t=1}^{T}\frac{1}{c_1 t}\sqrt{1 + (\ln K)^{-1}\sum_{s=1}^{t} a_s} \leq \frac{1 + \ln T}{c_1}\sqrt{1 + (\ln K)^{-1}\sum_{t=1}^{T} a_t} \leq O\left(\frac{\ln T}{c_1 \sqrt{\ln K}}\sqrt{\sum_{t=1}^{T} a_t}\right)$, where the last inequality follows from $a_1 = \ln K$. Combining the above inequalities, we obtain (12).

Let us next show (13). From (9), we have [LHS of (13)] $= \sum_{t=1}^{T}\frac{c_1}{\sqrt{1 + (\ln K)^{-1}\sum_{s=1}^{t} a_s}} \cdot a_{t+1} = 2c_1 \sqrt{\ln K}\sum_{t=1}^{T}\frac{a_{t+1}}{\sqrt{\ln K + \sum_{s=1}^{t} a_s} + \sqrt{\ln K + \sum_{s=1}^{t} a_s}} \leq 2c_1 \sqrt{\ln K}\sum_{t=1}^{T}\frac{a_{t+1}}{\sqrt{\sum_{s=1}^{t+1} a_s} + \sqrt{\sum_{s=1}^{t} a_s}} = 2c_1 \sqrt{\ln K}\sum_{t=1}^{T}\left(\sqrt{\sum_{s=1}^{t+1} a_s} - \sqrt{\sum_{s=1}^{t} a_s}\right) = 2c_1 \sqrt{\ln K}\left(\sqrt{\sum_{s=1}^{T+1} a_s} - \sqrt{a_1}\right) \leq 2c_1 \sqrt{\ln K}\sqrt{\sum_{t=1}^{T} a_t}$, where inequalities follow from $a_t \leq a_1 = \ln K$. This proves (13).

Inequalities (12) and (13) combined with (11) lead to the regret bound in Proposition 1. $\qquad\square$

270 In addition, $\sum_{t=1}^{T} a_t = \sum_{t=1}^{T} H(q_t)$ is bounded with $Q(i^*)$ defined in (7), as follows:

271 **Lemma 4.** *Suppose $a_t = H(q_t)$. For any $i^* \in V$, we have $\sum_{t=1}^{T} a_t \le Q(i^*) \ln \frac{eKT}{Q(i^*)}$.*

272 We are now ready to prove Theorem 4.

273 *Proof of Theorem 4.* From Lemma 4, if $Q(i^*) \le e$, we have $\sum_{t=1}^{T} a_t \le e \ln(KT)$ and otherwise, we
274 have $\sum_{t=1}^{T} a_t \le Q(i^*) \ln(KT)$. Hence, we have $\sum_{t=1}^{T} a_t \le \ln(KT) \cdot \max\{e, Q(i^*)\}$. Combining
275 this with Proposition 1, we obtain (10). Since $\bar{Q} \le T$, we have $R_T \le \hat{c}\sqrt{T}$ in adversarial regimes.
276 We next show $R_T = O\left(\frac{\hat{c}^2}{\Delta_{\min}} + \sqrt{\frac{C\hat{c}^2}{\Delta_{\min}}}\right)$.

277 From Lemma 2, (2) implies if the environment satisfies (Δ, C, T) self-bounding constraint (2), we
278 have $R_T \ge \frac{\Delta_{\min}}{2}\bar{Q} - C$. Combining this with Proposition 1 and Lemma 4, it holds for any $\lambda > 0$
279 that

$$R_T = (1+\lambda)R_T - \lambda R_T \le (1+\lambda)\tilde{c}\sqrt{\bar{Q}\ln(KT)} - \frac{\lambda\Delta_{\min}}{2}\bar{Q} + \lambda C$$

$$\le \frac{((1+\lambda)\tilde{c})^2 \ln(KT)}{2\lambda\Delta_{\min}} + \lambda C = \frac{\tilde{c}^2 \ln(KT)}{\Delta_{\min}} + \frac{1}{2\lambda}\frac{\tilde{c}^2 \ln(KT)}{\Delta_{\min}} + \frac{\lambda}{2}\left(\frac{\tilde{c}^2 \ln(KT)}{\Delta_{\min}} + 2C\right),$$

280 where the first inequality follows from Proposition 1, Lemma 4, the condition of $Q(i^*) \ge e$,
281 and (25). The second inequality follows from $a\sqrt{x} - \frac{b}{2}x = \frac{a^2}{2b} - \frac{1}{2}\left(\frac{a}{\sqrt{b}} - \sqrt{bx}\right) \le \frac{a^2}{2b}$ which
282 holds for any $a, b, x \ge 0$. By choosing $\lambda = \sqrt{\frac{\tilde{c}^2 \ln(KT)}{\Delta_{\min}} / \left(\frac{\tilde{c}^2 \ln(KT)}{\Delta_{\min}} + 2C\right)}$, we obtain $R_T =$
283 $O\left(\frac{\hat{c}^2}{\Delta_{\min}} + \sqrt{\frac{C\hat{c}^2}{\Delta_{\min}}}\right)$. □

6 Weakly observable case

285 This section provides an algorithm achieving regret bounds in Theorem 2. Let D be a weakly
286 dominating set, defined in Definition 2, and let $V_1 = \bigcup_{i \in D} N^{\text{out}}(i)$, $V_2 = V \setminus V_1$. We consider here
287 the FTRL approach given by (3) with $U = D$ and regularizer functions defined as

$$\psi_t(p) = \beta_t \sum_{i \in V_1} h(p(i)) + \sum_{i \in V_2} \sqrt{t}g(p(i)),$$

$$\text{where} \quad h(x) = x \ln x + (1-x)\ln(1-x), \quad g(x) = -2\sqrt{x} - 2\sqrt{1-x}. \quad (14)$$

288 The regularization with $h(x)$ for V_1 is a variant of Shannon-entropy regularization, which can be
289 considered as a modification of the approach of the Exp3.G by Alon et al. [2015]. The remaining
290 part defined with $g(x)$ for V_2 is a modification of the approach used in the Tsallis-INF algorithm by
291 Zimmert and Seldin [2021], which is a BOBW algorithm for MAB problems. Intuitively, approaches
292 for MAB work well for vertices in V_2 as they have self-loops, i.e., choosing actions in V_2 admits
293 bandit feedback.

294 Let us define parameters γ_t and β_t by $\beta_1 = c_2$ and

$$\gamma_t' = \frac{c_1 b_t}{c_1 + \left(\sum_{s=1}^{t} b_s\right)^{1/3}}, \quad \beta_{t+1} = \beta_t + \frac{c_2 b_t}{\gamma_t' \left(c_1 + \sum_{s=1}^{t-1} \frac{b_s a_{s+1}}{\gamma_s'}\right)^{1/2}}, \quad \gamma_t = \gamma_t' + \frac{2|D|}{\beta_t}, \quad (15)$$

295 where $c_1, c_2 > 0$ are input parameters such that $c_1 \ge 2\ln K$ and with $\{a_t\}$ and $\{b_t\}$ are defined by

$$a_t = -\sum_{i \in V_1} h(q_t(i)), \quad b_t = \sum_{i \in V_1} q_t(i)(1 - q_t(i)). \quad (16)$$

296 Note that a_t and $\hat{c}$ used in this Section 6 are different from those defined in Section 5. We then have
297 the following regret bounds:

298 **Theorem 5.** *If the feedback graph G is weakly observable, the FTRL algorithm (3) with $U = D$ and*
299 *ψ_t defined by (14) and (15) enjoys a regret bound of*

$$R_T \le \hat{c} \cdot \max\left\{\bar{Q}^{2/3}, c_1^2\right\} + O\left((|V_2|\ln T \cdot \bar{Q})^{1/2}\right), \quad \text{where}$$

$$\hat{c} = O\left(c_1 + \frac{1}{\sqrt{c_1}}\left(\frac{|D|\ln T}{c_2} + c_2\right)\sqrt{\ln(KT)}\right). \quad (17)$$

Consequently, if $T \geq K^3$, we have $R_T = O\left(\hat{c}T^{2/3}\right)$ in adversarial regimes and

$$R_T = O\left(\frac{\hat{c}^3}{\Delta_{\min}^2} + \left(\frac{C^2\hat{c}^3}{\Delta_{\min}^2}\right)^{1/3} + \frac{|V_2|\ln T}{\Delta_{\min}} + \sqrt{\frac{C|V_2|\ln T}{\Delta_{\min}}}\right) \tag{18}$$

in adversarial regimes with self-bounding constraints.

We obtain $\hat{c} = O\left((|D|\ln T \cdot \ln(KT))^{1/3}\right)$ by setting $c_1 = \Theta\left((|D|\ln T \cdot \ln(KT))^{1/3}\right)$ and $c_2 = \Theta\left(\sqrt{|D|\ln T}\right)$. By using a weakly dominating set D such that $|D| = O(\delta(G))$, we obtain the regret bounds in Theorem 2. The remainder of this section is dedicated to the proof of Theorem 5.

We start with the following regret bound:

Lemma 5. *If ψ_t is given by (14) and if $\gamma_t \geq \frac{2|D|}{\beta_t}$, we have $R_T \leq R_T^{(1)} + R_T^{(2)}$, where*

$$R_T^{(1)} = O\left(\mathbf{E}\left[\sum_{t=1}^{T}\left(\gamma_t + \frac{|D|b_t}{\gamma_t\beta_t} + (\beta_{t+1} - \beta_t)a_{t+1}\right) + a_1\beta_1\right]\right), \tag{19}$$

$$R_T^{(2)} = O\left(\mathbf{E}\left[\sum_{t=1}^{T}\frac{1}{\sqrt{t}}\sum_{i\in V_2}\sqrt{q_t(i)(1 - q_t(i))}\right]\right), \tag{20}$$

with $\{a_t\}$ and $\{b_t\}$ defined by (16).

When showing (19) and (20), we use techniques used in the proofs of Alon et al. [2015, Theorem 2] and of Zimmert and Seldin [2021, Lemma 11]. We then have the following bound:

Proposition 2. *If γ_t and β_t are given by (15), $R_T^{(1)}$ satisfying (19) is bounded as*

$$R_T^{(1)} = O\left(\mathbf{E}\left[c_1 B_T^{2/3} + \tilde{c}\sqrt{c_1^2 + (\ln K + A_T)\left(c_1 + B_T^{1/3}\right)}\right]\right), \tag{21}$$

where $A_T = \sum_{t=1}^{T} a_t$, $B_T = \sum_{t=1}^{T} b_t$ and $\tilde{c} = O\left(\frac{1}{\sqrt{c_1}}\left(\frac{|D|\ln T}{c_2} + c_2\right)\right)$.

Values of A_T and B_T in this proposition can be bounded with $Q(i^*)$ defined in (7), as follows:

Lemma 6. *A_T and B_T defined in Proposition 2 satisfy $A_T \leq 2Q(i^*)\ln\frac{eKT}{Q(i^*)}$ and $B_T \leq 2Q(i^*)$.*

Further, $R_T^{(2)}$ in Lemma 5 can be bounded with $\bar{Q}$ as follows:

Lemma 7. *$R_T^{(2)}$ satisfying (20) is bounded as $R_T^{(2)} = O\left(\sqrt{|V_2|\ln T \cdot \bar{Q}}\right)$.*

Proof of Theorem 5. From Proposition 2 and Lemma 6, if $\bar{Q} \geq c_1^3$, we have

$$R_T^{(1)} = O\left(\mathbf{E}\left[c_1 Q(i^*)^{2/3} + \tilde{c}\sqrt{Q(i^*)\ln(KT)Q(i^*)^{1/3}}\right]\right) \leq O\left(\left(c_1 + \tilde{c}\sqrt{\ln(KT)}\right)\bar{Q}^{2/3}\right),$$

where the inequality follows from Jensen's inequality. Hence, there exists $\hat{c}$ such that $R_T^{(1)} \leq \hat{c} \cdot \bar{Q}^{2/3}$ and $\hat{c} = O\left(c_1 + \tilde{c}\sqrt{\ln(KT)}\right)$. Combining this with Lemma 7, we obtain (17). As we have $\bar{Q} \leq T$, in adversarial regimes with $T \geq K^3$, it follows from (17) that $R_T = O\left(\hat{c} \cdot \max\{T^{2/3}, c_1^2\} + (K\ln T \cdot T)^{1/2}\right) = O\left(\hat{c} \cdot T^{2/3}\right)$, where the second equality follows from the $T \geq K^3$. Let us next show (18). From (17) and Lemma 2, for any $\lambda \in (0, 1]$, we have

$$R_T = (1 + \lambda)R_T - \lambda R_T = O\left((1 + \lambda)\hat{c} \cdot \bar{Q}^{2/3} + (1 + \lambda)(|V_2|\ln T \cdot \bar{Q})^{1/2} - \lambda\Delta_{\min}\bar{Q} + \lambda C\right).$$

By an argument similar to the proof of Theorem 4, we have $(1 + \lambda)(|V_2|\ln T \cdot \bar{Q})^{1/2} - \lambda\Delta_{\min}\bar{Q} = O\left(\left(1 + \frac{1}{\lambda}\right)\frac{|V_2|\ln T}{\Delta_{\min}}\right)$. We also have $(1 + \lambda)\hat{c} \cdot \bar{Q}^{2/3} - \lambda\Delta_{\min}\bar{Q} = \left(\frac{(1+\lambda)^3\hat{c}^3}{\lambda^2\Delta_{\min}^2}\right)^{1/3}\left(\lambda\Delta_{\min}\bar{Q}\right)^{2/3} - \lambda\Delta_{\min}\bar{Q} = O\left(\frac{(1+\lambda)^3\hat{c}^3}{\lambda^2\Delta_{\min}^2}\right) = O\left(\left(1 + \frac{1}{\lambda^2}\right)\frac{\hat{c}^3}{\Delta_{\min}^2}\right)$, where the second equality follows from $x^{1/3}y^{2/3} \leq \frac{1}{3}x + \frac{2}{3}y$ that holds for any $x, y \geq 0$. Combining these inequalities, we obtain $R_T = O\left(\left(1 + \frac{1}{\lambda^2}\right)\frac{\hat{c}^3}{\Delta_{\min}^2} + \left(1 + \frac{1}{\lambda}\right)\frac{|V_2|\ln T}{\Delta_{\min}} + \lambda C\right)$. By choosing λ that minimizes the RHS, we obtain (18). $\qquad\square$

References

N. Alon, N. Cesa-Bianchi, O. Dekel, and T. Koren. Online learning with feedback graphs: Beyond bandits. *Journal of Machine Learning Research*, 40(2015), 2015.

N. Alon, N. Cesa-Bianchi, C. Gentile, S. Mannor, Y. Mansour, and O. Shamir. Nonstochastic multi-armed bandits with graph-structured feedback. *SIAM Journal on Computing*, 46(6):1785–1826, 2017.

I. Amir, I. Attias, T. Koren, Y. Mansour, and R. Livni. Prediction with corrupted expert advice. *Advances in Neural Information Processing Systems*, 33:14315–14325, 2020.

P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2):235–256, 2002a.

P. Auer, N. Cesa-Bianchi, Y. Freund, and R. E. Schapire. The nonstochastic multiarmed bandit problem. *SIAM Journal on Computing*, 32(1):48–77, 2002b.

G. Bartók, D. P. Foster, D. Pál, A. Rakhlin, and C. Szepesvári. Partial monitoring – classification, regret bounds, and algorithms. *Mathematics of Operations Research*, 39(4):967–997, 2014.

S. Bubeck and A. Slivkins. The best of both worlds: Stochastic and adversarial bandits. In *Conference on Learning Theory*, pages 42–1. JMLR Workshop and Conference Proceedings, 2012.

S. Caron, B. Kveton, M. Lelarge, and S. Bhagat. Leveraging side observations in stochastic bandits. In *Proceedings of the Twenty-Eighth Conference on Uncertainty in Artificial Intelligence*, pages 142–151, 2012.

N. Cesa-Bianchi and G. Lugosi. Combinatorial bandits. *Journal of Computer and System Sciences*, 78(5):1404–1422, 2012.

N. Cesa-Bianchi, C. Gentile, Y. Mansour, and A. Minora. Delay and cooperation in nonstochastic bandits. In *Conference on Learning Theory*, pages 605–622. PMLR, 2016.

A. Cohen, T. Hazan, and T. Koren. Online learning with feedback graphs without the graphs. In *International Conference on Machine Learning*, pages 811–819. PMLR, 2016.

L. Erez and T. Koren. Towards best-of-all-worlds online learning with feedback graphs. *Advances in Neural Information Processing Systems*, 34, 2021.

Y. Freund and R. E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of computer and system sciences*, 55(1):119–139, 1997.

P. Gaillard, G. Stoltz, and T. Van Erven. A second-order bound with excess losses. In *Conference on Learning Theory*, pages 176–196. PMLR, 2014.

A. Gupta, T. Koren, and K. Talwar. Better algorithms for stochastic bandits with adversarial corruptions. In *Conference on Learning Theory*, pages 1562–1578. PMLR, 2019.

B. Hu, N. A. Mehta, and J. Pan. Problem-dependent regret bounds for online learning with feedback graphs. In *Uncertainty in Artificial Intelligence*, pages 852–861. PMLR, 2020.

S. Ito. On optimal robustness to adversarial corruption in online decision problems. In *Advances in Neural Information Processing Systems*, 2021a.

S. Ito. Parameter-free multi-armed bandit algorithms with hybrid data-dependent regret bounds. In *Conference on Learning Theory*, pages 2552–2583. PMLR, 2021b.

T. Jin and H. Luo. Simultaneously learning stochastic and adversarial episodic mdps with known transition. *Advances in Neural Information Processing Systems*, 33:16557–16566, 2020.

T. Jin, L. Huang, and H. Luo. The best of both worlds: stochastic and adversarial episodic mdps with unknown transition. *Advances in Neural Information Processing Systems*, 34, 2021.

T. L. Lai, H. Robbins, et al. Asymptotically efficient adaptive allocation rules. *Advances in applied mathematics*, 6(1):4–22, 1985.

T. Lattimore and C. Szepesvári. Bandit algorithms. *preprint, Revision: 1699*, 2019.

C.-W. Lee, H. Luo, C.-Y. Wei, M. Zhang, and X. Zhang. Achieving near instance-optimality and minimax-optimality in stochastic and adversarial linear bandits simultaneously. In *International Conference on Machine Learning*, pages 6142–6151, 2021.

N. Littlestone and M. K. Warmuth. The weighted majority algorithm. *Information and computation*, 108(2):212–261, 1994.

S. Lu, Y. Hu, and L. Zhang. Stochastic bandits with graph feedback in non-stationary environments. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI)*, 2021a.

S. Lu, G. Wang, and L. Zhang. Stochastic graphical bandits with adversarial corruptions. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI)*, 2021b.

H. Luo and R. E. Schapire. Achieving all with no parameters: AdaNormalHedge. In *Conference on Learning Theory*, pages 1286–1304. PMLR, 2015.

T. Lykouris, V. Mirrokni, and R. Paes Leme. Stochastic bandits robust to adversarial corruptions. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 114–122, 2018.

S. Mannor and O. Shamir. From bandits to experts: On the value of side-observations. *Advances in Neural Information Processing Systems*, 24, 2011.

B. McMahan. Follow-the-regularized-leader and mirror descent: Equivalence theorems and l1 regularization. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 525–533. JMLR Workshop and Conference Proceedings, 2011.

C.-Y. Wei and H. Luo. More adaptive algorithms for adversarial bandits. In *Conference on Learning Theory*, pages 1263–1291, 2018.

J. Zimmert and Y. Seldin. Tsallis-inf: An optimal algorithm for stochastic and adversarial bandits. *Journal of Machine Learning Research*, 22(28):1–49, 2021.

J. Zimmert, H. Luo, and C.-Y. Wei. Beating stochastic and adversarial semi-bandits optimally and simultaneously. In *International Conference on Machine Learning*, pages 7683–7692. PMLR, 2019.