MARS: Toward More Efficient Multi-Agent Collaboration for LLM Reasoning

Abstract

Large language models (LLMs) have achieved impressive results in natural language understanding, yet their reasoning capabilities remain limited when operating as single agents. Multi-Agent Debate (MAD) has been proposed to address this limitation by enabling collaborative reasoning among multiple models in a round-table debate manner. While effective, MAD introduces substantial computational overhead due to the number of agents involved and the frequent communication required. In this paper, we propose MARS (Multi-Agent Review System), a role-based collaboration framework inspired by the review process. In MARS, an author agent generates an initial solution, reviewer agents provide decisions and comments independently, and a meta-reviewer integrates the feedback to make the final decision and guide further revision. This design enhances reasoning quality while avoiding costly reviewer-to-reviewer interactions, thereby controlling resource consumption. We compared MARS with both MAD and other state-of-the-art reasoning strategies across multiple benchmarks. Extensive experiments with different LLMs show that MARS matches the accuracy of MAD while reducing token usage by approximately 50%. Code is available at https://anonymous.4open.science/r/MARS_Anonymous-7471/README.md.

1 Introduction

Recent advances in large language models (LLMs) have brought revolutionary changes to the field of natural language processing and understanding (Minaee et al., 2024; Hadi et al., 2023; Li et al., 2025; Brown et al., 2020). With their unprecedented performance on language generation tasks such as chat completion, question answering, and code generation, these models are expected to extend their impact to more general and challenging real-world applications, including knowledge-intensive reasoning. However, when it comes to problems involving deep factual knowledge and complex structures, their reasoning abilities still remain limited (Mirzadeh et al., 2024; Jiang et al., 2024). For instance, many state-of-the-art models can only achieve about 30% - 40% accuracy on the GPQA benchmark.

To enhance reasoning during inference, several prompting techniques have been proposed, including Chain-of-Thought (CoT) (Wei et al., 2022), Tree-of-Thought (ToT) (Yao et al., 2023), and self-reflection (Shinn et al., 2023). While these approaches significantly improve LLM performance, they operate in a single-agent setting, where the model lacks external feedback and often fails to correct its own mistakes. Motivated by this limitation, recent works have explored multi-agent collaboration, in which agents provide feedback to each other to enhance reasoning. Among these, the Multi-Agent Debate (MAD) framework (Du et al., 2023) is the most widely adopted: multiple agents are recruited to tackle the same problem, exchange responses, and refine their answers by considering disagreements, with the final solution derived via majority voting after a round-table discussion.

Despite MAD achieving a significantly improved performance in reasoning, a key drawback is its high resource cost: both token consumption and inference time increase substantially compared to single-agent systems, due to intensive communication among agents. This raises a fundamental question: **Can we reduce resource consumption while preserving the response quality of multi-agent reasoning?**

To address this challenge, we draw inspiration from two sources: verifier-based architectures and the hierarchical evaluation structure of peer review. On one hand, recent studies on agent tuning with synthesized trajectories incorporate verifiers or critics as key components (Fu et al., 2025; Gao et al., 2024; Shi et al., 2025). These verifiers, either rule-based or LLM-based, check and filter low-quality

trajectories or intermediate results, underscoring the importance of systematic review and quality control. On the other hand, peer review practices demonstrate the effectiveness of hierarchical evaluation: authors (or agents) refine their work based on structured feedback, while final decisions are reached through systematic aggregation. Unlike the round-table discussion in MAD, where agents communicate freely, peer review emphasizes independence: reviewers provide evaluations without direct interaction, yet the process reliably converges to fair and consistent outcomes.

Based on these considerations, we propose **M**ulti-**A**gent **R**eview **S**ystem (**MARS**) for LLM reasoning, in which agents take on the roles of author, reviewers, and meta-reviewer to mimic a structured review process. Given a user query, the author agent first generates an initial response. Instead of producing their own answers from scratch, reviewer agents evaluate this response, focusing on identifying potential errors. Different to the round-table discussion in MAD, where agents engage in frequent communication, reviewers in MARS operate independently, each providing a decision, review comments, and a confidence score. The meta-reviewer then aggregates these evaluations and issues a final judgment with justification: if the decision is *accept*, the author's initial response is adopted as the final answer; if the decision is *reject*, the meta-reviewer generates feedback to guide the author's revision. By structuring collaboration around independent review and feedback, MARS matches the reasoning quality of MAD while consuming substantially fewer tokens and requiring less inference time.

We conducted a series of experiments on three commonly utilized reasoning benchmarks, using both closed-source LLMs (e.g., ChatGPT) and open-source models. With the same number of agents, MARS consistently reduced the resource usage while keeping the accuracy comparable to MAD across all datasets (Table 1). For example, the token consumption of GPT-4o-mini on GPQA is reduced from 17083 to 7903 per query, while achieving a slightly higher accuracy. These results demonstrated both the effectiveness and efficacy of the MARS framework. In summary, this work has the following major contributions:

- We propose **MARS**, a role-based multi-agent framework by following a hierarchical evaluation process to increase the computational efficiency and preserve the performance of multi-agent reasoning.

- Experiments on multiple benchmarks validated that MARS matches the accuracy of the SOTA method MAD while reducing token usage by ∼50% when implementing with different LLMs.

- We conduct a comprehensive analysis of multi-agent reasoning dynamics, revealing critical insights into how scaling the number of agents, deploying heterogeneous LLMs across specific roles, and enforcing reviewer personas impact overall system performance.

2 Related Work

LLM Reasoning. The reasoning capability of LLMs has become a research focus in recent years, with various methods proposed at both the training and inference stages. Prompting-based approaches, such as CoT(Wei et al., 2022), ToT(Yao et al., 2023), and self-reflection(Shinn et al., 2023), introduce structured pipelines to guide the model to decompose the problem and think step-by-step before generating the final answer. These methods are more straightforward and efficient, but the effectiveness is limited by the model's inherent reasoning ability. In parallel, there are also advanced reasoning models or agents which are finetuned with reasoning trajectories(Gao et al., 2024; Tan et al., 2025; Huang et al., 2022). These models come with reasoning and tool usage abilities naturally, but will require more computational resource for model training.

Multi-agent Collaboration. A single agent's capability is often insufficient for problems that require complex reasoning and specialized knowledge. Recent research also revealed that LLMs tend to adhere to their initial answers and struggle to identify and correct their own mistakes without external information. To address this, many studies have started to explore the collaborative behaviors of multiple agents. MAD is the most prominent framework in this line(Du et al., 2023; Smit et al., 2023; Liang et al., 2023), where multiple agents work on the same problem through round-table discussion, iteratively exchanging responses and refining their answers by leveraging the feedback from others. While effective in improving reasoning, MAD introduces substantial computational overhead: both token consumption and inference time

grow rapidly with the number of agents and communication rounds, making it costly for practical deployment.

Answer Verification. Many finetuning methods for LLM agents rely on synthetic reasoning and tool usage trajectories(Sun et al., 2025; Ficek et al., 2025; Lee et al., 2025; Fu et al., 2025). To ensure the quality of the structure, intermediate steps, and final results of the trajectories, recent works have designed various verifiers for quality control. These verifiers are either rule-based modules with human-defined principles, or LLM-based utilizing the inherent error-detection and evaluation abilities of large models. Unlike primary agents, verifiers are not required to generate full answers to user queries; instead, they specialize in detecting mistakes in reasoning steps and final results. The effectiveness of this design in improving reliability has been demonstrated in various agent systems. In our framework, reviewer agents serve a similar role: they provide independent decisions, comments, and suggestions, offering the author agent clearer and more explicit feedback to guide revisions of its initial response.

3 Methodology

3.1 Overview

In this section, we introduce the MARS framework, which is designed for reducing resource demands in multi-agent systems. We begin with the problem formulation, then describe the roles assigned to different agents, and finally outline the architecture and mechanisms of how the MARS framework works for complex reasoning tasks.

Problem Formulation. For a given reasoning task, let x_i denote the input prompt (original problem description wrapped by our prompting templates), and let y_i denote the model's response containing the final answer. Different from MAD where multiple agents are equivalent to each other, MARS adopts a role-based design. LLMs are employed to play three distinct roles, namely **author**, who generates initial responses, **reviewer**, who generates evaluation on the author's output, and **meta-reviewer**, who integrates reviewers' comments and provides feedback for the author. We use $\mathcal{A}$ to denote the author agent, $\mathcal{R}_j, j = 1, 2, ..., m$ to denote the reviewer agents, and $\mathcal{M}$ to denote the meta-reviewer agent, respectively.

3.2 MARS Framework

The MARS framework implements a structured, role-based collaboration among agents to improve both reasoning accuracy and efficiency (Figure 1). Given a user query, the author agent generates an initial response. This output is then independently evaluated by multiple reviewer agents, each producing a decision, explanatory comments, and a confidence score without interacting with each other. A meta-reviewer agent aggregates these reviews to issue a judgment and, when necessary, provides targeted feedback to guide the author's revision. This hierarchical evaluation and feedback loop enables efficient parallel review while enhancing robustness through systematic error detection and correction. The details of each component and step are provided below (a summary of the procedures is available in Algorithm 1).

Author's initial response. For an input prompt x_i, the **author agent** generates an initial response containing both the reasoning trajectory and the final answer. To make the subsequent review process verifiable, we adopt the Chain-of-Thought (CoT) paradigm, requiring the author to output explicit intermediate reasoning steps alongside the final answer (see Appendix D.1.1 for the prompt template). Mathematically, this step can be presented as a function:

$$t_i, y_i = \mathcal{A}(x_i) \tag{1}$$

where t_i denotes the sequence of reasoning steps and y_i denotes the final answer.

Reviewer's evaluation. After the author produces an initial response, the review stage begins with m **reviewer agents**, denoted $\mathcal{R}_1, \mathcal{R}_2, \ldots, \mathcal{R}_m$. Each reviewer receives the author's output as input and generates a review comprising: (i) a binary decision (accept or reject), (ii) a confidence score, and (iii) textual justification. If the decision is *reject*, the justification must explicitly identify errors in either the intermediate reasoning steps or the final prediction (see Appendix D.1.2 for the prompt template). The review process of the j-th reviewer for the input x_i can be mathematically presented as a function:

$$r_{ij} = \mathcal{R}_j(x_i, t_i, y_i), \quad j = 1, 2, ..., m \tag{2}$$

Meta-review and feedback. Unlike the normal peer review process, we do not incorporate direct feedback from the reviewers to the author after the review stage. Instead, a **meta-reviewer agent** consolidates reviewer feedback, makes decisions,

Figure 1: Overview of the architecture of MARS and baselines. (a) Basic single model inference (top) and self-reflection (bottom). (b) Self-consistency. (c) Multi-Agent-Debate (MAD). (d) Multi-Agent Review System (MARS). In MARS, the author agent receives a user query and generates an initial response. Each reviewer agent evaluates the response and provides a decision, confidence level, and justification (e.g., reasons for the decision, identified author mistakes). The meta-reviewer integrates review comments and makes the final decision, with suggestions for answer revision. Finally, the author agent incorporates the feedback and updates its response, leading to enhanced reasoning.

and communicates with the author. This design is driven by two factors: (1) **Efficiency** — a direct discussion between reviewers and the author would substantially increase token usage and inference time, reducing reasoning efficiency; (2) **Role simplification** — Exposing the author to multiple, potentially redundant or conflicting comments would impose extra decision-making, such as filtering overlapping feedback or resolving disagreements, which could distract it from revising the response. We consider that by centralizing feedback integration in the meta-reviewer, the author remains focused on updating their answer, thereby maintaining reasoning quality.

The meta-reviewer processes all reviewer outputs, summarizes comments, resolves conflicts or redundancies, and issues a final decision. If the decision is *accepted*, the author's initial response is adopted as the final response. If the decision is *rejected*, the meta-reviewer provides explicit feedback to the author, including (i) the reasons for rejection (e.g., errors in the reasoning path) and (ii) concrete suggestions for improvement (see Appendix D.1.4 for the prompt template). This meta-reviewer can be mathematically presented as a function:

$$m_i = \mathcal{M}(x_i, t_i, y_i, r_i) \tag{3}$$

, where m_i denotes the meta-reviewer's output, and r_i is a concatenation of all the reviewer outputs, $r_i = r_{i1} \oplus r_{i2} \oplus ... \oplus r_{im}$

Rebuttal stage. After the meta-review stage, a final decision is issued regarding the author's initial response. If the decision is *rejected*, the author agent is required to revise the solution by leveraging both its reasoning history and the meta-reviewer's feedback. Concretely, the author agent will review its step-by-step thoughts t_i and incorporate the meta-reviewer's suggestions to identify and correct errors (see Appendix D.1.5 for the prompt template). Once all steps have been re-examined, the author agent produces an updated answer y_i^*. This process can be formulated as:

$$y_i^* = \mathcal{A}(t_i, y_i, m_i) \tag{4}$$

Upon generating y_i^*, the updated response is fed back into the review stage. This iterative cycle of review and revision continues until the meta-reviewer issues an *accepted* decision or a pre-defined maximum number of iterations K is reached (see Algorithm 1).

3.3 Calibration of Reviewer Confidence

Reviewers may occasionally make reasoning errors, leading to divergent decisions and uncertainties at

the review stage. To assist the meta-reviewer in accurately weighing these evaluations, it is essential to quantify reviewer confidence. As detailed previously, our framework prompts each reviewer to output a verbalized confidence score alongside their decision and justification. However, recent studies demonstrate that LLMs frequently exhibit significant overconfidence when relying on vanilla verbalized confidence elicited via prompting (Xiong et al., 2023).

Conversely, research indicates that the probability distribution of output tokens intrinsically reflects a model's underlying uncertainty. Building on this insight, we propose utilizing the token-level probability distribution of the reviewers' responses for confidence calibration. Specifically, for a response r_{ij} generated by the j-th reviewer for the i-th query, consisting of N tokens $\{t_1, t_2, \ldots, t_N\}$, we first compute the average log probability of the generated sequence:

$$\text{AvgLogProb}_{ij} = \frac{1}{N} \sum_{k=1}^{N} \log P(t_k) \quad (5)$$

A higher average log probability (closer to 0) indicates greater model certainty. To convert this into a normalized confidence score bounded between 0 and 1, we exponentiate the average log probability:

$$Conf_{ij} = \exp(\text{AvgLogProb}_{ij}) \quad (6)$$

In practice, this sequence-level probability calibrates the initial confidence level of each reviewer. This refined metric is then propagated to the meta-reviewer via the prompt template (D.1.3), providing a statistically grounded indicator of whether a given reviewer's feedback is reliable.

4 Experiments

4.1 Setup

Benchmarks. We evaluate MARS on three commonly utilized reasoning benchmarking sets: (1) MMLU (Hendrycks et al., 2020) consists of multiple-choice questions across diverse academic subjects such as elementary mathematics, history, computer science, and law; (2) GPQA (Rein et al., 2024) is a graduate-level QA dataset spanning biology, physics, and chemistry, which is of high-quality and even challenging for domain experts, making it a strong test of reasoning ability; (3) GSM8K (Cobbe et al., 2021) is a math word problem dataset that evaluates grade school level mathematical reasoning.

Models and baselines. We use both closed-source (GPT-3.5-turbo, GPT-4o-mini) and open-source (Mixtral-8×7b, Mixtral-8×22b, Llama3.3-70b) models as agent backbones. The open-source model is accessed through NVIDIA NIM platform via API calls. We compare MARS against several single-agent and multi-agent baselines, including Chain-of-Thought (CoT) (Wei et al., 2022), Self-reflection (Shinn et al., 2023), Self-consistency (Wang et al., 2022), Multi-agent Debate (MAD) (Du et al., 2023), and Diverse Multi-agent Debate (DMAD) (Liu et al., 2025). Detailed introductions and experimental settings of the baselines, as well as their corresponding prompts are available in Appendix B and Appendix D.

Metrics. Prior work primarily assessed reasoning methods by the accuracy of the final answer, where MAD has demonstrated strong performance. In contrast, MARS is designed to improve computational efficiency in LLM-based reasoning, with success defined by achieving accuracy comparable to MAD while substantially reducing resource consumption. Accordingly, we evaluate methods based on the integration of three metrics: (i) final-answer accuracy, (ii) average number of tokens generated per query, and (iii) average inference time (seconds) per query.

4.2 Main Results

The primary experimental results across all models and datasets are summarized in Table 1. We highlight the following key observations:

(1) **Accuracy.** MAD and MARS consistently rank among the top two methods in final-answer accuracy, outperforming all of the other baselines under most settings. With the expanded evaluation across five diverse LLMs, MARS demonstrates superior or highly competitive performance. Their relative advantage depends on the backbone model and task: for example, on GSM8K with GPT-3.5, MAD reaches 79.00% accuracy versus 75.67% for MARS. However, MARS outperforms MAD on the remaining four models for the same task, including achieving 90.33% with Mixtral 8x22b (compared to MAD's 87.00%). Furthermore, MARS secures the highest accuracy on the challenging GPQA dataset with advanced models like GPT-4o-mini (48.33%) and Llama3-70b (60.00%). Overall, MARS achieves comparable or superior accuracy to MAD across an extensive array of state-of-the-art models and complex tasks.

(2) **Token consumption.** Although both MAD

Method	GPT-3.5		GPT-4o-mini		Mixtral 8x7b		Mixtral 8x22b		Llama3-70b	
	Acc.	Tok.	Acc.	Tok.	Acc.	Tok.	Acc.	Tok.	Acc.	Tok.
GPQA										
CoT	31.00	414	43.33	677	33.67	759	41.33	721	47.67	963
Self-reflection	29.67	890	37.67	1597	35.00	1625	38.00	1579	56.33	2079
Self-consistency	33.67	1686	40.67	2910	35.67	3033	41.67	2840	56.67	3470
MAD	31.00	7567	47.50	17083	35.67	12835	**47.00**	13308	59.67	19255
DMAD	35.67	5609	47.33	17229	34.00	14139	43.33	13509	56.33	18082
MARS	**36.33**	3741	**48.33**	7903	**37.33**	6441	44.00	5418	**60.00**	6633
MMLU										
CoT	68.00	283	81.67	357	62.00	438	73.33	434	84.00	446
Self-reflection	70.33	609	80.67	847	60.00	1042	77.33	988	83.67	1087
Self-consistency	69.33	1141	85.00	1515	61.67	1742	76.33	1757	82.33	1919
MAD	**71.33**	4647	85.33	8338	61.00	7118	76.67	7200	84.00	9370
DMAD	71.00	4023	85.33	8706	54.33	8658	**83.00**	7570	84.67	9641
MARS	71.00	2692	**85.67**	4210	**63.00**	3887	77.67	3829	**84.67**	4210
GSM8K										
CoT	73.33	262	96.00	384	60.00	381	86.33	373	97.00	335
Self-reflection	67.00	577	92.33	894	53.67	826	86.00	817	97.33	777
Self-consistency	77.00	1045	97.00	1548	67.00	1536	87.00	1517	97.33	1410
MAD	**79.00**	4355	97.67	7440	68.67	6809	87.00	6805	97.33	6307
DMAD	73.33	5136	96.33	8831	66.33	7724	83.33	7283	97.33	7659
MARS	75.67	2508	**98.00**	3389	**69.00**	4994	**90.33**	3515	**97.67**	3313

Table 1: Performance comparison across datasets including Accuracy (Acc. %) and average number of tokens (Tok.). Best accuracy scores per dataset are **bolded**, and second-best are underlined.

and MARS achieve high accuracy across reasoning tasks, their multi-agent design naturally requires higher token usage compared to single-agent baselines. Notably, MARS consistently reduces the average number of tokens per query by roughly 50% relative to MAD, a scaling advantage that holds true across all tested models. For instance, on the GPQA benchmark with GPT-4o-mini, MAD consumes an average of 17,083 tokens per query, whereas MARS requires only 7,903 tokens. Given that MARS achieves comparable or better accuracy, this demonstrates that the framework makes the multi-agent collaboration paradigm substantially more efficient and practical for large-scale deployment while preserving response quality.

(3) **Inference time.** Another critical aspect of a reasoning strategy is inference time, particularly for interactive applications such as ChatGPT. As shown in Table 4, MARS reduces inference time by more than 30% compared to MAD, enabling more responsive user interactions and more scalable large-scale experimentation.

Our results reveal a key limitation of prior MAD-inspired strategies: their gains in reasoning quality come with prohibitive computational overhead. MARS fills this efficiency gap to a certain level, reducing token usage and inference time by about 50% while preserving accuracy. This advance makes multi-agent reasoning not only more effective but also practical for large-scale and real-time applications. Figure 2 visualizes this efficiency gain, highlighting the favorable trade-off MARS achieves between accuracy and token consumption relative to self-consistency and MAD.

Figure 2: Accuracy-Resource trade-off across different models on GPQA. MARS demonstrates a significant reduction in token averaged tokens compared to MAD, while achieving higher accuracy than self-consistency.

4.3 Additional Analysis

4.3.1 Scalability

In this section, we evaluate the scalability of MARS versus MAD to further demonstrate the efficiency

Figure 3: Comparison of MARS and MAD on GPQA with varying number of agents. Row 1: using GPT-3.5-turbo as the backbone; Row 2: using GPT-4o-mini as the backbone. Column 1: accuracy scores; Column 2: averaged number of tokens.

advantage of MARS. Figure 3 presents their performance across different backbone models and varying numbers of agents. From the left column of Figure 3, we observe that the accuracy of both methods generally increases as the number of agents grows, consistent with prior findings that collaborative reasoning benefits from larger agent pools. This trend suggests that scaling the number of agents can enhance reasoning performance in multi-agent frameworks. Noted, MAD employs a fully connected communication structure that causes computational cost per query to grow rapidly as the number of agents increases. As shown in the right column of Figure 3, both token usage and inference time grow sharply with additional debaters, severely limiting scalability. In contrast, MARS avoids this bottleneck by designing the parallel reviewer to generate independent evaluations and a meta-reviewer agent to aggregate reviews. This structure enables MARS to improve reasoning efficiency while maintaining performance, with token consumption and inference time growing linearly with the number of reviewers.

4.3.2 Evaluating Different Mixtures of Models

In this section, we evaluate how utilizing heterogeneous backbone models impacts reasoning outcomes. While our primary experiments deployed the same LLM across all agent roles, recent studies suggest that mixing different models can introduce complementary analytical perspectives. To explore this, we tested various combinations of GPT-3.5-turbo and Mixtral 8x22b within the MARS frame-

work on the GPQA benchmark. As shown in Table 2, three key observations emerge: (1) **Stronger auxiliary agents elevate performance.** For a GPT author, integrating the more capable Mixtral model into the reviewer or meta-reviewer roles consistently improves the final score, scaling from 35.33 up to 39.00. (2) **The author's inherent capacity bounds the system.** Despite the assistance of strong Mixtral reviewers and meta-reviewers, a GPT author (maximum 39.00) cannot match the baseline performance of a Mixtral author (minimum 41.67). The author agent ultimately dictates the overall performance ceiling. (3) **Model diversity yields unexpected synergies.** The highest overall accuracy (46.40) is achieved when Mixtral serves as the author, but GPT acts as both the reviewers and the meta-reviewer. This configuration even surpasses all-Mixtral settings, indicating that injecting diverse reasoning styles during the review phase is a non-trivial factor that warrants further investigation.

Author	Reviewers	Meta	Acc.
gpt	gpt+mixtral	gpt	35.33
gpt	mixtral+mixtral	gpt	36.00
gpt	gpt+mixtral	mixtral	38.00
gpt	mixtral+mixtral	mixtral	39.00
mixtral	gpt+mixtral	mixtral	43.50
mixtral	gpt+gpt	mixtral	41.67
mixtral	gpt+mixtral	gpt	42.23
mixtral	gpt+gpt	gpt	46.40

Table 2: Comparison of different author–reviewer–meta-reviewer configurations on GPQA.

4.3.3 Effect of reviewer personas

Recent work suggests that assigning distinct personas to agents can improve performance by promoting diversity. Motivated by this, we explored whether diversifying reviewers through predefined personas could enhance feedback quality and overall reasoning performance. In this variant, namely MARS-P, reviewers were instructed to adopt specific roles (e.g., conservative vs. aggressive; see Appendix D.3 for prompt details) when evaluating the author's response.

Surprisingly, as shown in Table 3, introducing personas did not yield improvements across tasks (except a marginal improvement on MMLU). Analysis of the review content suggests two main factors: (i) the inherent randomness of LLMs already

provides a degree of diversity in reviewer feedback, and persona prompts did not add significant variance; and (ii) when the author's response is correct, aggressive reviewers often generate unnecessarily critical or noisy feedback, which can confuse the meta-reviewer and cause over-corrections. These results indicate that relying on the model's natural variability might be more effective than enforcing artificial personas.

Model	GPQA	MMLU	GSM8K
GPT-3.5	36.33 / 34.00	71.00 / 72.00	75.67 / 73.33
GPT-4o-mini	48.33 / 47.00	85.67 / 85.67	98.00 / 97.00
Mixtral 8x7b	37.33 / 35.67	63.00 / 66.67	69.00 / 66.00
Mixtral 8x22b	44.00 / 40.00	77.67 / 80.00	90.33 / 88.67
Llama3.3-70b	60.00 / 56.67	84.67 / 82.67	97.67 / 97.00

Table 3: Ablation study on persona assignment across datasets. Scores are reported as (w/o Persona / w/ Persona).

4.4 Case Study

To illustrate how MARS operates, we present a case study from the GSM dataset that demonstrates the framework's step-by-step reasoning process (Figure 4; additional examples appear in Appendix F). The problem describes four dogs, where the first weighs 10 pounds, and each subsequent dog weighs a constant multiple of the previous one. The task is to determine the weight of the fourth dog.

The author agent began by denoting the first dog's weight as A and correctly deriving that the fourth weight should be $22A$. However, it mistakenly recomputed A as $5/11$, which contradicts the given information and led to an incorrect final answer. During the review phase, Reviewer 1 successfully identified this error and explicitly flagged the inconsistency; Reviewer 2 also rejected the author's answer but failed to provide a clear justification. At the meta-review stage, the meta-reviewer integrated these signals, recognized the erroneous recomputation of A, and instructed the author to recalculate using the correct initial weight. Incorporating this feedback, the author substituted $A = 10$ pounds and derived the correct result of $22A = 220$ pounds.

We highlight three insights from this case: (1) *Error propagation in long reasoning chains.* For tasks requiring multiple reasoning steps (seven in this example), even a minor mistake can cascade into an incorrect final answer, underscoring the importance of intermediate verifications for the reasoning process. (2) *Reviewer contributions.* Reviewers in MARS can identify errors in the reasoning chain and provide detailed feedback to guide answer revision. While not all reviewers generate high-quality comments, this variability suggests potential benefits from involving multiple reviewers. (3) *Effectiveness of MARS.* By incorporating external feedback rather than relying solely on self-correction, MARS overcomes limitations of single-agent reasoning and improves final accuracy without incurring excessive computational cost.

Figure 4: Case study of MARS on a GSM example. Upon receiving the user query, the author agent first generates an initial response but incorrectly recomputed a given variable, leading to an incorrect final answer. The reviewers identified the mistake and generated feedback, which guided the author agent to revise the solution, resulting in the correct answer.

5 Conclusion

In this work, we introduced MARS (Multi-Agent Review System), a framework that enables efficient collaboration among LLMs through a propose–review–feedback–update architecture. MARS addresses the limitations of self-reflection in single-agent settings, enhances reasoning quality, and avoids the heavy computational cost of debate-based methods. Extensive experiments across diverse benchmarks and models show that MARS consistently outperforms strong baselines and matches the accuracy of Multi-Agent Debate while reducing resource consumption by about 50%. These findings suggest that direct communication among all agents is not required for effective collaboration, and that the review-style architectures provide a promising paradigm for scalable and efficient multi-agent reasoning.

Limitations

Although MARS achieved strong performance in both accuracy and efficiency, there are still several challenges remaining to be solved. (1) Confidence estimation. The reviewer agents output a confidence score, which helps the meta-reviewer to estimate the reliability of the review comments. In this paper, the confidence score is calibrated by a token probability-based uncertainty estimation. However, LLM uncertainty estimation is not yet a definitively solved problem, and incorporating more advanced calibration methods from recent studies remains a promising direction for future work. (2) Over-correction. In MARS, the decision and suggestions of meta-reviewer will highly influence the final answer, especially when the meta-decision is *reject*. One potential issue is that a correct initial response may be overturned if the meta-reviewer provides negative feedback, guiding the author to a wrong direction. Although we attempted to mitigate this by curating the feedback prompt template (the author is asked to insist on its initial answer when disagreeing with the meta-reviewer), we cannot guarantee to avoid it in our current setting. Future work should include how to design more effective mechanisms to prevent unnecessary revisions. (3) Additionally, our current experiments constrain the maximum number of revision / debate rounds to two for both MARS and MAD due to computational resource and time limits. Systematically investigating the impact of additional interaction rounds on both reasoning performance and token consumption remains an important direction for future work.

References

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. 2023. Improving factuality and reasoning in language models through multiagent debate. In *Forty-first International Conference on Machine Learning*.

Aleksander Ficek, Somshubra Majumdar, Vahid Noroozi, and Boris Ginsburg. 2025. Scoring verifiers: Evaluating synthetic verification for code and reasoning. *arXiv preprint arXiv:2502.13820*.

Dayuan Fu, Keqing He, Yejie Wang, Wentao Hong, Zhuoma Gongque, Weihao Zeng, Wei Wang, Jingang Wang, Xunliang Cai, and Weiran Xu. 2025. Agentrefine: Enhancing agent generalization through refinement tuning. *arXiv preprint arXiv:2501.01702*.

Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaojian Ma, Tao Yuan, Yue Fan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, and Qing Li. 2024. Multi-modal agent tuning: Building a vlm-driven agent for efficient tool usage. *arXiv preprint arXiv:2412.15606*.

Muhammad Usman Hadi, Rizwan Qureshi, Abbas Shah, Muhammad Irfan, Anas Zafar, Muhammad Bilal Shaikh, Naveed Akhtar, Jia Wu, Seyedali Mirjalili, and 1 others. 2023. Large language models: a comprehensive survey of its applications, challenges, limitations, and future prospects. *Authorea preprints*, 1(3):1–26.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2020. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*.

Jiaxin Huang, Shixiang Shane Gu, Le Hou, Yuexin Wu, Xuezhi Wang, Hongkun Yu, and Jiawei Han. 2022. Large language models can self-improve. *arXiv preprint arXiv:2210.11610*.

Bowen Jiang, Yangxinyu Xie, Zhuoqun Hao, Xiaomeng Wang, Tanwi Mallick, Weijie J Su, Camillo J Taylor, and Dan Roth. 2024. A peek into token bias: Large language models are not yet genuine reasoners. *arXiv preprint arXiv:2406.11050*.

Hyunseok Lee, Seunghyuk Oh, Jaehyung Kim, Jinwoo Shin, and Jihoon Tack. 2025. Revise: Learning to refine at test-time via intrinsic self-verification. *arXiv preprint arXiv:2502.14565*.

Jiawei Li, Yang Gao, Yizhe Yang, Yu Bai, Xiaofeng Zhou, Yinghao Li, Huashan Sun, Yuhang Liu, Xingpeng Si, Yuhao Ye, and 1 others. 2025. Fundamental capabilities and applications of large language models: A survey. *ACM Computing Surveys*.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Shuming Shi, and Zhaopeng Tu. 2023. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*.

Yexiang Liu, Jie Cao, Zekun Li, Ran He, and Tieniu Tan. 2025. Breaking mental set to improve reasoning through diverse multi-agent debate. In *The Thirteenth International Conference on Learning Representations*.

Shervin Minaee, Tomas Mikolov, Narjes Nikzad, Meysam Chenaghlu, Richard Socher, Xavier Amatriain, and Jianfeng Gao. 2024. Large language models: A survey. *arXiv preprint arXiv:2402.06196*.

Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2024. Gsm-symbolic: Understanding the limitations of mathematical reasoning in large language models. *arXiv preprint arXiv:2410.05229*.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2024. Gpqa: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Weijie Shi, Han Zhu, Jiaming Ji, Mengze Li, Jipeng Zhang, Ruiyuan Zhang, Jia Zhu, Jiajie Xu, Sirui Han, and Yike Guo. 2025. Legalreasoner: Step-wised verification-correction for legal judgment reasoning. *arXiv preprint arXiv:2506.07443*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36:8634–8652.

Andries Smit, Paul Duckworth, Nathan Grinsztajn, Thomas D Barrett, and Arnu Pretorius. 2023. Should we be going mad? a look at multi-agent debate strategies for llms. *arXiv preprint arXiv:2311.17371*.

Linzhuang Sun, Hao Liang, Jingxuan Wei, Bihui Yu, Tianpeng Li, Fan Yang, Zenan Zhou, and Wentao Zhang. 2025. Mm-verify: Enhancing multimodal reasoning with chain-of-thought verification. *arXiv preprint arXiv:2502.13383*.

Xingwei Tan, Marco Valentino, Mahmud Akhter, Maria Liakata, and Nikolaos Aletras. 2025. Enhancing logical reasoning in language models via symbolically-guided monte carlo process supervision. *arXiv preprint arXiv:2505.20415*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. 2023. Can llms express their uncertainty? an empirical evaluation of confidence elicitation in llms. *arXiv preprint arXiv:2306.13063*.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822.

A MARS Algorithm

Algorithm 1: MARS algorithm

Input: input query x, author model $\mathcal{A}$, m reviewer models
$\{\mathcal{R}_j \mid j = 1, \ldots, m\}$,
meta-reviewer model $\mathcal{M}$, maximum iterations K

Output: final answer y^*

Initialization Stage:

$t, y \leftarrow \mathcal{A}(x)$;   // Generate thoughts and initial answer (Eq. 1)

$k \leftarrow 1$

$decision \leftarrow$ Reject

while $decision ==$ *Reject* **and** $k \leq K$ **do**

    Review Stage:

    for $j = 1$ **to** m **do**

        $r_j \leftarrow \mathcal{R}_j(x, t, y)$;   // Reviewers output decision, confidence, and justification

    $r \leftarrow \{r_j \mid j = 1, \ldots, m\}$; // Collect all reviewer comments

    Meta-Review Stage:

    $decision, f \leftarrow \mathcal{M}(x, t, y, r)$;
// Meta-reviewer evaluates reviews to output final decision and feedback f

    if $decision ==$ *Accept* **then**

        break ;   // Terminate loop early if answer is accepted

    Revision Stage:

    $t, y \leftarrow \mathcal{A}(x, t, y, f)$;   // Author revises thoughts and answer based on feedback f

    $k \leftarrow k + 1$

$y^* \leftarrow y$; // Final answer is the most recent y

return y^*

B Baselines and Experiment Details

We compare MARS against the following baselines:

- **Chain-of-Thought (CoT).** All models in our experiments are enabled with CoT, which prompts step-by-step reasoning and serves as the most basic baseline.

- **Self-reflection.** This is a single-agent approach in which the model is prompted to evaluate and revise its own response.

- **Self-consistency.** This approach exploits the inherent stochasticity of LLMs by sampling multiple reasoning paths for the same query and aggregating them through majority voting to produce the final answer.

- **Multi-agent Debate (MAD)** is a framework in which multiple agents engage in a round-table discussion, with each agent generating an answer by combining its own reasoning with the responses of others. All agents play equivalent roles in this process.

- **Diverse Multi-agent Debate (DMAD)** is a recent variant of the MAD framework. Unlike traditional MAD, where all agents uniformly employ Chain-of-Thought (CoT) reasoning, DMAD assigns distinct reasoning strategies to different agents to explicitly foster cognitive diversity.

In our experiments, we followed the standard manner of CoT by asking the model to think about the user query step-by-step. For a fair comparison, we adopt a consistent prompt design: all methods use CoT prompting for the initial reasoning process. For example, the initial reasoning step in self-reflection and each reasoning path in self-consistency share the same CoT prompt template. Reflection, debate, review, and feedback methods require distinct prompt styles due to their structural differences. Detailed prompt templates are provided in Appendix D.

We used the standard OpenAI SDK for API calls of all the models used in this work. All of the parameters are set as their default values. For fair comparison, we use the same number of agents in MARS and MAD. Both methods will run one update round after the initial round. While MARS is naturally extendable to multiple rounds of review and revision, we leave a systematic study of this setting to future work due to time and cost constraints.

For each dataset, we randomly sample 100 problems in each experiment, and report the averaged performance after 3 runs.

C Additional Experimental Results

D Prompt Templates

In this section, we provide prompt templates for all the methods used in this paper, including both MARS and the compared baselines.

Table 4: Comparison of average inference time (seconds) per query across datasets and models. The lowest inference time among multi-agent methods is **bolded** for each setting.

Method	GPT-3.5	GPT-4o-mini	Mixtral 8x7b	Mixtral 8x22b	Llama3-70b
GPQA					
CoT	1.58	7.63	16.05	3.92	7.61
Self-reflection	2.44	11.45	38.08	6.00	13.24
Self-consistency	6.37	29.20	68.17	23.11	52.33
MAD	17.04	85.67	79.33	36.83	104.25
DMAD	12.77	84.06	128.67	33.78	102.78
MARS	9.54	49.02	79.24	22.21	49.77
MMLU					
CoT	2.07	3.48	20.38	2.29	2.73
Self-reflection	4.28	5.42	29.82	3.90	6.86
Self-consistency	4.93	14.55	47.76	14.44	29.60
MAD	11.38	41.58	77.31	17.39	51.78
DMAD	10.67	42.96	105.87	23.89	64.03
MARS	7.61	28.14	55.91	16.15	36.49
GSM8K					
CoT	1.67	3.48	4.32	2.50	2.24
Self-reflection	2.63	5.42	26.84	3.46	4.31
Self-consistency	5.97	18.53	47.78	14.63	26.35
MAD	11.58	39.69	79.21	23.55	28.67
DMAD	14.47	46.86	54.61	20.31	70.35
MARS	7.17	23.16	63.15	16.23	27.53

D.1 Prompt Templates for MARS

D.1.1 Author Agent

The author agent is prompted to give its initial response using chain-of-thoughts. The following prompt shows that the author receives the user query, generates intermediate thoughts on the problem, and then the final answer. Specifically, the answer format shown here is for QA problems. When applied to math datasets, the format could be changed to

"Answer: [the final numerical answer]"

"Your final answer must be a single numerical number at the end of the response."

```
You are an assistant. Please help to
    solve the following problem:
{user_query}

Give your thoughts about the question
    and the final answer in the
    following format:
Thoughts: [your thoughts with immediate
    results]
Answer: [the final single capital letter
    answer in the form (X). X is chosen
    from [A,B,C,D]]

Your final answer must be a single
    capital letter in the form (X)
at the end of the response.
```

D.1.2 Reviewer Agent

```
You are an objective reviewer. The
    author has submitted an answer to a
    problem.
Your goal is to check for correctness,
    NOT to find faults that don't exist.

Criteria: Check for factual correctness
    and reasoning. Verify why the other
    options are wrong.

Question: {user_query}

Author's Answer: {author_response}

---
OUTPUT FORMAT:
My Independent Analysis: [Analyze the
    question and evaluate each option A,
    B, C, D]
My Selected Option: [e.g., (A)]
Comparison: [Does your option match the
    Author's?]
Decision: [right | wrong] (Vote 'right'
    if the Author's option matches yours
    )
Confidence: [1-5]
Justification: [Explain why the Author's
    reasoning is correct or incorrect]
---
```

D.1.3 Confidence Calibration

```
NOTE ON RELIABILITY SCORES:
- Each Reviewer provides a 'Reliability
    Score' (0.0 to 1.0) based on their
    internal model uncertainty.
```

```
- High Score (>0.8): The Reviewer is
    mathematically confident. Trust
    their specific calculations/facts.
- Low Score (<0.6): The Reviewer is
    uncertain or confused. You should be
     skeptical of their critique,
    especially if they disagree with a
    High-Score reviewer.
```

D.1.4 Meta-Reviewer Agent

```
You are the meta-reviewer. The author
    has submitted an answer.

Question: {user_query}
Answer: {author_response}

You must decide whether the answer is
    correct based on both your own
knowledge and the reviewers' comments
    below:

--- Reviewer Feedback ---
{combined_reviews}

Do not only rely on the reviewers, you
    must also think by yourself.

Provide your conclusion in the following
     format:

Decision: [right | wrong]
Justification: [reasons of your decision
    ]
Suggestions: [your suggestions for
    updating the answer, only needed
                when decision is wrong]
Answer: [your recommended answer]
```

D.1.5 Feedback to Author

To avoid over-correction, the author is prompted to think carefully before accepting the meta-reviewer's suggestions. The author will only start to revise its initial answer when it strongly agrees with the meta-reviewer. After the decision is made, it will move on to update its answer following the feedback.

```
Your answer was reviewed and marked as
    incorrect by the meta-reviewer.

--- Meta-reviewer Feedback ---
{meta_decision}

If you strongly agree with the meta-
    reviewer's suggestions, revise your
answer accordingly. If you disagree,
    insist on your initial answer and
repeat it. Do not always trust the meta-
    reviewer -- you must think for
yourself whether to trust the
    suggestions.

Make sure to state your reasoning and
    final answer in this format:
```

```
Reasons: [your reasons of accepting or
    rejecting the suggestions]
Thoughts: [your new step-by-step
    thoughts on the problem after
                considering the suggestions]
Answer: [the final single capital letter
    answer in the form (X).
        X is chosen from [A,B,C,D]]
```

D.2 Prompt Templates for baselines

In this section, we show the prompt templates for the baselines. For a fair comparison, the same CoT template is applied to the initial input of all the techniques. Therefore, we did not include the prompts for self-consistency here since it just applies the same prompt several times. For self-reflection, we provide the prompt for the reflection step. For MAD, we provide both the prompts for the initial response and the debate process for each agent.

D.2.1 Self-Reflection Prompts

```
You wrote the following response to a
    problem:

Question: {user_query}
Answer: {response}

Carefully review your own answer. Are
    there any mistakes or thoughts not
    grounded in the given problem or
    known facts?
- If yes, explain the problems and
    revise your answer accordingly.
- If not, confirm and repeat your
    initial answer.

Your final response must follow this
    format:
Mistakes (if any):
Answer: [the final single capital letter
    answer in the form (X).
        X is chosen from [A,B,C,D]]
```

D.2.2 Debate Prompt

```
You are an assistant. Please help to
    solve the following problem:
{user_query}

Give your thoughts about the computation
    steps and the final answer in the
    following format:
Thoughts: [your step-by-step thinking
    process with immediate results]
Answer: [the final single capital letter
    answer in the form (X).
        X is chosen from [A,B,C,D]]

Your final answer must be a single
    capital letter at the end of the
    response.
```

```
These are the solutions to the problem
    from other agents:

One agent solution: ```{response_1}```
One agent solution: ```{response_2}```
...

Using the solutions from other agents as
    additional information,
can you provide your final answer to the
    problem?

Make sure to state your thoughts and new
    answer with this format:
Thoughts: [your step-by-step thinking
    process]
Answer: [the final capital letter answer
    ]

Your final answer must be a single
    capital letter at the end of the
    response.
```

D.3 Reviewer Personas

Conservative Persona

```
Your decision should be conservative.

Goal:
Minimize false alarms. Only label 'wrong
    ' when there is a decisive,
demonstrable error that changes the
    final answer.

Heuristics:
- Require at least TWO independent
    checks (e.g., recomputation +
    boundary/unit check) before
    declaring 'wrong'.
- Minor arithmetic slips that do not
    affect the final answer => prefer '
    right' with notes in Justification.
- Missing small steps != 'wrong' if the
    step is standard and the result
    follows.

Confidence:
- 5 only if two checks agree
- 4 if one check is strong
- <=3 if any uncertainty remains
```

Aggressive Persona

```
Your decision should be aggressive.

Goal:
Minimize false acceptances. Label 'wrong
    ' when any essential step is missing
    , unjustified, or numerically
    inconsistent.

Heuristics:
- Penalize ambiguous leaps, missing
    assumptions/units, and unverified
    claims even if the final number
    looks plausible.
- If any step is unsupported or
    contradicts problem constraints,
```

```
    prefer 'wrong'.
- If correct, still list at least two
    vulnerabilities the author should
    fix.

Confidence:
- 5 if multiple issues are found or if
    cross-checks clearly contradict
- 4 when evidence is strong but not
    exhaustive
- <=3 if partial doubt
```

E   LLM Usage Statement

Large language models (LLMs) were used solely as general-purpose assistive tools for this work. Their usage was limited to grammar checking, language polishing, and LaTeX table formatting. LLMs were not involved in research ideation, methodological design, data analysis, or substantive writing of the manuscript.

F   Additional Case Studies

Question	A photon $h\nu$ propagates in the Oz direction of the laboratory frame (R). It collides elastically with a particle m at rest in (R). We denote $\alpha = \frac{h\nu}{mc^2}$, and $v = \beta c$ the velocity of the COM frame (R') of the system photon-particle relative to (R). What is the expression of β?
Options:
(A) $\alpha \times \left(\frac{1}{1+\alpha}\right)$
(B) $\alpha \times \left(\frac{1}{\sqrt{1+\alpha}}\right)$
(C) $\alpha \times \left(\frac{1}{1-\alpha}\right)$
(D) $\alpha \times \left(\frac{1}{\sqrt{1-\alpha}}\right)$
Author Response	Thoughts: The problem requires determining the velocity βc of the COM frame. Using conservation of momentum and energy, the motion must account for the photon's energy and the particle's rest mass. Relativistic mechanics often involve a correction factor like $\sqrt{1 \pm \alpha}$. Examining the options, B seems most suitable based on common relativistic calculations involving square roots.
Answer: (B)
Reviewer 1	Decision: wrong
Confidence: 5
Justification: By conservation of energy, $E_{\text{total}} = h\nu + mc^2 = (1+\alpha)mc^2$. By conservation of momentum, $p_{\text{total}} = \frac{h\nu}{c}$. The COM velocity is given by $\beta c = \frac{p_{\text{total}}c}{E_{\text{total}}}$. This simplifies to $\beta = \frac{\alpha}{1+\alpha}$. The author incorrectly assumed a square root is necessary.
Reviewer 2	Decision: wrong
Confidence: 4
Justification: The author correctly discussed conservation principles but arrived at the wrong numerical expression. The correct formulation is based directly on the conservation of momentum and energy, yielding $\beta = \frac{\alpha}{1+\alpha}$ without a square root.
Meta-Review	Decision: wrong
Justification: Both Reviewers analyzed the problem independently and showed detailed steps relying on conservation equations, verifying that β depends on $1 + \alpha$. The author's inclusion of a square root deviated from the correct formula and added unnecessary complexity.
Suggestions: Revisit the momentum conservation and relate it correctly to the total energy without introducing arbitrary square root factors.
Author Rebuttal	Thoughts: Upon reevaluating, I recognize the importance of correctly applying conservation of momentum and energy. The total energy before the collision is $(1 + \alpha)mc^2$ and the momentum relates to the COM frame, leading directly to $\beta = \frac{\alpha}{1+\alpha}$. The confusion in my initial answer stemmed from the improper inclusion of a square root term, which is not necessary in this fundamental particle-photon interaction setup.
Answer: (A)

Table 5: Case study from GPQA: The MARS framework successfully corrects a heuristic hallucination by relying on rigorous physics derivations provided by the reviewer agents.

Question	Consider a system of 3 spin-1/2 particles with a Hamiltonian $H = A(\mathbf{S}_1 \cdot \mathbf{S}_2 + \mathbf{S}_1 \cdot \mathbf{S}_3 + \mathbf{S}_2 \cdot \mathbf{S}_3)$. The state is $\psi = \frac{1}{\sqrt{3}}(\lvert \uparrow\uparrow\downarrow\rangle + \lvert \uparrow\downarrow\uparrow\rangle + \lvert \downarrow\uparrow\uparrow\rangle)$. Is this an eigenfunction of H?
(A) It is an eigenstate of H, with eigenvalue $\frac{3}{4}A\hbar^2$
(B) It is not an eigenstate of H, with expectation value $\frac{2}{3}A\hbar^2$
(C) It is an eigenstate of H, with eigenvalue $\frac{2}{3}A\hbar^2$
(D) It is not an eigenstate of H, with expectation value $\frac{3}{4}A\hbar^2$
Author Response	Thoughts: The state ψ is a symmetric superposition of spin configurations of three particles. Given that it represents one of the symmetric combinations, it tends to suggest a mixed state rather than a defined eigenvalue.
Answer: (D)
Reviewer 1	Decision: wrong
Confidence: 5
Justification: ψ is a symmetric combination of three particles. Any pair of two spins in this symmetric state operates as a triplet. For a triplet state, $\mathbf{S}_i \cdot \mathbf{S}_j = \frac{1}{4}\hbar^2$. The Hamiltonian has three such pairs, so $H\psi = 3 \times A(\frac{1}{4}\hbar^2)\psi = \frac{3}{4}A\hbar^2\psi$. It is indeed an eigenstate.
Reviewer 2	Decision: wrong
Confidence: 4
Justification: The state lacks the sole triplet representation, hence is not an eigenstate. Computing the expectation value yields $\frac{2}{3}A\hbar^2$.
Meta-Review	Decision: wrong
Justification: Reviewer 1 provides a thorough and robust analysis verifying that ψ is an eigenstate due to its symmetric properties, correctly deriving the energy $\frac{3}{4}A\hbar^2$. Reviewer 2's expectation calculation is contradicted by this proof.
Suggestions: The author should calculate the action of H on the stated ψ more explicitly, as demonstrated by Reviewer 1.
Author Rebuttal	Thoughts: After reevaluating, it is clear that ψ forms a fully symmetric combination. The Hamiltonian acts on pairs of spin operators. Due to this symmetry, ψ is an eigenstate of H, and summing the triplet pair interactions leads to the specific eigenvalue $\frac{3}{4}A\hbar^2$.
Answer: (A)

Table 6: Case study from GPQA: The MARS Meta-Reviewer successfully adjudicates between conflicting reviewers, selecting the rigorous quantum mechanical derivation over flawed reasoning.