A Rotated Hyperbolic Wrapped Normal Distribution for Hierarchical Representation Learning

Abstract

We present a rotated hyperbolic wrapped normal distribution (RoWN), a simple yet effective alteration of a hyperbolic wrapped normal distribution (HWN). The HWN expands the domain of probabilistic modeling from Euclidean to hyperbolic space, where a tree can be embedded with arbitrary low distortion in theory. In this work, we analyze the geometric properties of the *diagonal* HWN, a standard choice of distribution in probabilistic modeling. The analysis shows that the distribution is inappropriate to represent the data points at the same hierarchy level through their angular distance with the same norm in the Poincaré disk model. We then empirically verify the presence of limitations of HWN, and show how RoWN, the newly proposed distribution, can alleviate the limitations on various hierarchical datasets, including noisy synthetic binary tree, WordNet, and Atari 2600 Breakout.

1 Introduction

Hyperbolic space has served as an effective medium to learn parsimonious representations of hierarchical data, including vocabulary with relationships (Nickel and Kiela, 2017, 2018; Tifrea et al., 2019), knowledge graphs (Chami et al., 2020; Sun et al., 2020), and social networks (Zhao et al., 2011; Shavitt and Tankel, 2008). Recent studies reveal that the underlying anatomy in much complex data is non-Euclidean, supporting the success of representation learning in hyperbolic space (Bronstein et al., 2017). However, due to the absence of well-defined distribution that is easy to sample and has analytic density function in hyperbolic space, earlier studies have focused on the non-probabilistic learning framework.

Hyperbolic wrapped normal distribution (HWN) has been recently proposed as an alternative to the celebrated normal distribution in Euclidean space. With an analytic density function and easiness of sampling, the HWN expands the domain of probabilistic modeling from Euclidean to hyperbolic space. The HWN has been successfully applied in various probabilistic models, including VAE (Kingma and Welling, 2014) and probabilistic word embeddings (Vilnis and McCallum, 2015). However, unlike the normal distribution in Euclidean space, the geometric characteristics of the HWN have not been fully understood so far. Therefore, figuring out what can be done or not with the HWN is difficult.

In this work, we analyze the geometric properties of a *diagonal* HWN, a standard choice of distribution in many probabilistic models (Mathieu et al., 2019; Nagano et al., 2019). Based on the observation that the principal axes of the diagonal normal distribution in Euclidean space have a parallel structure with the standard bases, we also focus on the structure of the principal axes of HWN in the hyperbolic space to delve into a deeper understanding. Our analysis shows that the principal axes of the diagonal HWN are locally parallel to the standard bases in the Poincaré disk model.

(a) Poincaré disk model   (b) Lorentz model

Figure 1: Visualization of the hyperbolic space models. (a) The Poincaré disk model can embed a given tree-structured data with low distortions as shown in the illustration. The black segments refer to the shortest path between the points in Poincaré disk model. The red dashed line denotes the continuous points in the same hierarchy level. (b) Lorentz model is another model for the hyperbolic space. The blue line is the shortest path between the points on the Lorentz model. The red line is the projected geodesic via the diffeomorphism, which is still a geodesic of the Poincaré disk model.

Figure 1 (a) shows a common understanding on learned representation of hierarchical data in Poincaré disk. The hierarchical structure spreads out like the spokes of a wheel. The local variation in a hierarchy can then be represented as an angular difference between nodes at the same level of the norm, i.e., the principal axis representing local variation is orthogonal to the radial axis. However, our analysis of the geometric property reveals that the local variation can only be modeled along with the standard bases with the diagonal HWN.

To fix the structure of the principal axes in the diagonal HWN, we propose a simple yet effective alteration of HWN, named a rotated hyperbolic wrapped normal distribution (RoWN). By rotating the diagonal covariance matrix before parallel transportation of HWN, we could resolve the limitations in local variation structure while keeping the valuable properties, such as easy sampling and tractable density of the original HWN.

We verify the representation learned with RoWN agrees with the common characteristic of representation in the hyperbolic space, which is barely observable with the diagonal and the full covariance HWN, by using *synthetic noisy binary tree* dataset. We demonstrate the usefulness of RoWN on the benchmark datasets: WordNet and Atari 2600 breakout. We summarize our contributions as follows:

1. We provide an analysis of geometric properties of HWN and its potential limitations in representation learning.

2. We propose a novel and efficient method of using hyperbolic distribution, namely RoWN, and apply it to probabilistic models.

3. We demonstrate the performance of RoWN through the comparison with the Euclidean normal distribution, diagonal covariance HWN, and full covariance HWN on one synthetic dataset and two benchmark datasets.

2   Preliminaries

This section reviews the wrapped normal distribution defined on the Lorentz model. We first introduce the Lorentz model of the hyperbolic space and necessary concepts to understand the wrapped normal distribution.

2.1   The Lorentz model

Hyperbolic space is a non-Euclidean space, having a constant negative Gaussian curvature. Figure 1 illustrates two models for the hyperbolic space, among four standard equivalent models: (1) Klein

model, (2) Poincaré disk model, (3) Lorentz (Hyperboloid) model, and (4) Poincaré half-plane model. In particular, the Lorentz model is famous for its numerical stability in computing the distance and comes with a simpler closed form of geodesics (Nickel and Kiela, 2018). The Lorentz model $\mathbb{L}^n$ is the Riemannian manifold consisting of the set of points $\boldsymbol{z} \in \mathbb{R}^{n+1}$ satisfying $\langle \boldsymbol{z}, \boldsymbol{z} \rangle_{\mathcal{L}} = -1$ and $z_0 > 0$, where the Lorentizan product is defined as:

$$\langle \boldsymbol{x}, \boldsymbol{y} \rangle_{\mathcal{L}} := -x_0 y_0 + \sum_{i=1}^{n} x_i y_i,$$

which also works as the metric tensor on the hyperbolic space, i.e., the metric tensor g of Lorentz model is $g(\boldsymbol{x}) = \mathrm{diag}[-1, 1, \cdots, 1]$

2.2 Tangent space of the Lorentz model

Let $\mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n$ be a tangent space of $\boldsymbol{x}$ at $\mathbb{L}^n$. $\mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n$ is a set of points satisfying the orthogonality relation with $\boldsymbol{x}$ in terms of the Lorentzian product: $T_{\boldsymbol{x}} \mathbb{L}^n := \{\boldsymbol{u} : \langle \boldsymbol{u}, \boldsymbol{x} \rangle_{\mathcal{L}} = 0\}$. The metric tensor g induces an inner product $\langle \cdot, \cdot \rangle_{\boldsymbol{x}} : \mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n \times \mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n \to \mathbb{R}$. Geodesic $\gamma : [0, 1] \to \mathbb{L}^n$ generalizes straight lines in Riemannian manifold. The exponential map $\exp_{\boldsymbol{x}} : \mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n \to \mathbb{L}^n$ maps a tangent vector $\boldsymbol{u} \in \mathcal{T}_{\boldsymbol{x}} \mathbb{L}^n$ onto $\mathbb{L}^n$ as

$$\exp_{\boldsymbol{x}}(\boldsymbol{u}) := \cosh(\|\boldsymbol{u}\|_{\mathcal{L}})\boldsymbol{x} + \sinh(\|\boldsymbol{u}\|_{\mathcal{L}})\frac{\boldsymbol{u}}{\|\boldsymbol{u}\|_{\mathcal{L}}}, \tag{1}$$

such that $\exp_{\boldsymbol{x}}(\boldsymbol{u}) = \boldsymbol{y}, \gamma(0) = \boldsymbol{x}, \gamma(1) = \boldsymbol{y}$. The log map, inverse of the exponential map, is defined as $\log_{\boldsymbol{u}}(\boldsymbol{x}) := \exp_{\boldsymbol{x}}^{-1}(\boldsymbol{u})$.

Parallel transport is an operation that transports a tangent vector in the tangent space at $\boldsymbol{x}$ to another vector in the tangent space at $\boldsymbol{y}$ along the geodesic from $\boldsymbol{x}$ to $\boldsymbol{y}$ without changing its metric tensor. The parallel transport in the Lorentz model is given by:

$$\mathrm{PT}_{\boldsymbol{x} \to \boldsymbol{y}}(\boldsymbol{v}) := \boldsymbol{v} + \frac{\langle \boldsymbol{y} - \alpha\boldsymbol{x}, \boldsymbol{v} \rangle_{\mathcal{L}}}{\alpha + 1}(\boldsymbol{x} + \boldsymbol{y}), \tag{2}$$

where $\alpha = -\langle \boldsymbol{x}, \boldsymbol{y} \rangle_{\mathcal{L}}$.

2.3 Hyperbolic wrapped normal distribution

One of the key challenges in adopting hyperbolic space to probabilistic models is finding a distribution on hyperbolic space that is easy to sample and has a closed-form density function. The two most common distributions of hyperbolic space used in previous work are Riemannian normal distribution (Mathieu et al., 2019; Said et al., 2014) and hyperbolic wrapped normal distribution (HWN) (Nagano et al., 2019). Our work is mainly based on the HWN because sampling in Riemannian normal distribution is limited with only a unit variance.

The sampling process with the HWN follows:

1. Sample $\boldsymbol{v} \in \mathbb{R}^n$ from a Gaussian distribution $\mathcal{N}(\boldsymbol{0}, \Sigma)$ in Euclidean space.
2. Parallel transport the vector $[0, \boldsymbol{v}] \in \mathcal{T}_{\boldsymbol{0}_{\mathcal{L}}} \mathbb{L}^n$ to the tangent space.
3. Project the transported tangent vector to $\mathbb{L}^n$ using exponential mapping.

The density of a sample can be measured via the change of variable method. For convenience, we denote the procedure 2 and 3 as a single operation:

$$f_{\boldsymbol{\mu}}(\boldsymbol{v}) := \exp_{\boldsymbol{\mu}}(\mathrm{PT}_{\boldsymbol{0}_{\mathcal{L}} \to \boldsymbol{\mu}}([0, \boldsymbol{v}])), \tag{3}$$

with given $\boldsymbol{\mu} \in \mathbb{L}^n$ and $\boldsymbol{v} \in \mathbb{R}^n$, and $\boldsymbol{0}_{\mathcal{L}} = [1, \ldots, 0]$ stands for the origin of $\mathbb{L}^n$.

3 Rotated Hyperbolic Wrapped Normal Distribution

This section introduces several observations on the geometric properties of the HWN distribution transformation from the Euclidean space to the hyperbolic space. We show the limitations of the a diagonal HWN for representation learning of hierarchical data. Then, we propose a simple yet effective modification of the HWN, called a rotated hyperbolic wrapped normal distribution.

Figure 2: Visualization of (a) the principal axes of the normal distribution in the Euclidean space, (b) the transported version of two axes in the hyperbolic space, and (c) the probability density plot of the distributions. (a) The contour line (green) can be represented as an ellipse with major principal axis (blue) and minor principal axis (red). (b) The transformed principal axes become geodesics in the hyperbolic space. The major principal axis of the RoWN passes the hyperbolic origin and crosses with the minor axis at the mean point, whereas the major and minor axes of the diagonal HWN is locally parallel to the standard axes. (c) The principal axes determine the shapes of the posterior distributions.

3.1 Observations on the hyperbolic wrapped normal distribution

First, we investigate the changes in the normal distribution during the transformation from Euclidean to hyperbolic space by Equation 3. As the principal axes characterize the covariance structure of the normal distribution in the Euclidean space, we investigate how the principal axes are transformed in the hyperbolic space. Before deriving our main proposition, we first show that straight lines that pass through the origin in the Euclidean space are transformed to the geodesics in the hyperbolic space by Equation 3.

Proposition 1. *Suppose $\ell_{\boldsymbol{s}}(t) = t\boldsymbol{s} \in \mathbb{R}^n$ be a line passing through the origin, where $\boldsymbol{s} \in \mathbb{R}^n$ is a directional vector. Then the curve $f_{\boldsymbol{\mu}}(\ell_{\boldsymbol{s}}(t))$ in the Lorentz model $\mathbb{L}^n$ becomes a geodesic.*

The proof of the proposition is provided in Appendix A. The proposition indicates that every straight line that passes through the origin including the principal axes, is transformed into a geodesic in the hyperbolic space.

Based on the first proposition, we provide our main proposition, which fully characterizes the structure of principal axes when projected to the Poincaré disk model:

Proposition 2. *Let $\mathrm{Proj}(\boldsymbol{u})$ be the projection function from Lorentz model to Poincaré model, i.e., $\mathrm{Proj}(\boldsymbol{u}) = \frac{x_{1:}(\boldsymbol{u})}{x_0(\boldsymbol{u})+1}, \forall \boldsymbol{u} \in \mathbb{L}^n$. Let $\ell_{\boldsymbol{s}}$ be a principal axis of the normal distribution defined in $\mathbb{R}^n$ and $\boldsymbol{\mu}$ the mean of HWN in $\mathbb{L}^n$, then $\boldsymbol{s}$ is the tangent vector of $\mathrm{Proj}(f_{\boldsymbol{\mu}}(\ell_{\boldsymbol{s}}))$ on $\mathrm{Proj}(\boldsymbol{\mu})$.*

The proof of the proposition is provided in Appendix B. The proposition reveals that the principal axes of the HWN are locally parallel to the standard bases in the Poincaré disk model. To visualize the proposition, we plot the contour line and the principal axes of the two-dimensional diagonal covariance normal distribution before and after the transformation in Figure 2. We observe that the tangent lines of the transformed principal axes are parallel to the standard bases in the hyperbolic space.

When a popular diagonal normal distribution is employed as a prior distribution, the locally parallel principal axes might be problematic in learning hierarchical representations. For example, suppose

	(a) Diagonal HWN	(b) Full covariance HWN	(c) RoWN

Figure 3: Visualization of the posterior distribution of hyperbolic VAE on a synthetic binary tree dataset with different prior choices. The red dots denote the posterior means of the root and four representative children. The upper row shows the samples from the posterior distributions where the color denotes the level of noises. The bottom row shows the means of the posterior distributions. Overall, RoWN better aligns local variation in angular difference.

126 one tries to represent the variability along the radial direction or in angular differences. In that case,
127 both the primary (red) and minor (blue) axes in Figure 2b cannot model the variability properly.

3.2 Rotated hyperbolic wrapped normal distribution

129 Based on the observation, we propose a simple yet effective alternative to the diagonal HWN, a
130 rotated hyperbolic wrapped normal distribution (RoWN). Rotating covariance matrix to the direction
131 of $\boldsymbol{\mu}$ enables aligning the major axis of the normal distribution in the Euclidean space to the radial
132 axis in the hyperbolic space as visualized in the Figure 2.

133 To construct the distribution, we start with a mean vector $\boldsymbol{\mu} \in \mathbb{L}^n$ and a diagonal covariance matrix Σ
134 as in the standard HWN. We change the covariance matrix of the normal distribution as follows:

    1. Compute the rotation matrix $\boldsymbol{R}$ that rotates the x-axis ($[\pm 1, \ldots, 0] \in \mathbb{R}^n$) to $\boldsymbol{\mu}_{1:}$.

    2. Substitute the covariance matrix of Gaussian normal with $\boldsymbol{R}\Sigma\boldsymbol{R}^T$.

137 Thus, the rotation matrix $\boldsymbol{R}$, which rotates a unit vector from $\boldsymbol{x}$ to $\boldsymbol{y}$, can be computed as:

$$\boldsymbol{R} = \boldsymbol{I} + (\boldsymbol{y}^T\boldsymbol{x} - \boldsymbol{x}^T\boldsymbol{y}) + \frac{1}{1 + \langle \boldsymbol{x}, \boldsymbol{y} \rangle}(\boldsymbol{y}^T\boldsymbol{x} - \boldsymbol{x}^T\boldsymbol{y})^2. \tag{4}$$

Algorithm 1 Sampling process with the rotated hyperbolic wrapped normal distribution

---

Input Mean $\boldsymbol{\mu} \in \mathbb{L}^n$, diagonal covariance matrix $\Sigma \in \mathbb{R}^{n \times n}$

Output Sample $\boldsymbol{z} \in \mathbb{L}^n$

  1: $\boldsymbol{x} = [\pm 1, \ldots, 0] \in \mathbb{R}^n, \boldsymbol{y} = \boldsymbol{\mu}_{1:}/\|\boldsymbol{\mu}_{1:}\|$ ▷ $\pm$ is determined by the sign of $\boldsymbol{\mu}_1$
  2: $\boldsymbol{R} = \boldsymbol{I} + (\boldsymbol{y}^T\boldsymbol{x} - \boldsymbol{x}^T\boldsymbol{y}) + (\boldsymbol{y}^T\boldsymbol{x} - \boldsymbol{x}^T\boldsymbol{y})^2/(1 + \langle \boldsymbol{x}, \boldsymbol{y} \rangle)$
  3: Rotate $\hat{\Sigma} = \boldsymbol{R}\Sigma\boldsymbol{R}^T$
  4: Sample $\boldsymbol{v} \sim \mathcal{N}(\boldsymbol{0}, \hat{\Sigma})$
  5: **return** $\boldsymbol{z} = f_{\boldsymbol{\mu}}(\boldsymbol{v})$

(a) Noisy synthetic binary tree

(b) Learned representations

Figure 4: Illustration of a noisy synthetic binary tree. (a) We construct a noisy synthetic binary tree by adding spherical noises defined with θ. The continuous samples are generated at the same distance from the root. (b) We train the depth three noisy synthetic binary tree with hyperbolic VAE with RoWN as a prior distribution and visualize the means of the posterior distributions. The black lines show the underlying hierarchical structure, and the color denotes the level of noise. The hierarchy and the local variations are well preserved in the representations.

Note that the construction is straightforward but still keeps the following benefits of the HWN: 1) The sampling can be done efficiently, and 2) the computation of the probability density of the samples is tractable. As the HWN provides a tractable probability density function for any kind of covariance matrix, we can easily compute the probability density of a given sample from RoWN. See Appendix C for more details.

We empirically demonstrate the influence of different prior choices in Figure 3. We visualize the posterior distributions of the synthetic binary tree dataset of depth two after training a hyperbolic VAE. As the result shows, the model with the diagonal HWN represents the variation in a child parallel to the standard bases, whereas the model with RoWN represents the variation in angular difference. Please check the detailed description on the synthetic dataset in Section 4.1.

4 Experiments

In this section, we exhibit three different experiments, where each experiment presents different behavior of RoWN in diverse applications. For all applications, we compare the performance of RoWN with three baselines, including the normal distribution in the Euclidean space and the diagonal HWN (Nagano et al., 2019), and the full covariance HWN.

4.1 Noisy synthetic binary tree

A synthetic binary tree dataset is first used to show the performance of representing hierarchy in Nagano et al. (2019), where each node in a tree corresponds to a sequence of binary values. Figure 4a shows an example of the depth three binary tree, where a parent and child only differ in one digit. We add spherical noises to the nodes in the same level of hierarchy as described in Figure 4a as the noisy samples. With the data points with additional noises, we can create a dataset containing a local-level variation in the hierarchy. For the experiments, we uniformly sample the spherical noise from $[0, \pi/4]$.

We train hyperbolic VAE on *noisy synthetic binary tree* with varying depths. The detailed model description is available in Appendix D. We set the latent dimension the same as the depth. We report 1) the correlation between the hamming distance and the embedding distance and 2) the correlation between the depth and the Poincaré norm of the embeddings. The first correlation is computed over all possible pairs of test points. As Table 1 shows, the full covariance HWN and

Table 1: Results of *noisy synthetic binary tree*. The results are averaged over 10 runs. The hyperbolic models outperform the Euclidean model in all settings. Overall, RoWN preserves the hierarchical information better than the other distributions.

		Depth			
		4	5	6	7
Correlation w/ distance	Euclidean	$0.748_{\pm.032}$	$0.740_{\pm.013}$	$0.741_{\pm.008}$	$0.733_{\pm.014}$
	HWN (diagonal Σ)	$0.814_{\pm.008}$	$0.791_{\pm.023}$	$0.817_{\pm.010}$	$0.759_{\pm.025}$
	HWN (full Σ)	$0.827_{\pm.015}$	$0.798_{\pm.026}$	$0.798_{\pm.010}$	$0.794_{\pm.014}$
	RoWN	$0.820_{\pm.015}$	$0.807_{\pm.017}$	$0.822_{\pm.017}$	$0.788_{\pm.016}$
Correlation w/ depth	Euclidean	$0.762_{\pm.117}$	$0.807_{\pm.038}$	$0.712_{\pm.054}$	$0.612_{\pm.049}$
	HWN (diagonal Σ)	$0.918_{\pm.028}$	$0.808_{\pm.076}$	$0.862_{\pm.035}$	$0.697_{\pm.076}$
	HWN (full Σ)	$0.956_{\pm.015}$	$0.878_{\pm.051}$	$0.870_{\pm.033}$	$0.815_{\pm.055}$
	RoWN	$0.930_{\pm.026}$	$0.911_{\pm.027}$	$0.901_{\pm.034}$	$0.827_{\pm.047}$

RoWN improve the diagonal HWN except depth six, outperforming the Euclidean model in every setting. RoWN preserves the depth information better than the other distributions in general. We additionally visualize the posterior mean obtained by training the tree of depth three in Figure 4b, where the hierarchical structure is well preserved in the hyperbolic embedding space.

4.2 WordNet

We train a probabilistic word embedding model with WordNet dataset (Fellbaum, 1998). The dataset consists of 82,115 nouns and 743,241 hypernymy relationships, where the hypernymy relationships express the explicit hierarchy between the nouns. The Bayesian hyperbolic embedding model (Nagano et al., 2019) is employed to learn the representations with the objective of as follows:

$$\mathcal{L}(\boldsymbol{\theta}) = \mathbb{E}_{(s \sim t, s \not\sim t')}[\max(0, m + D_{\mathrm{KL}}(q_s \| q_t) - D_{\mathrm{KL}}(q_s \| q_{t'}))], \tag{5}$$

where m is a margin, θ_i represents the mean and variance parameters of normal distribution q_i defined for noun i, and $s \sim t$ and $s \not\sim t$ denote the presence and absence of hypernymy relation between word pair s and t, respectively.

We evaluate the learned representations by computing the average rank of all the hypernymies. The rank of a given pair of words s and t is computed among the distances between all possible pairs of the words s and t' without hypernymy. Table 2 shows the empirical performances of representing the word data. We report the performance with the mean rank (MR) and the mean average precision (mAP). RoWN preserves the hierarchical structure better than the other distributions, while the full covariance HWN fails due to the unstable optimization.

4.3 Atari 2600 Breakout

Trajectories of some Atari 2600 games can be structured as a tree-like hierarchy along the time horizon as Nagano et al. (2019) points out. For example, given Atari 2600 Breakout, the root node can be the starting state of the game where no blocks have been broken. As the game progresses the states of the blocks form hierarchical structure depending on which blocks have been broken. To learn the implicit hierarchy that can be observed from the trajectories of Breakout, we train the VAE models with the Atari 2600 Breakout images.

The images of Breakout are collected by using a pre-trained Deep Q-network (Mnih et al., 2015) and divided into training set and test set with 90,000 and 10,000 images respectively. We label each image with the score obtained from the game environment. So the labels are correlated to the number of broken blocks. To train VAE, we use a DCGAN-based architecture, which was originally used to evaluate HWN in Nagano et al. (2019). The detailed architecture is provided in Appendix D. To evaluate the models, we measure the correlation between the Poincaré norm of the test images and the

Poincaré disk model   Diagonal HWN   RoWN

Figure 5: The generated images from a trained VAE endowed with RoWN by using Atari 2600 Breakout images. Every five images are generated from the randomly sampled latent vectors of dimensionality two having Poincaré norm 0.1, 0.9, 0.95. The larger norm of the sample latent vectors, the more blocks are broken out in the generated images.

labeled scores. The evaluation results and the generated images from the trained models are reported in Table 3 and Figure 5, respectively. In learning Breakout images, RoWN and the full covariance HWN outperform the diagonal HWN. Especially, RoWN aligns the hierarchical structures better with respect to the norm in low latent dimensions.

5   Related work

Hierarchical representation learning with hyperbolic space.   Earlier studies on learning representation of hierarchical data have focused on embedding the hierarchical structure into Euclidean space (Nickel et al., 2011; Grover and Leskovec, 2016; Nguyen et al., 2017), which are later shown to require excessive number of dimensions to embed the original structure without any distortion (Linial et al., 1994). The hyperbolic space has been proposed as an alternative medium to embed the hierarchical data. Theoretically, any tree-structured data can be embedded to the hyperbolic space with arbitrarily low distortion (Sarkar, 2011). Based on the theory, learning representation of hierarchical structure in the hyperbolic space has been shown great success in various datasets including WordNet hierarchy, graph-structured data, and social network data (Nickel and Kiela, 2017, 2018; Chami et al., 2020; Sun et al., 2020; Zhao et al., 2011; Shavitt and Tankel, 2008). However, these studies are only limited to modeling the explicit hierarchy, which means that the dataset contains an explicit relation

Table 2: Results of *WordNet*. The results are average of 5 runs. Based on the rank of hypernymy pairs among non-hypernymy pairs, we report the mean rank (MR) and mean average precision (mAP) for evaluation.

		latent dimension		
		5	10	20
MR	Euclidean	$13.968_{\pm 0.504}$	$3.862_{\pm 0.281}$	$1.955_{\pm 0.157}$
	HWN (diagonal Σ)	$16.590_{\pm 1.146}$	$3.891_{\pm 0.447}$	$2.062_{\pm 0.088}$
	HWN (full Σ)	$557.309_{\pm 18.006}$	$466.513_{\pm 75.142}$	$599.140_{\pm 18.916}$
	RoWN	$16.271_{\pm 2.985}$	$2.888_{\pm 0.162}$	$1.783_{\pm 0.090}$
mAP	Euclidean	$0.565_{\pm 0.014}$	$0.801_{\pm 0.020}$	$0.902_{\pm 0.008}$
	HWN (diagonal Σ)	$0.565_{\pm 0.020}$	$0.805_{\pm 0.015}$	$0.905_{\pm 0.007}$
	HWN (full Σ)	$0.032_{\pm 0.003}$	$0.063_{\pm 0.005}$	$0.079_{\pm 0.021}$
	RoWN	$0.593_{\pm 0.024}$	$0.844_{\pm 0.009}$	$0.921_{\pm 0.005}$

Table 3: Results of *Atari 2600 Breakout*. The results are averaged over 10 runs. We measure the correlation between the score of an image and the Poincaré norm of the posterior mean.

		Latent dimension		
		10	15	20
Correlation btw. score and norm	Euclidean	$0.379_{\pm.007}$	$0.436_{\pm.029}$	$0.479_{\pm.020}$
	HWN (diagonal Σ)	$0.478_{\pm.011}$	$0.513_{\pm.006}$	$0.513_{\pm.008}$
	HWN (full Σ)	$0.483_{\pm.011}$	$0.520_{\pm.009}$	$0.563_{\pm.010}$
	RoWN	$0.497_{\pm.014}$	$0.556_{\pm.014}$	$0.561_{\pm.029}$

between data points. Furthermore, the learning frameworks are limited in the non-probabilistic setting because of the absence of well-behaved distribution in hyperbolic space.

Distributions in the hyperbolic space. The probabilistic model enables measuring the uncertainty and provides a principled way of learning. To extend the probabilistic learning framework from Euclidean to hyperbolic space or Riemannian manifold in general, one needs to define a well-behaved distribution that has a tractable density and is easy to sample from. Recently, a few studies has proposed probabilistic learning schemes in the hyperbolic space (Mathieu et al., 2019; Nagano et al., 2019). Mathieu et al. (2019) introduces reparametrizable sampling schemes for the two canonical Gaussian generalizations defined on the Poincaré disk model. The scheme is used to train a hyperbolic VAE and show an improved generalization performance with high interpretability. Nagano et al. (2019) suggests a method of integrating the Bayesian framework with the hyperbolic space in the Lorentz model where the simpler closed form of geodesics is defined. Based on Nagano et al. (2019), we analyze the geometric properties of the distribution lying on the Lorentz model and show the limitations of the existing method.

6 Limitations

We explore a better method of representing hierarchical data in the hyperbolic space. To this end, we propose a simple yet effective alternative of hyperbolic wrapped normal distribution. However, the proposed distribution is limited only to the hyperbolic space and no generalization method toward Rimannian space is studied yet. To explore the usefulness of alternative Riemannian spaces, finding a common distribution that can work well in any Riemannian space will be necessary.

RoWN is a subset of the full covariance HWN. However, in many cases RoWN outperforms the full covariance HWN in our experiments. In general, optimizing the covariance matrix requires to learn the quadratic number of parameters with respect to the dimensionality. We conjecture the hardness of optimization leads to the poor performance of the full covariance HWN. To overcome this limitation, a search for a better optimization algorithm in hyperbolic space needs to be explored.

7 Conclusions

In this work, we propose a novel method of using RoWN for representing the data with a hierarchical structure. With an in-depth analysis of the geometric properties of HWN, we demonstrate why the common choice of the diagonal covariance matrix for HWN may be inappropriate but the rotated covariance matrix. Our empirical results present that RoWN exhibits better representation ability, both qualitatively and quantitatively, compared to all the baselines: Euclidean normal distribution, diagonal HWN, and full covariance HWN. We hope that our method helps better understanding the anatomy of hyperbolic space and be a promising technique for efficient representation learning.

References

Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 2017.

Ines Chami, Adva Wolf, Da-Cheng Juan, Frederic Sala, Sujith Ravi, and Christopher Ré. Low-dimensional hyperbolic knowledge graph embeddings. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, July 2020.

Christiane Fellbaum. *WordNet: An Electronic Lexical Database*. Bradford Books, 1998.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, 2016.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In Yoshua Bengio and Yann LeCun, editors, *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

N. Linial, E. London, and Y. Rabinovich. The geometry of graphs and some of its algorithmic applications. In *Proceedings 35th Annual Symposium on Foundations of Computer Science*, 1994.

Emile Mathieu, Charline Le Lan, Chris J. Maddison, Ryota Tomioka, and Yee Whye Teh. Continuous hierarchical representations with poincaré variational auto-encoders. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*. Curran Associates, Inc., 2019.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 2015.

Yoshihiro Nagano, Shoichiro Yamaguchi, Yasuhiro Fujita, and f Masanori Koyama. A wrapped normal distribution on hyperbolic space for gradient-based learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, Proceedings of Machine Learning Research. PMLR, 2019.

Kim Anh Nguyen, Maximilian Köper, Sabine Schulte im Walde, and Ngoc Thang Vu. Hierarchical embeddings for hypernymy detection and directionality. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, September 2017.

Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. A three-way model for collective learning on multi-relational data. In *International Conference on Machine Learning*, 2011.

Maximillian Nickel and Douwe Kiela. Poincaré embeddings for learning hierarchical representations. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*. Curran Associates, Inc., 2017.

Maximillian Nickel and Douwe Kiela. Learning continuous hierarchies in the Lorentz model of hyperbolic geometry. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, Proceedings of Machine Learning Research. PMLR, 2018.

Salem Said, Lionel Bombrun, and Yannick Berthoumieu. New riemannian priors on the univariate normal model. *Entropy*, 2014.

Rik Sarkar. Low distortion delaunay embedding of trees in hyperbolic plane. In *Proceedings of the 19th International Conference on Graph Drawing*. Springer-Verlag, 2011.

Yuval Shavitt and Tomer Tankel. Hyperbolic embedding of internet graph for distance estimation and overlay construction. *IEEE ACM Transactions on Networking*, 2008.

Zequn Sun, Muhao Chen, Wei Hu, Chengming Wang, Jian Dai, and Wei Zhang. Knowledge association with hyperbolic knowledge graph embeddings. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, November 2020.

Alexandru Tifrea, Gary Becigneul, and Octavian-Eugen Ganea. Poincare glove: Hyperbolic word embeddings. In *International Conference on Learning Representations*, 2019.

Luke Vilnis and Andrew McCallum. Word representations via gaussian embedding. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Xiaohan Zhao, Alessandra Sala, Haitao Zheng, and Ben Y. Zhao. Efficient shortest paths on massive social graphs. In *7th International Conference on Collaborative Computing: Networking, Applications and Worksharing (CollaborateCom)*, 2011.