No-regret Learning in Repeated First-Price Auctions with Budget Constraints

Abstract

Recently the online advertising market has exhibited a gradual shift from second-price auctions to first-price auctions. Although there has been a line of works concerning online bidding strategies in first-price auctions, it still remains open how to handle budget constraints in the problem. In the present paper, we initiate the study for a buyer with budgets to learn online bidding strategies in repeated first-price auctions. We propose an RL-based bidding algorithm against the optimal non-anticipating strategy under stationary competition. Our algorithm obtains $\widetilde{O}(\sqrt{T})$-regret if the bids are all revealed at the end of each round. With the restriction that the buyer only sees the winning bid after each round, our modified algorithm obtains $\widetilde{O}(T^{\frac{7}{12}})$-regret by techniques developed from survival analysis. Our analysis extends to the more general scenario where the buyer has any bounded instantaneous utility function with regrets of the same order.

1 Introduction

The market for online advertising has extensively grown in recent years. It is estimated that the volume of online advertising worldwide will reach 500 billion dollars in 2022 (Statista, 2021). In such a market, advertising platforms use auctions to allocate ad opportunities. Typically, the advertiser has a limited amount of capital for an advertisement campaign and thus all rounds of competition are *interconnected by budgets*. Furthermore, the advertiser has very limited knowledge of 1) her valuation of certain keywords and 2) the competition she is facing. Many works have been devoted to developing algorithms for *learning* strategies for optimally spending the budget in repeated *second*-price auctions (see Section 1.1).

Nevertheless, we have witnessed numerous switches from second-price auctions to first-price auctions in the online advertising market. A recent remarkable example is Google AdSenses' integrated move at the end of 2021 (LLC, 2021). Earlier examples also include AppNexus, Index Exchange, and OpenX (Sluis, 2017). This industry-wide shift is due to various factors including a fairer transactional process and increased transparency. Further, the shift to first-price auctions brings about major importance to the following open question which is barely considered in previous works:

How should budget-constrained advertisers learn to compete in repeated first-price *auctions?*

This paper thus initiates the study of learning to bid with budget constraints in repeated first-price auctions. We note that the application of first-price auctions with budgets is not limited to online advertising mentioned above. Traditional competitive environments like mussel trade in Netherlands (van Schaik et al., 2001), modern price competition, and procurement auctions (e.g. U.S. Treasury Securities auction (Chari and Weber, 1992)) are examples as well.

Challenges and contributions The challenges in this setting are two-fold.

The first challenge relates to information structure. In practical auctions, it is often the case that only the highest bid is revealed (Esponda, 2008). This is known as *censored*-feedback or *winner's curse* in literature (Capen et al., 1971). This affects the information structure of learning since the buyer learns less information when she wins. This makes the problem challenging compared to standard contextual bandits (c.f. Section 1.1).

The second challenge is more fundamental. It is known that the strategy in first-price auctions is notoriously complex to analyze, even in the static case (Lebrun, 1996). To get an intuitive feeling of this difficulty in our problem compared to repeated second-price auctions, let us consider the offline case where the opponents' bids are all known. Given the budget, the problem for second-price auctions can be reduced to a pure knapsack problem, where the budget is regarded as weight capacity and prices as weights. This structure enables mature techniques including duality theory to be applied to study the benchmark strategy. Pitifully in first-price auctions, since the payment depends on the buyer's own bid, the previous approach/benchmark is not directly usable. We provide a concrete example to further illustrate such difficulty.

Example 1.1. *Consider a case where the buyer's value v follows a uniform distribution on $[0.4, 1]$ and the highest bid m of the opponents' follows a uniform distribution on $[0, 0.5]$. The budget B is set to be half of the time horizon $0.5T$. The first-best benchmark (an anticipating[1] strategy that knows the values and bids) is*

$$\mathop{\mathbb{E}}_{\substack{\boldsymbol{v} \sim F^T \\ \boldsymbol{m} \sim G^T}} \left[\max_{b_1,\ldots,b_T} \sum_{t=1}^{T} (v_t - b_t)\mathbf{1}_{\{b_t \geq m_t\}} \right] \quad \text{subject to} \quad \sum_{t=1}^{T} \mathbf{1}_{\{b_t \geq m_t\}} b_t \leq B \quad \forall (v_t)_{t=1}^T; (m_t)_{t=1}^T.$$

In hindsight, we need to pay as close to m_t as possible. Using the theory of knapsack, the utility is $T \cdot \mathbb{E}[\mathbf{1}_{\{V \geq M\}}(V - M)]^+ = 0.45T$. On the contrary, the optimal non-anticipating bidding strategy in a first-price auction is to bid $\frac{V}{2}$ and the utility is $T \cdot \mathbb{E}[\mathbf{1}_{\{\frac{V}{2} \geq M\}}\frac{V}{2}] = 0.26T$. There is already an $\Omega(T)$ separation between the first-best benchmark and the ideal case with full information.

This example shows that simple characterization of the optimal in previous works is not applicable. Furthermore, it remains unclear what methodology can be applied in first-price auctions with budgets. The state-of-the-art adaptive pacing strategy downgrades to truthful bidding as the budget increases, so in first-price auctions, it may result in *near-zero* reward and thus cannot have any theoretical guarantee (see (Balseiro and Gur, 2019, §2.4) for further discussions).

The present paper takes the first step to combat the challenges mentioned above with a dynamic programming approach. Correspondingly, our contribution is also two-fold:

- We provide an RL-based learning algorithm. Through the characterization of the optimal strategy, we obtain $\widetilde{O}(\sqrt{T})$-regret guarantee for the algorithm in the full-feedback case[2].
- In the censored-feedback setting, by techniques developed from survival analysis, we modify our algorithm and obtain a regret of $\widetilde{O}(T^{\frac{7}{12}})$.

1.1 RELATED WORK

Repeated second-price auctions with budgets There is a flourishing source of literature on bidding strategies in repeated auctions with budgets. Through the lens of online learning, Balseiro and Gur (2019) identify asymptotically optimal online bidding strategies known as *pacing* (a.k.a. bid-shading in literature) in repeated second-price auctions with budgets. Inspired by the pacing strategy, Flajolet and Jaillet (2017) develop no-regret non-anticipating algorithms for learning with contextual information in repeated second-price auctions. Another line of works that uses similar techniques in the present paper includes Amin et al. (2012); Tran-Thanh et al. (2014); Gummadi et al. (2012). Gummadi et al. (2012) and Amin et al. (2012) study bidding strategies in repeated second-price auctions with budget constraints, but the former does not involve any learning and the latter does not provide any regret analysis (their estimator is biased). Tran-Thanh et al. (2014) derive regret bounds for the same scenario but the optimization objective is the number of items won instead of value or surplus. Baltaoglu et al. (2017) also use dynamic programming to tackle repeated second-price auctions with budgets. However, they assume per-round budget constraints and their dynamic programming algorithm is for allocating bids among multiple items. Again, we emphasize that no prior work has been done in repeated first-price auctions with budgets since the structure of the problem (compared to second-price variants) is fundamentally different (recall Example 1.1).

---

[1]An algorithm is anticipating if bid selection depends on future observations, see Flajolet and Jaillet (2017).
[2]This is especially practical in public-sector auctions (Chari and Weber, 1992) as regulations mandate all bids to be revealed.

Repeated first-price auctions without budgets Two notable works concerning repeated first-price auctions are Han et al. (2020b) and Han et al. (2020a). Han et al. (2020b) introduce a new problem called monotone group contextual bandits and obtain an $O(\sqrt{T} \ln^2 T)$-regret algorithm for repeated first-price auctions *without* budget constraints under stationary settings. This bound is improved to $O(T^{\frac{1}{3}+\epsilon})$ by Achddou et al. (2021) with additional assumptions on distributions. Han et al. (2020a) concentrate on an adversarial setting and develop a mini-max optimal online bidding algorithm with $O(\sqrt{T} \ln T)$ regret against all Lipschitz bidding strategies. Badanidiyuru et al. (2021) consider the problem in a contextual setting. A crucial difference is that in the present paper, budgets are involved thus the algorithms from previous works are not directly suitable for our needs.

Bandit with knapsack From the bandit side, Badanidiyuru et al. (2013) develop bandit algorithms under resource constraints. They show that their algorithm can be used in dynamic procurement, dynamic posted pricing with limited supply, etc. However, since the bidder observes her value *before* bidding in our problem, results by Badanidiyuru et al. (2013) cannot be directly applied to our setting. Our setting also relates to contextual bandit problems with resource constraints (Badanidiyuru et al., 2014; Agrawal and Devanur, 2016; Agrawal et al., 2016). Nevertheless, applying this contextual bandit approach requires discretizing the action space, which needs Lipschitz continuity of distributions. Our approach does not rely on any continuity assumption. Further, the performance guarantee (typically $\widetilde{O}(T^{\frac{2}{3}})$) is worse than ours. It also does not fit into our information structure when the feedback is censored.

2 PRELIMINARIES

Auction mechanism We consider a repeated first-price auction with budgets. Specifically, we suppose that the buyer has a limited budget B to spend in a time horizon of $T \le +\infty$ (can be *unknown* to her) rounds. At the beginning of each round $t = 1, 2, \ldots, T$, the bidder privately observes a value v_t for a fresh copy of item and bids b_t according to her past observations $\boldsymbol{h}_t$ and value v_t. Denote the strategy she employs as $\pi \colon (v_t, B_t, \boldsymbol{h}_t) \to b_t$, which maps her current budget B_t, value v_t and past history $\boldsymbol{h}_t$ to a bid. Let m_t be the maximum bid of the other bidders. Since the auction is a *first* price auction, if b_t is larger than m_t, then the buyer wins the auction, is charged b_t, and obtains a utility of $v_t - b_t$; otherwise she loses and the utility is 0. Therefore, the instantaneous utility of the buyer is

$$r_t = (v_t - b_t)\mathbf{1}_{\{b_t \ge m_t\}}.$$

The exact information structure of history the buyer observes is dictated by how the mechanism reveals m_t. In full generality, we assume that the feedback is censored, i.e. only the highest bid is revealed at the end of each round and the winner does not observe m_t exactly. This is considered to be an informational version of *winner's curse* (Capen et al., 1971) and is of practical interest (Esponda, 2008). For the purpose of modeling, we suppose that ties are broken in favor of the buyer but this choice is arbitrary and by no means a limitation of our approach.

Next, we state the assumptions on m_t and v_t. Without loss of generality, we assume that b_t, m_t, v_t are normalized to be in $[0, 1]$. In the present paper, we consider a stochastic setting where m_t and v_t are drawn from some distributions F, G *unknown* to the buyer, respectively, and independent from the past. We will also refer to the cumulative distribution functions of F, G with the same notations. No further assumptions will be made on F, G. Now, the expected instantaneous utility of the buyer at time t with strategy π is

$$R^\pi(v_t, b_t) = \mathop{\mathbb{E}}_{m_t \sim F}[r_t] = (v_t - b_t)F(b_t).$$

To argue for the reasonability of this assumption, note that although other buyers may also involve learning behavior, it is typical that in a real advertising market, there are a large number of buyers. The specific buyer only faces a different small portion of them and is completely oblivious of whom she is facing in each round. Therefore, the buyer's sole objective is to maximize her utility (instead of fooling other buyers) and by the law of large numbers, the price m_t and value v_t the buyer observes are independent and identically distributed at least for a period of time.

Buyer's target and regret The buyer aims at maximizing her long-term accumulated utility subject to budget constraints. Recall that the instantaneous utility of the buyer is $r_t = (v_t - b_t)\mathbf{1}_{\{b_t \ge m_t\}}$.

The payment is $c_t = b_t \mathbf{1}_{\{b_t \geq m_t\}}$ and the budget will then decrease accordingly as the payment incurs. She can continue to bid as long as the budget has not run out but must stop at

$$\tau^* = \min\left\{T + 1, \min\left\{t \in \mathbb{N} : \sum_{\tau=1}^{t} c_\tau = B\right\} + 1\right\}.$$

The buyer's problem now becomes to determine how much to bid in each round to maximize her accumulated utility. In line with works Gummadi et al. (2012); Golrezaei et al. (2019); Deng and Zhang (2021), the buyer adopts a discount factor $\lambda \in (0, 1)$. She takes discounts since she does not know T or τ^* — Discount factors can be interpreted to be the estimate of the probability that the repeated auction will last for at least t rounds (Devanur et al., 2014; Drutsa, 2018). It means that the process will terminate at each round with probability $1 - \lambda$ (Uehara et al., 2021). On the economic side, in important real-world markets like online advertising platforms, buyers are impatient for opportunities since companies of different sizes have different capabilities. Discount factors model how impatient the buyer is in (Drutsa, 2017; Vanunts and Drutsa, 2019). Now the buyer's optimization problem is to determine a *non-anticipating* strategy π for the following:

$$\max_{\pi} \quad \mathbb{E}_{\substack{\boldsymbol{v} \sim F^T \\ \boldsymbol{m} \sim G^T}} \left[\sum_{t=1}^{T} \lambda^{t-1} r_t\right] \quad \text{subject to} \quad \sum_{t=1}^{T} \mathbf{1}_{\{b_t \geq m_t\}} b_t \leq B \quad \forall (v_t)_{t=1}^{T}; (m_t)_{t=1}^{T},$$

where $b_t = \pi(v_t, B_t, \boldsymbol{h}_t)$. Here, $\boldsymbol{v} := (v_1, \ldots, v_T)$ denotes the sequence of private values the buyer observes and $\boldsymbol{m} := (m_1, \ldots, m_T)$ is the sequence of the highest bids of the other bidders. $V^\pi(B, t)$ denotes the expected accumulated utility using strategy π with budget B and starting from time t. Let π^* denote the optimal bidding strategy with the knowledge of the underlying distributions F and G. The corresponding expected accumulated utility is $V^{\pi^*}(B, t)$. (We sometimes use $V(\cdot, \cdot)$ to represent $V^{\pi^*}(\cdot, \cdot)$ for convenience in the rest of the paper.)

We now come to define the regret. First write the per-episode revenue suboptimality for each round t as

$$\text{SubOpt}_t(\pi_t) = V^{\pi^*}(B_t, t) - V^{\pi_t}(B_t, t),$$

where π_t is the strategy used in round t. Our evaluation metric is then the sum of suboptimality for $t = 1, \ldots, T$, namely

$$\text{Regret}(T) = \mathbb{E}\left[\sum_{t=1}^{T} \text{SubOpt}_t(\pi_t)\right], \tag{1}$$

where the expectation is taken over the trajectories of the achievement of $\boldsymbol{v}$ and the realization of others' bids inexplicitly.

The definition of regret comes from traditional reinforcement learning (RL) literature of infinite-horizon discounted model (Kaelbling et al., 1996). The definition is also inspired by the recent advances in Yang et al. (2021); He et al. (2021); Liu and Su (2020); Zhou et al. (2021). Zhou et al. (2021) call it cumulative error. It reflects the suboptimality for π_t to learn the optimal valuation of attending the auction.

In the most common scenario, such as Balseiro and Gur (2019), the budget constraint is linear to time horizon T, i.e. $\frac{B}{T} \sim \Theta(1)$. Therefore, a bidder has an expectation that she will win for $O(T)$ rounds. With a causal policy, it is easy to suffer $O(T)$ regret which is intolerable for bidders. It leads to the challenge to achieve a sublinear regret in first-price auctions and we design algorithms to answer the question.

3   BIDDING ALGORITHM AND ANALYSIS

In this section, we present our bidding algorithm and the high-level ideas in the analysis of regret. We first consider the case where the feedback is not censored, i.e. the buyer is aware of m_t no matter whether she wins or not. Then we extend our algorithm to the case where the feedback is censored with techniques developed from survival analysis.

3.1 FULL FEEDBACK

When F and G are known, the buyer's problem can be viewed as offline. The technical challenge lies in the observation that even when the distributions are known, the buyer's problem cannot be directly analyzed as a knapsack problem. To tackle this challenge, we use a dynamic programming approach to solve the problem. In particular, the optimal strategy π^* satisfies the following Bellman equation:

$$b^*(B_\tau, v) \in \arg\max_b [(v - b) + \lambda V(B_\tau - b, \tau + 1)]F(b) + \lambda V(B_\tau, \tau + 1)(1 - F(b)),$$

$$V(B_\tau, \tau) = \mathbb{E}_v[(v - b^*) + \lambda V(B_\tau - b^*, \tau + 1)]F(b^*) + \lambda V(B_\tau, \tau + 1)(1 - F(b^*)),$$

for all $\tau \in \mathbb{N}$ and $0 \le B_\tau \le B$. Note that for any $B_\tau < 0$, $V(B_\tau, \tau) = -\infty$. By choosing appropriate initialization conditions, we can solve the equation recursively and obtain the optimal bidding strategy together with the function $V(\cdot, \cdot)$. The above recursion also characterizes the optimal solution, which will be used in the analysis later.

When the buyer does not have the information of F and G, she can learn the distributions from past observations. Therefore, it is natural to maintain estimations $\hat{F}$ and $\hat{G}$ of the true distributions. Our algorithm for the full-feedback case is now depicted in Algorithm 1. To ease technical loads, we first assume the knowledge of G and only estimate F in Algorithm 1. Later, we will add the estimation of G and its analysis is presented in Theorem 3.2.

Algorithm 1 Algorithm for the full-feedback case

1: **Input**: Initial budget B and constant C_1 ▷ C_1 is an arbitrary positive constant
2: Initialize the estimation $\hat{F}$ of F to a uniform distribution over $[0, 1]$ and $B_1 \leftarrow B$
3: **for** $t = 1, 2, \ldots$ **do**
4:      Observe the value v_t in round t
5:      Let t_0 be the smallest integer that satisfies $\lambda^{t_0 - t} \frac{1}{1-\lambda} < \frac{C_1}{\sqrt{t}}$
6:      Set $V_{\hat{F}}(B_{t_0}, t_0) = 0$ for any B_{t_0} ▷ $V_{\hat{F}}$ is algorithm's estimation of V
7:      **for** $\tau = t_0, t_0 - 1, \ldots, t$ **do**
8:          $Q_{v, \hat{F}}(B_\tau, \tau, b) \leftarrow [(v - b) + \lambda V_{\hat{F}}(B_\tau - b, \tau + 1)]\hat{F}(b) + \lambda V_{\hat{F}}(B_\tau, \tau + 1)(1 - \hat{F}(b))$
9:          Solve the optimization problem $\hat{b}^*_\tau \leftarrow \arg\max_b Q_{v, \hat{F}}(B_\tau, \tau, b)$
10:        $V_{\hat{F}}(B_\tau, \tau) \leftarrow \mathbb{E}_{v \sim G}[Q_{v, \hat{F}}(B_\tau, \tau, \hat{b}^*_\tau)]$
11:      **end for**
12:      Place a bid $\hat{b}_t \leftarrow \arg\max_b Q_{v, \hat{F}}(B_t, t, b)$
13:      Observe m_t, c_t and r_t from this round of auction and update $\hat{F}(x) = \frac{1}{t} \sum_{i=1}^{t} \mathbf{1}_{\{m_i \le x\}}$.
14:      $B_{t+1} \leftarrow B_t - c_t$. If $B_{t+1} \le 0$ then halt.
15: **end for**

Similar to prior work (Amin et al., 2012), Algorithm 1 performs exploration and exploitation simultaneously. The buyer initializes the estimation of F to a uniform distribution (Line 2). At round t, the buyer observes her valuation. Then, she uses her estimation of F to solve the dynamic programming problem recursively[3] to obtain an estimation of the optimal bid (Line 7~Line 11). To provide a base case for recursion, note that for sufficiently large $t_0 \gg t$, $V_{\hat{F}}(\cdot, t_0)$'s impact to $V_{\hat{F}}(\cdot, t)$ is negligible due to the discount $\lambda^{t_0 - t}$. Therefore, the buyer can approximate $V_{\hat{F}}(\cdot, t_0)$ with zero for t_0 (Line 5). Finally, the auction proceeds with m_t, r_t, c_t revealed and the buyer updates her information accordingly (Line 13~Line 14).

Analysis of regret To analyze the algorithm, we first assume that Algorithm 1 knows the distribution G exactly and establishes the regret. Then we add the contribution of the estimation of F.

Theorem 3.1. *Under the circumstance that F is unknown, the worse-case regret of Algorithm 1 is $\widetilde{O}(\sqrt{T})$, where the regret is computed according to Equation* (1). *Explicitly, if we take $C_1 = 1$,*

$$Regret(T) \le \left(4\sqrt{\frac{1}{2} \ln 2T^2} \frac{1 + \lambda}{(1 - \lambda)^3} + \frac{4}{1 - \lambda} \right) \sqrt{T} + 1.$$

---

[3]For the non-trivial case $B \le T$, this can be solved in $O\left(\frac{T^{4.5}}{(1-\lambda)^6}\right)$ time with only $O(T^{-\frac{1}{2}})$ loss (see, e.g. Chow and Tsitsiklis, 1989).

To show an example of the application of the result, let us take the budget B to scale linearly with T as in Balseiro and Gur (2019); Flajolet and Jaillet (2017). Specifically, assume that $T < +\infty$ and there exists a constant β such that the budget $B = \beta T$, then we establish that the regret is $\widetilde{O}(\sqrt{T})$ in this special case. Indeed, under this condition, we can simply set $t_0 = T + 1$ and $V_{\hat{F}}(B_{T+1}, T+1) = 0$ for any B_{T+1} in Algorithm 1. Therefore, $C_1 = 0$ and the worst-case regret is bounded by $\left(4\sqrt{\frac{1}{2}\ln 2T^2 \frac{1+\lambda}{(1-\lambda)^3}}\right)\sqrt{T} + 1$.

Next, we deal with the case where G is also initially unknown. Based on Algorithm 1, we additionally maintain an estimation $\hat{G}$ of G based on past observations of valuations. $\hat{G}$ is initialized to be a uniform distribution and will be used to solve the dynamic programming problem (see Line 7 of Algorithm 2). Using similar techniques as before (with more work), we obtain the following theorem.

Theorem 3.2. *Under the circumstance that F, G are both unknown, it holds that the worst-case regret of Algorithm 1 using empirical distribution functions to estimate F and G is $\widetilde{O}(\sqrt{T})$. Explicitly, if we take $C_1 = 1$,*

$$Regret(T) \le \left(\sqrt{\frac{1}{2}\ln 4T^2 \frac{6(1+\lambda)}{(1-\lambda)^3}} + \frac{4}{1-\lambda}\right)\sqrt{T} + 1.$$

3.2 CENSORED FEEDBACK

In this subsection, we deal with the case that the buyer can only see the winner's bid after each round. In other words, the feedback is left-censored. Concretely, the buyer's observation is

$$o_t = \max\{b_t, m_t\}.$$

When she wins, the exact value of m_t is not revealed. The buyer only knows that m_t is smaller than her bid in the current round. To estimate the distribution of m_t, there is a classical statistics (KM estimator) developed by Kaplan and Meier (1958) for the estimation of F in this scenario. However, the KM estimator assumes the sequence $(m_t)_{t=1}^T$ is deterministic, which does not fit our needs. Although Suzukawa (2004)'s extension allows random censorship, it requires independence between b_t and m_t, which is not realistic since we use the estimated distribution to place bids.

To tackle this problem, we first introduce an estimator proposed by Zeng (2004) denoted by $\hat{F}_n$ to take place of the previous empirical distribution used in Algorithm 1.

Estimation procedure We now present the procedure for estimating F under censored feedback. It suffices to estimate the distribution function of $1 - m_t$ which is right-censored by $1 - b_t$. Let $y_t = \min\{1 - m_t, 1 - b_t\}, r_t = \mathbf{1}_{\{m_t \ge b_t\}}$. The observations can now be described as $(y_t, r_t, \boldsymbol{h}_t)_{t=1}^T$.

Roughly speaking, to decouple the dependency between m_t, b_t, we use the fact that b_t and m_t are independent conditioning on $\boldsymbol{h}_t$. Intuitively, the history $\boldsymbol{h}_t$ provides information for getting enough effective samples for m_t. Next, we establish models to estimate the hazard rate functions[4] of $1 - m_t, 1 - b_t$ using $\boldsymbol{h}_t$. With the hazard rate functions, we use the maximum likelihood method with a kernel to compute the final estimation $\hat{F}_t$ and obtain Equation (3).

Details follow. We initialize with a sequence (bandwidth) $(a_t)_{t=1}^T$ such that $\frac{\log^2 a_t}{ta_t^2} \to 0, ta_t^2 \to \infty, ta_t^4 \to 0$ as $t \to +\infty$ and a symmetric kernel function $K(\cdot, \cdot) \in C^2(\mathbb{R}^2)$ with bounded gradient. Now, at each time t, we compute two vectors $\boldsymbol{\beta}_t, \boldsymbol{\gamma}_t$ which maximize each of the followings

$$f(\boldsymbol{\beta}) = \sum_{\tau=1}^t \frac{r_\tau}{t}\left(\boldsymbol{\beta}^\top \boldsymbol{h}_\tau - \log\sum_{y_i \ge y_\tau} e^{\boldsymbol{\beta}^\top \boldsymbol{h}_\tau}\right), g(\boldsymbol{\gamma}) = \sum_{\tau=1}^t \frac{1-r_\tau}{t}\left(\boldsymbol{\gamma}^\top \boldsymbol{h}_\tau - \log\sum_{y_i \ge y_\tau} e^{\boldsymbol{\gamma}^\top \boldsymbol{h}_\tau}\right). \tag{2}$$

We arbitrarily pad $\boldsymbol{h}_1, \ldots, \boldsymbol{h}_t$ with zeros to make their length the same (we will show that this is without loss of generality in a moment). Compute $\boldsymbol{Z}_t = (\boldsymbol{\beta}_t^\top \boldsymbol{h}_t, \boldsymbol{\gamma}_t^\top \boldsymbol{h}_t)^\top$. The survival function of $1 - m_t$, or equivalently the cumulative distribution function of m_t, is estimated based on Zeng

---

[4]The hazard rate function of a random variable X with p.d.f. f and c.d.f. F is $H_X(x) = \frac{f(x)}{1-F(x)}$.

(2004)'s estimator

$$\hat{F}_t(x) = \frac{1}{t} \sum_{i=1}^{t} \prod_{j=1}^{t} \left(1 - \frac{K((\boldsymbol{Z}_i - \boldsymbol{Z}_j)/a_n)\mathbf{1}_{\{y_j \leq x\}} r_j}{\sum_{m=1}^{n} K((\boldsymbol{Z}_i - \boldsymbol{Z}_m)/a_n)\mathbf{1}_{\{y_j \leq y_m\}}} \right). \tag{3}$$

Now, we are ready to apply the estimator to design the algorithm for the censored-feedback case. Note that the new estimator's convergence rate is slower than that for the full-feedback case. Therefore, compared to Algorithm 1, Algorithm 2 is now a multi-phase algorithm. The algorithm only updates the estimation of $\hat{F}$ at the end of each phase (see Figure 1 for an illustration). The other elements of each phase in Algorithm 2 are similar to Algorithm 1.

Algorithm 2 Algorithm for the censored-feedback case

1: **Input**: Initial budget B and constant C_1 ▷ C_1 is an arbitrary positive constant
2: Initialize the estimation $\hat{F}$ of F and the estimation $\hat{G}$ of G to uniform distributions over $[0,1]$
3: $B_1 \leftarrow B$
4: **for** Phase $i = 1, 2, \ldots$ **do**   ▷ Phase i $(i > 1)$ lasts for 2^i rounds. Phase 1 lasts for 2 rounds
5:      **for** each t in the time interval of round i **do**
6:          Observe the value v_t in round t
7:          Update $\hat{G}(x) = \frac{1}{t} \sum_{i=1}^{t} \mathbf{1}_{\{v_i \leq x\}}$.
8:          Let t_0 be the smallest integer that satisfies $\lambda^{t_0 - t} \frac{1}{1-\lambda} < \frac{C_1}{\sqrt{t}}$
9:          Set $V_{\hat{F},\hat{G}}(B_{t_0}, t_0) = 0$ for any B_{t_0} ▷ $V_{\hat{F},\hat{G}}$ is algorithm's estimation of V
10:          **for** $\tau = t_0, t_0 - 1, \ldots, t$ **do**   ▷ This loop can be moved to the end of each phase to reduce the invocation time from T to $\ln T$
11:              $Q_{\hat{F},\hat{G}}(B_\tau, \tau, b) \leftarrow [(v - b) + \lambda V_{\hat{F},\hat{G}}(B_\tau - b, \tau + 1)]\hat{F}(b) + \lambda V_{\hat{F},\hat{G}}(B_\tau, \tau + 1)(1 - \hat{F}(b))$
12:              Solve the optimization problem $\hat{b}_\tau^* \leftarrow \arg\max_b Q_{\hat{F},\hat{G}}(B_\tau, \tau, b)$
13:              $V_{\hat{F},\hat{G}}(B_\tau, \tau) \leftarrow \mathbb{E}_{v \sim G}[Q_{\hat{F},\hat{G}}(B_\tau, \tau, \hat{b}_\tau^*)]$
14:          **end for**
15:          Place a bid $\hat{b}_t \leftarrow \arg\max_b Q_{\hat{F},\hat{G}}(B_t, t, b)$
16:          Observe o_t, c_t and r_t from this round of auction
17:          $B_{t+1} \leftarrow B_t - c_t$. If $B_{t+1} \leq 0$ then halt.
18:      **end for**
19:      Update $\hat{F}$ using the estimator specified in Equation (3) with data observed before this phase
20: **end for**

Figure 1: Schematic representation of the phases in Algorithm 2. Algorithm 2 updates its estimates of F at the end of each phase.

Analysis of regret   To analyze the performance of Algorithm 2, we will prove a series of lemmas on the estimation error of Equation (3). We concentrate on the performance of the new estimator since this is the major difference between Algorithm 1 and Algorithm 2. In particular, our proof relies on the following convergence result.

Lemma 3.3 (Zeng). *Let $\hat{F}_n$ be the estimation of F after using n observations. We have*

$$\sqrt{n}(\hat{F}_n(1-x) - F(1-x)) \Longrightarrow \mathcal{B}(x) \quad in \quad \ell^\infty([0,1]),$$

where $\mathcal{B}(x)$ is a Gaussian process.

Before we proceed to apply the lemma, we verify a series of prerequisites mentioned in Zeng (2004) to make sure it holds. First, we make sure that conditioning on $\boldsymbol{h}_t$, the random variables $1 - m_t$

and $1 - b_t$ are independent. Indeed, b_t is completely decided by $\boldsymbol{h}_t$ and m_t is independent of $\boldsymbol{h}_t$. Second, we note that the maximizer shown in Equation (2) is essentially doing Cox's proportional hazards regression analysis. To establish consistency of the estimator, we show that at least one of $\widetilde{m}_t := 1 - m_t$ and $1 - b_t$ follows Cox's proportional model. That is to say, there exists $\boldsymbol{\beta}$ and a function $f(y)$ such that the hazard rate function of $\widetilde{m}_t$ or $1 - b_t$ conditioning on $\boldsymbol{h}_t$ exactly follows

$$H(y \mid \boldsymbol{h}_t) = f(y)e^{\boldsymbol{\beta}^\top \boldsymbol{h}_t}. \tag{4}$$

Equation (4) holds for $\widetilde{m}_t$. In fact, taking $\boldsymbol{\beta} = \boldsymbol{0}$ and $f(y) = \frac{F'(1-y)}{1-F(1-y)}$ suffices. Since we take $\boldsymbol{\beta} = \boldsymbol{0}$, consistency establishes regardless of the way we pad $\boldsymbol{h}_t$.

Next, consider some phase at time $2^n \le t \le 2^{n+1} - 1$. The estimation $\hat{F}_n$ is computed using the first 2^n observed data points. Applying similar techniques for the rate of convergence of empirical process (Norvaiša and Paulauskas, 1991), we obtain the following lemma on the performance of $\hat{F}$ in Algorithm 2.

Lemma 3.4. *Under the update process in Algorithm 2, for any $2^n \le t \le 2^{n+1} - 1$, we have the following bounds for the estimation $\hat{F}_n$:*

$$|\Pr(\sup_b |\sqrt{2^n}(\hat{F}_n(1-b) - F(1-b))| \ge r) - \Pr(\sup_b |\mathcal{B}(1-b)| \ge r)| \le M(1+r)^{-3}\ln^2 t \cdot t^{-\frac{1}{6}},$$

where M is a constant depending only on F and Algorithm 2.

Finally, we now bound the difference between $\hat{F}_n$ and F with the help of Lemma 3.4.

Lemma 3.5. *Recall that we use the first 2^n data points to estimate $\hat{F}$. Under the update procedure of Algorithm 2, for any $2^n \le t \le 2^{n+1} - 1$, with probability at least $1 - T^{-\frac{5}{12}}/(2\ln T)$*

$$\sup_x |\hat{F}(x) - F(x)| \le \sqrt{2}C_5(4M\ln^3 T)^{\frac{1}{3}}t^{-\frac{5}{9}}T^{\frac{5}{36}}.$$

With Lemma 3.5 in hand, we now have

Theorem 3.6. *Under the circumstance that F, G are both unknown and the feedback is censored, the worst-case regret of Algorithm 2 is $\widetilde{O}(T^{\frac{7}{12}})$. Explicitly, if we take $C_1 = 1$,*

$$Regret(T) \le \left(\frac{9\sqrt{2}(1+\lambda)}{2(1-\lambda)^3}C_5(4M\ln^3 T)^{\frac{1}{3}} + 1\right)T^{\frac{7}{12}} + \left(\sqrt{\frac{1}{2}\ln 4T^{\frac{17}{12}}}\frac{2(1+\lambda)}{(1-\lambda)^3} + \frac{4}{1-\lambda}\right)\sqrt{T}.$$

Remark 3.7. *The setting in Han et al. (2020b) is a special case of ours, where there are no budget constraints and $\lambda = 0$ (thus removing the $\frac{1}{1-\lambda}$ factor in our results). The buyer's aim is to maximize $(v - b)F(b)$ each round. This is equivalent to $V_{\hat{F}} = 0$ in our setting with no need to estimate G, yielding regret $\widetilde{O}(\sqrt{T})$ in the full-feedback case and regret $\widetilde{O}(T^{\frac{7}{12}})$ in the censored-feedback case.*

Remark 3.8. *The regret-bound looks unusual at a first glance. The reason is that the convergence rate of the estimator is lower than that in the commonly used "Hoeffding-type" or "Bernstein-type" inequalities. However, due to the information structure, they are not suitable to be used in our environment to our best knowledge. The regret-bound is the best possible considering current literature.*

4 EMPIRICAL EVALUATION

Although this is mostly a theory paper, we briefly provide some experimental evidence to show that our algorithm is efficient and performs well to complement the theoretical result.

Setup The datasets of values and highest bids of the opponents are obtained by 1) sampling from uniform distributions over $[0, 1]$, and 2) sampling from right-truncated exponential distributions. Note that by domain knowledge, most valuations and bids in online auctions follow exponential distributions, so we believe that our simulations can correctly reflect real scenarios[5].

---

[5]We are unable to obtain real datasets on first-price auctions with budgets due to the fact that currently, most platforms are on the transition to first-price auctions so there are no public datasets to the best of our knowledge.

The discount factor is set to be an extreme $\lambda = 1 - 10^{-7}$ to test the robustness of our algorithm. On each realized trajectory of values and highest bids, we only reveal v_t and $\max(m_t, b_t)$ to the bidder (i.e. Algorithm 2). The dynamic programming part of the algorithm is computed using heuristics (sampling and gradient descent). For the benchmark, we use a standard benchmark — fixed pacing parameter that has the knowledge of the realized values and bids. Although this is an anticipating strategy stronger than our theoretical benchmark, we believe it serves as a strong and suitable benchmark because pacing is widely applied in practice.

We fix $T = 2000000$ and vary $\rho = B/T$ from 0.005 to 1.0 — the target average expenditure rate that reflects how much the bidder is constrained to budgets. The utility of the online algorithm is compared to the benchmark to evaluate how the performance varies w.r.t. budgets.

Figure 2: Utilities of the algorithm and the benchmark with $T = 200000$ and B/T from 0.005 to 1.0. Left: uniform distribution. Right: exponential distribution.

Results and discussion The results are shown in Figure 2, where we plot the rewards of the algorithm and the benchmark as a function of $\rho = B/T$. We make the following observations regarding the results. First, although the benchmark is anticipating, our algorithm achieves near-optimal compared to the offline benchmark. The online loss incurred by our strategy is less than 5% in cases for almost all the ρ values. Second, we observe that the strategy of our algorithm in the $\rho = 1$ region recovers that of the Bayesian optimal, providing additional evidence that the algorithm indeed learns the best non-anticipating strategy. Finally, we highlight that in our experiments, each step of decisions takes less than $10\,\mathrm{ms}$ to perform, which is realistic for real-time deployment.

5 DISCUSSION AND CONCLUSION

In this paper, we develop a learning algorithm to adaptively bid in repeated first-price auctions with budgets. On the theoretical side, our algorithm, together with its analysis of $\widetilde{O}(\sqrt{T})$-regret in the full-feedback case and $\widetilde{O}(T^{\frac{7}{12}})$-regret in the censored-feedback case, takes the first step in understanding the problem. On the practical side, our algorithm is simple and readily applicable to the digital world that has shifted to first-price auctions.

Questions raise themselves for future explorations. We observe here that in the limiting case $\lambda \to 1$, the optimal bidding strategy in Algorithm 2 is similar to a *pacing* strategy, which relates to the open question[6] raised in Balseiro and Gur (2019). In the limiting case of $\lambda \to 1$, the optimal bid of Algorithm 2 is of the form $\frac{v_t}{1+x_t}$, where x_t is a pacing multiplier that depends only on B_t and F and can be computed without solving the dynamic programming problem. This observation can be viewed as a corollary of (Theorem 3.1 Gummadi et al., 2012). This connection between Algorithm 2 and pacing suggests further investigations[7]. Other immediate open questions include establishing lower bounds of regret for our problem.

---

[6]"A question of theoretical and practical interest is how to extend the adaptive pacing approach that is suggested in this paper to nontruthful mechanisms such as first-price auctions."

[7]We note here that parallel to our work, Gaitonde et al. (2022) extend the pacing techniques to a class of auction forms (called core auctions). They obtain $\widetilde{O}(T^{\frac{3}{4}})$-regret bounds against *the best linear policy* under the *value-maximization* objective.

REFERENCES

Juliette Achddou, Olivier Cappé, and Aurélien Garivier. Fast rate learning in stochastic first price bidding. In *Asian Conference on Machine Learning*, pages 1754–1769. PMLR, 2021.

Shipra Agrawal and Nikhil Devanur. Linear contextual bandits with knapsacks. *Advances in Neural Information Processing Systems*, 29, 2016.

Shipra Agrawal, Nikhil R. Devanur, and Lihong Li. An efficient algorithm for contextual bandits with knapsacks, and an extension to concave objectives. In *Conference on Learning Theory*, pages 4–18. PMLR, 2016.

Kareem Amin, Michael Kearns, Peter Key, and Anton Schwaighofer. Budget optimization for sponsored search: Censored learning in MDPs. *arXiv preprint arXiv:1210.4847*, 2012.

Ashwinkumar Badanidiyuru, Robert Kleinberg, and Aleksandrs Slivkins. Bandits with knapsacks. In *2013 IEEE 54th Annual Symposium on Foundations of Computer Science*, pages 207–216. IEEE, 2013.

Ashwinkumar Badanidiyuru, John Langford, and Aleksandrs Slivkins. Resourceful contextual bandits. In *Conference on Learning Theory*, pages 1109–1134. PMLR, 2014.

Ashwinkumar Badanidiyuru, Zhe Feng, and Guru Guruganesh. Learning to bid in contextual first price auctions. *arXiv preprint arXiv:2109.03173*, 2021.

Santiago R. Balseiro and Yonatan Gur. Learning in repeated auctions with budgets: Regret minimization and equilibrium. *Management Science*, 65(9):3952–3968, 2019.

M. Sevi Baltaoglu, Lang Tong, and Qing Zhao. Online learning of optimal bidding strategy in repeated multi-commodity auctions. *Advances in Neural Information Processing Systems*, 30, 2017.

Edward C. Capen, Robert V. Clapp, and William M. Campbell. Competitive bidding in high-risk situations. *Journal of Petroleum Technology*, 23(06):641–653, 1971.

V. Chari and Robert Weber. How the us treasury should auction its debt. *Quarterly Review*, 16(4), 1992.

Chef-Seng Chow and John N Tsitsiklis. The complexity of dynamic programming. *Journal of complexity*, 5(4):466–488, 1989.

Yuan Deng and Hanrui Zhang. Prior-independent dynamic auctions for a value-maximizing buyer. *Advances in Neural Information Processing Systems*, 34, 2021.

Nikhil R Devanur, Yuval Peres, and Balasubramanian Sivan. Perfect bayesian equilibria in repeated sales. In *Proceedings of the twenty-sixth annual ACM-SIAM symposium on Discrete algorithms*, pages 983–1002. SIAM, 2014.

Alexey Drutsa. Horizon-independent optimal pricing in repeated auctions with truthful and strategic buyers. In *Proceedings of the 26th International Conference on World Wide Web*, pages 33–42, 2017.

Alexey Drutsa. Weakly consistent optimal pricing algorithms in repeated posted-price auctions with strategic buyer. In *International Conference on Machine Learning*, pages 1319–1328. PMLR, 2018.

Ignacio Esponda. Information feedback in first price auctions. *The RAND Journal of Economics*, 39 (2):491–508, 2008.

Arthur Flajolet and Patrick Jaillet. Real-time bidding with side information. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30, 2017.

Jason Gaitonde, Yingkai Li, Bar Light, Brendan Lucier, and Aleksandrs Slivkins. Budget Pacing in Repeated Auctions: Regret and Efficiency without Convergence. *arXiv e-prints*, art. arXiv:2205.08674, May 2022.

Negin Golrezaei, Adel Javanmard, and Vahab Mirrokni. Dynamic incentive-aware learning: Robust pricing in contextual auctions. *Advances in Neural Information Processing Systems*, 32, 2019.

Ramakrishna Gummadi, Peter Key, and Alexandre Proutiere. Repeated auctions under budget constraints: Optimal bidding strategies and equilibria. In *the Eighth Ad Auction Workshop*, volume 4, 2012.

Yanjun Han, Zhengyuan Zhou, Aaron Flores, Erik Ordentlich, and Tsachy Weissman. Learning to bid optimally and efficiently in adversarial first-price auctions. *arXiv preprint arXiv:2007.04568*, 2020a.

Yanjun Han, Zhengyuan Zhou, and Tsachy Weissman. Optimal no-regret learning in repeated first-price auctions. *arXiv preprint arXiv:2003.09795*, 2020b.

Jiafan He, Dongruo Zhou, and Quanquan Gu. Nearly minimax optimal reinforcement learning for discounted MDPs. *Advances in Neural Information Processing Systems*, 34:22288–22300, 2021.

Leslie Pack Kaelbling, Michael L Littman, and Andrew W Moore. Reinforcement learning: A survey. *Journal of Artificial Intelligence Research*, 4:237–285, 1996.

Edward L. Kaplan and Paul Meier. Nonparametric estimation from incomplete observations. *Journal of the American Statistical Association*, 53(282):457–481, 1958.

Bernard Lebrun. Existence of an equilibrium in first price auctions. *Economic Theory*, 7(3):421–443, 1996.

Shuang Liu and Hao Su. Regret bounds for discounted MDPs. *arXiv preprint arXiv:2002.05138*, 2020.

Google LLC. Faqs about adsense moving to a first-price auction - google adsense help. `https://support.google.com/adsense/answer/10858748?hl=en`, 2021. Accessed: 2022-05-06.

R. Norvaiša and V. Paulauskas. Rate of convergence in the central limit theorem for empirical processes. *Journal of Theoretical Probability*, 4(3):511–534, 1991.

Sarah Sluis. Big changes coming to auctions, as exchanges roll the dice on first-price. `https://www.adexchanger.com/platforms/big-changes-coming-auctions-exchanges-roll-dice-first-price/`, 2017.

Statista. Digital advertising spending worldwide from 2019 to 2024 (in billion u.s. dollars). `https://www.statista.com/statistics/237974/online-advertising-spending-worldwide/`, 2021. Accessed: 2022-05-05.

Akio Suzukawa. Unbiased estimation of functionals under random censorship. *Journal of the Japan Statistical Society*, 34(2):153–172, 2004.

Long Tran-Thanh, Lampros Stavrogiannis, Victor Naroditskiy, Valentin Robu, Nicholas R Jennings, and Peter Key. Efficient regret bounds for online bid optimisation in budget-limited sponsored search auctions. In *30th Conference on Uncertainty in AI*, 2014.

Masatoshi Uehara, Xuezhou Zhang, and Wen Sun. Representation learning for online and offline rl in low-rank mdps. *arXiv preprint arXiv:2110.04652*, 2021.

Frans D. J. van Schaik, Jack P. C. Kleijnen, et al. *Sealed-bid auctions: case study*. Center for Economic Research, 2001.

Arsenii Vanunts and Alexey Drutsa. Optimal pricing in repeated posted-price auctions with different patience of the seller and the buyer. *Advances in Neural Information Processing Systems*, 32, 2019.

Kunhe Yang, Lin Yang, and Simon Du. Q-learning with logarithmic regret. In *International Conference on Artificial Intelligence and Statistics*, pages 1576–1584. PMLR, 2021.

Donglin Zeng. Estimating marginal survival function by adjusting for dependent censoring using many covariates. *The Annals of Statistics*, 32(4):1533–1555, 2004.

Dongruo Zhou, Jiafan He, and Quanquan Gu. Provably efficient reinforcement learning for discounted MDPs with feature mapping. In *International Conference on Machine Learning*, pages 12793–12802. PMLR, 2021.