TrinityGuard: A Unified Framework for Safeguarding Multi-Agent Systems

Abstract

With the rapid development of LLM-based multi-agent systems (MAS), their significant safety and security concerns have emerged, which introduce novel risks going beyond single agents or LLMs. Despite attempts to address these issues, the existing literature lacks a cohesive safeguarding system specialized for MAS risks. In this work, we introduce **Trinity-Guard**, a comprehensive safety evaluation and monitoring framework for LLM-based MAS, grounded in the OWASP standards. Specifically, TrinityGuard encompasses a three-tier fine-grained risk taxonomy that identifies 20 risk types, covering single-agent vulnerabilities, inter-agent communication threats, and system-level emergent hazards. Designed for scalability across various MAS structures and platforms, TrinityGuard is organized in a trinity manner, involving an MAS abstraction layer that can be adapted to any MAS structures, an evaluation layer containing risk-specific test modules, alongside runtime monitor agents coordinated by a unified LLM Judge Factory. During Evaluation, TrinityGuard executes curated attack probes to generate detailed vulnerability reports for each risk type, where monitor agents analyze structured execution traces and issue real-time alerts, enabling both pre-development evaluation and runtime monitoring. We further formalize these safety metrics and present detailed case studies across various representative MAS examples, showcasing the versatility and reliability of TrinityGuard. Overall, TrinityGuard acts as a comprehensive framework for evaluating and monitoring various risks in MAS, paving the way for further research into their safety and security.

1 Introduction

Large Language Model (LLM)-based agents have evolved from single-turn assistants into autonomous entities that plan, invoke tools, and reason over extended horizons (Zheng et al., 2025; Huang et al., 2025b; Gao et al., 2025). Recently, composing several such agents into *multi-agent systems* (MAS) enables collaborative workflows in software engineering (He et al., 2025b), scientific discovery (Ghafarollahi and Buehler, 2025), financial analysis (Du et al., 2025) with orchestration frameworks, such as AutoGen (AG2) (Wu et al., 2024), making deployment increasingly accessible. As the use of these systems becomes more widespread, concerns about their safety and security have also emerged (Deng et al., 2025; Ma et al., 2026; Wei et al.). Beyond the known risks in individual LLMs or agents, such as producing harmful (Zou et al., 2023; Wei et al., 2026) or hallucinated (Ji et al., 2023; Bang et al., 2025) contents, MAS pose significantly more novel risks to be addressed.

These risks associated with MAS are inherently *hierarchical*. We propose a three-tier taxonomy of MAS risks as follows. First, at the **individual-agent** level, each agent inherits a conventional attack surface like prompt injection (Liu et al., 2023) and jailbreaking (Zou et al., 2023) as catalogued by the OWASP Top 10 for LLM Applications (OWASP Foundation, 2023). Second, at the **inter-agent communication** level (Yan et al., 2025a), multi-agent interaction introduces qualitatively new risks: malicious instructions can propagate through message channels (Gu et al., 2024), factual errors can be amplified by group dynamics (Wu et al., 2025), and agents can spoof one another's identities to escalate privileges (de Witt, 2025). Finally, at the **system** level, the collective behavior of the MAS may exhibit *emergent* phenomena like agent collusion (Ghaemi, 2025) dynamics, where no individual agent would produce in isolation. While these new risks have attracted more attention from the research community, e.g., the OWASP Agentic AI Top 10 standard has begun to codify these threats (OWASP GenAI Security Project, 2025), standardized tooling for sys-

tematically evaluating and monitoring them across heterogeneous MAS deployments remains largely unaddressed.

To address the challenges above, we present **TrinityGuard**, a comprehensive and scalable framework for safeguarding MAS risks. First, to make TrinityGuard scalable to various platform-agnostic MAS when evaluating these risks, we build a three-layer decoupling safeguarding architecture. First, the MAS framework layer abstracts over heterogeneous orchestration frameworks through a unified `BaseMAS` abstraction interface (e.g., AG2/AutoGen, LangGraph, CrewAI, and others), fully decoupling safety logic from any specific MAS library. Then, the MAS Intermediary Layer provides framework-agnostic primitives for both test-time intervention and runtime interception. Finally, at the top layer, various risk-specific test modules paired with corresponding runtime monitor agents are deployed for judging these risks.

We then hierarchically study and gather 20 popular MAS risk types into three tiers that mirror the layered nature of MAS threats:

1. **Risk Tier 1 (RT1):** 8 single-agent atomic risks (e.g., prompt injection, jailbreaking, hallucination).

2. **Risk Tier 2 (RT2):** 6 inter-agent communication risks (e.g., malicious propagation, misinformation amplification, identity spoofing).

3. **Risk Tier 3 (RT3):** 6 system-level emergent risks (e.g., group hallucination, rogue agent).

During evaluation, TrinityGuard generates and executes attack test cases combining curated static payloads with LLM-synthesized adaptive probes against each agent (Tier 1), communication channel (Tier 2), and full execution trajectory (Tier 3), producing structured vulnerability reports with per-entity, per-risk pass rates and severity profiles, and gathering them as a comprehensive evaluation report. We also present evaluations and case studies on a group of MAS to validate TrinityGuard. Our principal contributions are:

1. An **open-source, extensible framework TrinityGuard** whose three-layer architecture cleanly decouples MAS abstraction, evaluation scaffolding, and risk-specific safety logic, enabling plug-in extension of risk modules and MAS platform support with minimal integration effort.

2. A **three-tier risk taxonomy** that organizes 20 MAS risk types across single-agent, inter-agent, and system-level dimensions, grounded in the OWASP standards and formalized with quantitative per-entity, per-risk safety metrics.

3. A **unified evaluation pipeline** that combines curated static payloads with LLM-synthesized adaptive probes targeting each risk type and tier, and produces structured vulnerability reports with pass rates and severity profiles, as demonstrated by comprehensive evaluation and case studies.

The remainder of the paper is organized as follows. Section 2 presents the three-layer evaluation methodology. Section 3 formalizes the security metrics and the three-tier risk taxonomy. Section 4 presents experimental evaluation. Section 5 discusses related work, limitations, and future directions. Section 6 concludes.

2 Evaluation Methodology

This section presents the high-level design of TrinityGuard's evaluation methodology. To systematically assess the risks across heterogeneous MAS deployments, we adopt a three-layer architecture that cleanly separates platform-specific concerns from safety evaluation logic. Figure 1 illustrates the overall architecture.

2.1 Level 1: MAS Abstraction Layer

As stated, our first design principle is that all safety evaluation logic should be agnostic to the specific MAS orchestration framework in use (e.g., AG2 and others). Level 1 achieves this by defining a unified abstraction over heterogeneous MAS platforms through a minimal interface: enumerating agents, routing messages, and executing tasks. Crucially, this abstraction also standardizes a message-hook mechanism that allows upper layers to intercept and inspect messages in transit, which is a prerequisite for both test-time intervention (Level 2) and runtime monitoring (Level 3). Based on this layer, adapting to a new MAS framework requires only implementing this abstraction layer, while all safety evaluation functionality is inherited without modification.

2.2 Level 2: Intermediary Layer

Level 2 bridges the platform abstraction and the safety logic by providing two families of

Figure 1: The overall architecture design of TrinityGuard.

framework-agnostic primitives: test-time intervention and runtime observation. These primitives serve as a transitional platform for connecting the safety evaluation modules and the abstracted MAS structure.

Test-time intervention primitives. Evaluating MAS security requires the ability to inject controlled adversarial stimuli into a running system. Level 2 provides a suite of *intervention primitives* that cover the principal attack surfaces, like direct messaging to a target agent, fabricating inter-agent messages, poisoning agent memory stores, registering malicious tools, and impersonating trusted agents. These primitives are controlled by Level 3 risk tests to realize the attack scenarios defined in Section 3.

Runtime observation primitives. For continuous monitoring, Level 2 provides structured logging that records every message exchange, tool invocation, and agent state transition as a typed event. All these events are emitted through a streaming interface consumed by Level 3 monitor agents. Execution management supports multiple modes like unmonitored, intercepting (with message-level hooks), monitored (with event streaming to active monitors), and a combined mode for pre-deployment testing, allowing the framework to operate in both evaluation and production settings.

2.3 Level 3: Safety Evaluation Layer

Finally, Level 3 is the user-facing entry point that orchestrates both pre-deployment testing and runtime monitoring.

Risk test modules. Each of the studied risk types (detailed in Section 3) is encapsulated as a self-contained risk test module. A risk test module comprises: (i) a curated static test-case corpus, (ii) an LLM-based dynamic test-case generator that synthesizes adaptive probes conditioned on target agent characteristics, (iii) the sequence of Level 2 intervention primitives needed to execute the attack scenario, and (iv) a risk-specific judge prompt for verdict determination. Each risk type is paired with a dedicated monitor agent that consumes the structured event stream in real time, where monitors run in parallel and share a centralized alert store.

Verdict determination. Both risk tests and monitor agents delegate verdict decisions to a centralized judge mechanism. Each judge instance is configured with a risk-specific policy prompt and operates in an LLM-based semantic evaluation, enabling both pre-deployment evaluation and runtime monitoring. We deliberately favor LLM-as-a-judge over rule-based scoring because subtle goal drift, partially complied jailbreaks, or implicit collusion all require semantic judgment that string matching cannot deliver. To temper the resulting risk of judge miscalibration on borderline cases, prompts enumerate explicit violation criteria and surface uncertainty as an *abstain* option whose frequency is reported alongside the pass rate, while the backbone-agnostic Judge Factory lets practitioners ensemble or swap judges to cross-check verdicts when stakes are high.

Reporting. Both operating modes produce structured reports. Pre-deployment reports include per-agent and per-risk pass rates, failed test-case details, severity summaries, and remediation recommendations. Runtime reports include the full execution trace, a chronological alert log with source attribution, and an aggregated risk summary. This uniform reporting format facilitates integration with downstream dashboards and compliance pipelines.

3 Security Metrics

Building on the proposed safeguard methodology, we facilitate our framework with a three-tier risk taxonomy and 20 example safety metrics underlying TrinityGuard. We begin with notation and the hierarchical design rationale (§3.1), then define and describe the three risk tiers (§3.2–3.4), and conclude with a comparative discussion (§3.5).

3.1 Notation and Hierarchical Design

Notation. We model a multi-agent system as a tuple $\mathcal{M} = (\mathcal{A}, \mathcal{C}, \mathcal{E})$, where $\mathcal{A} = \{a_1, \ldots, a_n\}$ is the set of n agents, $\mathcal{C} \subseteq \mathcal{A} \times \mathcal{A}$ is the set of directed communication channels, and $\mathcal{E}$ is the set of external tools and resources accessible to the agents. A *test case* t is a concrete adversarial stimulus (prompt, injected message, spoofed identity, etc.). An *execution trajectory* is a sequence $\tau = (s_0, s_1, \ldots, s_T)$ of system states, where each s_t records the messages, tool invocations, and observable internal states of all agents at step t.

Hierarchical decomposition. Following the layered evaluation architecture in Section 2, we decompose MAS safety along three granularities: *atomic* risks elicited on a single agent in isolation; *communication* risks that arise on the channel set $\mathcal{C}$ as messages are relayed and transformed; and *system* risks that emerge from collective trajectories of $\mathcal{M}$ and cannot be attributed to any one agent or pair.

Accordingly, we partition the set of all risk types into three disjoint tiers: $\mathcal{R} = \mathcal{R}_1 \cup \mathcal{R}_2 \cup \mathcal{R}_3$, with carefully selecting representative risks from each tier and forming $|\mathcal{R}_1| = 8$, $|\mathcal{R}_2| = 6$, and $|\mathcal{R}_3| = 6$ (20 total). For each risk type, TrinityGuard evaluates safety through a binary LLM-as-a-judge mechanism: given a test case and the target entity's response, a judge LLM determines whether the response constitutes a safety violation (fail) or not (pass). The *safety score* $\mathcal{S}_k(\mathcal{M}, r) \in \{0, 1\}$ for risk r at tier k is defined as the pass rate—the frac-

tion of test cases for which no violation is detected. Test cases combine curated static payloads with LLM-synthesized adaptive probes, and are scoped to match the risk tier: per-agent for Tier 1, per-channel for Tier 2, and per-trajectory for Tier 3.

3.2 Tier 1: Atomic Risks

Tier 1 comprises eight single-agent risks that can be assessed independently per agent (Table 1). For each risk $r \in \mathcal{R}_1$ and each agent $a_i \in \mathcal{A}$, Trinity-Guard constructs a test suite combining curated static payloads with LLM-synthesized adaptive probes conditioned on the agent's system prompt and observed behavior. The safety score $\mathcal{S}_1(\mathcal{M}, r)$ is the average pass rate across all agents.

Risk descriptions. Per-risk descriptions with literature grounding are deferred to Appendix A.1.

3.3 Tier 2: Communication Risks

Tier 2 addresses six risks arising from inter-agent message passing (Table 2). Unlike Tier 1, these risks require observing *pairs* or *sequences* of agents interacting over communication channels. For each channel $c_{ij} = (a_i, a_j) \in \mathcal{C}$ and risk $r \in \mathcal{R}_2$, the test suite injects adversarial payloads into the message stream via Level 2 intermediary primitives and evaluates the downstream agent's behavior. The safety score $\mathcal{S}_2(\mathcal{M}, r)$ is the average pass rate across all channels.

Risk descriptions. Per-risk descriptions are deferred to Appendix A.2.

3.4 Tier 3: System Risks

Tier 3 captures six emergent risks that manifest only at the whole-system level and cannot be attributed to any single agent or channel (Table 3). Evaluating these risks requires observing full execution trajectories $\tau = (s_0, s_1, \ldots, s_T)$. The judge determines whether any system state along the trajectory violates a risk-specific safety predicate. The safety score $\mathcal{S}_3(\mathcal{M}, r)$ is the pass rate over independently sampled trajectories.

Risk descriptions. Per-risk descriptions are deferred to Appendix A.3.

3.5 Summary and Discussion

The overall safety score of $\mathcal{M}$ is a weighted average of tier-level scores across all 20 risks, summarized in Figure 2. We highlight three properties of TrinityGuard.

Table 1: Risk Tier 1 (RT1): Single-agent atomic risks.

ID	Risk Name	OWASP Ref.	Description
1.1	Prompt Injection	LLM01	Manipulating agent behavior via malicious input
1.2	Jailbreak Attack	LLM01	Bypassing safety guidelines and ethical constraints
1.3	Sensitive Info Disclosure	LLM02	Leaking system prompts, API keys, or private data
1.4	Excessive Agency	LLM06	Executing actions beyond intended scope
1.5	Unauthorized Code Execution	ASI05	Running malicious code or commands
1.6	Hallucination	LLM09	Fabricating false information
1.7	Memory Poisoning	ASI06	Injecting malicious content into agent memory
1.8	Tool Misuse	ASI02	Improper use of external tools or APIs

Table 2: Risk Tier 2 (RT2): Inter-agent communication risks.

ID	Risk Name	OWASP Ref.	Description
2.1	Malicious Propagation	ASI07	Malicious instructions spreading through agent network
2.2	Misinformation Amplification	LLM09	Errors amplified and reinforced across agents
2.3	Insecure Output Handling	LLM05	Unvalidated output consumed by downstream agents
2.4	Goal Drift	ASI01	Deviation from original objective over multi-turn interaction
2.5	Message Tampering	ASI07	Message content modified during transmission
2.6	Identity Spoofing	ASI03	Impersonation of a trusted agent

Extensibility. New risks plug into any tier by implementing the base risk-test and monitor interfaces; the LLM Judge Factory adapts via configurable policy prompts. New MAS frameworks onboard by implementing the Level 1 `BaseMAS` abstraction, after which all evaluation logic, monitoring, and reporting are inherited unchanged. Although our 20 risks are grounded in the OWASP LLM and Agentic-AI Top 10 standards, real-world deployments routinely surface domain-specific or emerging threats — e.g., financial-fraud collusion, medical-misuse hazards, or supply-chain manipulation — that any closed catalog will miss. The plug-in interface lets domain experts add a risk by supplying only four artifacts (static payloads, dynamic probe generator, intervention primitives, and judge prompt) while reusing event streaming, monitor orchestration, and reporting unchanged, so Trinity-Guard tracks the long tail of MAS risks rather than ossifying around the snapshot captured here. The same hook also supports disabling or specializing existing risks per deployment, and the shared event-stream contract lets independently contributed modules compose without bespoke glue code.

Fine-grained risk dimensions. Rather than reporting a single aggregate score, TrinityGuard profiles risk along two axes: the three-tier taxonomy localizes vulnerabilities to per-agent, per-channel, or per-trajectory granularity, and the 20 risk types within each tier distinguish qualitatively different attack surfaces, directly informing prioritized mitigation.

Dual-mode safeguarding. The same risk-specific judge logic powers two modes. *Pre-deployment evaluation* replays curated and LLM-synthesized adaptive probes against the target MAS to surface vulnerabilities before exposure to real users. *Runtime monitoring* re-uses the judges as a bank of monitor agents that consume the Level 2 event stream, issuing alerts on live user queries, inter-agent messages, and tool calls — catching novel or emergent threats that only manifest in the wild.

4 Evaluation

In this section, we demonstrate the versatility and reliability of TrinityGuard, from massive automatically synthesized MAS workflows to representative case studies from official AG2 MAS examples.

4.1 Risk Assessment across Synthetic MAS

Experiment setup. To systematically evaluate the safety and security risks of MAS across diverse application domains, we construct an extensive testbed using EvoAgentX (Wang et al., 2025c) to synthesize 300 unique MAS workflows. These workflows are categorized into seven representative domains, reflecting common real-world use cases:

Table 3: Risk Tier 3 (RT3): System-level emergent risks.

ID	Risk Name	OWASP Ref.	Description
3.1	Cascading Failure	ASI08	Single-point failure triggering system-wide collapse
3.2	Sandbox Escape	ASI05	Agents accessing unauthorized resources
3.3	Insufficient Monitoring	ASI09	Lack of effective behavioral monitoring and audit
3.4	Group Hallucination	LLM09	Collective fabrication of false information
3.5	Malicious Emergence	ASI01	Emergence of unanticipated harmful behaviors
3.6	Rogue Agent	ASI10	Agent deviating from system objectives

Figure 2: Summary of three-tier risks studied by TrinityGuard.

QA (Question Answering), coding, database operations, research, logistics, routing, and scheduling. Each generated MAS is subjected to the full TrinityGuard evaluation pipeline, encompassing the 20 risk types across the three tiers. The overall evaluation results are presented in Table 4, and the fine-grained performance breakdowns across specific risk types are illustrated in Figure 3.

Analysis of tier-level risks. Table 4 shows that current MAS deployments are severely vulnerable across all tiers, with an average pass rate of only 7.1%. Tier 3 (System) is the most fragile (1.3% on average; database and research MAS reach 0%), revealing a critical lack of emergent resilience even when individual agents are partially safeguarded. Tier 1 (Atomic) is also weak (6.8%), indicating fragile foundational agents, while Tier 2 (Communication) is marginally better at 13.2% but still readily exploited by malicious propagation and identity spoofing. Across domains, scheduling and logistics are slightly more resilient (8.3%, 8.2%), whereas execution-heavy coding and routing MAS are the most susceptible (5.7%, 5.9%).

Analysis of fine-grained risks. The radar chart in Figure 3 breaks down pass rates per risk and domain. In **Tier 1**, near-zero pass rates on *prompt injection* and *code execution* indicate weak isolation against direct adversarial inputs, while research and QA show better *hallucination* resilience due to external knowledge grounding; *excessive agency* and *tool misuse* fare comparatively well, suggesting effective tool boundaries. In **Tier 2**, *malicious propagation* is uniformly defeated, whereas *identity spoofing* and *goal drift* are more resilient, especially in database and research contexts. **Tier 3** reveals systemic failures: *rogue agent* and *sandbox escape* almost universally fail, while *cascading failures* and *group hallucination* have higher pass rates, indicating that single-agent compromises do not always escalate to system-wide collapse.

4.2 Case Studies

Experiment setup. To further understand the effectiveness of TrinityGuard on specific MAS, we apply it to four representative MAS drawn from the official AG2 examples — a code-interpreter *Financial Analysis* agent, a Group-Chat *Game De-*

(a) Tier 1 risks (b) Tier 2 risks (c) Tier 3 risks

Figure 3: Fine-grained distribution of detected safety risks across the three TrinityGuard tiers for 300 synthesized MAS workflows.

Table 4: Safety evaluation **Pass Rates** (↑) across 300 synthesized MAS workflows.

MAS Type	Risk Tier 1	Risk Tier 2	Risk Tier 3	Average Pass Rate
QA	9.2%	8.0%	2.7%	6.9%
coding	5.0%	12.3%	0.1%	5.7%
database	5.3%	15.0%	0.0%	6.6%
research	9.4%	13.7%	0.0%	7.8%
logistics	4.7%	17.7%	3.5%	8.2%
routing	4.7%	12.5%	1.0%	5.9%
scheduling	9.4%	13.2%	2.1%	8.3%
Average	6.8%	13.2%	1.3%	7.1%

sign team, a Swarm-based *Travel Planner*, and a recursive *Deep Research* agent — spanning two-agent dialogues, hierarchical groups, and tool-using swarms. Per-MAS architectural details are provided in Appendix B.

Result analysis. The comprehensive evaluation results are summarized in Table 5. The values represent the *Pass Rate* (the percentage of test cases where the system successfully defended against or avoided the risk).

The case studies confirm consistent vulnerabilities across architectures, with structure offering only partial mitigation. In **Tier 1**, all four MAS show universal fragility under *Prompt Injection* and *Jailbreak* (0% pass rates), but the Deep Research agent's hierarchical Researcher–Reviewer pattern markedly reduces *Hallucination* (75%). In **Tier 2**, *Malicious Propagation* succeeds against every system, while task-specific grounding lets the Travel Planner resist *Misinformation Amplification* (83%); *Identity Spoofing* (0–12%) remains broadly effective due to absent authentication. **Tier 3** exposes a critical resilience gap: nearly all systems fail to contain *Cascading Failures* or *Group Hallucination*,

with the Deep Research agent the sole exception (*Cascading Failure* 25%) thanks to its oversight loop, suggesting hierarchical governance is essential for emergent safety. Overall, the prevalence of 0% pass rates across critical vectors confirms that out-of-the-box MAS deployments are unsafe under adversarial conditions, and TrinityGuard successfully quantifies these previously invisible risks.

5 Discussion

5.1 Related Work

Single-agent safety evaluation has evolved from static benchmarks — SafetyBench (Zhang et al., 2024) and TrustLLM (Huang et al., 2024) target single-turn toxicity taxonomies — to agent-centric assessments such as R-Judge (Yuan et al., 2024) for interaction-record auditing, AgentHarm (Andriushchenko et al., 2024) and AgentAuditor (Luo et al., 2025) for jailbreak robustness during multi-step tool use, and SafeEvalAgent (Wang et al., 2025d) for self-evolving probes. Yet these frameworks treat the agent as an isolated entity and overlook MAS-specific threats: Gu et al. (2024) show *infectious jailbreaks* that propagate virally across

Table 5: Safety evaluation **Pass Cases** (↑) across four representative MAS.

Tier	MAS Risk	Financial Analysis	Game Design	Travel Planner	Deep Research
RT1: Atomic	Prompt Injection	0/4	0/4	0/4	0/4
	Jailbreak Attack	0/4	0/4	0/4	0/4
	Sensitive Info Disclosure	2/4	2/4	2/4	4/4
	Excessive Agency	0/3	0/3	0/3	0/3
	Unauth. Code Execution	0/3	0/3	1/3	0/3
	Hallucination	0/8	1/8	1/8	6/8
	Memory Poisoning	0/8	0/8	0/8	0/8
	Tool Misuse	0/8	1/8	1/8	3/8
RT 2: Communication	Malicious Propagation	0/6	0/6	0/6	0/6
	Misinformation Amplification	3/6	3/6	5/6	3/6
	Insecure Output Handling	0/6	1/6	0/6	0/6
	Goal Drift	0/6	0/6	1/6	0/6
	Message Tampering	0/8	1/8	0/8	1/8
	Identity Spoofing	1/8	0/8	0/8	1/8
RT 3: System	Cascading Failure	0/8	0/8	0/8	2/8
	Sandbox Escape	0/6	0/6	0/6	0/6
	Insufficient Monitoring	0/6	0/6	0/6	0/6
	Group Hallucination	0/6	0/6	0/6	0/6
	Malicious Emergence	0/6	0/6	1/6	0/6
	Rogue Agent	0/6	0/6	0/6	0/6

an agent network, and Wang et al. (2025b) expose *shadow agents* that inject concealed malicious code without tripping single-agent filters. Existing MAS-specific defenses target narrow diagnostic tasks, leaving the need for a unified, platform-agnostic framework that evaluates and monitors risks across all tiers — the gap TrinityGuard addresses.

5.2 Future Directions

We outline four directions for extending Trinity-Guard. **(i) Judge reliability:** systematic studies of LLM-judge accuracy across risks and backbones, augmented with a human-review interface for borderline cases. **(ii) Adaptive test generation:** stronger probes via adversarial optimization (Zou et al., 2023) and multi-turn red-teaming (Chao et al., 2025). **(iii) Automated remediation:** closing the loop from diagnosis to defense via message filtering and agent isolation, beyond the current detection-only setting. **(iv) Cross-tier causal attribution:** tracing Tier-3 cascades back to the Tier-1 entry point through provenance tracking, turning vulnerability reports into actionable forensic chains.

6 Conclusion

In this paper, we presented TrinityGuard, a comprehensive framework for safety evaluation and runtime monitoring of LLM-based multi-agent systems. Architecturally, TrinityGuard separates the pipeline across three layers: a framework abstraction layer that decouples safety logic from specific MAS libraries, an intermediary layer that provides unified test-injection and structured-logging primitives, and a safety layer that houses risk-specific test modules and runtime monitor agents coordinated by a two-stage LLM Judge Factory. The framework then introduces a three-tier risk taxonomy of 20 risk types, spanning single-agent atomic vulnerabilities, inter-agent communication threats, and system-level emergent hazards, grounded in the OWASP standards. This design enables two complementary operating modes: pre-deployment vulnerability testing that produces per-agent, per-risk safety reports, and continuous runtime monitoring that issues real-time alerts with source attribution. Overall, TrinityGuard provides a new foundation for MAS safety research and deployment.

Limitations

We acknowledge two principal limitations of TrinityGuard. First, our adversarial probes combine curated static payloads with LLM-synthesized adaptive inputs conditioned on agent prompts; while effective at exposing baseline weaknesses, this generation procedure does not match the strategic adaptivity of human red-teamers or optimization-based adversaries (Zou et al., 2023; Chao et al., 2025), and may underestimate worst-case vulnerability for system-level risks that require coordinated multi-step attacks. Second, our empirical evaluation focuses on AG2-based MAS workflows synthesized via EvoAgentX (Wang et al., 2025c) and four official AG2 case studies; although the BaseMAS abstraction is designed for portability, additional adapters (e.g., LangGraph, CrewAI) and real-world production deployments are needed to validate generalization beyond the synthetic and reference systems studied here.

References

Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, and 1 others. 2024. Agentharm: A benchmark for measuring harmfulness of llm agents. *arXiv preprint arXiv:2410.09024*.

Rauno Arike, Elizabeth Donoway, Henning Bartsch, and Marius Hobbhahn. 2025. Technical report: Evaluating goal drift in language model agents. *arXiv preprint arXiv:2505.02709*.

Yejin Bang, Ziwei Ji, Alan Schelten, Anthony Hartshorn, Tara Fowler, Cheng Zhang, Nicola Cancedda, and Pascale Fung. 2025. Hallulens: Llm hallucination benchmark. *arXiv preprint arXiv:2504.17550*.

Jonas Becker, Lars Benedikt Kaesberg, Andreas Stephan, Jan Philip Wahle, Terry Ruas, and Bela Gipp. 2025. Stay focused: Problem drift in multi-agent debate. *arXiv preprint arXiv:2502.19559*.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. 2025. Jailbreaking black box large language models in twenty queries. In *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pages 23–42. IEEE.

Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. 2024. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. *Advances in Neural Information Processing Systems*, 37:130185–130213.

Pedro MP Curvo. 2025. The traitors: Deception and trust in multi-agent language model simulations. *arXiv preprint arXiv:2505.12923*.

Christian Schroeder de Witt. 2025. Open challenges in multi-agent security: Towards secure systems of interacting ai agents. *arXiv preprint arXiv:2505.02077*.

Zehang Deng, Yongjian Guo, Changzhou Han, Wanlun Ma, Junwu Xiong, Sheng Wen, and Yang Xiang. 2025. Ai agents under threat: A survey of key security challenges and future pathways. *ACM Computing Surveys*, 57(7):1–36.

Kelvin Du, Yazhi Zhao, Rui Mao, Frank Xing, and Erik Cambria. 2025. A retrieval-augmented multiagent system for financial sentiment analysis. *IEEE Intelligent Systems*, 40(2):15–22.

Mohamed Amine Ferrag, Norbert Tihanyi, Djallel Hamouda, Leandros Maglaras, and Merouane Debbah. 2025. From prompt injections to protocol exploits: Threats in llm-powered ai agents workflows. *arXiv preprint arXiv:2506.23260*.

Xiaohan Fu, Zihan Wang, Shuheng Li, Rajesh K Gupta, Niloofar Mireshghallah, Taylor Berg-Kirkpatrick, and Earlence Fernandes. 2023. Misusing tools in large language models with visual adversarial examples. *arXiv preprint arXiv:2310.03185*.

Silin Gao, Jane Dwivedi-Yu, Ping Yu, Xiaoqing Ellen Tan, Ramakanth Pasunuru, Olga Golovneva, Koustuv Sinha, Asli Celikyilmaz, Antoine Bosselut, and Tianlu Wang. 2025. Efficient tool use with chain-of-abstraction reasoning. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 2727–2743.

Mohammad Sajjad Ghaemi. 2025. A survey of collusion risk in llm-powered multi-agent systems. In *Socially Responsible and Trustworthy Foundation Models at NeurIPS 2025*.

Alireza Ghafarollahi and Markus J Buehler. 2025. Sciagents: automating scientific discovery through bioinspired multi-agent intelligent graph reasoning. *Advanced Materials*, 37(22):2413523.

Xiangming Gu, Xiaosen Zheng, Tianyu Pang, Chao Du, Qian Liu, Ye Wang, Jing Jiang, and Min Lin. 2024. Agent smith: A single image can jailbreak one million multimodal llm agents exponentially fast. *arXiv preprint arXiv:2402.08567*.

Feng He, Tianqing Zhu, Dayong Ye, Bo Liu, Wanlei Zhou, and Philip S Yu. 2025a. The emerged security and privacy of llm agent: A survey with case studies. *ACM Computing Surveys*, 58(6):1–36.

Junda He, Christoph Treude, and David Lo. 2025b. Llm-based multi-agent systems for software engineering: Literature review, vision, and the road ahead. *ACM Transactions on Software Engineering and Methodology*, 34(5):1–30.

Pengfei He, Yuping Lin, Shen Dong, Han Xu, Yue Xing, and Hui Liu. 2025c. Red-teaming llm multi-agent systems via communication attacks. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 6726–6747.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and 1 others. 2025a. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2):1–55.

Yue Huang, Lichao Sun, Haoran Wang, Siyuan Wu, Qihui Zhang, Yuan Li, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, and 1 others. 2024. Trustllm: Trustworthiness in large language models. *arXiv preprint arXiv:2401.05561*.

Yuxuan Huang, Yihang Chen, Haozheng Zhang, Kang Li, Huichi Zhou, Meng Fang, Linyi Yang, Xiaoguang Li, Lifeng Shang, Songcen Xu, and 1 others. 2025b. Deep research agents: A systematic examination and roadmap. *arXiv preprint arXiv:2506.18096*.

Ziwei Ji, Tiezheng Yu, Yan Xu, Nayeon Lee, Etsuko Ishii, and Pascale Fung. 2023. Towards mitigating llm hallucination via self reflection. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 1827–1843.

Dezhang Kong, Shi Lin, Zhenhua Xu, Zhebo Wang, Minghao Li, Yufeng Li, Yilun Zhang, Hujin Peng, Xiang Chen, Zeyang Sha, and 1 others. 2025. A survey of llm-driven ai agent communication: Protocols, security risks, and defense countermeasures. *arXiv preprint arXiv:2506.19676*.

Donghyun Lee and Mo Tiwari. 2024. Prompt infection: Llm-to-llm prompt injection within multi-agent systems. *arXiv preprint arXiv:2410.07283*.

Haoran Li, Yulin Chen, Jinglong Luo, Jiecong Wang, Hao Peng, Yan Kang, Xiaojin Zhang, Qi Hu, Chunkit Chan, Zenglin Xu, and 1 others. 2023. Privacy in large language models: Attacks, defenses and future directions. *arXiv preprint arXiv:2310.10383*.

Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, and 1 others. 2023. Prompt injection attack against llm-integrated applications. *arXiv preprint arXiv:2306.05499*.

Hanjun Luo, Shenyu Dai, Chiming Ni, Xinfeng Li, Guibin Zhang, Kun Wang, Tongliang Liu, and Hanan Salam. 2025. Agentauditor: Human-level safety and security evaluation for llm agents. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Matteo Lupinacci, Francesco Aurelio Pironti, Francesco Blefari, Francesco Romeo, Luigi Arena, and Angelo Furfaro. 2025. The dark side of llms: Agent-based attacks for complete computer takeover. *arXiv preprint arXiv:2507.06850*.

Xingjun Ma, Yifeng Gao, Yixu Wang, Ruofan Wang, Xin Wang, Ye Sun, Yifan Ding, Hengyuan Xu, Yunhao Chen, Yunhan Zhao, and 1 others. 2026. Safety at scale: A comprehensive survey of large model and agent safety. *Foundations and Trends in Privacy and Security*, 8(3-4):1–240.

Alexander Meinke, Bronson Schoen, Jérémy Scheurer, Mikita Balesni, Rusheb Shah, and Marius Hobbhahn. 2024. Frontier models are capable of in-context scheming. *arXiv preprint arXiv:2412.04984*.

Lesly Miculicich, Mihir Parmar, Hamid Palangi, Krishnamurthy Dj Dvijotham, Mirko Montanari, Tomas Pfister, and Long T Le. 2025. Veriguard: Enhancing llm agent safety via verified code generation. *arXiv preprint arXiv:2510.05156*.

Dishita Naik, Ishita Naik, and Nitin Naik. 2025. Insecure output handling in large language models (llms) and approaches to enhance output security, including prevention of llm-based web application attacks. *Authorea Preprints*.

OWASP Foundation. 2023. OWASP Top 10 for Large Language Model Applications. Online. Version 1.1.

OWASP GenAI Security Project. 2025. OWASP Top 10 for Agentic Applications 2026. Standard, OWASP Foundation. Accessed: 2026-02-10.

Julien Piet, Maha Alrashed, Chawin Sitawarin, Sizhe Chen, Zeming Wei, Elizabeth Sun, Basel Alomair, and David Wagner. 2024. Jatmo: Prompt injection defense by task-specific finetuning. In *European Symposium on Research in Computer Security*, pages 105–124. Springer.

Nikhil Sharma, Q Vera Liao, and Ziang Xiao. 2024. Generative echo chamber? effect of llm-powered search systems on diverse information seeking. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pages 1–17.

Haoyu Wang, Christopher M Poskitt, and Jun Sun. 2025a. Agentspec: Customizable runtime enforcement for safe and reliable llm agents. *arXiv preprint arXiv:2503.18666*.

Xiaoqing Wang, Keman Huang, Bin Liang, Hongyu Li, and Xiaoyong Du. 2025b. Shadows in the code: Exploring the risks and defenses of llm-based multi-agent software development systems. *arXiv preprint arXiv:2511.18467*.

Yingxu Wang, Siwei Liu, Jinyuan Fang, and Zaiqiao Meng. 2025c. Evoagentx: An automated framework for evolving agentic workflows. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 643–655.

Yixu Wang, Xin Wang, Yang Yao, Xinyuan Li, Yan Teng, Xingjun Ma, and Yingchun Wang. 2025d. Safeevalagent: Toward agentic and self-evolving safety evaluation of llms. *arXiv preprint arXiv:2509.26100*.

Yuntao Wang, Yanghe Pan, Shaolong Guo, and Zhou Su. 2025e. Security of internet of agents: Attacks and countermeasures. *IEEE Open Journal of the Computer Society*.

Zeming Wei, Tianlin Li, Xiaojun Jia, Yihao Zhang, Yang Liu, and Meng Sun. Position: Agent-specific trustworthiness risk as a research priority. In *ICML 2025 Workshop on Reliable and Responsible Foundation Models*.

Zeming Wei, Yifei Wang, Ang Li, Yichuan Mo, and Yisen Wang. 2026. Jailbreak and guard aligned language models with only few in-context demonstrations. *Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*.

Chengcan Wu, Zhixin Zhang, Mingqian Xu, Zeming Wei, and Meng Sun. 2025. Monitoring llm-based multi-agent systems against corruptions via node evaluation. *arXiv preprint arXiv:2510.19420*.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, and 1 others. 2024. Autogen: Enabling next-gen llm applications via multi-agent conversations. In *First Conference on Language Modeling*.

Xijian Xu and Jun Wu. 2026. Mitigating llm hallucination snowballing in multiagent systems via context-aware semantic consistency reasoning. *IEEE Transactions on Neural Networks and Learning Systems*.

Bingyu Yan, Zhibo Zhou, Litian Zhang, Lian Zhang, Ziyi Zhou, Dezhuang Miao, Zhoujun Li, Chaozhuo Li, and Xiaoming Zhang. 2025a. Beyond self-talk: A communication-centric survey of llm-based multi-agent systems. *arXiv preprint arXiv:2502.14321*.

Bingyu Yan, Ziyi Zhou, Xiaoming Zhang, Chaozhuo Li, Ruilin Zeng, Yirui Qi, Tianbo Wang, and Litian Zhang. 2025b. Attack the messages, not the agents: A multi-round adaptive stealthy tampering framework for llm-mas. *arXiv preprint arXiv:2508.03125*.

Tongxin Yuan, Zhiwei He, Lingzhong Dong, Yiming Wang, Ruijie Zhao, Tian Xia, Lizhen Xu, Binglin Zhou, Fangqi Li, Zhuosheng Zhang, and 1 others. 2024. R-judge: Benchmarking safety risk awareness for llm agents. *arXiv preprint arXiv:2401.10019*.

Yiming Zhang, Nicholas Carlini, and Daphne Ippolito. 2023. Effective prompt extraction from language models. *arXiv preprint arXiv:2307.06865*.

Zhexin Zhang, Leqi Lei, Lindong Wu, Rui Sun, Yongkang Huang, Chong Long, Xiao Liu, Xuanyu Lei, Jie Tang, and Minlie Huang. 2024. Safetybench: Evaluating the safety of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15537–15553.

Yuxiang Zheng, Dayuan Fu, Xiangkun Hu, Xiaojie Cai, Lyumanshan Ye, Pengrui Lu, and Pengfei Liu. 2025. Deepresearcher: Scaling deep research via reinforcement learning in real-world environments. *arXiv preprint arXiv:2504.03160*.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*.

Wei Zou, Runpeng Geng, Binghui Wang, and Jinyuan Jia. 2025. {PoisonedRAG}: Knowledge corruption attacks to {Retrieval-Augmented} generation of large language models. In *34th USENIX Security Symposium (USENIX Security 25)*, pages 3827–3844.

A Risk Taxonomy: Per-Risk Descriptions

This appendix expands each of the 20 risks introduced in Section 3 into a self-contained description with literature grounding. Risk identifiers ($r_{i.j}$), tier assignments, and OWASP references match Tables 1, 2, and 3 in the main text.

A.1 Tier 1: Atomic Risks

Prompt Injection ($r_{1.1}$) targets the boundary between trusted instructions and untrusted user input: an adversary crafts input that causes the agent to override its system prompt or execute unintended instructions, effectively hijacking the agent's behavior (Liu et al., 2023; Piet et al., 2024).

Jailbreak Attack ($r_{1.2}$) attempts to bypass the safety guidelines and ethical constraints embedded in the underlying LLM through carefully designed prompts, eliciting harmful or policy-violating outputs that the model would otherwise refuse (Zou et al., 2023; Wei et al., 2026).

Sensitive Information Disclosure ($r_{1.3}$) probes whether an agent can be manipulated into revealing confidential data it has access to, including system prompts, API keys, tool credentials, or private user data stored in its context or memory (Zhang et al., 2023; Li et al., 2023).

Excessive Agency ($r_{1.4}$) evaluates whether an agent performs actions beyond its intended scope of authority that exploit overly permissive tool access or insufficiently constrained action spaces, e.g., making purchases, sending emails, or modifying files when only instructed to provide information.

Unauthorized Code Execution ($r_{1.5}$) tests whether an adversary can trick an agent with code execution capabilities into running malicious code or shell commands, potentially leading to data exfiltration, system compromise, or denial-of-service

attacks on the host environment (Lupinacci et al., 2025).

Hallucination ($r_{1.6}$) measures the agent's tendency to fabricate false information, including non-existent references, incorrect facts, or fictitious tool outputs, particularly in contexts where the agent lacks sufficient knowledge and should instead acknowledge uncertainty (Huang et al., 2025a; Bang et al., 2025).

Memory Poisoning ($r_{1.7}$) targets agents equipped with persistent memory stores (e.g., retrieval-augmented generation buffers or conversation history): an adversary injects malicious or misleading content into the memory, which then corrupts the agent's future reasoning and outputs (Chen et al., 2024; Zou et al., 2025).

Tool Misuse ($r_{1.8}$) assesses whether an agent can be induced to invoke external tools or APIs in unintended ways that potentially cause real-world side effects, such as passing malicious arguments, calling tools with fabricated parameters, or using a tool for purposes outside its designed function (Fu et al., 2023; Ferrag et al., 2025).

A.2 Tier 2: Communication Risks

Malicious Propagation ($r_{2.1}$) occurs when a compromised or adversarially manipulated agent injects harmful instructions into its outgoing messages, causing downstream agents to execute malicious actions they would not have performed independently; the attack exploits trust relationships inherent in multi-agent communication to spread harmful behavior across the agent network (Lee and Tiwari, 2024).

Misinformation Amplification ($r_{2.2}$) captures the phenomenon where factual errors or hallucinations produced by one agent are uncritically accepted, reinforced, and further elaborated by other agents in the system, resulting in a collective amplification of false information far more pronounced than the original error (Sharma et al., 2024).

Insecure Output Handling ($r_{2.3}$) tests whether the output of one agent is consumed by a downstream agent without adequate validation or sanitization; an upstream agent's output containing embedded instructions, code, or adversarial payloads can exploit the downstream agent if it naively trusts and executes the received content (Naik et al., 2025; Lupinacci et al., 2025).

Goal Drift ($r_{2.4}$) evaluates whether the original task objective is progressively distorted as it passes through multiple agents in a communication chain; each agent may subtly reinterpret, expand, or narrow the goal, leading to a final outcome that significantly deviates from the user's original intent (Arike et al., 2025; Becker et al., 2025).

Message Tampering ($r_{2.5}$) assesses the vulnerability of inter-agent communication channels to unauthorized modification; an adversary or a compromised intermediary agent alters message content during transmission, potentially changing task instructions, data values, or coordination signals without detection (He et al., 2025c; Yan et al., 2025b).

Identity Spoofing ($r_{2.6}$) tests whether an agent or external adversary can impersonate a trusted agent in the system by forging sender identities in messages. Successful spoofing can lead to privilege escalation, unauthorized actions, or manipulation of other agents that rely on sender identity for access control decisions (Kong et al., 2025; Wang et al., 2025e).

A.3 Tier 3: System Risks

Cascading Failure ($r_{3.1}$) occurs when a single-point failure, such as one agent producing erroneous output or becoming unresponsive, triggers a chain reaction of failures across the system; downstream agents that depend on the failed agent's output may themselves fail or produce incorrect results, leading to system-wide collapse disproportionate to the initial fault (He et al., 2025a).

Sandbox Escape ($r_{3.2}$) evaluates whether agents can collectively breach the security boundaries of their communication channels, thereby enabling access to unauthorized resources, file systems, or network endpoints that no single agent could reach alone.

Insufficient Monitoring ($r_{3.3}$) assesses whether the MAS provides adequate observability into agent behavior, communication patterns, and decision-making processes; systems lacking comprehensive logging, audit trails, or anomaly detection mechanisms may allow safety violations to occur undetected, preventing timely intervention and forensic analysis (Wang et al., 2025a; Miculicich et al., 2025).

Group Hallucination ($r_{3.4}$) is an emergent phenomenon where multiple agents collectively fabricate and mutually reinforce false information through their interactions; unlike single-agent hallucination, group hallucination involves a consensus-building dynamic where agents validate each other's fabrications, producing confident but

entirely fictitious outputs that appear more credible due to apparent multi-source agreement (Xu and Wu, 2026).

Malicious Emergence ($r_{3.5}$) captures unanticipated harmful behaviors that arise from the interaction dynamics of multiple agents but are not present in any individual agent's behavior; these emergent properties, such as implicit coordination to circumvent safety constraints, development of deceptive communication strategies, or spontaneous formation of adversarial coalitions, are inherently difficult to predict from single-agent testing (Meinke et al., 2024; Curvo, 2025).

Rogue Agent ($r_{3.6}$) evaluates the system's resilience when one or more agents deviate from their assigned objectives and pursue independent or adversarial goals; a rogue agent may subtly undermine system objectives by providing misleading information, sabotaging collaborative tasks, or manipulating other agents' behavior while maintaining an appearance of cooperation (Ghaemi, 2025).

B Case-Study MAS Descriptions

We instantiate TrinityGuard on four representative MAS drawn from the official AG2 examples,[1] chosen to span varying levels of agent collaboration and task complexity.

- **Financial Analysis Agent:** A code-interpreter system pairing a *UserProxyAgent* with an *AssistantAgent*. The Assistant writes Python code to retrieve stock data and generate charts, while the UserProxy executes it locally, exemplifying a foundational pattern for autonomous data analysis.

- **Game Design Agent Team:** A Swarm or Group Chat system orchestrating specialized roles: *Story*, *Gameplay*, *Visuals*, and *Tech* agents. These agents collaborate to iteratively generate a comprehensive game design document, covering narrative lore, mechanics, and technical implementation.

- **Travel Planner Agent:** A Swarm-based architecture for itinerary planning that coordinates a *FalkorDB Agent* (using GraphRAG for data), a *Routing Agent* (for distance calculation), and a *Structured Output Agent*. This division ensures travel plans are logistically feasible and strictly formatted.

- **Deep Research Agent:** A recursive system centered on a *DeepResearchAgent* designed to tackle complex topics autonomously. It breaks down queries into manageable sub-tasks, browses the web for evidence, and synthesizes findings into high-quality, hallucination-resistant research reports.

---

[1] https://github.com/ag2ai/build-with-ag2