Bayesian Q-learning With Imperfect Expert Demonstrations

Abstract

Guided exploration with expert demonstrations improves data efficiency for rein-
forcement learning, but current algorithms often overuse expert information. We
propose a novel algorithm to speed up Q-learning with the help of a limited amount
of imperfect expert demonstrations. The algorithm avoids excessive reliance on
expert data by relaxing the optimal expert assumption and gradually reducing the
usage of uninformative expert data. Experimentally, we evaluate our approach on
a sparse-reward chain environment and six more complicated Atari games with
delayed rewards. With the proposed methods, we can achieve better results than
Deep Q-learning from Demonstrations (Hester et al., 2017) in most environments.

1 Introduction

Reinforcement learning (RL) trains an agent to maximize expected cumulative rewards through
online interactions with an environment [1]. To speed up learning, online RL can be combined with
offline expert demonstrations [2], which guides the agent toward high-rewarding behaviours and thus
improves data efficiency. Most existing expert demonstration methods [3, 4] either clone behaviours
from the expert or bonus expert actions. However, agents are provided with imperfect expert data and
gain distracting guidance. Some works start handling the imperfect expert data but still lack solid
theoretical foundation [5, 6].

Our paper adopts Bayesian frameworks [7, 8], which provide an analytical method to incorporate extra
sub-optimal expert information for learning. In the probabilistic model for Bayesian inference, the
sub-optimal expert decision is assumed to rely on the Boltzmann distribution dependent on the optimal
expected returns from state-action pairs, called the optimal Q-values. Intuitively, our paper considers
that the expert would prefer actions with higher optimal Q-values. Based on this assumption, the
agent can infer values of the optimal Q-values from the given expert data during online learning and
correct estimated Q-values to better correspond to the expert behaviours. This inference is equivalent
to maximizing the posterior distribution of Q-values conditioned on expert data. To derive a posterior
maximum, our paper proposes to utilize the generalized extended Kalman filter (GEKF) [9], requiring
fewer restrictions on Q-values functions than other Bayesian RL frameworks [8, 10, 11].

Under the assumptions from the GEKF framework, we derive an iterative forward way to compute
Q-values, which consists of a Q-value-update step as in the Q-learning algorithm and an expert
correction step. In the correction step, our update rule weighs expert information according to
an agent's uncertainty of its self-learning result, measured by the estimated posterior variance of
learned Q-values. Thus, the larger Q-values' variance is, the more our expert correction encourages
expert behaviours by increasing expert actions' Q-values and decreasing non-experts' Q-values.
This mechanism reduces the influence of uninformative expert data and avoids excessive guided
exploration.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Furthermore, we propose our computationally efficient deep algorithm, Bayesian Q-learning from Demonstrations (BQfD), built on top of the Deep Q-learning Network (DQN) [12]. The algorithm embeds reliable expert knowledge into Q-values and leads to a more efficient exploration, as shown on a sparse-reward chain environment DeepSea and six randomly chosen Atari games. In most environments, our algorithm learns faster than Deep Q-learning from Demonstrations (DQfD) [2] and Prioritized Double Duelling (PDD) DQN [13].

2   Related Work

Reinforcement learning from demonstrations (RLfD) has drawn attention in recent years. This method only requires a small number of offline expert demonstrations and can noticeably improve performance. Deep Q-learning from demonstrations (DQfD) [2] includes an additional margin classification loss to ensure that Q-values of expert actions are higher than other actions.

However, these approaches do not consider the case where the expert is imperfect and can often have difficulty exceeding expert performance. In contrast, Nair et al. [5] handle suboptimal demonstrations by only cloning expert actions when their current estimated Q-values are higher than others. Zhang et al. [6] utilizes expert information when the cumulative Q-values on expert state-action pairs are larger than cumulative value functions. However, the learned Q-value is often unreliable and frequently changes, making it a poor judgment of expert data quality. At the same time, our measurement based on the posterior variance of estimated Q-values is more reasonable.

Jing et al. [14] models the suboptimal expert policy as a local optimum to maximize the expected returns and then constrains the agent to learn within a region around the expert policy, measured by KL divergence between occupancy measures. However, the local optimum condition is hard to satisfy, and the limitation of learning around the expert policy cannot deal with mistaken expert actions. In contrast, our assumption on Boltzmann distributed expert policy is much weaker.

3   Background

A Markov decision process [1] is a tuple $M = \langle \mathcal{S}, \mathcal{A}, P, \gamma, R, \rho \rangle$ where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, P is the time-homogeneous transition probability matrix with $P(s'|s,a)$ as elements, $\gamma \in (0,1)$ is the discount factor, R is the reward function, with $R(s,a)$ denoting a random vector describing rewards received after state-action pair (s,a) and ρ is the distribution of the initial state. At each time step h, the agent samples an action A_h from a policy μ, and then transits to the next state S_{h+1} and gains a reward $R(S_h, A_h)$. Our paper focuses on finite horizon cases with horizon H, where an agent stops at time step H. Also, our paper works on finite action and state spaces.

The expected discounted cumulative return starting from each state-action pair (s,a) at time step h and following the policy μ is called the Q-value, denoted by $q_h^\mu(s,a)$, and is defined as follows:

$$q_h^\mu(s,a) = \mathbb{E}_\tau [\sum_{t=h}^{H} \gamma^t R(S_t, A_t)],$$

where τ denotes trajectories with $S_h = s$, $A_h = a$, $S_t \sim P(\cdot|S_{t-1}, A_{t-1})$, $A_t \sim \mu(\cdot|S_h)$ and rewards $R(S_t, A_t)$. The unique optimal Q-value function at time h is defined as $q_h^*(s,a) = \sup_\mu q_h^\mu(s,a)$.

Optimal Q-values can be computed by Q-learning algorithm [15, 16], which estimates Q-values directly and is based on the following update rule:

$$Q_h(s,a) = (1-\alpha)Q_h(s,a) + \alpha[R(s,a) + \gamma \max_{a'} Q_{h+1}(S', a'),$$

where Q is an estimation of Q-values, $S' \sim P(\cdot|s,a)$ is a sampled next state, and $\alpha \in (0,1)$ is the learning rate.

Bayesian reinforcement learning assumes that there is an initial guess or a prior probability over the model parameters, denoted by $P(\mathcal{M})$. In the model-free case, we treat Q-values as random variables and implicitly embed parametric uncertainties from different MDPs. A prior distribution of the optimal Q-values at time h is defined as:

$$P(q_h^*(s,a) \leq c) = P(\{\mathcal{M} : q_{\mathcal{M},h}^*(s,a) \leq c\}).$$

Then algorithms compute the posterior probability of Q-values [8, 17].

4 Model and Algorithm

4.1 Probabilistic Model of Suboptimal Expert Actions

We start by modeling the relationship between expert actions and the optimal Q-values. The expert chooses the optimal actions most frequently but may contain mistakes and select low probability actions. The Boltzmann distribution can describe this behavior with the optimal Q-values as parameters. Under this distribution, expert actions are sampled proportional to the exponential of optimal Q-values up to a constant multiplier. As known, this assumed expert policy maximizes the expected returns regularized by the entropy [18], describing almost optimal but sometimes mistaken expert behaviors. The above assumption is formally presented as follows and shown on the left of figure 2, where the expert action at time h and state s is denoted by $A_{exp,h}(s)$.

Assumption 1. *Assume that expert demonstrations are drawn from a policy π_{expert} dependent on the optimal Q-values. Also, this policy follows the Boltzmann distribution:*

$$\pi_{expert}(a|s) = \frac{e^{\eta q^*(s,a)}}{\sum_{b \in \mathcal{A}} e^{\eta q^*(s,b)}}, \tag{1}$$

where η is any positive constant.

Moreover, we capture the relationship between the optimal Q-values at different time steps in our probabilistic model through the Bellman equation. Without the knowledge of environment dynamics, our model relies on samples of the reward and the next state to evaluate the the Bellman equation, which are widely accepted in the field [15]. Therefore, we re-write the Bellman equation in a stochastic form as

$$q^*(s,a) = R(s,a) + max_{a' \in \mathcal{A}} \gamma q^*(S',a') + \nu, \tag{2}$$

where $R(s,a)$ and the next state S' are sampled according to the rules of the underlying MDP. This random noise ν captures the randomness from the dynamics. Then, the whole model of relationships among rewards, optimal Q-values, and expert actions along a trajectory is presented in figure 2 in the appendix.

4.2 GEKF Framework

In order to compute the posterior probability, our paper leverages the generalized extended Kalman filter (GEKF) [9] under which the posterior mode is of analytical form. This framework requires extra expert information following an exponential family distribution, which is already assumed. Furthermore, the framework requires the random noise ν in the stochastic Bellman equation 2 at each Q-value update step to be Gaussian, which is also assumed in Osband et al. (2019) [11]. Meanwhile, this assumption does not hurt in the latter stage of training since the influence of the random noise gradually approaches zero as the number of samples increases, and the learning rate decays.

Assumption 2. *For all state-action pair (s,a), the noise ν is modeled independently by a Gaussian random variable $\nu \sim N(0,\lambda)$.*

Also, the GEKF framework approximates the posterior distribution by Gaussian and linearize the maximization operator in Q-value updates linearly as in Osband et al. (2019) [11].

4.3 Derivation of Q-values Update Rules

We derive our Q-value estimations Q under the above assumptions given by the GEKF framework [9]. Firstly, this estimation should satisfy the stochastic Bellman equation in equation 2. Secondly, it should maximize the posterior probability of the optimal Q-values conditioned on expert demonstrations. This task is stated as follows:

$$\max_{Q_{0:H-1}} P(q^*_{0:H-1} = Q_{0:H-1}|A_{exp,0:H-1}, R_{0:H-1}) \tag{3}$$

$$s.t. \quad q^*_H(s,a) = 0, \ \forall s \in \mathcal{S} \text{ and } \forall a \in \mathcal{A}$$

$$q^*_{h-1}(s,a) = R_{h-1}(s,a) + \gamma \max_{a'} q^*_h(S',a') + \nu, \ h = H, \cdots, 1, \ \forall s \in \mathcal{S} \text{ and } \forall a \in \mathcal{A},$$

where $q_h^* \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ represents the Q-value vector at step h with each element as the value of one state-action pair, and similar for R_h; moreover, $A_{exp,h} \in \mathbb{R}^{|\mathcal{S}|}$ represents the expert actions chosen at all states at step h. Then, we solve the constrained optimization problem and derive Q-values update rules as shown in the appendix following the steps in Sage (1997) [19].

Finally, our estimations can be computed step-by-step as presented in algorithm 1 in the appendix. In the prediction step, the algorithm updates Q-values as the Q-learning algorithm [15]. This update of estimated Q-values can be written as $Q_h = R_h + T_h Q_{h+1}$, using a transformation matrix $T \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}| \times |\mathcal{S}||\mathcal{A}|}$. Its element at each state-action pair and its next-state-maximal-action pair equals to one, that is $T[(s,a),(S',a')] = 1$ where $S' \sim P(\cdot|s,a)$ and $a' = argmax_b Q_{h+1}(S',b)$. And all other elements are zero.

Then, the algorithm computes the estimated posterior variance W. Our derivation gives that this variance is not updated by the transformation matrix T, but is also influenced by the Hessian of log expert policy $U \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}| \times |\mathcal{S}||\mathcal{A}|}$. The update first computes $N_h = T_h^T W_{h+1} T_h + \lambda I$, and then calculates the estimated variance $W_h = (N_h^{-1} + U_h)^{-1}$.

After computing the variance, expert information corrects Q-values as

$$Q_h(s,a) = Q_h(s,a) + \eta W_h[(s,a),(s,a)][\mathbb{1}[A_{exp,h}(s) = a] - \frac{exp(\eta Q_h(s,a))}{\sum_{b \in \mathcal{A}} exp(\eta Q_h(s,b))}].$$

A bonus weighted by the variance is given to expert actions and encourages the agent to explore them when it is not confident of the current learning result. When the variance of a Q-value estimate is low, the agent stops guided exploration by the expert and follows its own learnt policy. Thus, the agent can deal with inadequate expert data by gradually ignoring it.

4.4 Algorithm

Our paper proposes an algorithm Bayesian Q-learning from Demonstrations (BQfD) to realize the GEKF update rules of Q-values presented in algorithm 3 in the appendix. This algorithm samples a trajectory at the beginning of each turn and then updates Q-values by the sampled-based Bellman rule and the expert correction backward. Thus, our algorithm only updates the Q-value of the state-action pair (S_h, A_h) at each time step h and introduces a learning rate α for Bellman equation updates to reduce variances. This learning rate $\alpha_{n(s,a)}(s,a)$ is considered to be state-action pair dependent and decays as the number of that pair's visitations $n(s,a)$ increases. To avoid computations of the Hessian and the matrix inversion, we approximate the posterior variance at a state-action pair (s,a) roughly as a function of the visitation times, denoted by $w_{n(s,a)} = O(\frac{1}{(n(s,a)}\lambda)$.

Furthermore, our paper utilizes deep neural networks and proposes a deep BQfD based on Prioritized Dueling Double (PDD) Deep Q-learning Network (DQN) [12, 13, 20]. Notice that our current update rule requires expert information for every state, while a limited set of expert demonstrations is usually provided. Instead, our algorithm suggests storing expert data in the replay buffer and only performing expert correction when sampling expert data from the buffer.

5 Experiment

To evaluate the discernment of expert data, we test our algorithm using optimal and misleading expert data in a sparse-reward chain environment called DeepSea [11]. Then, we further test the data efficiency of our algorithm with the help of a limited amount of suboptimal human data on six complicated Atari games [21]. We compare against other two discrete-action algorithms: Prioritized Dueling Double (PDD) Deep Q-learning Network (DQN) [12, 13, 20] with EZ-greedy [22] exploration and Deep Q-learning from demonstrations (DQfD).

5.1 Chain Environment

DeepSea is a deterministic chain environment. A figure to describe the environment is shown in the appendix. There is a fixed but unknown reward at the most right state, consisting of either a treasure with a bonus of $+1$ or a bomb with a cost of -1. During learning, we always provide agents with an

Figure 1: This figure shows agents' performances for the treasure case on the left and the bomb case on the right. It presents the training rewards versus the number of training episodes in an environment of size 50. Our algorithm can rapidly discover the optimal reward given the optimal expert data and acquire the optimal behavior given wrong expert information.

Game	Length	DQN	DQfD	BQfD
Breakout	91M	221 ± 75	291 ± 119	$\mathbf{354 \pm 132}$
ChopperCommand	63M	4493 ± 1295	7067 ± 2403	$\mathbf{7377 \pm 2801}$
Freeway	23M	$\mathbf{30.4 \pm 0.4}$	28.2 ± 0.8	29.8 ± 0.8
MsPacman	76M	3628 ± 725	$\mathbf{4927 \pm 993}$	3550 ± 613
Seaquest	96M	20595 ± 8248	22388 ± 6294	$\mathbf{28546 \pm 11613}$
VideoPinball	116M	8619 ± 12582	17235 ± 15906	$\mathbf{30668 \pm 18772}$

Table 1: We present the average evaluation rewards over the previous 2M steps $\pm$ and the average standard deviations over the last 2M steps among three random seeds. BQfD shows apparent advantages in Breakout, ChopperCommand, Seaquest and VideoPinball and performs comparably to the best in Freeway and MsPacman.

expert trajectory towards the most right. Thus, in the treasure case, we test our algorithms' efficiency; in the bomb case, we evaluate our algorithms' robustness in the presence of highly misleading expert information. To provide a fair comparison, we include an expert trajectory to the replay buffer of DQN and provide no pretraining for any algorithms.

The results for the treasure case are shown on the left of figure 1. BQfD and DQfD can gain the optimal reward after one training episode much faster than DQN since the expert data directly leads to the reward, and these two algorithms extract expert information efficiently. But DQfD assumes the expert data to be optimal and causes catastrophic performance when expert demonstrations are misguiding, as seen in the bomb case, shown on the right of figure 1. On the contrary, our learning-from-demonstrations approach successfully learns the optimal policy, though the convergence speed is hindered due to confusing information. This result proves that BQfD efficiently extracts expert information and gradually stops using expert information.

5.2 Arcade Learning Environment

We further evaluated our approach on Arcade Learning Environments [21, 12]: Breakout, ChopperCommand, Freeway, MsPacman, VideoPinball, and Seaquest. The architecture for all three algorithms is the same as PDD DQN [12, 13, 2, 20] with prioritized replay buffer [23]. Baselines' hyperparameters follow the choices in their original papers. Meanwhile, we tune hyperparameters for BQfD on the environment Seaquest, and the detailed results are shown in the appendix. All approaches are provided with one human-generated expert trajectory and are pre-trained with this expert data. Given the randomness during training, all results shown are averaged over three random seeds.

The overall results are shown in table 1. Here, we present final-learned evaluation rewards: the average means and standard deviations of evaluation rewards over the last 2M steps. Our algorithm outperforms the baselines in Breakout, ChopperCommand, Seaquest, and VideoPinball. In MsPacman, it still performs better than DQN but slightly worse than DQfD. In general, both three algorithms perform much worse than humans on MsPacman. DQN dominates the game in Freeway, but our algorithm recovers from weak expert data compared to DQfD. Learning curves are shown in figure 4 in the appendix.

Acknowledgement

Thanks to Tianzi Yang and Sitao Luan for their valuable discussions. Also, thanks to professor Rupam Mahmood for the funding and support.

References

[1] Richard S Sutton and Andrew G Barto. Reinforcement learning: an introduction. 2018.

[2] Todd Hester, Matej Vecerik, Olivier Pietquin, Marc Lanctot, Tom Schaul, Bilal Piot, Dan Horgan, John Quan, Andrew Sendonaris, Ian Osband, et al. Deep q-learning from demonstrations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[3] Tim Brys, Anna Harutyunyan, Halit Bener Suay, Sonia Chernova, Matthew E Taylor, and Ann Nowé. Reinforcement learning from demonstration through shaping. In *Twenty-fourth international joint conference on artificial intelligence*, 2015.

[4] Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, page 1, 2004.

[5] Ashvin Nair, Bob McGrew, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Overcoming exploration in reinforcement learning with demonstrations. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6292–6299. IEEE, 2018.

[6] Xiaoqin Zhang, Huimin Ma, Xiong Luo, and Jian Yuan. Lidar: learning from imperfect demonstrations with advantage rectification. *Frontiers of Computer Science*, 16(1):1–10, 2022.

[7] Mohammad Ghavamzadeh, Shie Mannor, Joelle Pineau, Aviv Tamar, et al. Bayesian reinforcement learning: A survey. *Foundations and Trends® in Machine Learning*, 8(5-6):359–483, 2015.

[8] Richard Dearden, Nir Friedman, and Stuart Russell. Bayesian q-learning. *Aaai/iaai*, 1998:761–768, 1998.

[9] Ludwig Fahrmeir. Posterior mode estimation by extended kalman filtering for multivariate dynamic generalized linear models. In *Journal of the American Statistical Association*, pages 87.418: 501–509, 1992.

[10] Yaakov Engel, Shie Mannor, and Ron Meir. Bayes meets bellman: The gaussian process approach to temporal difference learning. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 154–161, 2003.

[11] Ian Osband, Benjamin Van Roy, Daniel J Russo, Zheng Wen, et al. Deep exploration via randomized value functions. *J. Mach. Learn. Res.*, 20(124):1–62, 2019.

[12] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

[13] Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Hasselt, Marc Lanctot, and Nando Freitas. Dueling network architectures for deep reinforcement learning. In *International conference on machine learning*, pages 1995–2003. PMLR, 2016.

[14] Mingxuan Jing, Xiaojian Ma, Wenbing Huang, Fuchun Sun, Chao Yang, Bin Fang, and Huaping Liu. Reinforcement learning from imperfect demonstrations under soft expert guidance. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 5109–5116, 2020.

[15] Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine learning*, 8(3):279–292, 1992.

[16] Chi Jin, Zeyuan Allen-Zhu, Sebastien Bubeck, and Michael I Jordan. Is q-learning provably efficient? *Advances in neural information processing systems*, 31, 2018.

[17] Ian Osband, John Aslanides, and Albin Cassirer. Randomized prior functions for deep reinforcement learning. *Advances in Neural Information Processing Systems*, 31, 2018.

[18] Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[19] Andrew P Sage and James L Melsa. Estimation theory with applications to communications and control. Technical report, SOUTHERN METHODIST UNIV DALLAS TEX INFORMATION AND CONTROL SCIENCES CENTER, 1971.

[20] Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

[21] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[22] Will Dabney, Georg Ostrovski, and André Barreto. Temporally-extended {\epsilon}-greedy exploration. *arXiv preprint arXiv:2006.01782*, 2020.

[23] Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

 Appendix

 Derivation of Generalized Extended Kalman Filters

We derive the Q-value update rules under assumptions from the GEKF framework. The proof follows the steps in Sage and James (1997) [19].

A Kalman filter estimates the hidden Q-values Q_h of an agent at each discrete time step $t = 0, ..., T$ given noisy expert observations $A_{exp,h}$, $h = H - 1, ..., 0$ and noisy transition functions. The Linear Kalman Filter requires the previous state Q_h and observation $A_{exp,h+1}$ to depend linearly on the current state Q_{h+1}. The extended Kalman filter relaxes these relationships to smooth functions. In this section, we discuss the generalized extended Kalman filter [9] where the observation $A_{exp,h+1}$ follows any exponential family distribution with the current state Q_{h+1} as parameters. The probabilistic model is defined as:

$$q_H^* = 0, \tag{4}$$
$$q_h^* = \phi(q_{h+1}^*) + \nu_h, \quad \nu_h \sim N(0, \lambda I),$$
$$P(A_{exp,h}(s, a) = a | q_h^*) = exp(\eta q_h^*(s, a) - log(\sum_b exp(\eta q_h^*(s, b)))).$$

The linear and extended Kalman filters assume that the posterior is a Gaussian distribution; thus, they do not need to distinguish between conditional means and posterior modes. However, these two estimators are not equivalent to the generalized extended Kalman filter. This paper focuses on the maximum a posteriori estimator for a Kalman filter [19]. Due to the Markovian assumptions of the model, the posterior distribution of hidden states is proportional to

$$P(q_{0:H}^* | A_{exp,0:H-1}, R_{0:H-1}) \propto \prod_{h=0}^{H-1} P(A_{exp,h} | q_h^*) \prod_{h=0}^{H-1} P(q_h^* | q_{h+1}^*, R_h) P(q_H^*),$$

Maximizing the posterior is equivalent to minimizing the negative log probability. By combining this objective with the probabilistic model in Equation 4, when $Q_H = 0$, we obtain:

$$- log P(q_{0:H}^* = Q_{0:H} | A_{exp,0:H-1}, R_{0:H-1})$$
$$\propto \frac{1}{2} \sum_{h=0}^{H-1} \|Q_h - \phi(Q_{h+1})\|_{(\lambda I)^{-1}}^2 - \sum_{t=0}^{H-1} \sum_{s,a} [\eta Q_h(s, a) - log(\sum_b exp(\eta Q_h(s, b)))],$$
$$=: \frac{1}{2} \sum_{h=0}^{H-1} \|Q_h - \phi(Q_{h+1})\|_{(\lambda I)^{-1}}^2 - \sum_{t=0}^{H-1} \psi(Q_h) \mathbb{1}[Q_H = 0],$$
$$=: J(Q_{0:H}).$$

Here, we write the log observation probability as $\psi(Q_h)$ and define the minimization objective $J(Q_{0:H})$, subject to equations in 4:

$$\min_{Q_{0:H-1}} J(Q_{0:H})$$
$$s.t. Q_H = 0,$$
$$Q_h = \phi(Q_{h+1}) + \nu_h, \ h = H - 1, ..., 0.$$

This optimization problem can be solved by exploiting Lagrangian multipliers $\alpha_0, ..., \alpha_H$. First, the equality constraints are combined into the loss to form a Lagrangian function:

$$L(Q_{0:H}, \lambda, \alpha_{0:H}) = \sum_{h=1}^{H} H(Q_h, \alpha_{h-1}, \nu_{h-1}) - \sum_{h=0}^{H} \alpha_h Q_h,$$

where

$$H(Q_h, \alpha_{h-1}, \nu_{h-1}) = \frac{1}{2} \|\nu_{h-1}\|_{(\lambda I)^{-1}}^2 - \psi(\phi(Q_h) + \nu_{h-1}) + \alpha_{h-1}(\phi(Q_h) + \nu_{h-1}).$$

Then, a minimal solution requires the gradients of the Lagrangian function over all variables to be zero at that point. This procedure results in a partial differential equation (PDE) system, also known as a two-point boundary value problem. For convenience, we denote the partial derivative of the log observation probability as:

$$l(Q_h) := \frac{\partial}{\partial Q_h}\psi(Q_h) = \frac{\partial}{\partial Q_h}\log(P(A_{exp,h}|q_h^* = Q_h)).$$

277 Then the PDE is presented as:

$$Q_h = \phi(Q_{h+1}) - \lambda[\frac{\partial\phi(Q_{h+1})}{\partial Q_{h+1}}]^{-1}\alpha_{h+1}, \tag{5}$$

$$\alpha_h = \left[\frac{\partial\phi(Q_{h+1})}{\partial Q_{h+1}}\right]^{-1}\alpha_{h+1} + l(Q_h),$$

$$\alpha_H = c, \quad \forall c \in \mathbb{R},$$

$$\alpha_0 = 0.$$

278 For simplicity, the differential equations above can be expressed as

$$Q_{h-1} = f(Q_h, \alpha_h, h), \tag{6}$$

$$\alpha_{h-1} = g(Q_h, \alpha_h, h).$$

279 This PDE system can be solved by the invariant embedding method. Our goal is to learn a function of
280 $Q_{0:H-1}$ which only depends on constants and the time step h, denoted as

$$Q_h = r(\alpha_h, h) \text{ and } \alpha_h = C.$$

281 According to this function, Q-values at the previous step $h - 1$ satisfy that

$$Q_{h-1} = r(\alpha_{h-1}, h - 1).$$

282 By plugging in function f and g in equation 6, we obtain

$$r(g(r(C, h), C, h), h - 1) = f(r(C, h), C, h). \tag{7}$$

283 Since those PDEs in equation 5 are all linear of Lagrangian multiplies $\alpha_{0:H}$, it is further assumed
284 that the function $r(C, h)$ is a linear function of variable C. Thus $r(C, h)$ can be written linearly by
285 $r(C, h) = D(h) - P(h)C$ where D and P are some smooth functions of step h. Since $r(C, h)$ must
286 satisfy the boundary assumptions $Q_h = r(C, h)$ for any $C \in \mathbb{R}$, $D(h)$ must equal to Q_h and thus
287 $r(C, h) = Q_h - P(h)C$. After substituting it into equation 7, we obtain

$$Q_{h-1} - P(h - 1)g(Q_h - P(h)C, C, h) = f(Q_h - P(h)C, C, h).$$

288 When deriving Q-value estimations backward, at each time step, we only maximize the posterior
289 probability from this step until termination. Thus, we work on the boundary of the PDE with
290 Lagrangian multiplier $C = \alpha = 0$. Therefore, the above equation holds at $C = 0$, and both sides'
291 derivatives over variable C are also equal. Thus, we gain the update rule:

$$Q_{h-1} - P(h - 1)g(Q_h, 0, h) = f(Q_h, 0, h),$$

$$P(h - 1)\frac{\partial g}{\partial C}(Q_h, 0, h) = -\frac{\partial f}{\partial C}(Q_h, 0, h).$$

292 The final step is to derive the initial conditions of Q_H, P_H. When the trajectory length is zero, we
293 have a simple loss $|Q_H - 0|$, and obviously, the minimum point is $Q_H = 0$. Recall that the invariant
294 embedding assumption gives $Q_H = r(\alpha_H, H) = Q_H - P(H)\alpha_H$ and the boundary value allows
295 α_H to be any constant. Therefore, we conclude that $P(H) = \mathbf{0}$.

296 Now we have an exact per-step update rule given these initial values.

$$Q_{h-1} = \phi(Q_h) + P(h - 1)\frac{\partial}{\partial Q_h}logP(A_{exp,h}|Q_h),$$

$$P(h - 1) = \lambda I + [\frac{\partial\phi(Q_h)}{\partial Q_h}]^T P(h)\frac{\partial\phi(Q_h)}{\partial Q_h},$$

$$P(h - 1) = [P^{-1}(h - 1) - \frac{\partial^2}{(\partial Q_h)^2}logP(A_{exp,h}|Q_h)]^{-1}.$$

297 with initial conditions $Q_H = 0$ and $P(H) = \mathbf{0}$. This provides the final Q-values update rule as seen
298 in algorithm 1. Here, function P is denoted by variance matrix W.

Algorithm 1 GEKF update rule for one episode

Initialize: Q-values at the last step $Q_H = 0$, Weight matrices of Q-value functions $W_H = \mathbf{0}^{|\mathcal{S}||\mathcal{A}| \times |\mathcal{S}||\mathcal{A}|}$, and Identity matrix I.

for time step $h = H - 1, ..., 0$ **do**

    Prediction step:

    Update Q-value of each state-action pair based on sampled reward and next state though Bellman equation

    $Q_h(s,a) = R_h(s,a) + T_h Q_{h+1}, \forall s, a$

    Correction step:

    Compute the estimated posterior variance

    $W_h = T_h^T W_{h+1} T_h + \lambda I$

    $W_h = (W_h^{-1} + U_h)^{-1}$

    Embed in the expert correction

    $Q_h(s,a) + = +\eta W_h[(s,a),(s,a)][\mathbb{1}[A_{exp,h}(s) = a] - \frac{exp(\eta Q_h(s,a))}{\sum_{b \in \mathcal{A}} exp(\eta Q_h(s,b))}]$

end for

Model and Algorithm

The whole model of relationships among rewards, optimal Q-values, and expert actions along a trajectory is presented on the right of figure 2.

Figure 2: (Left) The figure demonstrates the relationship between optimal Q-values and expert actions. Expert actions are sampled proportional to the exponential of optimal Q-values up to a constant multiplier. (Right) The figure also describes the Bellman update rule for the Q-values along a trajectory.

Based on the GEKF model, our estimations can be computed step-by-step as presented in algorithm 1 in a backward view. The per-step update rule comprises a prediction step, the sample-based Bellman update and a correction step. Note that W is the posterior covariance term in Kalman filters.

Our tabular BQfD algorithm shown in algorithm 2 is to avoid the matrix inversion and Hessian computation in the update of weights W. We only update the Q-value of the current state-action pair (s_h, a_h) and approximate the weight of $\{(s_h, a_h), (s_h, a_h)\}$ by a $O(\frac{1}{n^l(s_h, a_h)})$ term where $n^l(s_h, a_h)$ is the visitation time of this state-action pair until the episode l.

Next, we extend our algorithm and include deep neural networks. We use TD loss for non-expert transitions denoted as $J(theta)$ and use en expert-information embedded loss $J_{exp}(\theta)$ for expert transition, defined as:

$$J_{exp}(\theta_{main}) = (R(s,a) + \gamma Q(s', a^{max}; \theta_{target})$$
$$+ w_n \eta (1 - \frac{exp(\eta Q(s_h, a_h; \theta_{main}))}{\sum_{b \in \mathcal{A}} exp(\eta Q(s_h, b; \theta_{main}))} - Q(s, a; \theta_{main}))^2$$

where θ_{target} is the parameters of target network, θ_{main} are the parameters of the main network, and $a^{max} = argmax_a \tilde{Q}(s', a; \theta_{target})$. We also leverage prioritized replay buffer [23] to balance the amount of expert data and online training data. The detailed algorithm is presented in algorithm 3.

Algorithm 2 BQfD

Input: Expert actions $A_{exp}(s)$ for all states, a constant β.
Initialize: Q-value functions $Q_{0:H}^0 = 0$.
for Each episode l=1,2,... **do**
    Sample: Initialize S_0^l and sample a trajectory of length H by choosing A_h^l with maximum Q-value. Observe $\{R_h^l\}_{h=0}^{H-1}$.
    for Each time step h=H-1,...,0 **do**
        Q-value update
$$Q_h^l(s,a) = \begin{cases} \alpha_n[R_h^l + \gamma max_a Q_{h+1}^l(s_{h+1},a)] + (1-\alpha_n)Q_h^{l-1}(s_h,a_h), & if \ (s,a) = (s_h^l, a_h^l) \\ Q_h^{l-1}(s,a), \ otherwise \end{cases}$$
        if s_h is visited in expert demonstration **then**
            Compute Weight Decay
            $w_n = \frac{\beta^2 + 4n^l(s_h,a_h)}{(\beta + n^l(s_h,a_h))^2}$
            Expert Correction
            $Q_h^l(s_h,a_h) += \eta w_n(\mathbb{1}[a_h = A_{exp}(s_h)] - \frac{exp(\eta Q_h^l(s_h,a_h))}{\sum_{b \in \mathcal{A}} exp(\eta Q_h^l(s_h,b))})$
        end if
    end for
    Initialize: Q-value functions for next episode $Q_{H+1}^{l+1} = Q_0^l$
end for

Algorithm 3 BQfD deep

Initialize: D^{replay}: initialized with demonstration data set, θ_{main}: random weights for main network (random), θ_{target}: random weights for target network (random), τ: target network update frequency
Pretrain: Randomly sample from replay buffer and minimize loss $J_{exp}(\theta)$
for step t=1,2,... **do**
    Take action a at state s with maximum current Q-values $\tilde{Q}(s,a;\theta_{main})$
    Play action a and observe (s', r)
    Store $(s,a,r,s',terminal)$ into prioritized replay buffer D^{replay}
    Sample a mini-batch from D^{replay} according to prioritization
    if data is from expert **then**
        Minimize $J_{exp}(\theta_{main})$ and perform a gradient descent step to θ_{main}
    end if
    if data is newly drawn **then**
        Minimize $J(\theta_{main})$ and perform a gradient descent step to θ_{main}
    end if
    if t mod τ =0 **then**
        Update θ_{target} by θ_{main}
    end if
end for

Also, our algorithm weighs expert data to reduce off-policy biases. The importance sampling ratio is hard to calculate, so our algorithm uses a computationally-efficient weight

$$\left[\frac{e^{\eta Q(s,a)}}{\sum_b e^{\eta Q(s,b)}} \right]^\zeta$$

where the power ζ is a rescaling factor to avoid miniature weights. This ratio assigns higher values to more frequent state-action pairs under the current ϵ-greedy policy with respect to Q-estimates.

Experiment Setting

The DeepSea environment requires less than one hour of training on an Nvidia 2070 GPU. Each Atari game requires 21 days of training on Compute Canada server with only 1 GPU and 24GB memory. The GPU on Compute Canada is either Nvidia V100 or Nvidia P100. All codes are provided in the supplementary material.

DeepSea

As shown in figure 3, DeepSea is a deterministic chain environment represented as a square grid of size $N \times N$. All agents are initialized at the top-left corner. At each time step, the agent can move left or right but always moves down by one. Notice that the edges of the grid bound the agent's movements. Each game terminates whenever the agent reaches the bottom. The agent receives rewards of 0 for left actions and $\frac{-0.01}{N}$ for the right actions except for a fixed but unknown reward at the bottom-right state. The unknown reward consists of either a treasure with a bonus of $+1$ or a bomb with a cost of -1. DeepSea suffers from both sparse rewards and small negative rewards for movements towards the unknown reward. Thus, it is a suitable environment to test the efficiency of guided exploration.

Figure 3: The chain environment consists of a grid and two actions, left and right. At each step, the agent always moves down by one. The agent receives a fixed but unknown reward at the bottom-right corner, either a treasure or a bomb. The game ends whenever the agent reaches the bottom.

The architecture consists of two layers of Perceptron with Relu activation functions. It is followed by two dense layers with 256 hidden units that output value function and advantage function. The state is the current position denote by a 2-dimensional vector. The hyperparameters of BQfD are set as follows: learning rate $lr = 0.0005$, variance $\lambda = 0.6$, and expert policy parameter $\eta = 3$. The learning rate for other methods is tuned to be $lr = 0.05$. Detailed tuning results on game of grid size $N = 20$ are shown in table 2.

Atari

We further evaluated our approach on Arcade Learning Environments: Breakout, ChopperCommand, Freeway, MsPacman, VideoPinball, and Seaquest. The architecture for all three algorithms is the same as PDD DQN; it consists of three layers of convolution neural networks of filter sizes 32, 64, and 64, kernel sizes [8, 8], [4, 4], and [3, 3], and strides of 4, 2, 1 respectively where each layer has a ReLU activation function. Furthermore, the output is passed to two dense layers, which output the value and advantage functions. As in DQfD, the input features are grey-scaled Atari frames resized to [84, 84] with a history length of 4. Furthermore, we scale down the reward during training to allow for standardized learning rates for all games, and each reward r is scaled as $sign(r)log(1 + r)$.

We reuse hyperparameters from DQfD and prioritized replay buffer for the two baselines. For BQfD, we tune our hyperparameters on the environment Seaquest, including learning rate, variance, and expert priority decay ratio. However, all three algorithms cannot learn the game MsPacman.

BQfD Hyperparameter	
learning rate	0.0005
eta	3
variance	0.9
DQN Hyperparameter	
learning rate	0.05
exploration decay start frame	300
Bootstrapped DQN Hyperparameter	
learning rate	0.05
number of ensembles	20
DQfD Hyperparameter	
learning rate	0.05

Table 2: We present the values of hyperparameters for all algorithms tuned on a game of size 20.

BQfD Hyperparameter	
learning rate	0.000055
variance	22
expert decay ratio	4
DQN or DQfD Hyperparameter	
learning rate	0.0000625

Table 3: We present the values of hyperparameters in the table. These hyperparameters for BQfD are tuned on Seaquest and used for all environments except MsPacman; because all three algorithms do not perform well on MsPacman, and its hyperparameters are specifically tuned. The hyperparameters for DQN and DQfD are the same as in the original papers.

So we tune the learning rate and initial random exploration ratio on MsPacman separately. The hyperparameters are chosen as shown in table 3: learning rate $lr = 0.000055$ and variance $\lambda = 22$. The expert priority decay speed is set to 4, meaning priorities of expert data decay until 4×30 millions of simulation steps. The initial epsilon greedy exploration ratio is 1.0 for MsPacman and 0.0 for others. All approaches are provided with one human-generated expert trajectory and are pre-trained with this expert data. The expert trajectory is generated by a human player who understands the game's rules but occasionally makes mistakes. For Breakout, ChopperCommand, Freeway, MsPacman, Seaquest, and VideoPinball, the expert demonstrations contain a single trajectory of 110, 33800, 27, 30k, 34k, and 82k rewards, respectively. Furthermore, we ensured that, in total, the expert demonstrations consist of around 6k frames; note for Freeway, we repeated the same trajectory thrice as its maximum length of a single game is 2049.

The training on Atari games requires reloading due to time limits, but the replay buffer is not saved. The counting of visitation times for BQfD is reset to mean previous visitation times among expert data. Thus, there may exist a performance downgrade in the middle.

Arcade Learning Results

During the learning, the three algorithms' performances do not show significant differences initially. But the average evaluation performance slowly tilts in favor of BQfD; it learns fastest, and the order of DQN and DQfD varies. Surprisingly, BQfD's advantage arises in the latter stages of training instead of improving learning speed in the early stages. One reason might be that expert data leads to adequate explorations. Also, our approach encourages the agent to deviate from expert states and learn from trials and errors.

Figure 4: These figures present Breakout, ChopperCommand, SeaQuest, and Freeway's results averaged over three random seeds of BQfD, DQfD, and PDD DQN. We observe that BQfD's performance far exceeds other approaches and shows an obvious advantage in the late stage of learning.