DENSE RECURRENT NEURAL NETWORK WITH ATTENTION GATE

ABSTRACT

We propose the dense RNN, which has fully connections from each hidden state to multiple preceding hidden states of all layers directly. As the density of the connection increases, the number of paths through which the gradient flows can be increased. It increases the magnitude of gradients, which help to prevent the vanishing gradient problem in time. Larger gradients, however, can also cause exploding gradient problem. To complement the trade-off between two problems, we propose an attention gate, which controls the amounts of gradient flows. We describe the relation between the attention gate and the gradient flows by approximation. The experiment on the language modeling using Penn Treebank corpus shows dense connections with the attention gate improve the models performance.

1 INTRODUCTION

In order to analyze sequential data, it is important to choose an appropriate model to represent the data. Recurrent neural network (RNN), as one of the model capturing sequential data, is applied to many problems such as natural language (Mikolov et al., 2013), machine translation (Bahdanau et al., 2014), speech recognition (Graves et al., 2013). There are two main research issues to improve the RNNs performance: 1) vanishing and gradient problem and 2) regularization.

The vanishing and exploding gradient problems happen as the sequential data has long-term dependency (Hochreiter, 1998; Pascanu et al., 2013). One of the solutions is to add gate functions such as the long short-term memory (LSTM) and gated recurrent unit (GRU). The LSTM has additional gate functions and memory cells (Hochreiter & Schmidhuber, 1997). The gate function can prevent the gradient from being vanished during back propagation through time. Gated recurrent unit (GRU) has similar performance with less gate functions (Chung et al., 2014).

In addition to adding gate functions, there is a way to increase feedforward depth and recurrent depth to capture multiple timescales. Feedforward depth is the longest path from the input layer to the output layer. Recurrent depth is the longest path from arbitrary hidden state at time t to same hidden sate at time t+t' (Zhang et al., 2016). Increasing feedforward depth means stacking multiple recurrent layers deeply. It can capture fast and slow changing components in the sequential data (Schmidhuber, 1992; El Hihi & Bengio, 1996; Hermans & Schrauwen, 2013). The low level layer in the stacked RNN captures short-term dependency. As the layer is higher, the aggregated information from lower layer is abstracted. Thus, as the layer is higher, the capacity to model long-term dependency increases. The number of nonlinearities in the stacked RNN, however, is proportional to the number of unfolded time step regardless of the feedforward depth. Thus, the simple RNN and stacked RNN act identically in terms of long run.

Increasing recurrent depth also increases the capability to capture long-term dependency in the data. The hidden state in vanilla RNN has only connection to previous time steps hidden state with same layer. Adding the connections to multiple previous time steps hidden states can make the shortcut paths, which alleviates the vanishing problem (Lin et al., 1996; Soltani & Jiang, 2016).

The vanilla RNN has only one path connected with previous hidden states. Thus, it is hard to apply standard dropout technique for regularization as the information is being diluted during training of long-term sequences. By selecting the same dropout mask for feedforward, recurrent connections, respectively, the dropout can apply to the RNN, which is called a variational dropout.

This paper proposes a dense RNN that has both of feedforward and recurrent depth. The stacked RNN increases the complexity by increasing feedforward depth. NARX-RNN and HO-RNN increase the complexity by increasing recurrent depth. Gated feedback RNN has the fully connection between two consecutive timesteps. Feedforward depth and recurrent depth has orthogonal property. As the connection for gated feedback is not overlapped with extensions to two orthogonal directions, all three features can be modeled as one architecture, which enhances overall performance.

The contributions of this paper are summarized: 1) dense RNN that is aggregated model with feedforward depth, recurrent depth and gated feedback function, 2) extension of the variational dropout to the dense RNN.

2   BACKGROUND

There are largely two methods to improve the performance of RNN. One is to extend previous model by stacking multiple layers or adding gate functions. The other is using regularization such as dropout to avoid overfitting.

2.1   EXTENSION OF RECURRENT NEURAL NETWORK MODELS

In simple recurrent layer, h_t, the hidden state at time t, is a function of input x_t and preceding hidden state h_{t-1}, which is defined as follows:

$$h_t = \phi(h_{t-1}, x_t) = \phi(Wx_t + Uh_{t-1}) \tag{1}$$

where U and W are respectively the feedforward and recurrent weight matrix and ϕ means an element-wise nonlinear function such as $Tanh$. In simple recurrent layer, the last hidden state h_{t-1} has to memorize all historical inputs. As the memorizing capacity of the hidden state is limited, it is hard to capture long-term dependency in sequential data. Stacked recurrent neural network, stacked of the simple recurrent layers can capture the long-dependency, which is defined as follows:

$$h_t^j = \phi(W^j h_t^{j-1} + U^{j \to j} h_{t-1}^j) \tag{2}$$

where W^j is the weight matrix for transition from layer $j-1$ to j and U^j is the weight matrix for transition from in timestep $t-1$ to timestep t at layer j. The stacked RNN can model multiple timescales of the sequential data. As the information travels toward upper layer, the hidden state can memorize abstracted information of sequential data that covers more long-term dependency.

The other way to capture the long term dependency is to increase the recurrent depth by connecting the hidden state at timestep t directly to multiple preceding hidden states (Soltani & Jiang, 2016), which is defined as follows:

$$h_t^j = \phi(W^j h_t^{j-1} + \sum_{k=1}^{K} U^{(k,j) \to j} h_{t-k}^j) \tag{3}$$

where $U^{(k,j) \to j}$ is the weight matrix from layer j at timestep $t-k$ to layer j at timestep t, and K is the recurrent depth. The direct connections make the shortcut paths from preceding multiple hidden states. Compared with the model without shortcut paths, the model with shortcut paths enables to access preceding hidden states further way from h_t^j with same number of transitions.

Most recurrent models have only recurrent connections between hidden states with same layers. By adding feedback connections to the hidden state h_t^j from the preceding hidden states h_{t-1}^i at different layer of h_t^j, the model adaptively captures the multiple timescales from long-term dependency, which is defined as follows:

$$h_t^j = \phi(W^j h_t^{j-1} + \sum_{i=1}^{L} U^{i \to j} h_{t-1}^i) \tag{4}$$

where $U^{i \to j}$ is the weight matrix from layer i at timestep $t-1$ to layer j at timestep t, and L is the feedforward depth. To control the amount of flows between different hidden states with different time scales (Chung et al., 2014), the global gate is applied as follows:

$$h_t^j = \phi(W^j h_t^{j-1} + \sum_{i=1}^{L} g^{i \to j} U^{i \to j} h_{t-1}^i). \tag{5}$$

In (5), $g^{i \to j}$ is the gate to control the information flows from each hidden state to multiple preceding hidden states of all layers, which is defined as follows:

$$g^{i \to j} = \sigma(w_g h_t^{j-1} + u_g^{i \to j} h_{t-1}^*) \tag{6}$$

where w_g^j is a vector whose dimension is same with h_t^{j-1}, $u_g^{i \to j}$ is a vector whose dimension is same with h_{t-1}^* that is a concatenated vector of all hidden states from previous time step, and σ is an element-wise sigmoid function.

Gated feedback function is also applied to LSTM. In gated LSTM, input gate i_t^j, forget gate f_t^j, output gate o_t^j, and memory cell gate $\tilde{c}_t^j$ are defined as follows:

$$i_t^j = \sigma(W_i^j h_t^{j-1} + U_i^{j \to j} h_{t-1}^j), \tag{7a}$$

$$f_t^j = \sigma(W_f^j h_t^{j-1} + U_f^{j \to j} h_{t-1}^j), \tag{7b}$$

$$o_t^j = \sigma(W_o^j h_t^{j-1} + U_o^{j \to j} h_{t-1}^j), \tag{7c}$$

$$\tilde{c}_t^j = \phi((W_c^j h_t^{j-1} + \sum_{i=1}^{L} g^{i \to j} U_c^{i \to j} h_{t-1}^j). \tag{7d}$$

Compared with conventional LSTM, the gated feedback LSTM has gated feedback function in the memory cell gate $\tilde{c}_t^j$. Through gates and memory cell state in (7a)-(7d), the new memory cell state c_t^j and hidden state h_t^j respectively are calculated as follows:

$$c_t^j = f_t^j \cdot c_{t-1}^j + i_t^j \cdot \tilde{c}_t^j, \tag{8a}$$

$$h_t^j = o_t^j \cdot \phi(c_t^j) \tag{8b}$$

where the dot product means element-wise multiplication.

2.2 DROPOUT OF RECURRENT NEURAL NETWORK

As dropout is one method of neural network regularization, it prevents the model from being over-fitted to training set. However, it is hard to apply the standard dropout to recurrent connections. As the sequence is longer, the information is affected by the dropout many time during backpropagation through time, which makes memorizing long sequences hard. Thus, applying the standard dropout only to feedforward connections is recommended (Zaremba et al., 2014). It is expressed as follows:

$$h_t^j = \phi(W^j D_t^j (h_t^{j-1}) + U^{j \to j} h_{t-1}^j) = \phi(W^j (m_t^{j-1} \cdot h_t^{j-1}) + U^{j \to j} h_{t-1}^j) \tag{9}$$

where D_t^j, as a dropout operator for every time step, makes h_t^{j-1} being masked with Bernoulli dropout mask m_t^{j-1} randomly generated for every time step. Moon et al. (2015) proposed how to apply the dropout to recurrent connections efficiently. By considering the whole sequential data as one input at a sequential level, same dropout mask is applied to recurrent connections at all time steps during training, which is expressed as follows:

$$h_t^j = \phi(W^j D_t^j (h_t^{j-1}) + U^{j \to j} D^{j \to j} (h_{t-1}^j)) = \phi(W^j (m_t^{j-1} \cdot h_t^{j-1}) + U^{j \to j} (m^j \cdot h_{t-1}^j)) \tag{10}$$

where $D^{j \to j}$, as a time-independent dropout operator, makes h_{t-1}^j being masked with Bernoulli dropout mask m^j randomly generated regardless of time.

Gal & Ghahramani (2016) applied variational dropout to RNN and proved the relation between Bayesian inference and dropout theoretically. Variational dropout in RNN applies same masks re-gardless of time to feedforward connections, similar to recurrent connections, which is expressed as follows:

$$h_t^j = \phi(W^j D^j (h_t^{j-1}) + U^{j \to j} D^{j \to j} (h_{t-1}^j)) = \phi(W^j (m^{j-1} \cdot h_t^{j-1}) + U^{j \to j} (m^j \cdot h_{t-1}^j)). \tag{11}$$

Figure 1: (a) Conventional RNN unfolded in time. (b) Gated feedback RNN. (c) RNN with connections across multiple preceding states. (d) Dense RNN integrated with (b) and (c). Hidden states are represented in red. The connections used in current steps feedforward are highlighted in bold. The feedback connections between upper and lower layers are represented in yellow. (e) Unfolded Dense RNN in both of time and the number of preceding states.

3 DENSE RECURRENT NEURAL NETWORK

The skip connections that bypasses some layers enables deep networks to be trained better than the models without skip connections. Many research (He et al., 2016; Huang et al., 2016) uses skip connections toward feedback connections. In this paper, we apply the skip connections toward recurrent connections. The shortcut paths from preceding multiple hidden states to the hidden state at time t is equal to the skip connections through time. The shortcut paths include the feedback connections between different layers of different timesteps. Each connection is controlled by the attention gate, similar to the global gate in the gated feedback RNN. The dense RNN is defined as follows:

$$h_t^j = \phi(W^j h_t^{j-1} + \sum_{k=1}^{K} \sum_{i=1}^{L} g^{(k,i)\to j} U^{(k,i)\to j} h_{t-k}^i) \tag{12}$$

where $g^{(k,i)\to j}$ is the attention gate, which is defined as follows:

$$g^{(k,i)\to j} = \sigma(w_g^i h_t^{j-1} + u_g^{(k,i)\to j} h_{t-k}^i). \tag{13}$$

(13) is a function of preceding hidden state at layer i and time $t - k$, while (6) is a function of concatenated all preceding hidden states. The intuition why we change the gate function and we call it to attention gate is described in Section 3.1.

The dense RNN can be easily extended to dense LSTM. The dense LSTM is defined as follows:

$$i_t^j = \sigma(W_i^j h_t^{j-1} + \sum_{k=1}^{K} \sum_{i=1}^{L} g_i^{(k,i)\to j} U_i^{(k,i)\to j} h_{t-k}^i), \tag{14a}$$

$$f_t^j = \sigma(W_f^j h_t^{j-1} + \sum_{k=1}^{K} \sum_{i=1}^{L} g_f^{(k,i)\to j} U_f^{(k,i)\to j} h_{t-k}^i), \tag{14b}$$

$$o_t^j = \sigma(W_o^j h_t^{j-1} + \sum_{k=1}^{K} \sum_{i=1}^{L} g_o^{(k,i)\to j} U_o^{j\to j} h_{t-1}^j), \tag{14c}$$

$$\tilde{c}_t^j = \phi((W_c^j h_t^{j-1} + \sum_{k=1}^{K} \sum_{i=1}^{L} g_c^{(k,i)\to j} U_c^{i\to j} h_{t-1}^j). \tag{14d}$$

Unlike gated feedback LSTM, the attention gate g is applied to all gates and memory cell state.

We analyze the advantages of dense connections intuitively and theoretically. In addition, we propose the dropout method for dense connections.

3.1 INTUITIVE ANALYSIS

Recurrent connections enable to predict next data given previous sequential data. In the language modeling, the RNNs can predict next word based on the last word and the last context accumulated before the last word. It assumes only last word affect to predict next word. For instance, "the sky is" is given from the full sentence "the sky is blue" and the goal is to predict the word "blue". In this case, the preceding word "sky provides the better clue than the preceding word "is". Inspired by the fact, we propose the dense model that predicts the next word by directly referring to recent preceding words. In other words, the output h_t^j is a function of input h_t^{j-1} and recent preceding output h_{t-k}^j as in (3).

The higher the layer in a neural network, the more abstract the hidden states. In language modeling, hidden states represent the characteristics of words, sentences, and paragraphs as the layer increases. The conventional RNN has only the connection between same layer. It means the preceding words, sentences, paragraphs determine next words, sentences and paragraphs, respectively. The given word, however, can also determine the context of next paragraph. Also, the given paragraph can determine next word. For instance, the word "mystery" in "it is mystery" can be followed by the paragraph related to "mystery" and vice versa. The feedback connections can reflect the fact.

In (4), preceding words, sentences, and paragraphs affects next words, sentences, and paragraphs with same scale. Preceding words, however, dont affects next word prediction evenly. In the sentence "The sky is blue", the word "sky" has a very close relation with the word "blue". The word "The", as an article, has a less relation with the word "blue". The amount how two words are related depends on the kind of the two words. We define the the degree of relevance as gated attention g as in (5).

The attention g is determined by the preceding word itself and the last word given as input. In the sentence "The sky is blue", the features of the word "the", and "sky" denote h_{t-2}, and h_{t-1}, respectively and the word "is" denotes x_t or h_t^0. Then, the attention to predict the word"blue" from the word "The" is determined by the word "The and "blue". The attention to predict the word "blue" from the word "is" is determined by the word "is" and "blue". In other words, the attention is dependent on the previous hidden state h_{t-k}^j and input h_t^{j-1} at certain time step as in (13).

3.2 THEORETICAL ANALYSIS

The vanishing and exploding gradient problems happen the sequential data has long term dependency. During backpropagation through time, error E_T's gradient with respect to the recurrent weight matrix U^j is vanished or exploded as the sequence is longer, which is expressed as follows:

$$\frac{\partial E_T}{\partial U^j} = \sum_{t=1}^{T} \frac{\partial E_T}{\partial U^j} = \sum_{t=1}^{T} \frac{\partial E_T}{\partial h_T^j} \frac{\partial h_T^j}{\partial h_t^j} \frac{\partial h_t^j}{\partial U^j} = \sum_{t=1}^{T} \frac{\partial E_T}{\partial h_T^j} \left(\prod_{\tau=t+1}^{T} \frac{\partial h_\tau^j}{\partial h_{\tau-1}^j} \right) \frac{\partial h_t^j}{\partial U^j}. \tag{15}$$

The critical term related to vanishing and exploding gradient problems is $\partial h_\tau^j / \partial h_{\tau-1}^j$. To find the relation between vanishing and exploding gradient problems and dense connections, we assume

Figure 2: (a) The stable region from exploding gradient problem. The attention gate increases the stable region from 1 to $1/(KL)$. (b) The stable region from vanishing gradient problem. The attention gate decreases the stable region from 1 to $1/(KL)$. (c) The approximation of the attention gate to determine vanishing and exploding gradient boundary.

the worst situation in which the vanishing and exploding gradient problem may arise. The term $\partial h_\tau^j / \partial h_{\tau-1}^j$ denotes γ^j. If the γ_{max}^j is less than 1, the gradient with respect to U^j would be exploded and if the γ_{min}^j is greater than 1, gradient with respect to U^j would be vanished. In dense recurrent network, there are more paths to flow the gradients. The γ^j in dense recurrent network is approximated as follows:

$$\gamma^j = \sum_{k=1}^{K} \sum_{i=1}^{L} \frac{\partial h_{\tau+k-1}^i}{\partial h_{\tau-1}^j} = \sum_{k=1}^{K} \sum_{i=1}^{L} \gamma^{(k,i)\to j} \tag{16}$$

where the superscript $(k,i) \to j$ means the path's direction from $h_{\tau+k-1}^i$ to h_τ^j. Assuming $\gamma^{(k,i)\to j}$ is $\gamma_{max}^{(k,i)\to j}$, γ_{max}^j is $KL\gamma_{max}^{(k,i)\to j}$, which reduces the vanishing gradient boundary from 1 to $1/(KL)$ as shown in Figure 2(a).

Though dense connections are able to alleviate the vanishing gradient problem, it causes the gradient exploding. To alleviate the problem caused by dense connection, we add the attention gates as in (13). The attention gate $g^{(k,i)\to j}$ can control the magnitude of $\gamma^{(k,i)\to j}$, which is expressed as follows:

$$\gamma^j = \sum_{k=1}^{K} \sum_{i=1}^{L} \frac{\partial h_{\tau+k-1}^i}{\partial h_{\tau-1}^j} \approx \sum_{k=1}^{K} \sum_{i=1}^{L} g^{(k,i)\to j} \cdot \gamma^{(k,i)\to j}. \tag{17}$$

In (17), the $g^{(k,i)\to j}$ is trainable so that the vanishing and exploding boundary is determined adaptively. In dense RNN with attention gates, $h_{\tau+k-1}^i$ is expressed as follows:

$$h_{\tau+k-1}^i = \phi(g^{(k,i)\to j} \cdot U^{(k,i)\to j} h_{\tau-1}^j + \theta) \tag{18}$$

where θ is not relevant parameters with $h_{\tau-1}^j$, $g^{(k,i)\to j}$ is $\sigma(U_g^{(k,i)\to j} h_{\tau-1}^j)$. For simplicity, (18) is expressed as $y = \phi(g(U_g x) \cdot Ux + \theta)$. Gradient of y with respect to x is calculated as follows:

$$\begin{aligned}
\frac{\partial y}{\partial x} &= y(1-y)[g(1-g)U_g Ux + gU] \\
&= y(1-y)U[g(1-g)U_g x + g] = \tilde{g}y(1-y)U.
\end{aligned} \tag{19}$$

The (19) is scaled with $\tilde{g}$ compared to $\frac{\partial y}{\partial x} = y(1-y)U$ without attention gate g. As g and $\tilde{g}$ are similar as shown in Figure 2(c), $\tilde{g}$ is approximated g as in (19).

Table 1: Perplexity on the Penn Treebank language modeling task.

Network	# Hidden size	# Feed forward	# Recurrent	# Param.	Valid	Test
LSTM (Zaremba et al., 2014)	200	2	1	5M	104	100.4
	650	2	1	20M	86.2	82.7
	1500	2	1	66M	82.2	78.4
VD-LSTM+RE (Inan et al., 2016)	200	2	1	2.65M	89.9	85.1
	650	2	1	8.6M	77.4	74.7
	1500	2	1	19.8M	74.5	71.2
Dense LSTM (2 hidden layers)	200	2	1	3.0M	85.39	80.35
	200	2	2	3.6M	83.39	78.64
	200	2	3	4.3M	83.56	79.05
	200	2	4	4.9M	83.28	78.82
	200	2	5	5.6M	83.70	78.99
Dense LSTM (3 hidden layers)	200	3	1	3.9M	83.12	78.95
	200	3	2	5.40M	83.08	78.67
	200	3	3	6.9M	82.38	78.15
	200	3	4	8.3M	82.56	77.91
	200	3	5	9.8M	82.98	78.69

3.3 EXTENSION OF VARIATIONAL DROPOUT

In dense RNN, as recurrent depth increases, the number of parameters also increases, which makes the model vulnerable to overfitting to training dataset. To prevent the model from overfitting to training dataset, the dropout is applied. The variational dropout, proved to show good performance in the RNN models, uses same random masks at every time step for feedforward connections, and recurrent connections, respectively. In implementation of variational dropout, each state is dropped with the random mask, which is followed by weighted sum. This concept is extensively applied to dense RNN so that the same random mask is used regardless of time and recurrent depth as shown in Figure. Extension of variational dropout to the dense connection is expressed as follows:

$$h_t^j = \phi(W^j(m^{j-1} \cdot h_t^{j-1}) + \sum_{k=1}^{K} \sum_{i=1}^{L} g^{(k,i) \to j} U^{(k,i) \to j}(m^i \cdot h_{t-k}^i)). \tag{20}$$

4 EXPERIMENT

In our experiment, we used Penn Tree corpus (PTB) for language modeling. PTB consists of 923k training set, 73k validation set, and 82k test set. As a baseline model, we select the model proposed by Zaremba et al. (2014), which proposed how to predict next word based on the previous words. To improve the accuracy, Zaremba et al. (2014) proposed regularization method for RNN.

The baseline models hidden sizes are fixed as 200, 650, and 1500, which are called as small, medium, and large network. In this paper, we fixed hidden size as 200 for all hidden layers with varying the feedforward depth from 2 to 3, recurrent depth from 1 to 5. The word embedding weight was tied with word prediction weight.

The proposed dense model is trained with stochastic gradient decent. The initial rate was set to 20, which was decayed with 1.1 after the epoch was over 12. The training was terminated when the epoch reaches 120. As a regularization, we adopt variational dropout, which uses the random masks regardless of time. We configured the word embeddings dropout to 0.3, feedforward connections dropout 0.2, and recurrent connections dropout rate varies from 0.2 to 0.5. The Table 1, as a trained result, compares the baseline model, RNN model with variational dropout and using same word space. In dense RNN, the perplexity is better than two models. The best models recurrent depth is 2 and the perplexity of valid set is 83.28 and that of test set is 78.82.

5 CONCLUSION

This paper proposed dense RNN, which has fully connections from each hidden state to multiple preceding hidden states of all layers directly. Each previous hidden state has its attention gate that controls the amount of information flows. To evaluate the effect of dense connections, we used Penn Treebank corpus (PTB). The result of dense connection was confirmed by varying the recurrent depth with the attention gate. The dense connections with the attention gate made the models perplexity less than conventional RNN.

REFERENCES

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Salah El Hihi and Yoshua Bengio. Hierarchical recurrent neural networks for long-term dependencies. In *Advances in neural information processing systems*, pp. 493–499, 1996.

Yarin Gal and Zoubin Ghahramani. A theoretically grounded application of dropout in recurrent neural networks. In *Advances in neural information processing systems*, pp. 1019–1027, 2016.

Alex Graves, Abdel-rahman Mohamed, and Geoffrey Hinton. Speech recognition with deep recurrent neural networks. In *Acoustics, speech and signal processing (icassp), 2013 ieee international conference on*, pp. 6645–6649. IEEE, 2013.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Michiel Hermans and Benjamin Schrauwen. Training and analysing deep recurrent neural networks. In *Advances in neural information processing systems*, pp. 190–198, 2013.

Sepp Hochreiter. The vanishing gradient problem during learning recurrent neural nets and problem solutions. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 6(02): 107–116, 1998.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Gao Huang, Zhuang Liu, Kilian Q Weinberger, and Laurens van der Maaten. Densely connected convolutional networks. *arXiv preprint arXiv:1608.06993*, 2016.

Hakan Inan, Khashayar Khosravi, and Richard Socher. Tying word vectors and word classifiers: A loss framework for language modeling. *arXiv preprint arXiv:1611.01462*, 2016.

Tsungnan Lin, Bill G Horne, Peter Tino, and C Lee Giles. Learning long-term dependencies in narx recurrent neural networks. *IEEE Transactions on Neural Networks*, 7(6):1329–1338, 1996.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 3111–3119. Curran Associates, Inc., 2013.

Taesup Moon, Heeyoul Choi, Hoshik Lee, and Inchul Song. Rnndrop: A novel dropout for rnns in asr. In *Automatic Speech Recognition and Understanding (ASRU), 2015 IEEE Workshop on*, pp. 65–70. IEEE, 2015.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. *ICML (3)*, 28:1310–1318, 2013.

Jürgen Schmidhuber. Learning complex, extended sequences using the principle of history compression. *Neural Computation*, 4(2):234–242, 1992.

Rohollah Soltani and Hui Jiang. Higher order recurrent neural networks. *arXiv preprint arXiv:1605.00064*, 2016.

Wojciech Zaremba, Ilya Sutskever, and Oriol Vinyals. Recurrent neural network regularization. *arXiv preprint arXiv:1409.2329*, 2014.

Saizheng Zhang, Yuhuai Wu, Tong Che, Zhouhan Lin, Roland Memisevic, Ruslan R Salakhutdinov, and Yoshua Bengio. Architectural complexity measures of recurrent neural networks. In *Advances in Neural Information Processing Systems*, pp. 1822–1830, 2016.