MODELING PARTS, STRUCTURE, AND SYSTEM DYNAMICS VIA PREDICTIVE LEARNING

ABSTRACT

Humans easily recognize object parts and their hierarchical structure by watching how they move; they can then predict how each part moves in the future. In this paper, we propose a novel formulation that simultaneously learns a hierarchical, disentangled object representation and a dynamics model for object parts from unlabeled videos in a self-supervised manner. Our Parts, Structure, and Dynamics (PSD) model learns to first recognize the object parts via a layered image representation; second, predict hierarchy via a *structural descriptor* that composes low-level concepts into a hierarchical structure; and third, model the system dynamics by predicting the future. Experiments on multiple real and synthetic datasets demonstrate that our PSD model works well on all three tasks: segmenting object parts, building their hierarchical structure, and capturing their motion distributions.

1 INTRODUCTION

What makes an object an object? Researchers in cognitive science have made profound investigations into this fundamental problem; results suggest that humans, even young infants, recognize objects as continuous, integrated regions that move together (Carey, 2009; Spelke & Kinzler, 2007). Watching objects move, infants gradually build the internal notion of objects in their mind. The whole process requires little external supervision from experts.

Motion gives us not only the concept of objects and parts, but also their hierarchical structure. The classic study from Johansson (1973) reveals that humans recognize the structure of a human body from a few moving dots representing the keypoints on a human skeleton. This connects to the classic Gestalt theory in psychology (Koffka, 2013), which argues that human perception is holistic and generative, explaining scenes as a whole instead of in isolation. In addition to being unsupervised and hierarchical, our perception gives us concepts that are fully interpretable and disentangled. Having a symbolic representation of objects, we are able to reason about their motion, predict what is going to happen in the near future, and imagine counterfactuals like "what happens if?"

How can we build machines of such competency? Would that be possible to have an artificial system that learns an interpretable, hierarchical representation with system dynamics, purely from raw visual data with no human annotations? Recent research in unsupervised and generative deep representation learning has been making progress along this direction: there have been models that efficiently explain multiple objects in a scene (Huang & Murphy, 2015; Eslami et al., 2016), some simultaneously learning an interpretable representation (Chen et al., 2016). Most existing models however either do not produce a structured, hierarchical object representation, or do not characterize system dynamics.

In this paper, we propose a novel formulation that learns an interpretable, hierarchical object representation and scene dynamics by predicting the future. Our model requires no human annotations, learning purely from unlabeled videos. After watching many videos of objects moving, our model learns to recognize and segment each object and its parts, build their hierarchical structure, and capture their motion distribution with a generative model, which can be further utilized for future prediction and video synthesis.

Our model, named Parts, Structure, and Dynamics (PSD), learns to recognize the object parts via a layered image representation. PSD learns their hierarchy via a *structural descriptor* that composes low-level concepts into a hierarchical structure. Formulated as a fully differentiable module, the

---

Our project page: https://sites.google.com/view/hierarchical-motion.

(a) Visual observations   **(b)** Part recognition   **(c)** Hierarchical structure   **(d)** Motion

Figure 1: Observing human moving, humans are able to perceive disentangled object parts, understand their hierarchical structure, and capture their corresponding motion fields (without any annotations).

structural descriptor can be end-to-end trained within a neural network. PSD learns to model the system dynamics by predicting the future.

We evaluate our model in many possible ways. On real and synthetic datasets, we first examine its ability in learning the concept of objects and segmenting them. We then compute the likelihood that it correctly captures the hierarchical structure in the data. We finally validate how well it characterizes object motion distribution and predicts the future. Our system works well on all these tasks.

2 RELATED WORK

Our work is closely related to the research on learning an interpretable representation with a neural network (Hinton & Van Camp, 1993; Kulkarni et al., 2015b; Chen et al., 2016; Higgins et al., 2017; 2018). Recent papers explored using deep networks to efficiently explain an object (Kulkarni et al., 2015a; Rezende et al., 2016; Chen et al., 2018), a scene with multiple objects (Ba et al., 2015; Huang & Murphy, 2015; Eslami et al., 2016), sequential data (Li & Mandt, 2018; Hsu et al., 2017), and hierarchically structured signals (Esmaeili et al., 2018). In particular, Kulkarni et al. (2015b) proposed a convolutional inverse graphics network. Taking an image of a face, the network learns to infer its properties like pose and lighting. Chen et al. (2016) proposed to learn a disentangled representation without direct supervision. Wu et al. (2017) studied video de-animation, building an object-based, structured representation from a video. Higgins et al. (2018) learned an implicit hierarchy of abstract concepts from a few symbol-image pairs. Compared with these approaches, our model not only learns to explain observations, but also build a dynamics model that can be used for future prediction.

Physical scene understanding has attracted increasing attention in recent years (Fragkiadaki et al., 2016; Battaglia et al., 2016; Chang et al., 2017; Finn et al., 2016; Ehrhardt et al., 2017; Shao et al., 2014). Researchers have attempted to go beyond the traditional goals of high-level computer vision, inferring "what is where", to capture the physics needed to predict the immediate future of dynamic scenes, and to infer the actions an agent should take to achieve a goal. Most of these efforts do not attempt to learn physical object representations from raw observations. Some systems emphasize learning from pixels but without an explicitly object-based representation (Fragkiadaki et al., 2016; Agrawal et al., 2016), which makes generalization challenging. Others learn a flexible model of the dynamics of object interactions, but assume a decomposition of the scene into physical objects and their properties rather than learning directly from images (Chang et al., 2017; Battaglia et al., 2016; Kipf et al., 2018). A few very recent papers have proposed to jointly learn a perception module and a dynamics model (Watters et al., 2017; Wu et al., 2017; van Steenkiste et al., 2018). Our model moves further by simultaneously discovering the hierarchical structure of object parts.

Another line of related work is on future state prediction in either image pixels (Xue et al., 2016; Mathieu et al., 2016; Lee et al., 2018; Balakrishnan et al., 2018b;a) or object trajectories (Kitani et al., 2017; Walker et al., 2016). Some of these papers, including our model, draw insights from classical computer vision research on layered motion representations (Wang & Adelson, 1993). These papers often fail to model the object hierarchy. There has also been abundant research making use of physical models for human or scene tracking (Salzmann & Urtasun, 2011; Kyriazis & Argyros, 2013; Vondrak et al., 2013; Brubaker et al., 2009). Compared with these papers, our model learns to discover the hierarchical structure of object parts purely from visual observations, without resorting to prior knowledge.

3 FORMULATION

By observing objects move, we aim to learn the concept of object parts and their relationships. Take human body as an example (Figure 1). We want our model to parse human parts (e.g., torso, hands, and legs) and to learn their structure (e.g., hands and legs are both parts of the human body).

(a) Pairs of images   (b) Global motions of parts   (c) Local motions of parts

Figure 2: Knowing that the legs are part of human body, the legs' motion can be decomposed as the sum of the body's motion and the legs' local motion.

Formally, given a pair of images $\{\mathcal{I}_1, \mathcal{I}_2\}$, let $\mathcal{M}$ be the Lagrangian motion map (i.e. optical flow). Consider a system that learns to segment object parts and to capture their motions, without modeling their structure. Its goal is to find a segment decomposition of $\mathcal{I}_1 = \{\mathcal{O}_1, \mathcal{O}_2, \ldots, \mathcal{O}_n\}$, where each segment $\mathcal{O}_k$ corresponds to an object part with distinct motion. Let $\{\mathcal{M}_1^{\mathrm{g}}, \mathcal{M}_2^{\mathrm{g}}, \ldots, \mathcal{M}_n^{\mathrm{g}}\}$ be their corresponding motions.

Beyond that, we assume that these object parts form a hierarchical tree structure: each part k has a parent p_k, unless itself is the root of a motion tree. Its motion $\mathcal{M}_k^{\mathrm{g}}$ can therefore be decomposed into its parent's motion $\mathcal{M}_{p_k}^{\mathrm{g}}$ and a local motion component $\mathcal{M}_k^{\mathrm{l}}$ within its parent's reference frame. Specifically, $\mathcal{M}_k^{\mathrm{g}} = \mathcal{M}_{p_k}^{\mathrm{g}} + \mathcal{M}_k^{\mathrm{l}}$, if k is not a root. Here we make use of the fact that Lagrangian motion components $\mathcal{M}_k^{\mathrm{l}}$ and $\mathcal{M}_{p_k}^{\mathrm{g}}$ are additive.

Figure 2 gives an intuitive example: knowing that the legs are part of human body, the legs' motion can be written as the sum of the body's motion (e.g., moving to the left) and the legs' local motion (e.g., moving to lower or upper left). Therefore, the objective of our model is, in addition to identifying the object components $\{\mathcal{O}_k\}$, learning the hierarchical tree structure $\{p_k\}$ to effectively and efficiently explain the object's motion.

Such an assumption makes it possible to decompose the complex object motions into simple and disentangled local motion components. Reusing local components along the hierarchical structure helps to reduce the description length of the motion map $\mathcal{M}$. Therefore, such a decomposition should naturally emerge within a design with information bottleneck that encourages compact, disentangled representations. In the next section, we introduce the general philosophy behind our model design and the individual components within.

4 METHOD

In this section, we discuss our approach to learn the disentangled, hierarchical representation. Our model learns by predicting future motions and synthesizing future frames without manual annotations. Figure 3 shows an overview of our Parts, Structure, and Dynamics (PSD) model.

4.1 OVERVIEW

Motion can be decomposed in a layer-wise manner, separately modeling different object component's movement (Wang & Adelson, 1993). Motivated by this, our model first decomposes the input frame $\mathcal{I}_1$ into multiple feature maps using an *image encoder* (Figure 3c). Intuitively, these feature maps correspond to separate object components. Our model then performs convolutions (Figure 3d) on these feature maps using separate kernels obtained from a *kernel decoder* (Figure 3b), and synthesizes the local motions $\mathcal{M}_k^{\mathrm{l}}$ of separate object components with a *motion decoder* (Figure 3e). After that, our model employs a *structural descriptor* (Figure 3f) to recover the global motions $\mathcal{M}_k^{\mathrm{g}}$ from local motions $\mathcal{M}_k^{\mathrm{l}}$, and then compute the overall motion $\mathcal{M}$. Finally, our model uses an *image decoder* (Figure 3g) to synthesize the next frame $\mathcal{I}_2$ from the input frame $\mathcal{I}_1$ and the overall motion $\mathcal{M}$.

Our PSD model can be seen as a conditional variational autoencoder. During training, it employs an additional *motion encoder* (Figure 3a) to encode the motion into the latent representation z; during testing, it instead samples the representation z from its prior distribution $p_z(z)$, which is assumed to be a multivariate Gaussian distribution, where each dimension is *i.i.d.*, zero-mean, and unit-variance.

Figure 3: Our PSD model has seven components: **(a)** motion encoder; **(b)** kernel decoder; **(c)** image encoder; **(d)** cross convolution; **(e)** motion decoder; **(f)** structural descriptor; and **(g)** image decoder.

4.2   NETWORK STRUCTURE

We now introduce each component. More details will be discussed in Section A.1.

Motion Encoder.   Our motion encoder takes the flow field $\hat{\mathcal{M}}$ between two consecutive frames as input. It applies multiple convolutional and pooling layers. The output will be a $2d$-dimensional vector, which is then reshaped into a d-dimensional mean vector z_{mean} and a d-dimensional variance vector z_{var}. Finally, the latent motion representation z is sampled from $\mathcal{N}(z_{\text{mean}}, z_{\text{var}})$.

Kernel Decoder.   Our kernel decoder operates on the latent motion representation z. For each of the d dimensions, it applies a *separate* multi-layer fully-connected network to obtain a convolutional kernel. Therefore, each kernel corresponds to one dimension in the latent motion representation z.

Image Encoder.   Our image encoder takes the input frame $\mathcal{I}_1$ as input. It applies multiple convolutional and pooling layers, and the output will be a d-channel feature map. It then resizes the feature map to the input resolution with nearest neighbor sampling.

Cross Convolution.   The cross convolution layer (Xue et al., 2016) applies the convolutional kernels learned by the kernel decoder to the feature maps learned by the image encoder. Here, the convolution operations are carried out in a channel-wise manner (also known as depth-wise separable convolutions in Chollet (2017)): it applies each of the d convolutional kernels to its corresponding channel in the feature map. The output will be a d-channel transformed feature map.

Motion Decoder.   Our motion decoder takes the transformed feature map as input. For each of the d channels, it applies a *separate* multi-layer convolutional network to obtain the corresponding local motion for that dimension $\mathcal{M}_k^{\text{l}}$. Note that the local motion $\mathcal{M}_k^{\text{l}}$ is determined by z_k only.

Structural Descriptor.   Our structural descriptor recovers the global motions $\{\mathcal{M}_k^{\text{g}}\}$ from the local motions $\{\mathcal{M}_k^{\text{l}}\}$ and the hierarchical tree structure $\{p_k\}$ using

$$\mathcal{M}_k^{\text{g}} = \mathcal{M}_k^{\text{l}} + \mathcal{M}_{p_k}^{\text{g}} = \mathcal{M}_k^{\text{l}} + \left(\mathcal{M}_{p_k}^{\text{l}} + \mathcal{M}_{p_{p_k}}^{\text{g}}\right) = \cdots \tag{1}$$

$$= \mathcal{M}_k^{\text{l}} + \sum_{i \in P_k} \mathcal{M}_i^{\text{l}}, \quad \text{where } P_k \text{ is the set of ancestors of } \mathcal{O}_k, \tag{2}$$

$$= \mathcal{M}_k^{\text{l}} + \sum_{i \neq k} [i \in P_k] \cdot \mathcal{M}_i^{\text{l}}. \tag{3}$$

Then, we define the structural matrix $\mathcal{S}$ as $\mathcal{S}_{ik} = [i \in P_k]$. This is what we aim to learn. In practice, we relax the binary constraints on $\mathcal{S}$ to $[0, 1]$ to make this module differentiable. Finally, the overall motion can be simply computed as $\mathcal{M} = \sum_k \mathcal{M}_k^{\text{g}}$.

Image Decoder.   Given the input frame $\mathcal{I}_1$ and the predicted overall motion $\mathcal{M}$, our image decoder applies multiple convolutional and deconvolutional layers to synthesize the future image frame $\mathcal{I}_2$.

4.3   TRAINING DETAILS

Our objective function $\mathcal{L}$ is a weighted sum over three separate components:

$$\mathcal{L} = \mathcal{L}_{\text{recon}} + \beta \cdot \mathcal{L}_{\text{elbo}} + \gamma \cdot \mathcal{L}_{\text{struct}}, \quad \text{where } \beta \text{ and } \gamma \text{ are two weighting factors.} \tag{4}$$

(a) Input frame (b) Next frame (c) Reconstruction (d) Sampled future frames (e) Zoomed-in views (f) Hierarchical tree structure

Figure 4: Results of synthesizing future frames **(a-e)** and learning hierarchical structure **(f)** on shapes

(a) Input frame **(b)** Segmentation masks of different objects **(c)** Hierarchical tree structure

Figure 5: Results of segmenting different shapes **(b)** and learning hierarchical tree structure **(c)** on a dataset with more shapes.

The first component is the *pixel-wise reconstruction loss*, which enforces our model to accurately estimate the motion $\mathcal{M}$ and synthesize the future frame $\mathcal{I}_2$. We have $\mathcal{L}_{\text{recon}} = \|\mathcal{M} - \hat{\mathcal{M}}\|_2 + \alpha \cdot \|\mathcal{I}_2 - \hat{\mathcal{I}}_2\|_2$, where α is a weighting factor (which is set to 10^3 in our experiments).

The second component is the *variational loss*, which encourages our model to use as few dimensions in the latent representation z as possible (Xue et al., 2016; Higgins et al., 2017). We have $\mathcal{L}_{\text{elbo}} = \mathcal{D}_{\text{KL}}\big(\mathcal{N}(z_{\text{mean}}, z_{\text{var}}) \,\|\, p_z(z)\big)$, where $\mathcal{D}_{\text{KL}}(\cdot \,\|\, \cdot)$ is the KL-divergence, and $p_z(z)$ is the prior distribution of the latent representation (which is set to normal distribution in our experiments).

The last component is the *structural loss*, which encourages our model to learn the hierarchical tree structure so that it helps the motions $\mathcal{M}^1$ be represented in the most efficient (i.e. sparse) way: $\mathcal{L}_{\text{struct}} = \sum_{k=1}^{d} \|\mathcal{M}_k^1\|_2$.

During training, we first optimize $\mathcal{L}_{\text{recon}}$ and $\mathcal{L}_{\text{elbo}}$ to learn a *disentangled* representation, and we then jointly optimize the full objective function $\mathcal{L}$ to learn a *hierarchical* representation. More details will be provided in Section A.2.

5 EXPERIMENTS

We evaluate our model on three diverse settings: i) simple yet nontrivial shapes and digits, ii) Atari games of basketball playing, and iii) real-world human motions.

5.1 MOVEMENT OF SHAPES AND DIGITS

We first evaluate our method on shapes and digits. For each dataset, we rendered totally 100,000 pairs for training and 10,000 for testing, with random visual appearance (i.e., sizes, positions, and colors).

For the shapes dataset, we use three types of shapes: circles, triangles and squares. Circles always move diagonally, while the other two shapes' movements consist of two sub-movements: moving together with circles and moving in their own directions (triangles horizontally, and squares vertically). In the supplementary material, we also demonstrate an additional dataset with more shape.

As for the digits dataset, we use six types of hand-written digits from MNIST (LeCun et al., 1998). These digits are divided into two groups: 0's, 1's and 2's are in the first group, and 3's, 4's and 5's in the second group. The movements of digits in the same group have some intrinsic relations, while digits in different groups are independent of each other. In the first group, the tree structure is the same as that of our shapes dataset: replacing circles with 0's, triangles with 1's, and squares with 2's. The second group has a chain-like structure: 3's move diagonally, 4's move together with 3' and move horizontally at the same time, and 5's move with 4's and move vertically at the same time.

After training, our model should be able to synthesize future frames, segment different objects (i.e., shapes and digits), and discover the relationship between these objects.

(a) Input frame **(b)** Next frame **(c)** Reconstruction **(d)** Sampled future frames **(e)** Zoomed-in views **(f)** Hierarchical tree structure

Figure 6: Results of synthesizing future frames **(a-e)** and learning hierarchical structure **(f)** on digits.

Figure 7: Qualitative results of object segmentation on shapes and digits: **(a)** Ground-truth; **(b)** PSD; **(c)** NEM; and **(d)** R-NEM. In this visualization, we superimpose the segmentation masks on images.

	Shapes			Digits					
	Circles	Squares	Triangles	0's	1's	2's	3's	4's	5's
NEM	0.368	0.457	0.348	0.470	0.229	0.322	0.512	0.295	0.251
R-NEM	0.540	0.559	0.583	0.323	0.416	0.339	0.448	0.352	0.326
PSD (ours)	**0.935**	**0.816**	**0.905**	**0.750**	**0.742**	**0.739**	**0.739**	**0.472**	**0.641**

Table 1: Quantitative results (IoUs) of object segmentation on shapes and digits.

Future Prediction. In Figure 4d and Figure 6d, we present some qualitative results of synthesizing future frames. Our PSD model is able to capture the different motion patterns for each object and synthesize multiple possible future frames.

Latent Representation. After analyzing the representation z, we observe that its intrinsic dimensionality is very sparse. On the shapes dataset, there are three dimensions learning useful representations, each of which correspond to one particular shape, while all the other dimensions are very close to the Gaussian noise. Similarly, on digits dataset, there are six dimensions, corresponding to different digits. In further discussions, we will only focus on these meaningful dimensions.

Object Segmentation. For each meaningful dimension, the feature map can be considered as the segmentation mask of one particular object (by thresholding). We evaluate our model's ability on learning the concept of objects and segmenting them by computing the *intersection over union* (IoU) between model's prediction and the ground-truth instance mask. We compare our model with *Neural Expectation Maximization* (NEM) proposed by Greff et al. (2017) and *Relational Neural Expectation Maximization* (R-NEM) proposed by van Steenkiste et al. (2018). For these methods, each object (i.e., shape and digit) is not captured by one consistent dimension. For fair comparison, we manually iterate all possible mappings and select the one with the best performance. We present some qualitative results in Figure 7 and Figure 5b, and quantitative results in Table 1. Our PSD model significantly outperforms two baselines, because they cannot deal with highly occluded objects.

Hierarchical Structure. To discover the tree structure between these dimensions, we binarize the structural matrix and recover the hierarchical structure from it. We compare our PSD model with R-NEM and *Neural Relational Inference* (NRI) proposed by Kipf et al. (2018). As the NRI model requires objects' feature vectors (i.e., location and velocity) as input, we directly feed the coordinates of different objects in and ask it to infer the underlying interaction graph. In Figure 4f and Figure 6f, we visualize the hierarchical tree structure obtained from these models. Our model is capable of discovering the underlying structure; while two baselines fail to learn any meaningful relationships.

(a) Input frame (b) Next frame (c) Reconstruction (d) Offensive player (e) Ball (f) Defensive player (g) Hierarchical tree structure

Figure 8: Results of segmenting objects (**d-f**) and learning hierarchical structure (**g**) on Atari games.

(a) Input frame (b) Next frame (c) Reconstruction (d) Sampled future frames (e) Zoomed-in views

Figure 9: Qualitative results of synthesizing future frames on real-world human motions.

This might be because NRI and R-NEM both assume that the system dynamics is fully characterized by their current states and interactions, and therefore, they are not able to model the uncertainties in the system dynamics. On the challenging dataset with more shapes, our PSD model is still able to discover the underlying structure among them (see Figure 5c).

5.2 ATARI GAMES OF PLAYING BASKETBALL

We then evaluate our model on a dataset of Atari games. In particular, we select the Basketball game from the Atari 2600. In this game, there are two players competing with each other. Each player can move in eight different directions. The *offensive* player constantly dribbles the ball and throws the ball at some moment; while the *defensive* player tries to steal the ball from his opponent player. We download a video of playing this game from YouTube and construct a dataset with 5,000 pairs for training and 500 for testing.

Our PSD model discovers three meaningful dimensions in the latent representation z. We visualize the feature maps in these three dimensions in Figure 8. We observe that one dimension (in Figure 8d) is learning the *offensive player with ball*, another (in Figure 8e) is learning the *ball*, and the other (in Figure 8f) is learning the *defensive player*. We construct the hierarchical tree structure among these three dimensions from the structural matrix $\mathcal{S}$. As illustrated in Figure 8g, our PSD model is able to discover the relationship between the ball and the players: the offensive player *controls* the ball. This is because our model observes that the ball always moves along with the offensive player.

5.3 MOVEMENT OF HUMANS

We finally evaluate our method on two datasets of real-world human motions: the human exercise dataset used in Xue et al. (2016) and the yoga dataset used in Balakrishnan et al. (2018a). We estimate the optical flows between frames by an off-the-shelf package (Liu, 2009). Compared with previous datasets, these two require much more complicated visual perception, and they have challenging hierarchical structures. In the human exercise dataset, there are 50,000 pairs of frames used for training and 500 for testing. As for the yoga dataset, there are 4,720 pairs of frames for training and 526 for testing.

Future Prediction. In Figure 9 and Figure 10, we present qualitative results of synthesizing future frames. Our model is capable of predicting multiple future frames, each with a different motion.

(a) Input frame   **(b)** Next frame   **(c)** Reconstruction   **(d)** Sampled future frames   **(e)** Zoomed-in views

Figure 10: Qualitative results of synthesizing future frames on real-world human motions.

(a) Input frame   **(b)** Flow field   **(c)** Full torso   **(d)** Upper torso   **(e)** Arm   **(f)** Right leg   **(g)** Left leg   **(h)** Hierarchical tree structure

Figure 11: Results of segmenting parts **(c-g)** and learning hierarchical structure **(h)** on human motions.

(a) Input frame   **(b)** Flow field   **(c)** Full torso   **(d)** Left arm   **(e)** Right arm   **(f)** Left leg   **(g)** Right leg   **(h)** Hierarchical tree structure

Figure 12: Results of segmenting parts **(c-g)** and learning hierarchical structure **(h)** on human motions.

Object Segmentation.   In Figure 11 and Figure 12, we visualize the feature maps in several different dimensions. It turns out that each of these dimensions corresponds to one particular human part: full torsos (11c, 12c), upper torsos (11d), arms (11e), left arms (12d), right arms (12e), right legs (11f, 12g), and left legs (11g, 12f). Note that it is extremely challenging to distinguish different parts from motions, because different parts (e.g., arms and legs) might have similar motions (see Figure 11b). R-NEM is not able to segment any meaningful parts, let alone structure, while our PSD model gives imperfect yet reasonable part segmentation results.

Hierarchical Structure.   We recover the hierarchical tree structure among these dimensions from the structural matrix $\mathcal{S}$. From Figure 11h, our PSD model is able to discover that the upper torso and the legs are part of the full torso, and the arm is part of the upper torso, and from Figure 12h, our PSD model discovers that the arms and legs are parts the full torso.

Human Studies.   Determining the object parts is a relatively subjective process; it is impractical to define the ground-truth hierarchical structure. Therefore, it is difficult to conduct a strictly quantitative evaluation. Instead, we conduct the human studies, and it turns out that 13 out of 20 (**65%**) human annotators predict the same tree structure as ours. For these whose predicted tree structures are not consistent with ours, they all agree with our results and believe ours are more reasonable than theirs.

6   CONCLUSION

We have presented a novel formulation that simultaneously discovers object parts, their hierarchical structure, and the system dynamics from unlabeled videos. Our model uses a layered image representation, as well as a structural descriptor that learns to compose basic concepts. Experiments suggest that it works well on both real and synthetic datasets for part segmentation, hierarchical structure recovery, and motion prediction. We hope our work will inspire future research along the direction of learning structural object representations from raw sensory inputs.

REFERENCES

Pulkit Agrawal, Ashvin Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: Experiential learning of intuitive physics. In *NIPS*, 2016. 2

Jimmy Ba, Volodymyr Mnih, and Koray Kavukcuoglu. Multiple object recognition with visual attention. In *ICLR*, 2015. 2

Guha Balakrishnan, Amy Zhao, Adrian V Dalca, Fredo Durand, and John Guttag. Synthesizing images of humans in unseen poses. In *CVPR*, 2018a. 2, 7

Guha Balakrishnan, Amy Zhao, Adrian V Dalca, Fredo Durand, and John Guttag. Synthesizing images of humans in unseen poses. In *CVPR*, 2018b. 2

Peter W. Battaglia, Razvan Pascanu, Matthew Lai, Danilo Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. In *NIPS*, 2016. 2

Marcus A. Brubaker, David J. Fleet, and Aaron Hertzmann. Physics-based person tracking using the anthropomorphic walker. *IJCV*, 87(1-2):140–155, aug 2009. doi: 10.1007/s11263-009-0274-5. 2

Susan Carey. *The origin of concepts*. Oxford University Press, 2009. 1

Michael B Chang, Tomer Ullman, Antonio Torralba, and Joshua B Tenenbaum. A compositional object-based approach to learning physical dynamics. In *ICLR*, 2017. 2

Tian Qi Chen, Xuechen Li, Roger Grosse, and David Duvenaud. Isolating sources of disentanglement in variational autoencoders. *arXiv:1802.04942*, 2018. 2

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NIPS*, 2016. 1, 2

François Chollet. Xception: Deep learning with depthwise separable convolutions. In *CVPR*, 2017. 4

Sebastien Ehrhardt, Aron Monszpart, Niloy J Mitra, and Andrea Vedaldi. Learning a physical long-term predictor. *arXiv:1703.00247*, 2017. 2

SM Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, Koray Kavukcuoglu, and Geoffrey E Hinton. Attend, infer, repeat: Fast scene understanding with generative models. In *NIPS*, 2016. 1, 2

Babak Esmaeili, Hao Wu, Sarthak Jain, Siddharth Narayanaswamy, Brooks Paige, and Jan-Willem van de Meent. Hierarchical disentangled representations. *arXiv:1804.02086*, 2018. 2

Chelsea Finn, Ian Goodfellow, and Sergey Levine. Unsupervised learning for physical interaction through video prediction. In *NIPS*, 2016. 2

Katerina Fragkiadaki, Pulkit Agrawal, Sergey Levine, and Jitendra Malik. Learning visual predictive models of physics for playing billiards. In *ICLR*, 2016. 2

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Neural expectation maximization. In *NIPS*, 2017. 6

Irina Higgins, Loic Matthey, Arka Pal, Christopher P Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. Beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017. 2, 5, 12

Irina Higgins, Nicolas Sonnerat, Loic Matthey, Arka Pal, Christopher P Burgess, Matthew Botvinick, Demis Hassabis, and Alexander Lerchner. Scan: learning abstract hierarchical compositional visual concepts. In *ICLR*, 2018. 2

Geoffrey E Hinton and Drew Van Camp. Keeping the neural networks simple by minimizing the description length of the weights. In *COLT*, 1993. 2

Wei-Ning Hsu, Yu Zhang, and James Glass. Unsupervised learning of disentangled and interpretable representations from sequential data. In *NIPS*, 2017. 2

Jonathan Huang and Kevin Murphy. Efficient inference in occlusion-aware generative models of images. In *ICLR Workshop*, 2015. 1, 2

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015. 12

Gunnar Johansson. Visual perception of biological motion and a model for its analysis. *Perception & Psychophysics*, 14(2):201–211, 1973. 1

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015. 12

Thomas N Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard S Zemel. Neural relational inference for interacting systems. In *ICML*, 2018. 2, 6

Kris M. Kitani, De-An Huang, and Wei-Chiu Ma. Activity forecasting. In *Group and Crowd Behavior for Computer Vision*, pp. 273–294. Elsevier, 2017. doi: 10.1016/b978-0-12-809276-7.00014-x. 2

Kurt Koffka. *Principles of Gestalt psychology*. Routledge, 2013. 1

Tejas D Kulkarni, Pushmeet Kohli, Joshua B Tenenbaum, and Vikash Mansinghka. Picture: A probabilistic programming language for scene perception. In *CVPR*, 2015a. 2

Tejas D Kulkarni, William F Whitney, Pushmeet Kohli, and Josh Tenenbaum. Deep convolutional inverse graphics network. In *NIPS*, 2015b. 2

Nikolaos Kyriazis and Antonis Argyros. Physically plausible 3d scene tracking: The single actor hypothesis. In *CVPR*, 2013. 2

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proc. IEEE*, 86(11):2278–2324, 1998. 5

Jungbeom Lee, Jangho Lee, Sungmin Lee, and Sungroh Yoon. Msnet: Mutual suppression network for disentangled video representations. *arXiv:1804.04810*, 2018. 2

Yingzhen Li and Stephan Mandt. A deep generative model for disentangled representations of sequential data. In *ICML*, 2018. 2

Ce Liu. *Beyond pixels: exploring new representations and applications for motion analysis*. PhD thesis, Massachusetts Institute of Technology, 2009. 7

Andrew L Maas, Awni Y Hannun, and Andrew Y Ng. Rectifier nonlinearities improve neural network acoustic models. In *ICML*, 2013. 12

Michael Mathieu, Camille Couprie, and Yann LeCun. Deep multi-scale video prediction beyond mean square error. In *ICLR*, 2016. 2

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. In *NIPS Workshop*, 2017. 12

Danilo Jimenez Rezende, SM Eslami, Shakir Mohamed, Peter Battaglia, Max Jaderberg, and Nicolas Heess. Unsupervised learning of 3d structure from images. In *NIPS*, 2016. 2

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *MICCAI*, 2015. 12

Mathieu Salzmann and Raquel Urtasun. Physically-based motion models for 3d tracking: A convex formulation. In *ICCV*, 2011. 2

Tianjia Shao, Aron Monszpart, Youyi Zheng, Bongjin Koo, Weiwei Xu, Kun Zhou, and Niloy J Mitra. Imagining the unseen: Stability-based cuboid arrangements for scene understanding. *ACM TOG*, 33(6), 2014. 2

Elizabeth S Spelke and Katherine D Kinzler. Core knowledge. *Dev. Psychol.*, 10(1):89–96, 2007. 1

Sjoerd van Steenkiste, Michael Chang, Klaus Greff, and Jürgen Schmidhuber. Relational neural expectation maximization: Unsupervised discovery of objects and their interactions. In *ICLR*, 2018. 2, 6

Marek Vondrak, Leonid Sigal, and Odest Chadwicke Jenkins. Dynamical simulation priors for human motion tracking. *IEEE TPAMI*, 35(1):52–65, 2013. 2

Jacob Walker, Carl Doersch, Abhinav Gupta, and Martial Hebert. An uncertain future: Forecasting from static images using variational autoencoders. In *ECCV*, 2016. 2

John YA Wang and Edward H Adelson. Layered representation for motion analysis. In *CVPR*, 1993. 2, 3

Nicholas Watters, Andrea Tacchetti, Theophane Weber, Razvan Pascanu, Peter Battaglia, and Daniel Zoran. Visual interaction networks. In *NIPS*, 2017. 2

Jiajun Wu, Erika Lu, Pushmeet Kohli, Bill Freeman, and Josh Tenenbaum. Learning to see physics via visual de-animation. In *NIPS*, 2017. 2

Tianfan Xue, Jiajun Wu, Katherine Bouman, and Bill Freeman. Visual dynamics: Probabilistic future frame synthesis via cross convolutional networks. In *NIPS*, 2016. 2, 4, 5, 7

A.1 NETWORK DETAILS

In this section, we present some network details of our Parts, Structure, and Dynamics (PSD) model.

Dimensionality. The hyperparameter d is set to 32, which determines the *maximum* number of objects we are able to deal with. During training, the variational loss encourages our model to use as few dimensions in the latent representation z as possible, and consequently, there will be only a few dimensions learning useful representations, each of which correspond to one particular object, while all the other dimensions will be very close to the Gaussian noise.

Motion Encoder. Our motion encoder takes the flow field $\mathcal{M}$ between two image frames as input, with resolution of 128×128. The network then applies seven convolutional layers with number of channels $\{16, 16, 32, 32, 64, 64, 64\}$, kernel sizes 5×5, and padding sizes 2. Between convolutional layers, there are batch normalizations (Ioffe & Szegedy, 2015), Leaky ReLUs (Maas et al., 2013) with slope 0.2, and max-pooling layers of size 2×2. The output will have a size of $64 \times 1 \times 1$.

Kernel Decoder. Our kernel decoder consists of 32 separate fully connected networks, decoding the representation z to the convolutional kernels of size $32 \times 5 \times 5$. Within each network, we make uses four fully connected layers with number of hidden units $\{64, 128, 64, 25\}$. In between, there are batch normalizations and ReLU layers.

Image Encoder. Our image encoder applies six convolutional layers to the image, with number of channels $\{32, 32, 64, 64, 32, 32\}$, kernel sizes 5×5, and padding sizes 2, two of which are followed by an additional 2×2 max-pooling layer. We then upsample the feature maps by $4 \times$, and finally, the resolution of feature maps will be 128×128.

Motion Decoder. Our motion decoder estimates the x-axis and y-axis motions separately. For each axis, the network applies two 9×9, two 5×5 and two 1×1 depthwise separable convolutional layers, all with 32 channels. We stack the outputs from two branches together. The output motion will have a size of $32 \times 128 \times 128 \times 2$.

Image Decoder. We stack the input frame and overall motion together into a multi-channel image, and then, we employ the U-Net (Ronneberger et al., 2015) to synthesis the future frame.

A.2 TRAINING DETAILS

We implement our PSD model in PyTorch (Paszke et al., 2017). Optimization is carried out using ADAM (Kingma & Ba, 2015) with $\beta_1 = 0.9$ and $\beta_2 = 0.999$. We use a fixed learning rate of 10^{-3} and mini-batch size of 32. We propose the two-stage optimization schema, which first learns the disentangled and then learns the hierarchical representation.

In the first stage, we encourage the model to learn a *disentangled* representation (without structure). We set the γ in Equation 4 to 0 and fix the structural matrix $\mathcal{S}$ to the identity $\mathcal{I}$. The β in Equation 4 is the same as the one in the β-VAE (Higgins et al., 2017), and therefore, larger β's encourage the model to learn a more disentangled representation. We first initialize the β to 0.1 and then adaptively double the value of β when the reconstruction loss reaches a preset threshold.

In the second stage, we train the model to learn the *hierarchical* representation. We fix the weights of motion encoder and kernel decoder, and set the β to 0. We initialize the structural matrix $\mathcal{S}$, and optimize it with the image encoder and motion decoder jointly. We adaptively tune the value of γ in the same way as the β in the first stage.

A.3 ADDITIONAL DATASET WITH MORE SHAPES

We also construct an additional dataset with up to nine different shapes. We assign these shapes into four different groups: i) square and two types of parallelograms, ii) circle and two types of triangles, iii) two types of trapezoids, and iv) pentagon. The movements of shapes in the same group have intrinsic relations, while shapes in different groups are independent of each other. These nine shapes have their own different motion direction. In the first group, the tree structure is the same as that of our original shapes dataset: replacing circles with squares, triangles with left parallelograms, and squares with right parallelograms. In the second group, circle and two types of triangles form a chain-like structure, which is similar to the one in our digits dataset. In the third group, the structure is a chain contains two types of trapezoids. In the last group, there is only a pentagon.

A.4 MORE QUALITATIVE RESULTS

In Figure A1, we demonstrate more future prediction results on shapes and digits dataset. In Figure A2, we present several segmentation results on shapes (with more objects), exercise and yoga dataset.

(a) Input frame (b) Next frame (c) Reconstruction (d) Sampled future frames (e) Zoomed-in views

Figure A1: Additional results of future prediction on shapes and digits dataset.

(a) Input frame (b) Segmentation masks of different objects

(a) Input frame (b) Flow field (c) Full torso (d) Upper torso (e) Arm (f) Right leg (g) Left leg

(a) Input frame (b) Flow field (c) Full torso (d) Left arm (e) Right arm (f) Left leg (g) Right leg

Figure A2: Additional results of segmentation on shapes, exercise and yoga dataset.