ADVERSARIAL POLICY GRADIENT FOR ALTERNATING MARKOV GAMES

ABSTRACT

Policy gradient reinforcement learning has been applied to two-player alternate-turn zero-sum games, e.g., in AlphaGo, self-play REINFORCE was used to improve the neural net model after supervised learning. In this paper, we emphasize that two-player zero-sum games with alternating turns, which have been previously formulated as Alternating Markov Games (AMGs), are different from standard MDP because of their two-agent nature. We exploit the difference in associated Bellman equations, which leads to different policy iteration algorithms. As policy gradient method is a kind of generalized policy iteration, we show how these differences in policy iteration are reflected in policy gradient for AMGs. We formulate an adversarial policy gradient and discuss potential possibilities for developing better policy gradient methods other than self-play REINFORCE. The core idea is to estimate the *minimum* rather than the *mean* for the "critic". Experimental results on the game of Hex show the modified Monte Carlo policy gradient methods are able to learn better pure neural net policies than the REINFORCE variants. To apply learned neural weights to multiple board sizes Hex, we describe a board-size independent neural net architecture. We show that when combined with search, using a single neural net model, the resulting program consistently beats MoHex 2.0, the state-of-the-art computer Hex player, on board sizes from $9{\times}9$ to $13{\times}13$. We further show that integrating *minimum* playout return to Monte Carlo tree search provides additional improvements on $13{\times}13$ Hex.

1 INTRODUCTION

Reinforcement Learning (RL) is a trial-and-error paradigm where an agent learns by interacting with an environment. The *prediction* problem in RL seeks to learn the true value function of a following policy, while the *control* problem aims to find an optimal policy that maximizes the long-term expected cumulative reward. The environment is assumed to be a Markov Decision Process (MDP) (Bellman, 1957). Compared to dynamic programming, RL methods have the advantage of being model-free which learn by treating the environment as a black box. Dynamical programming is theoretically fundamental to reinforcement learning (Bertsekas & Tsitsiklis, 1996), as almost all RL algorithms are a form of *generalized policy iteration*, which improve the policy while estimating a value function (Sutton & Barto, 2017).

Model-free reinforcement learning methods have been successfully applied to many domains, including robotics (Kober et al., 2013), Atari games (Mnih et al., 2015; 2016; Schaul et al., 2016), and two-player board games (Tesauro, 1995; Silver et al., 2016). Most RL algorithms fall into one of two categories: value fitting and policy gradient. The value-fitting algorithms try to optimize a value function through iteratively minimizing a sequence of Bellman inconsistencies of observed states or state-action pairs, examples are on-policy SARSA (Rummery & Niranjan, 1994) and off-policy Q-learning (Watkins & Dayan, 1992). An optimal deterministic policy is implicitly learned when the value function converges to optimal.

The primary disadvantage of value-fitting methods such as Q-learning (Watkins & Dayan, 1992; Mnih et al., 2015; Wang et al., 2016; Mnih et al., 2016) is that they might be unstable when interacting with function approximation (Bertsekas & Tsitsiklis, 1996; Sutton et al., 2000). To gain stable behavior, often extra heuristic techniques (Lin, 1992; Schaul et al., 2016) and extensive hyper-parameter tuning are required. By contrast, policy gradient methods explicitly represent a policy as

a function of parameters: they learn through iteratively adjusting the parameterized policy by following estimation of gradients, thus converging to at least a local maximum (Peters & Bagnell, 2011). Policy gradients are applicable to continuous control (Silver et al., 2014; Schulman et al., 2015; 2017) or domains with large action space (Silver et al., 2016), whereas action-value learning methods often become infeasible (Lillicrap et al., 2016; Wang et al., 2017).

Both value and policy based reinforcement learning are well-studied in MDPs, where a single agent learns by exploiting a stationary environment. In this paper, we focus on policy gradient methods for two-player zero-sum games played in alternating turns, i.e., Alternating Markov Games (AMGs) (Littman, 1996). AMGs are a specialization of Stochastic Games (Shapley, 1953) but a generalization of MDPs by allowing exactly two players pursing diametrical goals. Many popular two-player games are of such kind, such as chess, checkers, backgammon and Go. The restriction of zero-sum in AMGs makes it possible to define a shared reward function such that one agent tries to maximize while the other agent tries to minimize it. Due to such a property, with a notion of *self-play* policy, standard reinforcement learning methods have been successfully applied to AMGs (Tesauro, 1995; Silver et al., 2016) by simply negating the reward signal of the opponent's turn.

In this paper, we reexamine the justifications of adapting standard reinforcement learning methods to AMGs. We begin by reviewing the fundamental differences in their corresponding Bellman equations, from which we show how the resulting policy iteration algorithms are disparate. We formulate an adversarial policy gradient objective specifically for AMGs, based on which we develop new policy gradient methods for AMGs. Specifically, we apply our approach to the game of Hex. We show that by modifying REINFORCE to estimate the *minimum* rather than the *mean* return of a self-play policy, stronger pure neural net players are obtained.

2 FINITE MDP

A finite MDP is a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{R}, \mathcal{P}, \gamma)$ where $\mathcal{S}$ is finite set of states, $\mathcal{A}$ is a set of actions, $\mathcal{R} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a reward function, and $\mathcal{P}$ defines the probabilistic transitions among states. An agent lives in an environment characterized by the Markov property, i.e., $\Pr(s_{t+1}|s_1, a_1, \ldots, s_t, a_t) = \Pr(s_{t+1}|s_t, a_t)$. The agent learns by receiving reward signals from interacting with the environment. The goal is to maximize the expected discounted cumulative reward: $\mathbb{E} \sum_{k=t}^{\infty} \gamma^{t-k} R_{t-k+1}$, where γ is a discounting factor $0 < \gamma \leq 1$ that controls the contribution of long-term and short-term rewards; $\gamma = 1$ is only possible in episodic tasks.

The basis for reinforcement learning in MDP is a set of *Bellman Equations*. For a given policy π:

$$v_\pi(s) = \sum_a \pi(s, a) \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma v_\pi(s')), \tag{1}$$

where $p(s'|s, a)$ is the transition function and $r(s, a, s')$ is the reward of taking a at s, leading to s'.

It is also popular to use an action-value function:

$$q_\pi(s, a) = \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma v_\pi(s')) \tag{2}$$

The above Bellman equations are the basis for *policy evaluation*, which computes the true value function for a given π. This corresponds to the *prediction* problem in RL. The *Optimal Bellman Equation* is a recursive relation for the optimal policy:

$$v_*(s) = \max_a \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma v_*(s'), \tag{3}$$

$$q_*(s, a) = \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma \max_{a'} q_*(s', a')). \tag{4}$$

A value iteration procedure derived by the above optimal Bellman equation converges to optimal (Bellman, 1957). Alternatively, it is also possible to derive a *policy iteration* (Howard, 1960; Bertsekas & Tsitsiklis, 1996) by combining Equation (1) and (3). In reinforcement learning, the precise model is usually assumed to be unknown. Learning typically interleaves *policy evaluation* and *policy improvement*, which is summarized as generalized policy iteration (Sutton & Barto, 2017).

3 ALTERNATING MARKOV GAMES

Alternating Markov Games (AMG) are a specialization of Stochastic Games with only two players: an AMG is a tuple $(\mathcal{S}_1, \mathcal{S}_2, \mathcal{A}_1, \mathcal{A}_2, \mathcal{R}, \mathcal{P}, \gamma)$ where $\mathcal{S}_1$ and $\mathcal{S}_2$ are respectively *this* and *other* agent's states, $\mathcal{A}_1$ and $\mathcal{A}_2$ are the actions at each player's states. MDPs can be viewed as a special case of AMGs by restricting $|\mathcal{S}_2| = 0$.

Since there are two players in AMGs, *policy evaluation* involves two policies, i.e., π_1 and π_2. Bellman equations for policy evaluation are:

$$\begin{cases} v_{\pi_1}(s) = \sum_a \pi_1(a|s) \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma v_{\pi_2}(s')), s \in \mathcal{S}_1 \text{ and } s' \in \mathcal{S}_2 \\ v_{\pi_2}(s) = \sum_a \pi_2(a|s) \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma v_{\pi_1}(s')), s \in \mathcal{S}_2 \text{ and } s' \in \mathcal{S}_1 \end{cases} \quad (5)$$

Action-value functions can also be defined:

$$\begin{cases} q_{\pi_1}(s,a) = \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma \sum_{a'} \pi_2(a'|s')q_{\pi_2}(s',a')), s \in \mathcal{S}_1 \text{ and } s' \in \mathcal{S}_2 \\ q_{\pi_2}(s,a) = \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma \sum_{a'} \pi_1(a'|s')q_{\pi_1}(s',a')), s \in \mathcal{S}_2 \text{ and } s' \in \mathcal{S}_1 \end{cases} \quad (6)$$

Let π_1 be the max player and π_2 be the min player. Assuming the π_2 is an optimal "counter policy" with respect to π_1, we may rewrite the above equation as:

$$q_{\pi_1}(s,a) = \sum_{s'} p(s'|s,a) \left\{ r(s,a,s') + \gamma \min_{a'} \sum_{s''} p(s''|s',a') \right.$$
$$\left. \left[r(s',a',s'') + \sum_{a''} \pi_1(a''|s'')q_{\pi_1}(s'',a'') \right] \right\}, \quad (7)$$
$$\text{where } s \in \mathcal{S}_1, s' \in \mathcal{S}_2 \text{ and } s'' \in \mathcal{S}_1.$$

The replacement of π_2 with a $\min$ operator is caused by the observation that, since π_1 is fixed, the problem reduces to a single-agent MDP where an agent tries to minimize the recevied rewards.

The optimal Bellman equation (also implies Nash equilibrium) can be expressed as:

$$\begin{cases} v^*(s) = \max_a \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma v^*(s')), s \in \mathcal{S}_1 \text{ and } s' \in \mathcal{S}_2, \\ v^*(s) = \min_a \sum_{s'} p(s'|s,a)(r(s,a,s') + \gamma v^*(s')), s \in \mathcal{S}_2 \text{ and } s' \in \mathcal{S}_1, \end{cases} \quad (8)$$

assuming that states in $\mathcal{S}_1$ belongs to the max player, the other one is the min player. A *value iteration* algorithm according to this minimax recursion converges to optimal (Condon, 1992). However, because the *policy evaluation* in AMGs consists of two policies π_1, π_2, the policy iteration, which alternates between policy evaluation and policy improvement, could have the following four formats:

Algo.1 Fix π_1^t, compute the optimal counter policy π_2^t, then fix π_2^t, compute the optimal counter policy π_1^{t+1}, alternating this procedure repeatedly,

Algo.2 Policy evaluation with π_1^t, π_2^t, switch both π_1^t and π_2^t to greedy policies with respect to current state-value function, continue this procedure repeatedly,

Algo.3 Policy evaluation with π_1^t, π_2^t, switch π_1^t to greedy policy with respect to the current state-value function and then compute the optimal counter policy for π_2^t, continue this procedure repeatedly,

Algo.4 Policy evaluation with π_1^t, π_2^t, switch π_2^t to greedy policy with respect to the current state-value function and then compute the optimal counter policy for π_1^t, continue this procedure repeatedly.

Intuitively speaking, all of those procedures are somewhat sensible, and perhaps would yield practical success. However, Condon (1990) showed that oscillation could be a problem that prevents **Algo.1** and **Algo.2** from converging, only **Algo.3** and **Algo.4** are correct, guaranteed to converge in general (Hoffman & Karp, 1966). **Algo.3** and **Algo.4** are duals. Variants of **Algo.3** or **Algo.4**, such as only switching one node to greedy every iteration then optimize the other player's strategy, are also correct, although they may have slower convergence rate (Condon, 1990).

4 ADVERSARIAL POLICY GRADIENT

Before presenting adversarial policy gradient for AMGs, we first review policy gradient in single agent MDP. In MDP, the strength of a policy π can be measured by (for brevity, we implicitly state that the policy is parameterized by θ):

$$J(\pi) = \sum_{s \in \mathcal{S}} d^\pi(s) \sum_a \pi(a|s) q_\pi(s, a), \tag{9}$$

where $d^\pi(s)$ is a state distribution under π. The gradient of $J(\pi)$ is:

$$\nabla J(\pi) = \sum_{s \in \mathcal{S}} d^\pi(s) \sum_a \pi(a|s) \nabla \log \pi(a|s) q_\pi(s, a) \tag{10}$$

The above formula is the Policy Gradient Theorem in MDP (Sutton et al., 2000), which implies that the gradient of the strength of a policy can be estimated by sampling according to π. The requirements are 1) π is differentiable, and 2) $q_\pi(s, a)$ can be estimated. This theorem can also be interpreted as a kind of generalized policy iteration, where the gradient ascent corresponds to policy improvement (Kakade, 2002), and $q_\pi(s, a)$ is obtained by some policy evaluation. Depending on how $q_\pi(s, a)$ is estimated, policy gradient algorithms can be categorized into two families: Monte carlo policy gradients that use Monte carlo to estimate q_π, e.g., REINFORCE (Williams, 1992) and actor-critic methods (Sutton et al., 2000; Wang et al., 2017) that use another parameter to approximate the action-value under π. Recent approaches (Gu et al., 2017) interpolate both.

Analogously, in AMGs, the joint strength for a pair of parameterized policies π_1 and π_2 may be defined as:

$$J(\pi_1, \pi_2) = \sum_s d^{\pi_1, \pi_2}(s) \sum_a \pi_1(a|s) q_{\pi_1}(s, a), \tag{11}$$

where $d^{\pi_1, \pi_2}(s)$ is the state-distribution given π_1 and π_2. A natural question is what is the gradient of $J(\pi_1, \pi_2)$ with respect to π_1 and π_2 respectively? One tempting derivation is to calculate the the gradient for both π_1 and π_2 simultaneously by treating the other policy as the "environment". Similar to the mutual greedy improvement in **Algo.2**, such a method tries to adapt based on the value function under current π_1, π_2, ignoring the fact that the opponent is a dynamic adversary who will also adapt its strategy for better counter-payoffs. Another possible algorithm is to fix π_1 and do a fix number of iterations to optimize π_2 by normal policy gradient as in MDP, and then fix π_2 for optimizing π_1, repeat such alternatively. However, this algorithm is an analog to **Algo.1**, which was shown to be non-convergent in general.

Following **Algo.3** and **Algo.4**, given the action-value function under π_1, π_2, a more reasonable approach for policy improvement is thus to switch π_2 to "greedy" (not necessary every node of π_2) and optimize π_1 by policy gradient. Therefore, assuming π_1 is the max player, we advocate the following objectives

$$\begin{cases} J^{\pi_1}(\pi_1, \pi_2) = \sum_s d^{\pi_1, \pi_2}(s) \sum_a \pi_1(a|s) \sum_{s'} p(s'|s, a) \left[r(s, a, s') + \gamma \min_{a'} q_{\pi_2}(s', a') \right] \\ J^{\pi_2}(\pi_1, \pi_2) = \sum_s d^{\pi_1, \pi_2}(s) \sum_a \pi_2(a|s) \sum_{s'} p(s'|s, a) \left[r(s, a, s') + \gamma \max_{a'} q_{\pi_1}(s', a') \right]. \end{cases} \tag{12}$$

Consequently, the gradients can be estimated by

$$\begin{cases} \nabla J^{\pi_1}(\pi_1, \pi_2) = \mathbb{E}_{\pi_1, \pi_2} \left[\nabla \log \pi_1(a|s) \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma \min_{a'} q_{\pi_2}(s', a')) \right] \\ \nabla J^{\pi_2}(\pi_1, \pi_2) = \mathbb{E}_{\pi_1, \pi_2} \left[\nabla \log \pi_2(a|s) \sum_{s'} p(s'|s, a)(r(s, a, s') + \gamma \max_{a'} q_{\pi_1}(s', a')) \right]. \end{cases} \tag{13}$$

The above formulation implies that, when computing the gradient for one policy, the other policy is simultaneously switched to "greedy". This joint-change forces the current player to adjust the action preferences according to the worst-case response of the opponent, which is desirable due to the adversarial nature of the game.

4.1 ADVERSARIAL MONTE CARLO POLICY GRADIENT

A straightforward implementation of Equation (12) is to obtain separate Monte carlo estimates for each next-action, and then apply the $\min$ or $\max$ operator. However, this may not be practically

feasible when the action space is large. We introduce a parameter k, by which only a subset of actions are considered in our adversarial Monte-Carlo policy gradient design.

As a minimal modification on self-play REINFORCE, the algorithm works as follows: after a batch of n games is generated by a self-play policy with game results, for each game, a single state-action pair (s, a) is sampled uniformly as a training example. However, instead of directly using the observed return z in batch as the estimated action-value for (s, a), we perform extra Monte carlo simulations to estimate the *minimum* return for (s, a). In below are two methods we propose:

> **AMCPG-A:** Run k self-play games from (s, a) using self-play policy π, then take the minimum of the k additional returns and z.

> **AMCGP-B:** Sample a s' from (s, a) according to state-action transition $p(\cdot|s, a)$, select top k actions suggested by π, for each selected action, obtain an Monte carlo estimate using self-play policy π, then take the minimum of the k additional returns and z.

Note that only "minimum" is used, because we assume the game result is with respect to the player to play at state s. It is easy to see that in **AMCPG-A**, if *mean* operator is used rather than *minimum*, a self-play REINFORCE variant is recovered. When $k = |\mathcal{A}(s')|$, **AMCPG-B** becomes a genuine implementation of Equation (12), but in this situation, even though each action-value's estimation is unbiased, bias could still be incurred when applying the $\min$ or $\max$. This is known as the "winner's curse" problem (Capen et al., 1971; Smith & Winkler, 2006).

We note that, as in MDPs, another possible direction is to implement Equation (12) in an adversarial actor-critic framework. The difference is that a $\min$ operator will be used when estimating the "critic". In practice, when neural net is used as a function approximator, the minimum action-value would be easier to obtain by employing an architecture with both policy and action-value outputs. More desirably, as in Q-learning (Fox et al., 2016), bias might be alleviated by certain soft $\min$ operators.

5 RELATED WORK

Games are studied by different disciplines, including game theory, reinforcement learning and computational complexity. Shapley (1953) introduced the notion of Stochastic Games, which is a multi-player framework that generalizes both Markov Decision Process (only one player) and repeated games (only one state). Condon (1990; 1992) initiated the study of *Simple Stochastic Games*, which are two-player games played on a directed graph with min, max and restricted probabilistic transition nodes. While her concern was largely from a computational complexity perspective, Condon (1990) showed that several variants of Hoffman-Karp's algorithms are incorrect. Littman (1996) formulated the notion of Alternating Markov Games, which is more general than *Simple Stochastic Games* by removing the restriction in action sets and probabilistic transitions. Littman (1994) proposed a minimax-Q learning algorithm that is applicable to Alternating Markov Games as well as two-player zero-sum games played with matrix payoffs.

One of the most noticeable study that uses reinforcement learning to play AMGs is by Tesauro (1995), who trained multi-layer neural network to play backgammon. Tesauro's program takes advantage of the symmetric (due to alternating and zero-sum) property of AMGs and learns the optimal value function by "greedy" self-play, relying on the stochastic environment for exploration. It was conjectured that the smoothness of the value function is one major factor for the particular success of TD-Gammon (Tesauro, 1995).

The recent advances of reinforcement learning are arguably primarily due to the use of deep neural networks (LeCun et al., 2015) as a much more expressive function approximator. Deep neural nets have been applied the game of Go (Maddison et al., 2015; Tian & Zhu, 2016; Clark & Storkey, 2015), leading to super-human Go-playing system AlphaGo (Silver et al., 2016). AlphaGo consists of several components including supervised learning for move prediction, reinforcement learning and Monte Carlo Tree Search (MCTS) (Coulom, 2006). Most recent AlphaGo Zero uses a "heavy" self-play based on MCTS to improve its parameterized neural net (Silver et al., 2017b). A similar approach is Expert Iteration (Anthony et al., 2017). One drawback of such methods is their huge computational cost when using MCTS self-play for data generation. For example, when applied to Shogi and chess, 5000 TPUs were used (Silver et al., 2017a).

Policy gradient reinforcement learning is a conventional fast RL method that can be used to refined a neural net policy by pure neural net self-play. In AlphaGo (Silver et al., 2016), policy gradient RL is used to improve the neural network model obtained by supervised learning. The improved model was less useful in search, much because its strong bias towards a single move. However, due to its better playing strength and fast speed, it was used to generate training data for a value net (Silver et al., 2016), which can be integrated into Monte carlo tree search. The policy gradient employed by AlphaGo is a variant of self-play REINFORCE that resembles **Algo.2**. A practical innovation is to select an opponent parameter from a pool of previous parameters, so as to increase the stability of the training. Policy gradient has also been applied to train a balanced policy (Silver & Tesauro, 2009); however, the requirement of an optimal supervision makes it less useful in practice (Huang et al., 2010).

Adversarial methods have also been adopted in MDP (Pinto et al., 2017), since errors may occur in simulated models, maximizing a worst-case return will generally produce more robust results. The alternating procedure proposed by Pinto et al. (2017) resembles **Algo.1**. The idea of adversarial learning is also used in generative models (Goodfellow et al., 2014), which leverage adversarial examples to train a more robust classifier.

6 EXPERIMENTS

In this section, we present experimental results of the proposed adversarial Monte carlo policy gradient algorithms of Section 4. We first introduce the game of Hex as a testbed, then present experimental results.

6.1 GAME OF HEX

The game of Hex is played on a $N \times N$ rhombus board, where black and white alternately place a stone on an unoccupied hexagonal cell. The goal is to connect two opposite sides of the board. Since its invention, the game of Hex has been an active research problem for mathematicians (Nash, 1952) and computer scientists (Shannon, 1953). Nash (1952) proved by strategy stealing argument that from the empty board, the game theoretic value is a first-player win. However, an explicit winning strategy is unclear — after an arbitrary opening move on the board, the theoretical result become unknown. Hex board can also be mapped into a Go-style grid, on which stones are played at intersections, as shown in Figure 1 (left). Usually 11×11 is considered as a regular board size; 13×13 is also played at computer Olympiad Hex tournaments.

Hex is challenging to play primarily because of its large and near-uniform branching factor and the difficulty of constructing a reliable evaluation function. One character that makes Hex simpler is that perfect play can sometimes be achieved whenever winning virtual connections are found by H-Search (Anshelevich, 2002).

Similar to the previous work in Go, we use deep convolutional neural networks as a function approximator. Figure 1(right) shows our architecture. Instead of fixing the board size, we design an architecture that receives multiple board size inputs, this can be achieved by having multiple parallel inputs with different shape when building the computation graph using Tensorflow (Abadi et al., 2016). Our architecture allows board sizes $8 \leq N \leq 15$. After padding, each raw board state is processed into 12 binary feature planes, which are: black stones, white stones, empty points, to-play, black bridge endpoints, white bridge endpoints, to-play save bridge points, to-play make-connection points, to-play form bridge points, opponent save bridge points, opponent form bridge points, opponent make-connection points.

6.2 RESULTS

6.2.1 PURE NEURAL NET POLICY GRADIENT

We apply policy gradient reinforcement learning to improve a policy net which was trained by supervised learning. In addition to our proposed adversarial Monte carlo policy gradient algorithms, for comparison purposes, we implement three REINFORCE variants:

(a) A regular Hex board in Go-style representation. Stones are played at intersections. A player wins by connecting their two sides by a group of their stones.

(b) Neural network architecture: It accepts different board size inputs, padded with an extra border using black or white stones.

Figure 1: Hex board (left) and neural network design (right)

- REINFORCE-V: Vanilla REINFORCE using a parameterized self-play policy. After a batch of n self-played games, each game is then replayed to determine batch policy gradient update $\frac{\alpha}{n} \sum_i^n \sum_t^{T_i} \nabla \log \pi(s_t^i, a_t^i; \theta) z_t^i$, where z_t^i is either $+1$ or -1.

- REINFORCE-A: An "AlphaGo-like" REINFORCE. It differs from REINFORCE-V by randomly selecting a set of previously saved parameter weights from former iterations as the opponent for self-play.

- REINFORCE-B: For each self-played game, only one state-action pair is uniformly selected for policy gradient update. It differs from AMCPG-A by using the mean of all $k + 1$ observed returns.

All methods are implemented using Tensorflow, sharing the same code base. They only differ in a few lines of code. A self-play policy is employed for all algorithms, which is equivalent to forcing π_1 and π_2 to share the same set of parameters. The game batch size n is set to 128. For each self-play game, the opening move is played uniform randomly. Learning rate is set to 0.001 after a grid search, vanilla stochastic gradient ascent is used as the optimizer. The reward signal $z \in \{+1, -1\}$ only appears after a complete self-play game; no discounting is used. For all algorithms, the same neural net architecture is adopted. The initial parameter weights were obtained from supervised learning on a dataset generated by MoHex (Henderson, 2010) self-play on board size 9×9. This supervised learning is only on 9×9 Hex. Because there is no board-size dependent fully connected layers in our architecture, the parameter weights can also be reused on other board sizes as the starting policy.

We run policy gradient reinforcement learning for 400 iterations for each method, on two different board sizes, 9×9 and 11×11, varying $k \in \{1, 3, 6, 9\}$. We use the open source player Wolve [1] (Henderson, 2010) as a benchmark to measure the relative performance of our learned models. After every 10 iterations, model weights are saved and then evaluated by playing against 1-ply Wolve. The primary strength of Wolve comes from its inferior cell analysis augmented H-Search, enabling it to discover winning strategies for perfect play much earlier than unenhanced H-Search. Wolve uses position evaluation with electric resistance evaluation (Anshelevich, 2002; Henderson, 2010) if no winning virtual connection can be found. Starting from trivial virtual connections (e.g., bridge pattern), H-Search (Anshelevich, 2002) computes larger virtual connections by iteratively applying an AND-OR combination rule, such a process is orders of magnitude slower than a pure neural net

---

[1] http://benzene.sourceforge.net/

Figure 2: Comparison of playing strength against Wolve on 9×9 and 11×11 Hex with different k. The curves represent the average winrate among 10 trials with Wolve as black and white.

evaluation using GPU. The tournaments with Wolve are played by iterating all opening moves, each repeated 5 times with Wolve as black or white.

Figure 2 compares the strength of these five different algorithms. REINFORCE-B is able to achieve similar performance with REINFORCE-V, even though the number of training samples used in the former algorithm is significantly less. This is perhaps because the reward signal in the same game is too much correlated. Consistent with the finding in Go (Silver et al., 2016), REINFORCE-A obtained small performance improvements on both 9×9 and 11×11 Hex. However, the newly developed algorithms AMCPG-A and AMCPG-B are able to learn better polices. They tend to learn faster, and generally achieve better results even when $k = 1$. The better performances are more clear on regular board size 11×11. Those results confirm the benefit of estimating the *minimum*, rather than *mean* return, when applying policy gradient methods to Alternating Markov Games.

The policy gradient training on both 9×9 and 11×11 Hex is very fast. On an Intel i7-6700 CPU computer with single GTX 1080 GPU, most took only a few hours. The longest training runs by AMCPG-A, AMCPG-B and REINFORCE-B ($k = 9$, 11×11 Hex) took about 12 hours. For $k = 3$ case, AMCPG-A, AMCPG-B and REINFORCE-B are about twice slower than REINFORCE-V and REINFORCE-A.

6.2.2 MINIMUM RETURN IN MONTE CARLO TREE SEARCH

In the previous section we have shown that policy gradient can benefit from minimum Monte Carlo return. State-of-the-art methods for Hex use Monte carlo tree search, which can be viewed as using the Monte-Carlo return as a "critic" to guide a tree represented policy. To further see the effect of using worst-case "critic" in MCTS, we proceed to apply minimum rollout return to MoHex 2.0 (Huang et al., 2013), the world champion Hex player since 2013. Mohex 2.0 is an improved version of MoHex 2011 (Arneson et al., 2010), with stronger virtual connection (Pawlewicz et al., 2015) for knowledge computation when the visit count of a node exceeds a threshold, better *in-tree* selection formula, pattern based prior knowledge and pattern based playout.

In the MCTS of MoHex 2.0, after an *in-tree* phase, a leaf node is selected, and then one or more rollouts are conducted by a fast playout policy trained on 13×13 expert Hex games. MoHex 2.0 back-propagates the average rollout result to the tree. Following the same idea as in the previous section, we modify MoHex 2.0 to use the minimum of the rollout results instead. To see the strength of minimum return, we experimentally compare three programs: MoHex 2.0, MoHex-A and MoHex-Mixed. For all programs, at each leaf node, 2 playouts are conducted. The difference between MoHex-A and MoHex 2.0 is that MoHex-A backs up the minimum playout results (w.r.t the player to play at the leaf) while MoHex 2.0 uses average playout results. MoHex-Mixed uses the linear combination of the minimum and average return, with factors 0.5 and 0.5.

Table 1 summarizes the results. Both MoHex-A and MoHex-Mixed have slightly better performance against MoHex 2.0, due to their deliberate consideration of minimum "critics".

Table 1: Winrates of MoHex-A and MoHex-Mixed against MoHex 2.0 with same number of simulations. All programs use the default parameters same as MoHex 2.0 except that *number_playouts_per_visit* is set to 2. On board size 13×13, every opening was tried 10 times with each player as black or white. 1690 games were played for each match.

Player	#Simulations	MoHex2.0 was white	MoHex2.0 was black	Overall winrate
MoHex-A	10^4	62.1%	43%	52.5%
MoHex-Mixed	10^4	62.8%	44.1%	53.5%

6.2.3 MOHEX-CNN FOR MULTIPLE BOARD SIZE HEX

Unlike previous work in Go (Silver et al., 2017b) or Hex (Anthony et al., 2017), the neural net we proposed has no board size dependent fully connected layers. This makes it possible to easily reuse the trained neural network on board sizes other than 9×9. To see the generalization ability across different board sizes in search, we incorporate the trained neural net to MoHex 2.0, the resulting program is MoHex-CNN. The difference between MoHex-CNN and MoHex 2.0 is that MoHex-

CNN replaces the prior probability of MoHex 2.0 with the policy neural net trained on 9×9 Hex games, i.e., the neural net model before policy gradient learning.

Table 2: Winrates of MoHex-CNN against MoHex 2.0 with same number of simulations. All programs use the same default parameters as MoHex 2.0. Every opening was tried twice with each player as black or white. Column 6 and 7 are respectively the average consumed time per game for each corresponding program.

Player	#Simulations	MoHex2.0 was white	MoHex2.0 was black	Overall winrate	Average time of MoHex-2.0	Average time of MoHex-CNN	Board size
MoHex-CNN	10^4	77.8%	59.3%	68.5%	4.5	6.8	9×9
MoHex-CNN	10^4	83%	58.0%	70.5%	12.3	17.1	10×10
MoHex-CNN	10^4	75.2%	48.8%	62.0%	13.4	18.2	11×11
MoHex-CNN	10^4	78.5%	55.6%	67%	29.4	36.0	12×12
MoHex-CNN	10^4	69.8%	45.6%	57.7%	41.7	49.9	13×13

Table 2 shows the winrates of MoHex-CNN on board sizes from 9×9 to 13×13. We note that board sizes smaller than 9 are not investigated because they can easily be solved by virtual connection computation or tree based proof number search (Henderson, 2010). MoHex 2.0 was not designed to play board size > 13, so we stop at board size 13. MoHex-CNN defeats MoHex 2.0 on every board size, which is remarkable since the neural net model was only trained on 9×9 Hex games for a few hours on a single GPU. The computation overhead is not significantly big, because in our implementation, neural net evaluation is computed in parallel with *prior pruning* [2] when expanding a node. We not that when giving the same computation time per move, MoHex-CNN could also beat MoHex 2.0, detailed results are shown in Appendix.

For 13×13 Hex, we have seen that adversarial Monte carlo return slightly improved MoHex 2.0, we further show results in Table 3 by combining the minimum Monte carlo return with MoHex-CNN. As in the previous section, MoHex-CNN-A uses the minimum of two playout returns while MoHex-CNN-Mixed uses the linear combination of *minimum* and *average* by factors 0.5 and 0.5.

Table 3: Winrates of MoHex-CNN-A and MoHex-CNN-Mixed against Mohex 2.0 with same number of simulations. All programs use the same default parameters as MoHex 2.0 except that at the leaf node *number_playouts_per_visit* is set to 2. On 13×13 Hex, every opening was tried twice with each player as black or white.

Player	#Simulations	MoHex2.0 was white	MoHex2.0 was black	Overall winrate
MoHex-CNN-A	10^4	68.6%	47.3%	58.0%
MoHex-CNN-Mixed	10^4	69.2%	56.2%	62.7%

In Table 3, using the mixed return achieves the best performance. This is perhaps because, different from policy gradient, the *in-tree* phase in MCTS is already an implicit form of *minimax*. It is known that in AMGs, stronger playout policy does not always produce better MCTS player (Silver & Tesauro, 2009), our results in Table 3 suggest that a moderate skewing of the critic to the worst-case may help the search.

6.2.4 COMPARISON WITH EXIT

ExIt competed against MoHex 2011 (Arneson et al., 2010) on 9×9 Hex. To have a grasp of the relative strengths of ExIt, MoHex 2011, MoHex 2.0 and MoHex-CNN, we present results of Mo-Hex 2.0 and MoHex-CNN played against MoHex 2011 on 9×9 Hex [3]. Following the experiment in (Anthony et al., 2017), we show the results with 10^4 and 10^5 simulations in Table 4.

When 10^4 simulations is used, both MoHex 2.0 and MoHex-CNN has similar winrates as ExIt. However, the 10^5 simulations MoHex 2.0 and MoHex-CNN obtain much better winrates than ExIt (Anthony et al., 2017). We further note that, the state-of-art for 9×9 Hex is that all openings have been

---

[2]Used by MoHex to prune proven inferior nodes whenever expanding a node

[3]In (Huang et al., 2013), MoHex 2.0 has been demonstrated to be stronger than MoHex 2011 on 11×11 and 13×13 Hex, but playing results on 9×9 board size were never presented.

Table 4: Results of ExIt, MoHex 2.0 and MoHex-CNN against MoHex 2011 on 9×9 Hex. All MoHex programs use the same default parameters, with 10^4 simulations (left) or 10^5 simulations (right). Every opening was tried twice with each player as black or white. ExIt's result is from (Anthony et al., 2017).

Player	MoHex 2011 was white	MoHex 2011 was black	Overall winrate	MoHex 2011 was white	MoHex 2011 was black	Overall winrate
MoHex 2.0	82.7%	66.7%	74.7%	79.0%	65.4%	72.2%
MoHex-CNN	85.2%	65.4%	75.3%	84.0%	71.6%	77.8%
ExIt	-	-	75.3%	-	-	59.3%

solved (Pawlewicz & Hayward, 2013) [4]. This parallel solver has been embedded into MoHex 2.0, but in default setting, it is turned off.

7 CONCLUSIONS

We reviewed MDP and AMG, and proposed a new adversarial policy gradient paradigm that uses the worst-case return as the "critic". We introduced two practical adversarial Monte carlo policy gradient methods. We evaluated our algorithms on game of Hex, the experimental comparisons show that the new algorithms are notably better than routinely adopted self-play REINFORCE variants. We also applied *minimum* return to Monte-carlo tree search, and observed better performance on 13×13 Hex. Another contribution we made is a multi-boardsize neural net architecture, we demonstrated that a single neural net model trained on smaller board size can effectively generalize to larger board sizes. As a result, using it as a prior knowledge, we are able to improve MoHex 2.0 consistently from 9×9 to 13×13 Hex. Since in practice, expert data is often scarce, difficult to generate with limited computation resources, in this paper we provided a more feasible approach for high-performance playing for multi-boardsize Hex.

On the other hand, based on the adversarial policy gradient formulation in AMGs, the Monte carlo policy gradients, either self-play REINFORCE-V or others, are not unbiased anymore, yet still have the drawback of being sample-inefficient, and may exhibit high variance. In this sense, an adversarial actor-critic framework is perhaps more appealing. In Monte carlo tree search framework, value neural network may also be used to replace Monte carlo rollouts. We leave this line of research as future work.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, et al. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *arXiv preprint arXiv:1603.04467*, 2016.

Vadim V Anshelevich. A hierarchical approach to computer Hex. *Artificial Intelligence*, 134(1-2): 101–120, 2002.

Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. *arXiv preprint arXiv:1705.08439*, 2017.

Broderick Arneson, Ryan B Hayward, and Philip Henderson. Monte carlo tree search in Hex. *IEEE Transactions on Computational Intelligence and AI in Games*, 2(4):251–258, 2010.

Richard Bellman. A Markovian decision process. *Journal of Mathematics and Mechanics*, pp. 679–684, 1957.

Dimitri P. Bertsekas and John N. Tsitsiklis. *Neuro-Dynamic Programming*. Athena Scientific, 1st edition, 1996. ISBN 1886529108.

Edward C Capen, Robert V Clapp, William M Campbell, et al. Competitive bidding in high-risk situations. *Journal of petroleum technology*, 23(06):641–653, 1971.

---

[4]The solver shows that among all 81 openings on 9×9 board, 53 are first player win.

Christopher Clark and Amos Storkey. Training deep convolutional neural networks to play Go. In *International Conference on Machine Learning*, pp. 1766–1774, 2015.

Anne Condon. On algorithms for Simple Stochastic Games. In *Advances in computational complexity theory*, pp. 51–72, 1990.

Anne Condon. The complexity of stochastic games. *Information and Computation*, 96(2):203–224, 1992.

Rémi Coulom. Efficient selectivity and backup operators in Monte-Carlo tree search. In *International conference on computers and games*, pp. 72–83. Springer, 2006.

Roy Fox, Ari Pakman, and Naftali Tishby. Taming the noise in reinforcement learning via soft updates. In *Proceedings of the Thirty-Second Conference on Uncertainty in Artificial Intelligence*, UAI'16, pp. 202–211, Arlington, Virginia, United States, 2016. AUAI Press.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Shixiang Gu, Timothy Lillicrap, Zoubin Ghahramani, Richard E Turner, and Sergey Levine. Q-prop: Sample-efficient policy gradient with an off-policy critic. In *ICLR*, 2017.

Philip Henderson. *Playing and solving the game of Hex*. PhD thesis, University of Alberta, 2010.

Alan J Hoffman and Richard M Karp. On nonterminating stochastic games. *Management Science*, 12(5):359–370, 1966.

Ronald A Howard. Dynamic programming and Markov processes. 1960.

Shih-Chieh Huang, Rémi Coulom, Shun-Shii Lin, et al. Monte-carlo simulation balancing in practice. *Computers and Games*, 6515:81–92, 2010.

Shih-Chieh Huang, Broderick Arneson, Ryan B Hayward, Martin Müller, and Jakub Pawlewicz. Mohex 2.0: a pattern-based MCTS Hex player. In *International Conference on Computers and Games*, pp. 60–71. Springer, 2013.

Sham M Kakade. A natural policy gradient. In *Advances in neural information processing systems*, pp. 1531–1538, 2002.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

Jens Kober, J Andrew Bagnell, and Jan Peters. Reinforcement learning in robotics: A survey. *The International Journal of Robotics Research*, 32(11):1238–1274, 2013.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *ICLR*, 2016.

Long-H Lin. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine learning*, 8(3/4):69–97, 1992.

Michael L Littman. Markov games as a framework for multi-agent reinforcement learning. In *Proceedings of the eleventh international conference on machine learning*, volume 157, pp. 157–163, 1994.

Michael Lederman Littman. *Algorithms for sequential decision making*. PhD thesis, Brown University Providence, RI, 1996.

Chris J Maddison, Aja Huang, Ilya Sutskever, and David Silver. Move evaluation in Go using deep convolutional neural networks. In *ICRL*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Belle-mare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning*, pp. 1928–1937, 2016.

John F Nash. Some games and machines for playing them. 1952.

Jakub Pawlewicz and Ryan B Hayward. Scalable parallel DFPN search. In *International Conference on Computers and Games*, pp. 138–150. Springer, 2013.

Jakub Pawlewicz, Ryan Hayward, Philip Henderson, and Broderick Arneson. Stronger virtual connections in Hex. *IEEE Transactions on Computational Intelligence and AI in Games*, 7(2):156–166, 2015.

Jan Peters and J Andrew Bagnell. Policy gradient methods. In *Encyclopedia of Machine Learning*, pp. 774–776. Springer, 2011.

Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In *ICML*, 2017.

Gavin A Rummery and Mahesan Niranjan. *On-line Q-learning using connectionist systems*, volume 37. University of Cambridge, Department of Engineering, 1994.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *ICLR*, 2016.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *Proceedings of the 32nd International Conference on Machine Learning (ICML-15)*, pp. 1889–1897, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Claude E Shannon. Computers and automata. *Proceedings of the IRE*, 41(10):1234–1241, 1953.

Lloyd S Shapley. Stochastic games. *Proceedings of the National Academy of Sciences*, 39(10):1095–1100, 1953.

David Silver and Gerald Tesauro. Monte-carlo simulation balancing. In *Proceedings of the 26th Annual International Conference on Machine Learning*, pp. 945–952. ACM, 2009.

David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *Proceedings of the 31st International Conference on Machine Learning (ICML-14)*, pp. 387–395, 2014.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *arXiv preprint arXiv:1712.01815*, 2017a.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of Go without human knowledge. *Nature*, 550(7676):354–359, 2017b.

James E Smith and Robert L Winkler. The optimizers curse: Skepticism and postdecision surprise in decision analysis. *Management Science*, 52(3):311–322, 2006.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. Preliminary Draft, MIT press Cambridge, second edition, 2017.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pp. 1057–1063, 2000.

Gerald Tesauro. Temporal difference learning and TD-Gammon. *Communications of the ACM*, 38 (3):58–68, 1995.

Yuandong Tian and Yan Zhu. Better computer Go player with neural network and long-term prediction. In *ICLR*, 2016.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Van Hasselt, Marc Lanctot, and Nando De Freitas. Dueling network architectures for deep reinforcement learning. In *ICML*, 2016.

Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Remi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. In *ICLR*, 2017.

Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine learning*, 8(3-4):279–292, 1992.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

APPENDIX

A PSEUDOCODE

We present the pseudocode of **AMCPG-A** and **AMCPG-B**.

Algorithm 1: Adversarial Monte-Carlo Policy Gradient (AMCPG-A and AMCPG-B)

---

1 Initialize θ ;
2 $ite \leftarrow 0$;
3 **while** $ite < maxIterations$ **do**
4 $\quad$ Self-play a batch of n games E using π ;
5 $\quad$ **for** $e_i \in E$ **do**
6 $\quad\quad$ Select a state-action pair (s_j, a_j) uniform randomly;
7 $\quad\quad$ Let $z(s_j, a_j)$ be the outcome with respect to action a_j at s_j in e_i;
8 $\quad\quad$ From (s_j, a_j),

$$z'(s_j, a_j) = \begin{cases} A: & \text{Self-play } k \text{ games using } \pi, \text{ record the minimum outcome with respect to } s_j; \\ B: & \text{Select top } k \text{ moves from } s'_j, \text{ from each move self-play a game using } \pi, \\ & \text{record the minimum outcome w.r.t } s_j; \end{cases}$$

$\quad\quad R^i \leftarrow \min\{z(s_j, a_j), z'(s_j, a_j)\}$;
9 $\quad\quad$ Write (s_j, a_j, R^i) to the batch ;
10 $\quad$ $\theta \leftarrow \theta + \frac{\alpha}{n} \sum_{i=1}^{n} \nabla \log \pi(s_j^i, a_j^i; \theta) R^i$;
11 $\quad$ $ite \leftarrow ite + 1$;

We also present the pseudo-code of **Algo.1**, **Algo.2** and **Algo.3** in Section 3.

B EXPERIMENTS

B.1 SUPERVISED LEARNING FOR INITIALIZATION

Since high quality data is not instantly available, to initialize the neural net weight, we first generated a dataset containing 10^6 state-action pairs by computer player MoHex played against MoHex, on 9×9 board. We train the policy neural net to maximize the log-likelihood on this dataset. The training only took $100,000$ steps with mini-batch 64, optimized using Adam (Kingma & Ba, 2015) with learning rate 0.001.

The resulting neural net could be used for multiple board sizes, its win-percentages against 1-play Wolve on 9×9 and regular board size 11×11 are respectively 13.2% and 4.6% (iterated all opening moves, 10 trails each opening with Wolve as Black or White).

Input feature has 12 binary planes, utilizing a "bridge pattern" in Hex.

B.2 MOHEX 2.0'S IN-TREE PHASE

Starting from the root node, MoHex 2.0 selects a child node according to the score function in below:

$$score(s, a) = (1 - w)\left(q(s, a) + c_b\sqrt{\frac{\log N(s)}{N(s, a)}}\right) + wR(s, a) + c_{pb}\frac{\rho(s, a)}{\sqrt{N(s, a) + 1}},$$

where $N(s), N(s, a)$ are respectively the visit counts of s and (s, a), $q(s, a)$ is the Q-value of (s, a), $R(s, a)$ is the RAVE value, $\rho(s, a)$ is the prior probability from move pattern weights, w, c_b, c_{pb} are weighting parameters. MoHex-CNN uses the same formula except that the prior probability is from neural net.

Algorithm 2: Policy Iteration algorithms for AMGs

---

1   **Procedure** `Algo.1()`:
2   π_1, π_2 are policies for player 1 and player 2;
3   Initialize π_1^0, π_2^0 arbitrarily;
4      $t \leftarrow 1$;
5      $\pi_1^t \leftarrow \pi_1^0$;
6      $stable \leftarrow false$;
7   **while** *not stable* **do**
8   Fix π_1^t;
9   Compute the optimal counter strategy for player 2 given player 1's stragy is fixed;
10   Let π_2^t be the computed optimal counter strategy;
11   Fix π_2^t;
12   Compute the optimal counter strategy for player 1 given player 2's strateg is fixed;
13   Let π_1^{t+1} be the computed optimal counter strategy;
14        $t \leftarrow t + 1$;
15   **if** $\pi_1^{t-1} = \pi_1^t$ *and* $\pi_2^{t-2} = \pi_2^{t-1}$ **then**
16          $stable \leftarrow true$;

17   **Procedure** `Algo.2()`:
18   π_1, π_2 are policies for player 1 and player 2;
19   Suppose player 1 is the max player, palyer 2 is the min player;
20   Initialize π_1^0, π_2^0 arbitrarily;
21      $t \leftarrow 0$;
22      $stable \leftarrow false$;
23   **while** *not stable* **do**
24   Fix π_1^t, π_2^t;
25   Compute the value function V_t under π_1^t, π_2^t by policy evaluation;
26   Let π_1^{t+1} be the greedily (max) modified policy w.r.t V_t;
27   Let π_2^{t+1} be the greedily (min) modified policy w.r.t V_t;
28        $t \leftarrow t + 1$;
29   **if** $\pi_1^t = \pi_1^{t-1}$ *and* $\pi_2^t = \pi_2^{t-1}$ **then**
30          $stable \leftarrow true$;

31   **Procedure** `Algo.3()`:
32   π_1, π_2 are policies for player 1 and player 2;
33   Suppose player 1 is the max player, palyer 2 is the min player;
34   Initialize π_1^0, π_2^0 arbitrarily;
35      $t \leftarrow 0$;
36      $stable \leftarrow false$;
37   **while** *not stable* **do**
38   Fix π_1^t, π_2^t;
39   Compute the value function V_t under π_1^t, π_2^t by policy evaluation;
40   Let π_1^{t+1} be the greedily (max) modified policy w.r.t V_t;
41   Fix π_1^{t+1};
42   Compute the optimal counter policy for player 2 given player 1's policy is fixed;
43   Let π_2^{t+1} be this optimal counter policy;
44        $t \leftarrow t + 1$;
45   **if** $\pi_1^t = \pi_1^{t-1}$ *and* $\pi_2^t = \pi_2^{t-1}$ **then**
46          $stable \leftarrow true$;

Plane index	Description	Plane index	Description
0	Black played stones	6	To play save bridge points
1	White played stones	7	To play make-connection points
2	Unoccupied points	8	To play form bridge points
3	Black or White to play	9	Opponent's save bridge points
4	Black bridge endpoints	10	Opponent's form bridge points
5	White bridge endpoints	11	Opponent's make-connection points

B.3 WITH THE SAME COMPUTATION TIME AND DFPN SOLVER TURNED ON

In computer Hex Olympiad tournament, MoHex is usually played with the parallel solver turned on. To demonstrate the full strength of MoHex-CNN compared to MoHex 2.0, we perform another experiments by limiting both programs with the same thinking time 5s per move, all with the DFPN solver turned on.

Table 5: Winrates of MoHex-CNN against Mohex 2.0 with the same time per move. All programs use the default parameters the same as MoHex 2.0 with parallel solver on. Every opening was tried twice with each player as black or white.

Opponent	Time per move (s)	MoHex2.0 was white	MoHex2.0 was black	Overall winrate	Average length of played games	Board size
MoHex-CNN	5	66.7%	51.9%	59.3%	39.5	9×9
MoHex-CNN	5	64.0%	56.0%	60.0%	48.2	10×10
MoHex-CNN	5	68.6%	56.2%	62.4%	58.1	11×11
MoHex-CNN	5	64.0%	52.8%	59.4%	69.7	12×12
MoHex-CNN	5	57.4%	55.6%	56.5%	80.6	13×13

As expected, the results show there on smaller board size like 9×9, due to the DFPN solver in both players, there is a significant decrease of MoHex-CNN's winrate. However, on larger board sizes, the influence of DFPN solver is small. We note that, in (Anthony et al., 2017), on 9×9 board size, ExIt's winrate against 4s-MoHex2011 with DFPN solver is 55.6%. MoHex 2.0's solver is also stronger than MoHex 2011 due to improved virtual connections.