THE LOTTERY TICKET HYPOTHESIS: FINDING SPARSE, TRAINABLE NEURAL NETWORKS

ABSTRACT

Neural network pruning techniques can reduce the parameter counts of trained networks by over 90%, decreasing storage requirements and improving computational performance of inference without compromising accuracy. However, contemporary experience is that the sparse architectures produced by pruning are difficult to train from the start, which would similarly improve training performance.

We find that a standard technique for pruning weights naturally uncovers subnetworks whose initializations made them capable of training effectively. Based on these results, we articulate the *lottery ticket hypothesis*: dense, randomly-initialized feed-forward networks contain subnetworks (*winning tickets*) that—when trained in isolation—arrive at comparable test accuracy in a comparable number of iterations. The winning tickets we find have won the initialization lottery: their connections have initial weights that make training particularly effective.

We present an algorithm to identify winning tickets and a series of experiments that support the lottery ticket hypothesis and the importance of these fortuitous initializations. We consistently find winning tickets that are less than 10-20% of the size of several fully-connected and convolutional feed-forward architectures for MNIST and CIFAR10. Furthermore, the winning tickets we find above that size learn faster than the original network and exhibit higher test accuracy.

1 INTRODUCTION

Techniques for eliminating unnecessary weights from neural networks (*pruning*) (LeCun et al., 1990; Hassibi & Stork, 1993; Han et al., 2015; Li et al., 2016) can reduce parameter-counts by more than 90% while maintaining accuracy. Doing so diminishes the size (Han et al., 2015; Hinton et al., 2015) or energy consumption (Yang et al., 2017; Molchanov et al., 2016; Luo et al., 2017) of trained networks, making inference more efficient. If the unpruned networks have such excess capacity, why do we not train the smaller, pruned architectures instead in the interest of more efficient training? Contemporary experience is that the sparse architectures uncovered by pruning are harder to optimize, reaching lower accuracy than the original networks when trained from the start.[1]

Consider an example. In Figure 1, we randomly sample and train sparse subnetworks from a fully-connected network for MNIST and convolutional networks for CIFAR10. Across various levels of sparsity, dashed lines trace the iteration of minimum validation loss[2] and the test accuracy at that iteration. The sparser the network, the slower the learning and the lower the eventual test accuracy.

In this paper, we show that there consistently exist sparse networks that train from the start and learn at least as fast as the original network while matching its test accuracy. In fact, they are subnetworks of the original, untrained networks. The solid lines in Figure 1 show some of the sparse networks that we find in this paper. Based on these results, we articulate *the lottery ticket hypothesis*.

---

[1] "Training a pruned model from scratch performs worse than retraining a pruned model, which may indicate the difficulty of training a network with a small capacity." (Li et al., 2016) "During retraining, it is better to retain the weights from the initial training phase for the connections that survived pruning than it is to re-initialize the pruned layers...gradient descent is able to find a good solution when the network is initially trained, but not after re-initializing some layers and retraining them." (Han et al., 2015)

[2] As a proxy for the speed at which a network learns, we use the iteration at which an early-stopping criterion would end training. The particular early-stopping criterion we employ throughout this paper is the iteration of minimum validation loss during training.

Figure 1: The iteration at which early-stopping would occur (left) and the test accuracy at that iteration (right) of the lenet architecture for MNIST and the conv2, conv4, and conv6 architectures for CIFAR10 (see Figure 2) when trained starting at various sizes. Dashed lines are randomly sampled sparse networks (average of ten trials). Solid lines are winning tickets (average of five trials).

The Lottery Ticket Hypothesis. *Any randomly-initialized, dense feed-forward neural network that trains to a particular test accuracy contains a subnetwork that is initialized such that—when trained in isolation—it can learn to match the accuracy of the original network after learning for at most the same number of training iterations.*

More formally, consider a dense feed-forward neural network $f(x; \theta)$ with initial parameters $\theta = \theta_0 \sim \mathcal{D}_\theta$. After j iterations of stochastic gradient descent (SGD) on a training set, f reaches minimum validation loss l_j and test accuracy a_j. In addition, consider training $f(x; \theta)$ with a mask $m \in \{0, 1\}^{|\theta|}$ on its parameters such that its initialization is $m \odot \theta_0$. After k iterations of SGD on the same training set (with m fixed), f reaches minimum validation loss l_k^m and test accuracy a_k^m with parameters $m \odot \theta_k^m$. The lottery ticket hypothesis predicts that $\exists\, m$ for which $k \leq j$ (*commensurate training time*), $a_k^m \geq a_j$ (*commensurate accuracy*), and $\|m\|_0 \ll |\theta|$ (*fewer parameters*). Let $P_m = \frac{\|m\|_0}{|\theta|}$ be the level of pruning of m, e.g., $P_m = 25\%$ when 75% of parameters are masked out.

We find that a standard pruning technique automatically uncovers such trainable subnetworks from fully-connected and convolutional feed-forward networks. We designate these untrained subnetworks $f(x; m \odot \theta_0)$ *winning tickets*, since those that we find have won the initialization lottery with a combination of weights and connections capable of training. When their remaining parameters are randomly reinitialized (e.g., $f(x; m \odot \theta_0')$ where $\theta_0' \sim \mathcal{D}_\theta$), our winning tickets no longer match the performance of the original network, indicating the importance of the original initialization and hinting at a possible explanation for the difficulty of training pruned networks from scratch.

Finding winning tickets. We identify winning tickets by training networks and subsequently pruning their smallest-magnitude weights. The set of connections that survives this process is the architecture of a winning ticket. Unique to our work, the winning ticket's weights are the values to which these connections were initialized *before training*. This forms our central experiment:

1. Randomly initialize a neural network $f(x; \theta_0)$ (where $\theta_0 \sim \mathcal{D}_\theta$).
2. Train the network for j iterations, reaching parameters θ_j.
3. Prune $s\%$ of the parameters, creating a mask m where $P_m = (100 - s)\%$.
4. To extract the winning ticket, reset the remaining parameters to their values in θ_0, creating the untrained network $f(x; m \odot \theta_0)$.

If dense networks contain winning tickets and pruning reveals them, then the network $f(x; m \odot \theta_0)$—when trained for j iterations—will reach similar accuracy to $f(x; \theta_j)$ at least as quickly, and m will be too sparse for a randomly-reinitialized or randomly-sparsified network to do the same.

Results. We identify winning tickets in a fully-connected architecture for MNIST and convolutional architectures for CIFAR10 across several optimization strategies (SGD, momentum, and Adam) with techniques like dropout, weight decay, and batchnorm. In deeper networks, our pruning-based strategy for finding winning tickets is sensitive to the learning rate: it requires warmup to find winning tickets at higher learning rates. The winning tickets we find are 10-20% (or less) of the size of the original network (*smaller size*). Down to that size, they meet or exceed the original network's test accuracy (*commensurate accuracy*) in at most the same number of iterations (*commensurate training time*). When training accuracy reaches 100%, winning tickets still maintain higher test accuracy,

Network	lenet	conv2	conv4	conv6	resnet18	vgg16	vgg19
Convolutions		64, 64, pool	64, 64, pool
128, 128, pool	64, 64, pool
128, 128, pool
256, 256, pool	16, 3x[16, 16]
3x[32, 32]
3x[64, 64]	2x64, pool
2x128, pool
3x256, pool
3x512, pool
3x512	2x64 pool
2x128, pool
4x256, pool
4x512, pool
4x512
FC Layers	300, 100, 10	256, 256, 10	256, 256, 10	256, 256, 10	avg-pool, 10	avg-pool, 10	avg-pool, 10
All/Conv Weights	266K	4.3M / 38K	2.4M / 260K	1.7M / 1.1M	274K / 270K	14.7M	20.0M
Iterations	50K	20K	25K	30K	30K	60K	60K
Optimizer	Adam 12e-3	Adam 2e-3	Adam 3e-3	Adam 3e-3	← SGD 0.1-0.01-0.001 Mom. 0.9 →		
Pruning Rate	20%	conv10% fc20%	conv10% fc20%	conv15% fc20%	conv10%	conv20%	conv20%

Figure 2: Architectures tested in this paper. Convolutions are 3x3. Lenet is from LeCun et al. (1998). Conv2/4/6 are variants of VGG (Simonyan & Zisserman, 2014). Resnet18 is from He et al. (2016). VGG16 and VGG19 for CIFAR10 are adapted from Anonymous (2019b). Initializations are Gaussian Glorot (Glorot & Bengio, 2010). Brackets denote residual connections around layers.

meaning they also generalize better. When randomly reinitialized, winning tickets perform far worse, meaning structure alone cannot explain a winning ticket's success.

The Lottery Ticket Conjecture. Returning to our motivating question, we extend our hypothesis into an untested conjecture that gradient descent seeks out and trains a subset of well-initialized weights. Randomly-initialized, unpruned networks are easier to train because they have more possible subnetworks from which training can recover a winning ticket.

Contributions.

- We demonstrate that pruning uncovers sparse, trainable networks that reach test accuracy comparable to the original, feed-forward networks from which they derived.
- We show that winning tickets at moderate levels of pruning learn faster and reach higher test accuracy than the original network.
- We propose the *lottery ticket hypothesis* as a new perspective on the composition of neural networks to explain these findings.

Implications. In this paper, we empirically study the lottery ticket hypothesis. Now that we have demonstrated the existence of winning tickets, we hope to exploit this knowledge to:

Improve the performance of training. Since winning tickets can be trained from the start in isolation, we can design training schemes that search for winning tickets and prune as early as possible.

Design better networks. Winning tickets reveal combinations of sparse architectures and initializations that are particularly adept at learning. We can find, study, and take inspiration from winning tickets to design new architectures and initialization schemes with the same inductive biases conducive to learning. We may even be able to transfer winning tickets discovered for one task to many others.

Improve our theoretical understanding of neural networks. We can study why randomly-initialized feed-forward networks seem to contain winning tickets and potential implications for theoretical study of generalization (Zhou et al., 2018; Arora et al., 2018) and optimization (Anonymous, 2019a).

2 WINNING TICKETS IN FULLY-CONNECTED NETWORKS

In this Section, we assess the lottery ticket hypothesis as applied to fully-connected networks trained on MNIST. We use the lenet-300-100 architecture (LeCun et al., 1998) as described in Figure 2. We follow the outline from Section 1: after randomly initializing and training a network, we prune the network and reset the remaining connections to their original initializations. We use a simple pruning heuristic: remove a percentage of the weights with the lowest magnitudes within each layer (as in Han et al. (2015)). Connections to outputs are pruned at half of the rate of the rest of the network. We explore other hyperparameters in Appendix E, including learning rates, optimization strategies (SGD, momentum), initialization schemes, and network sizes. We test two pruning strategies: *one-shot*

Figure 3: Test accuracy on lenet (iterative pruning) as training proceeds. Each curve is the average of five trials. Labels are the fraction of weights remaining in each layer after pruning. Error bars are the minimum and maximum of any trial.

(a) Early-stopping iteration and accuracy for one-shot pruning. (b) Accuracy at end of training.

(c) Early-stopping iteration and accuracy for all pruning methods.

Figure 4: Early-stopping iteration and test accuracy at early-stopping of lenet under one-shot and iterative pruning. Average of five trials; error bars for the minimum and maximum values. At iteration 50,000, training accuracy $\approx 100\%$ for $P_m \geq 2\%$ for iterative winning tickets (see Appendix B).

pruning and *iterative pruning*. One-shot pruning prunes in a single step. Iterative pruning repeatedly trains, prunes, and resets the weights, removing more of the network on each iteration.

Overview of results. Winning tickets found via pruning learn faster than the original network. Figure 3 plots the average test accuracy when training winning tickets iteratively pruned to different extents. Error bars are the minimum and maximum of any run. For the first pruning steps, networks learn faster and reach higher test accuracy the more they are pruned (left graph in Figure 3). A winning ticket comprising 51.3% of the weights from the original network (i.e., $P_m = 51.3\%$) reaches higher test accuracy faster than the original network but slower than when $P_m = 21.1\%$. When $P_m < 21.1\%$, learning slows (middle graph). When $P_m = 3.6\%$, a winning ticket regresses to the performance of the original network. A similar pattern repeats throughout this paper.

One-shot pruning. Figure 4a summarizes this behavior for all pruning levels under one-shot pruning (green line). On the left is the iteration at which each network reaches minimum validation loss (i.e., when the early-stopping criterion would halt training) in relation to the percent of weights remaining after pruning; on the right is test accuracy at that iteration. We use the iteration at which the early-stopping criterion is met as a proxy for how quickly the network learns. When $P_m = 17.6\%$, the average winning tickets reach minimum validation accuracy as early as the original network; when $95.0\% \geq P_m \geq 5.17\%$, test accuracy is higher than the original network. Further pruning beyond these thresholds causes learning to slow and accuracy to degrade.

Iterative pruning. Figure 4c shows the results of iteratively pruning by 20% per iteration (blue); one-shot data from Figure 4a is reproduced in green. (In 4b and 4c, the x-axis is logarithmic.) Iteratively-pruned winning tickets learn faster and reach higher test accuracy at smaller network sizes. The winning tickets learn faster as P_m decreases from 100% to 21%, at which point early-stopping occurs 38% earlier than for the original network. Further pruning causes learning to slow, returning to the early-stopping performance of the original network when $P_m = 3.6\%$. Test accuracy increases with pruning, improving by more than 0.3 percentage points when $P_m = 13.5\%$; after this point, accuracy decreases, returning to the level of the original network when $P_m = 3.6\%$. At the iteration of early stopping, training accuracy increases with pruning in a similar pattern to test accuracy, seemingly implying that winning tickets optimize more effectively but do not generalize better. However, at the end of training (Figure 4b), iteratively-pruned winning tickets still see a test accuracy improvement of up to 0.35 percentage points in spite of the fact that training accuracy consistently reaches 100% (see Appendix B), pointing to improved generalization. Although iterative pruning extracts smaller winning tickets, repeated training means they are costlier to find. However, we aim to analyze the behavior of winning tickets rather than to find them efficiently. Iterative pruning's advantage is that it puts a tighter upper-bound on the size of a winning ticket.

Random reinitialization. To measure the importance of a winning ticket's initialization, we retain the structure of a winning ticket (i.e., the mask m) but randomly sample a new initialization $\theta'_0 \sim \mathcal{D}_\theta$. We randomly reinitialize each winning ticket three times, making 15 total per point in Figure 4. We find that initialization is crucial for the efficacy of a winning ticket. The right graph in Figure 3 shows this experiment for iterative pruning. In addition to the original network and winning tickets at $P_m = 51\%$ and 21% are the random reinitialization experiments. Where the winning tickets learn faster as they are pruned, they learn progressively slower when randomly reinitialized. The broader results of this experiment are the red and orange lines in Figure 4c. Unlike winning tickets, the reinitialized networks learn increasingly slower than the original network and lose test accuracy after little pruning. The average reinitialized iterative winning ticket's test accuracy drops off from the original accuracy when $P_m = 21.1\%$, compared to 2.9% for the winning ticket. When $P_m = 21\%$, the winning ticket reaches minimum validation loss 2.51x faster than when reinitialized and is half a percentage point more accurate. All networks reach 100% training accuracy for $P_m \geq 5\%$; Figure 4b therefore shows that the winning tickets generalize substantially better than when randomly reinitialized. This experiment supports the lottery ticket hypothesis' emphasis on initialization: the original initialization withstands and benefits from pruning, while the random reinitialization's performance immediately suffers and diminishes steadily.

3 Winning Tickets in Convolutional Networks

Here, we apply the lottery ticket hypothesis to convolutional networks on CIFAR10. We consider the conv2, conv4, and conv6 architectures in Figure 2, which are scaled-down variants of the VGG (Simonyan & Zisserman, 2014) family. The networks have two, four, or six convolutional layers followed by two fully-connected layers. The networks cover the range from fully-connected to convolutional networks, with less than 1% of parameters in convolutional layers in conv2 to nearly two thirds in conv6. Appendix F includes an exploration of the hyperparameters, including other learning rates and optimization strategies (SGD, momentum). We investigate three questions:

Question 1: How does the lottery ticket hypothesis manifest for convolutional networks?

Question 2: What is the effect of randomly reinitializing winning tickets?

Question 3: What is the effect of pruning convolutions and fully-connected layers alone and together?

Question 1. The solid lines in Figure 5 (top) show the iterative lottery ticket experiment on conv2 (blue), conv4 (orange), and conv6 (green) at the pruning rates from Figure 2. The pattern from Section 2 repeats: as the network is pruned, it learns faster and test accuracy rises as compared to the original network. In this case, the results are more pronounced. Winning tickets reach minimum validation loss at best 3.5x faster for conv2 ($P_m = 8.8\%$), 3.5x for conv4 ($P_m = 9.2\%$), and 2.5x for conv6 ($P_m = 15.1\%$). Test accuracy improves at best 3.4 percentage points for conv2 ($P_m = 4.6\%$), 3.5 for conv4 ($P_m = 11.1\%$), and 3.3 for conv6 ($P_m = 26.4\%$). All three networks remain above their original average test accuracy when $P_m > 2\%$. As in Section 2, training accuracy at the early-stopping iteration rises with test accuracy; however, by the last iteration of training (Figure

Figure 5: Early-stopping iteration and test accuracy at early-stopping of the conv2/4/6 architectures when iteratively pruned and when randomly reinitialized. Each solid line is the average of five trials; each dashed line is the average of fifteen reinitializations (three per trial). At the last iteration, training accuracy $\approx 100\%$ for $P_m \geq 2\%$ for winning tickets.

Figure 6: Early-stopping iteration and accuracy of the conv2 (left), conv4 (middle), and conv6 (right) networks when only convolutions are pruned, only fully-connected layers are pruned, and both are pruned. The x-axis measures the number of pruning iterations, making it possible to see the relative contributions to the overall network made by pruning FC layers and convolutions individually.

5, bottom right), winning tickets maintain higher test accuracy as training accuracy reaches 100% across pruning levels (see Appendix B), suggesting improved generalization.

Question 2. We repeat the random reinitialization trial from Section 2, which appears as the dashed lines in Figure 5. These experiments again take increasingly longer to learn upon continued pruning. As in Section 2, test accuracy drops off more quickly for the random reinitialization experiments. However, unlike Section 2, test accuracy at early-stopping time initially remains steady and even improves for conv2 and conv4, indicating that—at moderate levels of pruning—the structure of the winning tickets alone may lead to better accuracy.

Question 3. Figure 6 shows the effect of pruning convolutions alone (green), fully-connected layers alone (orange) and pruning both (blue). The x-axis measures the number of pruning iterations to emphasize the relative contributions made by pruning convolutions and fully-connected layers to the overall network. In all three cases, pruning convolutions alone leads to higher test accuracy and faster learning; pruning fully-connected layers alone generally causes test accuracy to worsen

Figure 7: Early-stopping iteration and test accuracy at early-stopping of conv2/4/6 when iteratively pruned and trained with dropout. The dashed lines are the same networks trained without dropout (the solid lines in Figure 5). Learning rates are 0.0003 for conv2 and 0.0002 for conv4 and conv6.

and learning to slow. However, pruning convolutions alone has limited ability to reduce the overall parameter-count of the network, since fully-connected layers comprise 99%, 89%, and 35% of the parameters in conv2, conv4, and conv6.

4 WINNING TICKETS AND DROPOUT

Dropout (Srivastava et al., 2014; Hinton et al., 2012) improves network accuracy by randomly disabling a fraction of the units (i.e., randomly sampling a subnetwork) on each training iteration. Baldi & Sadowski (2013) characterize dropout as simultaneously training the ensemble of all subnetworks. Since the lottery ticket hypothesis suggests that one of these subnetworks comprises a winning ticket, it is natural to ask whether dropout and our strategy for finding winning tickets interact. Figure 7 shows the results of training conv2, conv4, and conv6 with a dropout rate of 0.5. Dashed lines are the network performance without dropout (the solid lines in Figure 5).[3] We continue to find winning tickets when training with dropout. Dropout increases initial test accuracy (2.1, 3.0, and 2.4 percentage points on average for conv2, conv4, and conv6, respectively), and iterative pruning increases it further (up to 2.3, 4.6, and 4.7 percentage points, respectively, on average). Learning becomes faster with iterative pruning as before, but less dramatically in the case of conv2. These improvements suggest that our iterative pruning strategy interacts with dropout in a complementary way. Srivastava et al. (2014) observe that dropout induces sparse activations in the final network; it is possible that dropout-induced sparsity primes a network to be pruned. If so, dropout techniques that target weights (Wan et al., 2013) or learn per-weight dropout probabilities (Molchanov et al., 2017; Louizos et al., 2018) could make winning tickets even easier to find.

5 VGG AND RESNET FOR CIFAR10

Here, we study the lottery ticket hypothesis as applied to networks evocative of the architectures and techniques used in practice. Specifically, we consider two classes of networks: VGG-style (Simonyan & Zisserman, 2014) deep convolutional networks (VGG16 and VGG19 on CIFAR10) and residual networks (He et al., 2016) (Resnet-18 on CIFAR10). (See Figure 2 for details.) These networks are trained with batchnorm, weight decay, gradually decreasing learning rate schedules, and augmented training data. We continue to find winning tickets for all of these architectures; however, our method for finding them, iterative pruning, is sensitive to the particular learning rate used.

VGG. We consider the variants of VGG16 and VGG19 adapted for CIFAR10 by Anonymous (2019b); we use the nearly the same training regime and hyperparameters: 160 epochs (112,480 iterations) with SGD with momentum (0.9) and decreasing the learning rate by a factor of 10 at 80 and 120 epochs. These networks have 14.7 and 20 million parameters, respectively. Figure 8 shows results of iterative pruning and random reinitialization on VGG19 (identical results for VGG16 are in Appendix H) at two different learning rates: 0.1 (used in Anonymous (2019b)) and 0.01. Rather than measure early-stopping time (which, for these larger networks is entangled with learning rate schedules), Figure 8 plots accuracy at three moments during training to illustrate the relative rates at which

---

[3]We choose new learning rates for the networks as trained with dropout—see Appendix F.5.

Figure 8: Test accuracy (at 30,000, 60,000, and 112,000 iterations) of the VGG19 architecture when iteratively pruned and when randomly reinitialized at two different learning rates. The same experiments for VGG16 appear in Appendix H.

Figure 9: Test accuracy (at 10,000, 20,000, and 30,000 iterations) of the resnet-18 architecture when iteratively pruned and when randomly reinitialized at two different learning rates.

accuracy improves. At the higher learning rate, iterative pruning does not find winning tickets for either network, and performance is no better than the random reinitialization experiments. However, at the lower learning rate, the usual pattern reemerges, with subnetworks that, after 160 epochs, remain within 0.2 percentage points of the original accuracy until 10.7% for both VGG16 and VGG19. As shown in the left plot in Figure 8, subnetworks at the lower learning rate consistently learn faster than the unpruned or reinitialized networks. When randomly reinitialized, the subnetworks learn more slowly and lose accuracy as they are pruned.[4]

In order to bridge the gap between lower learning rates and the higher learning rates, we explore the effect of linear learning rate warmup from 0 to the initial learning rate over k iterations. Training VGG19 with warmup ($k = 50000$, green line) at the higher learning rate (0.1) makes it possible to find winning tickets, exceeding the original accuracy when $P_m \geq 5.5\%$; as a bonus, warmup also slightly improves the test accuracy of the unpruned network.

Resnet-18. Resnet-18 (He et al., 2016) is a twenty-layer convolutional network with residual connections designed for CIFAR10. It has 271,000 parameters. We train the network for 30,000 iterations with SGD with momentum (0.9), decreasing the learning rate by a factor of 10 at 20,000 and 25,000 iterations. All other details are in Appendix G. Figure 9 shows the results of iterative pruning and random reinitialization at learning rates 0.1 (used in He et al. (2016)) and 0.008. These results largely mirror those of VGG: iterative pruning finds winning tickets at the lower learning rate but not the higher learning rate. Unlike VGG, the winning tickets at the lower learning rate do not attain the accuracy of the unpruned network at the higher learning rate (90.9%), reaching between 89.5% and 90.0% accuracy when $53.7\% \geq P_m \geq 13.2\%$ (36,000 parameters). At the lower learning rate, the winning ticket initially learns faster (left plot of Figure 9), but the unpruned network at the higher learning rate eventually catches up (right plot). However, winning tickets trained with warmup nearly close the accuracy gap with the unpruned network at the original learning rate, reaching 90.7% test accuracy with learning rate 0.03 (warmup, $k = 20000$) and $P_m = 39.5\%$. For these hyperparameters, we still find winning tickets when $P_m \geq 15\%$.

---

[4]These subnetworks do not technically qualify as winning tickets by our definition, since they do not exceed the accuracy of the original network; however, they stil achieve nearly the same test accuracy as the original network at levels of pruning for which a randomly reinitialized network cannot do the same.

6 DISCUSSION

Existing work on neural network pruning (e.g., Han et al. (2015)) demonstrates that the function learned by a neural network can often be represented with fewer parameters. Pruning typically proceeds by training the original network, removing connections, and further fine-tuning. In effect, the initial training warms up the weights of the pruned network so that it can learn in isolation during fine-tuning. We seek to determine if similarly sparse networks can learn from the start without any sort of pre-training. We find that the architectures studied in this paper reliably contain such trainable subnetworks, and the lottery ticket hypothesis proposes that this propretty applies in general. Our empirical study of the existence and nature of winning tickets invites a number of follow-up questions.

The importance of winning ticket initialization. When randomly reinitialized, a winning ticket learns more slowly and achieves lower test accuracy, suggesting that its initialization is important to its success. One possible explanation for this behavior is these initial weights happen to be close to their final values after training—that in the most extreme case, a winning ticket is already fully-trained. However, experiments in Appendix D show the opposite—that the winning ticket weights move further than other weights. This suggests that the benefit of the initialization is connected to the optimization algorithm, dataset, and model. For example, the winning ticket initialization might land in a region of the loss landscape that is particularly amenable to optimization.

The importance of winning ticket structure. The initialization that gives rise to a winning ticket is arranged in a particular sparse architecture. Since we uncover winning tickets through heavy use of training data, we hypothesize that the structure of our winning tickets encodes an inductive bias customized to the learning task at hand. Cohen & Shashua (2016) show that the inductive bias embedded in the structure of a deep network determines the kinds of data that it can separate more parameter-efficiently than can a shallow network; although Cohen & Shashua (2016) focus on the pooling geometry of convolutional networks, a similar effect may be at play with the structure of winning tickets, allowing them to learn even when heavily pruned.

The improved generalization of winning tickets. We reliably find winning tickets that exceed the test accuracy of the original network while matching its training accuracy, meaning they generalize better. We observe a pattern of increasing and then decreasing test accuracy as we prune, forming an *Occam's Hill* (Rasmussen & Ghahramani, 2001) where the original, overparameterized model has too much complexity (perhaps overfitting) and the extremely pruned model has too little. The conventional view of the relationship between compression and generalization is that shorter hypotheses can better generalize (Rissanen, 1986). Recent theoretical work shows a similar link for neural networks, proving tighter generalization bounds for networks that can be compressed further (Zhou et al. (2018) for pruning/quantization and Arora et al. (2018) for noise robustness). The lottery ticket hypothesis offers a complementary perspective on this relationship—that larger networks might explicitly contain simpler representations.

Implications for neural network optimization. Winning tickets can reach accuracy equivalent to that of the original, unpruned network, but with significantly fewer parameters. This observation connects to recent work on the role of overparameterization in neural network training. For example, Anonymous (2019a) prove that sufficiently overparameterized two-layer relu networks (with fixed-size second layers) trained with SGD converge to global optima. A key question, then, is whether the presence of a winning ticket is necessary or sufficient for SGD to optimize a neural network to a particular test accuracy. We conjecture (but do not empirically show) that SGD seeks out and trains a well-initialized subnetwork. By this logic, overparameterized networks are easier to train because they have more combinations of subnetworks that are potential winning tickets.

7 LIMITATIONS

We only consider vision-centric classification tasks on smaller datasets (MNIST, CIFAR10). We do not investigate larger datasets (namely Imagenet (Russakovsky et al., 2015)) because iterative pruning is exceedingly computationally intensive, requiring training a network 15 or more times consecutively for multiple trials; hyperparameter search multiplicatively increases this cost. In future work, we intend to explore more efficient methods for finding winning tickets that will make it possible to study the lottery ticket hypothesis in more resource-intensive settings.

Sparse pruning is our only method for finding winning tickets. Although we reduce parameter-counts, the resulting architectures are not optimized for modern libraries or hardware. In future work, we intend to study other pruning methods from the extensive contemporary literature, such as structured pruning (which would produce networks optimized for contemporary hardware) and non-magnitude pruning methods (which could produce smaller winning tickets or find them earlier).

The winning tickets we find have initializations that allow them to match the performance of the unpruned networks at sizes too small for randomly-initialized networks to do the same. However, we do not determine the properties of these initializations that, in concert with the inductive biases of the pruned network architectures, make these networks particularly adept at learning.

8 RELATED WORK

In practice, neural networks tend to be dramatically overparameterized. Distillation (Ba & Caruana, 2014; Hinton et al., 2015) and pruning (LeCun et al., 1990; Han et al., 2015) rely on the fact that parameters can be reduced while preserving accuracy. Even with sufficient capacity to memorize training data, networks naturally learn simpler functions (Zhang et al., 2016; Neyshabur et al., 2014; Arpit et al., 2017). Contemporary experience (Bengio et al., 2006; Hinton et al., 2015; Zhang et al., 2016) and Figure 1 suggest that overparameterized networks are easier to train. We show that dense networks contain sparse subnetworks capable of learning on their own starting from their original initializations. Several other research directions aim to train small or sparse networks.

Prior to training. Squeezenet (Iandola et al., 2016) and MobileNets (Howard et al., 2017) are specifically engineered image-recognition networks that are an order of magnitude smaller than standard architectures. Denil et al. (2013) represent weight matrices as products of lower-rank factors. Li et al. (2018) restrict optimization to a small, randomly-sampled subspace of the parameter space (meaning all parameters can still be updated); they successfully train networks under this restriction. We show that one need not even update all parameters to optimize a network, and we find winning tickets through a principled search process involving pruning. Our contribution to this class of approaches is to demonstrate that sparse, trainable networks exist within larger networks.

After training. Distillation (Ba & Caruana, 2014; Hinton et al., 2015) trains small networks to mimic the behavior of large networks; small networks are easier to train in this paradigm. Recent pruning work aims to compress large models into forms that run with limited resources (e.g., on mobile devices). Although pruning is central to our experiments, we aim to gain insight into why training needs the overparameterized networks that make pruning necessary. LeCun et al. (1990) and Hassibi & Stork (1993) first explored pruning based on second derivatives. More recently, Han et al. (2015) showed per-weight magnitude-based pruning substantially reduces the size of image-recognition networks. Han et al. iteratively train to convergence, prune, and continue training. Guo et al. (2016) restore pruned connections as they become relevant again. Han et al. (2017) and Jin et al. (2016) restore pruned connections to increase network capacity after small weights have been pruned and surviving weights fine-tuned. Other proposed pruning heuristics include pruning based on activations (Hu et al., 2016), redundancy (Mariet & Sra, 2016; Srinivas & Babu, 2015a), per-layer second derivatives (Dong et al., 2017), and energy/computation efficiency (Yang et al., 2017) (e.g., pruning convolutional filters (Li et al., 2016; Molchanov et al., 2016; Luo et al., 2017) or channels (He et al., 2017)). Cohen et al. (2016) observe that convolutional filters are sensitive to initialization ("The Filter Lottery"); after training, they randomly reinitialize unimportant filters.

During training. Bellec et al. (2018) train with sparse networks and replace weights that reach zero with new random connections. Srinivas et al. (2017) and Louizos et al. (2018) learn gating variables that minimize the number of nonzero parameters. Narang et al. (2017) integrate magnitude-based pruning into training. Gal & Ghahramani (2016) show that dropout approximates Bayesian inference in Gaussian processes. Bayesian perspectives on dropout learn dropout probabilities during training (Gal et al., 2017; Kingma et al., 2015; Srinivas & Babu, 2016). Techniques that learn per-weight, per-unit (Srinivas & Babu, 2016), or structured dropout probabilities naturally (Molchanov et al., 2017; Neklyudov et al., 2017) or explicitly (Louizos et al., 2017; Srinivas & Babu, 2015b) prune and sparsify networks during training as dropout probabilities for some weights reach 1. In contrast, we train networks at least once to find winning tickets. These techniques might also find winning tickets, or, by inducing sparsity, might beneficially interact with our methods.

REFERENCES

Anonymous. Gradient descent provably optimizes over-parameterized neural networks. In *Submitted to International Conference on Learning Representations*, 2019a. URL `https://openreview.net/forum?id=S1eK3i09YQ`. under review.

Anonymous. Rethinking the value of network pruning. In *Submitted to International Conference on Learning Representations*, 2019b. URL `https://openreview.net/forum?id=rJlnB3C5Ym`. under review.

Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. *ICML*, 2018.

Devansh Arpit, Stanisław Jastrzębski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, et al. A closer look at memorization in deep networks. In *International Conference on Machine Learning*, pp. 233–242, 2017.

Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? In *Advances in neural information processing systems*, pp. 2654–2662, 2014.

Pierre Baldi and Peter J Sadowski. Understanding dropout. In *Advances in neural information processing systems*, pp. 2814–2822, 2013.

Guillaume Bellec, David Kappel, Wolfgang Maass, and Robert Legenstein. Deep rewiring: Training very sparse deep networks. *Proceedings of ICLR*, 2018.

Yoshua Bengio, Nicolas L Roux, Pascal Vincent, Olivier Delalleau, and Patrice Marcotte. Convex neural networks. In *Advances in neural information processing systems*, pp. 123–130, 2006.

Joseph Paul Cohen, Henry Z Lo, and Wei Ding. Randomout: Using a convolutional gradient norm to win the filter lottery. *ICLR Workshop*, 2016.

Nadav Cohen and Amnon Shashua. Inductive bias of deep convolutional networks through pooling geometry. *arXiv preprint arXiv:1605.06743*, 2016.

Misha Denil, Babak Shakibi, Laurent Dinh, Nando De Freitas, et al. Predicting parameters in deep learning. In *Advances in neural information processing systems*, pp. 2148–2156, 2013.

Xin Dong, Shangyu Chen, and Sinno Pan. Learning to prune deep neural networks via layer-wise optimal brain surgeon. In *Advances in Neural Information Processing Systems*, pp. 4860–4874, 2017.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059, 2016.

Yarin Gal, Jiri Hron, and Alex Kendall. Concrete dropout. In *Advances in Neural Information Processing Systems*, pp. 3584–3593, 2017.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256, 2010.

Yiwen Guo, Anbang Yao, and Yurong Chen. Dynamic network surgery for efficient dnns. In *Advances In Neural Information Processing Systems*, pp. 1379–1387, 2016.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. In *Advances in neural information processing systems*, pp. 1135–1143, 2015.

Song Han, Jeff Pool, Sharan Narang, Huizi Mao, Shijian Tang, Erich Elsen, Bryan Catanzaro, John Tran, and William J Dally. Dsd: Regularizing deep neural networks with dense-sparse-dense training flow. *Proceedings of ICLR*, 2017.

Babak Hassibi and David G Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *Advances in neural information processing systems*, pp. 164–171, 1993.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Yihui He, Xiangyu Zhang, and Jian Sun. Channel pruning for accelerating very deep neural networks. In *International Conference on Computer Vision (ICCV)*, volume 2, pp. 6, 2017.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Geoffrey E Hinton, Nitish Srivastava, Alex Krizhevsky, Ilya Sutskever, and Ruslan R Salakhutdinov. Improving neural networks by preventing co-adaptation of feature detectors. *arXiv preprint arXiv:1207.0580*, 2012.

Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

Hengyuan Hu, Rui Peng, Yu-Wing Tai, and Chi-Keung Tang. Network trimming: A data-driven neuron pruning approach towards efficient deep architectures. *arXiv preprint arXiv:1607.03250*, 2016.

Forrest N Iandola, Song Han, Matthew W Moskewicz, Khalid Ashraf, William J Dally, and Kurt Keutzer. Squeezenet: Alexnet-level accuracy with 50x fewer parameters and< 0.5 mb model size. *arXiv preprint arXiv:1602.07360*, 2016.

Xiaojie Jin, Xiaotong Yuan, Jiashi Feng, and Shuicheng Yan. Training skinny deep neural networks with iterative hard thresholding methods. *arXiv preprint arXiv:1607.05423*, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Advances in Neural Information Processing Systems*, pp. 2575–2583, 2015.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pp. 598–605, 1990.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Chunyuan Li, Heerad Farkhoor, Rosanne Liu, and Jason Yosinski. Measuring the intrinsic dimension of objective landscapes. *Proceedings of ICLR*, 2018.

Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. *arXiv preprint arXiv:1608.08710*, 2016.

Christos Louizos, Karen Ullrich, and Max Welling. Bayesian compression for deep learning. In *Advances in Neural Information Processing Systems*, pp. 3290–3300, 2017.

Christos Louizos, Max Welling, and Diederik P Kingma. Learning sparse neural networks through l_0 regularization. *Proceedings of ICLR*, 2018.

Jian-Hao Luo, Jianxin Wu, and Weiyao Lin. Thinet: A filter level pruning method for deep neural network compression. *arXiv preprint arXiv:1707.06342*, 2017.

Zelda Mariet and Suvrit Sra. Diversity networks. *Proceedings of ICLR*, 2016.

Dmitry Molchanov, Arsenii Ashukha, and Dmitry Vetrov. Variational dropout sparsifies deep neural networks. *arXiv preprint arXiv:1701.05369*, 2017.

Pavlo Molchanov, Stephen Tyree, Tero Karras, Timo Aila, and Jan Kautz. Pruning convolutional neural networks for resource efficient transfer learning. *arXiv preprint arXiv:1611.06440*, 2016.

Sharan Narang, Erich Elsen, Gregory Diamos, and Shubho Sengupta. Exploring sparsity in recurrent neural networks. *Proceedings of ICLR*, 2017.

Kirill Neklyudov, Dmitry Molchanov, Arsenii Ashukha, and Dmitry P Vetrov. Structured bayesian pruning via log-normal multiplicative noise. In *Advances in Neural Information Processing Systems*, pp. 6778–6787, 2017.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. *arXiv preprint arXiv:1412.6614*, 2014.

Carl Edward Rasmussen and Zoubin Ghahramani. Occam's razor. In T. K. Leen, T. G. Dietterich, and V. Tresp (eds.), *Advances in Neural Information Processing Systems 13*, pp. 294–300. MIT Press, 2001. URL http://papers.nips.cc/paper/1925-occams-razor.pdf.

Jorma Rissanen. Stochastic complexity and modeling. *The annals of statistics*, pp. 1080–1100, 1986.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Suraj Srinivas and R Venkatesh Babu. Data-free parameter pruning for deep neural networks. *arXiv preprint arXiv:1507.06149*, 2015a.

Suraj Srinivas and R Venkatesh Babu. Learning neural network architectures using backpropagation. *arXiv preprint arXiv:1511.05497*, 2015b.

Suraj Srinivas and R Venkatesh Babu. Generalized dropout. *arXiv preprint arXiv:1611.06791*, 2016.

Suraj Srinivas, Akshayvarun Subramanya, and R Venkatesh Babu. Training sparse neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 138–145, 2017.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *The Journal of Machine Learning Research*, 15(1):1929–1958, 2014.

Li Wan, Matthew Zeiler, Sixin Zhang, Yann Le Cun, and Rob Fergus. Regularization of neural networks using dropconnect. In *International Conference on Machine Learning*, pp. 1058–1066, 2013.

Tien-Ju Yang, Yu-Hsin Chen, and Vivienne Sze. Designing energy-efficient convolutional neural networks using energy-aware pruning. *arXiv preprint*, 2017.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *arXiv preprint arXiv:1611.03530*, 2016.

Wenda Zhou, Victor Veitch, Morgane Austern, Ryan P Adams, and Peter Orbanz. Compressibility and generalization in large-scale deep learning. *arXiv preprint arXiv:1804.05862*, 2018.

Figure 10: The early-stopping iteration and accuracy at early-stopping of the iterative lottery ticket experiment on the mnist architecture when iteratively pruned using the resetting and continued training strategies.

A   ITERATIVE PRUNING STRATEGIES

In this Appendix, we examine two different ways of structuring the iterative pruning strategy that we use throughout the main body of the paper to find winning tickets.

Strategy 1: Resetting.

1. Randomly initialize a neural network $f(x; m \odot \theta)$ where $\theta = \theta_0$ and $m = 1^{|\theta|}$ is a mask.
2. Train the network for j iterations, reaching parameters $m \odot \theta_j$.
3. Prune $s\%$ of the parameters, creating an updated mask m' where $P_{m'} = (P_m - s)\%$.
4. Reset the weights of the remaining portion of the network to their values in θ_0. That is, let $\theta = \theta_0$.
5. Let $m = m'$ and repeat steps 2 through 4 until a sufficiently pruned network has been obtained.

Strategy 2: Continued Training.

1. Randomly initialize a neural network $f(x; m \odot \theta)$ where $\theta = \theta_0$ and $m = 1^{|\theta|}$ is a mask.
2. Train the network for j iterations.
3. Prune $s\%$ of the parameters, creating an updated mask m' where $P_{m'} = (P_m - s)\%$.
4. Let $m = m'$ and repeat steps 2 and 3 until a sufficiently pruned network has been obtained.
5. Reset the weights of the remaining portion of the network to their values in θ_0. That is, let $\theta = \theta_0$.

The difference between these two strategies is that, after each round of pruning, Strategy 2 retrains using the already-trained weights, whereas Strategy 1 resets the network weights back to their initial values before retraining. In both cases, after the network has been sufficiently pruned, its weights are reset back to the original initializations.

Figures 10 and 11 compare the two strategies on the lenet and conv2/4/6 architectures on the hyperparameters we select in Appendices E and F. In all cases, the Strategy 1 maintains higher validation accuracy and faster early-stopping times to smaller network sizes.

B   TRAINING ACCURACY FOR LOTTERY TICKET EXPERIMENTS

This brief appendix accompanies Figures 4 (Section 2) and Figure 5 (Section 3) in the main body of the paper. The aforementioned figures show the iteration of early-stopping, test accuracy at early-stopping, train accuracy at early-stopping, and test accuracy at the end of the training process.

Figure 11: The early-stopping iteration and accuracy at early-stopping of the iterative lottery ticket experiment on the conv2, conv4, and conv6 architectures when iteratively pruned using the resetting and continued training strategies.

Figure 12: Figure 4 augmented with a graph of the training accuracy at the end of 50,000 iterations.

However, we did not have the space to include a graph of the training accuracy at the end of the training process, which we assert to be 100% for all but the most heavily pruned networks. In this Appendix, we include that additional graph for reference.

C   COMPARING RANDOM REINITIALIZATION AND RANDOM SPARSITY

In this Appendix, we compare:

1. Networks found via iterative pruning with the original initializations (blue line in Figure 14).

2. Networks found via iterative pruning that are randomly reinitialized (orange line in Figure 14).

3. Random sparse subnetworks with the same number of parameters as those found via iterative pruning (green line in Figure 14).

Figure 14 shows this comparison for all of the major experiments in this paper. For the fully-connected lenet architecture for MNIST, we find that the randomly reinitialized networks outperform random sparisty. However, for all of the other, convolutional networks studied in this paper, there is no significant difference in performance between the two. We hypothesize that the fully-connected network for MNIST sees these benefits because only certain parts of the MNIST images contain useful information for classification, meaning connections in some parts of the network will be more valuable than others. This is less true with convolutions, which are not constrained to any one part of the input image.

Figure 13: Figure 5 augmented with a graph of the training accuracy at the end of the training process.

D   EXAMINING WINNING TICKETS

In this Appendix, we examinine the structure of winning tickets to gain insight into why winning tickets are able to learn effectively even when so heavily pruned. Throughout this appendix, we study the winning tickets from the lenet architecture trained on MNIST. Unless otherwise stated, we use the same hyperparameters as in Section 2: glorot initialization and adam optimization.

D.1   WINNING TICKET INITIALIZATIONS (ADAM)

Figure 15 shows the distributions of winning ticket initializations for four different levels of P_m. To clarify, these are the distributions of the initial weights of the connections that have survived the pruning process. The blue, orange, and green lines show the distribution of weights for the first hidden layer, second hidden layer, and output layer, respectively. The weights are collected from five different trials of the lottery ticket experiment, but the distributions for each individual trial closely mirror those aggregated from across all of the trials. The histograms have been normalized so that the area under each curve is 1.

The left-most graph in Figure 15 shows the initialization distributions for the unpruned networks. We use glorot initialization, so each of the layers has a different standard deviation. As the network is pruned, the first hidden layer maintains its distribution. However, the second hidden layer and the output layer become increasingly bimodal, with peaks on either side of 0. Interestingly, the peaks are asymmetric: the second hidden layer has more positive initializations remaining than negative initializations, and the reverse is true for the output layer. We found this pattern to hold for each of the trials individually, so the aggregated results in Figure 15 are representative.

The connections in the second hidden layer and output layer that survive the pruning process tend to have higher magnitude-initializations. Since we find winning tickets by pruning the connections with the lowest magnitudes in each layer at the *end*, the connections with the lowest-magnitude initializations must still have the lowest-magnitude weights at the end of training. A different trend holds for the input layer; it maintains its distribution, meaning a connection's initialization has less relation to its final weight.

Figure 14: The test accuracy at the last training iteration for each of the networks studied in this paper.

Figure 15: The distribution of initializations in winning tickets pruned to the levels specified in the titles of each plot. The blue, orange, and green lines show the distributions for the first hidden layer, second hidden layer, and output layer of the lenet architecture for MNIST when trained with the adam optimizer and the hyperparameters used in 2. The distributions have been normalized so that the area under each curve is 1.

Figure 16: Same as Figure 15 where the network is trained with SGD at rate 0.8.

D.2 WINNING TICKET INITIALIZATIONS (SGD)

We also consider the winning tickets obtained when training the network with SGD learning rate 0.8 (selected as described in Appendix E). The bimodal distributions from Figure 15 are present across all layers (see Figure 16. The connections with the highest-magnitude initializations are more likely to survive the pruning process, meaning winning ticket initializations have a bimodal distribution with peaks on opposite sides of 0. Just as with the adam-optimized winning tickets, these peaks are of different sizes, with the first hidden layer favoring negative initializations and the second hidden layer and output layer favoring positive initializations. Just as with the adam results, we confirm that each individual trial evidences the same asymmetry as the aggregate graphs in Figure 16.

D.3 REINITIALIZING FROM WINNING TICKET INITIALIZATIONS

Considering that the initialization distributions of winning tickets $\mathcal{D}_m$ are so different from the Gaussian distribution $\mathcal{D}$ used to initialize the unpruned network, it is natural to ask whether randomly reinitializing winning tickets from $\mathcal{D}_m$ rather than $\mathcal{D}$ will improve winning ticket performance. We do not find this to be the case. Figure 17 shows the performance of winning tickets whose initializations are randomly sampled from the distribution of initializations contained in the winning tickets for adam. More concretely, let $\mathcal{D}_m = \{\theta_0^{(i)} | m^{(i)} = 1\}$ be the set of initializations found in the winning ticket with mask m. We sample a new set of parameters $\theta_0' \sim \mathcal{D}_m$ and train the network $f(x; m \odot \theta_0')$. We perform this sampling on a per-layer basis. The results of this experiment are in Figure 17. Winning tickets reinitialized from $\mathcal{D}_m$ perform little better than when randomly reinitialized from $\mathcal{D}$. We attempted the same experiment with the SGD-trained winning tickets and found similar results.

D.4 PRUNING AT ITERATION 0

One other way of interpreting the graphs of winning ticket initialization distributions is as follows: weights that begin small stay small, get pruned, and never become part of the winning ticket. (The

Figure 17: The performance of the winning tickets of the lenet architecture for MNIST when the layers are randomly reinitialized from the distribution of initializations contained in the winning ticket of the corresponding size.

Figure 18: The performance of the winning tickets of the lenet architecture for MNIST when magnitude pruning is performed before the network is ever trained. The network is subsequently trained with adam.

only exception to this characterization is the first hidden layer for the adam-trained winning tickets.) If this is the case, then perhaps low-magnitude weights were never important to the network and can be pruned from the very beginning. Figure 18 shows the result of attempting this pruning strategy. Winning tickets selected in this fashion perform even worse than when they are found by iterative pruning and randomly reinitialized. We attempted the same experiment with the SGD-trained winning tickets and found similar results.

D.5   COMPARING INITIAL AND FINAL WEIGHTS IN WINNING TICKETS

In this subsection, we consider winning tickets in the context of the larger optimization process. To do so, we examine the initial and final weights of the unpruned network from which a winning ticket derives to determine whether weights that will eventually comprise a winning ticket exhibit properties that distinguish them from the rest of the network.

We consider the magnitude of the difference between initial and final weights. One possible rationale for the success of winning tickets is that they already happen to be close to the optimum that gradient descent eventually finds, meaning that winning ticket weights should change by a smaller amount than the rest of the network. Another possible rationale is that winning tickets are well placed in the optimization landscape for gradient descent to optimize productively, meaning that winning ticket weights should change by a larger amount than the rest of the network. Figure 19 shows that winning ticket weights tend to change by a larger amount then weights in the rest of the network, evidence that does not support the rationale that winning tickets are already close to the optimum.

It is notable that such a distinction exists between the two distributions. One possible explanation for this distinction is that the notion of a winning ticket may indeed be a natural part of neural network optimization. Another is that magnitude-pruning biases the winning tickets we find toward those containing weights that change in the direction of higher magnitude. Regardless, it offers hope that winning tickets may be discernable earlier in the training process (or after a single training run), meaning that there may be more efficient methods for finding winning tickets than iterative pruning.

Figure 19: Between the first and last training iteration of the unpruned network, the magnitude by which weights in the network change. The blue line shows the distribution of magnitudes for weights that are not in the eventual winning ticket; the orange line shows the distribution of magnitudes for weights that are in the eventual winning ticket.

E   HYPERPARAMETER EXPLORATION FOR FULLY-CONNECTED NETWORKS

This Appendix accompanies Section 2 of the main paper. It explores the space of hyperparameters for the lenet architecture evaluated in Section 2 with two purposes in mind:

1. To explain the hyperparameters selected in the main body of the paper.

2. To evaluate the extent to which the lottery ticket experiment patterns extend to other choices of hyperparameters.

E.1   EXPERIMENTAL METHODOLOGY

This Section considers the fully-connected lenet architecture (LeCun et al., 1998), which comprises two fully-connected hidden layers and a ten unit output layer, on the MNIST dataset. Unless otherwise stated, the hidden layers have 300 and 100 units each.

The MNIST dataset consists of 60,000 training examples and 10,000 test examples. We randomly sampled a 5,000-example validation set from the training set and used the remaining 55,000 training examples as our training set for the rest of the paper (including Section 2). The hyperparameter selection experiments throughout this Appendix are evaluated using the validation set for determining both the iteration of early-stopping and the accuracy at early-stopping; the examples in the main body of this paper (which make use of these hyperparameters) are evaluate accuracy on the test set. The training set is presented to the network in mini-batches of 60 examples; at each epoch, the entire training set is shuffled.

Unless otherwise noted, each line in each graph comprises data from three separate experiments. The line itself traces the average performance of the experiments and the error bars indicate the minimum and maximum performance of any one experiment.

Throughout this Appendix, we perform the lottery ticket experiment iteratively with a pruning rate of 20% per iteration (10% for the output layer); we justify the choice of this pruning rate later in this Appendix. On each iteration of the lottery ticket experiment, the network is trained for 50,000 training iterations regardless of when early-stopping occurs; in other words, no validation or test data is taken into account during the training process, and early-stopping times are determined retroactively by examining validation performance. We sample validation and test performance every 100 iterations.

For the main body of the paper, we opt to use the Adam optimizer (Kingma & Ba, 2014) and Gaussian Glorot initialization (Glorot & Bengio, 2010). Although we can achieve more impressive results on the lottery ticket experiment with other hyperparameters, we intend these choices to be as generic as possible in an effort to minimize the extent to which our main results depend on hand-chosen hyperparameters. In this Appendix, we select the learning rate for Adam that we use in the main body of the paper.

Figure 20: The validation loss as training progresses for several different levels of pruning in the iterative pruning experiment. Each line is the average of five training runs at the same level of iterative pruning; the labels are the percentage of weights from the original network that remain after pruning. Each network was trained with Adam at a learning rate of 0.0012. The left graph shows winning tickets that learn increasingly faster than the original network and reach lower loss. The middle graph shows winning tickets that learn increasingly slower after the fastest early-stopping time has been reached. The right graph contrasts the loss of winning tickets to the loss of randomly reinitialized networks.

Figure 21: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the lenet architecture trained with MNIST using the Adam optimizer at various learning rates. Each line represents a different learning rate.

In addition, we consider a wide range of other hyperparameters, including other optimization algorithms (SGD with and without momentum), initialization strategies (Gaussian distributions with various standard deviations), network sizes (larger and smaller hidden layers), and pruning strategies (faster and slower pruning rates). In each experiment, we vary the chosen hyperparameter while keeping all others at their default values (Adam with the chosen learning rate, Gaussian Glorot initialization, hidden layers with 300 and 100 units). The data presented in this appendix was collected by training variations of the lenet architecture more than 3,000 times.

Since we are interested in the speed at which networks learn, we study the iteration of minimum validation loss (for hyperparameter selection)—the moment when we would stop training according to the early-stopping criterion. Validation and test loss follow a pattern where they decrease early in the training process, reach a minimum, and then begin to increase as the model overfits to the training data. Figure 20 shows an example of the validation loss as training progresses; these graphs use iterative pruning and Adam with a learning rate of 0.0012 (the learning rate we will select in the following subsection).

E.2 LEARNING RATE

In this Subsection, we perform the lottery ticket experiment on the lenet architecture as optimized with Adam, SGD, and SGD with momentum at various learning rates.

Here, we select the learning rate that we use for Adam in the main body of the paper. Our criteria for selecting the learning rate are as follows:

Figure 22: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the lenet architecture trained with MNIST using stochastic gradient descent at various learning rates.

1. On the unpruned network, it should minimize training iterations necessary to reach early-stopping and maximize validation accuracy at that iteration. That is, it should be a reasonable hyperparameter for optimizing the unpruned network even if we are not running the lottery ticket experiment.

2. When running the iterative lottery ticket experiment, it should make it possible to match the early-stopping iteration and accuracy of the original network with as few parameters as possible.

3. Of those options that meet (1) and (2), it should be on the conservative (slow) side so that it is more likely to productively optimize heavily pruned networks under a variety of conditions with a variety of hyperparameters.

Figure 21 shows the early-stopping iteration and validation accuracy at that iteration of performing the iterative lottery ticket experiment with the lenet architecture optimized with Adam at various learning rates. According to the graph on the right of Figure 21, several learning rates between 0.0002 and 0.002 achieve similar levels of validation accuracy on the original network and maintain that performance to similar levels as the network is pruned. Of those learning rates, 0.0012 and 0.002 produce the fastest early-stopping times and maintain them to the smallest network sizes. We choose 0.0012 due to its higher validation accuracy on the unpruned network and in consideration of criterion (3) above.

We note that, across all of these learning rates, the lottery ticket pattern (in which learning becomes faster and validation accuracy increases with iterative pruning) remains present. Even for those learning rates that did not satisfy the early-stopping criterion within 50,000 iterations (2.5e-05 and 0.0064) still showed accuracy improvements with pruning.

E.3 OTHER OPTIMIZATION ALGORITHMS

E.3.1 SGD

Here, we explore the behavior of the lottery ticket experiment when the network is optimized with stochastic gradient descent (SGD) at various learning rates. The results of doing so appear in Figure 22. The lottery ticket pattern appears across all learning rates, including those that fail to satisfy the early-stopping criterion within 50,000 iterations. SGD learning rates 0.4 and 0.8 reach early-stopping in a similar number of iterations as the best Adam learning rates (0.0012 and 0.002) but maintain this performance when the network has been pruned further (to less than 1% of its original size for SGD vs. about 5% of the original size for Adam). Likewise, on pruned networks, these SGD learning rates achieve equivalent accuracy to the best Adam learning rates, and they maintain that high accuracy when the network is pruned as much as the Adam learning rates.

Figure 23: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the lenet architecture trained with MNIST using stochastic gradient descent with momentum (0.9) at various learning rates.

E.3.2 MOMENTUM

Here, we explore the behavior of the lottery ticket experiment when the network is optimized with SGD with momentum (0.9) at various learning rates. The results of doing so appear in Figure 23. Once again, the lottery ticket pattern appears across all learning rates, with learning rates between 0.025 and 0.1 maintaining high validation accuracy and faster learning for the longest number of pruning iterations. Learning rate 0.025 achieves the highest validation accuracy on the unpruned network and the fastest early-stopping times when pruned to less than 1% of its original size; however, its validation accuracy never increases as it is pruned, instead decreasing gradually.

E.4 ITERATIVE PRUNING RATE

Figure 24 shows the early-stopping iterations and validation accuracy when the lenet architecture is trained with Adam at our chosen learning rate and pruned iteratively at different rates. There is a tangible difference in learning speed and validation accuracy at early-stopping between the lowest pruning rates (0.1 and 0.2) and higher pruning rates (0.4 and above). The lowest pruning rates reach higher validation accuracy and maintain that validation accuracy to smaller network sizes; they also maintain fast early-stopping times to smaller network sizes. For the experiments throughout the main body of the paper and this Appendix, we use a pruning rate of 0.2, which mantains much of the accuracy and learning speed of 0.1 while reducing the number of training iterations necessary to get to smaller network sizes.

In all of the lenet experiments, we prune the output layer at half the rate of the rest of the network. Since the output layer is so small (1,000 weights out of 266,000 for the overall lenet architecture), we found that pruning it reaches a point of diminishing returns much before the other layers. In future work, it is worth considering strategies for finding the ideal pruning rates for each individual layer of the network.

E.5 INITIALIZATION DISTRIBUTION

To this point, we have considered only a Gaussian Glorot (Glorot & Bengio, 2010) initialization scheme for the network. Figure 25 performs the lottery ticket experiment while initialializing the lenet architecture from Gaussian distributions with a variety of standard deviations. The networks were optimized with Adam at the learning rate chosen earlier. The lottery ticket pattern continues to appear across all standard deviations. When initialized from a Gaussian distribution with standard deviation 0.1, the lenet architecture maintained high validation accuracy and low early-stopping times for the longest, approximately matching the performance of the Glorot-initialized network.

E.6 NETWORK SIZE

Throughout this section, we have considered the lenet architecture with 300 units in the first hidden layer and 100 units in the second hidden layer. Figure 26 shows the early-stopping iterations and

Figure 24: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment when pruned at different rates. Each line represents a different *pruning rate*—the percentage of lowest-magnitude weights that are pruned after each training iteration.

Figure 25: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment initialized with Gaussian distributions with various standard deviations. Each line is a different standard deviation for a Gaussian distribution centered at 0.

Figure 26: The early-stopping iteration and validation accuracy at at that iteration of the iterative lottery ticket experiment on the lenet architecture with various layer sizes. The label for each line is the size of the first and second hidden layers of the network. All networks had Gaussian Glorot initialization and were optimized with Adam (learning rate 0.0012). Note that the x-axis of this plot charts the number of *weights* remaining, while all other graphs in this section have charted the *percent* of weights remaining.

validation accuracy at that iteration of the lenet architecture with several other layer sizes. All networks we tested maintain the 3:1 ratio between units in the first hidden layer and units in the second hidden layer.

The lottery ticket hypothesis naturally invites a collection of questions related to network size. Generalizing, those questions tend to take the following form: according to the lottery ticket hypothesis, do larger networks, which contain more subnetworks, find "better" winning tickets? In line with the generality of this question, there are several different answers.

If we evaluate a winning ticket by the accuracy it achieves, then larger networks do find better winning tickets. The right graph in Figure 26 shows that, for any particular number of weights (that is, any particular point on the x-axis), winning tickets derived from initially larger networks reach higher accuracy. Put another way, in terms of accuracy, the lines are approximately arranged from bottom to top in increasing order of network size. It is possible that, since larger networks have more subnetworks, gradient descent found a better winning ticket. Alternatively, the initially larger networks have more units even when pruned to the same number of weights as smaller networks, meaning they are able to contain sparse subnetwork configurations that cannot be expressed by initially smaller networks.

If we evaluate a winning ticket by the time necessary for it to reach early-stopping, then larger networks have less of an advantage. The left graph in Figure 26 shows that, in general, early-stopping iterations do not vary greatly between networks of different initial sizes that have been pruned to the same number of weights. Upon exceedingly close inspection, winning tickets derived from initially larger networks tend to learn marginally faster than winning tickets derived from initially smaller networks, but these differences are slight.

If we evaluate a winning ticket by the size at which it returns to the same accuracy as the original network, the large networks do not have an advantage. Regardless of the initial network size, the right graph in Figure 26 shows that winning tickets return to the accuracy of the original network when they are pruned to between about 9,000 and 15,000 weights.

F   HYPERPARAMETER EXPLORATION FOR CONVOLUTIONAL NETWORKS

This Appendix accompanies Sections 3 and 4 of the main paper. It explores the space of optimization algorithms and hyperparameters for the conv2, conv4, and conv6 architectures evaluated in Section 3 and 4 with the same two purposes as Appendix E: explaining the hyperparameters used in the main body of the paper and evaluating the lottery ticket experiment on other choices of hyperparameters.

F.1   Experimental Methodology

The conv2, conv4, and conv6 architectures are variants of the VGG (Simonyan & Zisserman, 2014) network architecture scaled down for the CIFAR10 (Krizhevsky & Hinton, 2009) dataset. Like VGG, the networks consist of a series of modules. Each module has two layers of 3x3 convolutional filters followed by a maxpool layer with stride 2. After all of the modules are two fully-connected layers of size 256 followed by an output layer of size 10; in VGG, the fully-connected layers are of size 4096 and the output layer is of size 1000. Like VGG, the first module has 64 convolutions in each layer, the second has 128, the third has 256, etc. The conv2, conv4, and conv6 architectures have 1, 2, and 3 modules, respectively.

The CIFAR10 dataset consists of 50,000 32x32 color (three-channel) training examples and 10,000 test examples. We created a 5,000-example validation set from the training set and used the remaining 45,000 training examples as our training set for the rest of the paper. The hyperparameter selection experiments throughout this Appendix are evaluated on the validation set, and the examples in the main body of this paper (which make use of these hyperparameters) are evaluated on test set. The training set is presented to the network in mini-batches of 60 examples; at each epoch, the entire training set is shuffled.

The conv2, conv4, and conv6 networks are initialized with Gaussian Glorot initialization (Glorot & Bengio, 2010) and are trained for the number of iterations specified in Figure 2. The number of training iterations was selected such that heavily-pruned networks could still train in the time provided. On dropout experiments, the number of training iterations is tripled to provide enough time for the dropout-regularized networks to train. We optimize these networks with Adam, and select the learning rate for each network in this Appendix.

As with the MNIST experiments, validation and test performance is only considered retroactively and has no effect on the progression of the lottery ticket experiments. We measure validation and test loss and accuracy every 100 training iterations.

Each line in each graph of this section represents the average of three separate experiments, with error bars indicating the minimum and maximum value that any experiment took on at that point. (Experiments in the main body of the paper are conducted five times.)

We allow convolutional layers and fully-connected layers to be pruned at different rates; we select those rates for each network in this Appendix. The output layer is pruned at half of the rate of the fully-connected layers for the reasons described in Appendix E.

F.2   Learning Rate

In this Subsection, we perform the lottery ticket experiment on the the conv2, conv4, and conv6 architectures as optimized with Adam at various learning rates.

Here, we select the learning rate that we use for Adam in the main body of the paper. Our criteria for selecting the learning rate are the same as in Appendix E: minimizing training iterations and maximizing accuracy at early-stopping, finding winning tickets containing as few parameters as possible, and remaining conservative enough to apply to a range of other experiments.

Figure 27 shows the results of performing the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures. Since we have not yet selected the pruning rates for each network, we temporarily pruned fully-connected layers at 20% per iteration, convolutional layers at 10% per iteration, and the output layer at 10% per iteration; we explore this part of the hyperparameter space in a later subsection.

For conv2, we selct a learning rate of 0.0002, which has the highest initial validation accuracy, maintains both high validation accuracy and low early-stopping times for the among the longest, and reaches the fastest early-stopping times. This learning rate also leads to a 3.3 percentage point improvement in validation accuracy when the network is pruned to 3% of its original size. Other learning rates, such 0.0004, have lower initial validation accuracy (65.2% vs 67.6%) but eventually reach higher absolute levels of validation accuracy (71.7%, a 6.5 percentage point increase, vs. 70.9%, a 3.3 percentage point increase). However, learning rate 0.0002 shows the highest proportional decrease in early-stopping times: 4.8x (when pruned to 8.8% of the original network size).

Figure 27: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures trained using the Adam optimizer at various learning rates. Each line represents a different learning rate.

For conv4, we select learning rate 0.0003, which has among the highest initial validation accuracy, maintains high validation accuracy and fast early-stopping times when pruned by among the most, and balances improvements in validation accuracy (3.7 percentage point improvement to 78.6% when 5.4% of weights remain) and improvements in early-stopping time (4.27x when 11.1% of weights remain). Other learning rates reach higher validation accuracy (0.0004—3.6 percentage point improvement to 79.1% accuracy when 5.4% of weights remain) or show better improvements in early-stopping times (0.0002—5.1x faster when 9.2% of weights remain) but not both.

For conv6, we also select learning rate 0.0003 for similar reasons to those provided for conv4. Validation accuracy improves by 2.4 percentage points to 81.5% when 9.31% of weights remain and early-stopping times improve by 2.61x when pruned to 11.9%. Learning rate 0.0004 reaches high final validation accuracy (81.9%, an increase of 2.7 percentage points, when 15.2% of weights remain) but with smaller improvements in early-stopping times, and learning rate 0.0002 shows greater improvements in early-stopping times (6.26x when 19.7% of weights remain) but reaches lower overall validation accuracy.

We note that, across nearly all combinations of learning rates, the lottery ticket pattern—where early-stopping times were maintain or decreased and validation accuracy was maintained or increased during the course of the lottery ticket experiment—continued to hold. This pattern failed to hold at the very highest learning rates: early-stopping times decreased only briefly (in the case of conv2 or conv4) or not at all (in the case of conv6), and accuracy increased only briefly (in the case of all three networks). This pattern is similar to that which we observe in Section 5: at the highest learning rates, our iterative pruning algorithm fails to find winning tickets.

F.3 OTHER OPTIMIZATION ALGORITHMS

F.3.1 SGD

Here, we explore the behavior of the lottery ticket experiment when the conv2, conv4, and conv6 networks are optimized with stochastic gradient descent (SGD) at various learning rates. The results of doing so appear in Figure 28. In general, these networks—particularly conv2 and conv4—proved challenging to train with SGD and Glorot initialization. As Figure 28 reflects, we could not find SGD learning rates for which the unpruned networks matched the validation accuracy of the same networks when trained with Adam; at best, the SGD-trained unpruned networks were typically 2-3 percentage points less accurate. At higher learning rates than those in Figure 27, gradients tended to explode when training the unpruned network; at lower learning rates, the networks often failed to learn at all.

At all of the learning rates depicted, we found winning tickets. In all cases, early-stopping times initially decreased with pruning before eventually increasing again, just as in other lottery ticket experiments. The conv6 network also exhibited the same accuracy patterns as other experiments, with validation accuracy initially increasing with pruning before eventually decreasing again.

However, the conv2 and conv4 architectures exhibited a different validation accuracy pattern from other experiments in this paper. Accuracy initially declined with pruning before rising as the network was further pruned and eventually matching or surpassing the accuracy of the unpruned network. When they reached this accuracy level, the pruned networks still reached the point of early-stopping in about the same or fewer iterations than the unpruned network, constituting a winning ticket by our definition. Interestingly, this pattern also appeared for conv6 networks at slower SGD learning rates, suggesting that faster learning rates for conv2 and conv4 than those in Figure 27 might cause the usual lottery ticket accuracy pattern to reemerge. Unfortunately, at these higher learning rates, gradients exploded on the unpruned networks, preventing us from running these experiments.

F.3.2 MOMENTUM

Here, we explore the behavior of the lottery ticket experiment when the network is optimized with SGD with momentum (0.9) at various learning rates. The results of doing so appear in Figure 29. In general, the lottery ticket pattern continues to apply, with early-stopping times decreasing and accuracy increasing as the networks are pruned. However, there were two exceptions to this pattern:

Figure 28: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures trained using SGD at various learning rates. Each line represents a different learning rate. The legend for each pair of graphs is above the graphs.

Figure 29: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures trained using SGD with momentum (0.9) at various learning rates. Each line represents a different learning rate. The legend for each pair of graphs is above the graphs. Lines that are unstable and contain large error bars (large vertical lines) indicate that some experiments failed to learn effectively, leading to very low accuracy and very high early-stopping times; these experiments reduce the averages that the lines trace and lead to much wider error bars.

1. At the very lowest learning rates (e.g., learning rate 0.001 for conv4 and all but the highest learning rate for conv2), accuracy initially decreased before increasing to higher levels than reached by the unpruned network; this is the same pattern we observed when training these networks with SGD.

2. At the very highest learning rates (e.g., learning rates 0.005 and 0.008 for conv2 and conv4), early-stopping times never decreased and instead remained stable before increasing; this is the same pattern we observed for the highest learning rates when training with Adam.

Figure 30: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures with an iterative pruning rate of 20% for fully-connected layers. Each line represents a different iterative pruning rate for convolutional layers.

F.4 Iterative Pruning Rate

For the convolutional network architectures, we select different pruning rates for convolutional and fully-connected layers. In the conv2 and conv4 architectures, convolutional parameters make up a relatively small portion of the overall number of parameters in the models. By pruning convolutions more slowly, we are likely to be able to prune the model further while maintaining performance. In other words, we hypothesize that, if all layers were pruned evenly, convolutional layers would become a bottleneck that would make it more difficult to find lower parameter-count models that are still able to learn. For conv6, the opposite may be true: since nearly two thirds of its parameters are in convolutional layers, pruning fully-connected layers could become the bottleneck.

Our criterion for selecting hyperparameters in this section is to find a combination of pruning rates that allows networks to reach the lowest possible parameter-counts while maintaining validation accuracy at or above the original accuracy and early-stopping times at or below that for the original network.

Figure 30 shows the results of performing the iterative lottery ticket experiment on conv2 (top), conv4 (middle), and conv6 (bottom) with different combinations of pruning rates.

According to our criteria, we select an iterative convolutional pruning rate of 10% for conv2, 10% for conv4, and 15% for conv6. However, across all convolutional pruning rates, the lottery ticket pattern continued to appear.

F.5 LEARNING RATES (DROPOUT)

In order to train the conv2, conv4, and conv6 architectures with dropout, we repeated the exercise from the previous Subsection to select appropriate learning rates. Figure 27 shows the results of performing the iterative lottery ticket experiment on conv2 (top), conv4 (middle), and conv6 (bottom) with dropout and Adam at various learning rates. A network trained with dropout takes longer to learn, so we trained each architecture for three times as many iterations as in the experiments without dropout: 60,000 iterations for conv2, 75,000 iterations for conv4, and 90,000 iterations for conv6. We iteratively pruned these networks at the rates determined in Section F.4.

The conv2 network proved to be difficult to consistently train with dropout. The top right graph in Figure 31 contains wide error bars and low average accuracy for many learning rates, especially early in the lottery ticket experiments. This indicates that some or all of the training runs failed to learn; when they were averaged into the other results, they produced the aforementioned pattern in the graphs. At learning rate 0.0001, none of the three trials learned productively until pruned to more than 26.5%, at which point all three trials started learning. At learning rate 0.0002, some of the trials failed to learn productively until several rounds of iterative pruning had passed. At learning rate 0.0003, all three networks learned productively at every pruning level. At learning rate 0.0004, one network occasionally failed to learn. We selected learning rate 0.0003, which seemed to allow networks to learn productively most often while achieving among the highest initial accuracy.

It is interesting to note that networks that were unable to learn at a particular learning rate (for example, 0.0001) eventually began learning after several rounds of the lottery ticket experiment (that is, training, pruning, and resetting repeatedly). It is worth investigating whether this phenomenon was entirely due to pruning (that is, removing any random collection of weights would put the network in a configuration more amenable to learning) or whether training the network provided useful information for pruning, even if the network did not show improved accuracy.

For both the conv4 and conv6 architectures, a slightly slower learning rate (0.0002 as opposed to 0.0003) leads to the highest accuracy on the unpruned networks in addition to the highest sustained accuracy and fastest sustained learning as the networks are pruned during the lottery ticket experiment.

With dropout, the unpruned conv4 architecture reaches an average validation accuracy of 77.6%, a 2.7 percentage point improvement over the unpruned conv4 network trained without dropout and one percentage point lower than the highest average validation accuracy attained by a winning ticket. The dropout-trained winning tickets reach 82.6% average validation accuracy when pruned to 7.6%. Early-stopping times improve by up to 1.58x (when pruned to 7.6%), a smaller improvement than then 4.27x achieved by a winning ticket obtained without dropout.

With dropout, the unpruned conv6 architecture reaches an average validation accuracy of 81.3%, an improvement of 2.2 percentage points over the accuracy without dropout; this nearly matches the 81.5% average accuracy obtained by conv6 trained without dropout and pruned to 9.31%. The dropout-trained winning tickets further improve upon these numbers, reaching 84.8% average validation accuracy when pruned to 10.5%. Improvements in early-stopping times are less dramatic than without dropout: a 1.5x average improvement when the network is pruned to 15.1%.

At all learning rates we tested, the lottery ticket pattern generally holds for accuracy, with improvements as the networks are pruned. However, not all learning rates show the decreases in early-stopping times. To the contrary, none of the learning rates for conv2 show clear improvements in early-stopping times as seen in the other lottery ticket experiments. Likewise, the faster learning rates for conv4 and conv6 maintain the original early-stopping times until pruned to about 40%, at which point early-stopping times steadily increase.

Figure 31: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the conv2 (top), conv4 (middle), and conv6 (bottom) architectures trained using dropout and the Adam optimizer at various learning rates. Each line represents a different learning rate.

G   HYPERPARAMETER EXPLORATION FOR RESNET18

This Appendix accompanies the resnet18 experiments in Section 5. It explores the space of hyper-parametres for the resnet18 architecture evaluated in Section 5 in order to explain the hyperparameters used in the body of the paper and evaluate the lottery ticket experiment on other hyperparameters.

The resnet18 architecture was first introduced by He et al. (2016). The architecture comprises 20 total layers as described in Figure 2: a convolutional layer followed by nine pairs of convolutional layers (with residual connections around the pairs) and a fully-connected output layer.

We follow the experimental design of He et al. (2016):

- We divide the training set into 45,000 training examples and 5,000 validation examples. We use the validation set to select hyperparameters in this appendix and the test set to evaluate in Section 5.
- We augment training data using random flips and random four pixel pads and crops.
- We use a batch size of 128.
- We use batch normalization.
- We use weight decay of 0.0001.
- We use three stages of training at decreasing learning rates. Our stages last for 20,000, 5,000, and 5,000 iterations each, shorter than the 32,000, 16,000, and 16,000 used in He et al. (2016). Since each of our iterative pruning experiments requires training the network 30 times consecutively, we select this abbreviated training schedule to make it possible to explore a wider range of hyperparameters.

We use Gaussian Glorot initialization.

Since more than 98% of the weights in the network are in convolutions, we prune convolutions at a rate of 10% per iteration. We do not prune the 2560 parameters used to downsample residual connections or the 640 parameters in the fully-connected output layer, as they comprise such a small portion of the overall network.

For this experiment, we consider four sets of learning rate hyperparameters:

1. The learning rate hyperparameters from He et al. (2016): SGD with momentum (0.9) with learning rates of 0.1, 0.01, and 0.001 at the three training stages.

2. An alternate set of learning rates for SGD with momentum that are designed to find small, high-accuracy winning tickets.

3. An alternate set of learning rates for SGD (without momentum) that are designed to find small, high-accuracy winning tickets.

4. An alternative set of hyperparameters for SGD with momentum with linear learning rate warmup. Those hyperparameters include the learning rate and the number of iterations of warmup.

For the hyperparameter search, we prune convolutions at 20% per iteration in order to make it possible to explore the space of hyperparameters efficiently.

G.1   LEARNING RATE

In He et al. (2016), the network is trained with stochastic gradient descent (SGD) with momentum (0.9) at a learning rate of 0.1 for the first training stage, 0.01 for the second training stage, and 0.001 for the third training stage. We found that these hyperparameters produce the highest accuracy on the unpruned network of any hyperparameters we explored. However, our method for finding winning tickets (iterative pruning and resetting back to the original initalizations) is not successful with these hyperparameters. In this Subsection, we search for hyperparameters for SGD with and without momentum for which our method finds winning tickets.

We do by greedily selecting the learning rates that produce the highest-accuracy winning tickets at the smallest network sizes at the end of each stage of the learning rate schedule. In other words, we

Figure 32: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the resnet18 architecture as trained with SGD. The top row shows the early-stopping times and accuracy when training the network only for the first stage at various learning rates. The second row shows the early-stopping times and accuracy when training the network for the first two stages with our selected rate for the first stage (0.08) and various rates for the second stage. The third row shows the early-stopping times and accuracy when training the network for all three stages with our selected rates for the first two stages (0.08, 0.008) and various rates for the third stage. Each line corresponds to a particular learning rate, and the legends are above the corresponding graphs.

select the learning rate for the first stage of training by training the network only for the first stage at various learning rates. Once we select a learning rate for the first stage, we train for the first two stages with various second-stage learning rates. We follow the same procedure for the third stage once we have selected learning rates for the first two stages.

G.2 SGD

Here, we select learning rates for the lottery ticket experiment on resnet18 when the network is optimized with SGD. Figure 32 shows the results of performing the lottery ticket experiment on resnet18 at various learning rates. The top row shows the early-stopping times and accuracy when training the network only for the first stage at various learning rates. The second row shows the early-

stopping times and accuracy when training the network for the first two stages with our selected rate for the first stage (0.08) and various rates for the second stage. The third row shows the early-stopping times and accuracy when training the network for all three stages with our selected rates for the first two stages (0.08, 0.008) and various rates for the third stage.

In the first stage, learning rates between 0.04 and 0.1 show the typical lottery ticket pattern and reach accuracy levels above that of the original network until the network has been pruned to approximately 10%. At learning rates above 0.16, accuracy never increases as the network is iteratively pruned. We select a rate in the middle of the range of rates that produce improvements in accuracy: 0.08.

In the second stage, the range of learning rates we consider all evidence the lottery ticket pattern for accuracy. Since the second stage is a fine-tuning step that builds on the first stage, it is unsurprising that it mimics the accuracy pattern we observe for our selected learning rate during the first stage. We select learning rate 0.008 for the second stage, although there are many valid learning rates from among those we considered.

The third stage behaves in the same manner as the second stage for the same reasons. We select learning rate 0.0012, but there are many choices that result in similar behavior.

G.3 MOMENTUM

Here, we select learning rates for the lottery ticket experiment on resnet18 when the network is optimized with SGD with momentum (0.9), the same framework as used in He et al. (2016). The results of doing so are in Figure 33, which has the same structure as Figure 32.

In the first stage, learning rates between 0.006 and 0.01 produce the highest accuracy sustained to the smallest winning ticket sizes. Lower learning rates result in lower accuracy. Higher learning rates (such as 0.1, the rate used in He et al. (2016)) never lead to higher accuracy as the network is pruned. We select learning rate 0.008, which is in the middle of this range. Note that this learning rate is nearly an order of magnitude lower than the first stage learning rate in He et al. (2016). This learning rate produces peak validation accuracy of about 88%, about three percentage points higher than the validation accuracy learning rate 0.1 produces on the unpruned network. However, this accuracy advantage eventually disappears during the further pruning stages.

In the second stage, the range of learning rates we consider all evidence the lottery ticket pattern for accuracy. As with SGD, the second stage is a fine-tuning step, so it is unsurprising that it reflects the accuracy pattern of the first stage. We select learning rate 0.0008, which is in the middle of the range we consider.

The third stage has little, if any impact on accuracy. Since we have chosen learning rates that are an order of magnitude slower than He et al. (2016), this third stage likely learns at too slow of a rate to tangibly influence validation accuracy. We select 0.00012, which leads to accuracy representative of the range of learning rates we considered.

G.4 WARMUP

In this Subsection, we explore whether slowly warming up to a high learning rate can improve iterative pruning's ability to find winning tickets. To do so, we linearly increase the learning rate from 0 to the initial learning rate r for k iterations. Here, we show the combinations of hyperparameters we tested. In general, we used warmup periods of 5,000, 10,000, 15,000, and 20,000 iterations. We warmed the network up to initial learning rates of 0.015, 0.03, and 0.05. For reference, the initial learning rate of the network in He et al. (2016) is 0.1. Figures 34, 35, and 36 show the effect of warmup at learning rates 0.015, 0.03, and 0.05, respectively. (All graphs show learning rates with momentum (0.9)).

In general, training with warmup improves the accuracy that winning tickets are able to reach and, at higher learning rates, makes it possible to find winning tickets at all. In Figure 33, we were unable to find winning tickets when training at a learning rate higher than 0.01. Here, however, we find winning tickets using learning rates up to 0.05 so long as there is a sufficient warmup period (15,000 iterations in the case of 0.05). Since we are able to train the network at a higher learning rate, these winning tickets also achieve higher accuracy. For example, the hyperparameters chosen for momentum in the previous section reach a maximum of 90.5% validation accuracy at the end of training, whereas

Figure 33: The early-stopping iteration and validation accuracy at that iteration of the iterative lottery ticket experiment on the resnet18 architecture as trained with SGD with momentum (0.9). The top row shows the early-stopping iterations and accuracy when training the network only for the first stage at various learning rates. The second row shows the early-stopping iterations and accuracy when training the network for the first two stages with our selected rate for the first stage (0.008) and various rates for the second stage. The third row shows the early-stopping iterations and accuracy when training the network for all three stages with our selected rates for the first two stages (0.008, 0.0006) and various rates for the third stage. Each line corresponds to a particular learning rate, and the legends are above the corresponding graphs.

Figure 34: The effect of various amounts of linear learning rate warmup on the accuracy of resnet-18 at the end of training with learning rate 0.015.

Figure 35: The effect of various amounts of linear learning rate warmup on the accuracy of resnet-18 at the end of training with learning rate 0.03.

a winning ticket trained at learning rate 0.03 with 20,000 iterations of warmup reaches maximum validation accuracy of 91.5% ($P_m = 32.2\%$), matching the validation accuracy achieved by training the unpruned network with the original hyperparameters.

H EXPERIMENT DETAILS FOR VGG16 AND VGG19 ON CIFAR10

This Appendix accompanies the VGG16 and VGG19 experiments in Section 5. Rather than explore the space of hyperparameters, we use those from Anonymous (2019b). The VGG16 and VGG19 architectures were first designed by Simonyan & Zisserman (2014) for Imagenet. The versions we use were modified by Anonymous (2019b) for CIFAR10. The networks are structured as described in Figure 2: they have five groups of 3x3 convolutional layers, the first four of which are followed by max-pooling (stride 2) and the last of which is followed by average pooling. The network has one final dense layer connecting the result of the average-pooling to the output.

We largely follow the training procedure for resnet18 described in Appendix G:

- We use the same train/test/validation split.

Figure 36: The effect of various amounts of linear learning rate warmup on the accuracy of resnet-18 at the end of training with learning rate 0.05.

Figure 37: Test accuracy (at 30,000, 60,000, and 112,000 iterations) of the VGG16 architecture when iteratively pruned and when randomly reinitialized at two different learning rates.

- We use the same data augmentation procedure.
- We use a batch size of 64.
- We use batch normalization.
- We use a weight decay of 0.0001.
- We use three stages of training at decreasing learning rates. We train for 160 epochs (112,480 iterations), decreasing the learning rate by a factor of ten after 80 and 120 epochs.
- We use Gaussian Glorot initialization.

We prune the convolutional layers of the network at a rate of 20% per iteration, and we do not prune the 5120 parameters in the output layer.

Anonymous (2019b) uses an initial pruning rate of 0.1. We train VGG16 and VGG19 with both this learning rate and a learning rate of 0.01. We do not perform any other hyperparameter search.

In 5, we report the performance of iterative pruning on VGG19. In Figure 37 here, we show the equivalent results for VGG16. The results are largely the same as for VGG19. At the higher learning rate, the subnetworks found by iterative pruning perform no better than when randomly reinitialized. At the lower learning rate, the subnetworks perform much better, remaining within 0.2 percentage points of the original accuracy so long as $P_m \geq 10.7$. Finally, when trained to the higher learning rate with 50,000 iterations of linear warmup, we find winning tickets that exceed the accuracy of the original network while $P_m \geq 10.7\%$.