AN EFFICIENT FRAMEWORK FOR LEARNING SENTENCE REPRESENTATIONS

ABSTRACT

In this work we propose a simple and efficient framework for learning sentence representations from unlabelled data. Drawing inspiration from the distributional hypothesis and recent work on learning sentence representations, we reformulate the problem of predicting the context in which a sentence appears as a classification problem. This allows us to efficiently learn different types of encoding functions, and we show that the model learns high-quality sentence representations. We demonstrate that our sentence representations outperform state-of-the-art unsupervised and supervised representation learning methods on several downstream NLP tasks that involve understanding sentence semantics while achieving an order of magnitude speedup in training time.

1 INTRODUCTION

Methods for learning meaningful representations of data have received widespread attention in recent years. It has become common practice to exploit these representations trained on large corpora for downstream tasks since they capture a lot of prior knowlege about the domain of interest and lead to improved performance. This is especially attractive in a transfer learning setting where only a small amount of labelled data is available for supervision.

Unsupervised learning allows us to learn useful representations from large unlabelled corpora. The idea of self-supervision has recently become popular where representations are learned by designing learning objectives that exploit labels that are freely available with the data. Tasks such as predicting the relative spatial location of nearby image patches (Doersch et al., 2015), inpainting (Pathak et al., 2016) and solving image jigsaw puzzles (Noroozi & Favaro, 2016) have been successfully used for learning visual feature representations. In the language domain, the distributional hypothesis has been integral in the development of learning methods for obtaining semantic vector representations of words (Mikolov et al., 2013b). This is the assumption that the meaning of a word is characterized by the word-contexts in which it appears. Neural approaches based on this assumption have been successful at learning high quality representations from large text corpora.

Recent methods have applied similar ideas for learning sentence representations (Kiros et al., 2015; Hill et al., 2016; Gan et al., 2016). These are encoder-decoder models that learn to predict/reconstruct the context sentences of a given sentence. Despite their success, several modelling issues exist in these methods. There are numerous ways of expressing an idea in the form of a sentence. The ideal semantic representation is insensitive to the form in which meaning is expressed. Existing models are trained to reconstruct the surface form of a sentence, which forces the model to not only predict its semantics, but syntactic aspects that are irrelevant to the meaning of the sentence as well.

The other major problem associated with these models is computational cost. These methods have a word level reconstruction objective that involves sequentially decoding the words of target sentences. Training with an output softmax layer over the entire vocabulary is a significant source of slowdown in the training process. This further limits the size of the vocabulary and the model.

We circumvent these problems by proposing an objective that operates directly in the space of sentence embeddings. The generation objective is replaced by a discriminative approximation where the model attempts to identify the embedding of a correct target sentence given a set of sentence candidates. In this context, we interpret the 'meaning' of a sentence as the information in a sentence that allows it to predict and be predictable from the information in context sentences. We name our approach **quick thoughts (QT)**, to mean efficient learning of thought vectors.

Our key contributions in this work are the following:

- We propose a simple and general framework for learning sentence representations efficiently. We train widely used encoder architectures an order of magnitude faster than previous methods, achieving better performance at the same time.

- We establish a new state-of-the-art for unsupervised sentence representation learning methods across several downstream tasks that involve understanding sentence semantics.

The pre-trained encoders will be made publicly available.

2 RELATED WORK

We discuss prior approaches to learning sentence representations from labelled and unlabelled data.

Learning from Unlabelled corpora.   Le & Mikolov (2014) proposed the paragraph vector (PV) model to embed variable-length text. Models are trained to predict a word given it's context or words appearing in a small window based on a vector representation of the source document. Unlike most other methods, in this work sentences are considered as atomic units instead of as compositional function of its words.

Encoder-decoder models have been successful at learning semantic representations. Kiros et al. (2015) proposed the skip-thought vectors model, which consists of an encoder RNN that produces a vector representation of the source sentence and a decoder RNN that sequentially predicts the words of adjacent sentences. Drawing inspiration from this model, Gan et al. (2016) explore the use of convolutional neural network (CNN) encoders. The base model uses a CNN encoder and reconstructs the input sentence as well as neighboring sentences using an RNN. They also consider a hierarchical version of the model which sequentially reconstructs sentences within a larger context.

Autoencoder models have been explored for representation learning in a wide variety of data domains. An advantage of autoencoders over context prediction models is that they do not require ordered sentences for learning. Socher et al. (2011) proposed recursive autoencoders which encode an input sentence using a recursive encoder and a decoder reconstructs the hidden states of the encoder. Hill et al. (2016) considered a de-noising autoencoder model (SDAE) where noise is introduced in a sentence by deleting words and swapping bigrams and the decoder is required to reconstruct the original sentence. Bowman et al. (2015) proposed a generative model of sentences based on a variational autoencoder.

Hill et al. (2016) introduced the FastSent model which uses a bag-of-words representation of the input sentence and predicts the words appearing in context (and optionally, the source) sentences. The model is trained to predict the appearance of a given word in the target sentences. Arora et al. (2016) consider a weighted BoW model followed by simple post-processing and show that it performs better than BoW models trained on paraphrase data.

Encoder-decoder based sequence models are known to work well, but they are slow to train on large amounts of data. On the other hand, bag-of-words models train efficiently by ignoring word order. We incorporate the best of both worlds by retaining flexibility of the encoder architecture, while still being able to to train efficiently.

Structured Resources.   There have been attempts to use labeled/structured data to learn sentence representations. Hill et al. (2016) learn to map words to their dictionary definitions using a max margin loss that encourages the encoded representation of a definition to be similar to the corresponding word. Wieting et al. (2015) and Wieting & Gimpel (2017) use paraphrase data to learn an encoder that maps synonymous phrases to similar embeddings using a margin loss. Hermann & Blunsom (2013) consider a similar objective of minimizing the inner product between paired sentences in different languages. Wieting et al. (2017) explore the use of machine translation to obtain more paraphrase data via back-translation and use it for learning paraphrastic embeddings.

Conneau et al. (2017) consider the supervised task of Natural language inference (NLI) as a means of learning generic sentence representations. The task involves identifying one of three relationships between two given sentences - entailment, neutral and contradiction. The training strategy consists

Figure 1: Overview. (a) The approach adopted by most prior work where given an input sentence the model attempts to generate a context sentence. (b) Our approach replaces the decoder with a classifier which chooses the target sentence from a set of candidate sentences.

of learning a classifier on top of the embeddings of the input pair of sentences. The authors show that sentence encoders trained for this task perform strongly on downstream transfer tasks.

3 PROPOSED FRAMEWORK

The distributional hypothesis has been operationalized by prior work in different ways. A common approach is illustrated in Figure 1(a), where an encoding function computes a vector representation of an input sentence, and then a decoding function attempts to generate the words of a target sentence conditioned on this representation. In the skip-thought model, the target sentences are those that appear in the neighborhood of the input sentence. There have been variations on the decoder such as autoencoder models which predict the input sentence instead of neighboring sentences (Hill et al., 2016) and predicting properties of a window of words in the input sentence (Le & Mikolov, 2014).

Instead of training a model to reconstruct the surface form of the input sentence or its neighbors, our formulation attempts to focus on the semantic aspects of sentences. The meaning of a sentence is the property that creates bonds between a sequence of sentences and makes it logically flow. Motivated by this, we take the following approach: use the meaning of the current sentence to predict the meanings of adjacent sentences, where meaning is represented by an embedding of the sentence computed from an encoding function. Despite the simplicity of the modeling approach, we show that it facilitates learning rich representations.

Our approach is illustrated in figure 1(b). Given an input sentence, it is encoded as before using some function. But instead of generating the target sentence, the model chooses the correct target sentence from a set of candidate sentences. Viewing generation as choosing a sentence from all possible sentences, this can be seen as a discriminative approximation to the generation problem.

A key difference between these two approaches is that in figure 1(b), the model can choose to ignore aspects of the sentence that are irrelevant in constructing a semantic embedding space. In figure 1(a) however, the reconstruction loss forces the model to predict local structural information about target sentences that may be irrelevant to its meaning (e.g., is governed by grammar rules). Loss functions defined in a feature space as opposed to the raw data space have been found to be more attractive in recent work for similar reasons (Larsen et al., 2015; Pathak et al., 2017).

Formally described, let f and g be parametrized functions that take a sentence as input and encode it into a fixed length vector. Let s be a given sentence. Let S_{ctxt} be the set of sentences appearing in the context of s (for a particular context size) in the training data. Let S_{cand} be the set of candidate sentences considered for a given context sentence $s_{ctxt} \in S_{ctxt}$. In other words, S_{cand} contains a valid context sentence s_{ctxt} (ground truth) and many other non-context sentences, and is used for the classification objective as described below.

For a given sentence position in the context of s (e.g., the next sentence), the probability that a candidate sentence $s_{\text{cand}} \in S_{\text{cand}}$ is the correct sentence (i.e., appearing in the context of s) for that position is given by

$$p(s_{\text{cand}}|s, S_{\text{cand}}) = \frac{\exp[c(f(s), g(s_{\text{cand}}))]}{\sum_{s' \in S_{\text{cand}}} \exp[c(f(s), g(s'))]} \tag{1}$$

where c is a scoring function/classifier.

The training objective maximizes the probability of identifying the correct context sentences for each sentence in the training data D.

$$\sum_{s \in D} \sum_{s_{\text{ctxt}} \in S_{\text{ctxt}}} \log p(s_{\text{ctxt}}|s, S_{\text{cand}}) \tag{2}$$

The modeling approach encapsulates the Skip-gram approach of Mikolov et al. (2013b) when words play the role of sentences. In this case the encoding functions are simple lookup tables considering words to be atomic units, and the training objective maximizes the similarity between the source word and a target word in its context given a set of negative samples.

Alternatively, we considered an objective function similar to the negative sampling approach of Mikolov et al. (2013b). This takes the form of a binary classifier which takes a sentence window as input and classifies them as plausible and implausible context windows. We found objective (2) to work better, presumably due to the relaxed constraint it imposes. Instead of requiring context windows to be classified as positive/negative, it only requires ground-truth contexts to be more plausible than contrastive contexts. This objective also performed empirically better than a max-margin loss.

In our experiments, c is simply defined to be an inner product $c(u, v) = u^T v$. This was motivated by considering pathological solutions where the model learns poor sentence encoders and a rich classifier to compensate for it. This is undesirable since the classifier will be discarded and only the sentence encoders will be used to extract features for downstream tasks. Minimizing the number of parameters in the classifier encourages the encoders to learn disentangled and useful representations.

We consider f, g to have different parameters, although they were motivated from the perspective of modeling sentence meaning. Another motivation comes from word representation learning methods which use different sets of input and output parameters. Parameter sharing is further not a significant concern since these models are trained on large corpora. At test time, for a given sentence s we consider its representation to be the concatenation of the outputs of the two encoders $[f(s) \ g(s)]$.

Our framework allows flexible encoding functions to be used. We use RNNs as f and g as they have been widely used in recent sentence representation learning methods. The words of the sentence are sequentially fed as input to the RNN and the final hidden state is interpreted as a representation of the sentence. We use gated recurrent units (GRU) (Chung et al., 2015) as the RNN cell similar to Kiros et al. (2015).

4 EXPERIMENTAL RESULTS

4.1 EVALUATING SENTENCE EMBEDDINGS

We evaluate our sentence representations by using them as feature representations for downstream NLP tasks. Alternative fine-grained evaluation tasks such as identifying word appearance and word order were proposed in Adi et al. (2017). Although this provides some useful insight about the representations, these tasks focus on the syntactic aspects of a sentence. We are more interested in assessing how well representations capture sentence semantics and hence stick to the traditional approach of evaluating using downstream tasks.

4.2 DATA

Models were trained on the 7000 novels of the BookCorpus dataset (Kiros et al., 2015). The dataset consists of about 45M ordered sentences. We also consider a larger corpus for training: the UMBC corpus (Han et al., 2013), a dataset of 100M web pages crawled from the internet, preprocessed and

tokenized into paragraphs. The dataset has 129M sentences, about three times larger than BookCorpus. For models trained from scratch, we used case-sensitive vocabularies of sizes 50k and 100k for the two datasets respectively.

4.3 TRAINING

A minibatch is constructed using a contiguous sets of sentences in the corpus. For each sentence, all the sentences in the minibatch are considered to be the candidate pool S_{cand} of sentences for classification. This simple scheme for picking contrastive sentences performed as well as other schemes such as random sampling and picking nearest neighbors of the input sentence. Hyperparameters including batch size, learning rate, prediction context size were obtained using prediction accuracies (accuracy of predicting context sentences) on the validation set. A context size of 3 was used, i.e., predicting the previous and next sentences given the current sentence. We used a batch size of 400 and learning rate of 5e-4 with the Adam optimizer for all experiments.

4.4 EVALUATION

Tasks We evaluate the sentence representations on tasks that require understanding sentence semantics. The following classification benchmarks are commonly used: movie review sentiment (MR) (Pang & Lee, 2005), product reviews (CR) (Hu & Liu, 2004), subjectivity classification (SUBJ) (Pang & Lee, 2004), opinion polarity (MPQA) (Wiebe et al., 2005), question type classification (TREC) (Voorhees & Buckland, 2003) and paraphrase identification (MSRP) (Dolan et al., 2004). The semantic relatedness task on the SICK dataset (Marelli et al., 2014) involves predicting relatedness scores for a given pair of sentences that correlate well with human judgements.

The MR, CR, SUBJ, MPQA tasks are binary classification tasks. 10-fold cross validation is used in reporting test performance for these tasks. The other tasks come with train/dev/test splits and the dev set is used for choosing the regularization parameter. We follow the evaluation scheme of Kiros et al. (2015) where feature representations of sentences are obtained from the trained encoders and a logistic/softmax classifier is trained on top of the embeddings for each task while keeping the sentence embeddings fixed.

4.4.1 COMPARISON AGAINST UNSUPERVISED METHODS

Table 1 compares our work against representations from prior methods that learn from unlabelled data. The dimensionality of sentence representations and training time are also indicated. For our RNN based encoder we consider variations that are analogous to the skip-thought model. The uni-QT model uses a uni-directional RNN as the sentence encoder. The bi-QT model uses two RNNs, one processing the sentence in the forward direction and the other in reverse, and uses the concatenation of the final hidden states of the two RNNs as the sentence representation. The combine-QT model concatenates the representations (at test time) learned by the uni-QT and bi-QT models.

Models trained from scratch on BookCorpus. While the FastSent model is efficient to train (training time of 2h), this efficiency stems from using a bag-of-words encoder. Bag of words provides a strong baseline because of its ability to preserves word identity information. However, the model performs poorly compared to most of the other methods. Bag-of-words is also conceptually less attractive as a representation scheme since it ignores word order, which is a key aspect of meaning.

The de-noising autoencoder (SDAE) performs strongly on the paraphrase detection task (MSRP). This is attributable to the reconstruction (autoencoding) loss which encourages word identity and order information to be encoded in the representation. However, it fails to perform well in other tasks that require higher level sentence understanding and is also inefficient to train ($\sim$ 1 week).

Our uni/bi/combine-QT variations perform comparably (and in most cases, better) to the skip-thought model and the CNN-based variation of Gan et al. (2016) in all tasks despite requiring much less training time. Since these models were trained from scratch, this also shows that the model learns good word representations as well.

MultiChannel-QT. Next, we consider using pre-trained word vectors to train the model. The MultiChannel-QT model (MC-QT) is defined as the concatenation of two bi-directional RNNs. One of these uses fixed pre-trained word embeddings coming from a large vocabulary ($\sim$ 3M) as input.

Model	Dim	Training time (h)	MR	CR	SUBJ	MPQA	TREC	MSRP (Acc)	(F1)	SICK r	ρ	MSE
GloVe BoW	300	-	78.1	80.4	91.9	87.8	85.2	72.5	81.1	0.764	0.687	0.425
Trained from scratch on BookCorpus data												
SDAE	2400	192	67.6	74.0	89.3	81.3	77.6	**76.4**	83.4	N/A	N/A	N/A
FastSent	<500	2*	71.8	78.4	88.7	81.5	76.8	72.2	80.3	N/A	N/A	N/A
ParagraphVec	<500	4*	61.5	68.6	76.4	78.1	55.8	73.6	81.9	N/A	N/A	N/A
uni-skip	2400	336	75.5	79.3	92.1	86.9	91.4	73.0	81.9	0.848	0.778	0.287
bi-skip	2400	336	73.9	77.9	92.5	83.3	89.4	71.2	81.2	0.841	0.770	0.300
combine-skip	4800	336†	76.5	80.1	**93.6**	87.1	**92.2**	73.0	82.0	0.858	0.792	0.269
combine-cnn	4800	-	77.2	80.9	93.1	**89.1**	91.8	75.5	82.6	0.853	0.789	0.279
uni-QT	2400	11	77.2	82.8	92.4	87.2	90.6	74.7	82.7	0.844	0.778	0.293
bi-QT	2400	9	77.0	83.5	92.3	87.5	89.4	74.8	82.9	0.855	0.787	0.274
combine-QT	4800	11†	**78.2**	**84.4**	93.3	88.0	90.8	76.2	**83.5**	**0.860**	**0.796**	**0.267**
Use pre-trained word vectors												
combine-cnn	4800	-	77.8	82.1	93.6	**89.4**	92.6	76.5	83.8	0.862	0.798	0.267
MC-QT	4800	11	**80.4**	**85.2**	**93.9**	**89.4**	92.8	76.9	84.0	0.868	0.801	0.256
+ UMBC data												
combine-QT	4800	28	81.3	84.5	94.6	89.5	92.4	75.9	83.3	0.871	0.807	0.247
MC-QT	4800	28	**82.4**	**86.0**	**94.8**	**90.2**	92.4	**76.9**	**84.0**	**0.874**	**0.811**	**0.243**

Table 1: Comparison of sentence representations on downstream tasks. The baseline methods are GloVe bag-of-words representation, De-noising auto-encoders and FastSent from Hill et al. (2016), the paragraph vector distributed memory model (Le & Mikolov, 2014), skip-thought vectors (Kiros et al., 2015) and the CNN model of Gan et al. (2016). Training times indicated using * refers to CPU trained models and † assumes concatenated representations are trained independently. Performance figures for SDAE, FastSent and ParagraphVec were obtained from Hill et al. (2016). Higher numbers are better in all columns except for the last (MSE). The table is divided into different sections. The bold-face numbers indicate the best performance values among models in the current and all previous sections. Best overall values in each column are underlined.

While the other uses tunable word embeddings trained from scratch (from a smaller vocabulary $\sim$ 50k). This model was inspired by the multi-channel CNN model of Kim (2014) which considered two sets of embeddings. With different input representations, the two models discover less redundant features, as opposed to the uni and bi variations suggested in Kiros et al. (2015). We use GloVe vectors (Pennington et al., 2014) as pre-trained word embeddings. The MC-QT model outperforms all previous methods, including the variation of Gan et al. (2016) which uses pre-trained word embeddings.

UMBC data. Because our framework is efficient to train, we also experimented on a larger dataset of documents. Results for models trained on BookCorpus and UMBC corpus pooled together ($\sim$ 174M sentences) are shown at the bottom of the table. We observe strict improvements on a majority of the tasks compared to our BookCorpus models. This shows that we can exploit huge corpora to obtain better models while keeping the training time practically feasible.

Note that our models were trained with much larger vocabulary sizes than most previous models. Our approach is also memory efficient. The paragraph vector model has a big memory footprint since it has to store vectors of documents used for training. Softmax computations over the vocabulary in the skip-thought and other models with word-level reconstruction objectives incur heavy memory consumption. Our RNN based implementation (with the indicated hyperparamters and batch size) fits within 3GB of GPU memory, a majority of it consumed by the word embeddings.

4.4.2 COMPARISON AGAINT SUPERVISED METHODS

Table 2 compares our approach against methods that learn from labelled/structured data. The CaptionRep, DictRep and NMT models are from Hill et al. (2016) which are trained respectively on the tasks of matching images and captions, mapping words to their dictionary defintions and machine translation. The InferSent model of Conneau et al. (2017) is trained on the NLI task. In addition to the benchmarks considered before, we additionally also include the sentiment analysis binary classification task on Stanford Sentiment Treebank (SST) (Socher et al., 2013).

Model	MR	CR	SUBJ	MPQA	SST	TREC	MSRP		SICK
CaptionRep	61.9	69.3	77.4	70.8	-	72.2	-	-	-
DictRep	76.7	78.7	90.7	87.2	-	81.0	68.4	76.8	-
NMT En-to-Fr	64.7	70.1	84.9	81.5	-	82.8	-	-	-
InferSent	81.1	**86.3**	92.4	**90.2**	84.6	88.2	76.2	83.1	**0.884**
MC-QT	**82.4**	86.0	**94.8**	**90.2**	**87.6**	**92.4**	**76.9**	**84.0**	0.874

Table 2: Comparison against supervised representation learning methods on downstream tasks.

Model	MR	CR	SUBJ	MPQA	SST	TREC	MSRP		SICK
Ensemble	82.7	**86.7**	**95.5**	90.3	**88.2**	93.4	78.5	85.1	**0.881**
Task specific methods									
AdaSent	**83.1**	86.3	**95.5**	**93.3**	-	92.4	-	-	-
CNN	81.5	85.0	93.4	89.6	88.1	**93.6**	-	-	-
TF-KLD	-	-	-	-	-	-	80.4	85.9	-
DT-LSTM	-	-	-	-	-	-	-	-	0.868

Table 3: Comparison against task-specific supervised models. The models are AdaSent (Zhao et al., 2015), CNN (Kim, 2014), TF-KLD (Ji & Eisenstein, 2013) and Dependency-Tree LSTM (Tai et al., 2015). Note that our performance values correspond to a linear classifier trained on fixed pre-trained embeddings, while the task-specific methods are tuned end-to-end.

The Infersent model has strong performance on the tasks. Our multichannel model trained on the (BookCorpus + UMBC) data outperforms InferSent in most of the tasks, with most significant margins in the SST and TREC tasks. Infersent is strong in the SICK task presumably due to the following reasons. The model gets to observes near paraphrases (entailment relationship) and sentences that are not-paraphrases (contradiction relationship) at training time. Furthermore, it considers difference features ($|u - v|$) and multiplicative features ($u * v$) of the input pair of sentences u, v during training. This is identical to the feature transformations used in the SICK evaluation as well.

Ensemble We consider ensembling to exploit the strength of different types of encoders. Since our models are efficient to train, we are able to train many models in the amount of time it takes to train one model from most previous unsupervised learning methods. We consider a subset of the following model variations for the ensemble.

- Model type - Uni/Bi-directional RNN
- Word embeddings - Trained from scratch/Pre-trained
- Dataset - BookCorpus/UMBC

Models are combined using a weighted average of the predicted log-probabilities of individual models, the weights being normalized validation set performance scores. Results are presented in table 3. Performance of the best purely supervised task-specific methods are shown at the bottom for reference. Note that these numbers are not directly comparable with the unsupervised methods since the sentence embeddings are not fine-tuned. We observe that the ensemble model closely approaches the performance of the best supervised task-specific methods, outperforming them in 3 out of the 8 tasks.

4.4.3 IMAGE-SENTENCE RANKING

In this experiment we consider the image-to-caption and caption-to-image retrieval tasks. The MSCOCO dataset (Lin et al., 2014) has been traditionally used for this task. We use the train/val/test split proposed in Karpathy & Fei-Fei (2015). The training, validation and test sets respectively consist of 113,287, 5000, 5000 images, each annotated with 5 captions. Performance is reported as an average over 5 splits of 1000 image-caption pairs each from the test set.

The evaluation setting is identical to Kiros et al. (2015). Images and captions are represented using features which are held fixed during training. The two representations are projected down to the same dimensionality (1000) and a margin loss encourages matching image-caption pairs to have higher inner products that mismatching pairs. As in prior work, we use VGG-Net features (4096-

COCO Retrieval								
	Image Annotation				Image Search			
Model	**R@1**	**R@5**	**R@10**	**Med** r	**R@1**	**R@5**	**R@10**	**Med** r
Unsupervised pre-training methods								
Combine-skip	33.8	67.7	82.1	3	25.9	60.0	74.6	4
Combine-cnn	34.4	-	-	3	26.6	-	-	4
MC-QT	**37.1**	**72.0**	**84.7**	**2**	**27.9**	**63.3**	**78.3**	**3**
Direct supervision of sentence representations								
DVSA	38.4	69.6	80.5	**1**	27.4	60.2	74.8	3
GMM+HGLMM	39.4	67.9	80.9	2	25.1	59.8	76.6	4
m-RNN	41.0	73.0	**83.5**	2	29.0	42.2	**77.0**	3
Order	**46.7**	**88.9**	-	2	**37.9**	**85.9**	-	**2**

Table 4: Image-caption retrieval. The purely supervised models are respectively from (Karpathy & Fei-Fei, 2015), (Klein et al., 2015), (Mao et al., 2014) and (Vendrov et al., 2015).

dimensional) as the image representation. Sentences are represented using the respective representation learning methods.

Results are presented in table 4. We outperform previous unsupervised pre-training methods by a significant margin, strictly improving the median retrieval rank for both the annotation and search tasks. We also outperform some of the purely supervised task specific methods by some metrics.

4.4.4 NEAREST NEIGHBORS

Our model and the skip-thought model have conceptually similar objective functions. This suggests examining properties of the embedding spaces to better understand how they encode semantics. We consider a nearest neighbor retrieval experiment to compare the embedding spaces. We use a pool of 1M sentences from a Wikipedia dump for this experiment. For a given query sentence, the best neighbor determined by cosine distance in the embedding space is retrieved.

Table 5 shows a random sample of query sentences from the dataset and the corresponding retrieved sentences. These examples show that our retrievals are often more related to the query sentence compared to the skip-thought model. It is interesting to see in the first example that the model identifies a sentence with similar meaning even though the main clause and conditional clause are in a different order. This is in line with our goal of learning representations that are less sensitive to the form in meaning is expressed.

Query	Seizures may occur as the glucose falls further .
ST	It may also occur during an excessively rapid entry into autorotation .
QT	When brain glucose levels are sufficiently low , seizures may result .
Query	This evidence was only made public after both enquiries were completed .
ST	This visa was provided for under Republic Act No .
QT	These evidence were made public by the United States but concealed the names of sources .
Query	He kept both medals in a biscuit tin .
ST	He kept wicket for Middlesex in two first-class cricket matches during the 1891 County Championship .
QT	He won a three medals at four Winter Olympics .
Query	The American alligator is the only known natural predator of the panther .
ST	Their mascot is the panther .
QT	The American alligator is a fairly large species of crocodilian .
Query	Several of them died prematurely : Carmen and Toms very young , while Carlos and Pablo both died .
ST	At the age of 13 , Ahmed Sher died .
QT	Many of them died in prison .
Query	Music for " Expo 2068 " originated from the same studio session .
ST	His 1994 work " Dialogue " was premiered at the Merkin Concert Hall in New York City .
QT	Music from " Korra " and " Avatar " was also played in concert at the PlayFest festival in Mlaga , Spain in September 2014 .

Query	Mohammad Ali Jinnah yielded to the demands of refugees from the Indian states of Bihar and Uttar Pradesh , who insisted that Urdu be Pakistan 's official language .
ST	Georges Charachidzé , a historian and linguist of Georgian origin under Dumzil 's tutelage , became a noted specialist of the Caucasian cultures and aided Dumzil in the reconstruction of the Ubykh language .
QT	Wali Mohammed Wali 's visit thus stimulated the growth and development of Urdu Ghazal in Delhi .
Query	The PCC , together with the retrosplenial cortex , forms the retrosplenial gyrus .
ST	The Macro domain from human , macroH2A1.1 , binds an NAD metabolite O-acetyl-ADP-ribose .
QT	The PCC forms a part of the posteromedial cortex , along with the retrosplenial cortex (Brodmann areas 29 and 30) and precuneus (located posterior and superior to the PCC) .
Query	The tour included a date at Nashville 's Ryman Auditorium known also as the original Grand Ole Opry .
ST	The tour 's final performance was held at Montreux Jazz Festival in Switzerland .
QT	The tour included appearances at the 2007 Pitchfork Music Festival and Primavera Sound Festival .
Query	With the exception of what are known as the Douglas Treaties , negotiated by Sir James Douglas with the native people of the Victoria area , no treaties were signed in British Columbia until 1998 .
ST	All the assets of the Natal Railway Company , including its locomotive fleet of three , were purchased for the sum of 40,000 by the Natal Colonial Government in 1876 .
QT	With few exceptions (the Douglas Treaties of Fort Rupert and southern Vancouver Island) no treaties were signed .

Table 5: Nearest neighbors retrieved by the skip-thought model (ST) and our model (QT).

5 CONCLUSION

We proposed a framework to learn generic sentence representations efficiently from large unlabelled text corpora. Our simple approach learns richer representations than prior unsupervised and supervised methods, consuming an order of magnitude less training time. We establish a new state-of-the-art for unsupervised sentence representation learning methods on several downstream tasks. We believe that exploring scalable approaches to learn data representations is key to exploit unlabelled data available in abundance.

REFERENCES

Yossi Adi, Einat Kermany, Yonatan Belinkov, Ofer Lavi, and Yoav Goldberg. Fine-grained analysis of sentence embeddings using auxiliary prediction tasks. In *ICLR*, 2017.

Sanjeev Arora, Yingyu Liang, and Tengyu Ma. A simple but tough-to-beat baseline for sentence embeddings.(2016). 2016.

Samuel R Bowman, Luke Vilnis, Oriol Vinyals, Andrew M Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. *arXiv preprint arXiv:1511.06349*, 2015.

Junyoung Chung, Caglar Gülçehre, Kyunghyun Cho, and Yoshua Bengio. Gated feedback recurrent neural networks. In *ICML*, pp. 2067–2075, 2015.

Alexis Conneau, Douwe Kiela, Holger Schwenk, Loic Barrault, and Antoine Bordes. Supervised learning of universal sentence representations from natural language inference data. *arXiv preprint arXiv:1705.02364*, 2017.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1422–1430, 2015.

Bill Dolan, Chris Quirk, and Chris Brockett. Unsupervised construction of large paraphrase corpora: Exploiting massively parallel news sources. In *Proceedings of the 20th international conference on Computational Linguistics*, pp. 350. Association for Computational Linguistics, 2004.

Zhe Gan, Yunchen Pu, Ricardo Henao, Chunyuan Li, Xiaodong He, and Lawrence Carin. Unsupervised learning of sentence representations using convolutional neural networks. *arXiv preprint arXiv:1611.07897*, 2016.

Kelvin Guu, Tatsunori B Hashimoto, Yonatan Oren, and Percy Liang. Generating sentences by editing prototypes. *arXiv preprint arXiv:1709.08878*, 2017.

Lushan Han, Abhay L. Kashyap, Tim Finin, James Mayfield, and Johnathan Weese. UMBC_EBIQUITY-CORE: Semantic Textual Similarity Systems. In *Proceedings of the Second Joint Conference on Lexical and Computational Semantics*. Association for Computational Linguistics, June 2013.

Karl Moritz Hermann and Phil Blunsom. Multilingual distributed representations without word alignment. *arXiv preprint arXiv:1312.6173*, 2013.

Felix Hill, Kyunghyun Cho, and Anna Korhonen. Learning distributed representations of sentences from unlabelled data. *arXiv preprint arXiv:1602.03483*, 2016.

Minqing Hu and Bing Liu. Mining and summarizing customer reviews. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 168–177. ACM, 2004.

Yangfeng Ji and Jacob Eisenstein. Discriminative improvements to distributional sentence similarity. In *EMNLP*, pp. 891–896, 2013.

Andrej Karpathy and Li Fei-Fei. Deep visual-semantic alignments for generating image descriptions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3128–3137, 2015.

Yoon Kim. Convolutional neural networks for sentence classification. *arXiv preprint arXiv:1408.5882*, 2014.

Ryan Kiros, Yukun Zhu, Ruslan R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Skip-thought vectors. In *Advances in Neural Information Processing Systems*, pp. 3276–3284, 2015.

Benjamin Klein, Guy Lev, Gil Sadeh, and Lior Wolf. Associating neural word embeddings with deep image representations using fisher vectors. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4437–4446, 2015.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. *arXiv preprint arXiv:1512.09300*, 2015.

Quoc V Le and Tomas Mikolov. Distributed representations of sentences and documents. In *ICML*, volume 14, pp. 1188–1196, 2014.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Junhua Mao, Wei Xu, Yi Yang, Jiang Wang, Zhiheng Huang, and Alan Yuille. Deep captioning with multimodal recurrent neural networks (m-rnn). *arXiv preprint arXiv:1412.6632*, 2014.

Marco Marelli, Stefano Menini, Marco Baroni, Luisa Bentivogli, Raffaella Bernardi, and Roberto Zamparelli. A sick cure for the evaluation of compositional distributional semantic models. In *LREC*, pp. 216–223, 2014.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013a.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pp. 3111–3119, 2013b.

Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In *hlt-Naacl*, volume 13, pp. 746–751, 2013c.

Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pp. 69–84. Springer, 2016.

Bo Pang and Lillian Lee. A sentimental education: Sentiment analysis using subjectivity summarization based on minimum cuts. In *Proceedings of the 42nd annual meeting on Association for Computational Linguistics*, pp. 271. Association for Computational Linguistics, 2004.

Bo Pang and Lillian Lee. Seeing stars: Exploiting class relationships for sentiment categorization with respect to rating scales. In *Proceedings of the 43rd annual meeting on association for computational linguistics*, pp. 115–124. Association for Computational Linguistics, 2005.

Deepak Pathak, Philipp Krahenbuhl, Jeff Donahue, Trevor Darrell, and Alexei A Efros. Context encoders: Feature learning by inpainting. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2536–2544, 2016.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. *arXiv preprint arXiv:1705.05363*, 2017.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *EMNLP*, volume 14, pp. 1532–1543, 2014.

Richard Socher, Eric H Huang, Jeffrey Pennington, Andrew Y Ng, and Christopher D Manning. Dynamic pooling and unfolding recursive autoencoders for paraphrase detection. In *NIPS*, volume 24, pp. 801–809, 2011.

Richard Socher, Alex Perelygin, Jean Y Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, Christopher Potts, et al. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the conference on empirical methods in natural language processing (EMNLP)*, volume 1631, pp. 1642. Citeseer, 2013.

Kai Sheng Tai, Richard Socher, and Christopher D Manning. Improved semantic representations from tree-structured long short-term memory networks. *arXiv preprint arXiv:1503.00075*, 2015.

Ivan Vendrov, Ryan Kiros, Sanja Fidler, and Raquel Urtasun. Order-embeddings of images and language. *arXiv preprint arXiv:1511.06361*, 2015.

Ellen M Voorhees and L Buckland. Overview of the trec 2003 question answering track. In *TREC*, volume 2003, pp. 54–68, 2003.

Janyce Wiebe, Theresa Wilson, and Claire Cardie. Annotating expressions of opinions and emotions in language. *Language resources and evaluation*, 39(2):165–210, 2005.

John Wieting and Kevin Gimpel. Revisiting recurrent networks for paraphrastic sentence embeddings. *arXiv preprint arXiv:1705.00364*, 2017.

John Wieting, Mohit Bansal, Kevin Gimpel, and Karen Livescu. Towards universal paraphrastic sentence embeddings. *arXiv preprint arXiv:1511.08198*, 2015.

John Wieting, Jonathan Mallinson, and Kevin Gimpel. Learning paraphrastic sentence embeddings from back-translated bitext. *arXiv preprint arXiv:1706.01847*, 2017.

Yelp. Yelp dataset challenge. *https://www.yelp.com/dataset/challenge*, 2017.

Han Zhao, Zhengdong Lu, and Pascal Poupart. Self-adaptive hierarchical sentence model. *arXiv preprint arXiv:1504.05070*, 2015.

A Analogy Making

In this experiment we compare the ability of our model and skip-thought vectors to reason about analogies in the sentence embedding space. The analogy task has been widely used for evaluating word representations. The task involves answering questions of the type $A : B :: C :?$ where the answer word shares a relationship to word C that is identical to the relationship between words A and B. We consider an analogous task at the sentence level and formulate it as a retrieval task where the query vector $v(C) + v(B) - v(A)$ is used to identify the closest sentence vector $v(\hat{D})$ from a pool of candidates. This evaluation favors models that produce meaningful dimensions.

Guu et al. (2017) exploit word analogy datasets to construct sentence tuples with analogical relationships. They mine sentence pairs (s_1, s_2) from the Yelp dataset (Yelp, 2017) which approximately differ by a single word, and use these pairs to construct sentence analogy tuples based on known word analogy tuples. The dataset has 1300 tuples of sentences collected in this fashion. For each sentence tuple we derive 4 questions by considering three of the sentences to form the query vector. The candidate pool for sentence retrieval consists of all sentences in this dataset and 1M other sentences from the Yelp dataset.

Table 6 compares the retrieval performance of our representations and skip-thought vectors on the above task. Results are classified under word-pair categories in the Google and Microsoft word analogy datasets (Mikolov et al., 2013a;c). Our model outperforms skip-thoughts across several categories and has good performance in the family and verb transformation categories .

Method	Google			Microsoft					
	gram4-superlative	gram3-comparative	family	JJR_JJS	VB_VBD	VBD_VBZ	NN_NNS	JJ_JJS	JJ_JJR
Combine-skip	0.00	0.00	0.04	0.12	**0.38**	0.44	0.00	0.00	0.00
MC-QT	**0.04**	**0.06**	**0.34**	**0.18**	0.34	**0.52**	**0.06**	**0.06**	**0.08**

Table 6: Analogy task - Retrieval performance.

Q	dr. <person>and his staff are simply amazing !
dr. <person>and her staff are simply amazing ! ! !
i had the chicken and my husband had the pulled pork sandwich .
A	i had the pulled pork sandwich and my wife had the pulled chicken sandwich. ✓
Q	place looks great inside .
place looked great inside .
the complimentary valet is also a nice touch .
A	the complimentary valet was also a nice touch . ✓
Q	i liked the beef better than the chicken .
i like the chicken better than the beef .
i wanted to like this place so badly !
A	i want so badly to like this place ! ! ✓
Q	the egg drop soup is the best .
the egg drop soup is good .
horrible food and worst customer service .
A	horrible food and worst customer service . ✗

Table 7: Analogy task - Qualitative results. In each table cell the first three sentences form the query and the last sentence is the answer retrieved by the model.

Table 7 shows some qualitative retrieval results. Each row of the table shows three sentences that form the query and the answer identified by the model. The last row shows an example where the model fails. This is a common failure case of both methods where the model assumes that A and B are identical in a question $A : B :: C :?$ and retrieves sentence C as the answer.

These experiments show that the our representations possess better linearity properties. The transformations evaluated here are mostly syntactic transformations involving a few words. It would be interesting to explore other high-level transformations such as switching sentiment polarity and analogical relationships that involve several words in future work.