Neural Regression, Representational Similarity, Model Zoology & Neural Taskonomy at Scale in Rodent Visual Cortex

Abstract

How well do deep neural networks fare as models of mouse visual cortex? A majority of research to date suggests results far more mixed than those produced in the modeling of primate visual cortex. Here, for the first time, we perform a large-scale benchmark of dozens of deep neural network models in mouse visual cortex using multiple methods of comparison and multiple modes of verification. Using the Allen Brain Observatory's 2-photon calcium-imaging dataset of activity in over 59,000 rodent visual cortical neurons recorded in response to natural scenes, we replicate findings and resolve discrepancies, ultimately demonstrating that modern neural networks can in fact be used to explain activity in the mouse visual cortex to a more reasonable degree than previously suggested. Using our benchmark as an atlas, we offer preliminary answers to overarching questions about levels of analysis (e.g. do models that better predict the representations of individual neurons also predict representational geometry across neural populations?); questions about the properties of models that best predict the visual system overall (e.g. does training task or architecture matter more for augmenting predictive power?); and questions about the mapping between biological and artificial representations (e.g. are there differences in the kinds of deep feature spaces that predict neurons from primary versus posteromedial visual cortex?). Along the way, we introduce a novel, highly optimized neural regression method that achieves SOTA scores (with gains of up to 34%) on the publicly available benchmarks of primate BrainScore. Simultaneously, we benchmark a number of models (including vision transformers, MLP-Mixers, normalization free networks and Taskonomy encoders) outside the traditional circuit of convolutional object recognition. Taken together, our results provide a reference point for future ventures in the deep neural network modeling of mouse visual cortex, hinting at novel combinations of method, architecture, and task to more fully characterize the computational motifs of visual representation in a species so indispensable to neuroscience.

1 Introduction

To date, the most successful models of biological visual cortex are object-recognizing deep neural networks applied to the prediction of neural activity in primate visual cortex [1–5]. The predictive power of these models is so substantial that they can be used for synthesizing stimuli that drive neural activity beyond its typical range [6, 7]. The success of these models in predicting mouse visual cortex, however, has been a bit more modest. Later, fully connected layers seem to predict mouse visual cortex better than early convolutional layers — contrasting the traditional schematic wherein the simple and complex cells found in primate visual cortex [8] are best modeled by early convolutional

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

and pooling layers [9]. Some have even suggested that randomly initialized networks are as predictive of rodent brains as trained networks, while still outperforming handcrafted features [10]. Here, we re-examine at large scale the state of neural network modeling in the visual cortices of mice, using many thousands of neurons, over 110 distinct neural network models, and two methods of mapping models to brain. We summarize this survey in four main results:

1. Training matters. The randomly initialized variants of some convolutional architectures fare well when predicting individual neural responses, but representational geometry is always better captured by features learned in service of some task. (Segmentation seems best.)
2. Features of intermediate complexity dominate in the prediction of all cortical sites, but there may be a slight upwards gradient in complexity from primary visual cortex onwards.
3. Taskonomic tools that have previously been shown to approximate functional organization in primates fail to strongly differentiate the anatomical regions in mice, with the same kinds of tasks dominant across multiple, distinct neural sites.
4. When aggregated in similar ways, representational similarity and neural regression methods capture similar trends in the kinds of feature spaces that best predict the biology.

2 Methods

2.1 Datasets

For neural data, we use the Allen Brain Observatory Visual Coding[1] dataset [11] collected with two-photon calcium-imaging from the visual cortex of 256 awake adult transgenic mice and consisting of approximately 59,610 unique, individual neurons. Calcium-imaging fluorescence patterns are preprocessed and deconvolved by the Allen Institute[2]. The neurons sampled include neurons from 6 visual cortical areas at 4 cortical depths across 12 genetic cre lines. The visual experiments recorded activity for both artificial images (e.g., diffraction gratings) and 118 natural scenes. We analyze only the latter to ensure comparable inputs to what is typically used in the training of deep nets. Each natural scene is displayed 50 times over the course of an assay.

To ensure an optimal signal to noise ratio, we perform a significant amount of subsetting on the full neural population, beginning by subsetting only excitatory neurons. Recent analyses suggest neural activity throughout mouse visual cortex is often impacted by extraneous, external body movements [12]. For this reason, we subsequently filter out any neurons whose peak responses to the presentation of natural scene images are significantly modulated by the mouse's running speed, using an ANOVA metric provided by the Allen Institute. We further subselect neurons by assessing their split-half reliability across trials (with each split-half constituting 25 of 50 presentations for each image), keeping only those neurons exhibiting 0.8 reliability and above. This thresholding still leaves 6619 neurons for analysis, is in line with prior work on primates, and supports, for example, the construction of cortical representational dissimilarity matrices (RDMs) with split-half reliabilities as high as 0.93. (More details on the relationship between our metrics and neural reliability, including visualizations of some of our results across many degrees of thresholding, can be found in the appendix.)

2.2 Model Zoology

To explore the influence of model architecture on predictive performance, we use 26 model architectures from the Torchvision (PyTorch) model zoo [13] and 66 model architectures from the Timm [14] model zoo [15–49]. These models include convolutional networks, vision transformers, normalization-free networks and MLP-Mixer models; all models are feed-forward. For each of these models, we extract the features from one trained and one randomly initialized variant (using whatever initialization scheme the model authors deemed best) so as to better disentangle what training on object recognition affords us in terms of predictive power.

---

[1]Available under a non-commercial use license under the Allen Institute terms of use http://www.alleninstitute.org/legal/terms-use/

[2]More details are available in the whitepapers released with the observatory data: http://observatory.brain-map.org/visualcoding/transgenic

2.3 Neural Taskonomy

Model zoology provides decent perspective on the computations related to object recognition, but the responsibilities of the visual cortex extend far beyond identifying the category of an object. To probe a wider range of tasks, we turn to Taskonomy: a single architecture trained on 24 different common computer vision tasks [50], ranging from autoencoding to edge detection. The model weights we use are from updated PyTorch implementations of the original Tensorflow models [51]. Key to the engineering of Taskonomy is the use of an encoder-decoder design in which only the construction of the decoder varies across tasks. While recent analyses using a similar approach in human visual cortex with fMRI data [52] have tended to focus only on the latent space of each task's encoder, we choose to extract representations across all layers, better situating Taskonomy within the same empirical paradigm that has so far defined the modeling of object recognition in the primate brain. For further clarity, we cluster the 24 tasks according to their 'Taskonomic' category — a total of 5 clusters (2D, 3D, semantic, geometric or other) that we further collapse into 4 clusters (lumping the only member of the 'other' category — a denoising autoencoder — in with its closest cousin — a vanilla autoencoder in the '2D' category). These purely data-driven clusters are derived from estimates of how effectively a set of features learned for one task transfer to (or boost the performance in) another task [50]. Use of the Taskonomy models provides a unique opportunity to test variance in training regimes without the confound of simultaneous changes in architecture.

2.4 Comparing Representations across Biological & Artificial Networks

Two methods predominate in the comparison of neural recordings to deep neural networks: at the most abstract level, one of these compares representational geometries computed across the activations of many individual neurons [53, 54]; the other attempts to predict the activity of individual neurons directly [54, 55]. Both of these techniques are grounded in the use of image-computable models and a shared stimulus set, but differ in the types of transformation applied to the neural activity generated by those stimuli. Given the difference in both target (neural populations versus individual neurons) and transforms (correlation matrices versus dimensionality reduction) we attempt a variant of each type of analysis here, comparing the two directly on the exact same neural data, with the same models and the same stimulus set, and in a granular, layer-by-layer fashion. A more nuanced review of neural mapping methods is provided in the appendix.

2.4.1 Representational Similarity Analysis

To compare the representational geometries of a given model to the representational geometries of the brain, we begin by computing classic representational dissimilarity matrices (RDMs) [56]. We compute RDMs by correlating the activations of all neurons in a given neural site to the 118 images in the stimulus set, extracting only the upper triangle from the resultant matrices (one for each of the 6 cortical areas surveyed). We compute RDMs for the artificial networks in similar fashion, aggregating the responses of the artificial neurons in a given layer, before aggregating them once more into a correlation matrix. We then measure the relationship between the RDMs computed from the biological and artificial networks with a second-order Pearson correlation between the flattened upper triangles of each. The resultant coefficient constitutes the score for how well a given model layer predicts the representational geometry of a given cortical area.

2.4.2 Encoding Models (Neural Regression)

To more directly compare the biological and artificial neural activations in our data, we use a style of regression made popular in the modeling of primate visual cortex, epitomized by BrainScore [4]. Variants of this approach abound, but most consist of extracting model activations, performing dimensionality reduction, and then some form of cross-validated penalized or principal components regression. The dimensionality-reduced feature spaces of the model are used as the regressors of the activation patterns in a given neuron. After testing a number of these variants, we settled on sparse random projection for dimensionality reduction (which proved far more computationally efficient than standard PCA, without sacrifice in terms of regression scores), followed by ridge regression (in place of the more frequently used partial least squares regression). We further discuss these and similar methods in the appendix.

The details of our method (programmed with [57]) are as follows: Given a network, we first extract a predetermined number of sparse random projections (4096, in this case) from each layer — in line with the Johnson-Lindenstrauss lemma for the number of observations (images shown to the

mice) in our data set. After extracting the random projections from the activations in each individual model layer, we regress these projections on each individual neuron using ridge regression (with a lambda penalty of 1.0). The use of a penalized regression in this case allows us to monopolize generalized cross-validation (a linear algebraic form of leave-one-out cross-validation), yielding a set of predictions for the activity of each neuron for each image[3]. We then compute the Pearson correlation between the predicted and actual activity for each neuron to obtain a score per neuron per model layer, which we then aggregate by taking the mean of neural scores across cortical area.

2.5 Model Rankings

To rank the models according to how well they predict the variance in a given cortical area, we take the max across layers. In effect, this requires that a model 'commit' only one layer to the prediction of each area. In the case of our neural regression metric we call these scores the 'SRP-Ridge Max'; in the case of our representational similarity metric we call these scores the 'RSA Max'. A final mean taken over the SRP-Ridge Max and RSA Max scores per model per cortical area yields our overall model ranking.

2.6 Non-Neural Network Baselines

Prior to the ascendancy of neural network models, a significant amount of time and craft was invested in the hand-engineering of features to simultaneously facilitate image recognition and capture meaningful subsets of neural variance. In this work, we test how well a small subset of those features are able to explain the variance in rodent visual cortex, using both our neural encoding and representational similarity metrics. Our non-neural network baselines consist of random fourier features [58] (computed specifically to match the dimensionality of our neural network predictors), handcrafted gabor filters and GIST (spatial envelope) descriptors [59].

3 Results

3.1 Does our neural regression method work?

To ascertain whether our novel neural regression method works, we first verify its efficacy on a known benchmark: the activity of 256 cells in the V4 and IT regions of two Rhesus macaque monkeys, a core component of BrainScore [4]. BrainScore's in-house method involves a combination of principal components analysis (for dimensionality reduction) and k-fold cross-validated partial least squares regression (for the linear mapping of model to brain activity). Here, we exchange principal components analysis for sparse random projection and partial least squares regression for ridge regression with generalized cross-validation. We compute the scores for each benchmark in the same fashion as BrainScore: as the Pearson correlation coefficient between the actual and predicted (cross-validated) activity of the biological neurons in the V4 and IT samples.

Taking for example a standard AlexNet architecture, our neural regression method yields gains of 16.5% (from 0.550 to 0.641) & 16.9% (from 0.508 to 0.593) on reported scores for V4 and IT, respectively. Across 6 other Torchvision architectures we tested with scores posted on the BrainScore leaderboard, our method yields gains on average of 13% for V4 and 23% for IT, and at its best yields a gain of 34% for SqueezeNet1-0 predicting IT. We consider this a strong validation of our neural regression method, which is both less computationally expensive, far faster and (to the extent that the generalized cross validation represents the optimal approximation of how well the mappings fit to our models might generalize to novel biological samples) more accurate than the combination of PCA and PLS. (More detailed results and speed tests may be found in the appendix.)

3.2 How do trained models compare to randomly initialized models?

Previous work in the deep neural network modeling of mouse visual cortex found that a randomly initialized VGG16 predicted neural responses as well, if not slightly better than, a VGG16 trained on ImageNet [10], suggesting that the neural predictivity of the features produced by a trained object recognition model are perhaps no better than the features produced by a randomly initialized one. Our results, on the other hand, suggest that the neural predictivity of trained versus randomly initialized

---

[3]The use of generalized cross-validation is particularly beneficial in datasets with fewer probe images, where k-fold cross-validation means losing a significant degree of information in each fit.

models more generally depends on both the particular model being tested and the particular method used to produce the mappings between model and brain.

At the level of individual neurons (neural regression), 17 of the 92 model architectures we tested had randomly initialized variants that either matched or outperformed their ImageNet-trained counterparts. Replicating previous findings, we found these 17 architectures to include VGG16, as well as all 3 other VGG variants (11, 13 & 19), AlexNet, the DenseNet architectures (121, 169, 201), and almost all of the normalization-free architectures. Despite this, a paired student's t-test of the scores across *all* models demonstrates that ImageNet-trained architectures are overall more performant than their randomly initialized counterparts ($p = 1.29 \times 10^{-40}$, Cohen's $d = 2.40$). At the level of representational geometry, ImageNet-trained models categorically outperform their randomly initialized counterparts, and by a large margin ($p = 2.29 \times 10^{-29}$, Cohen's $d = 3.45$).

Taken together, these results strongly affirm that *training matters*, and that randomly initialized features can only go so far in the prediction of meaningful neural variance. Differences between ImageNet-trained and randomly initialized models are shown in fig. 1.

3.3 What kinds of architectures best predict rodent visual cortex?

The overall best architecture for predicting mouse visual cortex across both individual neurons (SRP-Ridge) and representational geometries (RSA) was an Inception-ResNet hybrid (Inception-ResNet-V2). There is a small, positive correlation between the depth of a model (the number of distinct layers) for both the RSA-Max metric and SRP-Ridge metric (Spearman $r = 0.22, p = 0.001$ and $r = 0.192, p = 0.007$, respectively), and a small, negative correlation for the total number of trainable parameters in the RSA Max metric (Spearman $r = -0.18, p = 0.007$). The latter of these is most likely driven by the relatively poor performance of parameter-dense architectures like VGG.

Strikingly, trends previously noted in macaques [60] fail to materialize here. In particular, models with higher top-1 accuracies on ImageNet do not perform significantly better than models with lower top-1 accuracies. This relative parity is driven in large part it seems by newer models like EfficientNets, which across the board have dominant scores on ImageNet, but sometimes middling or poor scores in the predictions of rodent visual cortex we've tabulated here.

Compared to all other architecturess, transformers on average fare slightly worse in the RSA Max metric (student's $t = -3.96, p = 0.004$, Hedge's $g = -0.913$), but moderately better in the SRP-Ridge Max metric (student's $t = 2.45, p = 0.023$, Hedge's $g = 0.633$). Other contrasts (including between models with and without residual connections or normalization) are available in the appendix.

Strikingly, transformers and MLP-Mixers boast the largest differences between ImageNet-trained and randomly initialized variants in the SRP-Ridge Max metric, with all pairwise t-tests significant at $alpha = 0.05$ after Bonferroni correction for multiple comparisons. This strongly suggests that the advantage of those randomly initialized variants that matched or outperformed their ImageNet-trained counterparts is an advantage conferred by properties of convolutional architectures (e.g., translation invariance), and not necessarily an advantage shared across random feature spaces writ large. The rankings of these and other architectures may be found in fig. 1.

3.4 What kinds of tasks best predict rodent visual cortex?

The overall best Taskonomy encoder across both the RSA and SRP-Ridge Max is 2D segmentation (ranking second and first respectively; see fig. 2). At the level of individual neurons (SRP-Ridge), 2D tasks (keypoints, autoencoding, inpainting) dominate. At the level of representational geometry (RSA), all 2D tasks but 2D segmentation fall to the bottom of the rankings, and Semantic tasks (object recognition and semantic segmentation) rise to 2nd and 3rd place.

This reshifting in rank presents a curious case for interpretation, suggesting most likely that while the representations of individual neurons may be coordinated more by the lower level, less abstract features necessary for performing well on most 2D tasks, the overall neural population codes are coordinated more by the parsing of the visual input into ethologically and spatially relevant units via the segmentation and classification tasks. Notably, the original research from which these PyTorch models were adopted offers an auxiliary data point that may anchor this interpretation more concretely. The top 3 models in our RSA Max metric (2D segmentation, object classification, semantic segmentation) are likewise in the top 5 of a ranking the original researchers produced by pitting the Taskonomy encoders against one another as pretrained 'perceptual systems' for reinforcement

Figure 1: Rankings across 40 of 92 model architectures (deliberately sampled to demonstrate variety), sorted by the scores of the ImageNet-trained variants (red) of each. Instances in which the randomly initialized variants (blue) outperform their ImageNet-trained counterparts are visible in those rows where the blue entirely overlaps the red. Error bars are 95% bootstrapped confidence intervals across the 6 cortical areas. As in [10], some randomly initialized and ImageNet-trained models like VGG16 have equal scores in neural regression, but ImageNet-trained models categorically dominate in representational similarity. The full set of 92 rankings is available in the appendix.

Figure 2: Rankings across Taskonomy encoders, color coded by the Taskonomic cluster to which each belongs. Notice the contrast between the SRP-Ridge Max (which favors 2D tasks) and RSA Max metric (which favors Semantic tasks), but also the relative rank of 2D Segmentation in both.

learning agents learning to navigate a virtual environment (see [51], figure 13 in the appendix). This raises the possibility that the reason these models are optimally predicting the visual neural population code for mice is simply because that code is coordinated in service of navigation.

3.5 How well do non-neural network baselines predict rodent visual cortex?

Non-neural network baselines somewhat uniformly fail to predict cortical activity. We tested three baselines: 1) a bank of Gabor filters of applied to 8x8 grids of each image, 2) the PCs of the resultant feature matrices (i.e. the Gist descriptors [59])), 3) and the max across 600 iterations of 4096 random Fourier features (a dimensionality matching that of our SRPs). Ridge regressed with generalized cross-validation, these feature models score 0.032, 0.026 and -0.014, respectively.

3.6 Does training or architecture matter more for better prediction?

The range in scores between the best and worst performing model architecture trained on ImageNet is 0.209 to 0.121 (0.088) for the SRP-Ridge Max and 0.458 to -0.117 (0.575) for the RSA Max metric (excluding the two normalization-free architectures that produced negative scores and are otherwise significant outliers, the range is more like 0.458 to 0.347 (0.111)); the range between the best and worst performing model in Taskonomy is 0.190 to 0.126 (0.064) for the SRP-Ridge Max and 0.440 to 0.331 (0.109) for RSA Max. These results point ambiguously in the direction of architecture as mattering slightly more, but it seems perfectly possible that novel combinations of architecture and task could push this range further than modifications to either in isolation.

3.7 How 'deep' are the layers that best predict rodent visual cortex?

Across all ImageNet-trained architectures, regardless of metric, the features most predictive of rodent visual cortex are found about a third of the way into the model (see the peaks in the lowess curves in fig. 4). These early to intermediate visual features go beyond basic edge detection but are far from the highly abstracted representations adjacent to final fully connected layers. Across Taskonomy encoders, 2D & Geometric tasks yield their best features in earlier layers; 3D & Semantic tasks yield their best features in more intermediate and later layers. (These motifs vary only slightly by cortical area, a result we discuss in the next section and in fig. 3.)

3.8 Are there differences in model predictions across cortical area?

Here, we attempt to answer this question from two perspectives: that of function and that of hierarchy.

Research into primate visual cortex over the last two decades has unveiled a significant degree of functional (not just anatomical) organization [61–63], with distinct subregions defined in large part by their activity in response to different kinds of stimuli. To replicate this in mouse visual cortex we search for Taskonomic organization, a proxy of functional organization wherein distinct neural sites are better or worse predicted by the features from different taskonomy encoders. Curiously, and in contrast to previous findings in human fMRI [52], it seems to be the case that the scores of different Taskonomic clusters are relatively consistent across cortical area; see fig. 3 (left).) This suggests that mouse visual cortex may be more functionally (or Taskonomically) homogenous than primate visual cortex, with anatomical descriptors providing little to no cue of functional difference. (For breakdowns of Taskonomy scores across genetic cre line instead of cortical area, see the appendix). Another alternative is that the tasks of computer vision are just not so neatly mapped onto the tasks of biological vision in mice.

Another possible difference across cortical area is one of hierarchy. In primate visual cortex, there seems to be a distinct information processing hierarchy along the ventral visual stream [64–66], with posterior sites like V1 and V3 defined by features like oriented edge detectors, and more anterior sites like V4 and IT defined by more complex morphologies. While there continues to be some debate as to whether a similar hierarchy exists in rodent visual cortex, the relative depth at which our models optimally predict cortical activity does unveil at least a preliminary gradient. For details, see fig. 3.

3.9 How do the predictions compare across RSA and neural regression?

While prior work has attempted to answer this question theoretically [67], it's rarely the case that representational similarity and neural regression are compared directly and empirically. Here, we compare our RSA and SRP-Ridge metric both at the level of overall rankings (taking the max across

Figure 3: The average depth (from 0 to 1) of layers from ImageNet-trained architectures that score maximally on different cortical areas (left) and breakdowns across cortical area of the scores on Taskonomy (right). Displayed here, for simplicity's sake, are only the results from the RSA (SRP-Ridge versions are available in the appendix). The plot on the left demonstrates that there does indeed seem to be a hierarchy that loosely follows the anatomy of the rodent visual system, with earlier layers predicting the primary visual area (VISp) and later layers predicting anteromedial and posteromedial visual areas (VISam & VISpm). The plot on the right shows that there don't seem to be major 'Taskonomic' dissociations across cortical area. Semantic tasks dominate in all but VISrl where, surprisingly, the randomly initialized version of Taskonomy is ascendant — though we caveat this by noting VISrl boasts the overall lowest scores of any of the cortical areas.

layers) and at the level of individual layers, the latter of which provides a much more detailed assessment of how different feature spaces map to cortical representation.

In terms of overall rankings, the Spearman rank order correlation between the two methods is either 0.56 ($p = 8.36 \times 10^{-19}$) or 0.59 ($p = 3.17 \times 10^{-12}$), depending on whether you include or exclude the randomly initialized architectures. In terms of layer by layer comparisons, we decompose the Spearman correlation across distinct combinations of model and cortical area. The average coefficient between the two methods, along with bootstrapped 95% confidence intervals is 0.468 [0.447,0.489] or 0.626 [0.613,0.639], again depending on the inclusion or exclusion of the random models. This suggests a significant degree of overlap between the kinds of features that optimally predict the representations of both individual neurons and neural populations. Of course, the averages here obscure some meaningful subtrends and idiosyncrasies; see fig. 4. Also note that while the overall trends are similar, the scores for the neural encoding method are significantly lower than scores for the representational similarity analysis. With more probe images, we expect that the parametric linear mapping would be more competitive with the nonparameteric distances of representational similarity.

4 Discussion

Our intent with this work was to provide a preliminary atlas for further ventures into the deep neural network modeling of rodent visual cortex. To this end, we have deliberately invested in introspective analyses of the tools we used, as well as the curation of deep neural networks we hope will provide informative waypoints. Obviously, the atlas is far from complete. Newer model classes like self-supervised models, recurrent models [68, 69], equivariant models [70], and models used in robotics (e.g. for visual odometry [71]) are promising candidates for inclusion in future benchmarks, and our neural encoding & representational similarity metrics are just two of many variants.

Nevertheless, the results we have presented here indicate that neural recordings from the visual brains of mice can be compared to neural networks in much the same way as recordings from the visual brains of monkeys. Having as reference two animal models that occupy very different ecological niches and are separated by tens of million years of evolution makes it far more likely that insights into vision gleaned across both are truly fundamental to the process of making perceptual sense of the world — and are not just some idiosyncratic quirk specific to any one evolutionary trajectory. Primate and rodent vision differ significantly even in fairly basic ways: mice lack a fovea, have a retina dominated by rods for vision under low light, and spatial acuity less than 20/1000 [72], making their primary visual system more akin to the primate peripheral system. It is possible that mice rely on vision as a sort of broad bandpass filter for lower-frequency, dynamic stimuli that the mouse can then flee, fight or further investigate with its whiskers — perhaps its most sophisticated sensory organ (and also, it seems, a compelling candidate for neural network modeling [73]).

Figure 4: Aggregate layer by layer comparisons across ImageNet-trained models (left) and Taskonomy models (right). The horizontal axis shows relative model layer depth, from the first to the last layer. Because the models on the left vary significantly in size, we discretize the relative depths into bins of size 0.01 (100 bins). The jagged, semitransparent lines are the mean scores at a given depth. (These are particularly jagged for transformers due to the heterogeneous nature of the computational blocks, which engenders large troughs in predictive power). The opaque, smoothed trend lines are the outputs of locally weighted linear regressions (lowess) computed at each point with a span of 2/3 the width of the axis. Plots show that covolutional networks and transformers have similar predictive power at similar depths despite their significant computational differences. (right) Features most predictive of cortical responses across the Taskonomy models vary in their relative depth increasing in later layers. The reversal in the ranks of 2D models between RSA Max and SRP Ridge Max is seen as a vertical shift in the intercept of the curve relating depth to score – though note that the slope and shape of the curve remain similar across metrics. 2D models are most predictive in the early layers, but are nevertheless superseded by other tasks in the RSA Max.

The dominance in our Taskonomy results of 2D segmentation, object recognition and semantic segmentation (all tasks that have elsewhere been shown to provide fertile, transferable features for the simulation of robotic navigation) underscores the indispensable point that perceptual systems should always be considered in service of behavior. The unparalleled access, resolution, and control afforded by rodent neuroimaging have already revolutionized our understanding of the relationship between perceptual representation and behavioral output. Combined with novel methods like the embedding of neural networks in virtual agents [74] in ecologically realistic environments, this kind of data may well provide a testbed for better situating the tasks of computer vision in the broader behavioral context of agentic scene understanding.

Perhaps the most immediately pressing future direction of this work is manifest in the simple reality that even with our most predictive models, we've explained only a fraction of the highly reliable neural variance this dataset has to offer. One of the best models in any neural site is Taskonomy's 2D Segmentation in the anterolateral visual area (VISal), with an RSA Max score of 0.538, translated to an R^2 of 0.289. This constitutes approximately a third of the total explainable variance in this site, defined in this case simply as the square of the neural RDM's split-half reliability, $R^2 = 0.773$. Only novel combinations of architecture, task and methodology will close this gap and more fully model the rich diversity and fiendish complexity of biological brains at scale — even the very smallest ones.

Code: Code for the replication of our analysis may be found at this anonymous GitHub repository: https://github.com/annonymousecode/Model-Zoology-and-Neural-Taskonomy (License GPL v2)

Compute: We used a single machine with 8 Nvidia RTX 3090 GPUs, 755gb of RAM, and 96 CPUs. GPUs were used only for extracting model activations. Dimensionality reduction and regression computations were CPU and RAM intensive. Replicating all of our results would take approximately two weeks on a similar machine.

Ethics: Lest our science forget the life that powers it, we must note that behind the phenomenal dataset provided by the Allen Institute are 256 laboratory mice, each of which was subjected to multiple surgeries, a highly invasive neuroimaging technique and genetic engineering. The moral parameters of this particular praxis of neuroscience are contentious, and not without reason. While we believe centralized, comprehensive and (most importantly) public datasets like those provided by the Allen Institute may actually decrease the total number of laboratory animals required for similar kinds of empirical projects, we acknowledge with solemnity the cost to life required.

References

[1] Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

[2] Daniel LK Yamins and James J DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature neuroscience*, 19(3):356, 2016.

[3] Santiago A Cadena, George H Denfield, Edgar Y Walker, Leon A Gatys, Andreas S Tolias, Matthias Bethge, and Alexander S Ecker. Deep convolutional models improve predictions of macaque v1 responses to natural images. *PLoS computational biology*, 15(4):e1006897, 2019.

[4] Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, Kailyn Schmidt, Daniel L. K. Yamins, and James J. DiCarlo. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv preprint*, 2018.

[5] Rishi Rajalingham, E.B. Issa, P. Bashivan, K. Kar, K. Schmidt, and J.J. DiCarlo. Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks. *The Journal of Neuroscience*, 38(33): 7255–7269. doi: 10.1523/JNEUROSCI.0388-18.2018. URL https://doi.org/10.1523/JNEUROSCI.0388-18.2018.

[6] Pouya Bashivan, Kohitij Kar, and James J DiCarlo. Neural population control via deep image synthesis. *Science*, 364(6439), 2019.

[7] Edgar Y Walker, Fabian H Sinz, Erick Cobos, Taliah Muhammad, Emmanouil Froudarakis, Paul G Fahey, Alexander S Ecker, Jacob Reimer, Xaq Pitkow, and Andreas S Tolias. Inception loops discover what excites neurons most using deep predictive models. *Nature neuroscience*, 22(12):2060–2065, 2019.

[8] David H Hubel and Torsten N Wiesel. Receptive fields and functional architecture of monkey striate cortex. *The Journal of physiology*, 195(1):215–243, 1968.

[9] Jianghong Shi, Eric Shea-Brown, and Michael Buice. Comparison against task driven artificial neural networks reveals functional properties in mouse visual cortex. In *Advances in Neural Information Processing Systems*, pages 5765–5775, 2019.

[10] S. A. Cadena, F. H. Sinz, T. Muhammad, E. Froudarakis, E. Cobos, E. Y. Walker, J. Reimer, M. Bethge, A. Tolias, and A. S. Ecker. How well do deep neural networks trained on object recognition characterize the mouse visual system? 2019.

[11] Saskia EJ de Vries, Jerome A Lecoq, Michael A Buice, Peter A Groblewski, Gabriel K Ocker, Michael Oliver, David Feng, Nicholas Cain, Peter Ledochowitsch, Daniel Millman, et al. A large-scale standardized physiological survey reveals functional organization of the mouse visual cortex. *Nature Neuroscience*, 23(1):138–151, 2020.

[12] Simon Musall, Matthew T Kaufman, Ashley L Juavinett, Steven Gluf, and Anne K Churchland. Single-trial neural dynamics are dominated by richly varied movements. *Nature neuroscience*, 22(10):1677–1686, 2019.

[13] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[14] Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

[15] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*, pages 1097–1105, 2012.

[16] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Conference on Computer Vision and Pattern Recognition*, pages 4700–4708, 2017.

[17] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Conference on Computer Vision and Pattern Recognition*, pages 1–9, 2015.

[18] Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Conference on Computer Vision and Pattern Recognition*, pages 2820–2828, 2019.

[19] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Conference on Computer Vision and Pattern Recognition*, pages 4510–4520, 2018.

[20] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[21] Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Conference on Computer Vision and Pattern Recognition*, pages 1492–1500, 2017.

[22] Xiangyu Zhang, Xinyu Zhou, Mengxiao Lin, and Jian Sun. Shufflenet: An extremely efficient convolutional neural network for mobile devices. In *Conference on Computer Vision and Pattern Recognition*, pages 6848–6856, 2018.

[23] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[24] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

[25] Forrest N Iandola, Song Han, Matthew W Moskewicz, Khalid Ashraf, William J Dally, and Kurt Keutzer. Squeezenet: Alexnet-level accuracy with 50x fewer parameters and¡ 0.5 mb model size. *arXiv preprint arXiv:1602.07360*, 2016.

[26] Alexey Bochkovskiy, Chien-Yao Wang, and Hong-Yuan Mark Liao. Yolov4: Optimal speed and accuracy of object detection, 2020.

[27] Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alex Alemi. Inception-v4, inception-resnet and the impact of residual connections on learning, 2016.

[28] Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks, 2020.

[29] Fisher Yu, Dequan Wang, Evan Shelhamer, and Trevor Darrell. Deep layer aggregation, 2019.

[30] Qilong Wang, Banggu Wu, Pengfei Zhu, Peihua Li, Wangmeng Zuo, and Qinghua Hu. Eca-net: Efficient channel attention for deep convolutional neural networks, 2020.

[31] Bichen Wu, Xiaoliang Dai, Peizhao Zhang, Yanghan Wang, Fei Sun, Yiming Wu, Yuandong Tian, Peter Vajda, Yangqing Jia, and Kurt Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search, 2019.

[32] Mingxing Tan and Quoc V. Le. Mixconv: Mixed depthwise convolutional kernels, 2019.

[33] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale, 2020.

[34] Xiang Li, Wenhai Wang, Xiaolin Hu, and Jian Yang. Selective kernel networks, 2019.

[35] Chenxi Liu, Barret Zoph, Maxim Neumann, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search, 2018.

[36] Jie Hu, Li Shen, Samuel Albanie, Gang Sun, and Enhua Wu. Squeeze-and-excitation networks, 2019.

[37] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows, 2021.

[38] François Chollet. Xception: Deep learning with depthwise separable convolutions, 2017.

[39] Niv Nayman, Yonathan Aflalo, Asaf Noy, and Lihi Zelnik-Manor. Hardcore-nas: Hard constrained differentiable neural architecture search, 2021.

[40] Stéphane d'Ascoli, Hugo Touvron, Matthew Leavitt, Ari Morcos, Giulio Biroli, and Levent Sagun. Convit: Improving vision transformers with soft convolutional inductive biases, 2021.

[41] Weijian Xu, Yifan Xu, Tyler Chang, and Zhuowen Tu. Co-scale conv-attentional image transformers, 2021.

[42] Kai Han, Yunhe Wang, Qi Tian, Jianyuan Guo, Chunjing Xu, and Chang Xu. Ghostnet: More features from cheap operations, 2020.

[43] Ben Graham, Alaaeldin El-Nouby, Hugo Touvron, Pierre Stock, Armand Joulin, Hervé Jégou, and Matthijs Douze. Levit: a vision transformer in convnet's clothing for faster inference, 2021.

[44] Ilya Tolstikhin, Neil Houlsby, Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Thomas Unterthiner, Jessica Yung, Andreas Steiner, Daniel Keysers, Jakob Uszkoreit, Mario Lucic, and Alexey Dosovitskiy. Mlp-mixer: An all-mlp architecture for vision, 2021.

[45] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, Quoc V. Le, and Hartwig Adam. Searching for mobilenetv3, 2019.

[46] Andrew Brock, Soham De, Samuel L. Smith, and Karen Simonyan. High-performance large-scale image recognition without normalization, 2021.

[47] Andrew Brock, Soham De, and Samuel L. Smith. Characterizing signal propagation to close the performance gap in unnormalized resnets, 2021.

[48] Xiaohan Ding, Xiangyu Zhang, Ningning Ma, Jungong Han, Guiguang Ding, and Jian Sun. Repvgg: Making vgg-style convnets great again, 2021.

[49] Hugo Touvron, Piotr Bojanowski, Mathilde Caron, Matthieu Cord, Alaaeldin El-Nouby, Edouard Grave, Armand Joulin, Gabriel Synnaeve, Jakob Verbeek, and Hervé Jégou. Resmlp: Feedforward networks for image classification with data-efficient training, 2021.

[50] Amir R Zamir, Alexander Sax, William Shen, Leonidas J Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3712–3722, 2018.

[51] Alexander Sax, Jeffrey O Zhang, Bradley Emi, Amir Zamir, Silvio Savarese, Leonidas Guibas, and Jitendra Malik. Learning to navigate using mid-level visual priors. *arXiv preprint arXiv:1912.11121*, 2019.

[52] Aria Wang, Michael Tarr, and Leila Wehbe. Neural taskonomy: Inferring the similarity of task-derived representations from brain activity. In *Advances in Neural Information Processing Systems*, pages 15475–15485, 2019.

[53] Nikolaus Kriegeskorte, Marieke Mur, Douglas A Ruff, Roozbeh Kiani, Jerzy Bodurka, Hossein Esteky, Keiji Tanaka, and Peter A Bandettini. Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron*, 60(6):1126–1141, 2008.

[54] Umut Güçlü and Marcel AJ van Gerven. Increasingly complex representations of natural movies across the dorsal stream are shared between subjects. *NeuroImage*, 145:329–336, 2017.

[55] Matteo Carandini, Jonathan B Demb, Valerio Mante, David J Tolhurst, Yang Dan, Bruno A Olshausen, Jack L Gallant, and Nicole C Rust. Do we know what the early visual system does? *Journal of Neuroscience*, 25(46):10577–10597, 2005.

[56] N. Kriegeskorte, M. Mur, D.A. Ruff, R. Kiani, J. Bodurka, H. Esteky, and P.A. Bandettini. Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron*, 60(6):1126–1141. doi: 10.1016/j.neuron.2008.10.043. URL https://doi.org/10.1016/j.neuron.2008.10.043.

[57] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

[58] Ali Rahimi, Benjamin Recht, et al. Random features for large-scale kernel machines. In *NIPS*, volume 3, page 5. Citeseer, 2007.

[59] Aude Oliva and Antonio Torralba. Modeling the shape of the scene: A holistic representation of the spatial envelope. *International journal of computer vision*, 42(3):145–175, 2001.

[60] Kamila Maria Jozwik, Martin Schrimpf, Nancy Kanwisher, and James J DiCarlo. To find better neural network models of human vision, find better neural network models of primate vision. *BioRxiv*, page 688390, 2019.

[61] Nancy Kanwisher. Functional specificity in the human brain: a window into the functional architecture of the mind. *Proceedings of the National Academy of Sciences*, 107(25):11163–11170, 2010.

[62] Kalanit Grill-Spector and Kevin S Weiner. The functional architecture of the ventral temporal cortex and its role in categorization. *Nature Reviews Neuroscience*, 15(8):536–548, 2014.

[63] Dwight J Kravitz, Kadharbatcha S Saleem, Chris I Baker, and Mortimer Mishkin. A new neural framework for visuospatial processing. *Nature Reviews Neuroscience*, 12(4):217–230, 2011.

[64] D.J. Felleman and D.C. Van Essen. Distributed hierarchical processing in the primate cerebral cortex. *Cerebral Cortex*, 1(1):1–47.

[65] J.J. DiCarlo, D. Zoccolan, and N.C. Rust. How does the brain solve visual object recognition? *Neuron*, 73(3):415–434. doi: 10.1016/j.neuron.2012.01.010. URL https://doi.org/10.1016/j.neuron.2012.01.010.

[66] Nicole C Rust and James J DiCarlo. Selectivity and tolerance ("invariance") both increase as visual information propagates from cortical area v4 to it. *Journal of Neuroscience*, 30(39):12978–12995, 2010.

[67] Jörn Diedrichsen and Nikolaus Kriegeskorte. Representational models: A common framework for understanding encoding, pattern-component, and representational-similarity analysis. *PLoS computational biology*, 13(4):e1005508, 2017.

[68] K. Kar, J. Kubilius, K. Schmidt, E.B. Issa, and J.J. DiCarlo. Evidence that recurrent circuits are critical to the ventral stream's execution of core object recognition behavior. *Nature Neuroscience*. doi: 10.1038/s41593-019-0392-5. URL https://doi.org/10.1038/s41593-019-0392-5.

[69] Jonas Kubilius, Martin Schrimpf, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, Aran Nayebi, Daniel Bear, Daniel L. K. Yamins, and James J. DiCarlo. Brain-Like Object Recognition with High-Performing Shallow Recurrent ANNs. In H. Wallach, H. Larochelle, A. Beygelzimer, F. D'Alché-Buc, E. Fox, and R. Garnett, editors, *Neural Information Processing Systems (NeurIPS)*, pages 12785—-12796. Curran Associates, Inc., 2019. URL http://papers.nips.cc/paper/9441-brain-like-object-recognition-with-high-performing-shallow-recurrent-anns.

[70] Ivan Ustyuzhaninov, Santiago A Cadena, Emmanouil Froudarakis, Paul G Fahey, Edgar Y Walker, Erick Cobos, Jacob Reimer, Fabian H Sinz, Andreas S Tolias, Matthias Bethge, et al. Rotation-invariant clustering of neuronal responses in primary visual cortex. In *International Conference on Learning Representations*, 2019.

[71] Sen Wang, Ronald Clark, Hongkai Wen, and Niki Trigoni. Deepvo: Towards end-to-end visual odometry with deep recurrent convolutional neural networks. *2017 IEEE International Conference on Robotics and Automation (ICRA)*, May 2017. doi: 10.1109/icra.2017.7989236. URL http://dx.doi.org/10.1109/ICRA.2017.7989236.

[72] GT Prusky and RM Douglas. Characterization of mouse cortical spatial vision. *Vision research*, 44(28):3411–3418, 2004.

[73] Chengxu Zhuang, Jonas Kubilius, Mitra JZ Hartmann, and Daniel L Yamins. Toward goal-driven neural network models for the rodent whisker-trigeminal system. In *Advances in Neural Information Processing Systems*, pages 2555–2565, 2017.

[74] Josh Merel, Diego Aldarondo, Jesse Marshall, Yuval Tassa, Greg Wayne, and Bence Ölveczky. Deep neuroethology of a virtual rodent. *arXiv preprint arXiv:1911.09451*, 2019.