On the Conditioning Consistency Gap in Conditional Neural Processes

Abstract

Neural processes are meta-learning models that map context sets to predictive distributions. While inspired by stochastic processes, NPs do not generally satisfy the Kolmogorov consistency conditions required to define a valid stochastic process. This inconsistency is widely acknowledged but poorly understood. Practitioners note that NPs work well despite the violation, without quantifying what this means. We address this gap by defining the conditioning consistency gap, a KL divergence measuring how much a CNP's predictions change when a point is added to the context versus conditioned upon. Our main results show that for CNPs with bounded encoders and Lipschitz decoders, the consistency gap is $O(1/n^2)$ in context size n, and that this rate is tight. These bounds explain why CNPs behave approximately consistently for moderate context sizes while potentially exhibiting inconsistency in the few-shot regime.

1 Introduction

Neural processes (Garnelo et al., 2018a;b) combine the flexibility of neural networks with the uncertainty quantification of Gaussian processes. Given a context set of input-output pairs, a neural process outputs a predictive distribution over outputs at new inputs. This framework has found applications in meta-learning, few-shot prediction, and sequential decision-making.

However, neural processes do not define valid stochastic processes in the sense of Kolmogorov. A stochastic process must satisfy two consistency conditions: marginalization consistency (integrating out variables yields the correct marginal) and conditioning consistency (the chain rule of probability holds). While CNPs satisfy marginalization consistency by construction as their decoder factorizes over target points, they violate conditioning consistency. Adding a point to the context and re-running the encoder does not produce the same result as conditioning a joint distribution.

This violation is well-known. The original neural process paper (Garnelo et al., 2018b) notes that the consistency conditions from the Kolmogorov extension theorem are only approximately satisfied. The Neural Process Family tutorial (Dubois et al., 2020) states explicitly that "in practice, NPs yield good predictive performance even though they can violate this consistency." Recent work on Flow Matching Neural Processes (Hamad & Rosenbaum, 2025) provides detailed discussion of which NP variants satisfy which consistency conditions, noting that CNPs are consistent over marginalization but not conditioning, while other variants like Neural Diffusion Processes exhibit the opposite pattern.

Despite this awareness, no prior work has quantified the consistency violation. How large is the gap? Does it vanish as context size grows? Under what conditions is it worst? Without answers to these questions, the statement that NPs "work well despite" inconsistency remains vague.

We provide a quantitative analysis of consistency in neural processes. We define the conditioning consistency gap as a KL divergence measuring how much predictions change when a point is added to the context versus conditioned upon, and derive exact characterizations and bounds for this quantity. For CNPs with linear decoders and constant variance, we show the gap is $O(1/n^2)$ in context size n, and extend this to general

Lipschitz decoders where the same rate holds. We further prove this rate is tight by constructing explicit CNPs that achieve it.

These results explain the empirical success of CNPs. For contexts of moderate size, the consistency gap is negligible. A context of 100 points yields a gap on the order of 10^{-4} nats under reasonable parameter settings. Our analysis also identifies the few-shot regime as where inconsistency is most severe, and characterizes the worst case as arising from "maximally surprising" new observations that differ substantially from the existing context.

2 Related Work

The neural process framework was introduced by Garnelo et al. (2018a) for conditional neural processes (CNPs) and extended to latent neural processes (Garnelo et al., 2018b). Subsequent work has developed many variants including attentive neural processes (Kim et al., 2019), convolutional neural processes (Gordon et al., 2020; Foong et al., 2020), and transformer-based neural processes (Nguyen & Grover, 2022). Our analysis focuses on the original CNP architecture but the techniques may extend to other variants.

The consistency issue has been noted since the original papers. Garnelo et al. (2018b) acknowledge that their model only approximately satisfies the Kolmogorov conditions. The Neural Process Family tutorial (Dubois et al., 2020) provides detailed discussion of exchangeability and consistency, noting that different architectures violate different conditions. Recent work (Dutordoir et al., 2023; Hamad & Rosenbaum, 2025) explicitly addresses consistency, with the latter providing a taxonomy of which models satisfy which conditions. However, none of this work quantifies the violation or provides bounds.

There is substantial work on generalization bounds for meta-learning (Baxter, 2000; Pentina & Lampert, 2014; Amit & Meir, 2018; Rothfuss et al., 2021), including information-theoretic approaches (Jose & Simeone, 2021). These bounds address how well a meta-learner generalizes to new tasks, not whether its predictions define a consistent stochastic process. Our work is complementary as we characterize a structural property (consistency) rather than a statistical one (generalization).

3 Setup

Let $(\mathcal{X}, \mathcal{Y})$ denote the input and output spaces, with $\mathcal{X} \subseteq \mathbb{R}^{d_x}$ and $\mathcal{Y} \subseteq \mathbb{R}^{d_y}$. A context set is a finite collection $C = \{(x_i, y_i)\}_{i=1}^n \subset \mathcal{X} \times \mathcal{Y}$.

Definition 1 (Conditional Neural Process). *A Conditional Neural Process (CNP) consists of:*

1. *An encoder $h : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}^d$ mapping context pairs to representations*

2. *An aggregator $a : (\mathbb{R}^d)^n \to \mathbb{R}^d$, typically mean aggregation: $r_C = \frac{1}{n} \sum_{i=1}^n h(x_i, y_i)$*

3. *A decoder defining $p_\theta(y \mid x; C) = \mathcal{N}(\mu_\theta(x, r_C), \sigma_\theta(x, r_C)^2 I)$*

For a context set C and a new observation (x_*, y_*), we write $C^+ = C \cup \{(x_*, y_*)\}$ for the augmented context.

4 Consistency Conditions

A stochastic process defines a consistent family of finite-dimensional distributions satisfying the Kolmogorov extension theorem. For predictive models, this translates to two conditions.

Definition 2 (Marginalization Consistency). *A predictive model $p(y_T \mid x_T; C)$ is marginalization consistent if for all target sets T and subsets $S \subset T$:*

$$\int p(y_T \mid x_T; C) \, dy_{T \setminus S} = p(y_S \mid x_S; C)$$

Definition 3 (Conditioning Consistency). *A predictive model is conditioning consistent if for all contexts C, observations (x_*, y_*), and targets $(x_\dagger, y_\dagger)$:*

$$p(y_\dagger \mid x_\dagger; C^+) = \frac{p(y_*, y_\dagger \mid x_*, x_\dagger; C)}{p(y_* \mid x_*; C)}$$

whenever $p(y_* \mid x_*; C) > 0$.

Remark 1. *CNPs are marginalization consistent by construction, since the decoder factorizes over target points:*

$$p(y_T \mid x_T; C) = \prod_{t \in T} p(y_t \mid x_t; C)$$

However, this factorization is what breaks conditioning consistency.

5 The Conditioning Consistency Gap

Definition 4 (Conditioning Consistency Gap). *For a CNP with context C, new observation (x_*, y_*), and target $x_\dagger$, the conditioning consistency gap is:*

$$\Delta(x_*, y_*, x_\dagger; C) = D_{\mathrm{KL}}\left(p_\theta(y_\dagger \mid x_\dagger; C^+) \,\|\, p_\theta(y_\dagger \mid x_\dagger; C)\right)$$

For conditioning consistency to hold, we would require $p(y_\dagger \mid x_\dagger; C^+) = p(y_\dagger \mid x_\dagger; C)$ (since the factorized joint implies the conditional equals the marginal). Thus $\Delta = 0$ iff conditioning consistency holds locally at $(x_*, y_*, x_\dagger)$.

For Gaussian predictive distributions with means μ_C, μ_{C^+} and variances $\sigma_C^2, \sigma_{C^+}^2$:

$$\Delta = \log \frac{\sigma_C}{\sigma_{C^+}} + \frac{\sigma_{C^+}^2 + (\mu_{C^+} - \mu_C)^2}{2\sigma_C^2} - \frac{1}{2}$$

Remark 2. *The conditioning consistency gap measures deviation from the identity $p(y_\dagger \mid x_\dagger; C^+) = p(y_\dagger \mid x_\dagger; C)$. This identity would hold if the predictive distributions came from a factorized joint $p(y_*, y_\dagger \mid x_*, x_\dagger; C) = p(y_* \mid x_*; C) \cdot p(y_\dagger \mid x_\dagger; C)$, since conditioning on y_* would then provide no information about $y_\dagger$. Ironically, a nonzero gap is what makes CNPs useful. observing (x_*, y_*) should change predictions at $x_\dagger$. The gap quantifies this update; consistency would imply the model ignores new evidence. a consistent model (like a GP) can also update predictions when conditioned on new data, but it just does so through the proper conditioning rule on a well-defined joint. CNPs update predictions through an inconsistent mechanism (recomputing the representation), which happens to work well empirically.*

6 Results

We first establish how the representation changes when augmenting the context.

Lemma 1 (Representation Update). *Under mean aggregation, adding (x_*, y_*) to a context of size n yields:*

$$r_{C^+} - r_C = \frac{h(x_*, y_*) - r_C}{n + 1}$$

Proof. Direct computation:

$$r_{C^+} = \frac{1}{n+1}\left[\sum_{i=1}^{n} h(x_i, y_i) + h(x_*, y_*)\right] = \frac{n \cdot r_C + h(x_*, y_*)}{n + 1}$$

Subtracting r_C gives the result. $\qquad\square$

Theorem 1 (Consistency Gap for Linear Decoders). *Suppose the decoder has the form $\mu_\theta(x, r) = W(x)^\top r$ for some $W : \mathcal{X} \to \mathbb{R}^{d \times d_y}$, and constant variance $\sigma_\theta(x, r) = \sigma > 0$. Then the conditioning consistency gap satisfies:*

$$\Delta(x_*, y_*, x_\dagger; C) = \frac{\|W(x_\dagger)^\top (h(x_*, y_*) - r_C)\|^2}{2\sigma^2(n+1)^2}$$

In particular, if $\|W(x)\|_{\mathrm{op}} \leq B_W$ for all x and $\|h(x, y)\| \leq B_h$ for all (x, y), then:

$$\Delta(x_*, y_*, x_\dagger; C) \leq \frac{2B_W^2 B_h^2}{\sigma^2(n+1)^2} = O\left(\frac{1}{n^2}\right)$$

Proof. With constant variance $\sigma_{C^+} = \sigma_C = \sigma$, the KL divergence simplifies to:

$$\Delta = \frac{(\mu_{C^+} - \mu_C)^2}{2\sigma^2}$$

The mean difference is:

$$\mu_{C^+}(x_\dagger) - \mu_C(x_\dagger) = W(x_\dagger)^\top (r_{C^+} - r_C) = \frac{W(x_\dagger)^\top (h(x_*, y_*) - r_C)}{n+1}$$

Substituting yields the first claim. For the bound, note that $\|r_C\| \leq B_h$ by convexity, so $\|h(x_*, y_*) - r_C\| \leq 2B_h$. □

Corollary 1 (Vanishing Gap). *Under the conditions of Theorem 1, for any $\epsilon > 0$, the conditioning consistency gap satisfies $\Delta < \epsilon$ whenever:*

$$n > \sqrt{\frac{2B_W^2 B_h^2}{\sigma^2 \epsilon}} - 1$$

7 Extension to Lipschitz Decoders

Theorem 2 (Consistency Gap for Lipschitz Decoders). *Suppose $\mu_\theta(x, \cdot)$ is L_μ-Lipschitz and $\sigma_\theta(x, \cdot)$ is L_σ-Lipschitz for all x, with $\sigma_\theta(x, r) \geq \sigma_{\min} > 0$. If $\|h(x, y)\| \leq B_h$ for all (x, y), then for sufficiently large n:*

$$\Delta(x_*, y_*, x_\dagger; C) \leq \frac{2(L_\mu^2 + 2L_\sigma^2)B_h^2}{\sigma_{\min}^2(n+1)^2} + O\left(\frac{1}{n^3}\right) \quad \text{for } n > \frac{4L_\sigma B_h}{\sigma_{\min}}$$

Proof. Let $\delta_r = r_{C^+} - r_C$, so $\|\delta_r\| \leq 2B_h/(n+1)$ by Lemma 1. By Lipschitz continuity:

$$|\mu_{C^+} - \mu_C| \leq L_\mu \|\delta_r\| \leq \frac{2L_\mu B_h}{n+1}$$

$$|\sigma_{C^+} - \sigma_C| \leq L_\sigma \|\delta_r\| \leq \frac{2L_\sigma B_h}{n+1}$$

The KL divergence between Gaussians $\mathcal{N}(\mu_1, \sigma_1^2)$ and $\mathcal{N}(\mu_0, \sigma_0^2)$ with $\mu_1 = \mu_0 + \epsilon_\mu$ and $\sigma_1 = \sigma_0 + \epsilon_\sigma$ satisfies (see Lemma 2 below):

$$D_{\mathrm{KL}} = \frac{\epsilon_\mu^2}{2\sigma_0^2} + \frac{\epsilon_\sigma^2}{\sigma_0^2} + O(\epsilon^3)$$

Substituting $\epsilon_\mu \leq 2L_\mu B_h/(n+1)$, $\epsilon_\sigma \leq 2L_\sigma B_h/(n+1)$, and $\sigma_0 \geq \sigma_{\min}$ yields the result. □

Remark 3. *Unlike typical perturbation bounds that are $O(\epsilon)$, the KL divergence between nearby Gaussians is $O(\epsilon^2)$ because the linear terms cancel. This is a manifestation of the fact that KL divergence is locally quadratic, related to Fisher information.*

8 Tightness of Bounds

We now show that the $O(1/n^2)$ rate in Theorem 1 is tight: there exist CNPs achieving this rate.

Theorem 3 (Lower Bound). *For any $B_W, B_h, \sigma > 0$, there exists a CNP with $\|W(x)\|_{\mathrm{op}} \leq B_W$, $\|h(x,y)\| \leq B_h$, and constant variance σ, and a sequence of contexts C_n of size n, such that:*

$$\Delta(x_*, y_*, x_\dagger; C_n) = \frac{2B_W^2 B_h^2}{\sigma^2(n+1)^2}$$

matching the upper bound in Theorem 1.

Proof. We construct an explicit example. Let $d = d_y = 1$ (scalar representations and outputs) and define:

- Encoder: $h(x,y) = B_h \cdot \mathrm{sign}(y) \cdot \mathbf{1}_{|y|>0}$, i.e., h outputs $+B_h$ for positive y and $-B_h$ for negative y

- Decoder mean: $\mu_\theta(x,r) = B_W \cdot r$ (linear with slope B_W)

- Decoder variance: $\sigma_\theta(x,r) = \sigma$ (constant)

Consider the context $C_n = \{(x_i, y_i)\}_{i=1}^n$ where all $y_i < 0$. Then:

$$r_{C_n} = \frac{1}{n} \sum_{i=1}^n h(x_i, y_i) = \frac{1}{n} \cdot n \cdot (-B_h) = -B_h$$

Now take the new observation (x_*, y_*) with $y_* > 0$, so $h(x_*, y_*) = +B_h$. The representation difference is:

$$h(x_*, y_*) - r_{C_n} = B_h - (-B_h) = 2B_h$$

By Theorem 1, the consistency gap is:

$$\Delta = \frac{|W(x_\dagger)|^2 \cdot |h(x_*, y_*) - r_C|^2}{2\sigma^2(n+1)^2} = \frac{B_W^2 \cdot 4B_h^2}{2\sigma^2(n+1)^2} = \frac{2B_W^2 B_h^2}{\sigma^2(n+1)^2}$$

$$\square$$

Remark 4 (Interpretation). *The lower bound is achieved when:*

1. *The new observation is "maximally surprising" relative to the context (opposite sign of all context points)*

2. *The decoder fully utilizes its capacity (weight at the bound B_W)*

In benign cases where new observations are similar to the context, the gap will be much smaller. The $O(1/n^2)$ rate represents the worst case.

8.1 Corrected Bound for Lipschitz Decoders

We note that Theorem 2 can be strengthened. The KL divergence between Gaussians is locally quadratic:

Lemma 2. *For Gaussians with $\mu_1 = \mu_0 + \epsilon_\mu$ and $\sigma_1 = \sigma_0 + \epsilon_\sigma$ where $|\epsilon_\sigma| < \sigma_0/2$:*

$$D_{\mathrm{KL}}(\mathcal{N}(\mu_1, \sigma_1^2) \| \mathcal{N}(\mu_0, \sigma_0^2)) = \frac{\epsilon_\mu^2}{2\sigma_0^2} + \frac{\epsilon_\sigma^2}{\sigma_0^2} + O(\epsilon^3)$$

where $\epsilon = \max(|\epsilon_\mu|, |\epsilon_\sigma|)$.

Proof. Expand the KL divergence formula:

$$D_{\text{KL}} = \log \frac{\sigma_0}{\sigma_1} + \frac{\sigma_1^2 + (\mu_1 - \mu_0)^2}{2\sigma_0^2} - \frac{1}{2}$$

For the log term, using $\log(1 + x) = x - x^2/2 + O(x^3)$:

$$\log \frac{\sigma_0}{\sigma_0 + \epsilon_\sigma} = -\log \left(1 + \frac{\epsilon_\sigma}{\sigma_0}\right) = -\frac{\epsilon_\sigma}{\sigma_0} + \frac{\epsilon_\sigma^2}{2\sigma_0^2} + O(\epsilon_\sigma^3)$$

For the variance ratio term:

$$\frac{(\sigma_0 + \epsilon_\sigma)^2}{2\sigma_0^2} = \frac{1}{2} + \frac{\epsilon_\sigma}{\sigma_0} + \frac{\epsilon_\sigma^2}{2\sigma_0^2}$$

Combining:

$$D_{\text{KL}} = \left(-\frac{\epsilon_\sigma}{\sigma_0} + \frac{\epsilon_\sigma^2}{2\sigma_0^2}\right) + \left(\frac{1}{2} + \frac{\epsilon_\sigma}{\sigma_0} + \frac{\epsilon_\sigma^2}{2\sigma_0^2}\right) + \frac{\epsilon_\mu^2}{2\sigma_0^2} - \frac{1}{2}$$

$$= \frac{\epsilon_\sigma^2}{\sigma_0^2} + \frac{\epsilon_\mu^2}{2\sigma_0^2} + O(\epsilon^3)$$

$\square$

Corollary 2 (Improved Lipschitz Bound)**.** *Under the conditions of Theorem 2, for sufficiently large n:*

$$\Delta(x_*, y_*, x_\dagger; C) = O\left(\frac{1}{n^2}\right)$$

The rate is $O(1/n^2)$ regardless of whether variance depends on the representation.

Proof. By Lipschitz continuity and Lemma 2:

$$\Delta \leq \frac{L_\mu^2 \|r_{C^+} - r_C\|^2}{2\sigma_{\min}^2} + \frac{L_\sigma^2 \|r_{C^+} - r_C\|^2}{\sigma_{\min}^2} + O(1/n^3)$$

Since $\|r_{C^+} - r_C\| \leq 2B_h/(n+1)$, both terms are $O(1/n^2)$. $\square$

9 Discussion

Our results establish that the conditioning consistency gap for CNPs with bounded encoders and Lipschitz decoders is $O(1/n^2)$ in context size, and that this rate is tight. This provides a theoretical explanation for the empirical observation that CNPs work well in practice despite not defining valid stochastic processes, because the inconsistency becomes negligible for sufficiently large context sets. For a context of size $n = 100$ and reasonable constants ($B_W = B_h = 1$, $\sigma = 1$), the consistency gap is on the order of 10^{-4} nats, which is unlikely to affect downstream performance in most applications.

The $O(1/n^2)$ rate has practical implications. Consistency violations are most severe in the few-shot regime with fewer than ten context points, which is a regime where CNPs are often deployed. For moderate context sizes above fifty points, CNPs are approximately consistent and the gap becomes negligible. Applications requiring strict consistency, such as certain sequential decision making settings where predictions must cohere across time, should either ensure sufficiently large contexts or consider alternative architectures that guarantee consistency by construction.

The tightness result (Theorem 3) reveals consistency violations are worst when the new observation is maximally surprising relative to the existing context. In the constructed example, all context points have one sign while the new observation has the opposite sign, maximizing the representation shift. This suggests that in benign settings where new observations are similar to existing context, the actual consistency gap

will be much smaller than the worst-case bound. Practitioners working with smoothly varying data may experience effectively consistent behavior even with small contexts.

An interesting consequence of our analysis is that the $O(1/n^2)$ rate holds regardless of whether the decoder variance depends on the representation. One might expect that allowing variance to change with context would introduce additional inconsistency, but Lemma 2 shows that the KL divergence between nearby Gaussians is locally quadratic in both mean and variance perturbations. The linear terms cancel, yielding the same asymptotic rate.

Several questions remain open. How does the gap behave for latent neural processes with stochastic encoders? The latent variable introduces additional structure that may either help or hurt consistency. What is the relationship between the conditioning consistency gap and downstream task performance? Our bounds are information-theoretic, but the operational consequences for tasks like Bayesian optimization are unclear. Can training objectives be modified to explicitly minimize the consistency gap, perhaps through a regularizer that penalizes large representation shifts?

Finally, do similar bounds hold for attention-based aggregation, which are increasingly popular in modern neural process variants? Attention does not satisfy the simple update rule, but we leave this to future work.

References

Ron Amit and Ron Meir. Meta-learning by adjusting priors based on extended PAC-Bayes theory. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 205–214. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/amit18a.html.

Jonathan Baxter. A model of inductive bias learning. *J. Artif. Int. Res.*, 12(1):149–198, March 2000. ISSN 1076-9757.

Yann Dubois, Jonathan Gordon, and Andrew YK Foong. Neural process family. http://yanndubs.github.io/Neural-Process-Family/, September 2020.

Vincent Dutordoir, Alan Saul, Zoubin Ghahramani, and Fergus Simpson. Neural diffusion processes. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 8990–9012. PMLR, 23–29 Jul 2023. URL https://proceedings.mlr.press/v202/dutordoir23a.html.

Andrew Foong, Wessel Bruinsma, Jonathan Gordon, Yann Dubois, James Requeima, and Richard Turner. Meta-learning stationary stochastic process prediction with convolutional neural processes. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 8284–8295. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/5df0385cba256a135be596dbe28fa7aa-Paper.pdf.

Marta Garnelo, Dan Rosenbaum, Christopher Maddison, Tiago Ramalho, David Saxton, Murray Shanahan, Yee Whye Teh, Danilo Rezende, and S. M. Ali Eslami. Conditional neural processes. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1704–1713. PMLR, 10–15 Jul 2018a. URL https://proceedings.mlr.press/v80/garnelo18a.html.

Marta Garnelo, Jonathan Schwarz, Dan Rosenbaum, Fabio Viola, Danilo J. Rezende, S. M. Ali Eslami, and Yee Whye Teh. Neural processes, 2018b. URL https://arxiv.org/abs/1807.01622.

Jonathan Gordon, Wessel P. Bruinsma, Andrew Y. K. Foong, James Requeima, Yann Dubois, and Richard E. Turner. Convolutional conditional neural processes. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=Skey4eBYPS.

Hussen Abu Hamad and Dan Rosenbaum. Flow matching neural processes. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL `https://openreview.net/forum?id=R8n2h7hzqS`.

Sharu Theresa Jose and Osvaldo Simeone. Information-theoretic generalization bounds for meta-learning and applications. *Entropy*, 23(1), 2021. ISSN 1099-4300. doi: 10.3390/e23010126. URL `https://www.mdpi.com/1099-4300/23/1/126`.

Hyunjik Kim, Andriy Mnih, Jonathan Schwarz, Marta Garnelo, Ali Eslami, Dan Rosenbaum, Oriol Vinyals, and Yee Whye Teh. Attentive neural processes. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=SkE6PjC9KX`.

Tung Nguyen and Aditya Grover. Transformer neural processes: Uncertainty-aware meta-learning via sequence modeling. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 16569–16594. PMLR, 2022. URL `https://proceedings.mlr.press/v162/nguyen22b.html`.

Anastasia Pentina and Christoph Lampert. A pac-bayesian bound for lifelong learning. In Eric P. Xing and Tony Jebara (eds.), *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pp. 991–999, Bejing, China, 22–24 Jun 2014. PMLR. URL `https://proceedings.mlr.press/v32/pentina14.html`.

Jonas Rothfuss, Vincent Fortuin, Martin Josifoski, and Andreas Krause. Pacoh: Bayes-optimal meta-learning with pac-guarantees. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 9116–9126. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/rothfuss21a.html`.