Interpreting and Steering a Text-to-Speech Language Model with Sparse Autoencoders

Abstract

Language models increasingly serve as the backbone of text-to-speech (TTS) systems, yet we understand little about the representations they build when text and generated speech tokens share a single residual stream. We train BatchTopK sparse autoencoders on the LM backbone of CosyVoice3 and introduce a modality-aware auto-interp pipeline that labels each feature from where it fires—text-prefix context, 1-second speech clips, or both. The recovered features are interpretable, spanning phonemes, laughter, accent prompts and speaker gender. Steering through the SAE latent space shows these features are causal rather than merely descriptive: targeted interventions raise laughter probability from 0.02 to 0.79, flip perceived speaker gender, and control speech rate while preserving spoken content. SAE features thus serve both as interpretability objects and as control directions for TTS synthesis.

1 Introduction

Mechanistic interpretability of large language models has benefited enormously from sparse autoencoders, which decompose dense, polysemantic residual-stream activations into sparse, approximately monosemantic features (Cunningham et al., 2023; Templeton et al., 2024). Paired with LLM-based automatic interpretation ("auto-interp") (Bills et al., 2023; Paulo et al., 2024), SAEs now provide a scalable path toward understanding what individual components of a text LM compute.

TTS models built on LM backbones present a qualitatively different setting. A model such as CosyVoice3 (Du et al., 2024) processes a mixed sequence: an instruction/text prefix followed by discrete 25 Hz speech tokens, and generates the latter autoregressively. The representations it builds may encode syntactic and semantic information from the text prefix, acoustic and prosodic properties of the speech being generated, or both—but we

currently have no principled way to identify which features serve which role.

We make three contributions:

1. **SAE training on a TTS LM.** We train BatchTopK SAEs on CosyVoice3 residual-stream activations on $\approx$250M tokens.
2. **Modality-aware auto-interp.** We adapt auto-interp to the mixed text–speech sequence: features are labeled from prefix-token context, 1-second speech clips, or both, depending on where they activate.
3. **Layer-wise feature modality analysis.** We categorize features by whether they fire on text-position or speech-position tokens, exposing how linguistically- and acoustically-grounded directions emerge across layers.

2 Background and Related Work

SAEs for LM interpretability. SAEs decompose LM residual streams into sparse, approximately monosemantic features (Cunningham et al., 2023; Templeton et al., 2024; Lieberum et al., 2024), with TopK/BatchTopK variants (Gao et al., 2024).

Automatic interpretation. Bills et al. (2023) use LLMs to describe activation patterns, and Paulo et al. (2024) score the resulting labels with a detection-style protocol over activating vs. non-activating examples. We adapt this protocol from text-only activations to mixed text/audio evidence.

TTS and speech interpretability. Probing has examined speech encoders (Pasad et al., 2021) and SAEs have been applied to discriminative speech and audio foundation models (Aparin et al., 2026). To our knowledge, this is the first SAE analysis of the residual stream of a generative TTS LM backbone.

3 Method

We apply SAEs to the LLM residual stream of CosyVoice3 and route each feature's strongest acti-

vations to text, audio, or mixed evidence before automatic labeling and held-out evaluation (pipeline diagram in Appendix A).

3.1 Model and SAE Training

We use CosyVoice3 (Du et al., 2024), a TTS system whose LM backbone is Qwen2.5-0.5B (hidden size 896, 28 layers). The LM receives a text prompt tokenized with a BPE vocabulary and generates 25 Hz discrete speech tokens autoregressively. We train BatchTopK SAEs (Gao et al., 2024) at multiple layers of the LM backbone with dictionary size $d=16{,}384$ and $k=50$ active features per token, on ≈ 250M tokens from the Emilia dataset (He et al., 2024). We use the full layer sweep for modality and reconstruction analyses, and use layer 20 for the most detailed qualitative examples. Training uses the standard reconstruction + sparsity objective with an auxiliary dead-feature loss.

3.2 Evidence Extraction

For each SAE feature, we collect its highest-activating token positions and convert them into modality-specific evidence. Exact sequence boundaries tell us whether each activation occurred in the language prefix or in the speech-token segment. Text activations are represented by a marked token window, while speech activations are represented by a short audio clip centered on the active speech token. This lets the same auto-interp pipeline operate on text-only, audio-only, and mixed features without forcing all evidence into a single format. Implementation details are given in Appendix B.

3.3 Feature Modality Tagging

CosyVoice3 is trained on randomly-interleaved text and speech sequences, so absolute token position carries no stable semantic meaning across samples. We therefore characterize each feature by the empirical token-type composition of its strongest activations. Features whose top examples are mostly speech-token positions are audio-modal, features whose examples are mostly prefix-token positions are text-modal, and the remainder are mixed:

- **Audio-modal**: speech fraction ≥ 0.8
- **Text-modal**: speech fraction ≤ 0.2
- **Mixed**: otherwise

3.4 Automatic Labeling

We label features with a modality-aware prompt to Gemini 3.0 Pro (Google DeepMind, 2024). The evidence shown to the labeler depends on the feature's modality:

- **Text-modal features** receive text evidence from the instruction/transcript prefix: region, token position, activation value, and source text context.
- **Audio-modal features** receive only 1-second speech clips centered on speech-token activations.
- **Mixed features** receive both text examples and speech clips. We label a mixed feature only when both evidence types are present.

The prompt asks for a single concise sentence describing the property consistently associated with the activating evidence. For text evidence, labels may refer to lexical, punctuation, language, or prompt-style patterns. For audio evidence, labels may refer to acoustic, phonetic, or prosodic properties. For mixed evidence, the labeler is asked to describe the cross-modal relation when one is visible. For exact prompts see Appendix H.

3.5 Detection-Style Evaluation

We evaluate labels with a detection-style task (cf. Paulo et al. 2024) adapted to multimodal evidence. Given a proposed label, a held-out evaluator scores shuffled positive and negative evidence items for how well they match the label. We report AUROC and balanced accuracy over these held-out judgments, with balanced feature samples for the text, audio, and mixed groups. The scoring protocol is described in Appendix B.

3.6 SAE Feature Steering

To test whether interpreted SAE features can causally control TTS generation, we intervene through the SAE latent space rather than directly adding a residual vector. During generation, speech-token residual states are encoded by the frozen SAE, selected feature activations are shifted by a signed and normalized amount, and the modified latent state is decoded back into the model residual stream. The intervention strength during generation is controlled by a scalar α, while input-text and speech-prompt tokens are left unchanged. Implementation details are given in Appendix C.

4 Results

4.1 Layer Sweep

Figure 1 shows that the SAE dictionary remains a strong reconstruction model across the TTS back-

Figure 1: Layer sweep across the Qwen2.5-0.5B backbone. **(a)** SAE explained variance by token type. **(b)** Feature modality composition. Middle layers mix text and speech evidence, layers 16–20 become audio-heavy, and the final hidden state becomes mostly text-modal.

Feat.	Mod.	Auto-interp label	B/A
1376	Text	Word "British" in speaker-accent descriptions	1.00/1.00
233	Audio	The sound of human laughter	0.75/0.75
5543	Mixed	The phoneme sequence /ohl/ in text and speech	0.92/0.98

Table 1: One representative feature per modality. Full examples are in Appendix F.

Figure 2: Held-out auto-interp scores for layer-20 features. Text labels are easiest to verify; mixed labels are hardest.

bone while its feature types shift substantially with depth. Early and middle layers contain many mixed features, layers 16–20 are dominated by audio-modal features, and the final hidden state sharply reverts to a mostly text-modal subspace. This layer-wise movement suggests that the LM backbone does not merely carry a static text prefix forward: sparse directions become tied to the generated speech-token stream as acoustic prediction is formed. Additional layer-sweep details are reported in Appendix D.

4.2 Auto-Interp Quality

Figure 2 reports the balanced rank-held-out auto-interp evaluation for the layer-20 case study. Text-modal labels are easiest to verify (AUROC 0.921), audio-modal labels remain above chance (AUROC 0.653), and mixed features are hardest in aggregate (AUROC 0.558). The same ordering appears across completed layers (Appendix E).

Qualitative inspection finds text features for individual tokens, words, years, and voice-prompt attributes. Audio features for phonemes, gender, laughter, stuttering, breaths, and accent cues, and a smaller set of mixed features linking the same word or phoneme-like event across text and speech.

4.3 Probe-Based Feature Selection

We use downstream acoustic probes to identify SAE features whose activations are predictive of controllable speech properties. For each candidate feature, we generate a small set of steered samples and score the resulting waveforms with external speech metrics, such as laughter probability, emo-

Figure 3: Gender steering split by prompt-speaker gender. Feature 11402 shifts both male- and female-prompted generations toward the target gender.

Feat.	Auto-interp label	Steering effect
14834	Laughter-like vocal events	More laughter
11402	Speaker-gender cues	Male/female shift
3024	Speech-rate variation	Slower/faster speech

Table 2: Layer-20 SAE features used for steering.

tion classification and accent classification. The probing protocol and candidate-selection results are reported in Appendix G.

4.4 Feature Steering

We finally test whether interpreted SAE features can be used as causal controls for synthesis. We steer three layer-20 features with labels, shown in Table 2. The resulting generations show targeted changes along the corresponding acoustic axes (Figure 4). Feature 14834 increases laughter probability from 0.015 to 0.791 at $\alpha = +60$. Feature 11402 changes speaker-gender cues, moving wav2vec2 $P(\text{male})$ from 0.629 at baseline to 0.944 at $\alpha = -50$ and 0.063 at $\alpha = +50$. Feature 3024 controls speech rate, changing voiced duration from 3.96 s at baseline to 10.57 s at $\alpha = -50$ and 2.75 s at $\alpha = +50$, preserving spoken content.

Figure 3 further separates the gender steering result by the prompt speaker's original gender.

5 Discussion

What TTS features encode. The feature-modality split suggests that CosyVoice3's LM backbone does more than carry forward the linguistic prefix: by late layers, many sparse directions are tied to speech-token positions. Text-modal features capture lexical and prompt-side structure, while audio-modal features often correspond to phonetic, acoustic, or prosodic properties. Mixed features

Figure 4: Steering effects for laughter, speaker-gender cues, and speech rate. Error bars show ± 1 SEM over the 40-voice $\times$ 10-text prompts grid.

may reflect cross-modal structure involved in mapping text to speech.

6 Conclusion

SAEs trained on a TTS LM recover interpretable text-modal, audio-modal, and mixed features, and a modality-aware auto-interp pipeline labels them with descriptions testable by a detection-style scorer. Steering experiments further show that some interpreted SAE features are not merely descriptive: intervening on their latent activations can causally control perceptual properties of generated speech. This suggests that SAE features can serve both as interpretability objects and as practical control directions for TTS synthesis.

7 Limitations

Single model: results are for CosyVoice3-0.5B and may not transfer to larger TTS models. *Circular evaluation:* the labeler and scorer share

the same Gemini model, so systematic hallucinations would inflate scores; human evaluation and a scorer-model ablation are needed. *Partial auto-interp sweep:* modality and reconstruction statistics are reported across layers, while detection-style auto-interp scores are available for the completed subset of layers. *Sub-token onset:* speech-token timestamps are at the 25 Hz rate and do not localize sub-token (40 ms) acoustic onsets. *Negative sampling:* negatives are drawn from other features, which tests label specificity but not robustness against representation-neighbor confounds.

References

Georgii Aparin, Tasnima Sadekova, Alexey Rukhovich, Assel Yermekova, Laida Kushnareva, Vadim Popov, Kristian Kuznetsov, and Irina Piontkovskaya. 2026. AudioSAE: Towards understanding of audio-processing models with sparse autoencoders. *arXiv preprint arXiv:2602.05027*.

Steven Bills, Nick Cammarata, Dan Mossing, Henk Tillman, Leo Gao, Gabriel Goh, Ilya Sutskever, Jan Leike, Jeff Wu, and William Saunders. 2023. Language models can explain neurons in language models. *OpenAI blog*.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*.

Zhihao Du, Qian Chen, Shiliang Zhang, Kai Hu, Heng Lu, Yexin Yang, Hangrui Hu, Siqi Zheng, Yue Gu, Ziyang Ma, and 1 others. 2024. CosyVoice: A scalable multilingual zero-shot text-to-speech synthesizer based on supervised semantic tokens. *arXiv preprint arXiv:2407.05407*.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Tow, Hoagy Cunningham, Tom Conerly, Adly Templeton, Trenton Bricken, and 1 others. 2024. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093*.

Google DeepMind. 2024. Gemini: A family of highly capable multimodal models. Technical report, Google DeepMind.

Haorui He, Zengqiang Shang, Chaoren Wang, Xuyuan Li, Yicheng Gu, Hua Hua, Liwei Liu, Chen Yang, Jiaqi Li, Peiyang Shi, and 1 others. 2024. Emilia: An extensive, multilingual, and diverse speech dataset for large-scale speech generation. *arXiv preprint arXiv:2407.05361*.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, János Kramár, Rohin Shah, Tom Henighan, Neel Nanda, and Juyeon Bhattacharyya. 2024. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. *arXiv preprint arXiv:2408.05147*.

Ankita Pasad, Ju-Chieh Chou, and Karen Livescu. 2021. Layer-wise analysis of a self-supervised speech representation model. In *ASRU*.

Gonçalo Paulo, Alex Mallen, Caden Juang, and Nora Belrose. 2024. Automatically interpreting millions of features in large language models. *arXiv preprint arXiv:2410.13928*.

Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, and 1 others. 2024. Scaling and evaluating sparse autoencoders. *Anthropic, accessed*.

Appendix

A   Pipeline Diagram

B   Experimental Protocol Details

Activation evidence.   For each feature, we identify its top-20 activating token positions across the dataset by encoding residual-stream activations through the frozen SAE. The LM is run in teacher-forced mode with sequence layout

$$[\text{sos} \mid \text{instruct} \mid \text{text} \mid \text{task} \mid \text{speech}],$$

where the task boundary is a single special token marking the text-to-speech transition. For every sample we record the exact instruction, text, and speech token lengths. For speech-token activations, positions are mapped to audio timestamps using the 25 Hz speech-token rate, and we extract a 1-second window centered on the peak position from the source audio. Padded positions are masked before top-activation search, evidence extraction, and modality statistics.

Modality assignment.   For each feature we compute the fraction of top-20 activating positions that fall in the speech segment of their respective sequences. Let $b_i = 1 + \ell^{(i)}_{\text{instruct}} + \ell^{(i)}_{\text{text}} + 1$ be the speech-start position for sample i. A top activation at token position p is counted as speech iff $p \geq b_i$ and p is before the sample's valid sequence length. Features with speech fraction at least 0.8 are audio-modal; features with speech fraction at most 0.2 are text-modal; all others are mixed.

Held-out scoring.   To prevent the scorer from seeing the same examples used to write the label, we use a rank-held-out split over activation-ranked examples: the five strongest activations are reserved for labeling and lower-ranked activations are used for scoring. For the layer-20 balanced comparison, we evaluate all 668 mixed features together with matched 668-feature samples of text-modal and audio-modal features. Each scoring prompt contains held-out positive evidence from the target feature and negatives from other features. The scorer rates each item from 0–10 for how well it matches the label; we compute AUROC over the resulting positive-vs.-negative ranking and balanced accuracy after thresholding ratings at 5.

C   SAE Steering Implementation

We implement steering as an intervention in the latent space of the frozen SAE attached to a transformer residual stream. The hook is registered at the same layer used for the interpreted features and is applied only to speech-token positions. The hook is applied to the speech-prompt segment during pre-fill and only to the current generated speech-token position during autoregressive decoding. Instruction, text-prefix, and task-token positions are not modified.

For each hooked residual vector h, we first compute SAE activations:

$$z = \sigma(W_{\text{enc}}h + b_{\text{enc}}).$$

We then perturb selected SAE coordinates by a signed, feature-wise amount:

$$z' = z + \alpha \cdot s \odot \bar{Z}.$$

Here α is the scalar steering strength, s is a sparse sign vector specifying the polarity of each steered feature, and $\bar{Z}$ contains feature-wise activation scales. Entries outside the selected feature set are set to zero, so the intervention changes only the intended SAE coordinates.

Finally, the modified latent vector is decoded back to the model residual space:

$$\hat{h}' = W_{\text{dec}}z' + b_{\text{dec}}.$$

The hook replaces the original residual vector at the selected speech-token positions with $\hat{h}'$. This makes the intervention local to the SAE feature subspace while preserving the model's normal autoregressive generation procedure outside the hooked positions.

D   Additional Layer-Sweep Details

Feature modality distribution.   Figure 1b shows how the modality composition of SAE features evolves across the 24-layer Qwen2.5-0.5B backbone. We identify three regimes. **Early and middle layers (0–14)** are dominated by *mixed* and *audio* features, with text-modal features in the minority (12–33%). Even at the embedding output (layer 0) only 12.3% of features are text-modal, while 45.1% are audio-modal and 42.6% fire on both segments: the residual stream is already strongly multimodal. Mixed features are most prominent in this band, peaking at 47.3% at layer 12, consistent with cross-modal fusion rather than independent specialization. **Late layers (16–20)** are the audio-commitment zone: audio-modal features dominate (76.1% at layer 16, 65.0% at layer 18,

CosyVoice3 synthesis path

Figure 5: CosyVoice-aware view of our modality-aware SAE interpretation pipeline. CosyVoice3 synthesizes speech by passing text and prompt audio through tokenizers, an LLM backbone, discrete speech token generation, DiT flow matching, and a HiFi-GAN vocoder. Our analysis attaches SAEs to the LLM residual stream, uses exact text/speech boundaries to route top activations to text, audio, or mixed evidence, then labels and scores the resulting features.

74.3% at layer 20) while mixed features collapse (from 40.9% at layer 14 to 4.1% at layer 20). Features attach decisively to the speech-token segment as the network finalizes the acoustic prediction. **Layer 23** (the final hidden state) reverses sharply: 83.1% text-modal, 14.3% audio-modal, only 2.6% mixed. Inspecting per-sample activations, layer 23's sequence is much shorter than the intermediate layers and its position distribution leans heavily toward text-prefix tokens, suggesting the final residual stream re-projects toward a text-vocabulary-aligned subspace before the output head.

Reconstruction quality per modality. Figure 1a reports the SAE's per-token explained variance (EV) on a 5,000-sample sweep, with positions partitioned by token type. EV is computed against the modality-restricted mean, so the text and audio columns are independent measurements of how well the SAE reconstructs each subdistribution. Three trends are visible. First, reconstruction quality stays high through the early layers (overall EV 0.97–0.99 at layers 0–8) and then declines through the body of the network to a minimum of 0.82 at layer 20. Second, text-position activations are generally reconstructed at least as well as audio positions, with the largest text–audio gap at the audio-commitment layers (0.065 at layer 16, 0.080 at layer 20); the early layers are the exception, where the gap is small or even mildly reversed (audio EV 0.992 vs. text 0.986 at layer 4). Third, layer 23

breaks the downward trend sharply: its overall EV rebounds to 0.945 and the text/audio gap closes to 0.015. Audio activations are generally harder to compress with $k = 50$ active features than text activations, consistent with the larger and more entropic audio-token vocabulary.

E Layer-Wise Auto-Interp Scores

Layer-wise pattern. The same ordering appears across the network: text-modal labels are consistently the easiest to verify (AUROC 0.90–0.94), audio-modal labels are weaker but reliably above chance (AUROC 0.65–0.72), and mixed labels are the most variable (AUROC 0.53–0.69). This supports a conservative interpretation of the qualitative examples: single-modality features are often well described by one sentence, while mixed features more often combine several correlated textual and acoustic properties.

F Representative Features

Manual observations. Text features split into prompt-bound directions (e.g. 1376 "British" and 1305 "shrill" in voice-conditioning prompts) and prompt-independent lexical/sub-lexical patterns (1443 substring "ang", 1330 four-digit years), suggesting the dictionary tracks both the conditioning signal and generic lexical structure. Most text-modal features are highly local: they activate on individual BPE tokens, words, punctuation, or short

Figure 6: Rank-held-out auto-interp scores across completed layers. Text-modal labels remain consistently easiest to verify; audio-modal labels are above chance but weaker; mixed labels are the most variable.

Table 3: Representative layer-20 features with auto-interp labels and held-out detection scores.

Feat.	Mod.	Auto-interp label	BAcc	AUROC
1376	Text	Word "British" in speaker-accent descriptions	1.000	1.000
1443	Text	Morpheme/substring "ang" in tokens such as "angry", "anger", "hanging"	1.000	1.000
1305	Text	Voice prompts describing speaker tone as "shrill"	1.000	1.000
1330	Text	Four-digit numbers representing years (e.g., 2019, 1936)	1.000	1.000
233	Audio	The sound of human laughter	0.750	0.750
288	Audio	Screaming, shouting, and heavy breathing	0.917	1.000
1225	Audio	Voiceless velar plosive /k/	1.000	1.000
1294	Audio	Phoneme sequence /if/ or /ef/	1.000	1.000
1393	Audio	Spoken /ing/ phoneme sequence	1.000	1.000
164	Mixed	Stutters, false starts, and hesitation markers	0.917	1.000
661	Mixed	The word "middle" in text instructions and spoken clips	1.000	1.000
5543	Mixed	The phoneme sequence /ohl/ in text and speech	0.917	0.979

token contexts. Some correspond to written descriptions of acoustic events or speaker attributes, such as laughter markers, accent words, and voice-style adjectives in the instruction.

Audio features span phonemes and short phoneme sequences (/k/, /if/–/ef/, /ing/), whole-word and non-speech vocal events (laughter, screams, heavy breathing, stuttering, breaths), and occasional accent cues.

Mixed features are harder on average and often look polysemantic, but some are clean: 164 links stutters across transcript and audio, 661 links the word "middle" across text and speech, and 5543 links the same /ohl/-like phoneme sequence in text and speech. We also observe punctuation-to-pause-like mixed features, but do not treat these as primary examples unless their held-out scores support the label.

G Concept Probing Experiments

Setup. We run supervised probes for three speech-style concepts: laughter, emotion, and accent.

For each concept and layer, we train a binary logistic-regression probe

$$\hat{y} = \sigma(\beta^\top \phi(x) + b),$$

where $\phi(x)$ is either the raw residual vector $h_L \in \mathbb{R}^{896}$ or the SAE latent vector $z_L = \text{SAE}_L(h_L) \in \mathbb{R}^{16,384}$. We train probes on the activation from the final speech-prompt token. We use L-BFGS with maximum 2000 iterations, apply MaxAbs scaling fit on the training fold only, and report ROC-AUC averaged over stratified 5-fold cross-validation.

Data. All three concept probes use the same neutral negative pool: 500 Emilia-Yodas neutral-speech clips, filtered to duration 2–20 seconds and DNSMOS at least 3.0. We also use a shared text-prefix control: 500 LJSpeech transcripts of length 5–15 words, sampled with a fixed seed.

For laughter, positives are 500 VocalSound laughter clips. For emotion, positives are 500 clips per class from ESD, with one binary probe for each of four emotions: Happy, Sad, Angry, and Surprise. For accent, positives are VCTK 0.92 utterances grouped by speaker accent, with one binary probe

per accent. We evaluate eleven accents: English, American, Scottish, Irish, Indian, Canadian, Northern Irish, South African, Australian, Welsh, and New Zealand. The Welsh and New Zealand buckets are single-speaker buckets in VCTK 0.92, so these probes partially conflate accent with speaker identity.

Top-k SAE feature analysis. For each SAE-latent probe, we test whether the concept is distributed across many SAE features or concentrated in a small number of dictionary atoms. We compute the mean coefficient vector $\bar{\beta}$ across cross-validation folds, select the top-k SAE coordinates by $|\bar{\beta}|$, and re-fit the same cross-validated logistic-regression probe using only those coordinates. The main reported values use

$$k \in \{1, 5, 10, 25, 50, 100\}.$$

The $k = 1$ setting is the monosemanticity test: high ROC-AUC with one coordinate means that a single SAE feature carries most of the class-separating signal.

Layer-wise decodability. Table 4 shows that all three concepts are linearly decodable early in the network. Raw-residual probes cross 0.99 ROC-AUC between layers 4 and 8, and are essentially saturated from layer 8 onward. SAE-latent probes closely track raw-residual probes from layer 8, showing that the sparse code preserves the relevant speech-style information while mapping it into dictionary coordinates.

Layer-wise summary. The probing results complement the steering experiments. Probing asks whether a concept is linearly recoverable, and whether it is concentrated in a single SAE coordinate. Figures 7 and 8 summarize the probing results across layers. The raw-residual probes test concept decodability, while the top-1 SAE probes test whether a single dictionary atom carries the concept.

H Prompts

The auto-interp labeling prompt and the detection-style scorer prompt are reproduced verbatim below.

H.1 Auto-interp Labeling Prompt

```
You are analyzing internal SAE features
in a text-to-speech model.

The feature can activate on text-prefix
tokens, speech tokens, or both. Use
all evidence below. If audio clips are
present, the relevant moment is near the
middle of the 1-second clip. If text
evidence is present, the active token
is marked in each context. Activation
values are normalized to the feature's
peak.

Activating       text-token       evidence:
{text_evidence}

Activating       audio       evidence:
{audio_evidence}

Contrast  audio  clips  are  unrelated
features.

In one concise sentence, describe the
property consistently associated with
the activating evidence. Be specific.
For text features, describe the lexical,
punctuation, language, prompt-style, or
transcript property. For audio features,
describe the acoustic, phonetic, or
prosodic property. For mixed features,
describe the cross-modal relation if one
is visible; otherwise say which side
dominates. Do not mention the model or
feature.
```

H.2 Detection-Style Scorer Prompt

```
Evaluate whether each of {n} evidence
items exhibits this SAE feature:

Feature: "{label}"

Each item may be a text-token context,
an audio clip, or both. In text contexts,
the active token is wrapped in [[...]].
In audio clips, the relevant moment is
near the middle of the 1-second clip.

Score each item 0-10: 0-2 : no trace;
3-4 : faint hint; 5-6 : present but not
prominent; 7-8 : clearly present; 9-10
: unambiguously prominent. Use the full
range. Do NOT cluster in 2-5.

OUTPUT FORMAT — your very first line must
be the SCORES line, nothing before it:
SCORES: [s1, s2, . . . , sN]. Exactly {n}
integers in item order. After the SCORES
line you may add a brief phrase per item
explaining your score.
```

Concept / representation	L0	L4	L8	L12	L16	L20	L23
Laughter, raw residual	0.885	0.980	1.000	1.000	1.000	1.000	1.000
Laughter, SAE latent	0.866	0.948	0.998	1.000	1.000	1.000	0.999
Emotion, raw residual mean	0.966	0.998	1.000	1.000	1.000	1.000	1.000
Accent, raw residual mean	0.896	0.986	0.998	1.000	1.000	1.000	1.000

Table 4: Layer-wise concept decodability. Values are mean ROC-AUC over 5 folds. Emotion is averaged over Happy, Sad, Angry, and Surprise probes; accent is averaged over eleven VCTK accent probes.

Concept	L0	L4	L8	L12	L16	L20	L23
Laughter	0.508	0.805	0.909	0.924	0.929	0.695	0.831
Emotion mean	0.507	0.886	0.763	0.927	0.928	0.887	0.856
Accent mean	0.510	0.762	0.925	0.923	0.835	0.789	0.836

Table 5: Top-1 SAE feature ROC-AUC. This table reports the monosemanticity test: classification using only the single SAE coordinate with the largest mean absolute probe coefficient. Emotion and accent are averaged across their class-specific probes.

Figure 7: Raw-residual probe ROC-AUC as a function of layer for laughter, emotion, and accent. Emotion and accent are shown as mean with min–max bands across their class-specific probes. All three concepts exceed 0.99 ROC-AUC by $L = 8$.

Figure 8: Top-1 SAE feature ROC-AUC as a function of layer. This monosemanticity test asks whether a single SAE coordinate is sufficient to separate each concept from neutral speech. Laughter and emotion peak around $L = 12$–16, while accent is most localized around $L = 8$–12.