Distributionally Adaptive Meta Reinforcement Learning

Abstract

Meta-reinforcement learning algorithms provide a data-driven way to acquire poli-
cies that quickly adapt to many tasks with varying rewards or dynamics functions.
However, learned meta-policies are often effective only on the exact task distribu-
tion on which they were trained and struggle in the presence of distribution shift
of test-time rewards or transition dynamics. In this work, we develop a frame-
work for meta-RL algorithms that are able to behave appropriately under test-time
distribution shifts in the space of tasks. Our framework centers on an adaptive
approach to distributional robustness that trains a population of meta-policies to
be robust to varying levels of distribution shift. When evaluated on a potentially
shifted test-time distribution of tasks, this allows us to choose the meta-policy with
the most appropriate level of robustness, and use it to perform fast adaptation. We
formally show how our framework allows for improved regret under distribution
shift, and empirically show its efficacy on simulated robotics problems under a
wide range of distribution shifts.

1 Introduction

The diversity and dynamism of the real world require reinforcement learning (RL) agents that
can quickly adapt and learn new behaviors when placed in novel situations. Meta reinforcement
learning provides a framework for conferring this ability to RL agents, by learning a "meta-policy"
trained to adapt as quickly as possible to tasks from a provided training distribution [40, 10, 34, 49].
Unfortunately, meta-RL agents are prone to overfitting to the distribution of tasks they are trained
on, and have been shown to behave erratically when asked to adapt to tasks beyond the training
distribution [5, 8]. As an example of this negative transfer, consider using meta-learning to teach
a robot to navigate to goals quickly (illustrated in Figure 1). The resulting meta-policy learns to
quickly adapt and walk to any target location specified in the training distribution, but explores poorly
and fails to adapt to any location not in that distribution. Overfitting is particularly problematic
for the meta-learning setting, since the scenarios where we need the ability to learn quickly are
usually exactly those where the agent experiences distribution shift. This type of meta-distribution
shift afflicts a number of real-world problems including autonomous vehicle driving [9], in-hand
manipulation [17, 1], and quadruped locomotion [25, 23, 19], where the test-time task distribution
may not be well represented during training.

In this work, we study meta-RL algorithms that learn meta-policies resilient to task distribution shift
at test time. One approach to enable this resiliency is to leverage the framework of distributional
robustness [38], training meta-policies that prepare for distribution shifts by optimizing the *worst-case*
empirical risk against a set of task distributions which lie within a bounded distance from the original
training task distribution (often referred to as an *uncertainty set*)). This allows meta-policies to
deal with potential test-time task distribution shift, bounding their worst-case test-time regret for

distributional shifts within the chosen uncertainty set. However, choosing an appropriate uncertainty set can be quite challenging without further information about the test environment, significantly impacting the test-time performance of algorithms under distribution shift. Large uncertainty sets allow resiliency to a wider range of distribution shifts, but the resulting meta-policy adapts very slowly at test time; smaller uncertainty sets enable faster test-time adaptation, but leave the meta-policy brittle to task distribution shifts. Can we get the best of both worlds?

Our key insight is that we can prepare for a variety of potential test-time distribution shifts by constructing and training against different uncertainty sets at training time. By preparing for adaptation against each of these uncertainty sets, an agent is able to adapt to a variety of potential test-time distribution shifts by adaptively choosing the most appropriate level of distributional robustness for the test distribution at hand. We introduce a conceptual framework called distributionally adaptive meta reinforcement learning formalizing this idea. At train time, the agent learns robust meta-policies with widening uncertainty sets, preemptively accounting for different levels of test-time distribution shift that may be encountered (Figure 2). At test time, the agent infers the level of distribution shift it is faced with, and then uses the corresponding meta-policy to adapt to the new task (Figure 3). In doing so, the agent is able to adaptively choose the best level of robustness for the test-time task distribution, preserving the fast adapta-

Figure 1: **Failure of Typical Meta-RL.** On meta-training tasks, π_{meta} explores effectively and quickly learns the optimal behavior (top row). When test tasks come from a slightly larger task distribution, exploration fails catastrophically, resulting in poor adaptation behavior (bottom row).

tion benefits of meta RL, while also ensuring good asymptotic performance under distribution shift. We instantiate a practical algorithm in this framework (DiAMetR), using learned generative models to imagine new task distributions close to the provided training tasks that can be used to train robust meta-policies.

The contribution of this paper is to propose a framework for making meta-reinforcement learning resilient to a variety of task distribution shifts, and DiAMetR, a practical algorithm instantiating the framework. DiAMetR trains a population of meta-policies to be robust to different degrees of distribution shifts and then adaptively chooses a meta-policy to deploy based on the inferred test-time distribution shift. Our experiments verify the utility of adaptive distributional robustness under test-time task distribution shift in a number of simulated robotics domains.

2   Related Work

Meta-reinforcement learning algorithms aim to leverage a distribution of training tasks to "learn a reinforcement learning algorithm", that is able to learn as quickly on new tasks drawn from the same distribution. A variety of algorithms have been proposed for meta-RL, including memory-based [7, 26], gradient-based [10, 36, 13] and latent-variable based [34, 49, 48, 11] schemes. These algorithms show the ability to generalize to new tasks drawn from the same distribution, and have been applied to problems ranging from robotics [28, 48, 19] to computer science education [44]. This line of work has been extended to operate in scenarios without requiring any pre-specified task distribution [12, 16], in offline settings [6, 29, 27] or in hard (meta-)exploration settings [50, 47], making them more broadly applicable to a wider class of problems. However, most meta-RL algorithms assume source and target tasks are drawn from the same distribution, an assumption rarely met in practice. Our work shows how the machinery of meta-RL can be made compatible with distribution shift at test time, using ideas from distributional robustness. Some recent work shows that model based meta-reinforcement learning can be made to be robust to a particular level distribution shift [24, 21] by learning a shared dynamics model against adversarially chosen task distributions. We show that we can build model-free meta-reinforcement learning algorithms, which are not just robust to a particular level of distribution shift, but can adapt to various levels of shift.

Distributional robustness methods have been studied in the context of building supervised learning systems that are robust to the test distribution being different than the training one. The key idea is to train a model to not just minimize empirical risk, but instead learn a model that has the lowest worst-case empirical risk among an "uncertainty-set" of distributions that are boundedly close to the empirical training distribution [38, 22, 2, 15]. If the uncertainty set and optimization are

chosen carefully, these methods have been shown to obtain models that are robust to small amounts of distribution shift at test time [38, 22, 2, 15], finding applications in problems like federated learning [15] and image classification [22]. This has been extended to the min-max robustness setting for specific algorithms like model-agnostic meta-learning [3], but are critically dependent on correct specification of the appropriate uncertainty set and applicable primarily in supervised learning settings. Alternatively, several RL techniques aim to directly tackle the robustness problem, aiming to learn policies robust to adversarial perturbations [42, 46, 33, 32]. [45] conditions the policy on uncertainty sets to make it robust to different perturbation sets. While these methods are able to learn conservative, robust policies, they are unable to adapt to new tasks as DiAMetR does in the meta-reinforcement learning setting. In our work, rather than choosing a single uncertainty set, we learn many meta-policies for widening uncertainty sets, thereby accounting for different levels of test-time distribution shift.

3   Preliminaries

Meta-Reinforcement Learning aims to learn a fast reinforcement learning algorithm or a "meta-policy" that can quickly maximize performance on tasks $\mathcal{T}$ from some distribution $p(\mathcal{T})$. Formally, each task $\mathcal{T}$ is a Markov decision process (MDP) $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma, \mu_0)$; the goal is to exploit regularities in the structure of rewards and environment dynamics across tasks in $p(\mathcal{T})$ to acquire effective exploration and adaptation mechanisms that enable learning on new tasks much faster than learning the task naively from scratch. A meta-policy (or fast learning algorithm) π_{meta} maps a history of environment experience $h \in (\mathcal{S} \times \mathcal{A} \times \mathcal{R})^*$ in a new task to an action a, and is trained to acquire optimal behaviors on tasks from $p(\mathcal{T})$ within k episodes:

$$\min_{\pi_{\text{meta}}} \mathbb{E}_{\mathcal{T} \sim p(\mathcal{T})} \left[\text{Regret}(\pi_{\text{meta}}, \mathcal{T}) \right],$$

$$\text{Regret}(\pi_{\text{meta}}, \mathcal{T}) = J(\pi_{\mathcal{T}}^*) - \mathbb{E}_{a_t^{(i)} \sim \pi_{\text{meta}}(\cdot | h_t^{(i)}), \mathcal{T}} \left[\frac{1}{k} \sum_{i=1}^{k} \sum_{t=1}^{T} r_t^{(i)} \right], \quad J(\pi_{\mathcal{T}}^*) = \max_{\pi} \mathbb{E}_{\pi, \mathcal{T}} [\sum_t r_t]$$

$$\text{where } h_t^{(i)} = (s_{1:t}^{(i)}, r_{1:t}^{(i)}, a_{1:t-1}^{(i)}) \cup (s_{1:T}^{(j)}, r_{1:T}^{(j)}, a_{1:T}^{(j)})_{j=1}^{i-1}. \tag{1}$$

Intuitively, the meta-policy has two components: an exploration mechanism that ensures that appropriate reward signal is found for all tasks in the training distribution, and an adaptation mechanism that uses the collected exploratory data to generate optimal actions for the current task. In practice, the meta-policy may be represented explicitly as an exploration policy conjoined with a policy update[10, 34], or implicitly as a black-box RNN [7, 49]. We use the terminology "meta-policies" interchangeably with that of "fast-adaptation" algorithms, since our practical implementation builds on [31] (which represents the adaptation mechanism using a black-box RNN). Our work focuses on the setting where there is potential drift between $p_{\text{train}}(\mathcal{T})$, the task distribution we have access to during training, and $p_{\text{test}}(\mathcal{T})$, the task distribution of interest during evaluation.

Distributional robustness [38] learns models that do not minimize empirical risk against the training distribution, but instead prepare for distribution shift by optimizing the *worst-case* empirical risk against a set of data distributions close to the training distribution (called an *uncertainty set*):

$$\min_{\theta} \max_{\phi} \mathbb{E}_{x \sim q_\phi(x)} [l(x; \theta)] \quad \text{s.t.} \quad D(p_{\text{train}}(x) || q_\phi(x)) \leq \epsilon \tag{2}$$

This optimization finds the model parameters θ that minimizes worst case risk l over distributions $q_\phi(x)$ in an ϵ-ball (measured by an f-divergence) from the training distribution $p_{\text{train}}(x)$.

4   Distributionally Adaptive Meta-Reinforcement Learning

In this section, we develop a framework for learning meta-policies, that given access to a training distribution of tasks $p_{\text{train}}(\mathcal{T})$, is still able to adapt to tasks from a test-time distribution $p_{\text{test}}(\mathcal{T})$ that is similar but not identical to the training distribution. We introduce a framework for distributionally adaptive meta-RL below and instantiate it as a practical method in Section 5.

4.1   Known Level of Test-Time Distribution Shift

We begin by studying a simplified problem where we can exactly quantify the degree to which the test distribution deviates from the training distribution. Suppose we know that p_{test} satisfies

Figure 2: DiAMetR first learns a meta-policy $\pi_{\text{meta}}^{\epsilon_1}$ and reward distribution $r_\omega(s, a, z)$ on train task distribution. Then, it uses the reward distribution to imagine different shifted test task distributions (orange dots) on which it learns different meta-policies $\{\pi_{\text{meta}}^{\epsilon_i}\}_{i=2}^M$, each corresponding to a different level of robustness .

$D(p_{\text{test}}(\mathcal{T})\|p_{\text{train}}(\mathcal{T})) < \epsilon$ for some $\epsilon > 0$, where $D(\cdot\|\cdot)$ is a probability divergence on the set of task distributions (e.g. an f-divergence [35] or a Wasserstein distance [41]). A natural learning objective to learn a meta-policy under this assumption is to minimize the *worst-case* test-time regret across any test task distribution $q(\mathcal{T})$ that is within some ϵ divergence of the train distribution:

$$\min_{\pi_{\text{meta}}} \mathcal{R}(\pi_{\text{meta}}, p_{\text{train}}(\mathcal{T}), \epsilon),$$

$$\mathcal{R}(\pi_{\text{meta}}, p_{\text{train}}(\mathcal{T}), \epsilon) = \max_{q(\mathcal{T})} \mathbb{E}_{\mathcal{T} \sim q(\mathcal{T})} \left[\text{Regret}(\pi_{\text{meta}}, \mathcal{T})\right] \quad \text{s.t.} \ D(p_{\text{train}}(\mathcal{T})\|q(\mathcal{T})) \leq \epsilon \quad (3)$$

Solving this optimization problem results in a meta-policy that has been trained to adapt to tasks from a *wider* task distribution than the original training distribution. It is worthwhile distinguishing this robust meta-objective, which incentivizes a *robust adaptation mechanism* to a wider set of tasks, from robust objectives in standard RL, which produce base policies robust to a wider set of dynamics conditions. The objective in Eq 3 incentivizes an agent to explore and adapt more broadly, not act more conservatively as standard robust RL methods [33] would encourage. Naturally, the quality of the robust meta-policy depends on the size of the uncertainty set. If ϵ is large, or the geometry of the divergence poorly reflect natural task variations, then the robust policy will have to adapt to an overly large set of tasks, potentially degrading the speed of adaptation.

4.2 Handling Arbitrary Levels of Distribution Shift

In practice, it is not known how the test distribution p_{test} deviates from the training distribution, and consequently it is challenging to determine what ϵ to use in the meta-robustness objective. We propose to overcome this via an adaptive strategy: to train meta-policies for *varying* degrees of distribution shift, and at test-time, inferring which distribution shift is most appropriate through experience.

We train a population of meta-policies $\{\pi_{\text{meta}}^{(i)}\}_{i=1}^M$, each solving the distributionally robust meta-RL objective (eq 3) for a different level of robustness ϵ_i:

$$\left\{\pi_{\text{meta}}^{\epsilon_i} := \arg\min_{\pi_{\text{meta}}} \mathcal{R}(\pi_{\text{meta}}, p_{\text{train}}(\mathcal{T}), \epsilon_i)\right\}_{i=1}^M \quad \text{where } \epsilon_M > \epsilon_{M-1} > \ldots > \epsilon_1 = 0 \quad (4)$$

In choosing a spectrum of ϵ_i, we learn a set of meta-policies that have been trained on increasingly large set of tasks: at one end ($i = 1$), the meta-policy is trained only on the original training distribution, and at the other ($i = M$), the meta-policy trained to adapt to any possible task within the parametric family of tasks. These policies span a tradeoff between being robust to a wider set of task distributions with larger ϵ (allowing for larger distribution shifts), and being able to adapt quickly to any given task with smaller ϵ (allowing for better per-task regret minimization).

With a set of meta-policies in hand, we must now decide how to leverage test-time experience to discover the right one to use for the actual test distribution p_{test}. We recognize that the problem of policy selection can be treated as a stochastic multi-armed bandit problem (precise formulation in Appendix A), where pulling arm i corresponds to running the meta-policy $\pi_{\text{meta}}^{\epsilon_i}$ for an entire meta-episode (k task episodes). If a zero-regret bandit algorithm (eg: Thompson's sampling [43]) is used , then after a certain number of test-time meta episodes, we can guarantee that the meta-policy selection mechanism will converge to the meta-policy that best balances the tradeoff between adapting quickly while still being able to adapt to all the tasks from $p_{\text{test}}(\mathcal{T})$.

To summarize our framework for distributionally adaptive meta-RL, we train a population of meta-policies at varying levels of robustness on a distributionally robust objective that forces the learned

Meta-policy selection during meta-test **Test time Meta-policy adaptation**

Thompson Sampling

$\pi_{\text{meta}}^{\epsilon}$

Figure 3: DiAMetR chooses appropriate meta-policy based on inferred distribution shift with Thompson's sampling and then quickly adapts the selected meta-policy to individual tasks during meta-test.

adaptation mechanism to also be robust to tasks not in the training task distribution. At test-time, we use a bandit algorithm to select the meta-policy whose adaptation mechanism has the best tradeoff between robustness and speed of adaptation specifically on the test task distribution. Combining distributional robustness with test-time adaptation allows the adaptation mechanism to work even if distribution shift is present, while obviating the decreased performance that usually accompanies overly conservative, distributionally robust solutions.

4.3 Analysis

To provide some intuition on the properties of this algorithm, we formally analyze adaptive distributional robustness in a simplified meta RL problem involving tasks $\mathcal{T}_g$ corresponding to reaching some unknown goal g in a deterministic MDP $\mathcal{M}$, exactly at the final timestep of an episode. We assume that all goals are reachable, and use the family of meta-policies that use a stochastic exploratory policy π until the goal is discovered and return to the discovered goal in all future episodes. The performance of a meta-policy on a task $\mathcal{T}_g$ under this model can be expressed in terms of the state distribution of the exploratory policy: $\text{Regret}(\pi_{\text{meta}}, \mathcal{T}_g) = \frac{1}{d_\pi^T(g)}$. This particular framework has been studied in [12, 20], and is a simple, interpretable framework for analysis.

We seek to understand performance under distribution shift when the original training task distribution is relatively concentrated on a subset of possible tasks. We choose the training distribution $p_{\text{train}}(\mathcal{T}_g) = (1 - \beta)\text{Uniform}(\mathcal{S}_0) + \beta\text{Uniform}(\mathcal{S}\backslash\mathcal{S}_0)$, so that p_{train} is concentrated on tasks involving a subset of the state space $\mathcal{S}_0 \subset \mathcal{S}$, with β a parameter dictating the level of concentration, and consider test distributions that perturb under the TV metric. Our main result compares the performance of a meta-policy trained to an ϵ_2-level of robustness when the true test distribution deviates by ϵ_1.

Proposition 4.1. *Let $\overline{\epsilon_i} = \min\{\epsilon_i + \beta, 1 - \frac{|\mathcal{S}_0|}{|\mathcal{S}|}\}$. There exists $q(\mathcal{T})$ satisfying $D_{TV}(p_{train}, q) \leq \epsilon_1$ where an ϵ_2-robust meta policy incurs excess regret over the optimal ϵ_1-robust meta-policy:*

$$\mathbb{E}_{q(\mathcal{T})}[\text{Regret}(\pi_{meta}^{\epsilon_2}, \mathcal{T}) - \text{Regret}(\pi_{meta}^{\epsilon_1}, \mathcal{T})] \geq \left(c(\epsilon_1, \epsilon_2) + \frac{1}{c(\epsilon_1, \epsilon_2)} - 2 \right) \sqrt{\overline{\epsilon_1}(1 - \overline{\epsilon_1})|\mathcal{S}_0|(|\mathcal{S}| - \mathcal{S}_0|)}$$

(5)

The scale of regret depends on $c(\epsilon_1, \epsilon_2) = \sqrt{\frac{\overline{\epsilon_2}^{-1} - 1}{\overline{\epsilon_1}^{-1} - 1}}$, a measure of the mismatch between ϵ_1 and ϵ_2.

We first compare robust and non-robust solutions by analyzing the bound when $\epsilon_2 = 0$. In the regime of $\beta \ll 1$, excess regret scales as $\mathcal{O}(\epsilon_1\sqrt{\frac{1}{\beta}})$, meaning that the robust solution is most necessary when the training distribution is highly concentrated in a subset of the task space. At one extreme, if the training distribution contains no examples of tasks outside $\mathcal{S}_0$ ($\beta = 0$), the non-robust solution incurs *infinite excess regret*; at the other extreme, if the training distribution is uniform on the set of all possible tasks ($\beta = 1 - \frac{|\mathcal{S}_0|}{|\mathcal{S}|}$), *robustness provides no benefit*.

We next quantify the effect of mis-specifying the level of robustness in the meta-robustness objective, and what benefits *adaptive* distributional robustness can confer. For small β and fixed ϵ_1, the excess regret of an ϵ_2-robust policy scales as $\mathcal{O}(\sqrt{\max\{\frac{\epsilon_2}{\epsilon_1}, \frac{\epsilon_1}{\epsilon_2}\}})$, meaning that excess regret gets incurred if the meta-policy is trained either to be too robust ($\epsilon_2 \gg \epsilon_1$) or not robust enough $\epsilon_1 \gg \epsilon_2$. Compared to a fixed robustness level, our strategy of training meta-policies for a sequence of robustness levels

Algorithm 1 DiAMetR: Meta-training phase

1: Given: $p_{\text{train}}(\mathcal{T})$, Return: Π
2: $\pi_{\text{meta},\theta}^{\epsilon_1}, \mathcal{D}_{\text{Replay-Buffer}} \leftarrow$ Solve equation 1 with off-policy RL[2]
3: Reward distribution r_ω, prior $p_{\text{train}}(z) \leftarrow$ Solve eq 6 using $\mathcal{D}_{\text{Replay-Buffer}}$
4: **for** ϵ in $\{\epsilon_2, \ldots, \epsilon_M\}$ **do**
5: Initialize $q_\phi(z)$, $\pi_{\text{meta},\theta}^{\epsilon}$ and $\lambda \geq 0$.
6: **for** iteration $n = 1, 2, \ldots$ **do**
7:   **Meta-policy:** Update $\pi_{\text{meta},\theta}^{\epsilon}$ using off-policy RL[2] [31]

$$\theta := \theta + \alpha \nabla_\theta \mathbb{E}_{z \sim q_\phi(z)} (\mathbb{E}_{\pi_{\text{meta},\theta}^{\epsilon}, \mathcal{P}}(\frac{1}{k} \sum_{i=1}^{k} \sum_{t=1}^{T} r_\omega(s_t^{(i)}, a_t^{(i)}, z)))$$

8:   **Adversarial task distribution:** Update q_ϕ using Reinforce [39]

$$\phi := \phi - \alpha \nabla_\phi (\mathbb{E}_{z \sim q_\phi(z)} [\mathbb{E}_{\pi_{\text{meta},\theta}^{\epsilon}, \mathcal{P}} [\frac{1}{k} \sum_{i=1}^{k} \sum_{t=1}^{T} r_\omega(s_t^{(i)}, a_t^{(i)}, z)]] + \lambda D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z))$$

9:   **Lagrange constraint multiplier:** Update λ to enforce $D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z)) < \epsilon$,

$$\lambda :=_{\lambda \geq 0} \lambda + \alpha(D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z)) - \epsilon)$$

10: **end for**
11: **end for**

$\{\epsilon_i\}_{i=1}^{M}$ ensures that this misspecification constant is at most the relative spacing between robustness levels: $\max_i \frac{\epsilon_i}{\epsilon_{i-1}}$. This enables the distributionally adaptive approach to *control* the amount of excess regret by making the sequence more fine-grained, while a fixed choice of robustness incurs larger regret (as we verify empirically in our experiments as well).

5 DiAMetR: A Practical Algorithm for Meta-Distribution Shift

In order to instantiate our distributionally adaptive framework into a practical algorithm, we must address how task distributions should be parameterized and optimized over, and also how the robust meta-RL problem can be solved with stochastic gradient methods. For simplicity, in the remainder of the paper, we focus on the setting where tasks share transition dynamics, but have different reward functions. We first introduce the individual components of task parameterization and robust optimization, and describe the overall algorithm in Algorithm 1 and 2.

Parameterizing Task Distributions: Since we assume that variations in tasks correspond to changes in the reward function, the problem of representing a task distribution reduces to learning distributions over reward functions. We propose to learn a probabilistic model of the task reward functions seen in the training task distribution, and use the learned latent representation as a space on which to parameterize uncertainty sets over new task distributions. Specifically, we jointly train a reward encoder $q_\psi(z|h)$ that encodes reward samples from an environment history into the latent space, and a decoder $r_\omega(s, a, z)$ mapping a latent vector z to a reward function using a dataset of trajectories collected from the training tasks. This generative model over reward functions can be trained as a standard latent variable model by maximizing a standard evidence lower bound (ELBO), trading off reward prediction and matching a prior $p_{\text{train}}(z)$ (chosen to be the unit gaussian).

$$\min_{\omega,\psi} \mathbb{E}_{h \sim \mathcal{D}} \left[\mathbb{E}_{z \sim q_\psi(z|h)} \left[\sum_{t=1}^{T} (r_\omega(s_t, a_t, z) - r_t)^2 \right] + D_{\text{KL}}(q_\psi(z|h) \| \mathcal{N}(0, I)) \right] \quad (6)$$

Having learned a latent space, we can parameterize new task distributions $q(\mathcal{T})$ as distributions $q_\phi(z)$ (the original training distribution corresponds to $p_{\text{train}}(z) = \mathcal{N}(0, I)$, and measure the divergence between task distributions as well using the KL divergence in this latent space $D(p_{\text{train}}(z) \| q_\phi(z))$.

Learning Robust Meta-Policies: Given this task parameterization, the next question becomes how to actually perform the robust optimization laid out in Eq:3. The distributional meta-robustness objective can be modelled as an adversarial game between a meta-policy $\pi_{\text{meta}}^{\epsilon}$ and a task proposal distribution $q(\mathcal{T})$. As described above, this task proposal distribution is parameterized as a distribution over latent

Environment	Task reward	r_{train}	$\{r_{\text{test}}^i\}_{i=1}^K$	Θ
`*-navigation`	$1[\|\text{agent} - \text{target}\|_2 \leq \delta]$	0.50	$\{0.55, 0.60, 0.65, 0.70\}$	2π
`Fetch reach`	$1[\|\text{gripper} - \text{target}\|_2 \leq \delta]$	0.10	$\{0.12, 0.14, 0.16, 0.18, 0.20\}$	2π
`Block push`	$1[\|\text{block} - \text{target}\|_2 \leq \delta]$	0.50	$\{0.60, 0.70, 0.80, 0.90, 1.0\}$	$\pi/2$

Table 1: Parameters for train task distribution $p_{\text{train}}(s_t) = \{(\Delta\cos\theta, \Delta\sin\theta) \mid \Delta \sim \mathcal{U}(0, r_{\text{train}}), \theta \sim \mathcal{U}(0, \Theta)\}$ and test task distributions $\{p_{\text{test}}^i(s_t) = \{(\Delta\cos\theta, \Delta\sin\theta) \mid \Delta \sim \mathcal{U}(r_{\text{test}}^{i-1}, r_{\text{test}}^i), \theta \sim \mathcal{U}(0, \Theta)\}\}_{i=1}^K$ (where $r_{\text{test}}^0 = r_{\text{train}}$) for different environments

space $q_\phi(z)$, while $\pi_{\text{meta}}^\epsilon$ is parameterized a typical recurrent neural network policy as in [31]. We parameterize $\{\pi_{\text{meta}}^{\epsilon_i}\}_{i=1}^M$ as a discrete set of meta-policies, with one for each chosen value of ϵ.

This leads to a simple alternating optimization scheme (see Algorithm 1), where the meta-policy is trained using a standard meta-RL algorithm (we use off-policy RL² [31] as a base learner), and the task proposal distribution with an constrained optimization method (we use dual gradient descent [30]). Each iteration n, three updates are performed: 1) the meta-policy π_{meta} updated to improve performance on the current task distribution, 2) the task distribution $q(z)$ updated to increase weight on tasks where the current meta-policy adapts poorly and decreases weight on tasks that the current meta-policy can learn, while staying close to the original training distribution, and 3) a penalty coefficient λ is updated to ensure that $q(z)$ satsifies the divergence constraint.

Test-time meta-policy selection: Since test-time meta-policy selection can be framed as a multi-armed bandit problem, we use a generic Thompson's sampling [43] algorithm (see Algorithm 2). Each meta-episode n, we sample a meta-policy $\pi_{\text{meta}}^\epsilon$ with probability proportional to its estimated average episodic reward, run the sampled meta-policy $\pi_{\text{meta}}^\epsilon$ for an meta-episode (k environment episodes) and then update the estimate of the average episodic reward. Since Thompson's sampling is a zero-regret bandit algorithm, it will converge to the meta-policy that achieves the highest average episodic reward and lowest regret on the test task distribution.

Algorithm 2 DiAMetR: Meta-test phase

1: Given: $p_{\text{test}}(\mathcal{T})$, $\Pi = \{\pi_{\text{meta},\theta}^{\epsilon_i}\}_{i=1}^M$
2: Initialize `TS = Thompson-Sampler()`
3: **for** meta-episode $n = 1, 2, ...$ **do**
4:     Choose meta-policy $i = $ `TS.sample()`
5:     Run $\pi_{\text{meta},\theta}^{\epsilon_i}$ for meta-episode
6:     `TS.update(`
        `arm=i,`
        `reward=meta-episode return)`
7: **end for**

---

6 Experimental Evaluation

| (a) Wheeled navigation | (b) Ant navigation | (c) Fetch reach | (d) Block push |

Figure 4: The agent needs to either navigate, move its gripper or push the block to an unobserved target location, indicated by green sphere, by exploring its environment and experiencing reward.

We aim to comprehensively evaluate DiAMetR and answer the following questions: **(1)** Do meta-policies learned via DiAMetR allow for quick adaptation under different distribution shifts in the test-time task distribution? **(2)** Does learning for multiple levels of robustness actually help the algorithm adapt more effectively than a particular chosen uncertainty level? **(3)** Does proposing uncertainty sets via generative modeling provide useful distributions of tasks for robustness?

Setup. We train DiAMetR on four continuous control environments: `Wheeled navigation` [13] (Wheeled driving a differential drive robot), `Ant navigation` (Ant controlling a four legged robotic quadruped), `Fetch reach` and `Block push` [13] (Figures 4a to 4d) (see Appendix H for more details). Each environment has a train task distribution $\mathcal{T}_i \sim p_{\text{train}}(\mathcal{T})$ such that each task $\mathcal{T}_i$ parameterizes a reward function $r_i(s, a) := r(s, a, \mathcal{T}_i)$. $\mathcal{T}_i$ itself remains unobserved, the agent

270 simply has access to reward values and executing actions in the environment. The meta-policies
271 are evaluated on train task distribution $p_{\text{train}}(\mathcal{T})$ and on different distributionally shifted test task
272 distribution $\{p^i_{\text{test}}(\mathcal{T})\}^K_{i=1}$. We use 4 random seeds for all our experiments and include the standard
273 error bars in our plots. In all of these problems, the distribution of train and test tasks is determined
274 by the distribution of the underlying target locations s_t, which determines the reward function (exact
275 distributions in Table 1). Since these environments have sparse rewards, DiAMetR uses a structured
276 VAE to model reward distributions (see Appendix C for more details).

6.1 Adaptation to Varying Levels of Distribution Shift

278 During meta test, given a test task distribution $p_{\text{test}}(\mathcal{T})$, DiAMetR uses Thompson sampling to select
279 the appropriate meta-policy $\pi^\epsilon_{\text{meta},\theta}$ within $N = 250$ meta episodes. $\pi^\epsilon_{\text{meta},\theta}$ can then solve any task
280 $\mathcal{T} \sim p_{\text{test}}(\mathcal{T})$ within 1 meta episode ($k = 2$ environment episode). Since DiAMetR adaptively
281 chooses a meta-policy during test time, we compare it to RL^2 with test time finetuning. Figure 5
282 shows that RL^2's performance more or less remains the same after test time finetuning showing
283 that 10 iteration (with 25 meta-episodes per iteration) isn't enough for RL^2 to learn an meta-policy
284 for a new task distribution. For comparison, RL^2 takes 1500 iterations (with 25 meta-episodes per
285 iteration) during training to learn a meta-policy for train task distribution.

Figure 5: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on different environments. We run the adaptation procedure for 10 iterations collecting 25 meta-episodes per iteration. The test target distance distribution for {Wheeled,Ant}-navigation is $\mathcal{U}(0.65, 0.70)$, for Fetch reach is $\mathcal{U}(0.65, 0.70)$ and for Block push is $\mathcal{U}(0.9, 1.0)$. We provide test time adaptation comparisons on other test target distance distributions in Appendix G.

286 To test DiAMetR's ability to adapt to varying levels of distribution shift, we evaluate it on the
287 above mentioned test task distributions. We compare DiAMetR with meta RL algorithms such as
288 (off-policy) RL^2 [31], VariBAD [49] and HyperX [50]. Figure 6 shows that DiAMetR outperforms
289 RL^2, VariBAD and HyperX on test task distributions. Furthermore, the performance gap between
290 DiAMetR and other baselines increase as distribution shift between test task distribution and train task
291 distribution increases. Naturally, the performance of DiAMetR also deteriorates as the distribution
292 shift is increased, but as shown in Fig 6, it does so much more slowly than other algorithms. We
293 also evaluate DiAMetR on train task distribution to see if it incurs any performance loss. Figure 6
294 shows that DiAMetR either matches or outperforms RL^2, VariBAD, and HyperX on the train task
295 distribution. We refer readers to Appendix D for results on point-navigation environment and
296 Appendix E for ablation studies and further experimental evaluations.

Figure 6: We evaluate DiAMetR and meta RL algorithms (RL^2, VariBAD and HyperX) on training task distribution and different test task distributions. DiAMetR outperforms RL^2, VariBAD and HyperX on train distributions and different test distributions. The first point r_{train} on the horizontal axis indicates the training target distance Δ distribution $\mathcal{U}(0, r_{\text{train}})$ and the subsequent points r^i_{test} indicate the shifted test target Δ distribution $\mathcal{U}(r^{i-1}_{\text{test}}, r^i_{\text{test}})$.

6.2 Analysis of Tasks Proposed by Latent Conditional Uncertainty Sets

We visualize the imagined test reward distribution for various distribution shifts. Specifically, we create a heatmap of imagined test reward functions. Figure 7 visualizes the imagined test reward distribution in `Ant-navigation` environment in increasing order of distribution shifts with respect to train reward distribution (with distribution shift parameter ϵ increasing from left to right). The train distribution of rewards has uniformly distributed target locations within the red circle. As clearly seen in Figure 7, as we increase the distribution shifts, the learned reward distribution model imagines more target locations outside the red circle.

(a) $\epsilon = 0.1$ (b) $\epsilon = 0.2$ (c) $\epsilon = 0.4$ (d) $\epsilon = 0.8$

Figure 7: Imagined test reward distributions in `Ant-navigation` environment in increasing order of distribution shifts. Train reward distribution is uniform within the red circle.

6.3 Analysis of Importance of Multiple Uncertainty Sets

DiAMetR meta-learns a family of adaptation policies, each conditioned on different uncertainty set. As discussed in section 4, selecting a policy conditioned on a large uncertainty set would lead to overly conservative behavior. Furthermore, selecting a policy conditioned on a small uncertainty set would result in failure if the test time distribution shift is high. Therefore, we need to adaptively select an uncertainty set during test time. To validate this phenomenon empirically, we performed an ablation study in Figure 8. As clearly visible, adaptively choosing an uncertainty set during test time allows for better test time distribution adaptation when compared to selecting an uncertainty set beforehand or selecting a large uncertainty set. These results suggest that a combination of training robust meta-learners and constructing various uncertainty sets allows for effective test-time adaptation under distribution shift. DiAMetR is able to avoid both overly conservative behavior and under-exploration at test-time.

Figure 8: Adaptively choosing an uncertainty set for DiAMetR policy (Adapt) during test time allows it to better adapt to test time distribution shift than choosing an uncertainty set beforehand (Mid). Choosing a large uncertainty set for DiAMetR policy (Conservative) leads to a conservative behavior and hurts its performance when test time distribution shift is low. The first point r_{train} on the horizontal axis indicates the training target distance Δ distribution $\mathcal{U}(0, r_{\text{train}})$ and the subsequent points r_{test}^i indicate the shifted test target distance Δ distribution $\mathcal{U}(r_{\text{test}}^{i-1}, r_{\text{test}}^i)$.

7 Discussion

In this work, we discussed the challenge of distribution shift in meta-reinforcement learning and showed how we can build meta-reinforcement learning algorithms that are robust to varying levels of distribution shift. We show how we can build distributionally "adaptive" reinforcement learning algorithms that can adapt to varying levels of distribution shift, retaining a tradeoff between fast learning and maintaining asymptotic performance. We then show we can instantiate this algorithm practically by parameterizing uncertainty sets with a learned generative model. We empirically showed that this allows for learning meta-learners robust to changes in task distribution.

There are several avenues for future work we are keen on exploring, for instance extending adaptive distributional robustness to more complex meta RL tasks, including those with differing transition dynamics. Another interesting direction would be to develop a more formal theory providing adaptive robustness guarantees in meta-RL problems under these inherent distribution shifts.

References

[1] T. Chen, J. Xu, and P. Agrawal. A system for general in-hand object re-orientation. In A. Faust, D. Hsu, and G. Neumann, editors, *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pages 297–307. PMLR, 08–11 Nov 2022. URL https://proceedings.mlr.press/v164/chen22a.html.

[2] J. Cohen, E. Rosenfeld, and Z. Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pages 1310–1320. PMLR, 2019.

[3] L. Collins, A. Mokhtari, and S. Shakkottai. Distribution-agnostic model-agnostic meta-learning. *CoRR*, abs/2002.04766, 2020. URL https://arxiv.org/abs/2002.04766.

[4] P.-T. De Boer, D. P. Kroese, S. Mannor, and R. Y. Rubinstein. A tutorial on the cross-entropy method. *Annals of operations research*, 134(1):19–67, 2005.

[5] T. Deleu and Y. Bengio. The effects of negative adaptation in model-agnostic meta-learning. *arXiv preprint arXiv:1812.02159*, 2018.

[6] R. Dorfman, I. Shenfeld, and A. Tamar. Offline meta learning of exploration. *arXiv preprint arXiv:2008.02598*, 2020.

[7] Y. Duan, J. Schulman, X. Chen, P. L. Bartlett, I. Sutskever, and P. Abbeel. Rl2: Fast reinforcement learning via slow reinforcement learning. *arXiv preprint arXiv:1611.02779*, 2016.

[8] A. Fallah, A. Mokhtari, and A. Ozdaglar. Generalization of model-agnostic meta-learning algorithms: Recurring and unseen tasks. *Advances in Neural Information Processing Systems*, 34, 2021.

[9] A. Filos, P. Tigkas, R. McAllister, N. Rhinehart, S. Levine, and Y. Gal. Can autonomous vehicles identify, recover from, and adapt to distribution shifts? In *International Conference on Machine Learning*, pages 3145–3153. PMLR, 2020.

[10] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pages 1126–1135. PMLR, 2017.

[11] H. Fu, H. Tang, J. Hao, C. Chen, X. Feng, D. Li, and W. Liu. Towards effective context for meta-reinforcement learning: an approach based on contrastive learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 7457–7465, 2021.

[12] A. Gupta, B. Eysenbach, C. Finn, and S. Levine. Unsupervised meta-learning for reinforcement learning. *arXiv preprint arXiv:1806.04640*, 2018.

[13] A. Gupta, R. Mendonca, Y. Liu, P. Abbeel, and S. Levine. Meta-reinforcement learning of structured exploration strategies. *Advances in neural information processing systems*, 31, 2018.

[14] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018.

[15] J. Hong, H. Wang, Z. Wang, and J. Zhou. Federated robustness propagation: Sharing adversarial robustness in federated learning. *arXiv preprint arXiv:2106.10196*, 2021.

[16] A. Jabri, K. Hsu, A. Gupta, B. Eysenbach, S. Levine, and C. Finn. Unsupervised curricula for visual meta-reinforcement learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[17] L. Ke, J. Wang, T. Bhattacharjee, B. Boots, and S. Srinivasa. Grasping with chopsticks: Combating covariate shift in model-free imitation learning for fine manipulation. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6185–6191. IEEE, 2021.

[18] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[19] A. Kumar, Z. Fu, D. Pathak, and J. Malik. Rma: Rapid motor adaptation for legged robots. *arXiv preprint arXiv:2107.04034*, 2021.

[20] L. Lee, B. Eysenbach, E. Parisotto, E. P. Xing, S. Levine, and R. Salakhutdinov. Efficient exploration via state marginal matching. *CoRR*, abs/1906.05274, 2019. URL http://arxiv.org/abs/1906.05274.

[21] Z. Lin, G. Thomas, G. Yang, and T. Ma. Model-based adversarial meta-reinforcement learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/73634c1dcbe056c1f7dcf5969da406c8-Abstract.html.

[22] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

[23] G. B. Margolis, G. Yang, K. Paigwar, T. Chen, and P. Agrawal. Rapid locomotion via reinforcement learning. *arXiv preprint arXiv:2205.02824*, 2022.

[24] R. Mendonca, X. Geng, C. Finn, and S. Levine. Meta-reinforcement learning robust to distributional shift via model identification and experience relabeling. *CoRR*, abs/2006.07178, 2020. URL https://arxiv.org/abs/2006.07178.

[25] T. Miki, J. Lee, J. Hwangbo, L. Wellhausen, V. Koltun, and M. Hutter. Learning robust perceptive locomotion for quadrupedal robots in the wild. *Science Robotics*, 7(62):eabk2822, 2022.

[26] N. Mishra, M. Rohaninejad, X. Chen, and P. Abbeel. A simple neural attentive meta-learner. *arXiv preprint arXiv:1707.03141*, 2017.

[27] E. Mitchell, R. Rafailov, X. B. Peng, S. Levine, and C. Finn. Offline meta-reinforcement learning with advantage weighting. In *International Conference on Machine Learning*, pages 7780–7791. PMLR, 2021.

[28] A. Nagabandi, I. Clavera, S. Liu, R. S. Fearing, P. Abbeel, S. Levine, and C. Finn. Learning to adapt in dynamic, real-world environments through meta-reinforcement learning. *arXiv preprint arXiv:1803.11347*, 2018.

[29] A. Nair, A. Gupta, M. Dalal, and S. Levine. Awac: Accelerating online reinforcement learning with offline datasets. *arXiv preprint arXiv:2006.09359*, 2020.

[30] Y. Nesterov. Primal-dual subgradient methods for convex problems. *Mathematical programming*, 120(1):221–259, 2009.

[31] T. Ni, B. Eysenbach, S. Levine, and R. Salakhutdinov. Recurrent model-free RL is a strong baseline for many POMDPs, 2022. URL https://openreview.net/forum?id=E0zOKxQsZhN.

[32] T. P. Oikarinen, W. Zhang, A. Megretski, L. Daniel, and T. Weng. Robust deep reinforcement learning through adversarial loss. In M. Ranzato, A. Beygelzimer, Y. N. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 26156–26167, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/dbb422937d7ff56e049d61da730b3e11-Abstract.html.

[33] L. Pinto, J. Davidson, R. Sukthankar, and A. Gupta. Robust adversarial reinforcement learning. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 2817–2826. PMLR, 2017. URL http://proceedings.mlr.press/v70/pinto17a.html.

[34] K. Rakelly, A. Zhou, C. Finn, S. Levine, and D. Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *International conference on machine learning*, pages 5331–5340. PMLR, 2019.

[35] A. Rényi. On measures of entropy and information. In *Proceedings of the Fourth Berkeley Symposium on Mathematical Statistics and Probability, Volume 1: Contributions to the Theory of Statistics*, volume 4, pages 547–562. University of California Press, 1961.

[36] J. Rothfuss, D. Lee, I. Clavera, T. Asfour, and P. Abbeel. Promp: Proximal meta-policy search. *arXiv preprint arXiv:1810.06784*, 2018.

[37] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017. URL http://dblp.uni-trier.de/db/journals/corr/corr1707.html#SchulmanWDRK17.

[38] A. Sinha, H. Namkoong, R. Volpi, and J. Duchi. Certifying some distributional robustness with principled adversarial training. *arXiv preprint arXiv:1710.10571*, 2017.

[39] R. S. Sutton, D. McAllester, S. Singh, and Y. Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in neural information processing systems*, 12, 1999.

[40] S. Thrun and L. Y. Pratt, editors. *Learning to Learn*. Springer, 1998. ISBN 978-1-4613-7527-2. doi: 10.1007/978-1-4615-5529-2. URL https://doi.org/10.1007/978-1-4615-5529-2.

[41] L. N. Vaserstein. Markov processes over denumerable products of spaces, describing large systems of automata. *Problemy Peredachi Informatsii*, 5(3):64–72, 1969.

[42] E. Vinitsky, Y. Du, K. Parvate, K. Jang, P. Abbeel, and A. M. Bayen. Robust reinforcement learning using adversarial populations. *CoRR*, abs/2008.01825, 2020. URL https://arxiv.org/abs/2008.01825.

[43] D. Wolpert and W. Macready. No free lunch theorems for optimization. *IEEE Transactions on Evolutionary Computation*, 1(1):67–82, 1997. doi: 10.1109/4235.585893.

[44] M. Wu, N. Goodman, C. Piech, and C. Finn. Prototransformer: A meta-learning approach to providing student feedback. *arXiv preprint arXiv:2107.14035*, 2021.

[45] A. Xie, S. Sodhani, C. Finn, J. Pineau, and A. Zhang. Robust policy learning over multiple uncertainty sets. *arXiv preprint arXiv:2202.07013*, 2022.

[46] H. Zhang, H. Chen, D. S. Boning, and C. Hsieh. Robust reinforcement learning on state observations with learned optimal adversary. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=sCZbhBvqQaU.

[47] J. Zhang, J. Wang, H. Hu, T. Chen, Y. Chen, C. Fan, and C. Zhang. Metacure: Meta reinforcement learning with empowerment-driven exploration. In *International Conference on Machine Learning*, pages 12600–12610. PMLR, 2021.

[48] T. Z. Zhao, A. Nagabandi, K. Rakelly, C. Finn, and S. Levine. Meld: Meta-reinforcement learning from images via latent state models. *arXiv preprint arXiv:2010.13957*, 2020.

[49] L. Zintgraf, K. Shiarlis, M. Igl, S. Schulze, Y. Gal, K. Hofmann, and S. Whiteson. Varibad: A very good method for bayes-adaptive deep rl via meta-learning. *arXiv preprint arXiv:1910.08348*, 2019.

[50] L. M. Zintgraf, L. Feng, C. Lu, M. Igl, K. Hartikainen, K. Hofmann, and S. Whiteson. Exploration in approximate hyper-state space for meta reinforcement learning. In *International Conference on Machine Learning*, pages 12991–13001. PMLR, 2021.

A Test time Meta Policy Selection

As discussed in Section 4, to adapt to test time task distribution shifts, we train a family of meta-policies $\Pi = \{\pi_{\text{meta}}^{\epsilon_i}\}$ to be robust to varying degrees of distribution shifts. We then choose the appropriate meta-policy during test-time based on the inferred task distribution shift. In this section, we frame the test-time selection of meta-policy from the family Π as a stochastic multi-arm bandit problem. Every iteration involves pulling an arm i which corresponds to executing $\pi_{\text{meta}}^{\epsilon_i}$ for 1 meta-episode (k environment episodes) on a task $\mathcal{T} \sim p_{\text{test}}(\mathcal{T})$. Let R_i be the expected return for pulling arm i

$$R_i = \mathbb{E}_{\pi_{\text{meta}}^{\epsilon_i}, \mathcal{T} \sim p_{\text{test}}(\mathcal{T})} \left[\frac{1}{k} \sum_{i=1}^{k} \sum_{t=1}^{T} r_t^{(i)} \right] \tag{7}$$

Let $R^* = \max_{i \in \{1,\dots,M\}} R_i$ and $\pi_{\text{meta}}^{\epsilon}$ be the corresponding meta-policy. The goal of the stochastic bandit problem is to pull arms $i_1, \dots, i_N \in \{1, \dots, M\}$ such that the test-time regret $\mathcal{R}_N$ is minimized

$$\mathcal{R}_N^{\text{test}} = NR^* - \sum_{t=1}^{N} R_{i_t} \tag{8}$$

with constraint that i_t can depend only on the information available prior to iteration t. We choose Thompson sampling, a zero-regret bandit algorithm, to solve this problem. In principle, Thompson sampling should learn to choose $\pi_{\text{meta}}^{\epsilon}$ after N iterations.

B DiAMetR with Generative Models

To learn a robust meta-policy, we need to define uncertainty sets which are parameterized via $q(\mathcal{T})$ and the probability divergence $D(\cdot||\cdot)$. In Section 5, we parameterize task (i.e. reward function) distribution as latent space distributions $q_\phi(z)$ and measure the divergence between train and test task distribution via KL divergence in latent space $D(p_{\text{train}}(z)||q_\phi(z))$. In this section, we show the distributionally robust meta reinforcement learning objective (eq 3) resulting from the above-mentioned task distribution parameterization:

$$\max_\theta \min_\phi \mathbb{E}_{z \sim q_\phi(z)} \left[\mathbb{E}_{\pi_{\text{meta},\theta}^{\epsilon}, \mathcal{P}} \left[\frac{1}{k} \sum_{i=1}^{k} \sum_{t=1}^{T} r_\omega(s_t^{(i)}, a_t^{(i)}, z) \right] \right]$$
$$D_{\text{KL}}(p_{\text{train}}(z)||q_\phi(z)) \leq \epsilon \tag{9}$$

This objective function is solved in Algorithm 1 for different values of ϵ.

C Structured VAE for modelling reward distributions

In Section 5, we show how to learn reward function distribution with a variational autoencoder (VAE) [18]. In this section, we leverage the sparsity in reward functions (i.e. $0/1$ rewards) in the environments used and describe a structured VAE to model $r_\omega(s, a, z)$ with $p(z) = \mathcal{N}(0, I)$ and KL-divergence for $D(\cdot||\cdot)$. Let $\overline{h} = (\sum_{t=1}^{T} r_t s_t)/(\sum_{t=1}^{T} r_t)$ be the mean of states achieving a $+1$ reward in trajectory h. The encoder $z \sim q_\psi(z|\overline{h})$ encodes $\overline{h}$ into a latent vector z. The reward model $r_\omega(s, a, z)$ consists of 2 components: (i) latent decoder $\hat{\overline{h}} = r_\omega^h(z)$ which reconstructs $\overline{h}$ and (ii) reward predictor $r_\omega^{\text{rew}}(s, \hat{\overline{h}}) = \exp(-\|M \odot (s - \hat{\overline{h}})\|_2^2/\sigma^2)$ which predicts reward for a state given the decoded latent vector. M is a masking function and σ is a learned parameter. The training objective becomes

$$\min_{\omega, \psi} \mathbb{E}_{h \sim \mathcal{D}} \left[\mathbb{E}_{z \sim q_\psi(z|\overline{h})} \left[\left\| \overline{h} - r_\omega^h(z) \right\|_2^2 + \sum_{t=1}^{T} \left\| r_\omega^{\text{rew}}(s_t, r_\omega^h(z)) - r_t \right\|^2 \right] + D_{\text{KL}}(q_\psi(z|\overline{h})||p(z)) \right] \tag{10}$$

The structure in the VAE helps in extrapolating reward functions when $z \sim q_\phi(z)$. This can be further verified by reduction in DiAMetR's performance on test-task distributions when using vanilla VAE (see Figure 9).

Figure 9: Using a vanilla VAE, in lieu of a structured VAE, to model task distribution hurts DiAMetR's performance on test-task distributions.

D Experimental Evaluation on Point Robot Navigation

In Section 6, we evaluated DiAMetR on `Wheeled-navigation`, `Ant-navigation`, `Fetch-reach` and `Block-push`. We continue the experimental evaluation of DiAMetR in this section and compare it to RL^2, VariBAD, and HyperX on train task distribution and different test task distributions of `Point-navigation` environment. We see that DiAMetR either matches or outperforms the baselines on train task distribution and outperforms the baselines on test task distributions. Furthermore, adaptively selecting an uncertainty set during test time allows for better test time distribution adaptation when compared to selecting an uncertainty set beforehand or selecting a large uncertainty set.

Figure 10: We evaluate DiAMetR and meta RL algorithms (RL^2, VariBAD and HyperX) on training goal distribution and different test goal distributions of `Point-navigation` environment. DiAMetR outperforms RL^2, VariBAD and HyperX on train goal distribution and different test goal distributions. Furthermore, adaptively selecting an uncertainty set of DiAMetR policy (Adapt) during test time allows it to better adapt to test time distribution shift than choosing an uncertainty set beforehand (Mid). Choosing a large uncertainty set of DiAMetR policy (Conservative) leads to a conservative behavior and hurts its performance when test time distribution shift is low. The first point r_{train} on the horizontal axis indicates the training target distance Δ distribution $\mathcal{U}(0, r_{\text{train}})$ and the subsequent points r_{test}^i indicate the shifted test target distance Δ distribution $\mathcal{U}(r_{\text{test}}^{i-1}, r_{\text{test}}^i)$.

E Ablation studies

Can improved meta-exploration help a meta-RL algorithm achieve robustness to test-time task distribution shifts? To test if improved meta-exploration can help meta-RL algorithm achieve robustness to test-time task distribution shifts, we test HyperX [50] on test-task distributions in different environments. HyperX leverages curiosity-driven exploration to visit novel states for improved meta-exploration during meta-training. Despite improved meta-exploration, HyperX fails to adapt to test-time task distribution shifts (see Figure 10 for results on `Point-navigation` and Figure 6 for results on other environments). This is because HyperX aims to minimize regret on train-task distribution and doesn't leverage the visited novel states to learn new behaviors helpful in adapting to test-time task distribution shifts. Furthermore, we note that the contributions of HyperX is complementary to our contributions as improved meta-exploration would help us better learn robust meta-policies.

Figure 11: Both SAC trained from scratch (SAC scratch) and SAC pre-trained on training task distribution (SAC finetune) take more than a million timesteps to solve test tasks. In comparison, DiAMetR takes $30k$ timesteps to select the right meta-policy which then solves new tasks from test distribution in $k-1$ environment episodes (i.e. 60 timesteps given $k=2$ and horizon $H=60$).

Can RL quickly solve test time tasks? To test if RL can quickly solve test-time tasks, we train Soft Actor Critic (SAC) [14] on 5 tasks sampled from a particular test task distribution. To make the comparison fair, we include a baseline that pre-trains SAC on train-task distribution. Figure 11 shows results on `Point-navigation`. We see that both SAC trained from scratch and SAC pre-trained on training task distribution take more than a million timesteps to solve test tasks. In comparison, DiAMetR takes $30k$ timesteps to select the right meta-policy which then solves new tasks from test distribution in $k-1$ environment episodes (i.e. 60 timesteps given $k=2$ and horizon $H=60$). This shows that meta-RL formulation is required for quick-adaptation to test tasks.

F Proof of Proposition 4.1

In this section, we prove the proposition in the main text about the excess regret of an ϵ_2-robust policy under and ϵ_1-perturbation (restated below).

Proposition 4.1. *Let* $\overline{\epsilon_i} = \min\{\epsilon_i + \beta, 1 - \frac{|\mathcal{S}_0|}{|\mathcal{S}|}\}$. *There exists* $q(\mathcal{T})$ *satisfying* $D_{TV}(p_{train}, q) \leq \epsilon_1$ *where an* ϵ_2-*robust meta policy incurs excess regret over the optimal* ϵ_1-*robust meta-policy:*

$$\mathbb{E}_{q(\mathcal{T})}[\text{Regret}(\pi_{meta}^{\epsilon_2}, \mathcal{T}) - \text{Regret}(\pi_{meta}^{\epsilon_1}, \mathcal{T})] \geq \left(c(\epsilon_1, \epsilon_2) + \frac{1}{c(\epsilon_1, \epsilon_2)} - 2 \right) \sqrt{\overline{\epsilon_1}(1 - \overline{\epsilon_1})|\mathcal{S}_0|(|\mathcal{S}| - \mathcal{S}_0|)}$$

(5)

The scale of regret depends on $c(\epsilon_1, \epsilon_2) = \sqrt{\frac{\overline{\epsilon_2}^{-1} - 1}{\overline{\epsilon_1}^{-1} - 1}}$, *a measure of the mismatch between* ϵ_1 *and* ϵ_2.

Summary of proof: The proof proceeds in three stages: 1) deriving a form for the optimal meta-policy for a *fixed* task distribution 2) proving that the optimal ϵ-robust meta-policy takes form:

$$\pi_{\text{meta}}^{\epsilon}(s) \propto \begin{cases} \sqrt{\frac{1 - \overline{\epsilon}}{|\mathcal{S}_0|}} & s \in \mathcal{S}_0 \\ \sqrt{\frac{\overline{\epsilon}}{|\mathcal{S}| - |\mathcal{S}_0|}} & s \notin \mathcal{S}_0 \end{cases}$$

and finally 3) showing that under the task distribution $p(\mathcal{T}_g) = (1 - \overline{\epsilon_1})\text{Uniform}(\mathcal{S}_0) + \overline{\epsilon_1}\text{Uniform}(\mathcal{S}\backslash\mathcal{S}_0)$, the gap in regret takes the form in the proposition.

Proof. For convenience, denote $\mathcal{S}_1 = \mathcal{S}\backslash\mathcal{S}_0$ and $\text{Regret}(\pi_{\text{meta}}, q(\mathcal{T})) = \mathbb{E}_q[\text{Regret}(\pi, \mathcal{T})]$. Furthermore, since the performance of a meta-policy depends only on its final-timestep visitation distribution (and any such distribution is attainable), we directly refer to $\pi(g)$ as the visited goal distribution of the meta-policy π_{meta}. Recall that the regret of π_{meta} on task $\mathcal{T}_g$ is given by $\frac{1}{\pi(g)}$.

We begin with the following lemma that demonstrates the optimal policy for a fixed task distribution.

Lemma F.1. *The optimal meta-policy* $\pi_q^* = \arg\min_\pi \text{Regret}(\pi, q(\mathcal{T}_g))$ *for a given task distribution* $q(\mathcal{T}_g)$ *is given by*

$$\pi_q^*(g) = \frac{1}{\int \sqrt{q(g')}\, dg'} \sqrt{q(g)}$$

(11)

The proof of the lemma is similar to the argument in Gupta et al. [12], Lee et al. [20]:

$$\pi_q^* = \underset{\pi(g)}{\arg\min}\,\text{Regret}(\pi, q(\mathcal{T}_g)) = \underset{\pi(g)}{\arg\min}\,\mathbb{E}_{\mathcal{T}_g \sim q}[\frac{1}{\pi(g)}] \tag{12}$$

Letting $Z = \int_g \sqrt{q(g)}$, we can rewrite the optimization problem as minimizing an f-divergence (with $f(x) = \frac{1}{x}$)

$$= \int \frac{1}{\pi(g)} q(g)\,dg \tag{13}$$

$$= Z^2 \int \frac{\sqrt{q(g)}/Z}{\pi(g)} \sqrt{q(g)}/Z\,dg \tag{14}$$

$$= Z^2 D_f(\pi \| \sqrt{q(g)}/Z) \tag{15}$$

This is minimized when both are equal, i.e. when $\pi_q^*(g) = \sqrt{q}/Z$, concluding the proof.

Lemma F.2. *The optimal ϵ-robust meta-policy $\pi^{*\epsilon} = \arg\min \mathcal{R}(\pi, p_{train}, \epsilon)$ takes form*

$$\pi^{\epsilon}(g) \propto \begin{cases} \sqrt{\frac{1-\bar{\epsilon}}{|\mathcal{S}_0|}} & g \in \mathcal{S}_0 \\ \sqrt{\frac{\bar{\epsilon}}{|\mathcal{S}|-|\mathcal{S}_0|}} & g \notin \mathcal{S}_0 \end{cases}$$

Define the distribution $q^{\epsilon}(\mathcal{T}_g) = (1-\bar{\epsilon})\text{Uniform}(\mathcal{S}_0) + \bar{\epsilon}\text{Uniform}(\mathcal{S}\backslash\mathcal{S}_0)$, which is an ϵ-perturbation of p_{train} under the TV metric. We note that there are two main cases: 1) if $\bar{\epsilon} = 1 - \frac{|\mathcal{S}_0|}{|\mathcal{S}|}$, then q^{ϵ} is uniform over the entire state space, and otherwise 2) it corresponds to uniformly taking ϵ-mass from $\mathcal{S}_0$ and uniformly distributing it across $\mathcal{S}_1$. Using the lemma, we can derive the optimal policy for q^{ϵ}, which we denote π^{ϵ}:

$$\pi^{\epsilon} = \underset{\pi(g)}{\arg\min}\,\text{Regret}(\pi, q^{\epsilon}(\mathcal{T})) = \frac{1}{\int \sqrt{q^{\epsilon}(g')}\,dg'} \sqrt{q(g)}, \tag{16}$$

Writing $Z_{\epsilon} = \int \sqrt{q(g')}\,dg'$, we can write this explicitly as

$$= \frac{1}{Z_{\epsilon}} \begin{cases} \sqrt{\frac{1-\bar{\epsilon}}{|\mathcal{S}_0|}} & g \in \mathcal{S}_0 \\ \sqrt{\frac{\bar{\epsilon}}{|\mathcal{S}|-|\mathcal{S}_0|}} & g \notin \mathcal{S}_0 \end{cases} \tag{17}$$

We now show that there exists no other distribution $q'(\mathcal{T})$ with $TV(p_{\text{train}}, q') \le \epsilon$ for which $\text{Regret}(\pi^{\epsilon}, q') \ge \text{Regret}(\pi^{\epsilon}, q^{\epsilon})$. We break this into the two cases for q^{ϵ}: if q^{ϵ} is uniform over all goals, then π^{ϵ} visits all goals equally often, and so incurs the same regret on every task distribution. The more interesting case is the second: consider any other task distribution $q'(g)$, and let q_0', q_1' be the probabilities of sampling goals in $\mathcal{S}_0$ and $\mathcal{S}_1$ respectively under q': $q_0' = \mathbb{E}_{g \sim q'}[1(g \in \mathcal{S}_0)]$ and $q_1' = 1 - q_0'$. The regret of π^{ϵ} on q' is given by

$$\text{Regret}(\pi^{\epsilon}, q'(\mathcal{T})) = \mathbb{E}_{g \sim q'}[\frac{1}{\frac{1}{Z_{\epsilon}}\sqrt{q(g)}}] \tag{18}$$

$$= Z_{\epsilon}(q_0'\sqrt{\frac{|\mathcal{S}_0|}{1-\bar{\epsilon}}} + q_1'\sqrt{\frac{|\mathcal{S}|-|\mathcal{S}_0|}{\bar{\epsilon}}}) \tag{19}$$

By construction of $\bar{\epsilon}$, we have that $\sqrt{\frac{|\mathcal{S}|-|\mathcal{S}_0|}{\bar{\epsilon}}} \ge \sqrt{\frac{|\mathcal{S}_0|}{1-\bar{\epsilon}}}$, and so this expression is maximized for the largest value of q_1'. Under a ϵ-perturbation in the TV metric, the maximal value of q_1 is given by $\beta + \epsilon = \bar{\epsilon}$:

$$\le Z_{\epsilon}((1-\bar{\epsilon})\sqrt{\frac{|\mathcal{S}_0|}{1-\bar{\epsilon}}} + \bar{\epsilon}\sqrt{\frac{|\mathcal{S}|-|\mathcal{S}_0|}{\bar{\epsilon}}}) \tag{20}$$

This is exactly the regret under our chosen task proposal distribution $q^{\epsilon}(\mathcal{T})$ (which has $q_1 = \bar{\epsilon}$)

$$= \text{Regret}(\pi^{\epsilon}, q^{\epsilon}(\mathcal{T})). \tag{21}$$

608 These two steps can be combined to demonstrate that π^ϵ is a solution to the robust objective.
609 Specifically, we have that

$$\mathcal{R}(\pi_\epsilon, p_{\text{train}}, \epsilon) = \max_{q':TV(p_{\text{train}},q')\leq\epsilon} \text{Regret}(\pi_\epsilon, q') = \text{Regret}(\pi_\epsilon, q^\epsilon) \tag{22}$$

610 so, for any other meta-policy π_{meta}, we have

$$\mathcal{R}(\pi, p_{\text{train}}, \epsilon) = \max_{q':TV(p_{\text{train}},q')\leq\epsilon} \text{Regret}(\pi, q') \geq \text{Regret}(\pi, q^\epsilon) \geq \text{Regret}(\pi^\epsilon, q^\epsilon) = \mathcal{R}(\pi^\epsilon, p_{\text{train}}, \epsilon) \tag{23}$$

611 This concludes the proof of the lemma. $\qquad\square$

612 Finally, to complete the proof of the original proposition, we write down (and simplify) the gap in
613 regret between π^{ϵ_1} and π^{ϵ_2} for the task distribution q^{ϵ_1} (as described above). We begin by writing
614 down the regret of π^{ϵ_1}:

$$\text{Regret}(\pi^{\epsilon_1}, q^{\epsilon_1}(\mathcal{T})) = Z_{\epsilon_1}\left((1-\overline{\epsilon_1})\sqrt{\frac{|\mathcal{S}_0|}{1-\overline{\epsilon_1}}} + \overline{\epsilon_1}\sqrt{\frac{|\mathcal{S}_1|}{\overline{\epsilon_1}}}\right) \tag{24}$$

$$= (\sqrt{|\mathcal{S}_0|(1-\overline{\epsilon_1})} + \sqrt{|\mathcal{S}_1|(\overline{\epsilon_1})})\left((1-\overline{\epsilon_1})\sqrt{\frac{|\mathcal{S}_0|}{1-\overline{\epsilon_1}}} + \overline{\epsilon_1}\sqrt{\frac{|\mathcal{S}_1|}{\overline{\epsilon_1}}}\right) \tag{25}$$

$$= (1-\overline{\epsilon_1})|\mathcal{S}_0| + \overline{\epsilon_1}|\mathcal{S}_1| + 2\sqrt{\overline{\epsilon_1}(1-\overline{\epsilon_1})|\mathcal{S}_0||\mathcal{S}_1|} \tag{26}$$

Next, we write the regret of π^{ϵ_2}

$$\text{Regret}(\pi^{\epsilon_2}, q^{\epsilon_1}(\mathcal{T})) = Z_{\epsilon_2}\left((1-\overline{\epsilon_1})\sqrt{\frac{|\mathcal{S}_0|}{1-\overline{\epsilon_2}}} + \overline{\epsilon_1}\sqrt{\frac{|\mathcal{S}_1|}{\overline{\epsilon_2}}}\right) \tag{27}$$

$$= (\sqrt{|\mathcal{S}_0|(1-\overline{\epsilon_2})} + \sqrt{|\mathcal{S}_1|(\overline{\epsilon_2})})\left((1-\overline{\epsilon_1})\sqrt{\frac{|\mathcal{S}_0|}{1-\overline{\epsilon_2}}} + \overline{\epsilon_1}\sqrt{\frac{|\mathcal{S}_1|}{\overline{\epsilon_2}}}\right) \tag{28}$$

$$= (1-\overline{\epsilon_1})|\mathcal{S}_0| + \overline{\epsilon_1}|\mathcal{S}_1| + \overline{\epsilon_1}\sqrt{|\mathcal{S}_0||\mathcal{S}_1|\frac{(1-\overline{\epsilon_2})}{\overline{\epsilon_2}}} + (1-\overline{\epsilon_1})\sqrt{|\mathcal{S}_0||\mathcal{S}_1|\frac{(\overline{\epsilon_2})}{1-\overline{\epsilon_2}}} \tag{29}$$

$$= (1-\overline{\epsilon_1})|\mathcal{S}_0| + \overline{\epsilon_1}|\mathcal{S}_1| + \overline{\epsilon_1}\sqrt{|\mathcal{S}_0||\mathcal{S}_1|\frac{(1-\overline{\epsilon_2})}{\overline{\epsilon_2}}} + (1-\overline{\epsilon_1})\sqrt{|\mathcal{S}_0||\mathcal{S}_1|\frac{(\overline{\epsilon_2})}{1-\overline{\epsilon_2}}} \tag{30}$$

$$= (1-\overline{\epsilon_1})|\mathcal{S}_0| + \overline{\epsilon_1}|\mathcal{S}_1| + \sqrt{|\mathcal{S}_0|\mathcal{S}_1|\overline{\epsilon_1}(1-\overline{\epsilon_1})}\left(\sqrt{\frac{\overline{\epsilon_1}}{(1-\overline{\epsilon_1})}\frac{(1-\overline{\epsilon_2})}{\overline{\epsilon_2}}} + \sqrt{\frac{(1-\overline{\epsilon_1})}{\overline{\epsilon_1}}\frac{\overline{\epsilon_2}}{(1-\overline{\epsilon_2})}}\right) \tag{31}$$

Now writing $c(\epsilon_1, \epsilon_2) = \sqrt{\frac{\overline{\epsilon_2}^{-1}-1}{\overline{\epsilon_1}^{-1}-1}} = \sqrt{\frac{1-\overline{\epsilon_2}}{\overline{\epsilon_2}}\frac{\overline{\epsilon_1}}{1-\overline{\epsilon_1}}}$

$$= (1-\overline{\epsilon_1})|\mathcal{S}_0| + \overline{\epsilon_1}|\mathcal{S}_1| + \sqrt{|\mathcal{S}_0|\mathcal{S}_1|\overline{\epsilon_1}(1-\overline{\epsilon_1})}\left(c(\epsilon_1,\epsilon_2) + \frac{1}{c(\epsilon_1,\epsilon_2)}\right) \tag{32}$$

$$= \text{Regret}(\pi^{\epsilon_1}, q^{\epsilon_1}(\mathcal{T})) + \sqrt{|\mathcal{S}_0|\mathcal{S}_1|\overline{\epsilon_1}(1-\overline{\epsilon_1})}\left(c(\epsilon_1,\epsilon_2) + \frac{1}{c(\epsilon_1,\epsilon_2)} - 2\right) \tag{33}$$

615 This concludes the proof of the proposition.

 # G   Meta-policy Selection and Adaptation during Meta-test

In this section, we show that DiAMetR is able adapt to various test task distributions across different environments by selecting an appropriate meta-policy based on the inferred test-time distribution shift and then quickly adapting the meta-policy to different tasks drawn from the test-distribution. RL^2's performance remains more or less the same after test-time finetuning showing that 10 iteration (with 25 rollouts per iteration) isn't enough for RL^2 to learn an adaptive policy for a new task distribution.

Figure 12: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on point robot navigation for various test task distributions. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

Figure 13: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on wheeled navigation for various test task distributions. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

Figure 14: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on ant navigation for various test task distributions. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

Figure 15: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on fetch reach for various test task distributions. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

Figure 16: We compare test time adaptation of DiAMetR with test time finetuning of RL^2 on block push for various test task distributions. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

H Environment Description

We describe the environments used in the paper:

- `{Point,Wheeled,Ant}-navigation`: The rewards for each task correspond to reaching an unobserved target location $s_{\mathcal{T}}$. The agent (i.e. Wheeled, Ant) must explore the environment to find the unobserved target location (Wheeled driving a differential drive robot, Ant controlling a four legged robotic quadruped). It receives a reward of 1 once it gets within a small δ distance of the target s_t, as in [13].

- `Dense Ant-navigation`: The rewards for each task correspond to reaching an unobserved target location $s_{\mathcal{T}}$. The Ant (a four legged robotic quadruped) must explore the environment to find the unobserved target location. It receives a reward of $-\|\text{agent}_{x,y} - s_{\mathcal{T}}\|$ where $\text{agent}_{x,y}$ is the (x,y) position of the Ant.

- `Wind navigation`: The rewards for each task correspond to reaching an unobserved target location s_t. While $s_{\mathcal{T}}$ is fixed across tasks (i.e. at $(1/\sqrt{2}, 1/\sqrt{2})$), the agent (a linear system robot)

much navigate in the presence of wind (i.e. a noise vector $w_\mathcal{T}$) that varies across tasks. It receives a reward of 1 once it gets within a small δ distance of the target $s_\mathcal{T}$.

- `Fetch reach`: Each task corresponds to moving the gripper to an unobserved target location s_t. The Fetch robot must move its gripper around and explore the environment to find the unobserved target location. Once the gripper gets within a small δ distance of the target s_t, it receives a reward of 1.

- `Block push`: Each task corresponds to moving the block to an unobserved target location s_t. The robot arm must move the block around and explore the environment to find the unobserved target location. Once the block gets within a small δ distance of the target s_t, it receives a reward of 1, as in [13].

Furthermore, Table 2 describes the state space $\mathcal{S}$, action space $\mathcal{A}$, episodic horizon H, frameskip for each environment and k (i.e. number of environment episodes in 1 meta episode).

Name	State space $\mathcal{S}$	Action space $\mathcal{A}$	Episodic Horizon H	Frameskip	k
Point-navigation	Box(2,)	Box(2,)	60	1	2
Wind-navigation	Box(2,)	Box(2,)	25	1	1
Wheeled-navigation	Box(12,)	Box(2,)	60	10	2
Ant-navigation	Box(29,)	Box(8,)	200	5	2
Dense Ant-navigation	Box(29,)	Box(8,)	200	5	2
Fetch reach	Box(17,)	Box(6,)	50	10	2
Block Push	Box(10,)	Box(4,)	60	10	2

Table 2: Environment Description

I Hyperparameters Used

Table 3 describes the hyperparameters used for the structured VAE for learning reward function distribution

latent z dimension (for reward and dynamics distribution)	16
$p(z)$ (for reward and dynamics distribution)	$\mathcal{N}(0, I)$
$q_\psi(z|\overline{h})$ (for reward distribution)	MLP(hidden-layers=[256, 256, 256])
$r_\omega^h(z)$	MLP(hidden-layers=[256, 256, 256])
$q_\psi(z|(s_t, a_t)_{t=1}^T)$ (for dynamics distribution)	GRU(hidden-layers=[256, 256, 256])
$p_\omega^{\text{dyn}}(s, a)$	MLP(hidden-layers=[256, 256, 256])
Train trajectories (from train task replay buffer)	$1e6/(\text{Episodic Horizon } H)$
Train Epochs	100
initial $\log \sigma$	-5
$\{\epsilon_i\}_{i=1}^M$ (*out-of-support* test task distributions)	$\{0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8\}$
$\{\epsilon_i\}_{i=1}^M$ (*in-support* test task distributions)	$\{0.0, 0.05, 0.1, 0.15, 0.2, 0.25, 0.3, 0.35, 0.4\}$
n_{tr} (num tasks in empirical $p_{\text{train}}(\mathcal{T})$)	200

Table 3: Hyperparameters for structured VAE

We use off-policy RL^2 [31] as our base meta-learning algorithm. We borrow the implementation from https://github.com/twni2016/pomdp-baselines. We use the hyperparameters from the config file https://github.com/twni2016/pomdp-baselines/blob/main/configs/meta/ant_dir/rnn.yml but found 1500 `num-iters` was sufficient for convergence of the meta-RL algorithm. Furthermore, we use 200 `num-updates-per-iter`. Our codebase can be found at https://drive.google.com/drive/folders/1KTjst_n0PlR0O7Ez3-WVj0jbgnl1ELD3?usp=sharing.

We parameterize $q_\phi(z)$ as a normal distribution $\mathcal{N}(\mu, \sigma)$ with $\phi = (\mu, \sigma)$ as parameters. We use REINFORCE with trust region constraints (i.e. Proximal Policy Optimization [37]) for optimizing $q_\phi(z)$. We borrow our PPO implementation from the package https://github.com/ikostrikov/pytorch-a2c-ppo-acktr-gail and default hyperparameters from https://github.com/ikostrikov/pytorch-a2c-ppo-

Environment	Task type	Task parameter distribution	$p_{\text{train}}(\mathcal{T})$	$\{p^i_{\text{test}}(\mathcal{T})\}^K_{i=1}$
`Point, Wheeled, Ant-navigation`	reward change, out-of-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \mathcal{U}(0, 0.5)$	$\Delta \sim \mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.55)$ $\mathcal{U}(0.55, 0.6), \mathcal{U}(0.6, 0.65)$ $\mathcal{U}(0.65, 0.7)$
`Point, Wheeled, Ant-navigation`	reward change, in-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \text{Exp}(\lambda = 5)$	$\Delta \sim \mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.55)$ $\mathcal{U}(0.55, 0.6), \mathcal{U}(0.6, 0.65)$ $\mathcal{U}(0.65, 0.7)$
`Dense Ant-navigation`	reward change, in-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \text{Exp}(\lambda = 5)$	$\Delta \sim \mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.55)$ $\mathcal{U}(0.55, 0.6), \mathcal{U}(0.6, 0.65)$ $\mathcal{U}(0.65, 0.7)$
`Wind -navigation`	dynamics change, out-of-support shift	$w_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \mathcal{U}(0, 0.05)$	$\Delta \sim \mathcal{U}(0, 0.05), \mathcal{U}(0.05, 0.06)$ $\mathcal{U}(0.06, 0.07), \mathcal{U}(0.07, 0.08)$ $\mathcal{U}(0.08, 0.09)$
`Wind -navigation`	dynamics change, in-support shift	$w_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \text{Exp}(\lambda = 40)$	$\Delta \sim \mathcal{U}(0, 0.05), \mathcal{U}(0.05, 0.06)$ $\mathcal{U}(0.06, 0.07), \mathcal{U}(0.07, 0.08)$ $\mathcal{U}(0.08, 0.09)$
`Fetch-reach`	reward change, out-of-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \mathcal{U}(0, 0.1)$	$\Delta \sim \mathcal{U}(0, 0.1), \mathcal{U}(0.1, 0.12)$ $\mathcal{U}(0.12, 0.14), \mathcal{U}(0.14, 0.16)$ $\mathcal{U}(0.16, 0.18), \mathcal{U}(0.18, 0.2)$
`Fetch-reach`	reward change, in-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, 2\pi)$	$\Delta \sim \text{Exp}(\lambda = 20)$	$\Delta \sim \mathcal{U}(0, 0.1), \mathcal{U}(0.1, 0.12)$ $\mathcal{U}(0.12, 0.14), \mathcal{U}(0.14, 0.16)$ $\mathcal{U}(0.16, 0.18)$
`Block-push`	reward change, out-of-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, \pi/2)$	$\Delta \sim \mathcal{U}(0, 0.5)$	$\Delta \sim \mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.6)$ $\mathcal{U}(0.6, 0.7), \mathcal{U}(0.7, 0.8)$ $\mathcal{U}(0.8, 0.9), \mathcal{U}(0.9, 1.0)$
`Block-push`	reward change, in-support shift	$s_\mathcal{T} = (\Delta \cos\theta, \Delta \sin\theta)$ $\Delta \sim \mathcal{U}(\Delta_{\min}, \Delta_{\max})$ $\theta \sim \mathcal{U}(0, \pi/2)$	$\Delta \sim \text{Exp}(\lambda = 4)$	$\Delta \sim \mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.6)$ $\mathcal{U}(0.6, 0.7), \mathcal{U}(0.7, 0.8)$ $\mathcal{U}(0.8, 0.9), \mathcal{U}(0.9, 1.0)$

Table 5: Parameters for train and test task distribution for `{Point,Wheeled, Ant}`-navigation, `Dense Ant-navigation`, `Wind-navigation`, `Fetch-reach` and `Block-push`. While tasks in `Wind-navigation` vary in dynamics, tasks in other environments vary in reward function. The shifted test task distributions can be either *in-support* or *out-of-support* of the training task distribution. All these task distributions are determined by distributions of underlying task parameters (say target location $s_\mathcal{T}$ or wind velocity $w_\mathcal{T}$), which either determine the reward function or the dynamics function.

acktr-gail/blob/master/a2c_ppo_acktr/arguments.py. Table 4 describes the hyperparameters for PPO that we changed.

num-processes	1
ppo-epoch	10
num-iters	3
num-env-trajectories-per-iter	100

Table 4: Hyperparameters for PPO for training q_ϕ per every meta-RL iteration

We use off-policy VariBAD [6] implementation from the package https://github.com/twni2016/pomdp-baselines/tree/main/BOReL with their default hyperparameters. We use HyperX [50] implementation from the package https://github.com/lmzintgraf/hyperx with their default hyperparameters. To make the comparisons fair, we ensure that the policy and the Q-function in VariBAD and HyperX have same architecture as that in off-policy RL^2 [31].

J   Alternate task distribution parameterization and handling task distributions with varying dynamics with DiAMetR

Algorithm 3 DiAMetR: Meta-training phase

1: Given: $p_{\text{train}}(\mathcal{T})$, Return: $\{\pi^{\epsilon_i}_{\text{meta},\theta}\}_{i=1}^M$
2: $\pi^{\epsilon_1}_{\text{meta},\theta}, \mathcal{D}_{\text{Replay-Buffer}} \leftarrow$ Solve equation 1 with off-policy RL[2]
3: Reward distribution r_ω, prior $p_{\text{train}}(z) \leftarrow$ Solve eq 34 using $\mathcal{D}_{\text{Replay-Buffer}}$
4: Dynamic distribution p_ω, prior $p_{\text{train}}(z) \leftarrow$ Solve eq 34 using $\mathcal{D}_{\text{Replay-Buffer}}$
5: **for** ϵ in $\{\epsilon_2, \dots, \epsilon_M\}$ **do**
6:    Initialize q_ϕ, $\pi^\epsilon_{\text{meta},\theta}$ and $\lambda \geq 0$.
7:    **for** iteration $n = 1, 2, \dots$ **do**
8:       **Meta-policy:** Update $\pi^\epsilon_{\text{meta},\theta}$ using off-policy RL[2] [31]

$$\theta := \theta + \alpha \nabla_\theta \mathbb{E}_{\mathcal{T} \sim p_{\text{train}}(\mathcal{T})}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, \mathcal{T}}[\frac{n_{\text{tr}} w_{\mathcal{T}}}{k \sum_{i=1}^{n_{\text{tr}}} w_{\mathcal{T}_i}} \sum_{i=1}^k \sum_{t=1}^T r_t^{(i)}]]$$

$$\theta := \theta + \alpha \nabla_\theta \mathbb{E}_{z \sim q_\phi(z)}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, \mathcal{P}}[\frac{1}{k} \sum_{i=1}^k \sum_{t=1}^T r_\omega(s_t^{(i)}, a_t^{(i)}, z)]]$$

$$\theta := \theta + \alpha \nabla_\theta \mathbb{E}_{\mathcal{T} \sim q_\phi(\mathcal{T})}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, p_\omega(\cdot,\cdot,z)}[\frac{1}{k} \sum_{i=1}^k \sum_{t=1}^T r_t^{(i)}]]$$

9:       **Adversarial task distribution:** Update q_ϕ using Reinforce [39]

$$\phi := \phi - \alpha \nabla_\phi (\mathbb{E}_{\mathcal{T} \sim p_{\text{train}}(\mathcal{T})}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, \mathcal{T}}[\frac{n_{\text{tr}} w_{\mathcal{T}}}{k \sum_{i=1}^{n_{\text{tr}}} w_{\mathcal{T}_i}} \sum_{i=1}^k \sum_{t=1}^T r_t^{(i)}]] + \lambda D_{\text{KL}}(p_{\text{train}}(\mathcal{T}) \| q_\phi(\mathcal{T}))$$

$$\phi := \phi - \alpha \nabla_\phi (\mathbb{E}_{z \sim q_\phi(z)}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, \mathcal{P}}[\frac{1}{k} \sum_{i=1}^k \sum_{t=1}^T r_\omega(s_t^{(i)}, a_t^{(i)}, z)]] + \lambda D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z))$$

$$\phi := \phi - \alpha \nabla_\phi (\mathbb{E}_{\mathcal{T} \sim q_\phi(\mathcal{T})}[\mathbb{E}_{\pi^\epsilon_{\text{meta},\theta}, p_\omega(\cdot,\cdot,z)}[\frac{1}{k} \sum_{i=1}^k \sum_{t=1}^T r_t^{(i)}]] + \lambda D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z))$$

10:       **Lagrange constraint multiplier:** Update λ to enforce $D_{\text{KL}}(p_{\text{train}} \| q_\phi) < \epsilon$,

$$\lambda :=_{\lambda \geq 0} \lambda + \alpha (D_{\text{KL}}(p_{\text{train}}(\mathcal{T}) \| q_\phi(\mathcal{T})) - \epsilon)$$

$$\lambda :=_{\lambda \geq 0} \lambda + \alpha (D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z)) - \epsilon) \quad \lambda :=_{\lambda \geq 0} \lambda + \alpha (D_{\text{KL}}(p_{\text{train}}(z) \| q_\phi(z)) - \epsilon)$$

11:    **end for**
12: **end for**

We present an updated version of DiAMetR that distinguishes between *in-support* and *out-of-support* task distribution shift and prescribes different task distribution parameterization for each case. It also handles task distributions with varying dynamics. DiAMetR, as presented in Section 5, is mostly focused towards handling *out-of-support* task distribution shift where tasks differ in reward function. We first describe different ways to parameterize task distribution and present the updated training algorithm in Algorithm 3. The test-time algorithm remains the same, as described in Algorithm 2. Figure 17 provides a visual description of DiAMetR during its meta-train and meta-test phase.

J.1   Parameterizing Task Distributions

Handling in-support distribution shifts: For handling in-support task distribution shifts, we propose to represent new task distributions as re-weighted training task distribution $q(\mathcal{T}) \propto w_{\mathcal{T}} p_{\text{train}}(\mathcal{T})$ where $w_{\mathcal{T}} > 0$ is a parameter. Since we have a finite set of training tasks, say $\{\mathcal{T}_i\}_{i=1}^{n_{\text{tr}}}$, new task distributions become $q(\mathcal{T}_i) = \frac{w_{\mathcal{T}_i}}{\sum_{i=1}^{n_{\text{tr}}} w_{\mathcal{T}_i}}$. With a slight abuse of notation, we can write empirical training task distribution as $p_{\text{train}}(\mathcal{T}_i) = \frac{1}{n_{\text{tr}}}$. We can use KL divergence to measure the divergence between training task distribution and test task distribution $D(p_{\text{train}}(\mathcal{T}) \| q_\phi(\mathcal{T})) = \sum_{i=1}^{n_{\text{tr}}} \frac{1}{n_{\text{tr}}} \log \frac{\sum_{i=1}^{n_{\text{tr}}} w_{\mathcal{T}_i}}{n_{\text{tr}} w_{\mathcal{T}_i}}$. We collectively represent the parameters $\phi = \{w_{\mathcal{T}_i}\}_{i=1}^{n_{\text{tr}}}$.

Meta Train phase   Meta Test phase

Figure 17: During meta-train phase, DiAMetR learns a family of meta-policies robust to varying levels of distribution shift (as characterized by ϵ_i). During meta-test phase, given a potentially shifted test-time distribution of tasks, DiAMetR chooses the meta-policy with the most appropriate level of robustness and use it to perform fast adaptation for new tasks sampled from the same shifted test task distribution.

Handling out-of-support distribution shift: For handling out-of-support task distribution shifts, we propose to learn a probabilistic model of the training task distribution, and use the learned latent representation as a space on which to parameterize uncertainty sets over new task distributions. Specifically, we jointly train a task encoder $q_\psi(z|h)$ that encodes an environment history into the latent space, and a decoder $\mathcal{T}_\omega(s, a, z)$ mapping a latent vector z to a property of the task using a dataset of trajectories collected from the training tasks. To describe the exact form of $\mathcal{T}_\omega$, we consider how tasks can differ and list two scenarios:

- **Tasks differ in reward functions:** $\mathcal{T}_\omega$ takes form of reward functions $r_\omega(s, a, z)$ that maps a latent vector z to a reward function.

- **Tasks differ in dynamics:** $\mathcal{T}_\omega$ takes form of dynamics $p_\omega(s, a, z)$ that maps a latent vector z to a dynamics function.

This generative model can be trained as a standard latent variable model by maximizing a standard evidence lower bound (ELBO), trading off reward prediction and matching a prior $p_{\text{train}}(z)$ (chosen to be the unit gaussian).

$$\min_{\omega, \psi} \mathbb{E}_{h \sim \mathcal{D}} \left[\mathbb{E}_{z \sim q_\psi(z|h)} \left[\sum_{t=1}^{T} l(\mathcal{T}_\omega(s_t, a_t, z), h, t) \right] + D_{\text{KL}}(q_\psi(z|h) || \mathcal{N}(0, I)) \right]$$

$$l(\mathcal{T}_\omega(s_t, a_t, z), h, t) = (r_\omega(s_t, a_t, z) - r_t)^2 \quad \text{when rewards differ}$$

$$l(\mathcal{T}_\omega(s_t, a_t, z), h, t) = \|p_\omega(s_t, a_t, z) - s_{t+1}\|^2 \quad \text{when dynamics differ} \tag{34}$$

Having learned a latent space, we can parameterize new task distributions $q(\mathcal{T})$ as distributions $q_\phi(z)$. The original training distribution corresponds to $p_{\text{train}}(z) = \mathcal{N}(0, I)$. We measure the divergence between train task distribution and new task distributions using the KL divergence in the latent space $D(p_{\text{train}}(z) || q_\phi(z))$.

J.2 Meta Policy update

We take a closer look at the meta-policy update (Line 8) in Algorithm 3. The way it collects state-action trajectories for training $\pi_{\text{meta}, \theta}^\epsilon$ is scenario dependent:

1. In-support shifted test task distributions: We directly interact with environment since the new tasks are still in-support of the empirical training task distribution and just have a different weighting (which just reweighs the loss term corresponding to that task).

2. Out-of-support shifted test task distributions where only rewards vary across tasks: We directly interact with environment since the transition dynamics is the same.

3. Out-of-support shifted test task distributions where only dynamics vary across tasks: We interact with a learned transition dynamics model.

 J.3   Structured VAE for modelling dynamics distribution

We describe our structured VAE architecture for modelling dynamics distribution $p_\omega(s,a,z)$ with $p(z) = \mathcal{N}(0, I)$ and KL-divergence for $D(\cdot||\cdot)$. It handles *out-of-support* shifted test task distributions where only dynamics vary across tasks. We leverage the fact that dynamics differ by an additive term. The encoder $z \sim q_\phi(z|(s_t, a_t)_{t=1}^T)$ encodes the state action trajectory to a latent vector z. The dynamics model takes the form $p_\omega(s,a,z) = W_\omega z + p_\omega^{\text{dyn}}(s,a)$ where W_ω is a parameter. The training objective becomes:

$$\min_{\omega, \psi} \mathbb{E}_{(s_t,a_t)_{t=1}^T \sim \mathcal{D}} \left[\mathbb{E}_{z \sim q_\psi(z|(s_t,a_t)_{t=1}^T)} \left[\sum_{t=1}^{T-1} \left\| p_\omega^{\text{dyn}}(s_t, a_t) + W_\omega z - s_{t+1} \right\|^2 \right] + D_{\text{KL}}(q_\psi(z|(s_t,a_t)_{t=1}^T)||p(z)) \right] \tag{35}$$

The structure in the VAE helps in extrapolating dynamics when $z \sim q_\phi(z)$.

Section 6 details experiments on *out-of-support* shifted test task distributions where only rewards vary across tasks. Appendix K details experiments on *out-of-support* shifted test task distributions where only dynamics vary across tasks. Appendix L details experiments on *in-support* shifted test task distributions. Table 5 provides parameters for train and test task distributions for different environments used in these experiments.

K   Evaluations on out-of-support shifted task distributions with varying dynamics

Figure 18: `Wind navigation`: The agent needs to navigate in presence of winds whose velocity $w_\mathcal{T}$ varies by task

To test DiAMetR on tasks with varying dynamics, we use the `wind navigation` environment (controlling a linear system robot in presence of wind, as shown in Figure 18) discussed in several prior works on meta-RL [31, 6]. In this section, we focus on *out-of-support* shifted test task distributions. To enable DiAMetR to imagine out-of-distribution dynamics that are out-of-support, we use structured VAE to model dynamics distribution (see Appendix J.3 for more details). Figure 19 shows that DiAMetR matches existing meta RL algorithms (RL^2, VariBAD and HyperX) on training task distribution and outperforms them on shifted test task distributions. Moreover, Figure 19 shows that adaptively choosing an uncertainty set during test time allows for better test time distribution adaptation when compared to selecting an uncertainty set beforehand or selecting a large uncertainty set.

Figure 19: We evaluate DiAMetR and meta RL algorithms (RL^2, VariBAD and HyperX) on training task distribution and different test task distributions of `Wind-navigation` environment. DiAMetR outperforms RL^2, VariBAD and HyperX on train task distribution and different test task distributions. Furthermore, adaptively selecting an uncertainty set for DiAMetR policy (Adapt) during test time allows it to better adapt to test time distribution shift than choosing an uncertainty set beforehand (Mid). Choosing a large uncertainty set for DiAMetR policy (Conservative) leads to a conservative behavior and hurts its performance when test time distribution shift is low. The first point p_1 on the horizontal axis indicates the training wind speed (Δ) distribution $\mathcal{U}(0, p_1)$ and the subsequent points p_i indicate the shifted wind speed (Δ) distribution $\mathcal{U}(p_{i-1}, p_i)$ (See Table 5 for more information on task distributions).

L   Evaluations on in-support shifted task distributions

We test DiAMetR's ability to adapt to varying levels of *in-support* task distribution shifts. Since these distribution shifts are *in-support*, we don't need to learn a generative model for task distribution (i.e. a reward distribution model or a dynamic distribution model). Instead, we represent adversarial task distribution $q_\phi(\mathcal{T}) \propto w_\mathcal{T} p_{\text{train}}(\mathcal{T})$ as a re-weighted (empirical) training task distribution.

Figure 20 shows that DiAMetR outperforms RL^2, VariBAD and HyperX on test task distributions. Furthermore, the performance gap between DiAMetR and other baselines increase as distribution shift between test task distribution and train task distribution increases. Naturally, the performance of DiAMetR also deteriorates as the distribution shift is increased, but as shown in Fig 20, it does so much more slowly than other algorithms. Furthermore, Figure 21 shows that adaptively choosing an uncertainty set during test time works better when compared to selecting an uncertainty set beforehand or selecting a large uncertainty set.

Figure 20: We evaluate DiAMetR and meta RL algorithms (RL^2, VariBAD and HyperX) on different *in-support* shifted test task distributions. DiAMetR either matches or outperforms RL^2, VariBAD and HyperX on these test task distributions. The first point p_1 on the horizontal axis indicates the task parameter (Δ) distribution $\mathcal{U}(0, p_1)$ and the subsequent points p_i indicate task parameter (Δ) distribution $\mathcal{U}(p_{i-1}, p_i)$. While task parameter for `wind navigation` is wind velocity $w_\mathcal{T}$, it is target location $s_\mathcal{T}$ for other environments. Table 5 details the task distributions used in this evaluation.

M   Evaluations on dense reward environments

We test the applicability of DiAMetR on an environment with dense rewards. We use a variant of `Ant navigation`, namely `Dense Ant-navigation` for this evaluation. Furthermore, the shifted test task distributions are *in-support* of the training task distribution (see Table 5 for a detailed

Figure 21: Adaptively choosing an uncertainty set for DiAMetR policy (Adapt) during test time allows it to better adapt to test time distribution shift than choosing an uncertainty set beforehand (Mid). Choosing a large uncertainty set for DiAMetR policy (Conservative) leads to a conservative behavior and hurts its performance when test time distribution shift is low. The first point p_1 on the horizontal axis indicates the task parameter (Δ) distribution $\mathcal{U}(0, p_1)$ and the subsequent points p_i indicate task parameter (Δ) distribution $\mathcal{U}(p_{i-1}, p_i)$. While task parameter for `wind navigation` is wind velocity $w_\mathcal{T}$, it is target location $s_\mathcal{T}$ for other environments. Table 5 details the task distributions used in this evaluation.

Figure 22: We evaluate DiAMetR and meta RL algorithms (RL^2, VariBAD and HyperX) on different *in-support* shifted test task distributions of `Dense Ant-navigation`. DiAMetR either matches or outperforms RL^2, VariBAD and HyperX on these test task distributions. Furthermore, selecting a single uncertainty set (that is neither too small nor too large) is sufficient in `Dense Ant-navigation` as DiAMetR(Adapt) and DiAMetR(Mid) have similar performances (within standard error). The first point p_1 on the horizontal axis indicates the task target distance (Δ) distribution $\mathcal{U}(0, p_1)$ and the subsequent points p_i indicate task target distance (Δ) distribution $\mathcal{U}(p_{i-1}, p_i)$.

description of these task distributions). Figure 22 shows that DiAMetR still outperforms existing meta RL algorithms (RL^2, VariBAD, HyperX) on shifted test task distributions. However, the gap between DiAMetR and other meta RL algorithms is less than in sparse reward environments. Furthermore, Figure 22 shows that selecting a single uncertainty set (that is neither too small nor too large) is sufficient in `Dense Ant-navigation` as DiAMetR(Adapt) and DiAMetR(Mid) have similar performances (within standard error).

N   Learning meta-policies with different support

We can alternatively try to learn multiple meta-policies, each with small and different (but slightly overlapping) support. In this way, there won't be any conservativeness tradeoff. To analyze this further, we focus on point navigation domain (with train target distance distribution as $\Delta \sim \mathcal{U}(0, 0.5)$) and experiment with out-of-support test task distribution.

Let's say we are learning the i^{th} meta-policy (corresponding to ϵ_i). Let $q_\phi^{i-1}(z) = \mathcal{N}(\mu^{i-1}, \sigma^{i-1})$ be the learned adversarial task distribution for $(i-1)^{\text{th}}$ meta-policy (corresponding to ϵ_{i-1}). To learn meta-policies with small and different support, we make 2 changes to Algorithm 1:

1. In step 7, we do a rejection sampling $z \sim q_\phi(z)$ with the condition that $\log q_\phi^{i-1}(z) \leq \beta$ (where β is a hyperparameter. We found $\beta = -45$ to work well).

Figure 23: We investigate if learning meta-policies with different support (DiAMetR(Adapt-RS)) is better than learning meta-policies with overlapping support (DiAMetR(Adapt)). We evaluate it on two different families of shifted task distributions. While the left figure shows evaluations on shifted task distributions with different support (i.e. $\mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.55), \mathcal{U}(0.55, 0.6), \mathcal{U}(0.6, 0.65), \mathcal{U}(0.65, 0.7)$), the right figure shows evaluations on shifted task distributions with overlapping support (i.e. $\mathcal{U}(0, 0.55), \mathcal{U}(0.0, 0.6), \mathcal{U}(0.0, 0.65), \mathcal{U}(0.0, 0.7)$). While DiAMetR(Adapt-RS) performs the best on shifted task distributions with different support, DiAMetR(Adapt) performs the best on shifted task distributions with overlapping support. Hence, whether meta-policies should have overlapping support depends on the nature of shifted test task distributions.

2. In step 8 and 9, we add another constraint that $D_{\mathrm{KL}}(p_{\mathrm{train}}(z)||q_\phi(z)) \geq \epsilon_{i-1}$ (in addition to $D_{\mathrm{KL}}(p_{\mathrm{train}}(z)||q_\phi(z)) \leq \epsilon_i$). This leads to learning of two weighting factors λ_1 and λ_2 (instead of just λ) that tries to ensure $D_{\mathrm{KL}}(p_{\mathrm{train}}(z)||q_\phi(z)) \in (\epsilon_{i-1}, \epsilon_i)$. We call this modified algorithm as DiAMetR (Adapt-RS) (where RS comes from rejection sampling).

The performance of this variant depends heavily on the form of the test task distribution. We first test it on task target distance distributions $\mathcal{U}(0, 0.5), \mathcal{U}(0.5, 0.55), \mathcal{U}(0.55, 0.6), \mathcal{U}(0.6, 0.65), \mathcal{U}(0.65, 0.7)$ (essentially testing on *rings* of disjoint support around the training distribution). We see that DiAMetR(Adapt-RS) maintains a consistent success rate of ~ 1 across various target task distributions and outperforms DiAMetR(Adapt) and RL^2. This is because each meta-policy has overall smaller (hence are less conservative) and mostly different support and for this type of test distribution, this scheme can be very effective.

However, when we test it on task target distance distributions $\mathcal{U}(0, 0.5), \mathcal{U}(0, 0.55), \mathcal{U}(0.0, 0.6), \mathcal{U}(0.0, 0.65), \mathcal{U}(0.0, 0.7)$ (essentially testing on *discs* which mostly include the training distribution), we see that DiAMetR(Adapt-RS) performs same as RL^2 and mostly relies on the base RL^2 (i.e. $\epsilon = 0$) for its performance.

Whether meta-policies should have overlapping support will depend on the nature of shifted test task distributions. If supports of test task distributions overlap, then it's better to have meta-policies with overlapping support. Otherwise, it's more efficient to have meta-policies with different support.

O Meta-policy Selection with CEM during Meta-test

We explore using Cross-entropy method (CEM) [4] for meta-policy selection during meta-test phase, as an alternative to Thompson's sampling. Algorithm 4 details the use of the CEM algorithm for meta-policy selection. For this evaluation, we use `point navigation` environment where tasks vary in reward functions and test task distribution is *out-of-support* of training task distribution. Table 5 provides detailed information about these train and test task distributions. Figure 24 shows that CEM has similar performance as Thompson's sampling.

Algorithm 4 DiAMetR: Meta-test phase with CEM

1: Given: $p_{\mathrm{test}}(\mathcal{T})$, $\Pi = \{\pi_{\mathrm{meta},\theta}^{\epsilon_i}\}_{i=1}^M$
2: Sample $\pi \sim \Pi$ (with uniform probability) to collect 25 meta-episodes
3: Calculate $(\mu_\epsilon, \sigma_\epsilon)$ using 10 (of 25) (i.e. top 40%) meta-episodes with highest returns
4: **for** iter $t = 2, 3, ..., 10$ **do**
5:     **for** meta-episode $n = 1, 2, .., 25$ **do**
6:         Sample $\epsilon \sim \mathcal{N}(\mu_\epsilon, \sigma_\epsilon)$
7:         Choose ϵ_i closest to ϵ
8:         Run $\pi_{\mathrm{meta},\theta}^{\epsilon_i}$ for meta-episode
9:     **end for**
10:    Calculate $(\mu_\epsilon, \sigma_\epsilon)$ using 10 (of 25) (i.e. top 40%) meta-episodes with highest returns
11: **end for**

(a) $\Delta \sim \mathcal{U}(0.5, 0.55)$ (b) $\Delta \sim \mathcal{U}(0.55, 0.6)$ (c) $\Delta \sim \mathcal{U}(0.6, 0.65)$ (d) $\Delta \sim \mathcal{U}(0.65, 0.7)$

Figure 24: We compare use of Thompson's sampling (DiAMetR(Adapt)) and Cross-entropy method (Di-AMetR(Adapt, CEM)) for test time adaptation of DiAMetRon point robot navigation for various test task distributions. While they have similar performance, they are both better than test-time finetuning of RL^2. We run the adaptation procedure for 10 iterations collecting 25 rollouts per iteration.

P   Visualizing Imagined test reward distributions

By imagined test reward distributions, we mean the learned $q_\phi(z)$ as a result of solving equation 3 (i.e. resulting from the adversarial task distribution update in Algorithm 1). To generate an imagined reward function, we sample $z \sim q_\phi(z)$ and pass the z into $r_\omega(s, a, z) = r_\omega(s, z)$ (given the learned reward is only dependent on state as mentioned in Appendix C). We then take the agent (for instance the ant) and reset its (x, y) location to different points in the (discretized) grid $[-1, 1]^2$ and calculate $r_\omega(s, z)$ at all those points. This gives us a reward map for a single imagined reward function. We sample 10000 of

(a) $\epsilon = 0.1$ (b) $\epsilon = 0.2$ (c) $\epsilon = 0.4$ (d) $\epsilon = 0.8$

Figure 25: Imagined test reward distributions in `Ant-navigation` environment in increasing order of distribution shifts. Train reward distribution is uniform within the red circle.

these reward functions and plot them together. As ϵ increases, we see an increase in imagined reward functions that are peaky around target locations outside the train target location region (i.e. the red circle).

Q   Cost of learning multiple meta-policies during meta-train phase

Training a population of meta-policies mainly requires more memory (both RAM and GPU) as the meta-policies are trained in parallel. It is true that granularity of epsilon affects the performance of DiAMeTR (as argued in section 4.3). If we increase the number of trained meta-policies, even though DiAMetR's final performance on various shifted test task distribution would improve, it would take more time/samples for test-time adaptation. While choosing the number of trained meta-policies, we need to balance between final asymptotic performance and time/samples taken for test-time adaptation. The main benefit of learning a distribution of such meta-policies is that it amortizes over many different shifted test time distributions and the meta-policies do not need to be relearned for each of these.

R   Visualizing meta-policies chosen by Thompson's sampling

Figure 26 visualize meta-policies chosen by Thompson's sampling during meta-test for different test task distributions of `Ant navigation`. The test task distributions are *out-of-support* of training task distribution. Table 5 describes parameters for these distributions in detail.

Figure 26: ϵ values corresponding to meta-policies chosen by Thompson's sampling during meta-test for different test task distributions of `Ant navigation`. The first point r_{train} on the horizontal axis indicates the training target distance Δ distribution $\mathcal{U}(0, r_{\text{train}})$ and the subsequent points r_{test}^i indicate the shifted test target distance Δ distribution $\mathcal{U}(r_{\text{test}}^{i-1}, r_{\text{test}}^i)$.