COHERENCE EVALUATION OF VISUAL CONCEPTS WITH OBJECTS AND LANGUAGE

ABSTRACT

Meaningful concepts are the fundamental elements of human reasoning. In explainable AI, they are used to provide concept-based explanations of machine learning models. The concepts are often extracted from large-scale image data sets in an unsupervised manner and are therefore not guaranteed to be meaningful to users. In this work, we investigate to which extent we can automatically assess the meaningfulness of such visual concepts using objects and language as forms of supervision. On the way towards discovering more meaningful concepts, we propose the "**S**emantic-level, **O**bject and **La**nguage-Guided **C**oherence **E**valuation" framework for visual concepts (SOLaCE). SOLaCE assigns semantic meanings in the form of words to automatically discovered visual concepts and evaluates their degree of intelligibility on this higher level without human effort. We consider the question of whether objects are sufficient as possible meanings, or whether a broader vocabulary including more abstract meanings needs to be considered. By means of a user study, we confirm that our simulated evaluations highly agree with the human perception of coherence. They can improve over mere visual metrics, even when only relying on objects.

1 INTRODUCTION

A multitude of artificial intelligence (AI) systems are built on top of and heavily rely on visual concepts. This term refers to specific parts of an image that can be attributed a higher meaning and are human-interpretable, e.g., "feet", "stripes" or "water" (Bau et al., 2017). In particular, concept-based explanations (Kim et al., 2018; Koh et al., 2020) have gained popularity in computer vision recently. However, it remains an open question how such interpretable concepts can be discovered in the data set. Current, unsupervised approaches do not always yield sensible results (see Fig. 1) and there are no established methods to assess their quality without human effort. Recent theoretical insights show that unsupervised approaches fail to find disentangled representations without additional supervision (Locatello et al., 2019). Objects, which are fundamental for human understanding of visual scenes (Löwe et al., 2020) and can be such a form of weak supervision and allow learning meaningful representations (Wu et al., 2021). We follow the similar idea that *meaningful visual concepts have concise descriptions in natural language*, for instance, the name of an object they encode. If such a meaning can be found, it may serve as a certificate for the interpretability of the corresponding concept and allows to separate meaningful

(a) intelligible concept   (b) non-meaningful concept

Figure 1: Two discovered visual concepts by the ConceptSHAP approach (Yeh et al., 2019) on the Animals with Attributes (AwA) data set (Xian et al., 2018). The concept activation map (overlay) indicates the location of the salient parts. While the left one can be easily assigned a meaning "animal snout") the right one is hard to understand. In this work, we investigate to which degree we can automatically quantify their meaningfulness.

Figure 2: **Overview.** For concepts (consisting of example images and activation maps) that are learned by deep neural networks (DNNs) and automatically discovered post-hoc, **SOLaCE** first provides Semantic Annotations for their meanings in the form of words. Subsequently, it computes a Coherence Assessment for the concepts relying on these annotations and simulates human rating.

from non-meaningful ones. We investigate whether a state-of-the-art object-detection and a joint vision-language model can provide the meanings and allow for an automated coherence assessment on a higher, semantic level. We collect 2600 human assessments[1] of visual concepts and show that (1) a very high correlation of $\rho = 0.86$ between the human assessment and our method can be achieved and that (2) using only objects as possible meanings results in higher correlation than using a broader vision-language model that also covers more abstract concepts.

2 RELATED WORK

Many works on conceptual explanations leverage *supervised concepts*. In this case, the set of possible concepts is given by concept annotations in the data set indicating concepts present or absent (Koh et al., 2020; Kazhdan et al., 2020). Unfortunately, most data sets do not have these kinds of annotations, so the important concepts are usually unknown in advance. Therefore, a second strain focuses on *unsupervised concepts*. They are discovered in the data in an unsupervised or weakly-supervised manner and provided as a set of salient examples (Ghorbani et al., 2019; Yeh et al., 2019; Akula et al., 2020). Yet, the problem how to evaluate the interpretability of the concepts discovered has not been resolved. User studies are the most common way of evaluation but can be prohibitively expensive and prone to design errors (Doshi-Velez & Kim, 2017). Akula et al. (2020) perform an extensive user study to measure *Justified Trust* and *Explanation Satisfaction*. Ghorbani et al. (2019), Yeh et al. (2019) and Laina et al. (2020) also use a human ground truth. Unlike these works, our assessors require no human ground truth, but nevertheless align well with human evaluation. Our framework is most closely related to the *class describability* measure by Laina et al. (2020). The authors propose a modified image-captioning model to automatically find concept descriptions, but do not perform an automated assessment based on these. We continue their work by incorporating the discovered meanings in an automated evaluation.

Our approach is model-agnostic and efficient as it leverages pretrained object detection and vision-language models with broad coverage. Unlike previous works, it is fully automated. We therefore present a powerful tool to (1) automatically assign semantic meaning in the form of words to arbitrary provided concepts and (2) quantify the intelligibility and coherence of these visual concepts. In turn, this will allow to filter out non-meaningful concepts and to provide better explanations.

3 SEMANTIC ANNOTATION AND COHERENCE ASSESSMENT

Building on the related work, we propose the SOLaCE framework to automatically assess the coherence of visual concepts at the semantic level. Our method relies on two modules as depicted in Fig. 2

---

[1]We will make our data set publicly available upon acceptance.

that can be independently implemented: (1) A *Semantic Annotation Module* to map the concepts to their meanings in the form of a set of words (Sec. 3.2); (2) a *Coherence Assessment Module* which subsequently assesses the coherence of the concepts in a numerical rating (Sec. 3.3). Like previous work (Ghorbani et al., 2019), we consider only single words as meanings in this context. Additional details regarding the implementation of the modules can be found in Appendix B.

3.1 VISUAL CONCEPTS

In alignment with prior work, let $\{\boldsymbol{x}_1, \boldsymbol{x}_2, \ldots, \boldsymbol{x}_n\}, \boldsymbol{x}_i \in \mathbb{R}^{H \times W \times C}$ be a set of n example images salient for a certain concept (Kim et al., 2018). Each example has a width of W, height of H and C channels. Concepts are *local*, i.e., they are only present in a specific part of an image (cf. also Fig. 1). Mu & Andreas (2020) therefore consider a concept to be a function on the pixels in the input space that evaluates to true, if the concept is present in that pixel. We adopt their approach but allow continuous values in the range $[0, 1]$. Thus, for every example, we also require a concept activation map $\{\boldsymbol{s}_1, \boldsymbol{s}_2, \ldots, \boldsymbol{s}_n\}, \boldsymbol{s}_i \in [0, 1]^{H \times W}$, with values of 1 indicating the highest correspondence to the concept. Combining both parts, we define a concept $\mathcal{C}$ as a set of n tuples of images and their corresponding activation maps, $\mathcal{C} = \{(\boldsymbol{x}_1, \boldsymbol{s}_1), (\boldsymbol{x}_2, \boldsymbol{s}_2), \ldots, (\boldsymbol{x}_n, \boldsymbol{s}_n)\} \in \mathfrak{C}_n$. In our notation $\mathfrak{C}_n$ denotes the space of concepts given by n examples.

3.2 SEMANTIC ANNOTATION MODULE

The annotation module in our framework assigns k words from a user-defined dictionary Ω. Each word comes with a corresponding numerical matching score and represents the semantic *meaning* $\mathcal{M}$ of a visual concept. Thus, $\mathcal{M} = \{(w_j, \gamma_{w_j}) \mid j = 1 \ldots k, w_j \in \Omega, \gamma_{w_j} \in \mathbb{R}\}$, where w denotes the words and γ_w the scores. Let $\mathfrak{M}_k$ be the space of meanings with k items, such that $\mathcal{M} \in \mathfrak{M}_k$. Formally, the module is a function $\mathrm{Sem}(\cdot)$ mapping a concept of n examples to its semantic meaning represented by k words: $\mathrm{Sem} : \mathfrak{C}_n \to \mathfrak{M}_k$. We employ two different implementation of Sem:

Object-Centric Annotation Module (OC).   First, we consider a plain object detection model. We choose FasterRCNN (Ren et al., 2015) for this purpose and use the implementation provided by the Detectron2 framework (Wu et al., 2019). To keep the model as general as possible, we train on the Visual Genome data set (Krishna et al., 2017) with 3434 object categories remaining after classes with insufficient coverage are removed. We use the class names as our dictionary Ω. To assign scores γ_w, we compute the Soft Intersection over Union (IoU) score (inspired by Bau et al. (2017)) between the object bounding boxes for object type $w \in \Omega$ and the concept activation.

Joint Vision-Language Annotation Module (JVL).   Because the object detection model has a specific scope due to the data it is trained on, we investigate a joint vision-language embedding with broader support. Such a model $J : \mathbb{R}^{H \times W \times C} \times \Omega \to \mathbb{R}$ maps both words and images to the same latent space and returns a scalar similarity score. We use the CLIP model (Radford et al., 2021) that has proven highly successful on various language-supported zero-shot learning tasks.

The dictionaries deployed in this case user-defined and can be large (we use $|\Omega| \approx 10,000$ common words), which is an advantage over the OC model. For each word $w \in \Omega$ and $(\boldsymbol{x}_i, \boldsymbol{s}_i) \in \mathcal{C}$, the embedding model efficiently matches w to example $\boldsymbol{x}_i$ and estimates a score, $y_{i,w} = J(\boldsymbol{x}_i, w)$. We further adjust the scores by using attribution maps of the vision-language model for the words (GradCAM, Selvaraju et al. (2017)) to particularly find relevant words that are aligned with concept activation maps. The alignment over all examples used to compute the final scores γ_w.

All Annotation Modules return the highest-scoring k words along with their respective scores.

3.3 COHERENCE ASSESSMENT MODULE

Having identified the meaning $\mathcal{M}$, the coherence assessment module $f : \mathfrak{C}_n \times \mathfrak{M}_k \to \mathbb{R}$ maps the concept and the meaning to a numerical interpretability rating. Note that some implementations of assessment functions only rely on either the meaning of the concept examples and ignore the other input. We consider three implementations of the module as follows:

Best-Aligned Meaning (BAM). These assessor only relies on the meaning $\mathcal{M}$ and uses the score of the most meaningful word discovered, $f_{bma}(\mathcal{C}, \mathcal{M}) = \max_{(w_j, \gamma_j) \in \mathcal{M}} \gamma_i$. This value represents the maximum possible alignment of this concept and a specific word. By our hypotheses, concepts that are highly aligned with a word should be meaningful and the corresponding word can be seen as a certificate for their meaning.

Visual embeddings (VE). This measure does not take the meaning into account but relies on the visual inputs only. Given the set of n examples for a concept $\{\boldsymbol{x}_i \mid i = 1 \dots n\}$, we use embedding vectors $\{\boldsymbol{h}_i \mid i = 1 \dots n, \, \boldsymbol{h}_i \in \mathbb{R}^{2048}\}$ that are extracted from a pretrained ResNet50 (He et al., 2016). To incorporate the concept activation $\boldsymbol{s_i}$ we use an $\boldsymbol{s_i}$-weighted version instead of plain Global Average Pooling (Lin et al., 2014) in the ResNet to compute the embedding $\boldsymbol{h}_i$. We study two variants $f_{ve,mean}(\mathcal{C}, \mathcal{M}) = d_{mean}(\mathcal{C})$ and $f_{ve,min}(\mathcal{C}, \mathcal{M}) = d_{min}(\mathcal{C})$ that use coherence measures on the set of embeddings: d_{mean} denotes the mean cosine between pairs of visual embeddings $\boldsymbol{h}_i$ for a concept and d_{min} the minimum cosine between two embeddings from the same concept.

Hybrid assessors (HY). It is also possible to combine different assessors to hybrid ones. We therefore investigate a simple weighted sum of multiple coherence assessors f_i, $f_{hy}(\mathcal{C}, \mathcal{M}) = \sum_i \lambda_i f_i(\mathcal{C}, \mathcal{M})$. We use a train-test split to fit the weights λ_i on a data set of human assessments.

To compute the final score q of a concept, we call both models sequentially, $q = f(\mathcal{C}, \text{Sem}(\mathcal{C}))$.

4 EVALUATION RESULTS

4.1 EVALUATION OF THE JOINT-VISION-LANGUAGE ANNOTATOR (JVL)

While the Object-Centric Annotator (OC) used in our work is an established model that we use in an off-the-shelf fashion without modification, we have to validate the functionality of the Joint Vision-Language Annotator (JVL). We start by comparing its provided annotations to labeled concepts in the Broden data set (Bau et al., 2017) containing 1197 frequent visual concepts. However, only some of the concepts come with activation maps (others are merely indicated as present or not), and we leave out concepts that have less than 3 examples with more than 8 % of the image salient for this concept. By this procedure, we arrive at a set of 572 concepts along with examples and corresponding activation maps. Additionally, the concepts are named by words, which we use as our ground truth and vocabulary ($|\Omega| = 572$). We run different annotation modules to see to what extent they can discover the true names. First, we compare our JVL module to a supervised baseline, that predicts the presence or absence of each concept and determines the final outcome by voting. Our JVL approach attains 72.6 % top-5 accuracy, compared to 61.7 % for the supervised model. Furthermore, we implement the annotation module devised by Laina et al. (2020) based on an image-captioning model. Because its vocab is not restricted to Broden Concepts, we compare it to the JVL with 10000 frequent words as vocabulary. Our JVL obtains 37, 7 % top-5 accuracy versus 27, 2 % for the model by Laina et al. (2020) (cf. Appendix C.1 for details). We have thus verified that our Annotation Module is capable of identifying the most common visual concepts and outperformed other methods, which is why we only consider the JVL annotator and the OC annotator further.

4.2 CORRESPONDENCE TO HUMAN ASSESSMENT

Evaluation Data Set Collection To evaluate the devised measures, we are looking for a diverse set of concepts of varying quality that will be assessed both by humans and our proposed framework for their meanings and coherence. We use two publicly available image data sets. Places365 (Zhou et al., 2017) consists of 365 categories of places encountered in everyday life and features 1.8 million training images (we use Places365-Standard). Animals with Attributes (AwA) 2 (Xian et al., 2018) was originally devised for zero-shot learning and contains 50 classes of animals and 37322 images. We do not make use of any attribute information in the data.

We train a supervised ResNet50 model on each data set. Then we extract concepts using the ConceptSHAP approach (Yeh et al., 2019). Additionally, we use a simpler method that relies on k-Means clustering of image regions similar to (Ghorbani et al., 2019; Akula et al., 2020). For all approaches, we find the most salient patches by iterating through the data set and computing the activations. Because most of the concepts are meaningful to some extent, we artificially extend our data set with

	Coherence Assessor			
	Visual Embeddings (VE)		Best-Aligned Meaning (BAM)	Hybrid (HY) combine (BAM) + (VE)
Annotation Module	with d_{min}	with d_{mean}	-	d_{mean} used for (VE)
Object Centric (OC)	0.72 ± 0.02	0.83 ± 0.01	0.70 ± 0.02	$\mathbf{0.86 \pm 0.03}$
Joint Vision-Language (JVL)			0.39 ± 0.02	0.83 ± 0.02

Table 1: **Correlation score (Pearson's ρ) of our assessment with human rating for different annotators and assessors.** We obtain the highest score if we combine the BAM assessor using the OC annotation module with the best performing variant of the VE assessor.

more negatives. These are created by duplicating an existing concept and randomly mixing in 25 % or 50 % of examples from other concepts on the same data set. We obtain 40 concepts by the method of Yeh et al. (2019) (the hyperparameter they use), 50 from the k-Means clustering and 20 for each mix-in percentage. Doing so for each of the two data sets, this result in a total of 260 concepts.

Collection of Human Assessments We collected 10 independent ground-truth meanings and assessments for each of the 260 concepts from 10 students at an average age of 24.9 (± 2.1). They were asked to assess the concepts given by $n = 18$ examples along with their activation maps. We chose this number because it fitted well on standard FullHD screens in a 3-by-6-array. First, raters are asked to give the best-fitting word for each concept. We provided the top-4 words from each of the semantic annotation modules as a choice, but also gave the raters the opportunity to give their own word in a text box. Subsequently, we asked the user to rate the fit of to concept to their (best possible) one-word description on a scale of four options between *not at all* (0) to *very well* (3).

Evaluation of Coherence Assessors We implement the coherence assessment modules defined and evaluate their correspondence to human judgment. We use the Pearson coefficient of correlation ρ between the automated rating and the one given by the users. Because some of the assessors (the hybrid models) have trainable parameters and our data set size is limited, we use 5-fold cross-validation and report the average results and the corresponding standard error. Results for 10 folds can be found in the supplement and are qualitatively equivalent.

Our results in Tab. 1 show that all three assessors are significantly correlated with the human rating. For the Best-Aligned Meaning (BAM), correlation using the OC annotator is higher ($\rho = 0.70$) than that obtained with the JVL annotator. We attribute this gap to the Grad-CAM activation maps for the words in the joint embedding, that are often not as precise as the detections by the OC annotator. The reduced supervision and increased generality come at a price. We also observed that most of the descriptions the users chose for any concepts were indeed physical objects and seldomly more abstract concepts, testifying to the importance of objects for human reasoning. The assessments computed on mere visual embeddings (VE) show an even higher correlation with human judgment. However, is possible to combine the BAM and VE assessors to a hybrid model by computing fixed weights for each assessor which leads to an increased correlation of $\rho = 0.86$ on the test set. This highlights that taking the semantic meaning into account can be beneficial for the assessment. Furthermore, the annotated words make the explanation easier to process compared to a set of examples.

5 DISCUSSION AND OUTLOOK

We discovered that object detections and visual embeddings allow for automatic assessment of concept coherence and can be combined with an assessor that exhibits a significant correlation to human assessment. While the OC annotator provided objects and locations of higher quality, the JVL's larger scope makes it a strong competitor if more general annotations are required. We hypothesize that with better vision-language embedding models and localization maps, the correlation with the human rating can further be improved. Overall, we believe our work can be impactful in many domains, as it is among the first to quantify the degree of interpretability automatically and on the semantic level. We therefore think our SOLaCE framework will help lead the way towards more user-friendly AI systems.

REFERENCES

Arjun Akula, Shuai Wang, and Song-Chun Zhu. Cocox: Generating conceptual and counterfactual explanations via fault-lines. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 2594–2601, 2020.

Peter Anderson, Xiaodong He, Chris Buehler, Damien Teney, Mark Johnson, Stephen Gould, and Lei Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6077–6086, 2018.

David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network dissection: Quantifying interpretability of deep visual representations. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6541–6549, 2017.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, 2020.

Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3558–3568, 2021.

Finale Doshi-Velez and Been Kim. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*, 2017.

Amirata Ghorbani, James Wexler, James Y Zou, and Been Kim. Towards automatic concept-based explanations. In *Advances in Neural Information Processing Systems*, volume 32, pp. 9277–9286, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

MD Zakir Hossain, Ferdous Sohel, Mohd Fairuz Shiratuddin, and Hamid Laga. A comprehensive survey of deep learning for image captioning. *ACM Computing Surveys (CsUR)*, 51(6):1–36, 2019.

Andrej Karpathy and Li Fei-Fei. Deep visual-semantic alignments for generating image descriptions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3128–3137, 2015.

Dmitry Kazhdan, Botty Dimanov, Mateja Jamnik, Pietro Liò, and Adrian Weller. Now you see me (cme): concept-based model extraction. *AIMLAI workshop at the 29th ACM International Conference on Information and Knowledge Management (CIKM)*, 2020.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International conference on machine learning*, pp. 2668–2677. PMLR, 2018.

Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *International Conference on Machine Learning*, pp. 5338–5348. PMLR, 2020.

Stefan Kraft, Klaus Broelemann, Andreas Theissler, and Gjergji Kasneci. Sparrow: Semantically coherent prototypes for image classification. *British Machine Vision Conference (BMVC)*, 2021.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, Michael S. Bernstein, and Li Fei-Fei. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International Journal of Computer Vision*, 123(1):32–73, 2017.

Iro Laina, Ruth Fong, and Andrea Vedaldi. Quantifying learnability and describability of visual concepts emerging in representation learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

Zhuowan Li, Quan Tran, Long Mai, Zhe Lin, and Alan L Yuille. Context-aware group captioning via self-attention and contrastive features. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3440–3450, 2020.

Min Lin, Qiang Chen, and Shuicheng Yan. Network in network. *2nd International Conference on Learning Representations (ICLR)*, 2014.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *international conference on machine learning*, pp. 4114–4124. PMLR, 2019.

Sindy Löwe, Klaus Greff, Rico Jonschkowski, Alexey Dosovitskiy, and Thomas Kipf. Learning object-centric video models by contrasting sets. *arXiv preprint arXiv:2011.10287*, 2020.

David Mimno, Hanna Wallach, Edmund Talley, Miriam Leenders, and Andrew McCallum. Optimizing semantic coherence in topic models. In *Proceedings of the 2011 conference on empirical methods in natural language processing*, pp. 262–272, 2011.

Jesse Mu and Jacob Andreas. Compositional explanations of neurons. In *Advances in Neural Information Processing Systems*, 2020.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster R-CNN: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, volume 28, pp. 91–99, 2015.

Michael Röder, Andreas Both, and Alexander Hinneburg. Exploring the space of topic coherence measures. In *Proceedings of the eighth ACM international conference on Web search and data mining*, pp. 399–408, 2015.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Svitlana Vakulenko, Maarten de Rijke, Michael Cochez, Vadim Savenkov, and Axel Polleres. Measuring semantic coherence of a conversation. In *International semantic web conference*, pp. 634–651. Springer, 2018.

Yi-Fu Wu, Jaesik Yoon, and Sungjin Ahn. Generative video transformer: Can objects be the words? In *International Conference on Machine Learning*, pp. 11307–11318. PMLR, 2021.

Yuxin Wu, Alexander Kirillov, Francisco Massa, Wan-Yen Lo, and Ross Girshick. Detectron2. https://github.com/facebookresearch/detectron2, 2019.

Yongqin Xian, Christoph H Lampert, Bernt Schiele, and Zeynep Akata. Zero-shot learning—a comprehensive evaluation of the good, the bad and the ugly. *IEEE transactions on pattern analysis and machine intelligence*, 41(9):2251–2265, 2018.

Chih-Kuan Yeh, Been Kim, Sercan O Arik, Chun-Liang Li, Tomas Pfister, and Pradeep Ravikumar. On completeness-aware concept-based explanations in deep neural networks. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

Kaja Zupanc and Zoran Bosnic. Automated essay evaluation augmented with semantic coherence measures. In *2014 IEEE International Conference on Data Mining*, pp. 1133–1138. IEEE, 2014.

A   ADDITIONAL RELATED WORK

Semantic coherence in topic modeling.   Semantic coherence is an established research area in topic modeling for natural language texts and dialogues Mimno et al. (2011); Röder et al. (2015); Vakulenko et al. (2018). Many works propose different coherence measures of which a variety are listed for example in the works of Röder et al. (2015) and Zupanc & Bosnic (2014). In our paper, we attempt to transfer the insights of these works to the vision domain.

Joint Vision-Language Models.   With the recent advancement in language (Brown et al., 2020) and vision-language models (Radford et al., 2021; Changpinyo et al., 2021) trained on extremely large and generic data sets, in this paper we investigate whether such a model can provide the necessary supervision to quantify the semantic coherence of concepts. Our work exhibits some similarities with image captioning (Karpathy & Fei-Fei, 2015; Anderson et al., 2018; Hossain et al., 2019) and group captioning in particular (Li et al., 2020). We build on this work to obtain an interpretability score that corresponds to human assessment, which has not been investigated in this context.

Meaningfulness Evaluation of Visual Concepts.   Kraft et al. (2021) propose a variety of evaluation measures for automatically discovered prototypes, relying on their alignment with ground truth objects or parts. Using a set of single words as a meaning has been proposed as an evaluation by Ghorbani et al. (2019), but the words are still given by human annotators. We compare our annotation module to that of Laina et al. (2020).

B   IMPLEMENTATION

B.1   APPLICABILITY OF OUR DEFINITION

For manually or algorithmically annotated concepts in the form of segmentation masks, such as in the Broden data set (Bau et al., 2017), the activation value for the pixel is set to 1 if the corresponding pixel is annotated for a certain concept and to 0 otherwise. Furthermore, activations of feature maps in convolutional neural networks (CNNs) can be upsampled to the image resolution and normalized to match our framework. Thereby, concepts learned by convolutional filters can be considered. Works that define concepts as vectors in the latent space (Ghorbani et al., 2019; Yeh et al., 2019), can be put to the test by computing the similarity (commonly cos-similarity) of the latent vector for each patch with the concept vector (cf. Yeh et al. (2019) for details).

B.2   OBJECT-CENTRIC ANNOTATION MODULE (OC)

For the supervised annotation, we draw inspiration from the object detection model shown by Anderson et al. (2018), that can detect both objects and attributes. We preprocess the VG (Krishna et al., 2017) data set and aggregate the object categories and attributes according to the WordNet synsets provided with the data set. Because classes with few observations are almost never predicted, we remove attributes and objects with less than 8 occurances. By doing so, we arrive at 3434 (before: 7842) object classes, and 2979 (before: 6277) attributes. We then train the Faster-RCNN provided by Detectron2 (Wu et al., 2019), with the additional attribute branch proposed by Anderson et al. (2018). We use the following hyper-parameters different from Detectron2's default settings: We used a small of learning rate of 1×10^{-4} that is further decreased by a factor of 10 after 80k and 90k iterations. We observed training to be sufficiently converged after 100k iterations. Because wrongly detected objects seemed to harm the assessment less that objects that were not detected at all, we uses a very low detection threshold of 0.3 which results in many detections. We experimented with the attribute information as well, but didn't use it in the final experiments in this paper. The output of the predictor can be seen in Fig. 3.

We use the class names as our dictionary Ω and use the Intersection over Union (IoU) score (inspired by Bau et al. (2017)) between the object bounding boxes and the concept activation as alignment score. The final score γ_w for a word w is given by the sum of the IoUs over all concept examples. Therefore, let $\boldsymbol{b}_{i,w} \in \{0,1\}^{H \times W}$ be a binary vector indicating the pixels that are in the bounding boxes for object w in image example i. The final score γ_w for a word w is given by the sum of the

Figure 3: Detections from FasterRCNN on a randomly chosen example for the from the VG test set. The predicted attribute is shown in brackets before the object class but not used in the final annotator.

Figure 4: **Visual-semantic alignment in the zero-shot annotation module.** The example image corresponds well to multiple words. Thus, to find out the correct one, the concept activation map s_i (first picture) has to align with the activation $\boldsymbol{\alpha}_{i,w}$ of candidate words w (each of the following pictures). We see that higher alignment leads to better scores γ_w (cf. Eqn. 2).

IoUs over all concept examples:

$$\gamma_w = \frac{1}{|\mathcal{C}|} \sum_{(\boldsymbol{x}_i, \boldsymbol{s}_i) \in \mathcal{C}} \frac{\sum \min(\boldsymbol{s}_i, \boldsymbol{b}_{w,i})}{\sum \max(\boldsymbol{s}_i, \boldsymbol{b}_{w,i})} \tag{1}$$

The min and max operations are applied pixel-wise and summation is done over all pixels.

B.3 JOINT VISION-LANGUAGE ANNOTATION MODULE (JVL)

For JVL model, we use the pretrained CLIP model Radford et al. (2021) with the ResNet50 back-bone, because it provided the most reliable word activation maps. To come up with an extensive set of possible candidate works, we fuse several sources to obtain a powerful dictionary Ω:

1. Google 10000 frequent words [2]
2. VG list of classes [3]
3. Most common nouns in English [4]

We only keep nouns in the source 1 (by applying the tagger from WordNet). During development of user surveys, we observed that verbs or adjectives were almost never chosen. Additionally, we

---

[2] We used the document named "google-10000-english.txt" under the link https://github.com/first20hours/google-10000-english
[3] https://visualgenome.org/data_analysis/statistics
[4] https://7esl.com/list-of-nouns/

think that it is fairer to compare to the supervised FasterRCNN that also uses only nouns. In total, $|\Omega| = 10037$ for the experiments. The exact words are provided with our data set. We compute the scores $y_{i,w}$ for all words and the images pairs, which can be done very efficiently, because of the form of the zero shot model: $y_{i,w} = J(\boldsymbol{x_i}, w) = J(\boldsymbol{u}(\boldsymbol{x_i}), \boldsymbol{v}(w))$, where $\boldsymbol{u} \in \mathbb{R}^d$ is a visual embedding and $\boldsymbol{v} \in \mathbb{R}^d$ a text embedding. For the CLIP model we use, $d = 512$. The vectors have the same dimensionality, and simple dot-products can provide the similarity score $(\boldsymbol{u} \cdot \boldsymbol{v})$, that is normalized via a softmax function. Thus, for all words and images, we have to compute their latent representations only once, and can compute the scores by a matrix multiplication $\boldsymbol{Y} = \boldsymbol{U}\boldsymbol{V}^\top$, where $\boldsymbol{Y} \in \mathbb{R}^{n \times |\Omega|}$ holds all the scores, $\boldsymbol{U} \in \mathbb{R}^{n \times d}$ contains one visual embedding per line, and $\boldsymbol{V} \in \mathbb{R}^{|\Omega| \times d}$ holds one word embedding per line. Because the dictionary is the same for all concepts, $\boldsymbol{V}$ can be precomputed beforehand. Thus, to compute all scores for a concept, it is only necessary to compute the visual embeddings $\boldsymbol{U}$ of the examples, and matrix-multiply them with the present word-vectors.

Due to high computational costs, we do not keep all words after this stage, but preselect a set of promising candidates based on the $y_{i,w}$. For each image $\boldsymbol{x_i}$ in the concept, we add the top p words with the highest similarity scores $y_{i,w}$ to a set of candidate words. This results in at most $p \cdot n$ candidates though fewer are returned in practice due to words reappearing. The other words are not further considered.

To align visual and semantic activations, we also estimate an activation map $\boldsymbol{\alpha}_{i,w} \in \mathbb{R}^{H \times W}$ (normalized to $[0, 1]$) for each candidate word using GradCAM Selvaraju et al. (2017) on the model J. The final score of a word is given by the negative Mean-Squared-Error (MSE) between all concept and word activation maps

$$\gamma_w = -\frac{1}{|C|} \sum_{(\boldsymbol{x_i}, \boldsymbol{s_i}) \in \mathcal{C}} \text{MSE}(\boldsymbol{s_i}, \boldsymbol{\alpha}_{i,w}). \tag{2}$$

The example in Figure 4 illustrates this approach.

B.4 VISUAL EMBEDDINGS COHERENCE ASSESSOR (VE)

The visual embeddings we use in this work stem from a ResNet50 model pretrained on ImageNet, that comes with the PyTorch framework. In this specific architecture, after the forth (and final) residual layer, the input is transformed into a tensor $\boldsymbol{\Phi}$ of dimensionality $\boldsymbol{\Phi} \in \mathbb{R}^{r \times r \times d}$ (given an input size 448×448, $r = 14, d = 2048$). Usually, this tensor is global average pooled (this is mathematically equivalent to taking the mean values) over the first two dimensions, resulting in a feature vector $\boldsymbol{h}_i \in \mathbb{R}^{2048}$. To bring in the locality information $\boldsymbol{s}_i$, we do not take the mean of the spatial dimensions, but resample the activation map to the same resolution as the feature vectors before the pooling (e.g., $\hat{\boldsymbol{s}_i} \in \mathbb{R}^{r \times r}$). We further normalize $\hat{\boldsymbol{s}_i}$ to sum up to 1 and take the the final feature vector to be

$$\boldsymbol{h}[t] = \sum_{l=1}^{r} \sum_{m=1}^{r} \hat{\boldsymbol{s}_i}[l, m]\boldsymbol{\Phi}[l, m, t], \forall t = 1 \dots d, \tag{3}$$

a special weighted average. For the visual coherence assessor we use the following measures $f_{v,mean}$,

$$f_{v,mean}(\mathcal{C}, \cdot) = \frac{1}{n^2} \sum_{i=1}^{k} \sum_{j=1}^{k} \frac{\boldsymbol{h}_i \cdot \boldsymbol{h}_j}{\|\boldsymbol{h}_i\|\|\boldsymbol{h}_j\|}, \tag{4}$$

which returns the average cosine between cluster examples and the minimal cos of two cluster members,

$$f_{v,min}(\mathcal{C}, \cdot) = \min_{i,j=1\dots n} \frac{\boldsymbol{h}_i \cdot \boldsymbol{h}_j}{\|\boldsymbol{h}_i\|\|\boldsymbol{h}_j\|}. \tag{5}$$

C ADDITIONAL EVALUATION RESULTS AND DETAILS

C.1 EVALUATION THE JOINT VISION LANGUAGE ANNOTATION MODULE (JVL)

In this section we provide details on how we confirmed the functionality of our Joint Vision Language (JVL) Annotation Module on the Broden data set.

Model	Top-5 Acc.	Top-1 Acc.
CLIP (Full Vocab)	$20.6 \pm 0.2\,\%$	$7.8 \pm 0.1\,\%$
Laina et al.	$27.2 \pm 0.2\,\%$	$8.5 \pm 0.3\,\%$
JVL (Ours, Full Vocab)	$37.7 \pm 0.5\,\%$	$19.6 \pm 0.2\,\%$
CLIP (Domain Vocab)	$58.3 \pm 0.2\,\%$	$36.7 \pm 0.1\,\%$
Supervised Baseline	$61.7 \pm 0.5\,\%$	$27.4 \pm 0.2\,\%$
JVL (Ours, Domain Vocab)	$\mathbf{71.2} \pm 0.2\,\%$	$\mathbf{48.6} \pm 0.2\,\%$

Table 2: **Agreement of the JVL annotation module with ground-truth annotations for the Broden dataset.** Top-5 and top-1 accuracy are reported for the plain CLIP module (no alignment with concept activation map) the Model by Laina et al. (2020), a supervised predictor, and our JVL model, which performs well in this experiment.

First, we had to conduct some preprocessing. Because the Broden data set is a fusion of several sources, some labels appear in different forms of synonyms (e.g., {bus, autobus}), singular and plural (e.g., {door, doors}) and hyponyms and hyperomyms (e.g., {table, coffee table}). We manually merge those words together into 449 sets before running the experiment and consider the prediction as correct, if the word proposed is in the same merged set as the ground truth. We provide the unmerged results in the supplement and the list of sets along with our code, so other researchers can reproduce our findings and compare their results to ours. We consider the following models to assign words to sets of examples from Broden:

Ours   We implement our JVL annotation model with the proposed saliency map alignment with CLIP (ResNet50 backbone) as embedding model. We use a general purpose vocabulary ("Full Vocab", $|\Omega|{=}10037$) with the most frequent English nouns and a special purpose vocabulary that contains the names of the Broden concepts ("Domain Vocab", $|\Omega|{=}572$).

CLIP   We compare our results against a plain implementation of CLIP without our alignment step. This model just returns the word with the highest summed score $\sum_i y_{i,w}$. We use the same two dictionaries.

Supervised Baseline   Furthermore, we implement a supervised baseline model for multilabel classification on the Broden data that predicts presence or absence of each of the 572 concepts for each example image. The final concept-level predictions are found by summing up the predictions (ground truth concept absent or present) for each example image and returning the concept with the highest overall score.

Laina et al.   Finally, we put the group captioning model devised by Laina et al. Laina et al. (2020) to the test. It is trained on the Conceptual Captions data set as in the original paper and outputs entire sentence captions for a group of images. We count the prediction as correct, if the ground-truth name of the concept appears in the sentence predicted. Note that this is a slight advantage over other models as there are several words in the caption.

For each ground truth concept, we sample sets of $n = 30$ examples (or use all images if there are not enough) and compare the prediction of the model to the ground truth names. Results of the experiment on Broden can be found in Table 2. We first observe that our saliency alignment ("Ours") can considerably improve the top-1 and top-5 score of the plain CLIP for both vocabularies. This highlights the benefit of our suggested method to incorporate locality information. The general purpose captioning model by Laina et al. is listed between the plain CLIP and our method. Accuracy can be much improved by using the domain specific-vocabulary. In this setting, our method can even outperform the supervised model. Overall, we see that the actual meaning is listed in the top five words in about $70\,\%$ of the cases and comes in first in about half of the cases. Considering the fine-grained nature of the problem (500+ classes), these are highly respectable results that prove our annotation module to be powerful enough to detect common visual concepts.

	Method/Dataset	Places365	AwA	N
Average Ratings	Yeh et al.	**2.22**	1.34	400
	k-Means	2.20	**1.44**	500
	25 % mix-in	1.45	1.10	200
	50 % mix-in	0.90	0.90	200

Table 3: **Mean human ratings (0: worst, 3: best)** for concepts from different methods ("Yeh et al.", "k-Means") on two datasets ("Places365", "AwA"). N denotes the total number of human ratings per dataset and "mix-in" gives a percentage of artificially randomized samples per concept. Ratings on unaltered concepts are significantly better than with randomized samples.

	Coherence Assessor			
	Visual Embeddings (VE)		Best-Aligned Meaning (BAM)	Hybrid (HY) combine (BAM) + (VE)
Annotation Module	with d_{min}	with d_{mean}	-	d_{mean} used for (VE)
Object Centric (OC)	0.73± 0.02	0.83 ± 0.01	0.71 ± 0.02	**0.86 ± 0.03**
Joint Vision-Language (JVL)			0.37 ± 0.02	0.83 ± 0.02

Table 4: **Correlation score (Pearson's ρ) of our assessment with human rating for different annotators and assessors.** This table corresponds to Tab 1 but using 10-fold cross-validation.

C.2 AGREEMENT WITH HUMAN ASSESSMENT

Probing the data set   First, we report the average ratings by method and data set in Tab. 3. We observe that the mix-in concepts get a lower ratings than the actual concept discovery algorithms which further decreases when more random images are mixed in. The data set thus passes this basic sanity check. The concepts on the Places365 data set are better received than those on AwA. They often focus on specific objects or scenes. We see that the method devised by Yeh et al. (2019) fares marginally better on the Places365, but is outperformed by the simpler k-Means approach on AwA.

Agreement between raters   We observed that rating the coherence of a concept can be a highly subjective task. Therefore, we investigate to what extent the raters agree on an evaluation. We run a test on the variance of our ratings. In our null hypotheses, all ratings are indenpendently drawn from the overall distribution of ratings, with sample standard deviation $\sigma_s = 0.93$. We then compute the sample standard deviation of the ratings for a single concept and perform a Chi-Squared test, to check if it is significantly smaller than σ_s. If the variance of the ratings is significantly smaller, than it would be in a random setting, this indicates a non-random agreement among the raters. Using $p = 0.01, p = 0.05$, we obtain a non-random agreement for 58 % and 82 % of the concepts respectively. We also compute Cohan's κ for multiple item agreement. Note however that this measure neglects the order of the items and treats all disagreements (e.g., the ratings (0,3) and (0,1)) equally. We get a value of $\kappa = 0.25$ which testifies an agreement above chance level, but indicates also disagreement among raters.

Results under 10-fold cross-validation   In Table 4 we provide the correlations between by our assessment modules and the human ratings using 10-fold cross-validation. The qualitative results are the same as in our main paper.