Nearest Neighbor Radiomics for Self-Supervised Chest X-ray Pneumonia Identification

Abstract

Self-supervised training minimizes a contrastive loss objective for unlabeled data. Contrastive loss estimates the distance in the latent space between positive pairs, which are pairs of images that are expected to have the same label. For medical images, choosing positive pairs is challenging because simple transformations like rotations or blurs are not class-invariant. In this paper, we show that choosing positive pairs with nearest-neighbor radiomics features for self-supervised training improves chest X-ray pneumonia identification accuracy by 8.4% without labeled data.

Keywords: Contrastive Learning, Radiomics, Chest X-Ray, Pneumonia

1. Introduction

Many diseases including pneumonia, an infectious disease of the lungs, can be diagnosed by human interpretation of chest X-rays. However, variability in radiologists' interpretations has motivated the use of deep learning models (Neuman et al., 2012) for automatic disease identification. Because these models require large amounts of labeled training data (Saraiva et al., 2019), methods such as transfer learning (Kundu et al., 2021) and contrastive learning (Han et al., 2021), have been explored to improve accuracy without extra data labeling. For example, NNCLR maximizes the similarity between latent embeddings of positive pairs of images, which are nearest neighbors in embedding space (Dwibedi et al., 2021). Although successful for natural image classification, NNCLR and other contrastive learning techniques do not directly extend for medical image classification, because pairs of visually similar or geometrically transformed medical images can have profoundly different pathology.

Thus, we propose an approach for self-supervised training in medical imaging that maximizes similarity in latent embedding space between different images that have nearest neighboring radiomics features. Radiomics reduces an image to a set of biologically meaningful and radiologist-interpretable features (Tomaszewski and Gillies, 2021). We hypothesize that self-supervised training with nearest-neighbor radiomics will learn latent embeddings that reflect variation in radiomics features, which better predict pathology. In this paper, we discuss our approach and evaluate it on chest X-ray pneumonia identification.

2. Methods

We propose using positive pairs with nearest-neighbor radiomics (NN-radiomics) for self-supervised training of chest X-ray classification models. The end-to-end methodology is (1) pretraining on a general labeled dataset such as ImageNet, (2) self-supervised pretraining with NN-radiomics and an algorithm for self-supervised learning such as SimSiam (Chen and He, 2021), and (3) supervised fine-tuning on the available labeled data for the specific task such as pneumonia identification.

(a) End-to-End Methodology for Training Chest X-Ray Models with NN-Radiomics SSL.

(b) Architecture for SimSiam-based NN-radiomics SSL.

Figure 1: Nearest-Neighbor Radiomics (NN-Radiomics) Self-Supervised Learning (SSL)

2.1. Self-supervised Pretraining with Nearest-Neighbor Radiomics

We use an off-the-shelf image segmentation model to extract the lungs from each chest X-ray image (Selvan et al., 2020). Then, we compute standard radiomics features using PyRadiomics (Ferreira Junior, 2021). For each unlabeled image, we then find its nearest neighboring image using the computed radiomics features. This produces a set of positive pairs with nearest neighboring radiomics.

The model is then pretrained using any existing self-supervised algorithm, such as Sim-Siam - which we used - or BYOL, that uses a set of positive pairs.

2.2. Model Architecture

The model architecture (Figure 1(b)) for chest X-ray classification consists of an encoder and a classifier (not pictured). The encoder is a backbone model (ResNet18 (Kaiming He and Sun, 2016) pretrained on ImageNet) with a projection MLP head and the classifier is a linear layer with an output size of 1. The parameters of the encoder are learned in the self-supervised pretraining step, and the classifier is trained on frozen features from the backbone component of the encoder during the supervised finetuning step.

2.3. Experimental Setup

We evaluated self-supervised training with NN-radiomics on a chest X-ray model for pneumonia detection. We used a binary pneumonia identification dataset of 5856 chest X-rays (Kermany, 2018) that we randomly split into pretraining, finetuning, testing, and validation splits in a 7:2:0.9:0.1 ratio. The model was pretrained for 20 epochs and finetuned for 60.

3. Results

RQ1: Is NN-radiomics a high-quality indicator of task-specific positive pairs?
We found that in a dataset of 4172 chest X-rays, 85.69% of nearest neighbor radiomics (NN-radiomics) positive pairs have the same label (pneumonia vs. control). Furthermore, 65.91% with pneumonia have the same type of pneumonia (viral vs. bacterial). The high

Figure 2: Examples of positive pairs with nearest neighboring radiomics features.

percentage of NN-radiomics positive pairs with same labels motivates learning similar latent embeddings via contrastive learning for NN-radiomics positive pairs.

Table 1: Accuracy on Pneumonia Identification

Method	Accuracy (F1)	AUROC
Baseline	0.7996	0.9313
Pretraining w. Random Positive Pairs	0.8141	0.9311
Pretraining w. 1st-NN-Radiomics Positive Pairs	0.8669	0.9517
Pretraining w. 10th NN-Radiomics	0.8557	0.9572
Pretraining w. 50th NN-Radiomics	0.8381	0.9537

RQ2: Can self-supervised pretraining with NN-radiomics boost accuracy? Our results in Table 1 demonstrate a notable boost in accuracy by pretraining with NN-radiomics-based contrastive learning compared to the baseline of no pretraining.

RQ3: How does nearness of radiomics positive pairs affect accuracy? We conduct an ablation on n where the nth-nearest radiomics pairs are used for self-supervised learning. The results in Table 1 demonstrate that accuracy degrades as the positive pairs used are farther in radiomics space.

4. Conclusion

We present an approach to pretraining chest X-ray models without labeled data by using positive pairs that have nearest neighboring radiomics features. Our results demonstrate a notable improvement in pneumonia identification accuracy through self-supervised pretraining of chest X-ray models using nearest-neighbor radiomics.

Acknowledgments

Acknowledgments withheld.

References

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15750–15758, 2021.

Debidatta Dwibedi, Yusuf Aytar, Jonathan Tompson, Pierre Sermanet, and Andrew Zisserman. With a little help from my friends: Nearest-neighbor contrastive learning of visual representations. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9588–9597, 2021.

Cardona Cardenas D. A. Moreno R. A. de Sá Rebelo M. F. Krieger J. E. Gutierrez M. A. Ferreira Junior, J. R. Novel chest radiographic biomarkers for covid-19 using radiomic features associated with diagnostics and outcomes. *Journal of digital imaging*, 34(2): 297–307, 2021.

Yan Han, Chongyan Chen, Ahmed Tewfik, Ying Ding, and Yifan Peng. Pneumonia detection on chest x-ray using radiomic features and contrastive learning. In *2021 IEEE 18th International Symposium on Biomedical Imaging (ISBI)*, pages 247–251. IEEE, 2021.

Shaoqing Ren Kaiming He, Xiangyu Zhang and Jian Sun. Deep residual learning for image recognition. CVPR, 2016.

Kang; Goldbaum Michael Kermany, Daniel; Zhang. Labeled optical coherence tomography (oct) and chest x-ray images for classification. 2018.

Rohit Kundu, Ritacheta Das, Zong Woo Geem, Gi-Tae Han, and Ram Sarkar. Pneumonia detection in chest x-ray images using an ensemble of deep learning models. *PloS one*, 16 (9):e0256630, 2021.

Mark I Neuman, Edward Y Lee, Sarah Bixby, Stephanie Diperna, Jeffrey Hellinger, Richard Markowitz, Sabah Servaes, Michael C Monuteaux, and Samir S Shah. Variability in the interpretation of chest radiographs for the diagnosis of pneumonia in children. *Journal of hospital medicine*, 7(4):294–298, 2012.

Aratã Andrade Saraiva, D. B. S. Santos, Nator Junior C. Costa, José Vigno Moura Sousa, Nuno M. Fonseca Ferreira, António Valente, and Salviano Soares. Models of learning to classify x-ray images for the detection of pneumonia using neural networks. In *BIOIMAGING*, 2019.

Raghavendra Selvan, Erik B. Dam, Nicki Skafte Detlefsen, Sofus Rischel, Kaining Sheng, Mads Nielsen, and Akshay Pai. Lung segmentation from chest x-rays using variational data imputation. ICML Workshop on The Art of Learning with Missing Values, July 2020. arXiv preprint arXiv:2020.2005.10052.

Michal R Tomaszewski and Robert J Gillies. The biological meaning of radiomic features. *Radiology*, 298(3):505–516, 2021.