IN A NUTSHELL, THE HUMAN ASKED FOR THIS: LATENT GOALS FOR FOLLOWING TEMPORAL SPECIFICATIONS

ABSTRACT

We address the problem of building agents whose goal is to satisfy out-of distribution (OOD) multi-task instructions expressed in temporal logic (TL) by using deep reinforcement learning (DRL). Recent works provided evidence that the deep learning architecture is a key feature when teaching a DRL agent to solve OOD tasks in TL. Yet, the studies on their performance are still limited. In this work, we analyse various state-of-the-art (SOTA) architectures that include generalisation mechanisms such as relational layers, the soft-attention mechanism, or hierarchical configurations when generalising safety-aware tasks expressed in TL. Most importantly, we present a novel deep learning architecture that induces agents to generate latent representations of their current goal given both the human instruction and the current observation from the environment. We find that applying our proposed configuration to SOTA architectures yields significantly stronger performance when executing new tasks in OOD environments.

1 INTRODUCTION

Building agents capable of learning from human instructions while generalizing their knowledge to satisfy new specifications is a crucial goal of artificial intelligence (Oh et al., 2017; Bahdanau et al., 2019; Hill et al., 2021). Deep reinforcement learning (DRL) has achieved some impressive successes training autonomous agents in complex scenarios (Silver et al., 2017; Samvelyan et al., 2019), which motivates ongoing research with DRL agents following human instructions expressed in natural language (Yu et al., 2018; Mao et al., 2019; Hill et al., 2020). Unfortunately, generalisation in DRL is linked to training autonomous agents with large numbers of instructions requiring to build manually those natural language expressions and their corresponding reward functions, which prevents such methods from scaling efficiently (Lake, 2019; Vaezipoor et al., 2021).

These considerations inspired recent research on agents learning from formally specified instructions (Wen & Topcu, 2016; Alshiekh et al., 2018; Simão et al., 2021) as a substitute for natural language. Formal languages (Huth & Ryan, 2004) offer desirable properties such as unambiguous semantics and compositional syntax, allowing to automatically generate large amounts of training instructions and their corresponding reward functions. Earlier contributions in this area rely on the compositional nature of formal languages, often employing multiple policy networks to execute temporal logic (TL) instructions, e.g., one network per sub-task within the given instruction (Andreas et al., 2017; Icarte et al., 2018) or one per symbol and object (Kuo et al., 2020). However, these approaches do not scale well with the number of instructions since policy networks are a computationally costly resource and, consequently, these earlier studies are restricted to relatively small state-spaces environments that require less computation, e.g., non-visual settings. More recent contributions (León et al., 2020; Vaezipoor et al., 2021) have presented DRL frameworks that are capable of generalizing to large numbers of out-of-distribution (OOD, i.e., never seen during training) instructions while relying on a single policy network. These latter studies evidence that deep learning architectures within DRL agents are a key feature towards the ability to generalise formal instructions.

In this work, we present a novel deep learning configuration – that we call latent-goal architecture – improving the performance of DRL agents when executing OOD instructions. In previous literature, architectures are designed to process visual inputs and specifications through separated channels

before being forwarded to the final output channels. Unfortunately, DRL agents are known to struggle with generalisation, and may struggle even with task-similar specifications. Here we argue that the standard configuration can be replaced by one where we still keep two separated channels, one processing the visual image as before, but the other is a multi-modal channel that processes *both* visual input and human instruction. By constraining the amount of information forwarded from the multi-modal channel, the agent is induced to generate latent representations of their goal using not only the human instructions but also the current state of the system. We find that architectures using this configuration achieve stronger OOD generalisation with multiple networks in several settings.

Contributions.   Our contributions are listed as follows: i) We propose a new deep learning configuration (the latent-goal architecture) designed to help agents to generalise when learning to execute zero-shot, i.e., unseen, instructions in OOD environments. ii) We are first to evaluate the performance of multiple state-of-the-art (SOTA) neural networks targeting generalisation when following temporal logic instructions and provide evidence that these networks perform better in OOD environments when working with latent-goals. iii) Through ablation studies, we find that relational modules generating independent pieces of information within their output are specially benefited from being used within the novel architecture presented in this work.

The remaining of the paper is structured as follows: Section 2 briefly introduces the key concepts needed to follow this work. Section 3 presents our framework and the proposed deep learning configuration. Section 4 details the experimental settings, empirical results and ablation studies. Last, Sections 5 and 6 discuss related works and conclusions, respectively.

2   BACKGROUND

We develop agents aimed to execute OOD instructions expressed in TL while navigating in partially observable (p.o.) environments. Specifically, agents operate with a fixed perspective and a limited visual range. Below we introduce the basic concepts used in the rest of the paper.

Reinforcement learning.   Our p.o. environment is modelled as a p.o. Markov decision process.

Definition 1 (POMDP). *A p.o. Markov decision process is a tuple $\mathcal{M} = \langle S, A, P, R, Z, O, \gamma \rangle$ where (i) S is the set of states $s, s', \ldots$; (ii) A is the set of actions $a, a', \ldots$; (iii) $P : S \times A \times S \to [0, 1]$ is the* (probabilistic) transition function*; (iv) $R : S \times A \times S \to \mathbb{R}$ is the* reward function*; (v) Z is the set of observations $z, z', \ldots$. (vi) $O : S \times A \times S \to Z$ is the* observation function. *(vii) $\gamma \in [0, 1)$ is the* discount factor.

At each time step t, the agent chooses an action $a_t \in A$ triggering an update in the current state from s_t to $s_{t+1} \in S$ according to P. Then, $R_t = R(s_t, a, s_{t+1})$ provides the reward associated with the transition, and $O(s_t, a_t, s_{t+1})$ generates a new observation o_{t+1} for the agent. Intuitively, the goal of the learning agent is to choose the policy π that maximizes the expected sum of discounted rewards: $V^\pi(x) \stackrel{\text{def}}{=} \mathbb{E}_\pi \left[\sum_{t \geq 0} \gamma^t r_t \right]$, where $\gamma \in [0, 1)$ is the discount factor (see Sutton & Barto (2018)).

Relational networks.   A relational network (RelNet) is a particular kind of deep learning architecture whose structure is explicitly designed for reasoning about relations (Kemp & Tenenbaum, 2008). Previous contributions on solving formal instructions with DRL have been mainly focused on multi-layer perceptrons (MLPs) and recurrent networks (Goodfellow et al., 2016), yet RelNets are of particular interest in our context since they hold promise to improve generalization in DRL (Santoro et al., 2018). Their central principle is to constrain the functional form of the neural network in the relational module so that it captures the core common properties needed to reason about the relations between entities (e.g., objects) and their properties (e.g. color), see Santoro et al. (2017). Recently, relational networks have been enhanced with the inclusion of the widely-known key-value *attention* mechanism (Bahdanau et al., 2015). This method relies on the computation of attention scores that are used to decide in which portions of the input data the layer using this mechanism should focus on, see Vaswani et al. (2017).

3 LEARNING TO SOLVE SATTL INSTRUCTIONS

The following section details the main features of our method. We extend the neuro-symbolic framework from León et al. (2020), to work with safety-aware instructions. Sec. 3.1 introduces the specific formal language we use to procedurally generate instructions. Sec. 3.2 details the symbolic module that maps the progression of the formal instruction and accordingly generates rewards for the neural module, instantiated as a DRL algorithm. Finally, Sec. 3.3 details the latent-goal architecture.

3.1 SAFETY-AWARE TASK TEMPORAL LOGIC

The core attribute of temporal logic (Huth & Ryan, 2004) is the capability of expressing the evolution of a system from a state to the next. This expressivity makes TL a suitable formalism to account for reward functions depending on the satisfaction of a given instruction (Giacomo et al., 2020). We investigate agents learning compositionally TL instructions in a similar fashion to León et al. (2020) with task temporal logic (TTL), a learning-oriented TL language intended to deal with reachability goals only. Since here we tackle safety constraints as well, we extend TTL to safety-aware task temporal logic (SATTL).

Definition 2 (SATTL). *Let AP be a set of propositional atoms. The sets of literals l, atomic tasks α, and temporal formulas T in SATTL are inductiveley defined as follows:*

$$
\begin{aligned}
l &::= &&+p \mid -p \mid l \vee l \\
\alpha &::= &&lUl \\
T &::= &&\alpha \mid T; T \mid T \cup T
\end{aligned}
$$

Literals l are positive ($+p$) or negative ($-p$) propositional atoms, or disjunctions thereof. Atomic tasks α are obtained by applying the temporal operator *until* (U) to pairs of literals. An atom $\alpha = lUl'$ is read as *it is the case that l until l' holds*. Temporal formulas T are built from atomic tasks by using sequential composition (;) and non-deterministic choice ($\cup$). Note that U and $\cup$ are different operators. We use an explicit positive operator ($+$) so that both positive and negative tasks have the same length. This is beneficial for learning negative literals ($-p$) when instructions are given visually, as highlighted in (León et al., 2020). The temporal operators *eventually* $\diamond$ and *always* $\square$ can be respectively defined as $\diamond l \equiv \text{true} U l$ and $\square l \equiv l U end$, where end is a particular atom true only at the end of the episode. As TTL, SATTL is interpreted over finite traces λ, which in this context refers to finite sequences of states and actions. We denote time steps, i.e., instants, on the trace as $\lambda[j]$, for $0 \leq j < |\lambda|$, where $|\lambda|$ is the length of the trace. While, $\lambda[i, j]$ is the (sub)trace between instants i and j. A *model* is a tuple $\mathcal{N} = \langle \mathcal{M}, L \rangle$, where $\mathcal{M}$ is a POMDP, and $L : S \to 2^{AP}$ is a labelling of states in S with atoms in AP.

Definition 3 (Satisfaction). *Let $\mathcal{N}$ be a model and λ a finite path. We define the satisfaction relation $\models$ for literals l, atomic tasks α, and temporal formulas T on path λ as follows:*

$$
\begin{aligned}
(\mathcal{N}, \lambda) &\models +p &&\textit{iff} && p \in L(\lambda[0]) \\
(\mathcal{N}, \lambda) &\models -p &&\textit{iff} && p \notin L(\lambda[0]) \\
(\mathcal{N}, \lambda) &\models l \vee l' &&\textit{iff} && (\mathcal{N}, \lambda) \models l \textit{ or } (\mathcal{N}, \lambda) \models l. \\
(\mathcal{N}, \lambda) &\models lUl' &&\textit{iff} && \textit{for some } 0 \leq j < |\lambda|, (\mathcal{N}, \lambda[j, |\lambda|]) \models l', \textit{ and for every } t \in [0, j), \\
& && && (\mathcal{N}, \lambda[t, j-1]) \models l \\
(\mathcal{N}, \lambda) &\models T; T' &&\textit{iff} && \textit{for some } 0 \leq j < |\lambda|, (\mathcal{N}, \lambda[0, j]) \models T \textit{ and } (\mathcal{N}, \lambda[j+1, |\lambda|]) \models T' \\
(\mathcal{N}, \lambda) &\models T \cup T' &&\textit{iff} && (\mathcal{N}, \lambda) \models T \textit{ or } (\mathcal{N}, \lambda) \models T'
\end{aligned}
$$

Intuitively, by Def. 3 an atomic task $\alpha = c_\alpha U g_\alpha$ is satisfied if the "safety" condition c_α remains true until goal g_α is fulfilled. In the context of this work we are not interested in strict safety warranties but in agents trying to reach a goal while aiming to minimize the violation of additional conditions. Thus, we may say our agent has satisfied α even though it has not fulfilled c_α at every time step before g_α. Formally, in those cases we consider traces that are not starting at the beginning of the episode, but from the state after the last violation. The agent is penalised for this behaviour through the reward function. Examples of tasks we use are $\alpha_1 = -\text{grass} U (+\text{axe} \vee +\text{sword})$ "avoid grass until you reach an axe or a sword" and $\alpha_2 = (+\text{soil} \vee +\text{mud}) U \text{axe}$ "move through soil or mud until reaching an axe". It is not difficult to prove that SATTL is a fragment of the well-known Linear-time Temporal Logic over finite traces (LTL_f) (De Giacomo & Vardi, 2013). We provide a translation of SATTL into LTL_f and the corresponding proof of truth preservation in Appendix E.

3.2 Neuro-symbolic agents

Our framework consist of a symbolic module and a neural module. Intuitively, given a formal instruction T in SATTL, the symbolic module (SM) decomposes T into a sequence of atomic tasks α to be solved sequentially by the neural module (NM), which is instantiated as a DRL algorithm.

Symbolic module. Formally, the first component of the SM is the *extractor* $\mathcal{E}$, which transforms the complex formula T into a list $\mathcal{K}$ consisting of all the sequences of atomic tasks α that satisfy T. As it is common in the literature (Kuo et al., 2020; Vaezipoor et al., 2021), we assume that the SM have access to an internal labelling function $\mathcal{L}_{\mathcal{I}} : Z \to 2^{AP}$. $\mathcal{L}_{\mathcal{I}}$ is the restriction of $\mathcal{L}$ to the observation space and maps the observations of the agent in Z into the set AP of atoms. Intuitively the labelling function acts as an *event detector* that fires when the propositions in AP hold in the environment. The second functionality is the *progression function* $\mathcal{P}$, which given the output of $\mathcal{L}_{\mathcal{I}}$ and the current list $\mathcal{K}$, selects the next task α for the NM and updates $\mathcal{K}$. Once α is selected, the NM follows the given instruction until it is satisfied or until the time horizon is reached, while the role of the SM is to evaluate the fulfillment of the task based on the signals from $\mathcal{L}_{\mathcal{I}}$. From the outputs of $\mathcal{L}_{\mathcal{I}}$, the SM generates an internal reward function R_I, which provides a reward signal for the NM. Given a task α, R_I is defined so that the agent receives a positive reward ($+1$) if the goal condition becomes true ($\mathcal{L}_I(z_t) = g_\alpha$), a strong penalisation (-1) if the agent is neither satisfying the goal nor the safety condition ($\mathcal{L}_I(z_t) \neq g_\alpha$ or c_α), and a small penalisation (-0.05) if none of the previous is true. The latter penalisation is meant to encourage the agent to reach the goal. The pseudocode of the SM and its functions $\mathcal{E}$ and $\mathcal{P}$ are included in the supplemental material (Appendix A). Since the inner functioning of our symbolic module is analogous to the one presented in León et al. (2020), where authors show how the SM can process complex formulas T given a NM that has learnt to execute tasks α, we devote the remaining sections to the study of procedural tasks and the role of the deep learning architecture within the NM, which are the main scope of this work.

Neural module. The NM consists of a DRL algorithm interacting with the environment to maximize the discounted cumulative reward from R_I. All our agents use the same A2C algorithm, a synchronous version of A3C (Mnih et al., 2016). To facilitate a fair comparison, all the deep learning architectures use the same visual encoder and output layers for the respective benchmarks. Appendix C provides further detail about these features. As anticipated, the core of our approach is the deep learning configuration, detailed below.

3.3 Latent-Goal architectures

Literature about autonomous agents with generalisation-specialized architectures such as relational deep layers (Shanahan et al., 2020) or modular hierarchical networks (Mittal et al., 2020), commonly follows a standard model architecture set-up where the output of a visual encoder is passed through a central module (CM), which in our context is either a relational layer or an MLP, followed by a recurrent layer. Unfortunately, deep learning agents struggle to generalise instructions compositionally (Lake, 2019), even when generalizing between task-similar instructions. Consequently, we propose a configuration that induces agents to interpret instructions and the current state of the model together when deciding their goal, helping them to generalise more effectively.

As a motivation example, let us consider two scenarios : 1) a robot that is at the center of an empty room with a red square at the bottom right corner, 2) a robot at the same position in a room that is identical to the one in (1) except that the red square is now green. Intuitively, we can say that, if we give the instruction "go to the red square" in (1), the goal of the robot is the same as if we say "go to the green square" in (2), because the two tasks can be abstracted as "turn to face the bottom right of the room, then move straight". In a nutshell, computing the human instruction together with the current state of the environment – being at the center of the room, with the object asked by the human in the bottom right corner – allows to deduce that the optimal policy is the same in both scenarios.

Consequently, it can be beneficial for agents to compute both human instructions and sensory inputs in a dedicated channel, generating a latent representation of the current goal. We call this type of deep learning model a *latent-goal architecture*. Figure 1 right shows our proposed configuration when instructions are given as text; while Figure 1 left illustrates the standard architecture from previous literature for comparison (Hill et al., 2020; Küttler et al., 2020; Vaezipoor et al., 2021). In the former, the key feature is that the decision-making layers receive two input streams L_g and L_s. L_g refers

Figure 1: Model architectures. **Left:** standard architecture from previous literature. The central module can be either fully-connected or relational layers. Outputs $\pi(a_t)$ and V_t refer to the actor and critic respectively (Mnih et al., 2016). **Right:** proposed latent-goal architecture.

Figure 2: **Left:** a 7x7 Minecraft map (left) and its corresponding extended observation (right) with the visual instruction "move through either soil or stone until reaching an axe or a sword". Tasks are specified in the top of the extended observation by depicting objects and SATTL operators. Each tile has a resolution of 9x9 pixels. **Right:** a 22x22 map in MiniGrid where the agent needs to "avoid orange lava until reaching a gray or dark-green key". Instructions are given through a text channel and each tile has 8x8x3 pixels. Highlighted cells indicate the field of vision of the agent.

to the latent goal, i.e., a representation of the agent's current goal given the state and the human instructions, and L_s is a vector that represent all sensory input processed by the agent except for the instruction. For a latent-goal architecture to generalise effectively there are two central design properties: i) L_s should be task-agnostic, i.e., the layers computing L_s should have no access to what the current task is. ii) L_g should be passed through an information bottleneck, e.g., a low-dimensional fully-connected layer (FC). Condition i) forces the layers computing L_s to generate representations of the states as generic as possible. Granting no access to the current task these layers cannot discern which elements provide penalisation or rewards, encapsulating information in a fashion that facilitates generalisation when executing novel instructions. Condition ii) ensures that output layers rely on the generic representation from L_s to extract most of the data from the environment, while the layers processing L_g should focus on providing enough information about the goal.

4 EXPERIMENTS

Here we start presenting the experimental settings and continue with the main experimental results that highlighting the benefits of latent-goal models. We finish with ablation studies to better understand the inner working of the novel configuration.

Table 1: Results with either training (train) or OOD instructions in 500 maps (per size) of different dimensions. Note that sizes 14 and 22 are OOD for all the agents. MC refers Minecraft whereas MG to MiniGrid. Results show the average reward and standard deviation from 10 independent runs (i.r.). Values are normalized so that 100 refers to the highest performance achieved by the best run globally in maps of the given size and benchmark. Best average rewards in each setting and size is bolded.

Map-size	MLP		RN		MHA		PrediNet	
	Train	Test	Train	Test	Train	Test	Train	Test
MG-7x7	18.2(5.7)	14.1(3.6)	20.6(5.4)	18.7 (6.4)	**45.9**(26.6)	9.2(3.7)	19.1(12.2)	15.9 (7.3)
MC-7x7	33.4(7.9)	21.1(3.2)	5(1.9)	3.2 (1.6)	41.1(7.7)	**36.6**(4.3)	21.8(3.7)	16.1(3.5)
MG-14x14	28.6(8.2)	21.1(5.7)	28.6(6.2)	27.5(6.0)	**57.3**(17.8)	21.9 (4.7)	31.2(10.7)	25.6(7.3)
MC-14x14	38.7(6.5)	32.0(4.5)	8.3(2)	7.9(2.4)	51.7(9.3)	45.8 (7.6)	40.2(5)	31.9(6.2)
MG-22x22	27.8(8.5)	21.6(4.3)	26.9(10.1)	24.3(5.1)	**54.9**(23.6)	22.7(6.8)	32.1(8.9)	24.1(8.0)
MC-22x22	47.8(3.6)	37.8(3.8)	9.2(1.5)	8.3(1.8)	56.9(10.7)	49.2(5)	48.7(10.3)	38(8.5)

Map-size	MLP^{LG} (ours)		RN^{LG} (ours)		MHA^{LG} (ours)		PrediNet^{LG} (ours)	
	Train	Test	Train	Test	Train	Test	Train	Test
MG-7x7	23.6(5.5)	21.6(2.6)	22.6(3.3)	21.8 (2.8)	42.0(24.9)	15.4(3.5)	32.1(9.3)	**26.1**(5.8)
MC-7x7	40.2(5.7)	24.7(2.6)	4.4(1)	4.2 (0.7)	35.2(5)	31.6(5.3)	**55.2**(17.6)	29.5(8.2)
MG-14x14	31.4(4.2)	24.6(3.8)	30.1(6.1)	29.2(6.9)	50.4(14.9)	24.0 (9.4)	37.0(6.7)	**30.6**(5.5)
MC-14x14	41.7(5.1)	35.4(4.2)	13.1(2.6)	11.5(2.2)	48.1(4.4)	41.8 (4.9)	**67**(5.2)	**51.7**(6.5)
MG-22x22	31.0(6.3)	22.5(5.0)	34.2(2.3)	25.1(1.5)	53.3(21.4)	25.4(8.2)	39.9(2.7)	**29.7**(7.0)
MC-22x22	52.6(8.6)	41.3(7.7)	11.7(1.5)	10.7(2.1)	58.4 (4.5)	51.5(5.5)	**77.5**(9.1)	**65.3**(6.1)

Empirical settings. We use two benchmarks. The first one is a Minecraft-inspired environment – Minecraft for short – widely used in the RL-TL literature (Andreas et al., 2017; Vaezipoor et al., 2021). Particularly, we use the variant from León et al. (2020) that works with procedural maps and instructions. In this setting, instructions are visually given as part of the observation. The second benchmark is MiniGrid (Chevalier-Boisvert et al., 2018), which is also a procedural benchmark where instructions are given as text through a separated channel. Agents are trained in maps of random size $n \times n$, for $n = [7 - 10]$, and evaluated in maps of size $n = 7, 14, 22$. Figure 2 illustrates maps from both benchmarks. Instructions are SATTL tasks (see α_1 or α_2 in Sec. 3.1 for examples). We evaluate generalisation to unseen instructions, thus results under label "Train", refer to performance with training instructions, while "Test" to OOD instructions. In MiniGrid, where agents require grounding words to objects, OOD specifications are formed with combinations of symbols and objects that were explicitly excluded from training, e.g., if an OOD instructions has the safety condition "avoid orange lava" it means that both color "orange" and shape "lava" where only present in training instructions of the type "reach orange lava". In Minecraft, where tasks are depicted with objects themselves, OOD instructions refer to tasks with zero-shot, i.e., never seen, objects. Since specifications are human-given, we assume access to the resolution of the visual instructions and select an encoder generating a visual embedding where instructions are independent from the rest the observation. This allows the separation of the task from the rest of the observation, which is beneficial for the latent-goal architectures that generate task-agnostic streams of data. Both benchmarks have at least 200K tasks for training and 65K OOD specifications. Further detail is given in Appendix B.

Networks and baselines. All the networks used in the experiments follow either a standard or a latent goal configuration (see Sec. 3.3). The encoder is a convolutional neural network (CNN) (LeCun et al., 2015) while the recurrent layer in the output is either a long short-term memory (LSTM) (Hochreiter & Schmidhuber, 1997), that we use with multi-layered architectures, or a bidirectional recurrent independent mechanism (BRIM) in the case of hierarchical models. In MiniGrid, where instructions are given as text, we use a bidirectional LSTM (Schuster & Paliwal, 1997). In Minecraft, the CNN is meant to produce a visual embedding where instructions and observations are independent from each other, allowing to split the information. We consider four variants for the central modules within the architectures. The first one is a relation net (RN) from (Santoro et al., 2017), designed to dispense FC and LSTM layers with relational reasoning. The second module is a multi-head attention net (MHA) (Zambaldi et al., 2018), which combines relational connections with key-value attention. The third one is a PrediNet (Shanahan et al., 2020), also combining relational and attention operations but specifically designed to form propositional representations of the output. The fourth module is an MLP consisting of a single FC layer, which is meant to act as baseline against the relation-based modules. Additional information about the different networks is given in Appendix C.3.

Table 2: Results from 5 i.r. of a vanilla BRIM (BRIM), a BRIM with residual connection (ResBRIM) and BRIM with latent goals (BRIM^{LG}). Best results for each setting and size are in bold.

Map-size	BRIM		ResBRIM		BRIM^{LG} (ours)		Random walker
	Train	Test	Train	Test	Train	Test	
MG-7x7	19.6(6.2)	15.1(4.7)	19.2(4.8)	16.7 (3.6)	**23.8**(5.4)	**17.1**(5.3)	4.3(0.4)
MC-7x7	27.9(6.3)	15.6(2.8)	58.6(10.4)	15.8 (2.3)	**77.2**(19.5)	**26.4**(7.0)	3.7(0.1)
MG-14x14	25.3(5.4)	19.9(6.2)	33.7(3.9)	25.0 (1.4)	**38.8**(9.8)	**26.8**(5.6)	9.5(1.3)
MC-14x14	37.9(8.2)	26.5(6.7)	63.5(5.5)	39.6(7.0)	**77.3**(21.3)	**46.8** (8.1)	11.5(1.4)
MG-22x22	26.5(7.1)	20.0 (7.6)	27.9 (3.0)	25.3(2.1)	**48.5**(26.0)	**30.3**(6.6)	13.6(4.2)
MC-22x22	41.5(8.4)	29.3(4.1)	60.6(10.4)	40.7(8.2)	**79.8**(17.0)	**58.4**(14.8)	11.1(0.5)

Results with multi-layer architectures. Table 1 shows the performance of the different multi-layer networks (see Table 2 for the reference of a random walker). Results labelled with CM networks (e.g., "MHA") refer to standard configurations, whose CM uses the network of the label. Correspondingly, results with the LG superscript (e.g., MHA^{LG}) refer to latent-goal configurations with the networks of the corresponding type in the CMs. Overall, we see that the latent-goal architecture improves the performance of all the networks in most scenarios. We also observe that for OOD sizes ($n = 14$ and $n = 22$) the best results are obtained by the latent-goal variant with every network, except for the MHA in MC-14x14. In the hardest setting ($n = 22$), the best latent-goal model achieves 33% and 22% better performance compared to the best standard architectures in Minecraft and MiniGrid, respectively. The PrediNet is the network that benefits the most from the latent-goal configuration (up to 74%) and PrediNet^{LG} becomes clearly the best architecture. Noticeably, the two most different results with latent-goal models come from the networks that combine relational and attention mechanisms (MHA and PrediNet). This point if further examined in the ablation below.

Results with hierarchical architectures. We demonstrate that latent goals improve the performance of hierarchical architectures. Specifically, in line with the two design conditions highlighted in Sec. 3.3, we evaluate empirically a hierarchical architecture that restricts the amount of information shared between layers of different hierarchy, while providing instruction and observation data to the bottom layer of the architecture and a task-agnostic input of the environment to the top-level of the hierarchy (see Figure 4 in the Appendix for an illustration). In these experiments we fix the PrediNet as the default network for the different CMs – note that the PrediNet^{LG} achieved the best results in the previous evaluation – and replaced the last LSTM of the architectures with a BRIM network (Mittal et al., 2020). BRIM is a modularized hierarchical network that holds promise for OOD generalisation in RL. A particularly interesting feature of BRIMs for our method is that they employ a sparse attention mechanism to communicate between different hierarchies of layers. Specifically, each layer is composed of various modules, and at each time step only the top k modules (according to a key-value attention mechanism) will be able to communicate with modules from different layers, where k is a hyperparameter. Thus, when using latent goals with BRIMs we remove the FC layer that acted as information-bottleneck above. An illustration of the architectures using BRIMs is given in Appendix C.3. We do not perform any hyperparameter optimization with BRIMs and use directly the same configuration from the RL experiments in Mittal et al. (2020). Table 2 contrasts the performance when using a vanilla BRIM layer (BRIM) against using a residual connection (He et al., 2016) (ResBRIM) or latent goals (BRIM^{LG}). We see that inducing the latent goals significantly improves the performance of the hierarchical network in all settings. Hence, we see that deep hierarchical architectures can also capitalize on specialized hierarchy levels where bottom layers produce latent representations of the goal while the higher levels receive task-agnostic information of the state. This yields larger benefits than traditional residual connections, where the same information is given to every layer of the hierarchy.

Ablations. Contrasting MHA and PrediNet with their latent-goal counterparts, we see that the particular differences of the PrediNet with respect to the MHA internal functioning benefits the proposed latent-goal architecture. After a closer inspection, we see that the most significant difference comes from a channeling of the input within the PrediNet. This network encourages a kind of the semantic separation of the representations that it learns, making an element-wise subtraction of the extracted features, an operation not found in the MHA. Additionally, we see that the PrediNet modifies its output to explicitly represent positions of the pair of features selected by each of its heads,

Table 3: Ablation studies in Minecraft (5 i.r. per variant). $\text{PrediNet}^{\text{LG}}_{\text{noSub}}$ and $\text{PrediNet}^{\text{LG}}_{\text{noPos}}$ are variants of $\text{PrediNet}^{\text{LG}}$ without the element-wise subtraction and the feature coordinates respectively. PNMHA^{LG} uses an MHA in CM2 while MHAPN^{LG} uses an MHA in CM1. Best results are in bold.

Ablations	7x7		14x14		22x22	
$\text{PrediNet}^{\text{LG}}$ variants	Train	Test	Train	Test	Train	Test
$\text{PrediNet}^{\text{LG}}_{\text{noSub}}$	41 (8)	22.8 (2.8)	64.7 (7.9)	42.3 (6.9)	63.7 (7.8)	46.4 (8.1)
$\text{PrediNet}^{\text{LG}}_{\text{noPos}}$	**50.6** (9.9)	29.3 (5)	**68.2** (10.8)	**48.1** (5.4)	**70.6** (9.3)	**56.4** (9.2)
PNMHA^{LG}	39.3 (7.6)	29.2 (6.2)	52.8 (3.9)	46.5 (7.9)	64.6 (6.7)	45.2 (10)
MHAPN^{LG}	49 (10)	**36.6** (7.5)	59.9 (9.8)	45.6 (4.9)	57.4 (6.4)	51.6 (7.6)

Table 4: Ablation studies with $\text{PrediNet}^{\text{LG}}$ in Minecraft (5 i.r. per variant). In the first set we explore the impact of different bottleneck sizes. In the second we contrast having L_s task-agnostic or not. For every ablation set, best results are bolded.

Ablations	7x7		14x14		22x22	
Bottleneck size						
4	**57.0** (8.4)	**26.0** (10.9)	72.0 (15.7)	**60.4** (5.9)	74.8 (17.2)	58.3 (12.9)
16	51.2 (11.6)	25.3 (5.4)	**81.7** (17.9)	49.4 (12.6)	**86.1** (15.6)	**61.8** (10.3)
64	49.8 (10.2)	19.1 (5.7)	69.3 (14.3)	38.2 (10.9)	64.2 (15.1)	38.1 (13.3)
256	56.7 (14.7)	25.4 (11.3)	70.5 (13.0)	33.2 (9.5)	71.7 (6.7)	41.2 (17.3)
L_s data type						
Task-agnostic	**51.2** (11.6)	**25.3** (5.4)	**81.7** (17.9)	**49.4** (12.6)	**86.1** (15.6)	**61.8** (10.3)
Not Task-agnostic	48.1 (13.6)	23.0 (4.6)	58.7 (10.4)	33.7 (5.8)	52.8 (3.9)	44.4 (7.3)

also not present in the MHA. Table 3 inspects the impact of individually removing these distinct features within the PrediNet and whether the PrediNet is beneficial in both CMs or it is better to use an MHA in any of the modules. We find that the element-wise subtraction is the key feature within the PrediNet since its removal reduces the performance of $\text{PrediNet}^{\text{LG}}$ to that of an MHA^{LG}. None of the networks using an MHA in one of the CMs outperform having a PrediNet in both.

Regarding the outlayer of MHA in MC-14x14, we believe that receiving instructions not preprocessed by a recurrent layer is preventing the MHA to overfit as much as it does in MiniGrid, thus achieving better performance in maps of close-to-distribution size. Still, note that MHA^{LG} outperforms MHA in three out of four OOD results. As for the reason why the standard PrediNet does not outperform the MHA in the same line that $\text{PrediNet}^{\text{LG}}$ outperforms MHA^{LG}, from Shanahan et al. (2020) we note that at the core of the PrediNet information is organised into small pieces that are processed in parallel channels limiting the ways these pieces can interact. This pressures the network to learn representations where each separate piece of information has independent meaning and utility. The result is a representation whose component parts are amenable to recombination. Such feature is highly beneficial for generalisation, but supposes that the following recurrent layer needs to combine those pieces while producing a meaningful output for both actor and critic. As highlighted in Santoro et al. (2017), recurrent layers struggle when relating independent pieces of information. The latent-goal configuration alleviates this problem by decoupling the problem of goal abstraction and state representation into separated channels. Consequently, a latent-goal architecture helps to exploit the full potential of the highly re-usable outputs produced by PrediNets. Consequently, when substituting the element-wise subtraction with a FC layer (as we do with $\text{PrediNet}^{\text{LG}}_{\text{noSub}}$), the output is no longer generating independent pieces of information from the parallel channels, thus reducing their utility and aligning the representations obtained from the PrediNet with the ones generated by an MHA, which employs a single channel of information.

Last, Table 4 provides the results of ablation studies regarding conditions (i) and (ii) from Sec. 3.3. We observe that for larger bottleneck sizes the generalisation performance drops significantly as the agent no longer relies on the generic representations from L_s since biased information from L_g is no longer constrained. That is, larger bottlenecks do not limit the information passed through L_g biasing the agent towards the objects used in the training tasks. We see a similar degradation in performance when providing information about the task through L_s, confirming that the benefits are drawn on the generic representations from an input that cannot tell on its own which objects are beneficial or

dangerous. Additionally, we perform control experiments in Minecraft to verify that our agents are learning compositionally from the training instructions, specially with negation, which previous work (Hill et al., 2020; León et al., 2020) have found particularly challenging. We find evidence that with standard architectures only the MLP and MHA are correctly following the OOD tasks. In the case of architectures inducing latent goals we observe that MLP^{LG}, MHA^{LG} and PrediNet^{LG} are able to execute correctly the instructions when applied to OOD objects. Results and further discussion is given in Appendix D.

5 RELATED WORK

Applying RL to autonomous agents executing formal specifications has become a thriving area of research. The earliest works combining RL and TL focused on tackling temporally extended goals, naturally described as a non-Markovian reward decision process (NRMDP), by generating an equivalent extended MDP were RL algorithms can be applied (Bacchus et al., 1996). Recent contributions in this line investigate increasingly diverse and expressive languages (Brafman et al., 2018; Camacho et al., 2019) or multi-agent systems (León & Belardinelli, 2020; Hammond et al., 2021). Beyond TL, we find methods such as *reward machines* (a type of finite state machine) (Icarte et al., 2018; Xu et al., 2020; Icarte et al., 2019), or RL-specific formal languages such as SPECTRL (Jothimurugan et al., 2019). Closer to our line of work, Kuo et al. (2020) presents a novel RL framework to follow OOD combinations of known tasks expressed in linear-time temporal logic (LTL) by training multiple networks (one per LTL operator and per object). In a similar line, Araki et al. (2021) introduces a hierarchical reinforcement learning framework aimed to learn policies that are optimal and composable while relying on different neural networks each specialized in one subtask. León et al. (2020) provides evidence that a DRL agent relying on a single neural network can learn compositionally from the training instructions when the convolutional layers are designed according to the environment where agents operate. Vaezipoor et al. (2021) tackles a similar problem in non-visual scenarios by pretraining a neural network to learn to interpret LTL instructions in navigation-based environments. Our work advances the state-of-the-art in agents following formal instructions by presenting a novel network architecture that improves the performance of DRL algorithms in OOD environments.

Due to the multi-modular nature of the proposed configuration, our work also has links to modular frameworks. Modular configurations hold promise in improving generalisation through its natural compositionality (Jothimurugan et al., 2019). Examples of modular frameworks include DRL agents that combine general control policies, where a global controller is able to combine with different lower-level modules in series of locomotion tasks (Huang et al., 2020). Closer to this work Karkus et al. (2020) propose a framework that makes use of a perception and a planner networks to selects the most suitable human-given instruction for each time step to be forwarded to a controller network. This differs from our proposed framework, where latent goals are sparsely communicated and learned from scratch without using any predefined human tasks as embedding of the goal.

6 CONCLUSIONS

By relying on the assumption that human instructions can be separated from the sensory input, we have presented a novel deep learning configuration that induces situated agents to generate latent representations of their current goal. Particularly, we have seen that deep learning can draw on architectures where output layers take decisions based on both task-agnostic representations of the environment's state and the output of a channel that processes observations and human instructions together. This configuration induces the agent to produce abstract representations of their current complex goal, yielding a better OOD generalisation, as long as the channel processing both human instructions and observations is forced through a small-enough information bottleneck. We have provided evidence of the strong potential this configuration has with multiple networks and settings. Additionally, a detailed ablation have shown that networks producing independent and composable outputs are the most benefited from the proposed architecture. We believe our findings may have a broad impact within the communities working with DRL, OOD generalisation and formal methods. Further, this work poses interesting questions about task abstraction and generalisation. It also remains open how well DRL agents can generalise when the symbolic part may not provide reliable feedback on task progression. We think that addressing these questions, among many others, will push the boundaries of applicability in RL.

REFERENCES

Mohammed Alshiekh, Roderick Bloem, Rüdiger Ehlers, Bettina Könighofer, Scott Niekum, and Ufuk Topcu. Safe reinforcement learning via shielding. *Proceedings of the AAAI Conference on Artificial Intelligence*, 32(1), Apr. 2018.

Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 166–175. JMLR. org, 2017.

Brandon Araki, Xiao Li, Kiran Vodrahalli, Jonathan DeCastro, Micah J Fry, and Daniela Rus. The logical options framework. *International Conference of Machine Learning (to appear)*, 2021.

Fahiem Bacchus, Craig Boutilier, and Adam Grove. Rewarding behaviors. In *Proceedings of the National Conference on Artificial Intelligence*, pp. 1160–1167, 1996.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron C. Courville. Systematic generalization: What is required and can it be learned? In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Ronen I Brafman, Giuseppe De Giacomo, and Fabio Patrizi. Ltlf/ldlf non-markovian rewards. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Alberto Camacho, R Toro Icarte, Toryn Q Klassen, Richard Valenzano, and Sheila A McIlraith. Ltl and beyond: Formal languages for reward function specification in reinforcement learning. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 6065–6073, 2019.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

Noam Chomsky and David W Lightfoot. *Syntactic structures*. Walter de Gruyter, 2002.

Giuseppe De Giacomo and Moshe Y Vardi. Linear temporal logic and linear dynamic logic on finite traces. In *Twenty-Third International Joint Conference on Artificial Intelligence*, 2013.

Giuseppe De Giacomo, Marco Favorito, Luca Iocchi, Fabio Patrizi, and Alessandro Ronca. Temporal logic monitoring rewards via transducers. In Diego Calvanese, Esra Erdem, and Michael Thielscher (eds.), *Proceedings of the 17th International Conference on Principles of Knowledge Representation and Reasoning, KR 2020, Rhodes, Greece, September 12-18, 2020*, pp. 860–870, 2020. doi: 10.24963/kr.2020/89.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.

Lewis Hammond, Alessandro Abate, Julian Gutierrez, and Michael Wooldridge. Multi-agent reinforcement learning with temporal logic specifications. In *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 583–592, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pp. 770–778. IEEE Computer Society, 2016. doi: 10.1109/CVPR.2016.90.

Felix Hill, Andrew Lampinen, Rosalia Schneider, Stephen Clark, Matthew Botvinick, James L McClelland, and Adam Santoro. Environmental drivers of systematicity and generalization in a situated agent. In *International Conference on Learning Representations*, 2020.

Felix Hill, Olivier Tieleman, Tamara von Glehn, Nathaniel Wong, Hamza Merzic, and Stephen Clark. Grounded language learning fast and slow. In *International Conference on Learning Representations*, 2021.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8):1735–1780, 1997. doi: 10.1162/neco.1997.9.8.1735.

Wenlong Huang, Igor Mordatch, and Deepak Pathak. One policy to control them all: Shared modular policies for agent-agnostic control. In *International Conference on Machine Learning*, pp. 4455–4464. PMLR, 2020.

Michael Huth and Mark Ryan. *Logic in Computer Science: Modelling and reasoning about systems*. Cambridge university press, 2004.

Rodrigo Toro Icarte, Toryn Klassen, Richard Valenzano, and Sheila McIlraith. Using reward machines for high-level task specification and decomposition in reinforcement learning. In *International Conference on Machine Learning*, pp. 2112–2121, 2018.

Rodrigo Toro Icarte, Ethan Waldie, Toryn Klassen, Rick Valenzano, Margarita Castro, and Sheila McIlraith. Learning reward machines for partially observable reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 15497–15508, 2019.

Kishor Jothimurugan, Rajeev Alur, and Osbert Bastani. A composable specification language for reinforcement learning tasks. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 13021–13030, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/f5aa4bd09c07d8b2f65bad6c7cd3358f-Abstract.html.

Peter Karkus, Mehdi Mirza, Arthur Guez, Andrew Jaegle, Timothy Lillicrap, Lars Buesing, Nicolas Heess, and Theophane Weber. Beyond tabula-rasa: a modular reinforcement learning approach for physically embedded 3d sokoban. *arXiv preprint arXiv:2010.01298*, 2020.

Charles Kemp and Joshua B. Tenenbaum. The discovery of structural form. *Proc. Natl. Acad. Sci. USA*, 105(31):10687–10692, 2008. doi: 10.1073/pnas.0802631105.

Yen-Ling Kuo, Boris Katz, and Andrei Barbu. Encoding formulas as deep networks: Reinforcement learning for zero-shot execution of LTL formulas. *CoRR*, abs/2006.01110, 2020.

Heinrich Küttler, Nantas Nardelli, Alexander H. Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/569ff987c643b4bedf504efda8f786c2-Abstract.html.

Brenden M Lake. Compositional generalization through meta sequence-to-sequence learning. In *Advances in Neural Information Processing Systems*, pp. 9788–9798, 2019.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436, 2015.

Borja G. León and Francesco Belardinelli. Extended markov games to learn multiple tasks in multi-agent reinforcement learning. In Giuseppe De Giacomo, Alejandro Catalá, Bistra Dilkina, Michela Milano, Senén Barro, Alberto Bugarín, and Jérôme Lang (eds.), *ECAI 2020 - 24th European Conference on Artificial Intelligence, 29 August-8 September 2020, Santiago de Compostela, Spain, August 29 - September 8, 2020 - Including 10th Conference on Prestigious Applications of Artificial Intelligence (PAIS 2020)*, volume 325 of *Frontiers in Artificial Intelligence and Applications*, pp. 139–146. IOS Press, 2020. doi: 10.3233/FAIA200086. URL https://doi.org/10.3233/FAIA200086.

Borja G León, Murray Shanahan, and Francesco Belardinelli. Systematic generalisation through task temporal logic and deep reinforcement learning. *arXiv preprint arXiv:2006.08767*, 2020.

Jiayuan Mao, Chuang Gan, Pushmeet Kohli, Joshua B. Tenenbaum, and Jiajun Wu. The neuro-symbolic concept learner: Interpreting scenes, words, and sentences from natural supervision. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Sarthak Mittal, Alex Lamb, Anirudh Goyal, Vikram Voleti, Murray Shanahan, Guillaume Lajoie, Michael Mozer, and Yoshua Bengio. Learning to combine top-down and bottom-up signals in recurrent neural networks with attention over modules. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6972–6986. PMLR, 2020.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

Junhyuk Oh, Satinder Singh, Honglak Lee, and Pushmeet Kohli. Zero-shot task generalization with multi-task deep reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2661–2670. JMLR. org, 2017.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder de Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2186–2188. International Foundation for Autonomous Agents and Multiagent Systems, 2019.

Adam Santoro, David Raposo, David G. T. Barrett, Mateusz Malinowski, Razvan Pascanu, Peter W. Battaglia, and Tim Lillicrap. A simple neural network module for relational reasoning. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 4967–4976, 2017.

Adam Santoro, Ryan Faulkner, David Raposo, Jack W. Rae, Mike Chrzanowski, Theophane Weber, Daan Wierstra, Oriol Vinyals, Razvan Pascanu, and Timothy P. Lillicrap. Relational recurrent neural networks. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pp. 7310–7321, 2018.

Mike Schuster and Kuldip K Paliwal. Bidirectional recurrent neural networks. *IEEE transactions on Signal Processing*, 45(11):2673–2681, 1997.

Murray Shanahan, Kyriacos Nikiforou, Antonia Creswell, Christos Kaplanis, David G. T. Barrett, and Marta Garnelo. An explicitly relational neural network architecture. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8593–8603. PMLR, 2020.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *arXiv preprint arXiv:1712.01815*, 2017.

Thiago D Simão, Nils Jansen, and Matthijs TJ Spaan. Alwayssafe: Reinforcement learning without safety constraint violations during training. In *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 1226–1235, 2021.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Pashootan Vaezipoor, Andrew Li, Rodrigo Toro Icarte, and Sheila McIlraith. Ltl2action: Generalizing ltl instructions for multi-task rl. *International Conference of Machine Learning (to appear)*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Min Wen and Ufuk Topcu. Probably approximately correct learning in stochastic games with temporal logic specifications. In *IJCAI*, pp. 3630–3636, 2016.

Zhe Xu, Ivan Gavran, Yousef Ahmad, Rupak Majumdar, Daniel Neider, Ufuk Topcu, and Bo Wu. Joint inference of reward machines and policies for reinforcement learning. In *Proceedings of the International Conference on Automated Planning and Scheduling*, volume 30, pp. 590–598, 2020.

Haonan Yu, Haichao Zhang, and Wei Xu. Interactive grounded language acquisition and generalization in a 2d world. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, et al. Deep reinforcement learning with relational inductive biases. In *International Conference on Learning Representations*, 2018.

Algorithm 1 Extractor function that obtains the the list of all the possible sequences of tasks

---

1: **Function** $\mathcal{E}$**, Input:** T
2: Initialize the list for the sequences of tasks $\mathcal{K}$
3: **for** each atomic task $\alpha \in T$ **do**
4:   **if** α is atomic positive or negative **then**
5:     **for all** $Seq \in \mathcal{K}$ **do**
6:       Seq.append(α)
7:     **end for**
8:   **else**
9:     // There are non-deterministic choices
10:     Initialize choice list: CL
11:     $LK \leftarrow length(\mathcal{K})$
12:     **for all** $Seq \in \mathcal{K}$ **do**
13:       **for all** choice $\in \alpha$ **do**
14:         CL.append(choice)
15:         Generate a clone per choice $Seq' \leftarrow Seq$
16:         $\mathcal{K}$.append(Seq')
17:       **end for**
18:     **end for**
19:     Initialize counter $c \leftarrow -1$
20:     **for** i in **range**($length(\mathcal{K})$) **do**
21:       **if** $i\% LK == 0$ **then**
22:         $c += 1$
23:       **end if**
24:       We append a different choice to each sequence cloned $\mathcal{K}[i]$.append($CL[c]$)
25:     **end for**
26:   **end if**
27: **end for**
28: **return** $\mathcal{K}$

A THE SYMBOLIC MODULE

In this section we include the pseudo-code of the of the extractor ($\mathcal{E}$) and progression ($\mathcal{P}$) functions of the symbolic module (SM), whose procedures are explained in Sec. 3.2 of the main text.

Algorithm 1 details the Extractor $\mathcal{E}$. Given the complex instruction T, $\mathcal{E}$ generates a list $\mathcal{K}$ with all the possible sequences of tasks α that satisfy T. Note that α are the tasks that the neural module (NM) is expected to learn/solve compositionally. Algorithm 2 refers to the Progression function $\mathcal{P}$, which updates $\mathcal{K}$ according to the true evaluation p_α given by the internal labelling function $\mathcal{L}_I$, that indicates to the SM how the previous task has been solved, and selects the next task α'.

B ENVIRONMENT DETAILS

Below expand the description of the benchmarks introduced in the main text:

Minecraft-inpired. In this environment agents have four actions: $Up, Down, Left, Right$ to move one square from their current position, according to the given direction. Specifically, we use a configuration where maps are procedurally generated by randomly selecting populations of objects, their placement and agent's starting position, and where each tile within has a resolution of 9x9 gray (1 channel) pixels. We generate 50 objects split into various sets. Each object is represented by a matrix of 9x9 values. These values were procedurally generated with pseudo-aleatory numbers (we used a fixed seed). The global set of objects is referred to as $\mathcal{X}$, where the total number of objects is $|\mathcal{X}| = 55$. The set is partitioned into pretraining set $|\mathcal{X}_1| = 35$, training set $|\mathcal{X}_2| = 20$ and a test set $|\mathcal{X}_3| = 20$, where $\mathcal{X} = \mathcal{X}_1 \cup \mathcal{X}_3$, $\mathcal{X}_2 \subset \mathcal{X}_1$ and $\mathcal{X}_1 \cap \mathcal{X}_3 = \emptyset$.

MiniGrid. In this environment there are three possible actions: $Move\ Straight$, $Turn\ Left$, $Turn\ Right$. Here objects are formed from compositions of colors and shapes. We expand the

---

Algorithm 2 Progression function that returns the next task to be solved.

```
 1: Function 𝒫, Input:𝒦, p_α
 2: if p_α ≠ ∅ then
 3:     for all Seq ∈ 𝒦 do
 4:         if p_α fulfills Seq[0] then
 5:             Seq.pop(Seq[0])
 6:         else
 7:             𝒦.pop(Seq)
 8:         end if
 9:     end for
10: end if
11: α' ← ∅
12: if 𝒦 == ∅ then
13:     return α'
14: else
15:     Select the head of the first sequence: α' ← 𝒦[0][0]
16:     for all Seq ∈ 𝒦 do
17:         // look for a non-deterministic choice
18:         if α' & Seq[0] can be combined then
19:             α' ← α' ∪ Seq[0]
20:         end if
21:     end for
22: end if
23: return α'
```
---

number of shapes and from MiniGrid to have eleven colors and eight shapes. We refer to the total set of colors and shapes as C and F respectively. We also divide the global set of instructions in four categories as follows:

- Reachability atomic goals, which have the form "$True\ U + p$".

- Negative reachability goals, e.g., "$True\ U - p_1 \vee -p_2$" or "$True\ U - p$".

- Positive instructions such as "$+ p_1\ U + p_2$" or "$+ p_1 \vee + p_2\ U + p_3 \vee + p_4$".

- Negative conditions, e.g., "$- p_1\ U + p_2 \vee + p_3$".

With atomic reachability goals we use sets C_1 and F_1 while training and C_2 and F_2 for testing, where $|C_1| = 8$, $|F_1| = 6$, $C = C_1 \cup C_2$, $C_1 \cap C_2 = \emptyset$, $F = F_1 \cup F_2$ and $F_1 \cap F_2 = \emptyset$. The remaining categories of instructions use C_3, F_3 in training and C_4, F_4 for testing, where $|C_3| = 8$, $|F_3| = 6$, $C = C_3 \cup C_4$, $C_3 \cap C_4 = \emptyset$, $F = F_3 \cup F_4$ and $F_3 \cap F_4 = \emptyset$. Also, $C_2 \subset C_3$, $C_4 \subset C_1$, $F_2 \subset F_3$ and $F_4 \subset F_1$. Intuitively, we use reachability goals to ground some shapes and color for our agents, and the rest of the instructions for the remaining elements. Then we test the agents with the unseen colors and shapes for each category.

Experiment Architecture. All the agents in this work use a pretrained encoder. While pretraining we use only instrucitons of the form $\diamond l = trueUl$, with objects from $\mathcal{X}_1$ in Minecraft, or C_1 and F_1 in MiniGrid. This pretraining stage helps the encoder to differentiate objects within the environment. Once pretrained, the encoder remains frozen to prevent overfitting. The training stage is 70M timesteps in Minecraft or 50M in MiniGrid, with maps of training size and populated with objects from the training sets. For testing, all the training parameters are frozen and the agents are evaluated in sets of 500 maps populated with OOD objects from the test sets. At the beginning of each episode, a task α is procedurally generated (e.g., α_1 or α_2 above). Train and test tasks are generated with objects from the corresponding set. In Minecraft, tasks include zero-shot (i.e., unseen) objects. Once we selected a task, a new map is generated where the agent is placed in an aleatory position, some or all the goal objects are randomly placed and some or all the objects for the constraint are also randomly placed. Additional objects from the corresponding set are also included in the map as distractions.

Figure 3: Training plots of the networks studied in Sec 4. Continuous lines correspond to the 50^{th} percentiles while the shadowed areas are the 25^{th} and 75^{th} percentiles. Note that good train performances do not yield to similarly good test results as detailed in the main text. **Left:** Minecraft training plots. **Right:** MiniGrid plots. Note general performance drop at 20M in this setting is motivated by the higher chance of generating larger training maps from that point on.

C   EMPIRICAL DETAIL

Here we include further details about the empirical evaluation. The final version of the paper will include a link to the the published code.

C.1   HARDWARE

For training we use various computing clusters with GPUs such as Nvidia Tesla K80, and GTX 1080. We employ Intel Xeon CPUs and 7700k and consume 5 GB of RAM per every three independent runs working in parallel. Running concurrently, each experiment typically takes 3 days to train, 4 days in the case of latent-goal configurations.

Note that these environments are specially suited for agents capable of relational reasoning (Kemp & Tenenbaum, 2008), i.e., for an agent to perform well it needs to 1) *relate* the objects that appear in the first rows of the visual input and their relative positions with respect to the SATTL symbols and 2) relate the instruction with what it perceives around itself. For more details about hyperparameters,

Figure 4: **Top:** vanilla BRIM and ResBRIM (without and with the residual connection respectively). Green cells within the BRIM layer refer to activated modules while gray cells are deactivated. The bottom layer receives as input the output of the central module and the hidden state from the upper layer in the previous time step (h'_{t-1}). The upper layer receives the output from the bottom layer (h_t). Only strong connections (the ones between activated modules) are shown. In the case of ResBRIM the upper layer also receives the output of the Central module. **Bottom:** BRIM^{LG}. The architecture is similar to the ResBRIM but the top layer receives as additional input an embedding from the observation exclusively (L_s). Consequently, the top layer has only access to the current goal through the lower layers of the hierarchy.

environments, hardware and computing time we refer to Appendix C in the supplemental material together with the code.

C.2 RL HYPERPARAMETERS

All of our agents are trained with A2C. Specifically, we use a discount factor $\gamma = 0.99$, a value loss weight of 0.5 and a batch size of 512. We work with a scheduled learning rate using a starting value of $8e^{-5}$, $6e^{-5}$ at the step 30 M, and $4e^{-5}$ at 55 M. In the case of BRIMs, which are significantly larger networks, we use a constant learning rate of $3e^{-5}$. These values offered the best results when testing after a grid-search in a range values between $1e^{-5}$ and $1e^{-3}$. The entropy-exploration term was fixed to $H = 1e^{-3}$ after testing with values in the range $[1e^{-5}, 1e^{-2}]$.

C.3 NETWORKS

Our models use 3-layer convolutional networks in both settings. Particularly, in Minecraft we use a kernel of 3x3 in the first and second layers and 1x1 in the third one. The number of channels in each layer are 8, 16 and 1 while the strides are 3, 3 and 1 respectively. Note that this encoder has been designed bearing in mind the resolution of the tiles within so that the latent representations (i.e., the outputs of the encoder) of the tasks are independent from the latent representations of the original observation z. This inductive bias is exploited in the latent-goal architectures. In MiniGrid all kernels and strides are of size 2. The number of channels are 16, 32 and 32 respectively. Note that encoders

Table 5: Study on compositional learning with zero-shot objects and instructions. Results show the performance obtained by each network in 200 test maps when rewards are given according to the "real goal", while the symbolic module provides the "given instruction" to the neural module. An agent learning compositionally should have 1^{st} row > 2^{nd} row > 3^{rd} row for the values within its column. Also, values lower than random are only acceptable in the third row (deceptive instruction). The mean performance of a random walker is 12.5 independently of the "given instruction".

				Real goal: $-cU+p$				
Given instruction	MLP	MLP^{LG}	RN	RN^{LG}	MHA	MHA^{LG}	PrediNet	PrediNet^{LG}
$-cU+p$	44.6(10.5)	70.6(11.9)	14(1.1)	13.9 (1)	55.8(6.1)	43.8(7.3)	17.5(1.2)	43.6(9.3)
true $U+p$	20.3(5.7)	18.0(4.6)	13.3(0.9)	13.9(1.4)	16.9(3.0)	19.9 (6.3)	19.9(3.4)	17.5(3.8)
$+cU+p$	8.7(1.6)	11.0(2.6)	7.9(2.2)	5.6(1.2)	10.8(2.6)	15.0(3.6)	8.2(1.8)	8.4(1.2)

are pretrained and then frozen. With MiniGrid's text instructions we use a bidirectional recurrent layer of size 32. In multi-layer configurations the other two recurrent layers are LSTMs of size 128. The information bottleneck is a FC layer of size 16.

For the central modules in the multilayered architectures, we use the best hyperparameters from a previous ablation study in Shanahan et al. (2020). Particularly, in the case of the MLP we use a single fully-connected layer with 640 units. The RN has a central hidden size of 256 units and an output size of 640 units. The MHA employs 32 head with a key size of 16 and value size of 20. Last, the PrediNet has 32 heads, with key and relation sizes of 16. The latent-goal variants use a FC layer of size 16 for the information bottleneck. Regarding BRIMs we use the hyperparameters recommended for RL in Mittal et al. (2020). Specifically, we use 2 hierarchical BRIM layers, with 6 modules of 50 LSTM units each. Four modules (k) are active at a given time step (top-k mechanism). Figure 4 illustrates the different BRIM configurations that we evaluate in Sec. 4 in the main text when working with visual instructions, i.e., the Minecraft setting.

C.4 Training plots

Figure 3 shows the training plots of the standard (top), latent-goal (middle) and BRIM (bottom) configurations in Minecraft (left) and Minigrid (right). In the later it can be appreciated a general decrease of performance the 20M mark. This is because we noticed that in MiniGrid, where the navigational features force the agent to further rely on memory, we noticed that agents struggled when learning with the default configuration of random sizes with $n = [7 - 10]$. To alleviate this, through the first 20 M steps we give a higher chance (70%) to maps of size 7, to help agents to learn from the instructions before navigating through larger maps. Note that good training performance, as shown in these training plots, does not necessarily mean good OOD performance. This is highlighted in Table 1 in the main text.

D Compositional learning

Here we assess whether our agents are learning compositionally from SATTL instructions and check if they are really following the given safety constraints when applied to OOD objects or if they are just learning to reach the goal g_α. We focus our study on their performance with negated constraints, since previous research highlighted as the most challenging type of instructions Hill et al. (2020); León et al. (2020). Compositional learning Lake (2019) (also known as systematic learning Hill et al. (2020)) refers to the ability of understanding and producing novel utterances by combining already known primitives Chomsky & Lightfoot (2002). In our context, an agent that is learning compositionally should be able to solve the instruction $-cU+p$ if the primitives c and p are known and it already learnt to solve $-c'U+p'$.

Table 5 shows the results from a control experiment where we track the performance of the agents according to tasks of the form $-cU+p$ when giving reliable, partially occluded or deceptive instructions. Specifically, every row shows the test performance of the multi-layered networks trained in Sec. 4 when providing rewards according to the instruction $-cU+p$, which intuitively means "avoid c until reaching p". The first row shows the performance of the agents when the SM provides *reliable instructions* to the NM, i.e., the instruction provided is the one used to generate rewards.

The second row shows the performance under the same setting, but where the extended observation provided to the NM is a reachability goal (true $U + p$). Intuitively, for the second row the agents are given the right goal p but not the safety constraint, i.e., partially occluding information of the real task. The third row shows the performance when the SM gives deceptive information abut the safety constrain ($+cU + p$), i.e., the SM is "telling" the NM to go through the objects that actually should be avoided. Agents learning systematically should show worse performance with partially occluded instructions than with the reliable ones, but still better than a random walker. Additionally, the worst performance should come when provided deceptive instructions.

From Table 5 we see that all the variants using the MHA and MLP modules follow the rule 1^{st} row $> 2^{nd}$ row $>$ random $> 3^{rd}$ (compositional rule, or c.r. for short). Notably, the best performance comes from a variant that does not use relational networks nor attention (MLP^{LG}). Still, this does not imply that MLPs are better suited for negation since agents were trained in a much wider variety of tasks and the MHA, MHA^{LG} and $\text{PrediNet}^{\text{LG}}$ outperformed the MLP^{LG} in the general evaluation test. In the case of the RN, the c.r. is satisfied but the general low performance and the small difference between the results of the first and the second rows (14 and 13.3 respectively) indicates weak generalisation. This is worse with the M-RN and the PrediNet having both equal or better performance with partially occluded instructions than when receiving the real task as input. Such results imply that these networks have not correctly learnt to generalise negated instructions. This is not the case with the $\text{PrediNet}^{\text{LG}}$, whose results correctly follow the c.r.. In addition, the worse performance of the $\text{PrediNet}^{\text{LG}}$ than the MHA with partially occluded and deceptive instructions suggests that the $\text{PrediNet}^{\text{LG}}$ advantage over the MHA in maps of OOD size (see Table 1 comes from a better ability of the former to execute safety constraints when compared with the later. Note that the larger the map the harder it is to find p; thus the bigger chances of accumulating penalizations due to "violations" of the safety condition.

Discussion   To the best of our knowledge, the only two works that include some empirical evidence of emergent compositional learning with negation, i.e., achieving a performance 50% better than chance are Hill et al. (2020); León et al. (2020). However, in those works negated instructions are interpreted as "something different from", e.g., "not p" intuitively meant "get something different from p". Instead, here we have an interpretation of negated atoms more aligned with propositional and temporal logic, and also to natural language, where "not p" intuitively means that p must be false. Hence, we believe this is the first work to show that DRL agents are capable of learning the abstract operator of negation in its classical interpretation and successfully apply it to new utterances.

E   SATTL AND LTL_f

We stated that SATTL is a fragment of the widely-used LTL_f. The syntax of LTL_f is defined as follows:

$$\varphi \quad ::= \quad p \mid \neg\varphi \mid \varphi_1 \wedge \varphi_2 \mid \bigcirc\varphi \mid \varphi_1 U \varphi_2$$

Since both LTL_f and SATTL are defined ofer finite traces, we can directly introduce the following translations:

$$\varphi \quad ::= \quad p \mid \neg\varphi \mid \varphi_1 \wedge \varphi_2 \mid \bigcirc\varphi \mid \varphi_1 U \varphi_2$$

Definition 4. *Translations τ from Task Temporal Logic to LTL_f are defined as follows:*

$$
\begin{aligned}
\tau(\alpha) &= lUl' \\
\tau(T \cup T') &= \tau(T) \vee \tau(T') \\
\tau(T;T') &= \begin{cases} lU(l' \wedge \tau(T')) & \text{if } T = \alpha \\ \tau(T_1;(T_2;T')) & \text{if } T = T_1;T_2 \\ \tau((T_1;T') \cup (T_2;T')) & \text{if } T = T_1 \cup T_2 \end{cases}
\end{aligned}
$$

We immediately prove that translation τ preserve the interpretation of formulae in SATTL.

Proposition 1. *Given a model $\mathcal{N}$ and trace λ, for every formula T in SATTL,*

$$(\mathcal{N}, \lambda) \models T \quad \text{iff} \quad (\mathcal{N}, \lambda) \models \tau(T)$$

Proof. The proof is by induction on the structure of formula T. The base case follows immediately by the semantics of SATTL and LTL$_f$.

As for the induction step, the case of interest is for formulae of type $T;T'$. In particular, $(\mathcal{N},\lambda) \models T;T'$ iff for some $0 \leq j < |\lambda|$, $(\mathcal{N},\lambda[0,j]) \models T$ and $(\mathcal{N},\lambda[j+1,|\lambda|]) \models T'$. By induction hypothesis, this is equivalent to $(\mathcal{N},\lambda[0,j]) \models lUl'$ and $(\mathcal{N},\lambda[j+1,|\lambda|]) \models \tau(T')$ in the case of $T = lUl'$. Finally, this is equivalent to $(\mathcal{N},\lambda) \models lU(l' \wedge \tau(T'))$. The cases for $T = T_1;T_2$ and $T = T_1 \cup T_2$ are dealt with similarly.

Finally, the case for $T \cup T'$ follows by induction hypothesis and the distributivity of $\vee$. $\qquad\square$