Risk-Controlled Lean-as-Judge for Natural-Language Mathematical Reasoning

Pauline Bourigault [1] **Xiaotong Ji** [2] **Matthieu Zimmer** [2] **Rasul Tutunov** [2] **Haitham Bou-Ammar** [2 3]

Abstract

Lean is increasingly used to judge natural-language mathematical answers, but its signal is partial: many answers never formalize, and a failed proof may reflect an ill-typed statement or a missing library fact, not a wrong answer. On MATH-500 we show this signal is (i) sharply coverage-dependent, that is the proof-winning answer is correct 96% of the time at high proved coverage but 20% at low, and (ii) sparse and often unfaithful: a 7B autoformalizer proves a class for only 28% of problems, and a manual audit finds only $\approx 43\%$ of those proofs faithful. We propose CovCal, a selector over Lean-trace diagnostics that certifies a finite-sample selective-risk bound on accepted answers or abstains, under two regimes (a conservative Bonferroni bound and a tighter dev-then-cal rule). Feasibility depends on autoformalization coverage: with the 7B formalizer the signal is too sparse and Bonferroni abstains on all 20 bootstrap partitions, whereas a prover-specialized formalizer reaches 79% coverage and flips it to feasible on 17 of 20, accepting $\approx 48\%$ of problems at 0.98 accepted accuracy. Since self-consistency alone is already 91% accurate, and confidence-only abstention gives a stronger empirical coverage–risk frontier in this setting, our contribution is not raw answer-selection accuracy. CovCal gives a precise account of when, and with which formalizer, a partial Lean trace is sufficiently covered to support a risk-controlled and auditable formal decision.

1. Introduction

A Lean-kernel-checked proof is strong positive evidence for the formal statement that Lean has checked. Recent

[1]Imperial College London [2]Huawei Noah's Ark Lab [3]UCL Centre for AI. Correspondence to: Pauline Bourigault <p.bourigault22@imperial.ac.uk>.

The 3^{rd} *AI for Math Workshop* at the 43^{rd} International Conference on Machine Learning (ICML), Seoul, South Korea, 2026.

NLP systems use this signal by translating natural-language question–answer pairs into Lean, attempting proof search, and preferring candidates whose formal proofs succeed (Yao et al., 2025; Liu et al., 2025). Our question is complementary: *when should a downstream system trust this formal signal, and when should it treat the signal as out-of-coverage?* The distinction matters because proof failure is not the same as mathematical falsity. A failed attempt may reflect an incorrect answer, but it may also reflect an ill-typed formalization, missing library context, or a proof-search timeout. Treating proof failure as a negative correctness signal therefore risks conflating mathematical incorrectness with lack of formal coverage.

In our pipeline, this asymmetry appears as a sharp reliability gap. When the answer classes holding most of the model's sampled solutions are formally proved, raw formal selection has a low error rate; when few of those solutions land in a proved class, its error rate rises sharply. A second view gives the same message: a proof is reliable when the proved answer clearly outweighs the highest-weight unresolved rival, that is the most-sampled answer class Lean left unresolved, but becomes unsafe when a heavily sampled rival remains unresolved. We refer to this empirical pattern as a *coverage cliff*: formal selection is accurate when proofs cover most of the sampled answer mass and unreliable otherwise.

This motivates a partial-observation view of Lean-based answer selection (Figure 1). The system does not observe the truth or falsity of every candidate answer. It observes only which normalized answer classes reach a usable Lean statement and which of those are proved. An *answer class* is a group of candidate strings that denote the same final answer, such as $1/2$, 0.5, and $2/4$. Candidate classes that are not formalized or not proved are therefore unresolved, not automatically wrong. CovCal uses simple diagnostics of this partial observation, that is typed coverage, proved coverage, unresolved rival mass, and formal margin, and accepts a formal answer only when a predeclared rule satisfies a finite-sample selective-risk certificate.

The threshold rule is chosen from a fixed finite grid, where each cell sets one cutoff for typed coverage, proved coverage, and the formal margin. We report two certification regimes. The Bonferroni regime searches over the whole grid on the calibration split and applies a union-bound cor-

Figure 1. CovCal treats Lean as a partial-observation judge: accept a Lean-backed answer only when the formal trace has sufficient coverage and margin, and abstain when too much answer mass remains unresolved. The method couples Lean-based formal traces with finite-sample selective prediction for the accepted formal subset.

rection for this search. The dev-then-cal regime chooses the threshold on an independent development split and certifies that single threshold once on the calibration split. Both regimes certify only the accepted formal predictions under their assumptions; neither certifies fallback answers or unresolved candidates.

What the formal route adds. Confidence-only abstention is a strong baseline, and we do not claim to beat it on raw coverage–accuracy. The signals certify different objects: confidence calibrates an opaque score, while Lean acceptance returns a kernel-checked artifact plus coverage/margin diagnostics. CovCal is therefore a conservative gatekeeper for auditable formal decisions.

Contributions.

1. **Coverage cliff.** On MATH-500, the proof-winning answer—the highest-weight answer class with a Lean proof—is correct 96% of the time at high proved coverage but only 20% at low coverage. Hence, a Lean proof is reliable only when coverage and margin are high.

2. **A real but sparse and imperfect signal.** The formal signal must be faithfulness-audited, not read as correctness: Lean proves a class for only 28% of problems, and a manual audit finds only $\approx 43\%$ of those proofs faithful to the problem (the rest are true-but-irrelevant or trivial $X = X$ identities).

3. **Method.** We frame formal answer selection as partial-observation selective prediction and propose CovCal, a conservative gatekeeper with finite-sample certificates. The guarantee covers only accepted formal predictions; unresolved inequivalent classes cannot be certified from formal observations alone without abstention.

4. **Feasibility is formalizer-governed.** Certificate feasibility is governed by autoformalization coverage: a 7B formalizer is too sparse for any Bonferroni certificate ($0/20$ bootstrap dev/cal/test splits), whereas a prover-specialized formalizer at 79% coverage flips it to feasible ($17/20$).

2. Formal Verifiers as NLP Judges

A general Lean-based judging pipeline has four stages. First, a candidate final answer is extracted from a natural-language solution. Second, the problem and candidate answer are translated into one or more Lean statements. Third, Lean attempts to elaborate each statement. Fourth, proof search attempts to close the elaborated statement. A verified proof gives strong positive evidence for the formal statement, but any stage can fail for reasons unrelated to the truth of the original informal answer. Autoformalization may change the semantics of the problem. Elaboration may fail because of syntax, type-class inference, missing imports, or library mismatch. Proof search may time out even for true statements. Hence, the absence of a proof is a heterogeneous event, not a mathematical label.

Prior work demonstrates the usefulness of this pipeline. FANS uses Lean 4 to formalize question–answer pairs and assist answer selection (Yao et al., 2025). Safe uses Lean 4 for retrospective step-aware verification of natural-language mathematical reasoning (Liu et al., 2025). These works show that formal proof can improve math reasoning systems. Our question is complementary: how much of the candidate-answer space is visible to the formal pipeline, and when is that partial trace sufficient for answer selection?

The answer requires separating three notions that are often collapsed: (i) whether a candidate answer is mathematically

correct, (ii) whether its intended formal statement is well represented in Lean, and (iii) whether the current prover can decide it within budget. COVCAL does not solve (i)–(iii). Instead, it measures the observable mass of candidates for which (ii) and (iii) are available, then calibrates the risk of trusting the resulting formal selection.

3. Problem Setup

We first describe the objects used by the selector. As a running example, suppose a model samples $K = 32$ solutions to the same problem. Several samples may end with surface forms such as $1/2$, 0.5, and $2/4$; these should count as one final-answer class rather than three different answers. Another group of samples may end with $3/4$. COVCAL reasons over these normalized classes and their total weights, not over raw strings.

Let $x \in \mathcal{X}$ be a natural-language mathematical problem with reference answer $a^\star(x)$. A generator or ensemble produces K candidate answers $a_1, \ldots, a_K$ with nonnegative weights $q_j(x)$ satisfying $\sum_j^K q_j(x) = 1$. The weights may be self-consistency frequencies (Wang et al., 2023), normalized reranker scores, or a uniform distribution over sampled candidates.

Answer classes. Raw candidate strings are a poor unit of selection: $1/2$, 0.5, and $\frac{2}{4}$ may be the same answer, while two candidates with the same surface form may correspond to different formalizations. We therefore map candidates to normalized answer classes

$$e_x(a_j) \in \mathcal{C}(x), \qquad (1)$$

using answer extraction, algebraic simplification, exact string normalization, or formal equivalence checks when available. The class weight is

$$Q_c(x) = \sum_{j:e_x(a_j)=c} q_j(x), \qquad \sum_{c \in \mathcal{C}(x)} Q_c(x) = 1. \quad (2)$$

All coverage, margin, and selection quantities are computed over classes instead of raw candidates. This prevents an unresolved duplicate of an already proved answer from being treated as a rival.

Formal observation. For each pair (x, a_j), a formalization module attempts to produce one or more Lean artifacts. A verifier elaborates each artifact and attempts proof search. We summarize the best status for candidate a_j by

$$s_j \in \mathcal{S},$$
$$\mathcal{S} = \{\texttt{proved}, \texttt{typechecked}, \texttt{illtyped},$$
$$\texttt{timeout}, \texttt{unformalized}\}. \qquad (3)$$

The five statuses are defined in Appendix F (proved is a kernel-checked proof; typechecked elaborates but is unproved; the rest are failures); optional decisive negation/inequivalence statuses are supported but not required.

For each answer class c, define class-level indicators

$$P_c(x) = \mathbb{I}\{\exists j : e_x(a_j) = c, \ s_j = \texttt{proved}\}, \qquad (4)$$
$$T_c(x) = \mathbb{I}\{\exists j : e_x(a_j) = c, \ s_j \in \mathcal{S}_{\text{typ}}\},$$
$$\mathcal{S}_{\text{typ}} = \{\texttt{proved}, \texttt{typechecked}, \texttt{timeout}\}. \quad (5)$$

$\mathcal{S}_{\text{typ}}$ is the elaborated-statement set; timeout qualifies since proof search runs only after elaboration. The formal observation $\mathcal{O}(x)$ consists of answer classes, class weights, statuses, proof artifacts when available, error logs, and the fixed prover budget. A selector returns an answer class $\hat{c}(x)$, a representative answer $\hat{a}(x)$, or abstains with $\perp$.

4. Coverage Diagnostics

The diagnostics answer three questions about the formal trace. How much candidate mass reached a well-formed Lean statement? How much candidate mass was actually proved? And, if a class was proved, does it dominate the strongest unresolved rival? These quantities are pipeline-agnostic and can be computed from answer-class weights and Lean status logs.

Definition 1 (Typed coverage). *The typed coverage mass is*

$$C_{\text{typ}}(x) = \sum_{c \in \mathcal{C}(x)} Q_c(x) T_c(x). \qquad (6)$$

Typed coverage measures how much candidate probability reached a well-formed Lean statement. Low typed coverage points to autoformalization, parsing, answer-normalization, or library-interface failure.

Definition 2 (Proved coverage). *The proved coverage mass is*

$$C_{\text{prf}}(x) = \sum_{c \in \mathcal{C}(x)} Q_c(x) P_c(x). \qquad (7)$$

Proved coverage measures how much answer-class probability is positively decided by the formal pipeline. It is distinct from proof existence: proving a low-weight class may be much less informative than proving the dominant class.

Definition 3 (Unresolved rival mass and formal margin). *If at least one class is proved, let*

$$c^+(x) = \arg \max_{c:P_c(x)=1} Q_c(x) \qquad (8)$$

be the highest-weight proved class. The unresolved rival mass is

$$R_{\text{unres}}(x) = \max_{c \neq c^+(x):P_c(x)=0} Q_c(x), \qquad (9)$$

with $R_{\mathrm{unres}}(x) = 0$ *when every other class is also proved or no rival exists. The formal margin is*

$$M(x) = Q_{c^+(x)}(x) - R_{\mathrm{unres}}(x), \qquad (10)$$

and $M(x) = -\infty$ *if no class is proved.*

The margin captures the main reliability condition: a proof of one answer is not decisive if a higher-weight inequivalent answer class remains unresolved.

Conflict indicators. If two inequivalent final-answer classes are both proved for the same informal problem, we mark a conflict and reject formal selection by default. This should not be read as a Lean inconsistency. It usually indicates an answer-normalization error, a semantic mismatch between generated formal statements, or incompatible autoformalizations of the informal problem.

Coverage cliffs. We use *coverage cliff* for the empirical scenario in which the reliability of formal answer selection changes sharply as a function of C_{typ}, C_{prf}, R_{unres}, or M. The hypothesis is stronger than "hard examples have lower proof rates": below a coverage threshold, failed or missing proofs become non-diagnostic because unresolved classes may be false, unformalized, or unproved.

5. Risk-Controlled Formal Selection

COVCAL is a selective wrapper around a base Lean selector. It does not require training a new theorem prover or changing the formalizer. Its contribution is to decide when the formal signal is sufficiently covered to determine the answer.

Base formal selector. The base selector returns the highest-weight proved answer class,

$$g_{\mathrm{F}}(x) = c^+(x), \qquad (11)$$

with $g_{\mathrm{F}}(x) = \perp$ if no class is proved or if a conflict is detected. The returned natural-language answer is a canonical representative of $c^+(x)$. More sophisticated formal selectors can be substituted, but the coverage logic is unchanged.

Acceptance rule. For a threshold tuple $\tau = (\tau_{\mathrm{typ}}, \tau_{\mathrm{prf}}, \tau_M)$, define

$$\begin{aligned} A_\tau(x) = \mathbb{I}\{ &C_{\mathrm{typ}}(x) \geq \tau_{\mathrm{typ}}, \; C_{\mathrm{prf}}(x) \geq \tau_{\mathrm{prf}}, \\ &M(x) \geq \tau_M, \; g_{\mathrm{F}}(x) \neq \perp, \\ &\text{no conflict}\}. \end{aligned} \qquad (12)$$

If $A_\tau(x) = 1$, COVCAL returns $g_{\mathrm{F}}(x)$. If $A_\tau(x) = 0$, the selective version abstains. A full-coverage system may instead call a fallback $g_{\mathrm{N}}(x)$ such as self-consistency or a

learned natural-language verifier; the formal selective-risk certificate below applies only to the accepted formal predictions, not to fallback outputs. The same machinery can wrap non-formal scores; our confidence-only baseline tests this comparison. The formal route differs because accepted examples include a Lean artifact and coverage/margin diagnostics, while confidence-only selection certifies only an empirical score. Algorithm 1 (Appendix B) summarizes the instance-level decision rule.

Risk-controlled threshold selection. Given a target selective-risk level ϵ and a finite grid $\mathcal{T}$, COVCAL chooses the least conservative rule whose calibration certificate is valid. We report two valid regimes; both produce a certificate of the form "with probability $\geq 1 - \delta$, the selected $\hat{\tau}$ has population selective risk at most ϵ," but they differ in sample efficiency.

The default operational regime is Bonferroni: optimize over the grid on the calibration split and pay a $|\mathcal{T}|$-fold union-bound penalty. Formally,

$$\hat{\tau}_{\mathrm{Bonf}} = \arg\max_{\tau \in \mathcal{T}} m_\tau \quad \text{s.t.} \quad U_{\delta/|\mathcal{T}|}(k_\tau, m_\tau) \leq \epsilon, \quad (13)$$

where m_τ and k_τ are the number of accepted calibration examples and accepted errors, and $U_\alpha(k, m)$ is the one-sided Clopper–Pearson upper bound with $U_\alpha(k, 0) = 1$. If no threshold is feasible, the selective method returns reject-all. This regime is conservative but makes no assumption on the dependence structure between the $|\mathcal{T}|$ cell statistics: they are jointly nested under the same calibration sample, so a generic union bound is the safest valid statement.

A tighter alternative is a dev-then-cal rule. First, a threshold $\hat{\tau}_{\mathrm{DC}}$ is selected using only the development split, for example by choosing the highest-coverage grid cell whose empirical dev error is at most ϵ under a deterministic tie-break. If no such cell exists, the procedure returns reject-all. Second, the selected threshold is evaluated once on the independent calibration split and is accepted only when

$$U_\delta\big(k_{\hat{\tau}_{\mathrm{DC}}}^{\mathrm{cal}}, m_{\hat{\tau}_{\mathrm{DC}}}^{\mathrm{cal}}\big) \leq \epsilon. \qquad (14)$$

Because $\hat{\tau}_{\mathrm{DC}}$ is a function only of the dev split, it is independent of the calibration sample. Hence, a single Clopper–Pearson bound at level δ is sufficient. Theorem 2 gives the finite-sample guarantee under i.i.d. dev/cal/deployment samples.

Practical choices. The default class weights are self-consistency frequencies; a class is marked proved if any of its artifacts is kernel-checked, and two inequivalent proved classes trigger rejection rather than a choice. All implementation choices, and the quantities frozen before calibration labels are used, are listed in Appendix B.

Method	Overall	Accepted	Acc. frac.	Test diag. UB
Regime-independent selectors ($n_{cal} = 151$, $\epsilon = 0.15$)				
Self-consistency	0.910 [0.903, 0.916]	0.910 [0.903, 0.916]	1.000 [1.000, 1.000]	0.138 [0.131, 0.146]
Confidence-only abst.	0.866 [0.857, 0.875]	0.969 [0.966, 0.973]	0.894 [0.884, 0.903]	0.068 [0.063, 0.072]
Raw Lean + fallback	0.891 [0.884, 0.899]	0.891 [0.884, 0.899]	1.000 [1.000, 1.000]	0.159 [0.150, 0.168]
Proof-existence abst.	0.193 [0.182, 0.203]	0.877 [0.857, 0.896]	0.220 [0.209, 0.231]	0.258 [0.234, 0.282]
Calibrated formal selectors — Bonferroni regime				
CovCal	reject-all (0/20 partitions certify)			
Calibrated formal selectors — dev-then-cal regime (12/20 partitions certify)				
CovCal	0.194 [0.184, 0.205]	0.932 [0.914, 0.949]	0.209 [0.197, 0.220]	0.192 [0.168, 0.216]
CovCal+fallback	0.905 [0.896, 0.913]	0.905 [0.896, 0.913]	1.000 [1.000, 1.000]	0.144 [0.135, 0.154]

Table 1. Main answer-selection results. Confidence-only abstention gives the strongest empirical coverage–risk frontier here; CovCal instead certifies a smaller Lean-backed subset when dev-then-cal succeeds, while Bonferroni rejects the sparse signal outright. Main MATH-500 run (Qwen2.5-Math-7B-Instruct, $n_{cal} = 151$, $\epsilon = 0.15$; $K = 20$ bootstrap, seed-mean 95% interval). *Test diag. UB* is a held-out Clopper–Pearson bound computed after rule selection—a diagnostic, not the certificate of Table 3; the top block is regime-independent.

6. Finite-Sample Guarantees

The guarantee certifies the selective risk of the complete frozen pipeline: candidate generation, answer normalization, formalization, proof search, coverage computation, and formal selection. It does not certify unresolved candidates and does not interpret failed Lean proofs as negative labels. The probability in the guarantee is over the random draw of calibration and future deployment examples, including any example-level randomness that is part of the frozen pipeline. In the reported bootstrap summaries, candidate and formalization logs are fixed, so only the dev/cal/test partition varies.

Selective risk. Let $\mathcal{D}_{\mathrm{cal}} = \{(X_i, C_i^\star)\}_{i=1}^n$ be a calibration set drawn i.i.d. from the same population as future test examples, where X_i is the problem and $C_i^\star$ is its normalized reference answer class. The pipeline outputs used by A_τ and g_{F} are computed without inspecting $C_i^\star$ except for final evaluation. For $\tau \in \mathcal{T}$, let

$$m_\tau = \sum_{i=1}^n A_\tau(X_i),$$

$$k_\tau = \sum_{i=1}^n A_\tau(X_i)\mathbb{I}\{g_{\mathrm{F}}(X_i) \neq C_i^\star\}. \qquad (15)$$

The population selective risk is

$$R(\tau) = \Pr[g_{\mathrm{F}}(X) \neq C^\star \mid A_\tau(X) = 1], \qquad (16)$$

with the harmless convention $R(\tau) = 0$ when $\Pr[A_\tau(X) = 1] = 0$.

Theorem 1 (Uniform selective-risk calibration under Bonferroni)**.** *Assume the threshold grid $\mathcal{T}$ is fixed before inspecting calibration labels, and the pipeline used to compute A_τ and g_{F} is fixed before calibration. If the calibration examples are i.i.d. from the deployment population, then with*

probability at least $1 - \delta$ over the calibration sample and any example-level pipeline randomness, for all $\tau \in \mathcal{T}$,

$$R(\tau) \leq U_{\delta/|\mathcal{T}|}(k_\tau, m_\tau). \qquad (17)$$

Consequently, whenever Eq. 13 returns a feasible threshold, the selected rule has selective risk at most ϵ with probability at least $1 - \delta$.

Accepted calibration errors at a fixed threshold are Bernoulli, so a one-sided Clopper–Pearson bound (Clopper & Pearson, 1934) controls its risk; the Bonferroni correction makes this simultaneous over the grid, letting the threshold be chosen after seeing calibration errors (proof in Appendix A).

Theorem 2 (Dev-then-cal selective-risk calibration, no union bound)**.** *Partition i.i.d. samples from the population $\mathcal{P}$ into an independent development split $\mathcal{D}_{\mathrm{dev}}$ and calibration split $\mathcal{D}_{\mathrm{cal}}$. Let $\hat{\tau} = f(\mathcal{D}_{\mathrm{dev}})$ be any $\sigma(\mathcal{D}_{\mathrm{dev}})$-measurable choice of threshold cell in $\mathcal{T} \cup \{\bot\}$; in particular, $\hat{\tau}$ may be the maximum-coverage dev-feasible cell with a deterministic tie-break. Let $m = m_{\hat{\tau}}^{\mathrm{cal}}$ and $k = k_{\hat{\tau}}^{\mathrm{cal}}$ be the accept count and accepted-error count on the calibration split. Define the certified output threshold*

$$\widehat{\tau}_{\mathrm{out}} = \begin{cases} \bot & \hat{\tau} = \bot, \text{ or } m = 0, \text{ or } U_\delta(k, m) > \epsilon, \\ \hat{\tau} & \text{otherwise.} \end{cases}$$

Then

$$\Pr\big[\widehat{\tau}_{\mathrm{out}} \neq \bot \implies R(\widehat{\tau}_{\mathrm{out}}) \leq U_\delta(k, m) \leq \epsilon\big] \\ \geq 1 - \delta. \quad (18)$$

Because $\hat{\tau}$ is fixed on dev, the cal split sees a single threshold, so the bound uses level δ rather than $\delta/|\mathcal{T}|$; strict dev/cal separation is the load-bearing assumption (proof in Appendix A).

dev-then-cal procedure. The selection rule, that is the highest-coverage dev-feasible cell then a single cal-side Clopper–Pearson check at level δ, and the boundary cases it handles (empty splits, zero accepts, all-errors, multiple ϵ targets, and the i.i.d./measurability requirements) are given in Appendix B.

Comparison of the two regimes. At our settings ($|\mathcal{T}| = 125$, $\delta = 0.05$), Theorem 1 spends $\alpha = 4 \times 10^{-4}$ per cell while Theorem 2 spends $\alpha = 0.05$ on a single cal-side bound, so the two regimes can disagree on feasibility for the same observations. The cliff (Section 8.1) is a property of the data and is identical under either regime; only the certificate's verdict depends on the bound. Section 8.3 reports both.

No coverage, no verifier-only certificate. The next proposition explains why coverage diagnostics are necessary.

Proposition 1 (Unresolved answer classes are indistinguishable). *Fix a problem x and a formal observation $\mathcal{O}(x)$. Suppose a verifier-only selector h selects a proved class $c_s = h(\mathcal{O}(x))$, but there is an unresolved answer class c_u with $Q_{c_u}(x) > 0$, $P_{c_u}(x) = 0$, and no formal evidence in $\mathcal{O}(x)$ proving, disproving, or identifying c_u as equivalent to c_s. Then there are two latent correctness assignments over the informal answer classes that are both compatible with the same formal observation but disagree on whether c_s is correct. Hence no non-vacuous pointwise correctness certificate for h follows from $\mathcal{O}(x)$ alone unless the selector resolves c_u, assumes it away, uses external semantic information or labels, or abstains.*

Intuitively, the formal log records what Lean could decide, not the truth values of classes it never resolved: an unresolved inequivalent rival leaves the selected proved class and that rival equally compatible with the same observation (proof in Appendix A). This is a certification statement, not an empirical claim that unresolved candidates are usually correct. Missing formal evidence is not evidence of mathematical falsehood. Calibration turns the partial observation into a controlled selective problem, using Lean where coverage suffices and forcing abstention or fallback elsewhere.

7. Experimental Protocol   ⌗ **Code repository**

We evaluate whether Lean-derived coverage diagnostics predict reliable formal selection on a filtered MATH-500 short-answer subset (Hendrycks et al., 2021; Lightman et al., 2024): 378 of 500 examples remain after excluding proof-only, diagram-dependent, and non-normalizable references. The split is 76/151/151 dev/cal/test, with $\epsilon = 0.15$ and $\delta = 0.05$. We also report a hard levels-4/5 slice, an autoformalizer ablation with generation fixed (Sec. 8.3), and an

Bin	#	Proof rate	Winner acc.
by proved coverage C_{prf} (all $n = 378$)			
$C_{\mathrm{prf}} < 0.25$	283	0.035	0.20
$0.25 \le C_{\mathrm{prf}} < 0.50$	6	1.000	0.33
$0.50 \le C_{\mathrm{prf}} < 0.75$	4	1.000	1.00
$C_{\mathrm{prf}} \ge 0.75$	85	1.000	0.96
by formal margin M (the 105 proved problems)			
$M < 0$	10	1.000	0.10
$0 \le M < 0.25$	5	1.000	0.40
$0.25 \le M < 0.5$	5	1.000	0.80
$M \ge 0.5$	85	1.000	0.98

Table 2. The coverage/margin cliff on the main run. # is problems per bin; *Proof rate* the fraction with a kernel-proved class; *Winner acc.* the accuracy of the highest-weight proved class among problems with a proof. The signal is sparse (most problems are in the lowest C_{prf} bin with almost no proofs) but sharply reliable when present: 96% at $C_{\mathrm{prf}} \ge 0.75$ vs 20% at $C_{\mathrm{prf}} < 0.25$ (98% vs 10% by margin).

AMC/AIME out-of-distribution set (Appendix H).

For each problem, Qwen2.5-Math-7B-Instruct generates $K = 32$ candidate solutions. We extract final answers, normalize them into answer classes, and assign each class a self-consistency weight Q_c. The pipeline then formalizes the top four answer classes and attempts Lean proof search. The resulting class statuses, which are `proved`, `typechecked`, `timeout`, `illtyped`, and `unformalized`, are the only formal observations used by CovCal.

We compare self-consistency, confidence-only abstention, raw Lean with fallback, proof-existence abstention, and CovCal with/without fallback. Thresholds use either the Bonferroni grid certificate or the dev-then-cal certificate from Sec. 6. The main target is $\epsilon = 0.15$, $\delta = 0.05$; the hard subset uses $\epsilon = 0.10$. Appendices give prompts, pipeline details, logs, filtering, hardware, and the tactic portfolio.

8. Results

The results support three main claims. First, the formal signal is real but sparse: Lean proves at least one answer class for only 28% of problems, and a manual audit finds only $\approx 43\%$ of proved statements faithful to the problem (versus the 74% an automated check labels non-trivial-and-correct; Sec. 8.2). Second, the signal is sharply coverage-dependent: the highest-weight proved class matches the reference answer 96% of the time at high proved coverage but only 20% at low coverage, and 98% versus 10% binned by formal margin (Tab. 2). Third, certifiability depends on autoformalization coverage: with the 7B Qwen2.5-Coder formalizer the sparse signal forces Bonferroni to reject on all 20 bootstrap partitions (dev-then-cal certifies 12/20), whereas the prover-specialized Goedel-Prover-V2-8B lifts coverage to 79% and flips Bonferroni to feasible on 17/20 (Tab. 1 and 3). Unless a column says calibration certificate, upper bounds in answer-selection tables are held-out diagnostics computed

after rule selection.

8.1. Main Answer-Selection Results

On the main run, self-consistency is already 91% accurate, and confidence-only abstention is strongest ($\approx 89\%$ accepted at ≈ 0.97 accepted accuracy). Formal selectors accept only 20–22% of test items; Bonferroni rejects all partitions, while dev-then-cal certifies only 12/20. Thus, CovCal does not claim to dominate confidence abstention, but to identify the Lean-backed subset that supports a risk-controlled, auditable formal decision. Fallback outputs are not certified.

The main diagnostic signal is not that hard examples have fewer proofs. Low-margin examples can have proof existence but still be unreliable because a stronger unresolved rival answer remains. This is the empirical reason for treating unproved candidate mass as unresolved instead of false.

8.2. Faithfulness Audit and Qualitative Examples

An automated rational-evaluation check classifies the 314 proved artifacts as genuine (40.1%, a $\mathbb{Q}$-true arithmetic identity), structural (33.4%, a true gcd/divisor/quantified statement), trivial (22.9%, an X = X identity), or spurious (2.5%, $\mathbb{Q}$-false), so 73.6% are non-trivial and correct. But non-trivial-and-correct is not *faithful*: a true statement may not capture the problem. A manual audit of 45 stratified examples (single annotator; diagnostic error analysis) makes the gap explicit: genuine proofs are faithful (6/6) and trivial ones are not, but *structural* statements almost never are (0/6). They assert a true side-fact or bare existence (e.g. $\exists n,\ n > 125 \wedge n = 129$ for a problem whose answer is 129), omitting the problem's actual condition, while the audited *spurious* cases are classifier false-positives (e.g. $(3{:}\mathbb{Q})/20 = 0.15$), not real errors. Reweighting the audited per-category rates by population frequency, only $\approx 43\%$ of proved statements are faithful, about half the 73.6% that typecheck and hold. Faithful verification is thus rarer than proof success suggests, and the audited failures are heterogeneous, including semantic drift, proof-search failure on faithful statements, and ill-typed statements, and supporting our treatment of a missing proof as unresolved rather than negative. Appendix I gives three worked examples (A)–(C): a proof trusted when the proved class dominates the formally visible mass (A), a missing proof treated as unresolved rather than wrong (B), and a low-weight or trivially formalized rival correctly distrusted by the margin (C). Accordingly, an accepted Lean proof should be read as a certificate for the generated formal statement plus a calibrated coverage decision, not as a standalone semantic certificate that the informal problem has been faithfully solved.

8.3. Ablations and Certification Regimes

The binding constraint on the main run is autoformalization coverage: only 28% of problems reach any proof (with the 7B Qwen2.5-Coder autoformalizer), which is what forces the conservative Bonferroni certificate to reject and leaves the tighter dev-then-cal regime feasible on only 12 of 20 partitions. Table 3 compares the two regimes on the same frozen observations. Because coverage is the bottleneck, we also vary the autoformalizer, holding generation fixed. The prover-specialized Goedel-Prover-V2-8B raises proved coverage from 28% to 79% at the same proof-winner precision (86%), and this denser signal flips the certificate from infeasible to feasible: Bonferroni now certifies on 17 of 20 partitions (versus 0 with Qwen2.5-Coder) and dev-then-cal on all 20, each accepting about 48% of test items at 0.98 accepted accuracy (Table 3). Scaling the formalizer further to the 32B Goedel-Prover-V2 does not extend this gain: proved coverage is 64% (below the 8B's 79%) and the certificate is marginally less feasible (Bonferroni 13/20, dev-then-cal 17/20), indicating that prover specialization rather than raw model scale is what lifts coverage past the feasibility threshold. In this protocol, autoformalization coverage is the binding constraint, but the fixed tactic portfolio may also understate coverage relative to retrieval-augmented or agentic provers; any stronger backend still inherits the faithfulness caveat of Sec. 8.2. Additional per-level breakdowns, ϵ-sensitivity, status-count, and hard-subset details are reported in Appendix H.

9. Related Work

Math reasoning and verifiers. Self-consistency, outcome-reward models, and process-reward models are common signals for natural-language mathematical reasoning (Wang et al., 2023; Cobbe et al., 2021; Uesato et al., 2022; Lightman et al., 2024; Wang et al., 2024). Lean-based systems such as FANS and Safe instead use formal proof as a positive correctness signal (Yao et al., 2025; Liu et al., 2025). Our focus is complementary: when the formal proof is absent, we ask whether the remaining formal trace is sufficiently covered to support answer selection.

Autoformalization and theorem proving. LLM autoformalization and Lean/Isabelle theorem proving remain sensitive to domain, library context, and dependency retrieval (Wu et al., 2022; Jiang et al., 2023; Yang et al., 2023; Azerbayev et al., 2023; Zheng et al., 2021; Yu et al., 2025; Patel et al., 2026; Lin et al., 2025). These works motivate our treatment of proof failure as heterogeneous instead of as a negative label. We use Qwen2.5-Math for generation and Qwen2.5-Coder for autoformalization (Yang et al., 2024; Hui et al., 2024); our contribution is the risk-controlled wrapper.

Autoformalizer (gen. fixed)	n_{cal}	Bonferroni ($\alpha = \delta/|\mathcal{T}|$)		Dev-then-cal ($\alpha = \delta$)		UB ratio
		reject@$K=20$	med cal UB	reject@$K=20$	med cal UB	(med)
Qwen2.5-Coder-7B (main)	151	20/20	–	8/20	0.121	–
Goedel-Prover-V2-8B	151	3/20	0.127	0/20	0.062	0.49×
Goedel-Prover-V2-32B	151	7/20	0.143	3/20	0.115	0.81×

Table 3. The two certificate regimes on the main run ($K = 20$ bootstrap, $\epsilon = 0.15$). Bonferroni applies $\alpha = \delta/|\mathcal{T}| = 4 \times 10^{-4}$ over the 125-cell grid; dev-then-cal applies $\alpha = \delta = 0.05$ (Theorem 2). *reject@K* counts refusing seeds; *med cal UB* is the median calibration-side bound over feasible seeds (– if none). Generation is held fixed; the Goedel-Prover-V2 rows vary only the autoformalizer.

Selective prediction and risk control. Selective classification trades coverage for risk (El-Yaniv & Wiener, 2010; Geifman & El-Yaniv, 2017). Risk-controlling prediction and conformal risk-control methods certify population risk for calibrated rules under distributional assumptions (Bates et al., 2021; Angelopoulos et al., 2024). COVCAL adapts this perspective to formal answer selection with partial observations: unresolved answer mass does not become a larger prediction set, but instead forces abstention unless a coverage rule can be certified.

10. Conclusion

We documented a coverage cliff in Lean-as-judge and proposed COVCAL, a selective wrapper that certifies risk only where enough formal evidence is visible. The lesson is not raw-accuracy dominance over self-consistency or confidence-only abstention, but conditional auditability: when enough answer mass is formalized, proved, and separated from unresolved rivals, COVCAL certifies a low-risk Lean-backed subset; when coverage is sparse, unfaithful, or shifted, it abstains.

11. Limitations

Scope of the certificate. The selective-risk guarantee covers only examples for which $A_{\hat{\tau}}(x) = 1$ and a formal answer is returned. It does not certify individual mathematical truth, does not assign a label to unresolved answer classes, and does not extend to fallback predictions made when $A_{\hat{\tau}}(x) = 0$. It also does not imply dominance over calibrated confidence-only selection.

Distributional assumptions. Both regimes require exchangeability of the calibration sample with future test points. The dev-then-cal regime additionally requires independence between the dev and cal splits and that $\hat{\tau}$ be a function of dev only; leakage from the cal split into threshold selection would invalidate Theorem 2. Distribution shift between calibration and deployment also voids the bound.

Feasibility depends on the autoformalizer. The certificate is only as good as the formal coverage it is given. With a 7B autoformalizer, only about 28% of problems are proved and Bonferroni rejects every bootstrap partition (dev-then-cal certifies 12/20). A prover-specialized formalizer raises coverage to 79% and makes Bonferroni feasible on 17/20, showing that the method is informative only when enough answer mass is formalized and proved. Raw scale is not a substitute: the 32B Goedel-Prover-V2 variant attains lower proved coverage (64%) than the 8B (79%) and is marginally less feasible. The fixed tactic portfolio may also understate coverage relative to stronger provers.

Single dataset and pipeline. The empirical evidence is from one dataset family (MATH-500), one candidate generator, and one proof style. We vary the autoformalizer (up to a 32B prover) but cannot claim the cliff or the coverage numbers transfer to symbolic Olympiad problems, multi-step formal proofs, other answer formats, or systems built on agentic provers with retrieval.

Bootstrap and partition variability. The reported $K = 20$ bootstrap captures variance from the dev/cal/test partition but not from candidate sampling or autoformalization stochasticity; the same observations are reused across seeds. A multi-seed re-run of generation and formalization would estimate the latter sources of variability.

Faithfulness of proved statements. A kernel-checked proof certifies the *generated* statement, not that the statement faithfully captures the informal problem. An automated rational-evaluation check of the 314 proved artifacts finds 73.6% non-trivial and correct, but our manual audit (45 stratified examples) shows this overstates faithfulness: many true *structural* statements assert a side-fact or bare existence, so only $\approx 43\%$ of proved statements are faithful to the problem, and a wrong answer class is proved in 8% of problems. This audit is diagnostic error analysis, not benchmark-grade annotation (*e.g.*, it uses a single annotator and small per-category samples) and the automated diagnostics alone do not flag a faithful-looking but semantically drifted statement. Semantic faithfulness therefore remains a separate requirement.

Ethical Considerations

Formal verification can make mathematical reasoning systems more reliable, but overclaiming from failed verification can mislabel correct reasoning as incorrect or produce misleading training signals. The proposed calibration framework is intended to make such limitations explicit. The work uses public math datasets and local open models; no personal data is involved. The main risk is that users may interpret calibrated acceptance as a guarantee for all examples rather than for the accepted subset under the stated data assumptions.

References

Angelopoulos, A. N., Bates, S., Fisch, A., Lei, L., and Schuster, T. Conformal risk control. In *International Conference on Learning Representations*, 2024.

Azerbayev, Z., Piotrowski, B., Schoelkopf, H., Ayers, E. W., Radev, D., and Avigad, J. ProofNet: Autoformalizing and formally proving undergraduate-level mathematics. *arXiv preprint arXiv:2302.12433*, 2023.

Bates, S., Angelopoulos, A., Lei, L., Malik, J., and Jordan, M. I. Distribution-free, risk-controlling prediction sets. *Journal of the ACM*, 68(6):1–34, 2021.

Clopper, C. J. and Pearson, E. S. The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika*, 26(4):404–413, 1934.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., Hesse, C., and Schulman, J. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

El-Yaniv, R. and Wiener, Y. On the foundations of noise-free selective classification. *Journal of Machine Learning Research*, 11:1605–1641, 2010.

Geifman, Y. and El-Yaniv, R. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, 2017.

Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., and Steinhardt, J. Measuring mathematical problem solving with the MATH dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, 2021.

Hui, B., Yang, J., Cui, Z., Yang, J., Liu, D., Zhang, L., Liu, T., Zhang, J., Yu, B., Lu, K., Dang, K., Fan, Y., Zhang, Y., Yang, A., Men, R., Huang, F., Zheng, B., Miao, Y., Quan, S., Feng, Y., Ren, X., Ren, X., Zhou, J., and Lin, J. Qwen2.5-Coder technical report. *arXiv preprint arXiv:2409.12186*, 2024.

Jiang, A. Q., Welleck, S., Zhou, J. P., Li, W., Liu, J., Jamnik, M., Lacroix, T., Wu, Y., and Lample, G. Draft, sketch, and prove: Guiding formal theorem provers with informal proofs. In *International Conference on Learning Representations*, 2023.

Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let's verify step by step. In *International Conference on Learning Representations*, 2024.

Lin, Y., Tang, S., Lyu, B., Yang, Z., Chung, J.-H., Zhao, H., Jiang, L., Geng, Y., Ge, J., Sun, J., Wu, J., Gesi, J., Lu, X., Acuna, D., Yang, K., Lin, H., Choi, Y., Chen, D., Arora, S., and Jin, C. Goedel-Prover-V2: Scaling formal theorem proving with scaffolded data synthesis and self-correction. *arXiv preprint arXiv:2508.03613*, 2025.

Liu, C., Yuan, Y., Yin, Y., Xu, Y., Xu, X., Chen, Z., Wang, Y., Shang, L., Liu, Q., and Zhang, M. Safe: Enhancing mathematical reasoning in large language models via retrospective step-aware formal verification. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12171–12186, Vienna, Austria, 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025. acl-long.594. URL https://aclanthology.org/2025. acl-long.594/.

Patel, N., Arias, N., Babayan, D., Cochran, V., Libman, T., Mahmood, H., McCarty, L., Munoz, S., Willey, L., and Flanigan, J. MathAtlas: A benchmark for autoformalization in the wild. *arXiv preprint arXiv:2605.14061*, 2026.

Uesato, J., Kushman, N., Kumar, R., Song, F., Siegel, N., Wang, L., Creswell, A., Irving, G., and Higgins, I. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Wang, P., Li, L., Shao, Z., Xu, R., Dai, D., Li, Y., Chen, D., Wu, Y., and Sui, Z. Math-Shepherd: Verify and reinforce LLMs step-by-step without human annotations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9426–9439, 2024.

Wang, X., Wei, J., Schuurmans, D., Le, Q., Chi, E. H., Narang, S., Chowdhery, A., and Zhou, D. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations*, 2023.

Wu, Y., Jiang, A. Q., Li, W., Rabe, M. N., Staats, C., Jamnik, M., and Szegedy, C. Autoformalization with large language models. In *Advances in Neural Information Processing Systems*, 2022.

Yang, A., Zhang, B., Hui, B., Gao, B., Yu, B., Li, C., Liu, D., Tu, J., Zhou, J., Lin, J., Lu, K., Xue, M., Lin, R., Liu, T., Ren, X., and Zhang, Z. Qwen2.5-Math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*, 2024.

Yang, K., Swope, A. M., Gu, A., Chalamala, R., Song, P., Yu, S., Godil, S., Prenger, R., and Anandkumar, A. LeanDojo: Theorem proving with retrieval-augmented language models. In *Advances in Neural Information Processing Systems*, 2023.

Yao, J., Wang, R., and Zhang, T. FANS: Formal answer selection for LLM natural language math reasoning using Lean4. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 3181–3200, Suzhou, China, 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025. emnlp-main.158. URL https://aclanthology.org/2025.emnlp-main.158/.

Yu, Z., Peng, R., Ding, K., Li, Y., Peng, Z., Liu, M., Zhang, Y., Yuan, Z., Xin, H., Huang, W., Wen, Y., Zhang, G., and Liu, W. FormalMATH: Benchmarking formal mathematical reasoning of large language models. *arXiv preprint arXiv:2505.02735*, 2025.

Zheng, K., Han, J. M., and Polu, S. MiniF2F: A cross-system benchmark for formal Olympiad-level mathematics. *arXiv preprint arXiv:2109.00110*, 2021.

Appendices

A. Proofs

Proof of Theorem 1. Fix a threshold $\tau \in \mathcal{T}$. Because A_τ and g_F are computed without calibration labels, the accepted calibration examples are an i.i.d. sample from the conditional deployment distribution given $A_\tau(X) = 1$, conditional on the number m_τ of accepted examples. Therefore, when $m_\tau > 0$, the accepted-error count satisfies

$$k_\tau \mid m_\tau \sim \text{Binomial}(m_\tau, R(\tau)).$$

If $m_\tau = 0$, the convention $U_\alpha(k, 0) = 1$ makes the bound vacuous. For $m_\tau > 0$, the one-sided Clopper–Pearson construction gives

$$\Pr\big[R(\tau) > U_{\delta/|\mathcal{T}|}(k_\tau, m_\tau)\big] \leq \delta/|\mathcal{T}|.$$

Taking a union bound over the finite predeclared grid yields

$$\Pr\big[\exists \tau \in \mathcal{T} : R(\tau) > U_{\delta/|\mathcal{T}|}(k_\tau, m_\tau)\big] \leq \delta.$$

On the complementary event, all grid cells are simultaneously valid. Since Eq. 13 selects $\hat{\tau}$ from this same grid after calibration, the selected threshold inherits the bound. If Eq. 13 is feasible, then $U_{\delta/|\mathcal{T}|}(k_{\hat{\tau}}, m_{\hat{\tau}}) \leq \epsilon$, hence $R(\hat{\tau}) \leq \epsilon$ on the simultaneous-validity event. □

Proof of Theorem 2. The map f depends only on the development split, so $\hat{\tau}$ is $\sigma(\mathcal{D}_{\text{dev}})$-measurable and independent of the calibration split. Conditional on the event $\hat{\tau} = \tau^\circ$ and on $m = m_{\tau^\circ}^{\text{cal}} = m^\circ > 0$, the cal accepted-error count is binomial:

$$k \mid \hat{\tau} = \tau^\circ, m = m^\circ \sim \text{Binomial}(m^\circ, R(\tau^\circ)).$$

The one-sided Clopper–Pearson bound therefore satisfies, for every fixed τ° and $m^\circ > 0$,

$$\Pr[R(\tau^\circ) > U_\delta(k, m^\circ) \mid \hat{\tau} = \tau^\circ, m = m^\circ] \leq \delta.$$

The certificate outputs $\hat{\tau}_{\text{out}} \neq \bot$ only when $m > 0$ and $U_\delta(k, m) \leq \epsilon$. Thus, conditional on any selected $\hat{\tau}$ and cal accept count $m > 0$, the implication

$$\hat{\tau}_{\text{out}} \neq \bot \implies R(\hat{\tau}_{\text{out}}) \leq U_\delta(k, m) \leq \epsilon$$

fails with probability at most δ. The reject-all branches make the implication true by convention. Marginalizing over $\hat{\tau}$ and m gives the stated probability bound. □

Proof of Proposition 1. Because $\mathcal{O}(x)$ contains no formal decision or equivalence relation for c_u, construct two possible latent interpretations that agree on all observed generated artifacts, weights, statuses, proved classes, and error logs. In the first interpretation, the selected class c_s is the intended correct answer class. In the second, the unresolved inequivalent class c_u is the intended correct answer class, while the formal observation remains unchanged because c_u was not resolved and no equivalence to c_s was established. The verifier-only selector receives identical observations in both interpretations and therefore returns the same class c_s. It is correct in the first interpretation and incorrect in the second. Thus the formal observation alone cannot yield a pointwise correctness certificate that is valid across all latent interpretations compatible with the unresolved rival. □

B. Method and Calibration Details

Instance-level decision rule.

dev-then-cal selection and certification. Define

$$\mathcal{T}_{\text{dev}} = \big\{\tau \in \mathcal{T} : m_\tau^{\text{dev}} > 0, \ k_\tau^{\text{dev}}/m_\tau^{\text{dev}} \leq \epsilon\big\}.$$

If $\mathcal{T}_{\text{dev}} = \emptyset$, the procedure returns reject-all. Otherwise,

$$\hat{\tau}_{\text{DC}} = \arg\max_{\tau \in \mathcal{T}_{\text{dev}}} m_\tau^{\text{dev}},$$

Algorithm 1 Coverage-calibrated formal selection (CovCal). Lean is trusted only when the proved answer class dominates enough formally visible answer-class mass.

Require: problem x, candidates $a_{1:K}$, weights $q_{1:K}$, statuses $s_{1:K}$, thresholds τ, fallback g_N
    Normalize candidates into answer classes $\mathcal{C}(x)$ and class weights $Q_c(x)$.
    Aggregate formal statuses into class indicators $T_c(x)$ and $P_c(x)$.
    Compute $C_{\text{typ}}(x)$, $C_{\text{prf}}(x)$, unresolved rival mass $R_{\text{unres}}(x)$, and margin $M(x)$.
    if no class is proved or conflicting proved classes exist **then**
        Return reject formal selection
    end if
    if $C_{\text{typ}}(x) \geq \tau_{\text{typ}}$, $C_{\text{prf}}(x) \geq \tau_{\text{prf}}$, and $M(x) \geq \tau_M$ **then**
        Return the highest-weight proved class $g_{\text{F}}(x)$
    else
        Return $\perp$ for selective evaluation, or $g_N(x)$ for full-answer evaluation
    end if

---

with deterministic lexicographic tie-breaking. This dev-stage screen is not a certificate; it is only a threshold-selection rule. The selected threshold is then certified on the independent calibration split and returned only if

$$m_{\hat{\tau}_{\text{DC}}}^{\text{cal}} > 0 \quad \text{and} \quad U_\delta\left(k_{\hat{\tau}_{\text{DC}}}^{\text{cal}}, m_{\hat{\tau}_{\text{DC}}}^{\text{cal}}\right) \leq \epsilon.$$

Otherwise the procedure returns reject-all. The requirement $m_{\hat{\tau}_{\text{DC}}}^{\text{cal}} > 0$ is a practical convention: a zero-coverage rule has vacuous selective risk, but it is reported as reject-all because it accepts no formal predictions.

Edge cases handled by Theorem 2. (i) Empty dev split: $\hat{\tau} = \perp$, reject-all (dev-then-cal is not applicable when the dev fraction is zero). (ii) No dev-feasible cell: $\hat{\tau} = \perp$, reject-all. (iii) Empty cal accept set: $m = 0$, reject-all (the $U_\delta(\cdot, 0) = 1$ convention makes the formula consistent but the certificate explicitly refuses). (iv) All cal accepts are errors: $k = m$, $U_\delta(m, m) = 1$, certificate refuses. (v) Multiple ϵ targets on the same data: select $\hat{\tau}$ once on dev and report the cal-side $U_\delta(k, m)$ as a single number, then check against each ϵ separately. Re-selecting per ϵ would re-introduce multiplicity and break the guarantee. (vi) Dev/cal/test distribution mismatch: the theorem fails. The i.i.d. assumption in the statement is necessary. (vii) $\hat{\tau}$ depends on cal: the theorem fails. Strict $\sigma(\mathcal{D}_{\text{dev}})$-measurability of $\hat{\tau}$ is the load-bearing assumption.

Practical choices. The method is deterministic after candidate generation and formalization logs are fixed. In experiments, we use self-consistency frequency as the primary weight: if K sampled solutions collapse to answer classes c, then Q_c is the fraction of samples in class c. Reranker-derived weights are reported only as an ablation. A class is marked proved if any of its formal artifacts is kernel checked; it is marked typed if any artifact elaborates or reaches proof search. If one artifact proves and another artifact for the same class fails, the class remains proved but the failure is retained for diagnostics. If two proved classes are inequivalent under answer normalization, the formal selector rejects rather than choosing between them. The threshold grid, target risk ϵ, confidence level $1 - \delta$, normalization rules, Lean version, imports, and proof budgets are fixed before calibration labels are used.

C. Implementation Details

The following items document the protocol used in the reported runs:

1. **Main dataset:** all-levels MATH-500, 378 kept after filtering (500 raw minus 122 excluded for non-normalizable references, proof-only items, and diagram-dependent geometry).

2. **Hard subset:** MATH-500 levels 4–5 only, 199 kept after the same filters.

3. **Candidate generator:** Qwen2.5-Math-7B-Instruct (bfloat16, vLLM 0.10.2), $K = 32$ samples, temperature 0.7, top-$p = 0.95$, maximum 2048 new tokens, final answer in
   `boxed{...}`.

4. **Class aggregation:** normalize final answers and compute Q_c from self-consistency frequency.

5. **Formalization:** Qwen2.5-Coder-7B-Instruct (bfloat16) autoformalization with four artifacts per top class and one error-feedback repair pass.

6. **Formalized classes:** top four classes per problem.

7. **Lean proving:** Lean $4.21.0$ with Mathlib at commit `308445d7`; tactic portfolio `norm_num`, `ring_nf`, `omega`, `linarith`, `nlinarith`, `simp`, `aesop`, `decide`, and short combinations; 20 seconds per tactic script.

8. **Calibration:** 20/40/40 development/calibration/test split with seed 0; target selective risk $\epsilon = 0.15$ on the all-levels run and $\epsilon = 0.10$ on the hard subset; confidence $1 - \delta = 0.95$; Clopper–Pearson bounds with Bonferroni correction over $\mathcal{T}$ (Appendix D; $|\mathcal{T}| = 125$).

9. **Baselines reported:** self-consistency, confidence-only abstention, raw Lean+fallback, proof-existence abstention, typed-coverage only, proved-coverage only, margin-only, COVCAL, and COVCAL+fallback.

D. Threshold Grid Used in Experiments

The grid used in all reported runs is

$$
\begin{aligned}
\mathcal{T}_{\text{typ}} &= \{0, 0.25, 0.5, 0.75, 0.9\}, \\
\mathcal{T}_{\text{prf}} &= \{0, 0.1, 0.25, 0.5, 0.75\}, \\
\mathcal{T}_M &= \{-0.5, 0, 0.1, 0.25, 0.5\}, \\
\mathcal{T} &= \mathcal{T}_{\text{typ}} \times \mathcal{T}_{\text{prf}} \times \mathcal{T}_M.
\end{aligned}
\tag{19}
$$

The grid must be fixed before inspecting calibration labels. Equation 13 then selects the accepted-fraction-maximizing rule whose risk upper bound is at most the target ϵ.

E. Prompt Templates

Candidate generation prompt.

Solve the following math problem. Give a concise derivation and put the final answer in boxed{...}. Problem: *[problem text]*

Lean autoformalization prompt.

You are formalizing a math contest answer in Lean 4 with Mathlib. Given the problem and proposed final answer, write a Lean theorem whose proof would certify that the proposed answer is correct for the problem. Requirements: (i) state the problem's actual mathematical claim with the proposed answer substituted in — do **not** write a trivial identity such as answer = answer; the theorem must be false if the answer is wrong; (ii) use $\mathbb{Q}$ or $\mathbb{R}$ (never $\mathbb{N}$) for any division, fraction, or non-integer arithmetic so that division is exact rather than floor division, annotating numeric literals with their type when needed, e.g. (125 : $\mathbb{Q}$) / 9; (iii) prefer simple statements and standard Mathlib notation. Return only Lean code. Problem: *[problem text]* Proposed answer: *[answer class]*

Repair prompt.

The Lean code below failed with the following error. Repair the theorem statement or proof while preserving the intended meaning of the problem and answer. Return only Lean code. Code: *[code]* Error: *[Lean error]*

F. What Is Generated and Analyzed

COVCAL does not require generating a complete formal proof for every problem. It requires a structured log of candidate answers and Lean verification attempts. The minimal unit is an answer class, not a raw model sample. For each problem, the generated record contains:

1. **Problem fields:** problem id, dataset, topic label, problem text, reference answer, normalized reference class, and inclusion/exclusion status.

2. **Candidate fields:** the K raw sampled solutions, extracted final answers, normalized answer classes, and self-consistency weights Q_c.

3. **Formalization fields:** for each top answer class, the generated Lean code, repair-round index, imports, and theorem statement.

4. **Lean fields:** artifact-level status, class-level status, tactic script or proof attempt, runtime, timeout flag, error message, Lean version, Mathlib commit, and hardware.

5. **Selection fields:** self-consistency class, highest-weight proved class, conflict flag, C_{typ}, C_{prf}, R_{unres}, M, CovCal accept/reject decision, fallback decision when used, and correctness.

Per-status definitions.   The best Lean status s_j of an artifact takes one of five values. `proved` means a Lean proof of the generated statement was found and kernel checked. `typechecked` means the statement elaborated but no proof was found. `timeout` means proof search began from a well-formed statement but exceeded the budget. `illtyped` and `unformalized` denote earlier failures. If a pipeline can also prove negations or inequivalence, those outcomes can be added as optional decisive statuses; they are not required by our method.

Existing verified Lean proofs.   Existing proof corpora can be used for supplementary analysis of proof-search or proof-edit coverage, but they do not replace the main answer-selection experiment. CovCal requires multiple candidate final-answer classes with weights and correctness labels. A corpus of already verified Lean proofs usually supplies proof success but not alternative wrong answer classes, unresolved rival mass, or natural-language answer-selection labels.

G. Additional Experimental Details

Filtering and splits.   We include problems whose final answer can be extracted as a number, expression, set, interval, finite tuple, or multiple-choice label mapped to a mathematical answer. We exclude diagram-dependent geometry, proof-only items, and examples whose official answer cannot be normalized. MATH-500 contributes 378 kept examples after 122 exclusions; the hard levels-4/5 subset is the 199-example slice of these at levels 4 and 5. Unless otherwise stated, examples are split after generation and formalization into development, calibration, and test partitions. The seed-0 split is preregistered; the bootstrap summaries resample the frozen observations over $K = 20$ dev/cal/test partitions.

Generation and normalization.   Qwen2.5-Math-7B-Instruct generates 32 solutions per problem at temperature 0.7, top-$p = 0.95$, and maximum 2048 new tokens. The normalizer strips admissible units and formatting, canonicalizes fractions/decimals/signs/whitespace, parses simple symbolic expressions, tests numeric equivalence for rationals, decimals, radicals, and finite tuples, and logs ambiguous cases. Class weights are self-consistency frequencies over normalized answer classes.

Formalization and Lean proving.   For each of the top four answer classes, Qwen2.5-Coder-7B-Instruct produces four Lean artifacts, followed by one error-feedback repair pass when elaboration fails. Lean proof search uses Lean 4.21.0 with Mathlib commit `308445d7`; the tactic portfolio is `norm_num`, `ring_nf`, `omega`, `linarith`, `nlinarith`, `simp`, `aesop`, `decide`, and short combinations, with a 20-second per-script budget. Main-run class-level statuses are 140 proved, 271 typechecked, 251 illtyped, 0 timeout, and 741 unformalized over 1403 answer-class observations, indicating that autoformalization-tier coverage, not prover timeout, dominates the negative trace.

Baselines.   The reported baselines are self-consistency, confidence-only abstention, raw Lean plus fallback, proof-existence abstention, typed-coverage-only, proved-coverage-only, margin-only, CovCal, and CovCal plus fallback. The fallback is self-consistency. Fallback predictions are useful for overall accuracy but are not covered by the selective-risk certificate unless separately calibrated.

Compute and hardware.   All experiments ran on a single compute node with one NVIDIA H100 80GB HBM3 GPU and 8 allocated CPU cores; generation and autoformalization use vLLM on the GPU, while Lean proof search runs on the CPU within the same job. The autoformalizer ablations took approximately 5.5 (Goedel-Prover-V2-8B) and 4.9 (Goedel-Prover-V2-32B) GPU-hours, and the main MATH-500 and AMC/AIME runs a few GPU-hours each (generation is replayed from cache across the ablations), for roughly 15–20 GPU-hours in total across all reported runs.

Selector	Overall	Accepted	Acc. frac.	Test UB
Self-consistency	0.910	0.910	1.000	0.138
Confidence-only	0.866	0.969	0.894	0.068
Raw Lean + fallback	0.891	0.891	1.000	0.159
Proof-existence	0.193	0.877	0.220	0.258
Typed-coverage only	0.194	0.867	0.224	0.268
Proved-coverage only	0.194	0.874	0.222	0.258
Margin only	0.194	0.932	0.209	0.192
CovCal	0.194	0.932	0.209	0.192
CovCal+fallback	0.905	0.905	1.000	0.144

Table 4. All nine selectors on the main run, dev-then-cal regime ($K = 20$ bootstrap, $n_{\text{cal}} = 151$, $\epsilon = 0.15$; seed-means). *Overall* counts abstentions as errors; *Acc. frac.* is the accepted fraction; *Test UB* is the held-out diagnostic upper bound. The calibrated rows (typed/proved/margin/CovCal) average over the $12/20$ feasible seeds; the others are regime-independent. Margin-only and CovCal coincide, indicating the margin threshold carries most of the selective signal here.

Figure 2. Accepted fraction versus held-out selective-risk upper bound on the main run (dev-then-cal; $K = 20$ bootstrap mean). The dashed line is $\epsilon = 0.15$. The formal selectors accept $\approx 21\%$ of items just above ϵ, while confidence-only abstention reaches 0.89 coverage at lower diagnostic risk; +fallback variants (full coverage) and the Bonferroni reject-all case are omitted.

H. Additional Results

This appendix presents supporting evidence behind the results summary in Sec. 8. Tables 5–10 provide the corresponding per-level, sensitivity, failure-status, and robustness details.

H.1. Full Answer-Selection Comparison

Table 4 reports all nine selectors on the main run under the dev-then-cal regime (under Bonferroni the calibrated rows are reject-all; Table 3). The single-diagnostic selectors clarify which diagnostic carries the signal: margin-only matches the joint CovCal rule exactly (0.93 accepted accuracy at 0.21 accepted fraction), whereas typed- and proved-coverage alone are slightly less precise. Thus, the formal margin carries most of the selective signal at this protocol. Figure 2 plots the accepted-fraction/risk tradeoff for the main selectors.

H.2. Per-Level and Domain Breakdowns

Table 2 bins the cliff coarsely; Table 5 aggregates the same main-run observations by MATH-500 difficulty level. Both coverage and reliability decline monotonically with difficulty: mean proved coverage falls from 0.44 at level 1 to 0.16 at level 5, and proof-existence accuracy on the proved subset falls from 1.00 to 0.74. The coverage drop is the steeper of the two (a $2.7\times$ reduction versus $1.4\times$ for accuracy), so in this protocol increasing difficulty primarily reduces visible formal coverage, while in-bin reliability degrades more slowly.

Table 6 gives a domain-level view. Geometry and calculus/analysis have substantially lower typed and proved coverage than algebra, number theory, and combinatorics (proved coverage 0.19 and 0.05 versus 0.23–0.31), so far fewer of their problems reach any formal verdict. This supports this work's central interpretation that the reliability of Lean-as-judge depends on how much answer-class mass becomes representable and decidable by the formal pipeline.

Level	n	$\bar{C}_{\text{typ}}$	$\bar{C}_{\text{prf}}$	PE acc.	Cert. feas.
1	35	0.797	0.441	1.00	–
2	64	0.733	0.328	0.91	–
3	80	0.627	0.226	0.90	–
4	97	0.616	0.191	0.78	–
5	102	0.520	0.162	0.74	–

Table 5. Per-level breakdown on the main MATH-500 run. $\bar{C}_{\text{typ}}$ and $\bar{C}_{\text{prf}}$ are mean typed/proved coverage within each level. PE acc. is proof-existence accepted accuracy on examples where at least one answer class is proved. Cert. feas. asks whether proof-existence alone certifies $\epsilon = 0.15$ within that level using the same Bonferroni confidence budget; all individual levels are too small for this single-bin stand-in to certify, which is expected and should not be read as evidence of zero useful signal.

Domain	n	Typed	Proved	Acc.	Top failure
Algebra	241	0.663	0.234	0.89	illtyped
Number theory	60	0.684	0.314	0.82	illtyped
Combinatorics	30	0.621	0.281	0.70	illtyped
Geometry	24	0.490	0.194	0.86	illtyped
Calculus / analysis	23	0.281	0.053	1.00	illtyped

Table 6. Domain-level formal coverage on the main run. Typed and Proved are mean C_{typ} and C_{prf} per domain; Acc. is the accuracy of the highest-weight proved class among problems where a proof exists; Top failure is the modal class-level Lean status among unsuccessful artifacts. Coverage is markedly lower for geometry and calculus/analysis (typed 0.49 and 0.28 versus 0.66 for algebra); the Acc. column is over the small proved subset of each domain (e.g. only 2 proved problems in calculus/analysis) and is noisy.

H.3. Status Counts and ϵ-Sensitivity

Table 7 gives the automated Lean-status breakdown. The dominant statuses are `unformalized` and `illtyped`; timeouts on well-formed statements are absent in the main run. These status counts support the claim that the main bottleneck occurs before proof search, but they remain coarser than a manual semantic audit.

Why the 32**B autoformalizer does not help (status-level view).** Table 8 compares class-level Lean statuses for the two Goedel-Prover-V2 autoformalizers with generation held fixed, and explains the headline of Sec. 8.3, that scaling from 8B to 32B lowers proved coverage ($79\% \rightarrow 64\%$). The gap is not a proof-search timeout: `timeout` is 0 for both models. Both models also elaborate statements at essentially the same rate. The `unformalized` count is nearly identical (656 vs. 651 of 1380 classes). The entire difference is a `proved`→`typechecked` shift: 493 classes are proved by the 8B but only 347 by the 32B, with the lost mass reappearing as `typechecked` ($191 \rightarrow 323$). The larger model writes statements that type-check just as often but that the fixed Mathlib tactic portfolio closes less often, consistent with prover specialization (shared by both Goedel-Prover-V2 models), rather than raw parameter count, being what lifts proved coverage past the certificate-feasibility threshold.

Table 9 reports the Bonferroni calibration certificates on the seed-0 main split. This table is intentionally separated from held-out answer-selection diagnostics: it is the calibration-side certificate used by the selection rule. On the sparse real signal the main split returns reject-all through $\epsilon = 0.20$ and certifies only at $\epsilon \gtrsim 0.26$; the smallest achievable Bonferroni upper bound at the most permissive cell is 0.257, well above the preregistered target $\epsilon = 0.15$.

A coarse-grid sensitivity check gives the same qualitative conclusion: a $3 \times 3 \times 3$ grid lowers the most-permissive-cell upper bound only modestly and does not bring it below $\epsilon = 0.15$. Thus the reject-all verdict is driven by the sparsity of the proved signal and the resulting accepted-set errors, not by the granularity of the threshold grid.

H.4. Hard Subset and AMC/AIME

Table 10 records two robustness settings. The hard MATH-500 levels 4–5 subset ($n = 199$, the hardest slice of the main run) has an even sparser proved signal than the full set and returns reject-all under *both* regimes at the stricter target $\epsilon = 0.10$. An AMC/AIME-style out-of-distribution set ($n = 164$), run on the same pipeline, confirms that the sparsity persists under a harder problem distribution: self-consistency accuracy is far lower (0.40 versus 0.91 on MATH-500), the proved signal is sparse (proof-existence accepts only $\approx 11\%$ of test items), and both certificate regimes return reject-all at $\epsilon = 0.10$.

For the hard subset, confidence-only abstention can produce a low held-out error bound, but that is not a Lean-backed formal

Lean class-level status	Count	Share
unformalized	741	0.528
typechecked	271	0.193
illtyped	251	0.179
proved	140	0.100
timeout	0	0.000

Table 7. Class-level Lean status distribution on the main run (1403 answer-class observations across 378 problems; best status per class). The taxonomy is automatic and based on pipeline statuses. Most answer classes are never formalized or fail elaboration; only 10% are proved, and no well-formed statement times out.

Lean class-level status	Goedel-V2-8B	Goedel-V2-32B
proved	493	347
typechecked	191	323
illtyped	40	59
unformalized	656	651
timeout	0	0
Proved coverage (problems)	79.1%	63.5%

Table 8. Class-level Lean status counts for the two autoformalizer ablations (1380 answer-class observations over the same 378 problems; best status per class, generation held fixed). Scaling 8B→32B leaves `unformalized` and `timeout` essentially unchanged but shifts mass from `proved` to `typechecked`: the larger model's statements elaborate as often but are closed by the fixed tactic portfolio less often, so proved coverage falls from 79% to 64%.

certificate. The formal coverage-based rows reject because the calibration-side Bonferroni upper bound for proof-existence alone is already above the target. This is the intended conservative behavior of the certificate when formal coverage is too low for the specified risk level.

I. Worked Examples

The three cases of Section 8.2 are presented next.

(A) Accept — faithful proof, full coverage. *Problem:* "What is the 2003rd term of the sequence of odd numbers $1, 3, 5, 7, \ldots$?" *Reference answer:* 4005. All $K{=}32$ samples collapse to the single answer class 4005 ($w{=}1.0$), which is proved. The kernel-checked statement is

$$2 \cdot 2003 - 1 = 4005 \qquad (\text{by } \texttt{norm\_num}),$$

a faithful closed form of "the nth odd number is $2n - 1$." Diagnostics: $C_{\text{typ}}{=}C_{\text{prf}}{=}1$, margin 1. COVCAL accepts 4005 (correct). *Lesson:* a proof is trusted when the proved class dominates the formally visible mass with a clear margin.

(B) Abstain — no formal signal, fallback correct. *Problem:* "Simplify $\cos\frac{2\pi}{15} \, \cos\frac{4\pi}{15} \, \cos\frac{8\pi}{15} \, \cos\frac{16\pi}{15}$." *Reference answer:* $\frac{1}{16}$. The dominant class $1/16$ ($w{=}0.84$) and the minor classes $1/32$ and $1/8$ all fail Lean elaboration. The trigonometric product identity does not autoformalize. So, $C_{\text{typ}}{=}C_{\text{prf}}{=}0$ and no class is proved. COVCAL abstains; the self-consistency fallback returns $1/16$ (correct). *Lesson:* a missing proof is unresolved, not negative; abstention plus fallback preserves the correct answer.

(C) Abstain — margin distrusts a vacuous proof of a wrong rival. *Problem:* "An equilateral triangle is inscribed in the parabola $x^2 = 8y$, such that one of the vertices of the triangle coincides with the vertex of the parabola. Find the side length of this equilateral triangle." *Reference answer:* $16\sqrt{3}$. The correct class $16\sqrt{3}$ ($w{=}0.88$) fails to autoformalize (illtyped); the only proved class is a low-weight rival 16 ($w{=}0.03$), whose "proof" is the vacuous identity

$$(16 : \mathbb{Q}) = 16 \qquad (\text{by } \texttt{norm\_num}),$$

which holds for any value and therefore provides no evidence about the answer. Diagnostics: $C_{\text{prf}}{=}0.03$, margin -0.84. Because the proved class carries far less weight than the unresolved dominant class, the strongly negative margin makes

ϵ	Selected $\hat{\tau}$	$(m_{\hat{\tau}}, k_{\hat{\tau}})$	Cal. UB
0.05	reject-all	n/a	n/a
0.10	reject-all	n/a	n/a
0.15	reject-all	n/a	n/a
0.20	reject-all	n/a	n/a
0.30	$(0, 0.1, 0)$	$(35, 1)$	0.257

Table 9. Bonferroni calibration-split certificates for the seed-0 main run ($n_{\mathrm{cal}} = 151$, $\delta = 0.05$, $|\mathcal{T}| = 125$). On the sparse real signal no grid cell certifies through $\epsilon = 0.20$, so COVCAL returns reject-all at the preregistered target $\epsilon = 0.15$; the most permissive cell first certifies near $\epsilon = 0.26$ with calibration upper bound 0.257. This is the conservative regime correctly refusing when the proved signal is too sparse to pay the $|\mathcal{T}| = 125$ union bound.

Setting	n	n_{cal}	ϵ	SC	PE acc.	PE frac. / verdict
Main MATH-500	378	151	0.15	0.910	0.877	0.220 / dev-cal 12/20
Hard MATH-500 L4–5	199	80	0.10	0.859	0.761	0.231 / reject-all (both)
AMC/AIME	164	66	0.10	0.400	0.429	0.108 / reject-all (both)

Table 10. Robustness settings versus the full main run. SC is self-consistency test accuracy; PE acc. and PE frac. are proof-existence accepted accuracy and accepted fraction; the last field gives the certificate verdict (ϵ as listed). The hard subset is the level-4/5 slice of the main run ($n = 199$); its proved signal is even sparser, so both regimes reject-all at the stricter $\epsilon = 0.10$. The AMC/AIME row is an out-of-distribution check on the same pipeline; its sparser signal and lower self-consistency accuracy likewise yield reject-all under both regimes at $\epsilon = 0.10$.

COVCAL abstain; the fallback recovers $16\sqrt{3}$ (correct). *Lesson:* proof existence on a low-weight or trivially formalized rival is correctly distrusted by the margin.