Max-Min Off-Policy Actor-Critic Method Focusing on Worst-Case Robustness to Model Misspecification

Abstract

In the field of reinforcement learning, owing to the high cost and risk of policy training in the real world, policies trained in a simulation environment are often transferred corresponding real-world environment. However, the simulation environment does not perfectly mimic the real-world environment, leading to model misspecification occurs. Multiple studies report significant deterioration of policy performance in a real-world environment. In this study, we focus on scenarios involving a simulation environment with uncertainty parameters and the set of their possible values, called the uncertainty parameter set. The aim is to optimize the worst-case performance on the uncertainty parameter set to guarantee the performance in the corresponding real-world environment, if it is included in the uncertainty parameter set. To obtain a policy that optimizes the worst-case performance, we propose an off-policy actor-critic approach called the Max-Min Twin Delayed Deep Deterministic Policy Gradient Algorithm (M2TD3), which solves a max-min optimization problem using a simultaneous gradient ascent descent approach. Experiments in Multi-Joint Dynamics with Contact (MuJoCo) environments show that the proposed method exhibited a worst-case performance superior to several baseline approaches.

1 Introduction

Applications of Deep Reinforcement Learning (DRL) to control tasks that involving interaction with the real world are limited due to the need for interaction between the agent and the real-world environment [33]. This difficulty arises because of (1) high interaction time costs, (2) high agent maintenance costs, and (3) safety issues during the interaction. Without enough interactions, DRL tends to overfit to specific interaction histories and to yields policies with poor generalizability and safety issues [25].

To circumvent this difficulty in performing many real-world interactions, simulation environments that estimate the characteristics of real-world environments are often employed. In such cases, the policy is trained in the simulation environment and then transferred to the real-world environment [37]. The use of a simulation environment enables enough interactions for effective DRL application. Moreover, because fast and general-purpose simulators such as Open Dynamics Engine (ODE) [30], Bullet [3] and Multi-Joint Dynamics with Contact (MuJoCo) [34] are available in the field of robotics, the cost of developing a simulation environment can sometimes be significantly lower than that for real-world interaction. However, because a simulation environment is an estimation of the real-world environment, discrepancies exist between the two [2]. Even if the simulation environment perfectly replicates the real-world environment, discrepancies may still occur; for example, as a result of robot degradation over time or weight changes due to part replacements [19]. Studies report significant degradation of policy trained in a simulation environment when transferred to the corresponding

37 real-world environment has been reported [8]. The above discrepancies limit the use of simulator
38 environments in practice, and thus, limit the use of DRL.

39 In this study, to guarantee performance in the corresponding real-world environment, we aim to
40 obtain a policy that maximizes the expected reward under the worst-case scenario in the uncertainty
41 parameter set Ω. We focus on a scenario where (1) a simulator $\mathcal{M}_\omega$ is available, (2) the model
42 uncertainty is parameterized by $\omega \in \Omega$ and ω is configurable in the simulation, and (3) the real-world
43 environment is realized with some $\omega^* \in \Omega$, where ω^* is fixed during an episode; however, (4) ω^* is
44 unknown or not fixed over episodes. We develop an off-policy deep deterministic actor-critic approach
45 to optimize the worst-case performance, called the Max-Min Twin Delayed Deep Deterministic Policy
46 Gradient Algorithm (M2TD3). By extending the bi-level optimization formulation of the standard
47 actor-critic method [26], we formulate our problem as a tri-level optimization, where the critic
48 network models a value for each tuple of state, action, and uncertainty parameter, and the actor
49 network models the policy of an agent and an estimate of the worst uncertainty parameter value. Based
50 on the existing deep deterministic actor-critic approach [17, 7], we design an algorithm to solve the
51 tri-level optimization problem by implementing several technical components to stabilize the training,
52 including multiple uncertainty parameters, their refreshing strategies, uncertainty parameter sampler
53 for interaction, and soft-min policy update. Numerical experiments on 19 MuJoCo environments
54 reveal the competitive and superior worst-case performance of our proposed approaches compared to
55 several baseline approaches.

2 Preliminaries

57 We consider an episodic Markov decision process (MDP) [6] family $\mathcal{M}_\Omega = \{\mathcal{M}_\omega\}_{\omega \in \Omega}$, where
58 $\mathcal{M}_\omega = \langle S, A, p_\omega, p_\omega^0, r_\omega, \gamma \rangle$ is the MDP with uncertainty parameter $\omega \in \Omega$. The state space S
59 and the action space A are subsets of real-valued vector spaces. The transition probability density
60 $p_\omega : S \times A \times S \to \mathbb{R}$, the initial state probability density $p_\omega^0 : S \to \mathbb{R}$ and the immediate reward
61 $r_\omega : S \times A \to \mathbb{R}$ depend on ω. The discount factor is denoted by $\gamma \in (0, 1)$.

62 We focus on an episodic task on $\mathcal{M}_\Omega$. Let $\mu_\theta : S \to A$ be a deterministic policy parameterized by
63 $\theta \in \Theta$. Given an uncertainty parameter $\omega \in \Omega$, the initial state follows $s_0 \sim p_\omega^0$. At each time step
64 $t \geqslant 0$, the agent observes state s_t and select action $a_t = \mu_\theta(s_t)$, interact with the environment; and
65 observes the next state $s_t' \sim p_\omega(\cdot \mid s_t, a_t)$, the immediate reward $r_t = r_\omega(s_t, a_t)$, and the termination
66 flag h_t. Here, $h_t = 1$ if s_t' is a terminal state or a predefined maximal time step for each past episode;
67 otherwise, $h_t = 0$. If $h_t = 0$, let $s_{t+1} = s_t'$; otherwise, the next state is reset by $s_{t+1} \sim p_\omega^0$. For
68 simplicity, we let $q_\omega(s_{t+1} \mid s_t, a_t)$ be the probability density of s_{t+1} given s_t and a_t. The discount
69 reward of the trajectory starting from time step t is $R_t = \sum_{k \geqslant 0} \gamma^k r_{t+k}$.

70 The action value function $Q^{\mu_\theta}(s, a, \omega)$ under ω is the expectation of R_t starting with $s_t = s$ and $a_t =$
71 a under ω; that is, $Q^{\mu_\theta}(s, a, \omega) = \mathbb{E}[R_t \mid s_t = s, a_t = a, s_{t+k+1} \sim q_\omega(\cdot \mid s_{t+k}, \mu_\theta(s_{t+k})) \, \forall k \geqslant 0]$,
72 where the expectation is taken over s_{t+k+1} for $k \geqslant 0$. Note that we introduce ω to the argument to
73 explain the Q-value dependence on ω; however, this is essentially the same definition as that for the
74 standard action value function $Q^{\mu_\theta}(s, a)$. The recursive formula is as follows:

$$Q^{\mu_\theta}(s, a, \omega) = r_\omega(s, a) + \gamma \mathbb{E}[Q^{\mu_\theta}(s', \mu_\theta(s'), \omega) \mid s' \sim q_\omega(\cdot \mid s, a)] \ . \tag{1}$$

75 We consider an off-policy reinforcement learning setting, where the agent interacts with $\mathcal{M}_\omega$ using a
76 stochastic behavior policy $\beta : S \times A \to \mathbb{R}$. However, the target policy to be optimized, denoted by
77 μ_θ is deterministic. Under a fixed $\omega \in \Omega$, the standard objective of off-policy learning is to maximize
78 the expected action value function over the stationary distribution ρ^β, such that

$$J_\omega(\theta) = \int_{s \in S} \rho^\beta(s \mid \omega) Q^{\mu_\theta}(s, \mu_\theta(s), \omega) \mathrm{d}s \ . \tag{2}$$

79 Here, $\rho^\beta(s \mid \omega) = \lim_{T \to \infty} \frac{1}{T} \sum_{t=0}^{T-1} \int_{s_0} q_{\omega,\beta}^t(s \mid s_0) p_\omega^0(s_0) \mathrm{d}s_0$ denotes the stationary distribution
80 under β and a fixed $\omega \in \Omega$, where the step-t transition probability density $q_{\omega,\beta}^t$ is defined as
81 $q_{\omega,\beta}^1(s' \mid s) = \int_{a \in A} q_\omega(s' \mid s, a) \beta(a \mid s) \mathrm{d}a$ and $q_{\omega,\beta}^t(s' \mid s) = \int_{\bar{s} \in S} q_{\omega,\beta}^{t-1}(\bar{s} \mid s) q_{\omega,\beta}^1(s' \mid \bar{s}) \mathrm{d}\bar{s}$.

82 We assume that the agent can interact with $\mathcal{M}_\omega$ for any $\omega \in \Omega$ during the training and can change
83 ω after every episode; that is, when $h_t = 1$. Our objective is to obtain the μ_θ that maximizes $J_\omega(\theta)$
84 under the worst environment $\omega \in \Omega$. In other words, we tackle the max-min optimization problem
85 requiring $\max_{\theta \in \Theta} \min_{\omega \in \Omega} J_\omega(\theta)$.

3 Related Work

Methods to handle model misspecification include (1) robust policy searching [23, 27, 20, 15, 12, 19], (2) transfer learning [32, 35, 28], (3) domain randomization (DR) [33], and (4) approaches minimizing worst-case sub-optimality gap [5, 18]. Robust policy searching includes methods that try to obtain the optimal policy under the worst possible disturbance or model misspecification, i.e., maximization of $\min_{\omega \in \Omega} J_\omega(\theta)$ for an explicitly or implicitly defined Ω. Transfer learning is a method in which a policy is trained on source tasks and then fine-tuned through interactions while performing the target task. DR is a method in which a policy is trained on source tasks that are sampled randomly from $\mathcal{M}_\Omega$. There are two types of DR approach: vanilla and guided. In vanilla DR [33], the policy is trained on source tasks that are randomly sampled from a pre-defined distribution on Ω. In guided DR [36], the policy is trained on source tasks; however, the ω distribution is guided towards the target task. Because we do not assume access to the target task, transfer learning and many guided DR approaches are outside the scope of this work. Some guided DR approaches, such as Active Domain Randomization [21], do not access the target task; however, they do not consider worst-case optimization either. Vanilla DR can be applied to the setting considered here. However, the objective of vanilla DR differs from the present aim, i.e., to maximize the performance averaged over Ω, that is, $\mathbb{E}_\omega[J_\omega(\theta) \mid \omega \sim \mathcal{U}(\Omega)]$, if the sampling distribution is $\mathcal{U}(\Omega)$. Approaches minimizing the worst-case sub-optimality gap [5, 18] do not optimize the worst-case performance, but attempt to obtain a policy that generalizes well on the uncertainty parameter set while avoiding too conservative performance which often attributes to the worst-case performance optimization.

Among the existing robust policy search methods, some adopt an adversarial approach to policy optimization. For example, Robust Adversarial Reinforcement Learning (RARL) [27] models the disturbance caused by an external force produced by an adversarial agent, and alternatively trains the protagonist and adversarial agents. Robust Reinforcement Learning (RRL) [23] models the disturbance in the same manner but has not been applied to the DRL framework. Minimax Multi-Agent Deep Deterministic Policy Gradient (M3DDPG) [15] has been designed to obtain a robust policy for multi-agent settings. This method is applicable to the setting targeted in this work if only two agents are considered. The above approaches frame the problem as a zero-sum game between a protagonist agent attempting to optimize μ_θ and an adversarial agent attempting to minimize the protagonist's performance, hindering the protagonist by generating the worst possible disturbance. If we consider ω as the disturbance policy parameter, and if the effect of the disturbance policy is included in p_ω, these settings are included in our formulation.

Other approaches attempt to estimate the robust value function, i.e., a value function under the worst uncertainty parameter. Among them, Robust Dynamic Programming (DP) [12] is a DP approach, while the Robust Options Policy Iteration (ROPI) [20] incorporates robustness into option learning [31], which allows agents to learn both hierarchical policies and their corresponding option sets. Robust Maximum A-posteriori Policy Optimization (R-MPO) [19] incorporates robustness in MPO [1]. Neither ROPI nor R-MPO require interaction with M_ω for an arbitrary $\omega \in \Omega$. This can be advantageous in scenarios where design of a simulator valid over Ω is tedious. However, methods of this type typically require additional assumptions for computation of the worst-case for each value function update, such as the finiteness of the state-action space and/or the finiteness of Ω. One can apply R-MPO to our setting by sampling finite scenarios from Ω for training. However, the choice of the training scenarios affect the worst-case performance.

Table 1 summarizes the robust policy search method taxonomy. Our proposed approach, M2TD3, considers the uncertainties in both the reward function and transition probability. The state and action spaces, as well as the uncertainty set, are assumed to be continuous. Table 2 compares the related methods considering their action value function definitions. For the methods that do not explicitly utilize action value function, those functions are interpreted from the objective functions. Both M3DDPG and M2TD3 maintain the value function for the tuple of (s, a, ω). However, a difference exists in that M3DDPG takes the worst ω' on the right-hand side, which yields a more

Table 1: Taxonomy of robust policy search. Cont.: Continuous space. Disc.: Discrete space.

Method	Uncertainty	S & A	Ω
R-MPO	Transition	Cont.	Disc.
ROPI	Transition	Disc.	Cont.
PAIRED, RARL, M3DDPG, RRL, M2TD3	Reward & Transition	Cont.	Cont.

Table 2: Comparison of action value functions in related methods

Method	Action Value Function
R-MPO, ROPI, Robust DP	$Q(s,a) = r(s,a) + \gamma \min_{\omega \in \Omega} \mathbb{E}[Q(s',\mu_\theta(s')) \mid s' \sim p_\omega(\cdot \mid s,a)]$
DR	$Q(s,a) = \mathbb{E}_{\omega \in \Omega}[r_\omega(s,a) + \gamma \mathbb{E}[Q(s',\mu_\theta(s')) \mid s' \sim p_\omega(\cdot \mid s,a)]]$
RRL, RARL	$Q_\omega(s,a) = r_\omega(s,a) + \gamma \mathbb{E}[Q_\omega(s',\mu_\theta(s')) \mid s' \sim p_\omega(\cdot \mid s,a)]$
M3DDPG	$Q(s,a,\omega) = r_\omega(s,a) + \gamma \mathbb{E}[\min_{\omega' \in \Omega} Q(s',\mu_\theta(s'),\omega') \mid s' \sim p_\omega(\cdot \mid s,a)]$
M2TD3	$Q(s,a,\omega) = r_\omega(s,a) + \gamma \mathbb{E}[Q(s',\mu_\theta(s'),\omega) \mid s' \sim p_\omega(\cdot \mid s,a)]$

conservative policy than M2TD3 for our setting. The value functions in RARL and M2TD3 are identical if ω is fixed. Note that ω is not introduced to the RARL value function because it does not simultaneously optimize μ_θ and the estimate of the worst ω. RARL repeats the θ and ω optimizations alternatively. In contrast, M2TD3 optimizes θ and ω simultaneously in a manner similar to the training processes of generative adversarial networks (GANs) [9]. For this purpose, we require an action value for each $\omega \in \Omega$.

A difference exists between the optimization strategies of RARL and M2TD3. As mentioned above, both methods try to maximize the worst-case performance $\min_{\omega \in \Omega} J_\omega(\theta)$. Conceptually, RARL repeats $\theta \leftarrow \operatorname{argmax}_\theta J_\omega(\theta)$ and $\omega \leftarrow \operatorname{argmin}_\omega J_\omega(\theta)$. However, this optimization strategy fails to converge even if the objective function $(\theta, \omega) \mapsto J_\omega(\theta)$ is concave-convex. As an example, consider the function $(x,y) \mapsto y^2 - x^2 + \alpha xy$. The RARL optimization strategy reads $x \leftarrow (\alpha/2)y$ and $y \leftarrow -(\alpha/2)x$, which causes divergence if $\alpha > 2$.[1] M2TD3 attempts to alleviate this divergence problem by applying the gradient-based max-min optimization method, which has been employed in GANs and other applications and analyzed for its convergence [22, 16].

4   M2TD3

We propose an off-policy actor-critic approach to obtain a policy that maximizes the worst-case performance on $\mathcal{M}_\Omega$, called M2TD3. Our approach is based on TD3, an off-policy actor-critic algorithm for a deterministic target policy. In TD3, the critic network Q_ϕ parameterized by $\phi \in \Phi$ is trained to approximate the Q^{μ_θ} of μ_θ, whereas the actor network models μ_θ with parameter $\theta \in \Theta$ and is trained to maximize $J_\omega(\theta)$. Note that ω is not considered and is fixed during the training. In this study to obtain the μ_θ that maximizes the performance under the worst ω, we extend TD3 by formulating the objective as a maximin problem and introducing a simultaneous gradient ascent descent approach.

The main difficulty in the worst-case performance maximization is in the estimation of the worst-case performance. Because the objective is expected to be non-concave with respect to the uncertainty parameter due to deep actor-critic networks, solving such a problem is considered intractable in general [4]. To stabilize the worst-case performance estimation, we introduce various techniques: multiple uncertainty parameters, an uncertainty parameter refresh strategy, and an uncertainty parameter sampler.

Formulation   We can formulate our objective as the following tri-level optimization:

$$\max_{\theta \in \Theta} \min_{\eta \in \Omega} J(\theta, \eta; \phi^*) \quad \text{s.t.} \quad \phi^* \in \operatorname*{argmin}_{\phi \in \Phi} L(\phi; \theta) \ , \tag{3}$$

where J and L are defined below. Note that this tri-level optimization formulation is an extension of the bi-level optimization formulation of the actor-critic approach proposed in [26].

We introduce a probability density $\alpha : \Omega \to \mathbb{R}$, from which an ω to be used in the interaction during the training phase is drawn for each episode. The relationship between η and α is similar to that between θ and β: that is, η and θ are the parameters to be optimized while α and β are introduced for exploration. Let $\rho_\alpha^\beta(s) = \int_{\omega \in \Omega} \rho^\beta(s \mid \omega)\alpha(\omega)\mathrm{d}\omega$ and $\rho_\alpha^\beta(s,a,\omega) = \beta(a \mid s)\rho^\beta(s \mid \omega)\alpha(\omega)$ be the

---

[1]One might think that a simple way to mitigate this issue would be to early-stop the optimization for each step of RARL. However, the problem remains. The protagonist agent in RARL does not consider the uncertainty parameter in the critic. This leads to a non-stationary training environment for both protagonist and adversarial agents. As the learning in a non-stationary environment is generally difficult [11], RARL will be unstable. The instability of RARL has also been investigated in the linear-quadratic system settings [38].

stationary distribution of s and the joint stationary distribution of (s, a, ω), respectively, under α and β.

The critic loss function $L(\phi; \theta)$ is designed to simulate the Q-learning algorithm. Let T_{μ_θ} be the functional satisfying $T_{\mu_\theta}[Q](s, a, \omega) = r_\omega(s, a) + \gamma \int_{s' \in S} Q(s', \mu_\theta(s'), \omega) q_\omega(s' \mid s, a) \mathrm{d}s'$. Then, (1) states that Q^{μ_θ} is the solution to $Q = T_{\mu_\theta}[Q]$. Therefore, the critic is trained to minimize the difference between Q_ϕ and $T_{\mu_\theta}[Q_\phi]$. This is achieved by minimizing

$$L(\phi; \theta) := \int_{s \in S} \int_{a \in A} \int_{\omega \in \Omega} (T_{\mu_\theta}[Q_\phi](s, a, \omega) - Q_\phi(s, a, \omega))^2 \rho_\alpha^\beta(s, a, \omega) \mathrm{d}s \mathrm{d}a \mathrm{d}\omega \ . \tag{4}$$

The min-max objective function of the actor network

$$J(\theta, \eta; \phi) := \int_{s \in S} Q_\phi(s, \mu_\theta(s), \eta) \rho_\alpha^\beta(s) \mathrm{d}s \tag{5}$$

measures the performance of μ_θ under the uncertainty parameter $\eta \in \Omega$ approximated using the critic network Q_ϕ instead of the ground truth Q^{μ_θ}. Similar to the standard actor-critic approach, we expect Q_ϕ to approach Q^{μ_θ} as the critic loss is minimized. Therefore, we expect $J(\theta, \eta; \phi^*)$ approximates $\int_{s \in S} Q^{\mu_\theta}(s, \mu_\theta(s), \eta) \rho_\alpha^\beta(s) \mathrm{d}s$ once we obtain $\phi^* \approx \mathrm{argmin}_{\phi \in \Phi} L(\phi; \theta)$.

Note that, even if $Q_{\phi^*} = Q^{\mu_\theta}$, our objective function $J(\theta, \eta; \phi^*)$ differs from $J_\omega(\theta)$ with $\omega = \eta$ in (2), in that the stationary distribution $\rho^\beta(s \mid \omega)$ under fixed ω in J_ω is replaced with $\rho_\alpha^\beta(s)$ under $\omega \sim \alpha$. However, this change allows us to utilize the replay buffer, which stores the interaction history, to approximate the objective $J(\theta, \eta; \phi)$. If α is concentrated at η, $J(\theta, \eta; \phi^*)$ coincides with $J_{\omega=\eta}(\theta)$.

Algorithmic Framework The framework of M2TD3 is designed to solve the tri-level optimization (3). The overall framework of M2TD3 follows that of TD3. In each episode, an uncertainty parameter ω is sampled from α. The training agent interacts with the environment $\mathcal{M}_\omega$ using behavior policy β. At each time step t, the transition $(s_t, a_t, r_t, s_t', h_t, \omega)$ is stored in the replay buffer, denoted by B. The critic network Q_ϕ is trained at every time step to minimize (4), with a mini-batch being drawn uniformly randomly from B. The actor network μ_θ and the worst-case uncertainty parameter η are trained in every T_{freq} step to optimize (5). Note that a uniform random sample (s, a, ω) taken from B can be regarded as a sample from the stationary distribution $\rho_\alpha^\beta(s, a, \omega)$. Similarly, s taken from B is regarded as a sample from $\rho_\alpha^\beta(s)$. These facts allow approximation of the expectations in (4) and (5) using the Monte Carlo method with mini-batch samples uniformly randomly taken from B. The algorithm of M2TD3 is summarized in Algorithm 1 in Appendix A.

Critic Update The critic network update, that is, minimization of (4), is performed by implementing the TD error-based approach. The concept is as follows. Let $\{(s_i, a_i, r_i, s_i', \omega_i)\}_{i=1}^M \subset B$ be the mini-batch, and let θ_t and ϕ_t be the actor and critic parameters at time step t, respectively. For each tuple, $T_{\mu_\theta}[Q_\phi](s_i, a_i, \omega_i)$ is approximated by $y_i = r_i + \gamma \cdot Q_{\phi_t}(s_i', \mu_{\theta_t}(s_i'), \omega_i)$. Then, (4) is approximated by the mean square error, such that

$$\tilde{L}(\phi) = \frac{1}{M} \sum_{i=1}^M \| y_i - Q_\phi(s_i, a_i, \omega_i) \|^2 \ . \tag{6}$$

Then, the update follows $\phi_{t+1} = \phi_t - \lambda_\phi \nabla_\phi \tilde{L}(\phi_t)$.

We incorporate the techniques introduced in TD3 to stabilize the training: clipped double Q-learning, target policy smoothing regularization, and target networks. We additionally introduce the smoothing regularization for the uncertainty parameter so that the critic is smooth with respect to η. Algorithm 2 in Appendix A summarizes the critic update and the details of each technique available in [7].

Actor Update Updating of the actor as well as the uncertainty parameter, that is, maximin optimization of (5), is performed via simultaneous gradient ascent descent [24], summarized in Algorithm 3 in Appendix A. Let ϕ_t, θ_t and η_t be the critic, policy, and the uncertainty parameters, respectively, at time step t. Instead of the optimal ϕ^* in (3), we use ϕ_t as its estimate. With the mini-batch $\{s_i\}_{i=1}^M \subset B$, we approximate the max-min objective (5) as

$$\tilde{J}_t(\theta, \eta) = \frac{1}{M} \sum_{i=1}^M Q_{\phi_t}(s_i, \mu_\theta(s), \eta) \ . \tag{7}$$

220 Then, we update θ and η as $\theta_{t+1} = \theta_t + \lambda_\theta \nabla_\theta \tilde{J}_t(\theta_t, \eta_t)$ and $\eta_{t+1} = \eta_t - \lambda_\eta \nabla_\eta \tilde{J}_t(\theta_t, \eta_t)$, respectively.

221 For higher-stability performance, we introduce multiple uncertainty parameters. The motivation is
222 twofold. One is to deal with multiple local minima of $J_t(\theta, \eta; \phi^*)$ with respect to η. As the critic
223 network becomes generally non-convex, there may exist multiple local minima of $J_t(\theta, \eta; \phi^*)$ with
224 respect to η. Once η is stacked at a local minimum point, e.g., η^*, θ may be trained to be robust around
225 a neighborhood of η^* and to perform poorly outside that neighborhood. The other is to deal with the
226 situation that the maximin solution (θ^*, ϕ^*) of $J_t(\theta, \eta; \phi^*)$ is not a saddle point, which happens when
227 the objective is non-concave in η [13]. In such a situation, more than one η is necessary to approximate
228 the worst-case performance $\max_\eta J_t(\theta, \eta; \phi^*)$ around (θ^*, ϕ^*) and a standard simultaneous gradient
229 ascent descent method fails to converge. To relax this defect of simultaneous gradient ascent descent
230 methods, we maintain multiple candidates for the worst η, denoted by $\eta_1, \ldots, \eta_N$. Therefore,
231 replacing $\min_\eta J(\theta, \eta; \phi^*)$ with $\min_{k=1,\ldots,N} J(\theta, \eta_k; \phi^*)$ in (5) has no effect on the optimal θ;
232 however, this change does affect the training behavior. Our update follows the simultaneous gradient
233 ascent descent on $\min_{k=1,\ldots,N} J_t(\theta, \eta_k)$: $\theta \leftarrow \theta + \lambda_\theta \nabla_\theta (\min_{k=1,\ldots,N} J_t(\theta, \eta_k))$ and $\eta_k \leftarrow \eta_k - $
234 $\lambda_\eta \nabla_{\eta_k} (\min_{\ell=1,\ldots,N} J_t(\theta, \eta_\ell))$ for $k = 1, \ldots, N$. Hence, θ is updated against the worst η_k and only
235 the worst η_k is updated.

236 For multiple uncertainty parameters to be effective, they must be distant from each other. Moreover,
237 all are expected to be selected as the worst parameters with non-negligible frequencies. Otherwise,
238 the advantage of having multiple uncertainty parameters is lessened. From this perspective, we
239 introduce a refreshing strategy for uncertainty parameters. That is, we resample $\eta_k \sim \mathcal{U}(\Omega)$ if one
240 of the following scenarios is observed: there exists η_ℓ such that the distance $d_\eta(\eta_k, \eta_\ell) \leqslant d_{\text{thre}}$; the
241 frequency p_k of η_k being selected as the worst-case during the actor update is no greater than p_{thre}.

242 **Uncertainty Parameter Sampler**   The uncertainty parameter sampler α controls the exploration-
243 exploitation trade-off in the uncertainty parameter. On one hand, exploration in Ω is necessary to
244 train the critic network. If the critic network is not well trained over Ω, it is difficult to locate the
245 worst η correctly. On the other hand, for $J(\theta, \eta; \phi^*)$ in (5) to coincide with $J_\omega(\theta)$ for $\omega = \eta$ in (2),
246 we require α to be concentrated at η. Otherwise, the optimal θ for $J(\theta, \eta; \phi^*)$ may deviate from that
247 of $J_\omega(\theta)$. We design α as follows. For the first T_{rand} steps, we sample the uncertainty parameter ω
248 uniform-randomly on Ω, i.e., $\alpha = \mathcal{U}(\Omega)$. Then, we set $\alpha = \sum_{k=1}^N p_k \cdot \mathcal{N}(\eta_k, \Sigma_\omega)$, where Σ_ω is the
249 predefined covariance matrix. We decrease Σ_ω as the time step increases. The rational behind the
250 gradual decrease of Σ_ω is that the training of the critic network is still important after T_{rand} to make
251 the estimation of the worst-case uncertainty parameter accurate.

5   Experiments

253 In this study, we conducted experiments on the optimal control problem using MuJoCo environments.
254 Hence, we demonstrated the problems of existing methods and assessed the worst-case performance
255 and average performance of the policy trained by M2TD3 for different continuous control tasks.

256 **Baseline Methods**   We summarizes the baseline methods adapted to our experiment setting: namely,
257 DR, RARL, and M3DDPG.

258 DR: The objective of DR is to maximize the expected cumulative reward for the distribution
259 $\alpha = \mathcal{U}(\Omega)$ of ω. In each training episode, ω is drawn randomly from $\mathcal{U}(\Omega)$ and the agent neglects ω
260 when training and performing the standard DRL. For fair comparison, we implemented DR with TD3
261 as the baseline DRL method.

262 RARL: We adapted RARL to our scenario by setting $\mu_\eta : s \mapsto \eta$ to the antagonist policy. In this
263 scenario, RARL was regarded as optimizing (2) for the worst $\omega \in \Omega$; hence, the objective was the
264 same as that of M2TD3. Note that the main technical difference between M2TD3 and RARL is the
265 optimization strategy, as RARL alternately optimizes θ and ω optimizes (2) for the worst $\omega \in \Omega$
266 while fixing the other parameters. The original RARL is implemented with Trust Region Policy
267 Optimization (TRPO) [29], but for fair comparison, we implemented it with DDPG, denoted as
268 RARL (DDPG). The experimental results of RARL (TRPO), the original RARL, are provided in
269 Appendix E.

270 M3DDPG: By considering a two-agent scenario and $\mu_\eta : s \mapsto \eta$ as the opponent-agent's policy,
271 we adapted M3DDPG to our setting. Because of the difficulty in replacing DDPG with TD3 in the
272 M3DDPG framework, we used DDPG as the baseline DRL.

Table 3: Avg. $\pm$ std. error of worst-case performance $R_{\text{worst}}(\mu)$ over 10 trials for each approach

Environment	M2TD3	SoftM2TD3	M2-DDPG	M3DDPG	RARL (DDPG)	DR (TD3)
Ant 1 ($\times 10^3$)	3.84 ± 0.10	$\mathbf{4.08 \pm 0.15}$	1.28 ± 0.19	0.49 ± 0.12	-1.24 ± 0.10	3.51 ± 0.08
Ant 2 ($\times 10^3$)	$\mathbf{4.13 \pm 0.11}$	3.92 ± 0.14	0.95 ± 0.20	-0.25 ± 0.13	-1.77 ± 0.09	1.64 ± 0.13
Ant 3 ($\times 10^3$)	$\mathbf{0.10 \pm 0.10}$	0.07 ± 0.20	-1.13 ± 0.28	-1.38 ± 0.22	-2.38 ± 0.07	-0.32 ± 0.03
HalfCheetah 1 ($\times 10^3$)	3.14 ± 0.10	$\mathbf{3.24 \pm 0.08}$	2.24 ± 0.25	-0.13 ± 0.12	-0.55 ± 0.02	3.19 ± 0.08
HalfCheetah 2 ($\times 10^3$)	2.61 ± 0.16	$\mathbf{2.82 \pm 0.16}$	2.54 ± 0.23	-0.58 ± 0.06	-0.70 ± 0.05	2.12 ± 0.13
HalfCheetah 3 ($\times 10^3$)	0.93 ± 0.21	$\mathbf{1.53 \pm 0.23}$	1.20 ± 0.22	-0.66 ± 0.08	-0.81 ± 0.07	1.09 ± 0.06
Hopper 1 ($\times 10^2$)	$\mathbf{6.21 \pm 0.45}$	5.98 ± 0.23	5.38 ± 0.43	4.14 ± 0.60	3.32 ± 0.78	5.28 ± 2.55
Hopper 2 ($\times 10^2$)	5.33 ± 0.28	$\mathbf{5.79 \pm 0.29}$	4.30 ± 0.57	2.58 ± 0.29	3.34 ± 0.89	4.68 ± 0.15
Hopper 3 ($\times 10^2$)	$\mathbf{2.84 \pm 0.25}$	1.98 ± 0.22	2.25 ± 0.29	0.73 ± 0.11	1.64 ± 0.46	2.10 ± 0.35
HumanoidStandup 1 ($\times 10^4$)	9.33 ± 0.70	9.49 ± 0.81	8.09 ± 0.92	8.00 ± 0.78	5.29 ± 0.45	$\mathbf{9.68 \pm 0.60}$
HumanoidStandup 2 ($\times 10^4$)	6.50 ± 0.70	$\mathbf{7.94 \pm 0.90}$	6.24 ± 0.54	6.37 ± 0.72	5.78 ± 0.73	7.31 ± 0.78
HumanoidStandup 3 ($\times 10^4$)	$\mathbf{6.20 \pm 0.64}$	5.99 ± 0.37	5.96 ± 0.58	6.01 ± 0.38	5.54 ± 0.76	5.41 ± 0.34
InvertedPendulum 1 ($\times 10^2$)	$\mathbf{8.22 \pm 1.13}$	6.53 ± 1.36	6.49 ± 1.33	1.09 ± 0.71	1.53 ± 0.64	3.18 ± 1.10
InvertedPendulum 2 ($\times 10^2$)	$\mathbf{3.56 \pm 1.32}$	1.36 ± 0.30	1.10 ± 0.62	0.02 ± 0.00	0.02 ± 0.00	0.57 ± 0.02
Walker 1 ($\times 10^3$)	2.83 ± 0.39	$\mathbf{3.02 \pm 0.22}$	1.19 ± 0.17	0.89 ± 0.18	0.09 ± 0.02	2.19 ± 0.40
Walker 2 ($\times 10^3$)	$\mathbf{3.14 \pm 0.39}$	2.64 ± 0.43	0.85 ± 0.12	0.39 ± 0.11	0.06 ± 0.04	2.31 ± 0.50
Walker 3 ($\times 10^3$)	1.94 ± 0.40	$\mathbf{2.00 \pm 0.35}$	0.82 ± 0.13	0.28 ± 0.09	0.00 ± 0.02	1.32 ± 0.34
Small HalfCheetah 1 ($\times 10^3$)	5.27 ± 0.12	5.07 ± 0.14	4.51 ± 0.18	1.26 ± 0.38	-0.52 ± 0.02	$\mathbf{6.76 \pm 0.18}$
Small Hopper 1 ($\times 10^3$)	2.88 ± 0.32	2.23 ± 0.32	1.40 ± 0.19	1.39 ± 0.21	0.51 ± 0.12	$\mathbf{3.42 \pm 0.11}$

Additionally, we implemented our approach with DDPG instead of TD3, denoted by M2-DDPG, for comparison purpose. We also implemented a variant of M2TD3, denoted as SoftM2TD3, performing a "soft" worst-case optimization to achieve a better average performance while considering the worst-case performance. The detail of SoftM2TD3 is described in Appendix B.

Experiment Setting We constructed 19 tasks based on 6 MuJoCo environments and with 1-3 uncertainty parameters, as summarized in Table 6 in Appendix C. Here, Ω was defined as an interval, which mostly included the default ω values.

To assess the worst-case performance of the given policy μ under $\omega \in \Omega$, we evaluated the cumulative reward 30 times for each of uncertainty parameter value $\omega_1, \ldots, \omega_K \in \Omega$. Here, $R_k(\mu)$ was defined as cumulative reward on ω_k averaged over 30 trials. Then, $R_{\text{worst}}(\mu) = \min_{1 \leqslant k \leqslant K} R_k(\mu)$ was measured as an estimate of the worst-case performance of μ on Ω. We also report the average performance $R_{\text{average}}(\mu) = \frac{1}{K} \sum_{k=1}^{K} R_k(\mu)$. A total of K uncertainty parameters $\omega_1, \ldots, \omega_K$ for evaluation were drawn as follows: for 1D ω, we chose $K = 10$ equally spaced points on the 1D interval Ω; for 2D ω, we chose 10 equally spaced points in each dimension of Ω, thereby obtaining $K = 100$ points; and for 3D ω, we chose 10 equally spaced points in each dimension of Ω thereby obtaining $K = 1000$ points.

For each approach, we trained the policy ten times in each environment. The training time steps $T_{\max}$ were set to 2M, 4M, and 5M for the environments with 1D, 2D, and 3D uncertainty parameters, respectively. The finally obtained policies were evaluated for their worst-case performances. For further details of the experiment settings, please refer to Appendix C

Comparison to Baseline Methods Table 3 summarizes the worst-case performances of the policies trained by M2TD3, SoftM2TD3, M2-DDPG, M3DDPG, RARL, and DR.. See also Table 7 in Appendix D for the results of TD3 trained on the reference uncertainty parameters as baselines, and Figure 2 in Appendix F for the learning curves. In most cases, M2TD3 and SoftM2TD3 outperformed DR and RARL and M3DDPG. Figure 1 shows the cumulative rewards of the policies trained by the six approaches for each ω values on the Ant 1, InvertedPendulum 1, and Walker 1 environments. See also Figure 4 in Appendix G for other environments.

Comparison with DR: DR does not attempt to optimize worst-case performance. In fact, it showed lower worst-case performance than M2TD3 and SoftM2TD3 in many scenarios because the obtained policy performs poorly on some uncertainty parameters while it performs well on average. One such example situation is observed in the results of InvertedPendulum 1 shown in Figure 1, where the policy obtained by DR exhibited a high performance for a wide range of $\omega \in \Omega$ but performed poorly for small ω. M2TD3 outperformed DR as well as the other baselines on such environments. However, in some scenarios such as HumanoidStandup 1, Small HalfCheetah 1, and Small Hopper 1, DR achieved a better worst-case performance than M2TD3. This outcome may be because the optimization of

Figure 1: Cumulative rewards under trained policies for each uncertainty parameter $\omega \in \Omega$. The average (solid line) and standard error (band) for each $\omega \in \Omega$, as well as the worst average value (dashed line) are shown. Left: Ant 1, Middle: InvertedPendulum 1, Right: Walker 1.

Table 4: Avg. $\pm$ std. error of average performance $R_{\text{average}}(\mu)$ over 10 trials for each approach

Environment	M2TD3	SoftM2TD3	M2-DDPG	M3DDPG	RARL (DDPG)	DR (TD3)
Ant 1 ($\times 10^3$)	4.51 ± 0.08	4.78 ± 0.16	2.05 ± 0.21	0.84 ± 0.14	-0.82 ± 0.06	$\mathbf{5.25 \pm 0.10}$
Ant 2 ($\times 10^3$)	5.44 ± 0.05	5.56 ± 0.01	3.03 ± 0.19	1.86 ± 0.38	-1.00 ± 0.06	$\mathbf{6.32 \pm 0.09}$
Ant 3 ($\times 10^3$)	2.66 ± 0.22	2.98 ± 0.23	0.30 ± 0.46	-0.33 ± 0.22	-1.31 ± 0.09	$\mathbf{3.62 \pm 0.11}$
HalfCheetah 1 ($\times 10^3$)	3.89 ± 0.06	4.00 ± 0.05	3.50 ± 0.12	1.01 ± 0.26	-0.46 ± 0.02	$\mathbf{5.93 \pm 0.18}$
HalfCheetah 2 ($\times 10^3$)	4.35 ± 0.05	4.52 ± 0.07	3.91 ± 0.08	0.77 ± 0.12	-0.08 ± 0.05	$\mathbf{5.79 \pm 0.15}$
HalfCheetah 3 ($\times 10^3$)	3.79 ± 0.09	4.02 ± 0.04	3.39 ± 0.21	0.58 ± 0.18	-0.21 ± 0.10	$\mathbf{5.54 \pm 0.16}$
Hopper 1 ($\times 10^3$)	$\mathbf{2.68 \pm 0.11}$	2.67 ± 0.18	1.79 ± 0.22	1.12 ± 0.21	0.38 ± 0.08	2.57 ± 0.15
Hopper 2 ($\times 10^3$)	$\mathbf{2.51 \pm 0.07}$	2.26 ± 0.12	1.49 ± 0.15	1.15 ± 0.11	0.66 ± 0.13	1.89 ± 0.08
Hopper 3 ($\times 10^3$)	0.85 ± 0.07	0.79 ± 0.04	0.87 ± 0.08	0.49 ± 0.11	0.47 ± 0.08	$\mathbf{1.50 \pm 0.07}$
HumanoidStandup 1 ($\times 10^5$)	1.08 ± 0.04	1.03 ± 0.07	1.05 ± 0.06	0.99 ± 0.06	0.77 ± 0.06	$\mathbf{1.12 \pm 0.05}$
HumanoidStandup 2 ($\times 10^5$)	0.97 ± 0.04	$\mathbf{1.07 \pm 0.05}$	0.93 ± 0.04	0.92 ± 0.04	0.85 ± 0.08	1.06 ± 0.04
HumanoidStandup 3 ($\times 10^5$)	$\mathbf{1.09 \pm 0.06}$	1.04 ± 0.03	0.98 ± 0.06	1.01 ± 0.04	0.87 ± 0.07	1.04 ± 0.07
InvertedPendulum 1 ($\times 10^2$)	$\mathbf{9.66 \pm 0.25}$	9.17 ± 0.54	8.79 ± 0.87	4.51 ± 0.12	4.21 ± 0.81	9.32 ± 0.11
InvertedPendulum 2 ($\times 10^2$)	6.13 ± 1.42	6.26 ± 0.95	8.27 ± 0.70	1.76 ± 0.51	3.07 ± 0.66	$\mathbf{9.18 \pm 0.07}$
Walker 1 ($\times 10^3$)	$\mathbf{3.70 \pm 0.31}$	3.51 ± 0.16	2.03 ± 0.26	1.55 ± 0.25	0.15 ± 0.03	3.59 ± 0.26
Walker 2 ($\times 10^3$)	$\mathbf{4.72 \pm 0.12}$	4.37 ± 0.32	2.39 ± 0.20	1.63 ± 0.22	0.26 ± 0.05	4.54 ± 0.31
Walker 3 ($\times 10^3$)	4.27 ± 0.21	4.21 ± 0.30	2.48 ± 0.24	1.65 ± 0.15	0.21 ± 0.07	$\mathbf{4.48 \pm 0.16}$
Small HalfCheetah 1 ($\times 10^3$)	6.00 ± 0.15	6.04 ± 0.13	5.71 ± 0.07	3.38 ± 0.34	-0.42 ± 0.01	$\mathbf{8.11 \pm 0.17}$
Small Hopper 1 ($\times 10^3$)	2.96 ± 0.31	2.44 ± 0.31	1.57 ± 0.21	1.53 ± 0.21	0.56 ± 0.13	$\mathbf{3.44 \pm 0.10}$

worst-case function values is generally more unstable than optimization of the expected function values.

Comparison with RARL: M2-DDPG outperformed RARL in most environments, with this performance difference originating from the different optimization strategies. As noted above, the optimization strategy employed in RARL often fails to converge. As we see in Figure 1, RARL failed to optimize the policy not only in the worst-case also on average in Ant 1 environment and Walker 1 environment. In the InvertedPendulum 1 environment, RARL could train the policy for some uncertainty parameter, but not for the worst-case uncertainty parameter.

Comparison with M3DDPG: In many cases, M2-DDPG outperformed M3DDPG. As discussed above, M3DDPG considers a stronger adversary than necessary (the worst ω for each time step). Therefore, the resulting policy was too conservative for this experiment and exhibited lower performance.

Average Performance Although our objective is maximizing the worst-case performance, the average performance is also important in practice. Table 4 compares the average performance of the six approaches. Generally, DR achieved the highest average performance as expected. However, interestingly, M2TD3 and SoftM2TD3 achieved competitive average performances to DR on several environments such as Hopper 1, 2, and Walker 1, 2. Moreover, comparison between Table 3 and Table 4 show that a few times higher average performance than worst-case performance on several environments such as Ant 3 and Hopper 1–3.

Table 5: Avg. $\pm$ std. error of worst-case performance $R_{\text{worst}}(\mu)$ and average performance $R_{\text{average}}(\mu)$ on InvertedPendulum 1 obtained by M2TD3 variants over 10 trials

Environment	N=5	N=1	N=10	w/o DRS	w/o PRS
worst-case ($\times 10^2$)	8.22 ± 1.13	5.77 ± 1.29	9.07 ± 0.89	9.07 ± 0.88	5.41 ± 1.45
average ($\times 10^2$)	9.66 ± 0.25	8.10 ± 0.90	9.89 ± 0.11	9.08 ± 0.88	6.90 ± 1.25

Ablation Study Ablation studies were conducted on InvertedPendulum 1 with the pole mass as the uncertainty parameters. M2TD3 with $N = 5$ was taken as the baseline. We tested several variants: with different multiple uncertainty parameters ($N = 1$ and 10), without distance-based refreshing strategy (w/o DRS) and without probability-based refreshing strategy (w/o PRS). Table 5 shows the results. Clearly, the inclusion of multiple uncertainty parameters as well as the probability-based refresh strategy contributed significantly to the worst-case performance and average performance, implying that both techniques contribute to better estimate the worst uncertainty parameter. Though DRS had little impact on the performance, one can implement prior knowledge in DRS by defining the distance and the threshold in the uncertainty parameter task-dependently, which we did not here.

Small Uncertainty Set (Limitation of M2TD3) Small HalfCheetah 1 and Small Hopper 1 were designed to have smaller uncertainty parameter set than HalfCheetah 1 and Hopper 1, and to reveal the effect of the size of the uncertainty parameter interval. As expected, a smaller uncertainty parameter set resulted in higher worst-case (Table 3) and average (Table 4) performances, for all approaches. Because M2TD3 performs the worst-case optimization, it is expected to show better worst-case performance than DR independently of the size of the uncertainty parameter set. However, on these environments, DR showed better worst-case performance than M2TD3, while M2TD3 achieved competitive or superior worst-case performance to DR on HalfCheetah 1 and Hopper 1. This may be because the max-min optimization performed by M2TD3 resulted in sub-optimal policies. When the uncertainty parameter set is small and the performance do not change significantly over the uncertainty parameter set, maximizing the average performance is likely to lead to a high worst-case performance. The sub-optimal results obtained by M2TD3 is then dominated by the results obtained by DR. Therefore, there is room for improvement in the maximin optimization in M2TD3.

6   Conclusion

In this study, we targeted the policy optimization aimed at maximizing the worst-case performance in a predefined uncertainty set. The list of the contributions are as follows. (i) We formulated the off-policy deterministic actor-critic approach to the worst-case performance maximization as a tri-level optimization problem (3). (ii) We developed the worst-case performance of M2TD3. The key concepts were incorporation of the uncertainty parameter into the critic network and use of the simultaneous gradient ascent descent method. Different technical components were introduced to stabilize the training. (iii) We evaluated the worst-case performance of M2TD3 on 19 MuJoCo environments through comparison with three baseline methods. Ablation studies revealed the usefulness of each component of M2TD3.

Finally, we remark on the limitations of this study and possible future works. First, our experiments were conducted in environments with uncertainty parameter having up to three dimensions. However, in a scenario where many of the coefficients of a kinetic model of a learning agent must be estimated through regression, all estimated coefficients are uncertain. In such a scenario, the dimensions can easily exceed three. Second, although our experiment setting conforms to that of [27] (i.e., the model misspecification is expressed by an external force given by the policy of an adversarial agent), we did not evaluate our proposed method for such a scenario. Both above cases have important applications. However, one limitation of both cases is that evaluation of the worst-case performance is very difficult because of the high dimensionality of the uncertainty-parameter. Indeed, the worst-case performance for ω is not reported in [27]. In future work, we will evaluate our proposed method for these two scenarios and develop tasks and tools for easy evaluation of the corresponding worst-case performance.

References

[1] Abbas Abdolmaleki, Jost Tobias Springenberg, Yuval Tassa, Rémi Munos, Nicolas Heess, and Martin A. Riedmiller. Maximum a posteriori policy optimisation. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[2] Anurag Ajay, Jiajun Wu, Nima Fazeli, Maria Bauzá, Leslie Pack Kaelbling, Joshua B. Tenenbaum, and Alberto Rodriguez. Augmenting physical simulators with stochastic neural networks: Case study of planar pushing and bouncing. In *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2018, Madrid, Spain, October 1-5, 2018*, pages 3066–3073. IEEE, 2018.

[3] Erwin Coumans et al. Bullet physics library. *Open source: bulletphysics. org*, 15(49):5, 2013.

[4] Constantinos Daskalakis, Stratis Skoulakis, and Manolis Zampetakis. The complexity of constrained min-max optimization. In Samir Khuller and Virginia Vassilevska Williams, editors, *STOC '21: 53rd Annual ACM SIGACT Symposium on Theory of Computing, Virtual Event, Italy, June 21-25, 2021*, pages 1466–1478. ACM, 2021.

[5] Michael Dennis, Natasha Jaques, Eugene Vinitsky, Alexandre M. Bayen, Stuart Russell, Andrew Critch, and Sergey Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

[6] Omar Darwiche Domingues, Pierre Ménard, Emilie Kaufmann, and Michal Valko. Episodic reinforcement learning in finite mdps: Minimax lower bounds revisited. In Vitaly Feldman, Katrina Ligett, and Sivan Sabato, editors, *Algorithmic Learning Theory, 16-19 March 2021, Virtual Conference, Worldwide*, volume 132 of *Proceedings of Machine Learning Research*, pages 578–598. PMLR, 2021.

[7] Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1582–1591. PMLR, 2018.

[8] Florian Golemo, Adrien Ali Taïga, Aaron C. Courville, and Pierre-Yves Oudeyer. Sim-to-real transfer with neural-augmented robot simulation. In *2nd Annual Conference on Robot Learning, CoRL 2018, Zürich, Switzerland, 29-31 October 2018, Proceedings*, volume 87 of *Proceedings of Machine Learning Research*, pages 817–828. PMLR, 2018.

[9] Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In Zoubin Ghahramani, Max Welling, Corinna Cortes, Neil D. Lawrence, and Kilian Q. Weinberger, editors, *Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada*, pages 2672–2680, 2014.

[10] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1856–1865. PMLR, 2018.

[11] Shariq Iqbal and Fei Sha. Actor-attention-critic for multi-agent reinforcement learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 2961–2970. PMLR, 2019.

[12] Garud N. Iyengar. Robust dynamic programming. *Math. Oper. Res.*, 30(2):257–280, 2005.

[13] Chi Jin, Praneeth Netrapalli, and Michael I. Jordan. What is local optimality in nonconvex-nonconcave minimax optimization? In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 4880–4889. PMLR, 2020.

[14] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

[15] Shihui Li, Yi Wu, Xinyue Cui, Honghua Dong, Fei Fang, and Stuart J. Russell. Robust multi-agent reinforcement learning via minimax deep deterministic policy gradient. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pages 4213–4220. AAAI Press, 2019.

[16] Tengyuan Liang and James Stokes. Interaction matters: A note on non-asymptotic local convergence of generative adversarial networks. In Kamalika Chaudhuri and Masashi Sugiyama, editors, *The 22nd International Conference on Artificial Intelligence and Statistics, AISTATS 2019, 16-18 April 2019, Naha, Okinawa, Japan*, volume 89 of *Proceedings of Machine Learning Research*, pages 907–915. PMLR, 2019.

[17] Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In Yoshua Bengio and Yann LeCun, editors, *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016.

[18] Zichuan Lin, Garrett Thomas, Guangwen Yang, and Tengyu Ma. Model-based adversarial meta-reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

[19] Daniel J. Mankowitz, Nir Levine, Rae Jeong, Abbas Abdolmaleki, Jost Tobias Springenberg, Yuanyuan Shi, Jackie Kay, Todd Hester, Timothy A. Mann, and Martin A. Riedmiller. Robust reinforcement learning for continuous control with model misspecification. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[20] Daniel J. Mankowitz, Timothy A. Mann, Pierre-Luc Bacon, Doina Precup, and Shie Mannor. Learning robust options. In Sheila A. McIlraith and Kilian Q. Weinberger, editors, *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pages 6409–6416. AAAI Press, 2018.

[21] Bhairav Mehta, Manfred Diaz, Florian Golemo, Christopher J. Pal, and Liam Paull. Active domain randomization. In Leslie Pack Kaelbling, Danica Kragic, and Komei Sugiura, editors, *3rd Annual Conference on Robot Learning, CoRL 2019, Osaka, Japan, October 30 - November 1, 2019, Proceedings*, volume 100 of *Proceedings of Machine Learning Research*, pages 1162–1176. PMLR, 2019.

[22] Lars M. Mescheder, Sebastian Nowozin, and Andreas Geiger. The numerics of gans. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 1825–1835, 2017.

[23] Jun Morimoto and Kenji Doya. Robust reinforcement learning. *Neural Comput.*, 17(2):335–359, 2005.

[24] Vaishnavh Nagarajan and J. Zico Kolter. Gradient descent GAN optimization is locally stable. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 5585–5595, 2017.

[25] Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pages 1–8. IEEE, 2018.

[26] David Pfau and Oriol Vinyals. Connecting generative adversarial networks and actor-critic methods. *CoRR*, abs/1610.01945, 2016.

[27] Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 2817–2826. PMLR, 2017.

[28] Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. Epopt: Learning robust neural network policies using model ensembles. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

[29] John Schulman, Sergey Levine, Pieter Abbeel, Michael I. Jordan, and Philipp Moritz. Trust region policy optimization. In Francis R. Bach and David M. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pages 1889–1897. JMLR.org, 2015.

[30] Russell Smith. Open dynamics engine, 2008. http://www.ode.org/.

[31] Richard S. Sutton, Doina Precup, and Satinder P. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artif. Intell.*, 112(1-2):181–211, 1999.

[32] Matthew E. Taylor and Peter Stone. Transfer learning for reinforcement learning domains: A survey. *J. Mach. Learn. Res.*, 10:1633–1685, 2009.

[33] Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2017, Vancouver, BC, Canada, September 24-28, 2017*, pages 23–30. IEEE, 2017.

[34] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2012, Vilamoura, Algarve, Portugal, October 7-12, 2012*, pages 5026–5033. IEEE, 2012.

[35] Wenhao Yu, C. Karen Liu, and Greg Turk. Policy transfer with strategy optimization. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

[36] Wenhao Yu, C. Karen Liu, and Greg Turk. Policy transfer with strategy optimization. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

[37] Wenhao Yu, Jie Tan, C. Karen Liu, and Greg Turk. Preparing for the unknown: Learning a universal policy with online system identification. In Nancy M. Amato, Siddhartha S. Srinivasa, Nora Ayanian, and Scott Kuindersma, editors, *Robotics: Science and Systems XIII, Massachusetts Institute of Technology, Cambridge, Massachusetts, USA, July 12-16, 2017*, 2017.

[38] Kaiqing Zhang, Bin Hu, and Tamer Basar. On the stability and convergence of robust adversarial reinforcement learning: A case study on linear quadratic systems. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.