Learning Sparse Representations of Preferences within Choquet Expected Utility Theory

Abstract

This paper deals with preference elicitation within Choquet Expected Utility (CEU) theory for decision making under uncertainty. We consider the Savage's framework with a finite set of states and assume that preferences of the Decision Maker over acts are observable. The CEU model involves two parameters that must be tuned to the value system of the decision maker: a set function (capacity) modeling weights attached to events, of size exponential in the number of states, and a utility function defined on the space of outcomes. Our aim is to learn a sparse representation of the CEU model from preference data. We propose and test a preference learning approach based on a spline representation of utilities and the sparse learning of capacities to obtain CEU models achieving a good tradeoff between the aim of sparsity and the expressivity required by preference data.

1 INTRODUCTION

Decision theory has developed an entire stream of theoretical works on the axiomatic foundations of preference models either for descriptive, normative or prescriptive purposes [von Neumann and Morgenstern, 1947, Savage, 1954, Fishburn, 1970, Gilboa, 2008, Quiggin, 2012, Wakker, 2013]. The mathematical models used to describe preferences include parameters that can be fitted to the value system of the decision maker (DM). The role of these preference parameters is well understood and the decision behavior of an individual can be interpreted by observing the values of these parameters. For example, in the expected utility theory, risk aversion is equivalent to the concavity of the utility function and the level of risk-aversion of an individual can be measured from the curvature and the slope of his/her utility function [Arrow, 1971, Pratt, 1978].

In the framework of decision under uncertainty (i.e., no probability of the events needs to be given) and risk (i.e., probabilities of the events are known) various models have been proposed, involving an increasing number of preferential parameters to cover an ever larger class of decision behaviors. For example, Tversky and Kahneman [1979] have observed a frequent violation of the *sure thing principle* of Savage [1954] in their experiments on preferences. Such violations preclude any representation of the observed preferences by the Expected Utility model (EU). Then, rank-dependent models have been introduced relying on a weakened version of the sure thing principle. Among them, the Choquet Expected Utility (CEU) model [Schmeidler, 1989] has received much attention due to its high descriptive possibilities and the fact that it boils down to well known simpler models for some well identified subclasses of capacities or utilities. Among them let us mention the rank-dependent utility (RDU) [Quiggin, 2012], the Yaari's model [Yaari, 1987] and the expected utility [Savage, 1954].

CEU can easily explain standard preference inversions as those observed in Allais' paradox (in the context of risk) and in Ellsberg paradox (in the context of uncertainty) [Ellsberg, 1961, Wakker, 2001]. However, the CEU model requires the definition of a non-necessarily additive set function (named capacity) that assigns a weight to every event that may occur in the problem, in addition to the utility function. In a problem where uncertainty is represented by a finite set of n states of nature, the set of events under consideration is the set of all subsets of S. Hence the definition of the capacity and therefore of CEU requires the determination, in the general case, of 2^n coefficients, in addition to those that are necessary for the definition of the utility function.

The growing number of preference parameters, justified by descriptive objectives, comes at a cost: sophisticated decision models are harder to learn and need larger bases of preference data to be able to make reliable predictions on new data. Since preference data are usually not very numerous in practical applications and may be costly to obtain (preference queries must be asked to the DM or

Submitted to the 38th Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only**.

derived from a history of previous decisions) there is a need of flexible approaches allowing to adapt the number of preference parameters used in the model to the expressivity required by preference data. This question is of particular relevance for CEU due to its expressivity but also to its lack of compactness in the general case. For this reason, we study in this paper the potential of sparse learning to determine compact instances of CEU from small preference databases.

One possible source of difficulties here is the interplay of utilities and capacities in the computation of CEU values, making the learning of these two types of parameters interdependent. Another difficulty comes from the fact that utilities and capacities are not directly observable and must be derived from preference statements over pairs of alternatives. Taking these specificities into account, we propose a learning approach that proceeds in two steps: using preference questions specially designed for utility elicitation we learn a spline representation of the utility function and then derive a sparse representation of the capacity from further preference examples.

The paper is organized as follows: Section 2 introduces the CEU model and some basic concepts and properties related to Choquet integrals. In Section 3 we review some works on learning decision models based on Choquet integrals and introduce the premises of a two-phase approach to learn utilities and then capacities from preference data. Then the learning of the utility function is presented in Section 4 and the learning of the capacity in Section 5. In the two latter sections we present numerical tests to show the effectiveness of the proposed approach.

2 BACKGROUND ON CEU

We adopt the standard setting of Savage [1954] for decision making under uncertainty. We have to compare acts the outcomes of which depend on the (unknown) state of nature. Here we consider a finite set of states $S = \{1, \ldots, n\}$ that is supposed to include all relevant possible futures.

The acts to be compared are seen as functions defined from S to the outcome space X. For simplicity we assume here that outcomes are payoffs and that X is the real line. Any possible act x is characterized by an outcome vector $(x_1, \ldots, x_n)$ where x_i is the outcome of x in state i, for $i = 1, \ldots, n$. We will denote $\mathcal{X} = X \times \ldots \times X$ the homogeneous cartesian product containing all possible acts given S and X. Within $\mathcal{X}$ we distinguish constant acts denoted $\bar{x} = (x, \ldots, x)$ for any $x \in X$ (their outcome does not depend on the state of nature). We also define a mixture of acts as follows: for any $A \subset S$ and for any two acts $x, y \in \mathcal{X}$, let xAy denote the act of $\mathcal{X}$ defined by:

$$(xAy)_i = \begin{cases} x_i & \text{if } i \in A \\ y_i & \text{otherwise} \end{cases} \quad i = 1, \ldots, n.$$

In this setting, any subset $A \subseteq S$ must be interpreted as an event. For instance, if $S = \{1, 2, 3\}$ the set $A = \{1, 3\}$ represents the event "$s = 1$ or $s = 3$" where s is the actual state of nature. Hence xAy represents an act whose outcome is x if event A occurs and y otherwise. A binary act is any mixture of constant acts of type $\bar{x}A\bar{y}$, $x, y \in X$. It represents an act whose consequence is x if A occurs and y otherwise. Such mixtures of constant acts will be useful to design informative preference queries in the elicitation of utilities as we will see later in the paper.

Now, we introduce the Choquet Expected Utility model in the context of Savage. It is defined from two parameters: a utility function u modeling the sensitivity of the DM with respect to outcomes and the capacity v which is a set function defined on 2^S, monotonic w.r.t to set inclusion (i.e., $v(A) \leq v(B)$ whenever $A \subseteq B \subseteq S$) and normalized (i.e., $v(\emptyset) = 0$ and $v(S) = 1$) modeling the sensitivity of the decision maker to uncertainty (its chance attitude, see Wakker [2001]). Given these two parameters u and v, the CEU model assigns to every act x an overall value $f_v^u(x)$ defined as the discrete Choquet integral of the utility of the outcome vector which reads as follows:

$$
\begin{aligned}
f_v^u(x) &= \sum_{i=1}^n \left[v(X_{(i)}) - v(X_{(i+1)}) \right] u(x_{(i)}) \quad (1) \\
&= \sum_{i=1}^n \left[u(x_{(i)}) - u(x_{(i-1)}) \right] v(X_{(i)}) \quad (2)
\end{aligned}
$$

where $(.)$ is any permutation of S such that $x_{(1)} \leq \ldots \leq x_{(n)}$, and $X_{(i)} = \{(i), \ldots, (n)\}$ is the event "the outcome of x is greater or equal to $x_{(i)}$" for $i = 1, \ldots, n$. Furthermore we assume that $x_{(0)} = 0$ and $X_{(n+1)} = \emptyset$. For example, if $S = \{1, 2, 3\}$ then $f_v^u(100, 10, 60) = u(10)v(\{1, 2, 3\}) + [u(60) - u(10)]v(\{1, 3\}) + [u(100) - u(60)]v(\{1\})$.

CEU theory provides an axiomatic framework under which the DM's preferences $\succsim$ over acts are represented by f [Schmeidler, 1989, Gilboa, 2008]. Formally we have: $x \succsim y$ iff $f_v^u(x) \geq f_v^u(y)$. Let us briefly recall some key properties that illustrate the role of the capacity in the model:

- the monotonicity of v is required to make sure that $f_v^u(x) \geq f_v^u(y)$ when $x_i \geq y_i$ for all $i \in S$.

- CEU boils down to Savage's expected utility when v is additive (i.e., $v(A \cup B) + v(A \cap B) = v(A) + v(B)$ for all $A, B \subseteq S$).

- the preference induced by f satisfies *uncertainty aversion* if and only if u is concave and v supermodular (i.e., $v(A \cup B) + v(A \cap B) \geq v(A) + v(B)$ for all $A, B \in S$) [Chateauneuf and Tallon, 2002]. Uncertainty aversion (a.k.a convexity of preferences) reads as follows: if the DM is indifferent between x and y (denoted $x \sim y$) then $\alpha x + (1 - \alpha)y$ will be preferred to x (and also to y by symmetry) for any $\alpha \in [0, 1]$. The convex mixture of x and y reduces the uncertainty of outcomes w.r.t x and y and makes the DM better off.

- *CEU* boils down to the rank-dependent utility for decision making under risk whenever $v(A) = w(p(A))$ where p is the probability measure on events and w is a monotonic weighting function such that $w(0) = 0$ and $w(1) = 1$ [Quiggin, 2012]. If in addition u is linear then CEU boils down to Yaari's model [Yaari, 1987].

Another useful formulation of the CEU model relies on the Möbius inverse of the capacity. The Möbius inverse of v is another set function m defined on S by: $m(A) = \sum_{B \subseteq A} (-1)^{|A \setminus B|} v(B)$ for all $A \subseteq S$. The coefficients $m(A)$ are called Möbius masses, they completely characterize v. We indeed have $v(A) = \sum_{B \subseteq A} m(B)$. The values of m can be positive or negative but add up to 1 since $\sum_{B \subseteq S} m(B) = v(S) = 1$. When v is additive the only non-null Möbius masses are those of singletons.

Interestingly enough, the CEU model can be directly expressed from the Möbius inverse by:

$$f_v^u(x) = \sum_{B \subseteq S} m(B) \min_{i \in B} \{u(x_i)\} \qquad (3)$$

This formulation shows that $f_v^u(x)$ might admit a compact representation whenever the Möbius inverse is sparse. A frequent option used to handle capacities with a sparse representation is to require that Möbius masses vanish for all subsets of states larger that a given k smaller than n. In this case, the resulting capacity is said to be k-additive [Grabisch, 1997] and admits a more compact representation than in the general case. For instance, when the capacity is 1-additive then all Möbius masses are null except for singletons where they are positive due to monotonicity. However, in this case, Equation 3 shows that f boils down to an expected utility with a significant loss of expressivity.

A more interesting tradeoff could be obtained with k-additivity for some small value of k larger than 1 but it seems difficult to select a suitable value of k without looking at preference data. Moreover it may happen that very sparse but still n-additive capacities perfectly match preference data. For example, this is the case when the DM is very pessimistic and behaves according to the maximin criterion. In this case $f_v^u(x) = \min\{u(x_i), i \in B\}$ which is an instance of CEU obtained from Equation 3 with $m(B) = 0$ for all $B \subset S$ and $m(S) = 1$. This shows that preferences induced by the maximin criterion could not be properly described by a k-additive capacity with $k < n$ despite the existence of a very sparse representation of f in terms of Möbius inverse. This calls for a more efficient approach to derive sparse representations of CEU from preference data. This is precisely the subject of the next sections.

In order to illustrate both the descriptive potential of CEU and its ability to admit a sparse representation in terms of Möbius inverse we now consider a standard urn example due to Ellsberg [1961].

Example 1. *An urn contains 90 balls including 30 red, and 60 blue or yellow balls in unknown proportion. We consider four bets, on the one hand x (resp. y) yielding 100 if the drawn ball is red (resp. blue), and on the other hand z (resp. w) yielding 100 if the drawn ball is not blue (resp. not red). Here $S = \{R, B, Y\}$ for red, blue, yellow, and the acts under consideration are $x = (100, 0, 0)$, $y = (0, 100, 0)$, $z = (100, 0, 100)$ and $w = (0, 100, 100)$. Note that the pair (x, y) compares similarly to the pair (z, w) except that the common outcome attached to yellow balls moves from 0 to 100. Despite this similarity, most of people prefer x to y but w to z. This is not representable by the Expected Utility model due to a violation of the sure thing principle.*

However, these preferences can be represented by CEU. Let us assume that $u(0) = 0$ and $u(100) = 1$ and $v(\{R\}) = 1/3, v(\{B\}) = v(\{Y\}) = 0, v(\{R, B\}) = v(\{R, Y\}) = 1/3, v(\{B, Y\}) = 2/3$ and $v(\{R, B, Y\}) = 1$. Note that for all events, v yields the lower possible probability of the event according to our knowledge of the urn content. We have $f_v^u(x) = 0v(\{R, B, Y\}) + (1 - 0)v(\{R\}) = 1/3$. Similarly we obtain $f_v^u(Y) = 0$, $f_v^u(z) = 1/3$ and $f_v^u(w) = 2/3$. Hence, $f_v^u(x) > f_v^u(y)$ and $f_v^u(w) > f_v^u(z)$ which is consistent with the observed preferences. Moreover, the Möbius inverse of v is everywhere 0 except that $m(\{R\}) = 1/3$ and $m(\{B, Y\}) = 2/3$. Hence we get a sparse representation of f that fits the observed preferences: $f_v^u(x_1, x_2, x_3) = u(x_1)/3 + 2\min\{u(x_2), u(x_3)\}/3$.

We end the section by mentioning a third representation of the capacity based on interaction indices, $I(A)$ for all $A \subseteq S$ [Grabisch, 1997] that will be discussed later in the paper. When A is a singleton $\{k\}$, the interaction index $I(\{k\})$ is nothing else but the so-called Shapley value measuring the average marginal increment $v((B \cup \{k\}) - v(B))$ for any event $B \subseteq A$ that does not contains k. The notion of Shapley interaction index extends to any subset A of S. Interaction indices can be uniquely defined from v or m indifferently. Conversely v and m can be obtained from I. For more details see Grabisch [1997]. In the case of Example 1, the interaction indices are given by $I(\emptyset) = 7/18$, $I(\{1\}) = I(\{2\}) = I(\{3\}) = 1/3, I(\{2.3\}) = 2/3$, the other coefficents being null.

3 LEARNING THE CEU MODEL

3.1 RELATED WORK

Fitting the parameters of a decision models based on a Choquet integral to observed preferences is a question present both in the literature on decision theory (preference elicitation) and in the literature on machine learning (preference learning). In the context of decision making under risk, some elicitation protocols proposing a series of preference queries involving pairs of lotteries have been proposed to construct methodically a set of points on the utility curve and then on the probability weighting function defining the capacity in

the RDU model and in cumulative prospect theory (CPT) [Wakker and Deneffe, 1996, Abdellaoui, 2000].

Another stream of work developed in the literature on multicriteria decision aid concerns the use of non-linear regression for the identification of the capacity from overall evaluations prescribed by the DM, and the use of ordinal regression method from preference examples, assuming the utilities are known Grabisch et al. [2008], Grabisch and Labreuche [2010]. The prior construction of utility in this setting is often based on direct queries on difference of attractiveness between attribute values, see e.g., the Macbeth method [Bana e Costa and Vansnick, 1997].

Another approach developed in AI consists in progressively reducing the uncertainty about the preference parameters. A first set of methods proceeds by successive reductions of the parameter space using preference queries adaptively selected for their information value (e.g., using the minimax regret criterion). This incremental approach was used for the identification of utilities in [Wang and Boutilier, 2003], for the identification of the probability weighting function [Hines and Larson, 2010, Perny et al., 2016], and for the identification of Choquet capacities in [Benabbou et al., 2017]. A second set of methods proposes another adaptive elicitation procedure based on a Bayesian approach used to iteratively revise a probability density on the parameter space, see e.g. [Chajewska et al., 2000] for utility elicitation and [Bourdache et al., 2019] for the capacity elicitation.

None of the above mentioned contributions addresses the question of learning sparse representations of the capacity; however, some of them assume that capacities are k-additives for a prior reduction of model complexity.

The Choquet integral is also used in machine learning to replace the linear function of variables, which is commonly used in standard regression methods [Gagolewski et al., 2019, Beliakov and Wu, 2020, Beliakov and Divakov, 2020]. For example, logistic regression was extended to Choquistic regression [Tehrani and Hülermeier, 2013, Tehrani et al., 2012a, 2011]. It is also used for learning to rank with the Choquet integral [Tehrani et al., 2012b] where the data are provided with the labels which are preference degrees from an ordered categorical scale. The Choquet integral was also introduced as a kernel method [Tehrani, 2021].

In the machine learning community, statistical regularization is used to find a tradeoff between the model's generalizing performance and the model's complexity [Tibshirani, 1996, Hastie et al., 2015]. In particular, the Lasso method introduces the L_1 penalty to the objective function to obtain a sparse solution in a high dimensional setting with small number of observations. It can be used to obtain compact representations of capacities that include, in the general case, $2^n - 2$ free parameters. Several attempts have been made to reduce the complexity of the non-additive integrals via the L_1 penalty term. For example, the sparsity inducing

penalty was applied to the capacity [Anderson et al., 2014, Adeyeba et al., 2015]; the penalised sum of squared errors with Gini-Simpson index regularisation and the L_0 norm on the Shapley values were considered in [Pinar et al., 2017]. The L_1 penalty was also applied to capacities represented by interaction indices in [de Oliveira et al., 2022].

The specificity of our approach is to learn from pairwise comparisons both a smooth utility function and a sparse Möbius representation of the capacity with no prior reduction of the class of admissible capacities, in the framework of decision making under uncertainty and CEU theory.

3.2 APPROXIMATING PREFERENCES WITH CEU

As usual in Decision Theory, utilities and any other parameters of the decision model are not assumed to be directly observable. The decision maker may have no idea of the model under consideration to describe her preferences and no technical background to understand their impact. Preference parameters must be derived from observed choices or from preference statements obtained from the DM on some pairs of alternatives. Standard preference statements are of type "x *is at least as good as* y" (denoted $x \succsim y$), or "x *and* y *are indifferent*" (denoted $x \sim y$). Within CEU theory such preference statements are interpreted by the following equations for any two acts x, y in $\mathcal{X}$:

$$x \succsim y \quad \Leftrightarrow \quad f_v^u(x) \geq f_v^u(y)$$
$$x \sim y \quad \Leftrightarrow \quad f_v^u(x) = f_v^u(y)$$

We remark that the above inequalities and equalities are linear in v for any fixed x, y and u by definition of f (see Equation 1). We assume here that such preference statements are available, either because a preference database is available or because the DM is able to answer on demand to some preference queries.

Given a set of indifference statements $\mathcal{I} = \{(x^i, y^i) \in \mathcal{X}^2 : x^i \sim y^i, i = 1, \dots, q\}$ and/or a set of preference statements $\mathcal{P} = \{(x^i, y^i) \in \mathcal{X}^2 : x^i \succsim y^i, i = 1, \dots, p\}$, we look for a utility function u and a capacity v that match with the observed preferences. Since the CEU model may not perfectly match with the preferences expressed by the DM, we look for an approximate representation of preferences data. The approximation problem can be formulated as follows:

$$\min \sum_{i=1}^q (\epsilon_i^+ + \epsilon_i^-) + \sum_{i=1}^p \epsilon_i \qquad (4)$$

$$\begin{cases} f_v^u(x^i) - f_v^u(y^i) + \epsilon_i^+ - \epsilon_i^- = 0, \ i = 1 \dots q \\ f_v^u(x^j) - f_v^u(y^j) + \epsilon_i \geq 0, \ \forall (x^j, y^j), \ j = 1 \dots p \\ v(A) \leq v(A \cup \{i\}) \forall i \in S, \forall A \subseteq S \setminus \{i\} \\ \quad \epsilon_i^+ \geq 0, \epsilon_i^- \geq 0, \epsilon_j \geq 0, i = 1 \dots q, j = 1 \dots p. \end{cases}$$

The third line in the system of constraints is here to enforce the monotonicity of v with respect to set inclusion. We

remark that the above optimization problem is not linear since Choquet values of type $f_v^u(x)$ appearing in constraints include products of variables defining the utilities $u(x_i)$ and the capacities values $v(X_i)$ (see Equation 1).

In many contributions on preference learning methods based on the discrete Choquet integral, the utility function is assumed to be known and the focus is made on fitting the capacity. In this case, all constraints of the approximation problem formulated in Equation 4 are linear in v and the capacity can be obtained using standard linear programming solvers. This suggests learning the utility function first and then the capacity.

On the other hand, some recent contributions propose to learn simultaneously the utility function and the capacity. Finding exact solutions simultaneously both for the utility function and the capacity is a difficult task, since the problem is not linear and the constraints are not convex. Some heuristics to solve this problem were proposed. An approach based on the Monte Carlo was introduced by Angilella et al. [2004], and Goujon and Labreuche [2013] discussed a fixed-point method where the problem is split into two iterative linear tasks. Another heuristic based on a linear approximation of the product of the utility functions with Shapley values and interaction indices was considered by Galand and Mayag [2017]. An approach to find an exact solution for both utilities and capacities (in the context of the Choquistic regression) was proposed by Tehrani et al. [2014] where the utility function was represented as a linear combination of sigmoid functions. More recently, Bresson et al. [2020] developed a neural architecture to learn both utilities and the corresponding parameters of hierarchical Choquet integrals.

Besides, in the framework of decision under uncertainty, an elicitation method based on specific tradeoff queries has been used to construct some points on the utility function in interaction with the DM [Wakker and Deneffe, 1996, Abdellaoui, 2000]. This elicitation approach is interesting because it shows that, by a careful selection of preference queries, the utility can be indirectly observed and acquired, regardless the capacity. We would like to use this specificity of the CEU model to learn the utility in a first stage. Then, determining the capacity becomes easier and we can focus on learning sparse representations of v in a second stage. These two stages are presented in the two following sections.

4 LEARNING THE UTILITY FUNCTION

4.1 ASSESSING UTILITIES FROM INDIFFERENCE STATEMENTS

Let us remind that the DM is not assumed to be able to provide the overall value of an act (this would amounts to directly ask for utilities values). This is a source of difficulty because constraints of type $f_v^u(x) = \alpha$ frequently used

to perform regressions cannot be obtained by questioning the DM. However the DM can be asked to compare any act x to a constant act $\bar{y} = (y, \dots, y)$ for some $y \in X$. Hence $x \succsim \bar{y}$ is equivalent to $f_v^u(x) \geq f_v^u(\bar{y}) = u(y)$. Whenever the DM is indifferent between x and $\bar{y}$ we have $f_v^u(x) = u(y)$. In such a case, outcome y is said to be the *certainty equivalent* of x. Indifference statements giving the certainty equivalent $\bar{y}$ of binary acts of type $\bar{x}A\bar{z}$ for some $x, z \in X$ such that $x > z$ are often considered for preference elicitation. Indeed, $\bar{x}A\bar{z} \sim \bar{y}$ means that $f_v^u(\bar{x}A\bar{z}) = v(A)u(x) + (1 - v(A))u(z) = u(y)$. Hence, if $v(A)$ is known for some A, this enables to derive $u(y)$ from $u(x)$ and $u(z)$. Thus, u might be constructed point by point on a given interval $[x_m, x_M]$ from such indifferences by starting with two reference values $u(x_m) < u(x_M)$ arbitrary selected (e.g., $u(x_m) = 0$ and $u(x_M) = 1$). This process was used to elicit utilities in the context of risk [Hines and Larson, 2010, Perny et al., 2016]. However, in our context we have no simple way to obtain $v(A)$ for some A before knowing the utility function. For this reason we propose to learn the utility function by regression from indifference statements obtained with the tradeoff method [Wakker and Deneffe, 1996, Abdellaoui, 2000] adapted to the context of uncertainty.

The tradeoff method initially introduced in the context of risk involves preferences queries using gambles. Here, we describe a counterpart of this method in the context of uncertainty, to assess the utilities of outcomes within a given interval $[x_m, x_M]$ using mixtures of constant acts. Let us consider any event A such that $\bar{x}A\bar{y} \succ \bar{y}$ for some pair (x, y) of outcomes. Within CEU theory this strict preference is translated into $f_v^u(\bar{x}A\bar{y}) > f_v^u(\bar{y})$ which is equivalent to $v(A)u(x) + (1 - v(A))u(y) > u(y)$, i.e., $v(A) > 0$. Such an event A is said to be a *non-null*. So, given a non-null event A, let us choose $z, r, R \in X$ such that $z \leq x_M < r < R$ and consider the two following preference queries:

$Q(y, z)$: what is the outcome y such that: $\bar{y}A\bar{R} \sim \bar{z}A\bar{r}$?
$Q(x, y)$: what is the outcome x such that: $\bar{x}A\bar{R} \sim \bar{y}A\bar{r}$?

With such indifferences, the DM makes a tradeoff between changing z in y (or changing y in z) and changing r in R. Since $r < R$ we have $x < y$ and $y < z$. Moreover we have $f_v^u(\bar{y}A\bar{R}) = v(A)u(y) + (1 - v(A))u(R)$ and $f_v^u(\bar{z}A\bar{r}) = v(A)u(z) + (1 - v(A))u(r)$. Hence $f_v^u(\bar{y}A\bar{R}) = f_v^u(\bar{z}A\bar{r})$ implies $v(A)u(y) + (1 - v(A))u(R) = v(A)u(z) + (1 - v(A))u(r)$ and therefore $v(A)[u(z) - u(y)] = (1 - v(A))[u(R) - u(r)]$. Similarly, $\bar{x}A\bar{R} \sim \bar{y}A\bar{r}$ implies $v(A)[u(y) - u(x)] = (1 - v(A))(u(R) - u(r))$. Hence $v(A)[u(z) - u(y)] = v(A)[u(y) - u(x)]$. Since $v(A) \neq 0$ we obtain:
$$u(z) - u(y) = u(y) - u(x) \tag{5}$$

Such queries are often involved in a *standard sequence* that consists in sequentially asking question $Q(x_{i+1}, x_i)$ for $i = 0$ to $N - 1$, starting from $x_0 = x_M$ until $x_N \geq x_m$. From the observed indifferences, Equation 5

yields $u(x_{i-1}) - u(x_i) = u(x_i) - u(x_{i+1})$ and therefore $u(x_{i+1}) = 2u(x_i) - u(x_{i-1})$. Hence, fixing arbitrarily the utilities of x_0 and x_1 completely determines the utilities $u(x_i)$ for $i > 1$. However, if the DM makes some errors in assessing x_i in the early steps of the sequence, these errors will propagate and impact the whole sequence. In order to reduce the error propagation, we propose to perform a regression from a database of indifference statements obtained from queries of type $Q(y, z)$ and $Q(x, y)$ rather than performing a standard sequence.

More precisely, our learning approach proceeds as follows: for various non-null events A, various steps $s = R - r$ defined by different pairs (r, R) and various z, the two preference queries $Q(y, z)$ and then $Q(x, y)$ are asked to the DM. The resulting database of indifference statements yields a set of necessary linear constraints on utility values given by Equation 5, for all triplets (x, y, z) obtained from the answers to Q queries. Then a regression by a monotonic spline is performed to identify the utility function that best fits the set of linear constraints on utility values.

4.2 MONOTONIC SPLINE REGRESSION UNDER UTILITY CONSTRAINTS

In order to represent the utility function, we use a monotonic spline function, i.e., a piecewise polynomial function of class C^k. Spline functions are widely used for data interpolation or approximation due to their ability to smoothly approximate complex shapes. Moreover they allow for a compact representation of utilities. Indeed, a spline function can be expressed as a linear combination of basis functions and is thus characterized by the coefficients of the combination. Since utility increases with payoffs, we will use a basis $(I_l)_{l=1}^L$ of monotonically increasing spline functions, known as I-spline functions [Ramsay, 1988] weighted by positive coefficients (adding up to 1 so as to have $u(x_M) = 1$). We use here cubic I-splines ($k = 3$) because they have matching first and second derivatives while preserving a local influence of every components. Formally, u is defined by:

$$\forall x \in [x_m, x_M], \ u_\alpha(x) = \sum_{l=1}^L \alpha_l I_l(x) \qquad (6)$$

where $\alpha = (\alpha_1, \ldots, \alpha_L) \in [0, 1]^L$.

For the sake of illustration, we represent in Figure 1 the I-spline basis for $L = 10$ (value used in our tests) and an instance of utility function generated from this basis.

Our observations have been obtained using the Q queries and the database consists of N triplets (x^i, y^i, z^i), as described in the previous subsection. We want to determine the parameters α_l that best fit the associated constraints $2u(y^i) - u(z^i) - u(x^i) = 0, i = 1, \ldots, N$ obtained from Equation 5. Hence, using Equation 6, the problem can be

Figure 1: $u(x)$ generated from the I-splines

formalized as a linear program with relaxed constraints:

$$\min z = \sum_{i=1}^N (\epsilon_i^+ + \epsilon_i^-)$$

$$\begin{cases} \sum_{l=1}^L \alpha_l (2I_l(y^i) - I_l(z^i) - I_l(x^i)) + \epsilon_i^+ - \epsilon_i^- = 0, \ \forall i \\ \sum_{l=1}^L \alpha_l = 1 \end{cases}$$

$$\epsilon_i^+ \geq 0, \epsilon_i^- \geq 0, \alpha_l \geq 0.$$

The optimal values α_l^* characterize a spline function that best fits the constraints. The N constraints induced from the database of triplets might not be sufficiently informative to determine a utility function with confidence.

Taking into consideration that the number of observations is always limited we need to assess the level of uncertainty of the utility function. To this end, we investigate a neighborhood of the optimal solution defined by $z^* \leq z \leq z^* + \delta$ where δ is a tolerance threshold and z^* is the optimal value of z. This neighborhood V contains all spline functions that satisfy the constraints on utilities with an error at most equal to $z^* + \delta$. The range of variation of utilities within this set is a good indicator of the level of uncertainty allowed by the constraints. It can be measured by the quantity $\rho = \max_{x \in [x_m, x_M]} \{\max_{\alpha \in V} u_\alpha(x) - \min_{\alpha \in V} u_\alpha(x)\}$ estimated by discretization of $[x_m, x_M]$. When ρ is too large, the constraints are considered too weak to allow for the identifiability of u; one should carry on the Q queries process.

Let us illustrate our approach. We simulate a Q queries process with an DM answering according to a given CEU model f_v^u. Answers to queries of type $Q(y, z)$ for a given z and a pair (r, R) are simulated by solving the equation $f_v^u(\bar{y}A\bar{R}) = f_v^u(\bar{z}A\bar{r})$ which gives $y = u^{-1}(u(z) + [u(R) - u(r)](v(A) - 1)/v(A))$. Then x is derived from y using a similar process to simulate the answer to question $Q(x, y)$. Then the resulting triplet (x, y, z) is slightly distorted using a random uniform noise. This process is iterated N times for randomly chosen z, r, R, and A. We used the mathematical programming solver Gurobi (version 9.1.2) to perform the optimization task. The result of the learning process is presented on Figure 2 where we increase the size of the database in order to reduce ρ. In this instance, u is already well estimated with tight bounds for $N = 32$.

This experiment has been conducted for 1000 utility functions u randomly generated in the space of spline functions.

Figure 2: Identification of the utility function u for $N = 4$, $N = 16$, $N = 32$ (left to right).

Below we show the decrease of ρ and of the average distance $d(u, u_{\alpha^*})$ between the estimated utility function u_{α^*} and u as the number N of learning examples increases.

	N = 4	N = 16	N = 32
ρ	0.687	0.124	0.072
$d(u, u_{\alpha^*})$	0.354	0.024	0.004

5 LEARNING THE CAPACITY

5.1 SPARSITY BASED ON MÖBIUS MASSES

In Section 2 we have mentioned two alternative representations of a general capacity v: the Möbius inverse m, and the interaction indices I. Let us compare now their ability to provide compact representations. First of all, we can remark that, if $v(\{i\}) > 0$ for some i, then $v(A) > 0$ for any event $A \supset \{i\}$. Moreover, m is at least as compact as v due to the following proposition.

Proposition 1. *Let v be a capacity and m its Möbius inverse, we have: $\|v\|_0 \geq \|m\|_0$, where $\|.\|_0$ denotes the L_0 norm, i.e., the number of non-zero coefficients.*

Proof. Consider a capacity v and its Möbius representation m. If $v(A) = 0$ for some $A \subseteq S$, then $v(B) = 0$ for all $B \subseteq A$. Hence $m(A) = \sum_{B \subseteq A}(-1)^{|A \setminus B|} v(B) = 0$. Then $\{A : v(A) = 0\} \subseteq \{A : m(A) = 0\}$ and $\|v\|_0 = 2^n - |\{A : \mu(A) = 0\}| \geq 2^n - |\{A : m(A) = 0\}| = \|m\|_0$. $\square$

Moreover, the following result shows that the representation of v in terms of interaction may lack of compactness e.g., when v is a belief function (i.e., when m is non-negative).

Proposition 2. *Let v be a capacity and m and I its Möbius and interaction representations respectively. If m is non-negative, then $\|I\|_0 \geq 2^{|T^*|}$, where $T^* = \arg\max_{T \subseteq S} \{|T| : m(T) > 0\}$.*

Proof. The interaction index I is linked to m by the following equation: $I(A) = \sum_{T \supset A} \frac{1}{t-a+1} m(T)$ for all $A \subseteq S$ [Grabisch, 1997]. Hence, for any T s.t. $m(T) > 0$, we have $I(A) > \frac{1}{t-a+1} m(T) > 0$ for all $A \subseteq T$. Let T^* be the subset of maximal cardinality among those such that $m(T) > 0$, then the $2^{|T^*|}$ subsets of T^* have a strictly positive interaction index. Hence, $\|I\|_0 \geq 2^{|T^*|}$. $\square$

To illustrate a consequence of this proposition, let us consider again the maximin criterion $f(x) = \min_i u(x_i)$ which is an instance of CEU obtained from Equation 3 with $m(A) = 0$ for all $A \subset S$ and $m(S) = 1$. Then the above proposition shows that $I(A) > 0$ for all $A \subset S$. In this case the I representation is of size 2^n whereas the Möbius representation is very sparse (it includes a single non-null coefficient). Considering the above propositions and the well-known interest of Möbius masses to identify focal elements in beliefs, we focus hereafter on regularizations based on the Möbius representation of v.

5.2 SPARSE LEARNING OF MÖBIUS MASSES

Given the utility function u obtained as described above, we want to learn a sparse Möbius representation of the CEU model, based on Equation 3. However, since $\|m\|_1 \geq \sum_{B \subseteq S} m(B) = 1$ by definition, it is not quite natural to penalize with $\|m\|_1$ since its impossibility to decrease to zero would make ineffective any further reinforcement of the penalization as soon as $\|m\|_1 = 1$.

To overcome the problem we use the following representation of m: $m(B) = 1/n + w_B$ if $|B| = 1$ and $m(B) = w_B$ if $|B| > 1$, where w_B are real coefficients (positive or negative) such that $\sum_{B \subseteq S} w_B = 0$ (hence $\sum_{B \subseteq S} m(B) = 1$). Note that when all coefficients w_B are null, CEU boils down to a simple instance of Expected Utility where states are equally weighted. In the general case, w represents the gap to this basic model. In order to obtain a sparse representation in terms of Möbius we penalise on $\|w\|_1$ instead of $\|m\|_1$. This leads to solve the following linear program, which is a regularized version of (4) reformulated from Möbius masses (m_B are variables representing the masses $m(B), B \subseteq S$):

$$\min \sum_{i=1}^{q}(\epsilon_i^+ + \epsilon_i^-) + \sum_{i=1}^{p} \epsilon_i + \lambda \sum_{B \subseteq S}(w_B^+ + w_B^-)$$

$$\begin{cases} \sum_{B \subseteq S} m_B(U_B^{x^i} - U_B^{y^i}) + \epsilon_i^+ - \epsilon_i^- = 0, \ i = 1...q \\ \sum_{B \subseteq S} m_B(U_B^{x^i} - U_B^{y^i}) + \epsilon_i \geq 0, \ i = 1...p \\ m_B = 1/n + w_B, \ \forall B \subseteq S : |B| = 1 \\ m_B = w_B, \ \forall B \subseteq S : |B| > 1 \\ w_B = w_B^+ - w_B^-, \ \forall B \subseteq S \\ \sum_{C \subseteq B} m_{C \cup \{i\}} \geq 0, \ \forall i \in S, \ \forall B \subseteq S \setminus \{i\} \end{cases}$$

$$\epsilon_i^+ \geq 0, \epsilon_i^- \geq 0, \epsilon_j \geq 0, w_B^+ \geq 0, , w_B^- \geq 0, m_B, w_B \in \mathbb{R}$$

where $U_B^{x^i} = \min_{j \in B}\{u(x_j^i)\}, \forall B \subseteq S, \forall i$.

Figure 3: Predictive performance versus sparsity

Figure 4: Comparative test error for sparse and dense models

Now, we share the results of our numerical experiments to illustrate the learned sparse model with the linear program described above. They also have been obtained with the Gurobi optimizer. First, we investigate the impact of sparsity of m on the generalizing performance. We generated preference data as follows. A utility function u and a Möbius-sparse capacity v are randomly generated and preferences compatible with f_v^u are generated. Training data take the form of N pairs (x^i, y^i) of acts whose outcomes are randomly drawn from $[x_m, x_M]$. The preferences are stated from this pairs as follows: let $\tilde{f}_v^u(x)$ be a perturbation of $f_v^u(x)$ by uniform noise randomly drawn from a given interval $[-\sigma, \sigma]$, for any act x. If the difference $|\tilde{f}_v^u(x^i) - \tilde{f}_v^u(y^i)| \leq \sigma$, then x^i and y^i are considered as indifferent. If the difference is greater than σ, we conclude to preference. Pairs with Pareto dominance are discarded.

For the sake of illustration, we present the results of our approach on a toy dataset with $n = 7$ and $N = 100$. Hence, we have $2^7 - 2$ parameters to learn. The learning is performed for various values of λ ranging from 0 to 100 in order to obtain a sequence of increasingly sparse representations. For each obtained model, we assess the performance in generalization by measuring the error rate on a test set of 1000 preferences. Figure 3 (left) shows the tradeoff between the test error and the compactness of the Möbius representation measured by $\|m\|_0$. The curve shows that the introduction of the penalization term relevantly reduces both the error in tests and the number of non-null masses up to a point where we get close to the true model. Beyond this point, we see that further enforcing sparsity is counterproductive and increases the error in tests. Figure 3 (right) represents three Möbius representations of the capacity respectively learned without regularization ($\lambda = 0$, plot (1)), with regularization and optimal tradeoff ($\lambda = 0.5$, plot (2)), and the true one (plot (3)). It shows that the penalty term is needed to recover a model close to the true one.

A second experiment aims at highlighting the very special benefit of the regularization for small preferences databases

in term of predictive performance. Figure 4 illustrates the advantage of sparse models (obtained by regularization) for settings where the number of preference examples is small. We observed the average error rate taken on 30 datasets of the same size, and iterated the process for different sizes ranging from 50 to 1000. We observe on Figure 4 that the smaller the dataset, the bigger the increase of performance obtained by regularized models.

6 CONCLUSION

We have presented a new approach for learning the utility function and the capacity in CEU. A compact representation of utilities is obtained using a I-spline representation via a regression from indifference learning examples. Then, a sparse representation of the capacity is obtained based on Möbius masses. Propositions 1 and 2 suggest that this approach is more efficient than regularization based on v or I to obtain compact representations of CEU. Our tests confirm the practical effectiveness of the method. By proposing various tradeoffs between compactness and performance in the test phase, our approach allows to simplify the general CEU model while maintaining the expressiveness required to describe the preference data.

A natural extension of this work is to develop an active learning version, both for utilities and capacities. When the utility curve is underspecified by the indifference constraints, the selection of new Q queries could be directed by their ability to reduce ρ. Also, an active selection of preference queries could reduce the number of examples required to learn a sparse representation of the capacity. Besides, we could extend our approach to the framework of multiattribute decision making. Q queries could be adapted to learn a utility function per attribute using spline regression; then a sparse representation of the capacity could be learned to reveal the non-essential attributes and determine a multiattribute utility model keeping non-additive utilities only when necessary.

References

Mohammed Abdellaoui. Parameter-free elicitation of utility and probability weighting functions. *Management Science*, 46(11):1497–1512, 2000.

Titilope A. Adeyeba, Derek T. Anderson, and Timothy C. Havens. Insights and characterization of l1-norm based sparsity learning of a lexicographically encoded capacity vector for the Choquet integral. In *FUZZ-IEEE*, pages 1 – 7, 2015.

Derek T. Anderson, Stanton R. Price, and Timothy C. Havens. Regularization-based learning of the Choquet integral. In *FUZZ-IEEE*, pages 2519 – 2526, 2014.

Silvia Angilella, Salvatore Greco, Fabio Lamantia, and Benedetto Matarazzo. Assessing non-additive utility for multicriteria decision aid. *European Journal of Operational Research*, 158(3):734 – 744, 2004.

Kenneth J Arrow. The theory of risk aversion. *Essays in the theory of risk-bearing*, pages 90–120, 1971.

Carlos A Bana e Costa and Jean-Claude Vansnick. A theoretical framework for measuring attractiveness by a categorical based evaluation technique (macbeth). In *Multicriteria Analysis*, pages 15–24. Springer, 1997.

Gleb Beliakov and Dmitriy Divakov. On representation of fuzzy measures for learning Choquet and Sugeno integrals. *Knowledge-Based Systems*, 189:105134, 2020.

Gleb Beliakov and Jian-Zhang Wu. Learning k-maxitive fuzzy measures from data by mixed integer programming. *Fuzzy sets and systems*, 412:41 – 52, 2020.

Nawal Benabbou, Patrice Perny, and Paolo Viappiani. Incremental elicitation of Choquet capacities for multicriteria choice, ranking and sorting problems. *Artificial Intelligence*, 246:152–180, 2017.

Nadjet Bourdache, Patrice Perny, and Olivier Spanjaard. Incremental elicitation of rank-dependent aggregation functions based on Bayesian linear regression. In *IJCAI*, pages 2023–2029, 2019.

Roman Bresson, Johanne Cohen, Eyke Hüllermeier, Christophe Labreuche, and Michèle Sebag. Neural representation and learning of hierarchical 2-additive Choquet integrals. In *IJCAI*, pages 1984–1991, 2020.

Urszula Chajewska, Daphne Koller, and Ronald Parr. Making rational decisions using adaptive utility elicitation. In *AAAI/IAAI*, pages 363–369, 2000.

Alain Chateauneuf and Jean-Marc Tallon. Diversification, convex preferences and non-empty core in the Choquet expected utility model. *Economic Theory*, 19(3):509–523, 2002.

Henrique Evangelista de Oliveira, Leonardo Tomazeli Duarte, and João Marcos Travassos Romano. Identification of the Choquet integral parameters in the interaction index domain by means of sparse modeling. *Expert Systems with Applications*, 187, 2022.

Daniel Ellsberg. Risk, ambiguity, and the Savage axioms. *The quarterly journal of economics*, pages 643–669, 1961.

Peter C Fishburn. Utility theory for decision making. Technical report, Research analysis corp McLean VA, 1970.

Marek Gagolewski, Simon James, and Gleb Beliakov. Supervised learning to aggregate data with the Sugeno integral. *IEEE Transactions on Fuzzy Systems*, 27(4):810 – 815, 2019.

Lucie Galand and Brice Mayag. A heuristic approach to test the compatibility of a preference information with a Choquet integral model. In *ADT*, pages 65 – 80, 2017.

Itzhak Gilboa. *Theory of Decision under uncertainty*. Cambridge University Press, 2008.

Bénédicte Goujon and Christophe Labreuche. Holistic preference learning with the Choquet integral. In *EUSFLAT*, 2013.

Michel Grabisch. K-order additive discrete fuzzy measures and their representation. *Fuzzy sets and systems*, 92(2): 167–189, 1997.

Michel Grabisch and Christophe Labreuche. A decade of application of the Choquet and Sugeno integrals in multicriteria decision aid. *Annals of Operations Research*, 175 (1):247–286, 2010.

Michel Grabisch, Ivan Kojadinovic, and Patrick Meyer. A review of methods for capacity identification in Choquet integral based multi-attribute utility theory: Applications of the Kappalab R package. *European journal of operational research*, 186(2):766–785, 2008.

Trevor Hastie, Robert Tibshirani, and Martin Wainwright. *Statistical learning with sparsity: the Lasso and Generalizations*. CRC Press, 2015.

Greg Hines and Kate Larson. Preference elicitation for risky prospects. In *AAMAS*, pages 889–896, 2010.

Patrice Perny, Paolo Viappiani, and Abdellah Boukhatem. Incremental preference elicitation for decision making under risk with the rank-dependent utility model. In *UAI*, 2016.

Anthony J. Pinar, Derek T. Anderson, Timothy C. Havens, Alina Zare, and Titilope Adeyeba. Measures of the Shapley index for learning lower complexity fuzzy integrals. *Granul. Comput.*, 2:303 – 319, 2017.

John W Pratt. Risk aversion in the small and in the large. In *Uncertainty in economics*, pages 59–79. Elsevier, 1978.

John Quiggin. *Generalized expected utility theory: The rank-dependent model*. Springer Science & Business Media, 2012.

James O. Ramsay. Monotone regression spline in action. *Statistical Science*, page 425–441, 1988.

Leonard J. Savage. *The Foundations of Statistics*. J. Wiley and Sons, New-York, 1954.

David Schmeidler. Subjective probability and expected utility without additivity. *Econometrica*, 57(3):571–587, 1989.

Ali Fallah Tehrani. The Choquet kernel on the use of regression problem. *Information Sciences*, 556:256 – 272, 2021.

Ali Fallah Tehrani and Eyke Hülermeier. Ordinal Choquistic regression. In *EUSFLAT*, 2013.

Ali Fallah Tehrani, Weiwei Cheng, and Eyke Hülermeier. Choquistic regression: generalizing logistic regression using the Choquet integral. In *EUSFLAT*, 2011.

Ali Fallah Tehrani, Weiwei Cheng, Krzysztof Dembczyński, and Eyke Hüllermeier. Learning monotone nonlinear models using the Choquet integral. *Machine Learning*, 89:183 – 211, 2012a.

Ali Fallah Tehrani, Weiwei Cheng, and Eyke Hülermeier. Preference learning using the Choquet integral: the case of multipartite ranking. *IEEE Transactions on Fuzzy Systems*, 20(6):1102 – 1113, 2012b.

Ali Fallah Tehrani, Christophe Labreuche, and Eyke Hüllermeier. Choquistic utilitaristic regression. In *DA2PL*, pages 35 – 42, 2014.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society. Series B (methodological)*, 58(1):267 – 88, 1996.

Amos Tversky and Daniel Kahneman. An analysis of decision under risk. *Econometrica*, 47(2):263–292, 1979.

John von Neumann and Oskar Morgenstern. *Theory of games and economic behavior*. Princeton University Press, 1947.

Peter Wakker and Daniel Deneffe. Eliciting von neumann-morgenstern utilities when probabilities are distorted or unknown. *Management science*, 42(8):1131–1150, 1996.

Peter P Wakker. Testing and characterizing properties of nonadditive measures through violations of the sure-thing principle. *Econometrica*, 69(4):1039–1059, 2001.

Peter P Wakker. *Additive representations of preferences: A new foundation of decision analysis*, volume 4. Springer Science & Business Media, 2013.

Tianhan Wang and Craig Boutilier. Incremental Utility Elicitation with the Minimax Regret Decision Criterion. In *IJCAI*, pages 309–316, 2003.

Menahem E Yaari. The Dual Theory of Choice under Risk. *Econometrica*, 55(1):95–115, 1987.