MULTIVARIATE TIME-SERIES IMPUTATION WITH DISENTANGLED TEMPORAL REPRESENTATIONS

ABSTRACT

Multivariate time series often faces the problem of missing value. Many time series imputation methods have been developed in the literature. However, these methods all rely on an entangled representation to model dynamics of time series, which may fail to fully exploit the multiple factors (e.g., periodic patterns) contained in the time series. Moreover, the entangled representation usually has no semantic meaning, and thus they often lack interpretability. In addition, many recent models are proposed to deal with the whole time series to capture cross-channel correlations and identify temporal dynamics, but they are not scalable to large-scale datasets. Different from existing approaches, we propose TIDER, a novel matrix factorization-based method with disentangled temporal representations that account for multiple factors, namely *trend*, *seasonality*, and *local bias*, to model complex dynamics. The learned disentanglement makes the imputation process more reliable and offers explainability for imputation results. Moreover, TIDER is scalable to large datasets. Empirical results show that our method not only outperforms existing approaches by notable margins on three real-world datasets, but also scales well to large datasets on which existing deep learning based methods struggle. Disentanglement validation experiments further demonstrate the robustness of our model in obtaining accurate and explainable disentangled components.

1 INTRODUCTION

Multivariate time series analysis (e.g., forecasting (Zeng et al., 2021) and classification (Li et al., 2022)) has a wide spectrum of applications such as traffic flow forecasting (Liu et al., 2020), electricity demand prediction (Kaur et al., 2021), motion detection (Laddha et al., 2021), health monitoring(Tonekaboni et al., 2021), etc. Most of these multivariate time series analysis approaches typically assume intact input for building models. However, real-world multivariate time series tends to have missing values caused by factors like device malfunction, communication failure, or costly measurement, which will impair the performance of these approaches or even make them inapplicable.

In light of this, many time series imputation methods have been proposed to infer missing values from the observed ones. A multivariate time series, denoted as $\mathbf{X} \in \mathbb{R}^{N \times T}$, consists of N univariate time series (called channels) spanning over T time steps. Hence, it offers two perspectives for imputing missing values: modeling cross-channel correlations and exploiting temporal dynamics. Earlier methods (Batista et al., 2002; Acuna & Rodriguez, 2004; Van Buuren & Groothuis-Oudshoorn, 2011; Box et al., 2015) either aggregate observed entries across channels by estimating the similarity between two distinct channels, or solely exploit local smoothness or linear assumption in the same channel to fill in missing values. Since these methods lack the ability of modeling nonlinear dynamics and complex correlations, they may not perform well in practice.

In recent years, deep learning based methods (Liu et al., 2019; Tashiro et al., 2021; Cini et al., 2022) were proposed for time series imputation. These methods typically employ Recurrent Neural Networks (RNNs) as the backbone to jointly model nonlinear dynamics along temporal dimension (by updating hidden states nonlinearly over time steps) and cross-channel correlations (by mapping $\mathbf{x}_t \in \mathbb{R}^N$ from data space to hidden state space). These RNN-based imputation models achieve better results by further combining with multi-task loss (Cao et al., 2018; Cini et al., 2022) or adversarial training (Liu et al., 2019; Miao et al., 2021). Despite their success, these methods rely solely on a

single entangled representation (hidden state) to model dynamics. However, for many real-world multivariate time series, their dynamics are rich combinations of multiple independent factors like trend, seasonality (periodicity), and local idiosyncrasy (Woo et al., 2022). Modeling combinations of these factors with a single entangled representation may not give good performance, as the entangled representation has to compromise itself to explain multiple orthogonal patterns (like local changes or exogenous interventions vs global patterns) together (Bengio et al., 2013). Furthermore, it becomes exacerbated when seasonal patterns dominate, as RNNs lack the inductive bias to initiatively capture periodicity (Hewamalage et al., 2021). In addition, the hidden states that these models learned are entangled and complex combination of various components. Thus it is difficult for them to provide interpretable information to explain imputation. Moreover, in these methods, the whole time series of length T is required to be fed into their models at each forward step, to capture temporal dynamics (some methods need to fed in all N time series at each step to get cross-channel correlations). This is prohibitively costly for large N and T. Therefore, these methods are not applicable to large datasets.

To address these limitations, in this paper, we propose a novel multivariate time series imputation method, Time-series Imputation with Disentangled tEmporal Representations (TIDER), in which we explicitly model the complex dynamics of multivariate time series with disentangled representations to account for different factors. We employ a low-rank matrix decomposition framework, and achieve the disentanglement by imposing different forms of constraints on different representations which compose the low-rank matrix. In particular, we introduce a neighboring-smoothness representation matrix to explain the trend, a Fourier series-based representation matrix to define periodic inductive bias, and a local bias representation matrix to capture idiosyncrasies specific to individual time step. These disentangled representations offer better flexibility and robustness to model the factors contributed to the dynamics in time series. Another notable benefit of these semantically meaningful disentangled representations is that they offer TIDER an interpretable perspective on imputation. Moreover, TIDER is a scalable model. It allows to optimize model parameters by randomly selecting a subset of entries from the $N \times T$ matrix as training samples for each forward step, and we adopt a mini-batch training paradigm. Therefore, our method can be applied to datasets with large N and T. In summary, our contributions are as follows.

- We propose a new multivariate time series imputation model, TIDER, which is featured with effective and explainable disentangled representations to account for various factors that characterize the complex dynamics of time series. To the best of our knowledge, TIDER is the first model to learn disentangled representations for multivariate time series imputation.

- TIDER is the first imputation model that introduces a learnable Fourier series-based representation to capture periodic patterns inherent in time series data.

- Extensive experiments show that our proposed method outperforms the baseline imputation methods in terms of effectiveness and scalability. Especially, for imputation task in long time series, TIDER achieves more than 50% improvement in MAE, compared with the best imputation baseline approach. Furthermore, TIDER is a scalable model. It can easily handle large multivariate time series while existing deep-learning methods struggle. We also demonstrate the explanability of the disentangled representations with a case study.

2 RELATED WORK

Early time series imputation methods based on simple statistical strategies focus on exploiting local smoothness of temporal dimension as well as the similarity between different channels. For example, SimpleMean/SimpleMedian (Fung, 2006) imputes missing values by averaging, and KNN (Batista et al., 2002) aggregates cross-channel observations to fill in missing slots with k-nearest neighbors. Several approaches attempt to impute by building linear dynamics, including linear imputation and state-space models (Durbin & Koopman, 2012). MICE (Van Buuren & Groothuis-Oudshoorn, 2011) explores the idea of estimating missing slots with chain equations. These methods typically lack the ability of exploiting nonlinear dynamics and complex correlation across channels.

A recent trend in imputation methods is to apply deep learning, particularly RNNs, for better capturing the nonlinearity of time series. BRITS (Cao et al., 2018) treats missing values as variables which participate in bidirectional RNN back-propagation and are updated with hidden states. GAIN (Yoon et al., 2018) combines Generative Adversarial Nets (GAN) and RNNs for imputation. NAOMI (Liu

et al., 2019) combines RNNs and adversarial training strategies to generate realistic-looking sequences. SSGAN (Miao et al., 2021) is a semi-supervised GAN-based model, and uses label information to assist imputation. GRIN (Cini et al., 2022) fuses graph message passing into the GRU structure to learn spatial-temporal patterns. All these approaches model dynamics based on a single entangled representation, which is insufficient to capture multiple factors underlying time series, especially when seasonality emerges, since RNNs lack the inductive bias to initiatively capture periodicity (Hewamalage et al., 2019). Moreover, these approaches are not scalable to large datasets since they have to process time series of length T at each forward step to capture temporal dynamics. Some approaches (Liu et al., 2019) also need to feed in all N time series at each step to capture cross-channel correlations.

Our proposed model TIDER is based on low-rank matrix factorization (Yu et al., 2016; Bjorck et al., 2021). Vanilla matrix factorization can impute missing entries by learning two latent factors $\mathbf{U}, \mathbf{V}$ to exploit low-rank structure. However, it fails to consider the temporal continuity of time-series. To address this, TRMF (Yu et al., 2016) imposes autoregressive constraints on temporal factor $\mathbf{V}$. However, similar to the aforementioned methods, TRMF also relies on an entangled representation matrix to account for all factors underlying the dynamics. In contrast, TIDER tackles this issue by introducing multiple disentangled representations. We achieve the disentanglement by enforcing different forms of constraints into different representations. Particularly, Fourier-Series-based seasonality representation is explored for the first time in imputation models, which plays a crucial role in accurate and explainable imputation as to be shown in our experiments.

3 PROBLEM STATEMENT

Given N univariate time series data $\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_N \in \mathbb{R}^T$ collected over T time steps, we represent it with a multivariate time series matrix $\mathbf{X} \in \mathbb{R}^{N \times T}$, whose n-th row represents n-th univariate time series (channel) $\mathbf{x}_n$ and t-th column denotes the observation of all time series at time step t. The multivariate time series matrix $\mathbf{X}$ is incomplete and a fraction of entries are missed. We aim to infer missing values from the observed ones, and we denote the mask matrix as $\mathbf{M} \in \{0, 1\}^{N \times T}$, where

$$M_{ij} = \begin{cases} 1, & \text{if } X_{ij} \text{ is observed,} \\ 0, & \text{otherwise.} \end{cases} \tag{1}$$

4 METHODOLOGY

4.1 METHOD OVERVIEW

As mentioned in Section 1, the existing deep learning based multivariate time-series imputation methods have two limitations: 1) they model complex temporal dynamics with a single entangled representation, which may not be capable of capturing the multiple factors contributing to the temporal dynamics of time series, and thus lacking accuracy and interpretability; 2) their scalability is limited, since they have to feed (all N) time series of time span T at each forward step to capture (cross-channel correlations and) temporal dynamics. TIDER is developed to address these two limitations. Our core idea is to decompose multivariate time series $\mathbf{X}$ into two latent factors $\mathbf{U}$ and $\mathbf{V}$, such that $\mathbf{U}$ only preserves features unique to each channel whereas $\mathbf{V}$ is determined by multiple disentangled representations that jointly capture temporal dynamics. We employ such factorization for two main reasons: 1) univariate time series channels (rows of $\mathbf{X}$) are usually highly correlated; 2) observations at different time steps (columns of $\mathbf{X}$) exhibit strong temporal dynamics.

The benefits of our design are twofold: 1) cross-channel correlations are decoupled since $\mathbf{U}$ only preserves channel-specific features, and thus it allows us to optimize model parameters by only selecting a subset of channels as training samples instead of considering all of them at each forward step, thereby enabling our approach to scale well to large datasets; 2) time-related information is isolated into $\mathbf{V}$, and it enables us to model the potentially complex temporal dynamics with multiple explainable disentangled representations.

Figure 1 shows the architecture of TIDER. We adopt a low-rank matrix decomposition framework to factorize multivariate time series matrix $\mathbf{X}$ into two latent factors $\mathbf{U}, \mathbf{V}$. $\mathbf{U}$ is a correlation-decoupled matrix which accounts for channel-specific patterns, while $\mathbf{V}$ is a matrix for time-related

Figure 1: Architecture of the proposed method TIDER. X is the multivariate time series matrix. U represents a correlation-decoupled matrix. V_t, V_s, and V_b denote trend representation matrix, seasonality representation matrix and bias representation matrix, respectively.

information. Since temporal dynamics underlying real-world time series can be rich and complex combinations of multiple factors, e.g., trend and seasonality, modeling them merely through an entangled representation matrix will lead to model degradation. Woo et al. (2022) proposes that under mild assumptions, seasonality and trend can be treated as independent factors in time series generating process, and Cohen (2013) suggests that independence can be used as a proxy criterion for disentanglement. Inspired by them, we propose to model $\mathbf{V}$ with multiple disentangled representations, each accounting for one particular factor. We achieve the disentanglement by enforcing distinct forms of constraints on different representations, which introduce distinct inductive biases into these representations and make them more liable to capture specific semantically-independent patterns. More specifically, we consider three important factors: *trend*, *seasonality*, and *bias*, which are specified by three representation matrix $\mathbf{V}_t$, $\mathbf{V}_s$, $\mathbf{V}_b$, respectively. Figure 2 illustrates an example of decomposing a time series into these three factors. Trend representation matrix $\mathbf{V}_t \in \mathbb{R}^{D \times T}$ captures the intrinsic trend which changes gradually and smoothly, and seasonality representation matrix $\mathbf{V}_s \in \mathbb{R}^{D \times T}$ illustrates the periodic patterns hidden in temporal dynamics. $\mathbf{V}_t$ and $\mathbf{V}_s$ jointly determine the dynamics driven by endogenous factors. Bias representation matrix $\mathbf{V}_b \in \mathbb{R}^{D_b \times T}$ characterizes variations specific to each time step. Intuitively, $\mathbf{V}_b$ explains the individual idiosyncratic behaviors of time steps, which are orthogonal to global dynamics but shared across channels at a given time step. Hence, we treat it differently from $\mathbf{V}_t$, $\mathbf{V}_s$ and interpret it as a residual term matrix, i.e., $\mathbf{X} - \mathbf{U}(\mathbf{V}_t + \mathbf{V}_s) \approx \mathbf{1}_{N \times D_b} \mathbf{V}_b$. Mathematically, we formulate the objective of TIDER as

$$\text{minimize} \, \|(\mathbf{X} - \mathbf{U}_a \mathbf{V}) \odot \mathbf{M}\|^2 + \lambda_t f_t(\mathbf{V}_t) + \lambda_b f_b(\mathbf{V}_b) + \eta_1 \|\mathbf{U}\|^2 + \eta_2 \|\mathbf{V}\|^2,$$

$$\mathbf{U}_a = [\, \mathbf{U} \mid \mathbf{1} \,] \in \mathbb{R}^{N \times (D+D_b)}, \quad \mathbf{V} = \begin{bmatrix} \mathbf{V}_t + \mathbf{V}_s \\ \mathbf{V}_b \end{bmatrix} \in \mathbb{R}^{(D+D_b) \times T}, \tag{2}$$

where $\mathbf{U}_a$ is the augmented matrix of latent factor $\mathbf{U} \in \mathbb{R}^{N \times D}$, f_t and f_b are corresponding inductive bias constraint functions imposed on $\mathbf{V}_t$ and $\mathbf{V}_b$. $\mathbf{M}$ is the mask matrix introduced in Sec 3. The last two terms $\eta_1 \|\mathbf{U}\|^2$, $\eta_2 \|\mathbf{V}\|^2$ are used to regularize the magnitude of latent factors, and $\lambda_t, \lambda_b, \eta_1, \eta_2$ are corresponding weights for each term. The learned $\mathbf{U}_a$ and $\mathbf{V}$ are used to generate the imputed time series $\hat{\mathbf{X}}$ as

$$\hat{X}_{ij} = \begin{cases} X_{ij}, & M_{ij} = 1, \\ (\mathbf{U}_a \mathbf{V})_{ij}, & M_{ij} = 0. \end{cases} \tag{3}$$

We are now ready to elaborate on the details of the three disentangled representation matrices.

4.2 Trend Representation Matrix

Trend representation matrix $\mathbf{V}_t$ characterizes the intrinsic trend of time series. The evolution patterns dominated by $\mathbf{V}_t$ are supposed to change gradually and smoothly in the absence of accidents or extreme events such as holidays (we will consider these external interventions and exogenous influences in $\mathbf{V}_b$). Based on this, we impose a smoothness constraint on $\mathbf{V}_t$ as

$$f_t(\mathbf{V}_t) = \sum_{j=2}^{T} \|\mathbf{v}_t^j - \mathbf{v}_t^{j-1}\|^2, \tag{4}$$

where $\mathbf{v}_t^j$ is the j-th column of $\mathbf{V}_t$. Equation 4 encourages close representations of two adjacent time steps in latent space, which will result in a smooth change in data space. Note that we only

Figure 2: Visualization of time series decomposition. (a) is the raw time series, whereas (b), (c), and (d) are its decomposed trend, seasonality, and residual component. The grey bars on the right of each subplot show the relative scales of the components. Each grey bar represents the same length.

impose constraints on two consecutive time steps to account for short-term patterns whereas long-term patterns are explained by $\mathbf{V}_s$. This is in contrast with TRMF (Yu et al., 2016) which uses one temporal matrix to account for both short-term and long-term patterns by imposing regression constraint.

4.3 SEASONALITY REPRESENTATION MATRIX

Real-world time series often demonstrate seasonal patterns. For instance, traffic flow exhibits strong daily and weekly seasonality due to regularity of human activities, such as commuting patterns. Solar power production presents clear periodic characteristics caused by climate seasonality and meteorological conditions. Motivated by this and Fourier analysis in Section A.1.2, we propose to model the seasonality of time series by parameterizing representation matrix $\mathbf{V}_s$ with Fourier basis.

$\mathbf{V}_s$ is a matrix with size $D \times T$, we represent each row with a superposition of $2K$ sinusoidal waves ($K \ll T$). More formally, let $\mathbf{A}, \mathbf{B} \in \mathbb{R}^{D \times K}$ be two learnable coefficient matrices, and $\phi_{\sin}$, $\phi_{\cos} \in \mathbb{R}^{T \times K}$ be the corresponding Fourier basis matrices, which are defined as

$$\mathbf{A} = \begin{bmatrix} | & | & & | \\ \mathbf{a}_1 & \mathbf{a}_2 & \dots & \mathbf{a}_K \\ | & | & & | \end{bmatrix}, \quad \phi_{\sin} = \begin{bmatrix} | & | & & | \\ \sin(1\omega\mathbf{t}) & \sin(2\omega\mathbf{t}) & \dots & \sin(K\omega\mathbf{t}) \\ | & | & & | \end{bmatrix}, \quad (5)$$

$$\mathbf{B} = \begin{bmatrix} | & | & & | \\ \mathbf{b}_1 & \mathbf{b}_2 & \dots & \mathbf{b}_K \\ | & | & & | \end{bmatrix}, \quad \phi_{\cos} = \begin{bmatrix} | & | & & | \\ \cos(1\omega\mathbf{t}) & \cos(2\omega\mathbf{t}) & \dots & \cos(K\omega\mathbf{t}) \\ | & | & & | \end{bmatrix}, \quad (6)$$

where $\mathbf{t} = [1, \dots, T]^\top$. For one specific time-series with period P, ω is calculated as $2\pi/P$.

Then the seasonality representation matrix $\mathbf{V}_s$ can be defined as

$$\mathbf{V}_s = \mathbf{A}\phi_{\sin}^\top + \mathbf{B}\phi_{\cos}^\top. \quad (7)$$

In other words, $\mathbf{V}_s$ is spanned by Fourier basis $\phi_{\sin}$ and $\phi_{\cos}$. In particular, the d-th row of $\mathbf{V}_s$, denoted by $(\mathbf{v}_s^d)^\top$, has the form

$$(\mathbf{v}_s^d)^\top = \sum_{k=1}^{K} \mathbf{A}_{d,k} \sin(k\omega\mathbf{t})^\top + \sum_{k=1}^{K} \mathbf{B}_{d,k} \cos(k\omega\mathbf{t})^\top, \quad (8)$$

which is a truncated Fourier series with coefficients $\mathbf{A}_{d,k}, \mathbf{B}_{d,k}$. This elaborate design of $\mathbf{V}_s$ provides meaningful periodic inductive bias, which enables our model to capture seasonal patterns more accurately and effectively, by learning coefficient matrices $\mathbf{A}, \mathbf{B}$ from data.

4.4 BIAS TEMPORAL REPRESENTATION MATRIX

The representation matrices $\mathbf{V}_t$, $\mathbf{V}_s$ presented so far jointly determine the dynamics driven by endogenous factors of multivariate time series. However, there are also various external factors

(e.g., holidays, weekdays/weekends) that could affect real-world time series. These external factors usually occur at specific time points and yield local variations within short time period, thus they are independent of endogenous dynamics and cannot be captured by V_t and V_s. And also, these factors impact nearly equally on all channels. To account for these local variations, inspired by the idea of user and item bias explored in collaborative filtering (Lü et al., 2012), we propose to learn another bias representation matrix $\mathbf{V}_b \in \mathbb{R}^{D_b \times T}$, where the representation of a specific time step is shared by all channels. In addition, we impose an autoregressive constraint on $\mathbf{V}_b$ in temporal dimension since the impact caused by local variation usually lasts for a short duration. Let $\mathbf{v}_t$ be the t-th column of $\mathbf{V}_b$ and L be the maximum time lag indicating duration, we define the constraint function as follows,

$$f_b(\mathbf{V}_b) = \sum_{t=L+1}^{T} \left\| \mathbf{v}_b^t - \sum_{l=1}^{L} \mathbf{W}_l \mathbf{v}_b^{t-l} \right\|^2, \tag{9}$$

where $\mathcal{W} = \{ \mathbf{W}_l \in \mathbb{R}^{D_b \times D_b} \mid l = 1 \ldots L \}$ is a group of learnable parameters. In our setting, D_b and L are small numbers, thus group $\mathcal{W}$ only incurs very few extra parameters.

4.5 Adaptive Weight for Trend and Seasonality

In Section 4.1, we use the additive form $\mathbf{V}_t + \mathbf{V}_s$ to characterize the influence of endogenous impacting factors. This implicitly assumes that trend and seasonality components contribute equally to endogenous dynamics. But in practice the importance of trend and seasonality can vary drastically across data sources, which is illustrated in Figure 2. To address this, we adopt a learnable parameter $\alpha \in (0, 1)$ to adaptively adjust the weight for these two components, which leads to a weighted additive form $\alpha \mathbf{V}_t + (1 - \alpha)\mathbf{V}_s$. The temporal matrix $\mathbf{V}$ in Equation 2 then becomes:

$$\mathbf{V} = \left[\begin{array}{c} \alpha\mathbf{V}_t + (1 - \alpha)\mathbf{V}_s \\ \mathbf{V}_b \end{array} \right]. \tag{10}$$

5 Experiments

we evaluate the performance of TIDER by comparing with existing multivariate time series imputation methods, in terms of imputation accuracy and scalability. We also show the explanability of TIDER with a case study. The code of TIDER is available at `https://anonymous.4open.science/r/TIDER-527C`.

5.1 Experimental Setup

Baseline Methods We compare our model with popular baselines used in the literature and recently-proposed methods, including statistical models (SimpleMean, KNN, MICE), MF-based methods (MF, MF+L2, SoftImpute, TRMF), and deep learning approaches (BRITS, GAIN, NAOMI, SingleRes, SAITS, CSDI). Details and settings of these baselines can be found in Section A.3. In addition, we also include TIDER (no W), a variant of TIDER without the learnable parameter α, to verify the effectiveness of the adaptive weight introduced in Section 4.5.

Datasets We use three real-world datasets of different characteristics. Guangzhou dataset is a relatively small one where all methods can fit in. Solar-energy shares an extremely long time-span while Westminster is one with large N. The latter two datasets are relatively large and thus some approaches struggle to handle them. For more details about datasets, please refer to Section A.2.

Evaluation Metrics We adopt RMSE, MAE, and MAPE to evaluate the imputation accuracy of all compared methods. Details of these three metrics can be found in Section A.4.

Training Setup We randomly remove a subset of entries from $\mathbf{X}$ as validation and test datasets separately. Let r be the missing rate variable, the ratio of training/validation/test is $(0.9 - r)/0.1/r$. For each model we run experiments 7 rounds on every dataset and report the imputed results averaged over these 7 runs. All experiments are conducted on a Linux workstation with a 32GB Tesla V100 GPU. For more detailed hyperparameter settings, please refer to Table 5.

Table 1: Imputation accuracy of different methods with missing rate $r = 0.2$

Method	Guangzhou			Solar-energy			Westminster		
($r = 0.2$)	RMSE	MAE	MAPE	RMSE	MAE	MAPE	RMSE	MAE	MAPE
SimpleMean	10.24	8.023	0.396	3.352	2.433	4.527	5.233	4.247	0.410
KNN	6.540	4.731	0.242	2.701	1.748	2.324	2.249	1.611	0.147
MF	5.642	4.301	0.188	3.769	2.447	4.243	2.275	1.641	0.137
MF+L2	5.400	4.074	0.177	2.761	1.918	2.760	2.109	1.523	0.134
SoftImpute	5.876	4.465	0.217	2.692	1.903	3.051	2.347	1.645	0.141
MICE	5.097	3.859	0.161	2.647	1.763	2.372	2.638	2.014	0.169
TRMF	4.563	3.407	0.148	3.212	2.010	2.937	1.903	1.370	0.119
BRITS	4.416	3.003	0.139	2.617	1.861	2.677	2.154*	1.488*	0.136*
GAIN	4.976	3.451	0.154	2.803	1.917	2.501	1.947	1.403	0.121
SAITS	4.407	3.025	0.140	OOM	OOM	OOM	1.893	1.366	0.119
CSDI	4.301	**2.991**	0.135	OOM	OOM	OOM	1.886	1.361	0.116
NAOMI	5.173	4.013	0.167	OOM	OOM	OOM	OOM	OOM	OOM
SingleRes	4.997	3.979	0.172	OOM	OOM	OOM	OOM	OOM	OOM
TIDER (no W)	4.431	3.229	0.142	1.872	0.893	2.522	1.981	1.426	0.127
TIDER	**4.168**	3.098	**0.132**	**1.676**	**0.874**	**2.227**	**1.867**	**1.354**	**0.115**
Improvement (%)	3.092	/	2.222	35.96	50.00	4.174	1.007	0.514	0.862

Table 2: Imputation accuracy of different methods with missing rate $r = 0.4$

Method	Guangzhou			Solar-energy			Westminster		
($r = 0.4$)	RMSE	MAE	MAPE	RMSE	MAE	MAPE	RMSE	MAE	MAPE
SimpleMean	9.949	7.901	0.384	3.259	2.412	4.889	5.243	4.259	0.407
KNN	6.712	4.955	0.252	2.724	1.835	2.874	2.391	1.714	0.159
MF	7.671	5.844	0.246	4.111	2.887	5.851	2.476	1.807	0.153
MF+L2	7.324	5.553	0.235	2.617	1.80	2.977	2.157	1.593	0.134
SoftImpute	5.811	4.465	0.209	2.536	1.849	3.311	2.333	1.637	0.145
MICE	7.119	5.417	0.235	2.756	1.823	3.517	2.755	2.113	0.175
TRMF	6.119	4.617	0.198	3.407	2.199	3.586	2.014	1.453	0.126
BRITS	4.874	3.335	0.158	2.842	1.985	3.146	2.180*	1.527*	0.138*
GAIN	5.550	3.671	0.192	2.639	1.883	3.117	2.337	1.711	0.145
SAITS	4.839	3.391	0.159	OOM	OOM	OOM	1.998	1.453	0.129
CSDI	4.813	**3.202**	0.157	OOM	OOM	OOM	1.982	1.437	0.124
NAOMI	5.986	4.543	0.222	OOM	OOM	OOM	OOM	OOM	OOM
SingleRes	6.051	4.705	0.252	OOM	OOM	OOM	OOM	OOM	OOM
TIDER (no W)	**4.708**	3.469	0.155	1.697	0.878	3.152	2.013	1.466	0.125
TIDER	4.764	3.527	**0.152**	**1.679**	**0.838**	**2.735**	**1.959**	**1.422**	**0.121**
Improvement (%)	2.182	/	3.185	33.79	54.03	4.836	1.160	1.055	2.419

5.2 IMPUTATION ACCURACY COMPARISON

Table 1 and Table 2 show the imputation accuracy of all methods on three datasets with different missing rate r. OOM indicates out of memory. The meaning of asterisk and improvement are illustrated in Section A.3. Our proposed TIDER achieves the best performance in most cases in terms of the three metrics. In particular, the superiority of our proposed method is much more significant in Solar-energy, the dataset with extremely large T. In addition, we observe that the imputation accuracy of all methods drops as missing rate r increases, which is as expected since fewer patterns are available.

Among all baseline methods, CSDI has the best performance on most datasets, and deep-learning methods (BRITS, GAIN, SAITS, CSDI) usually perform better than other baselines. However, TIDER outperforms these models by large margins on each dataset. This could be attributed to our model's ability of modeling multiple factors. For example, TIDER can capture periodic patterns underlying time series where these deep learning models typically lack the corresponding inductive bias. Moreover, on solar-energy dataset, where time span T is $52, 560$, many deep learning methods

Figure 3: Scalability test on Westminster dataset: (a) Memory usage of different methods varies over N from 0 to 5000 with fixed $T = 100$; (b) Memory usage of different methods varies over T from 100 to 700 with fixed $N = 100$; (c) The average running time taken by different methods for every 100 epochs when processing a 100×100 matrix.

run into OOM on a 32GB-memory GPU, even if we set the batch size to one. In contrast, TIDER is still applicable and achieves the best performance.

We observe that MF-based models can all work for datasets with large N and T. The difference between these models lies in constraints on $\mathbf{U}$ and $\mathbf{V}$. Compared with other MF-based baselines, TRMF outperforms others in most cases, since it intuitively captures auto-regressive dynamics. However, since TRMF employs merely an entangled representation, it cannot model complex dynamics well. TIDER (no W) and TIDER utilize disentangled features like trend, seasonality and local bias to rebuild patterns for time-series, which exploit explanatory temporal factors, thus achieving better imputation result. Furthermore, TIDER performs better than TIDER (no W). This is consistent with our previous analysis that trend and seasonality components might not contribute equally to global dynamics.

5.3 Scalability Analysis

We study the scalability of different methods in terms of both memory usage and training time. In particular, we compare our method with state-of-the-art imputation methods, BRITS, NAOMI, SingleRes, SAITS, and CSDI. Figure 3-(a) and Figure 3-(b) present the memory footprints of different methods against channel number N and time span T. It can be seen from Figure 3-(a) that memory usage of NAOMI and SingleRes grow rapidly with very steep slopes, and that of BRITS also grows quickly whereas TIDER needs much less memory. Similarly, Figure 3-(b) shows that the memory usage of NAOMI, SingleRes, and SAITS also grows fast as T increases. Again, TIDER needs the least amount of memory. There is also a gap between the curves of CSDI (BRITS) and TIDER in Figure 3, which is overwhelmed by the magnitude of NAOMI and SingleRes. We present these gaps in Section A.7. Lastly, Figure 3-(c) demonstrates the running time of different methods for 100 epochs when processing a 100×100 matrix. TIDER runs much faster than RNNs-based methods. Notably, TIDER outperforms BRITS by almost an order of magnitude. This is also true for the total time taken by entire training process. Thus, we can use a mini-batch paradigm to optimize TIDER's parameters, where we randomly select a subset of entries from the N × T time-series matrix as training samples for each forward step. Furthermore, the space complexity of BRITS is $O(N(N + T))$(Vaswani et al., 2017) while that of TIDER is $O(N + T)$. The complexity of NAOMI and SingleRes was not established and is tricky to analyze due to their complex divide-and-conquer strategy, but their complicated procedure yields more intermediate variables and thus results in more memory consumption than BRITS, as empirically validated by our experiments. In conclusion, this experiment demonstrates the scalability of our model, showing its ability to handle large datasets where existing RNN-based methods struggle.

5.4 Ablation Analysis

To verify the effectiveness of our proposed disentangled representation matrices, we conduct an ablation study on Guangzhou dataset by removing one of the trend, seasonality, and bias representation matrices while leaving the rest of the model unchanged. The ablative results with missing rate $r = 0.2\,(0.4)$ are presented in Table 3. We find that the model performance drops no matter which representation is removed, which validates that all of our proposed disentangled representations play an important role in imputation and jointly enhance the performance of the final model.

Table 3: Ablation Analysis of TIDER on Guangzhou dataset.

Name	RMSE	MAE	MAPE
$\mathbf{V}_s + \mathbf{V}_b$	7.241 (7.497)	5.388 (5.459)	0.272 (0.294)
$\mathbf{V}_t + \mathbf{V}_b$	5.680 (6.392)	4.311 (4.899)	0.190 (0.214)
$\mathbf{V}_s + \mathbf{V}_t$	5.297 (5.999)	4.014 (4.520)	0.170 (0.201)
TIDER	**4.168 (4.764)**	**3.098 (3.527)**	**0.132 (0.152)**

Figure 4: Case study of disentanglement. (a) is the original time-series, whereas (b),(c) and (d) represent the generated intrinsic trend, seasonality, and local variation within a period of time.

5.5 CASE STUDY OF DISENTANGLEMENT

This experiment is to demonstrate that the learned representations achieve disentanglement and offer explanability. We visualize a time-series from Guangzhou dataset and its learnt patterns, namely, trend patterns $\mathbf{u}^\top \mathbf{V}_t$, seasonality patterns $\mathbf{u}^\top \mathbf{V}_s$, and bias patterns $\mathbf{1}^\top \mathbf{V}_b$, where $\mathbf{u}^\top$ is the time-series representation (a row of $\mathbf{U}$). Figure 4 shows that the learned representations generate semantically meaningful patterns. Figure 4-(b) shows a gradually changing curve that corresponds to trend patterns, whereas Figure 4-(c) exhibits clear periodicity, and Figure 4-(d) manifests more idiosyncratic behaviors. Each of the displayed patterns captures information from a particular semantic perspective, which verifies that the learned representations $\mathbf{V}_t$, $\mathbf{V}_s$, $\mathbf{V}_b$ exhibit independence and disentanglement. We also conduct experiments on synthetic data in Section A.5 to further show TIDER's ability in learning meaningful and interpretable disentanglement.

6 CONCLUSION

In this paper, we propose a scalable multivariate time series imputation method, TIDER, with multiple novel inductive bias under the framework of low-rank matrix factorization. In contrast to existing imputation approaches, TIDER adopts semantically meaningful disentangled representations to account for multiple factors of a time series. In particular, it enables capturing periodicity with a novel Fourier basis-based representation and allows to identify local time variation with a time bias representation. TIDER's superiority is verified by experimental results. Moreover, it scales well to large datasets where the existing methods struggle or even cannot fit. In the future, it is interesting to investigate how to use the meaningful disentangled representations for forecasting tasks and how to design constraints on $\mathbf{U}$ when channel information is available. Furthermore, since now we use hyperparameter tuning techniques to decide P in V_s, how to obtain P adaptively in a data-driven way is also worth further investigation.

7 REPRODUCIBILITY STATEMENT

We provide an open-source implementation of our proposed model, TIDER, at `https://anonymous.4open.science/r/TIDER-527C`. Hyperparameter setting is shown in Section A.6. Users can download the code and run TIDER easily.

REFERENCES

Edgar Acuna and Caroline Rodriguez. The treatment of missing values and its effect on classifier accuracy. In *Classification, clustering, and data mining applications*. Springer, 2004.

Melissa J Azur, Elizabeth A Stuart, Constantine Frangakis, and Philip J Leaf. Multiple imputation by chained equations: what is it and how does it work? *International journal of methods in psychiatric research*, 20(1):40–49, 2011.

Gustavo EAPA Batista, Maria Carolina Monard, et al. A study of k-nearest neighbour as an imputation method. 2002.

Yoshua Bengio, Aaron C. Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE TPAMI*, 2013.

Johan Bjorck, Anmol Kabra, Kilian Q. Weinberger, and Carla P. Gomes. Characterizing the loss landscape in non-negative matrix factorization. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 6768–6776. AAAI Press, 2021. URL `https://ojs.aaai.org/index.php/AAAI/article/view/16836`.

George EP Box, Gwilym M Jenkins, Gregory C Reinsel, and Greta M Ljung. *Time series analysis: forecasting and control*. John Wiley & Sons, 2015.

Wei Cao, Dong Wang, Jian Li, Hao Zhou, Lei Li, and Yitan Li. Brits: Bidirectional recurrent imputation for time series. *NeurIPS*, 2018.

Jiawei Chen, Can Wang, Sheng Zhou, Qihao Shi, Jingbang Chen, Yan Feng, and Chun Chen. Fast adaptively weighted matrix factorization for recommendation with implicit feedback. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 3470–3477. AAAI Press, 2020. URL `https://ojs.aaai.org/index.php/AAAI/article/view/5751`.

Xinyu Chen, Yixian Chen, and Zhaocheng He. Urban traffic speed dataset of guangzhou, china, March 2018. URL `https://doi.org/10.5281/zenodo.1205229`.

Andrea Cini, Ivan Marisca, and Cesare Alippi. Filling the g_ap_s: Multivariate time series imputation by graph neural networks. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL `https://openreview.net/forum?id=kOu3-S3wJ7`.

Taco Cohen. *Learning transformation groups and their invariants*. PhD thesis, PhD thesis, University of Amsterdam, 2013.

Wenjie Du, David Côté, and Yan Liu. Saits: Self-attention-based imputation for time series. *arXiv preprint arXiv:2202.08516*, 2022.

James Durbin and Siem Jan Koopman. *Time series analysis by state space methods*, volume 38. OUP Oxford, 2012.

David S Fung. Methods for the estimation of missing values in time series. 2006.

Hansika Hewamalage, Christoph Bergmeir, and Kasun Bandara. Recurrent neural networks for time series forecasting: Current status and future directions. *CoRR*, abs/1909.00590, 2019. URL http://arxiv.org/abs/1909.00590.

Hansika Hewamalage, Christoph Bergmeir, and Kasun Bandara. Recurrent neural networks for time series forecasting: Current status and future directions. *International Journal of Forecasting*, 37 (1):388–427, 2021.

Manpreet Kaur, Shalini Panwar, Ayush Joshi, and Kapil Gupta. Residential electricity demand prediction using machine learning. In Sarika Jain and Sven Groppe (eds.), *Proceedings of the International Semantic Intelligence Conference 2021 (ISIC 2021), New Delhi, India, February 25-27, 2021*, volume 2786 of *CEUR Workshop Proceedings*, pp. 331–340. CEUR-WS.org, 2021. URL http://ceur-ws.org/Vol-2786/Paper41.pdf.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *ICLR*, 2014.

Ankit Laddha, Shivam Gautam, Gregory P. Meyer, Carlos Vallespi-Gonzalez, and Carl K. Wellington. Rv-fusenet: Range view based fusion of time-series lidar data for joint 3d object detection and motion forecasting. In *IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2021, Prague, Czech Republic, September 27 - Oct. 1, 2021*, pp. 7060–7066. IEEE, 2021. doi: 10.1109/IROS51168.2021.9636083. URL https://doi.org/10.1109/IROS51168.2021.9636083.

Guozhong Li, Byron Choi, Jianliang Xu, Sourav S. Bhowmick, Daphne Ngar-yin Mah, and Grace Lai-Hung Wong. IPS: instance profile for shapelet discovery for time series classification. In *38th IEEE International Conference on Data Engineering, ICDE 2022, Kuala Lumpur, Malaysia, May 9-12, 2022*, pp. 1781–1793. IEEE, 2022. doi: 10.1109/ICDE53745.2022.00179. URL https://doi.org/10.1109/ICDE53745.2022.00179.

Shuai Liu, Guojie Song, and Wenhao Huang. Real-time transportation prediction correction using reconstruction error in deep learning. *ACM Trans. Knowl. Discov. Data*, 14(2):17:1–17:20, 2020. doi: 10.1145/3369871. URL https://doi.org/10.1145/3369871.

Yukai Liu, Rose Yu, Stephan Zheng, Eric Zhan, and Yisong Yue. Naomi: Non-autoregressive multiresolution sequence imputation. *NeurIPS*, 2019.

Linyuan Lü, Matúš Medo, Chi Ho Yeung, Yi-Cheng Zhang, Zi-Ke Zhang, and Tao Zhou. Recommender systems. *Physics reports*, 2012.

Rahul Mazumder, Trevor Hastie, and Robert Tibshirani. Spectral regularization algorithms for learning large incomplete matrices. *JMLR*, 2010.

Xiaoye Miao, Yangyang Wu, Jun Wang, Yunjun Gao, Xudong Mao, and Jianwei Yin. Generative semi-supervised learning for multivariate time series imputation. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 8983–8991. AAAI Press, 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/17086.

Elias M Stein and Rami Shakarchi. *Fourier analysis: an introduction*, volume 1. Princeton University Press, 2011.

Gábor Takács, István Pilászy, Bottyán Németh, and Domonkos Tikk. Matrix factorization and neighbor based algorithms for the netflix prize problem. In *RecSys*, 2008.

Yusuke Tashiro, Jiaming Song, Yang Song, and Stefano Ermon. Csdi: Conditional score-based diffusion models for probabilistic time series imputation. *Advances in Neural Information Processing Systems*, 34:24804–24816, 2021.

Sana Tonekaboni, Danny Eytan, and Anna Goldenberg. Unsupervised representation learning for time series with temporal neighborhood coding. In *ICLR*, 2021.

Stef Van Buuren and Karin Groothuis-Oudshoorn. mice: Multivariate imputation by chained equations in r. *Journal of statistical software*, 2011.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *CoRR*, 2017.

Gerald Woo, Chenghao Liu, Doyen Sahoo, Akshat Kumar, and Steven C. H. Hoi. Cost: Contrastive learning of disentangled seasonal-trend representations for time series forecasting. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL `https://openreview.net/forum?id=PilZY3omXV2`.

Jinsung Yoon, James Jordon, and Mihaela Schaar. Gain: Missing data imputation using generative adversarial nets. In *International conference on machine learning*, pp. 5689–5698. PMLR, 2018.

Hsiang-Fu Yu, Nikhil Rao, and Inderjit S Dhillon. Temporal regularized matrix factorization for high-dimensional time series prediction. *NIPS*, 2016.

Sebastian Zeng, Florian Graf, Christoph Hofer, and Roland Kwitt. Topological attention for time series forecasting. In *NeurIPS*, 2021.

A APPENDIX

A.1 PRELIMINARY

A.1.1 LOW-RANK MATRIX FACTORIZATION

Given a matrix $\mathbf{X} \in \mathbb{R}^{N \times T}$ with rank $k \ll \min\{N, T\}$, the low-rank matrix factorization aims to factorize $\mathbf{X}$ as the product of two low-rank matrices $\mathbf{U} \in \mathbb{R}^{N \times k}$ and $\mathbf{V} \in \mathbb{R}^{k \times T}$,

$$\mathbf{X} = \mathbf{U}\mathbf{V}. \tag{11}$$

This low-rank matrix factorization can be extended to the circumstance where the true rank of $\mathbf{X}$ is larger than k. In such a case, we use a metric ℓ to measure the discrepancy between $\mathbf{X}$ and the approximated product $\mathbf{U}\mathbf{V}$ as

$$\ell(\mathbf{X}, \mathbf{U}\mathbf{V}) = \|\mathbf{X} - \mathbf{U}\mathbf{V}\|^2, \tag{12}$$

where $\| \cdot \|$ denotes the Frobenius norm of a matrix. This low-rank approximation is fairly reasonable in practice, since many real-world structural observation matrices are low rank. This has been widely adopted and extensively studied in recommender systems (Takács et al., 2008; Chen et al., 2020). In the context of multivariate time series data, we propose to adopt low-rank matrix factorization for two reasons: 1) univariate time series channels (the rows of $\mathbf{X}$) are usually highly correlated; 2) observations at different time steps (the columns of $\mathbf{X}$) exhibit strong dependencies.

A.1.2 FOURIER SERIES

Fourier analysis(Stein & Shakarchi, 2011) states that any real-valued periodic function $f(x)$ can be represented by an infinite series of sinusoidal functions, known as the Fourier series. These sinusoidal functions have their own coefficients and distinct frequencies. More formally, the Fourier series for a function $f(x)$ with its period P can be described as

$$f(x) = \sum_{n=0}^{\infty} a_n \cos(n\omega x) + \sum_{n=0}^{\infty} b_n \sin(n\omega x), \tag{13}$$

where $\omega = 2\pi/P$, and $a_n, b_n \in \mathbb{R}$ are the corresponding coefficients. Since $\sin(n\omega x)$ and $\cos(n\omega x)$ functions are orthogonal to each other and are able to span over the entire functional space, they are also called Fourier basis.

A.2 DATASET DETAILS

- Guangzhou Traffic Data. This dataset(Chen et al., 2018) contains traffic speed of 214 anonymous urban road segments for 5 days with a 10-minute sampling rate in Guangzhou, China. It results in a 214×500 multivariate time series matrix.

Table 4: Summary of dataset statistics.

Name	Number of channels (N)	Number of time steps (T)
Guangzhou[1]	214	500
Solar-Energy[2]	137	52,560
Westminster[3]	7,489	744

- Solar-Energy Production Data. This dataset consists of solar power production records of 137 PV plants in Alabama, USA sampled every 10 minutes. It results in a $137 \times 52,560$ data matrix.
- Westminster Uber Movement Data. This dataset contains hourly averaged speed of road segments in Westminster, in Jan 2020, released by Uber. Dimension of its data matrix is $7,489 \times 744$.

The dataset statistics are summarized in Table 4.

A.3 DETAILS OF BASELINE MODELS

The details of baseline methods are briefly summarized as follows. For SimpleMean, KNN, and SoftImpute, we use their implementation provided by the package fancyimpute whereas for BRITS, GAIN, SAITS, CSDI, NAOMI and SingleRes, we use the source codes released by their authors.

- SimpleMean(Acuna & Rodriguez, 2004)[4] It imputes missing entries with mean values of corresponding columns.
- KNN(Batista et al., 2002)[5] It first finds k nearest rows with the highest similarity score to the target row, and then uses the weighted sum of these k rows for imputation.
- SoftImpute(Mazumder et al., 2010)[6]. It is a matrix completion approach based on iterative soft thresholding of Singular Value Decomposition (SVD).
- MICE(Azur et al., 2011)[7]. It is the abbreviation for Multivariate Imputation by Chained Equations, a widely-used R package for imputation.
- MF(Takács et al., 2008). It applies low-rank matrix factorization without any constraint on the latent factors.
- MF+L2(Takács et al., 2008). It applies low-rank matrix factorization with L2 regularization on $\mathbf{U}$ and $\mathbf{V}$.
- TRMF(Yu et al., 2016). It applies low-rank matrix factorization with an autoregressive constraint imposed on temporal matrix $\mathbf{V}$.
- BRITS(Cao et al., 2018)[8]. It is a time series imputation method based on Bidirectional Recurrent Neural Nets and a time decay mechanism.
- GAIN(Yoon et al., 2018)[9]. It employs Generative Adversarial Nets (GAN) for imputation.
- SAITS(Du et al., 2022)[10]. It imputes missing values based on self-attention mechanism.
- CSDI(Tashiro et al., 2021)[11]. It utilizes score-based diffusion models to explore correlations between observed values and for imputation.
- NAOMI(Liu et al., 2019)[12]. It combines Bidirectional Recurrent Neural Nets with adversarial training to offer non-autoregressive style imputation. The divide-and-conquer strategy is adopted.

---

[4] https://github.com/iskandr/fancyimpute
[5] https://github.com/iskandr/fancyimpute
[6] https://github.com/iskandr/fancyimpute
[7] https://github.com/amices/mice
[8] https://github.com/caow13/BRITS
[9] https://github.com/jsyoon0823/GAIN
[10] https://github.com/WenjieDu/SAITS
[11] https://github.com/ermongroup/CSDI
[12] https://github.com/felixykliu/NAOMI

Figure 5: Disentanglement validation on synthetic dataset. Time series are composed of the same trend but different seasonalities. (a) shows the raw time series. (b) and (d) show the trend and seasonality components TIDER has learned. (c) and (e) depict the ground trend and seasonality components which compose the raw time series.

- SingleRes(Liu et al., 2019)[13]. It is the autoregressive counterpart of NAOMI.

In our experiments, we find that BRITS with the suggested batch size and RNN hidden size will result in OOM (Out of Memory) on the Westminster dataset. Thus we reduce the batch size to 1 and the dimension of RNN to 10 such that it could just fit the 32 GB GPU on that dataset, we use an asterisk symbol to indicate its results in Table 1 and Table 2.

Furthermore, in order for reader's better understanding, we add another row named 'Improvement'(last row of each table). It is calculated as follows,

$$Improvement = \frac{best\_baseline - TIDER^\wp}{best\_baseline} \times 100\%$$
(14)

where $best\_baseline$ represents for the best performance among all the compared baseline models, $TIDER^\wp$ stands for the better one between TIDER and TIDER(no W).

A.4 Details of Metrics

Root Mean Square Error (RMSE), Mean Absolute Error (MAE), and Mean Absolute Percentage Error (MAPE) are adopted to evaluate the imputation accuracy of all compared methods. These three metrics are defined as

$$\text{RMSE} = \sqrt{\frac{\sum_{ij \in \Omega}(\mathbf{X}_{ij} - \hat{\mathbf{X}}_{ij})^2}{|\Omega|}}, \text{MAE} = \frac{\sum_{ij \in \Omega}|\mathbf{X}_{ij} - \hat{\mathbf{X}}_{ij}|}{|\Omega|}, \text{MAPE} = \sum_{ij \in \Omega}\frac{|\mathbf{X}_{ij} - \hat{\mathbf{X}}_{ij}|}{|\Omega| \cdot |\mathbf{X}_{ij}|}.$$
(15)

where $\mathbf{X}_{ij}$ denotes the ground-truth values, $\hat{\mathbf{X}}_{ij}$ is the imputed values, and Ω is the index set of missing entries to be evaluated.

---

[13]https://github.com/felixykliu/NAOMI

Figure 6: Disentanglement validation on synthetic dataset. Time series are composed of different trends but the same seasonality. (a) shows the raw time series. (b) and (d) show the trend and seasonality components TIDER has learned. (c) and (e) depict the ground trend and seasonality components which compose the raw time series.

A.5 DISENTANGLEMENT VALIDATION ON SYNTHETIC DATASET

We conducted supplementary experiments to validate TIDER's disentangling ability, where we build two sets of synthetic multivariate time-series data. The time-series instances in the first set are composed of the same trend components but different seasonality components, while those in the second set consist of different trend components but the same seasonality components. We use TIDER to capture explanatory factors of these time series and compare the disentangled components learned with ground truth components used in constructing these synthetic data. The results are depicted in Figure 5 and Figure 6. We can clearly find that the disentangled components TIDER learned are very similar to the ground-truth ones, and the disentangled representations which supposed to be close to each other actually looks similarly. This further validates TIDER's power in identifying meaningful, explainable, and realistic disentangled explanatory factors underlying time series.

A.6 HYPERPARAMETER SETTING

We implement TIDER using Python 3.6 and Pytorch 1.9, and optimize the model parameters using Adam(Kingma & Ba, 2014) with a learning rate 0.001.

The general principle and guidelines on parameter setting are as follows:

- ω: This hyperparameter is involved in the seasonality representation matrix. ω is in close relation with the time-series period P. At present, P is chosen by jointly using our prior knowledge of different time series and hyperparameter tuning techniques. We first construct a candidate list of P based on our knowledge of these time series and select the best one according to performance on validation datasets. We set P for Guangzhou, Solar-Energy, and Westminster datasets as 168, 168, and 24 respectively. In other words, the optimal ω for these datasets are $\frac{\pi}{84}$, $\frac{\pi}{84}$ and $\frac{\pi}{12}$.
- D: Dimension for matrix $\mathbf{U}$ and $\mathbf{V}_t$ is also an important hyperparameter. Small D will lack the ability to learn enough information while large D is prone to overfitting.
- λ_t, λ_b: These are the corresponding weights for the constraint functions of the trend representation matrix and bias representation matrix, respectively. We tune them by making a choice from a scale set $\{0.01, 0.1, 0.2, 0.5, 0.8\}$.

Table 5: Hyperparameters of TIDER for the three datasets.

Name ($r = 0.2$)	Guangzhou	Solar-Energy	Westminster
batch size	32	32	512
epoch	500	500	500
D	50	50	150
D_b	2	2	2
η_1	0.01	0.01	0.01
η_2	0.01	0.01	0.01
λ_t	0.1	0.01	0.01
λ_b	0.2	0.1	0.1
K	30	2	15
ω	$\frac{\pi}{84}$	$\frac{\pi}{84}$	$\frac{\pi}{12}$
Name ($r = 0.4$)	**Guangzhou**	**Solar-Energy**	**Westminster**
batch size	32	32	512
epoch	500	500	500
D	50	50	150
D_b	2	2	2
η_1	0.01	0.01	0.01
η_2	0.01	0.01	0.01
λ_t	0.1	0.01	0.01
λ_b	0.2	0.5	0.1
K	20	2	20
ω	$\frac{\pi}{84}$	$\frac{\pi}{84}$	$\frac{\pi}{12}$

(a)	(b)

Figure 7: Supplementary scalability test on Westminster dataset. (a) Memory usage between TIDER and CSDI varies over N from 0 to 5000 with fixed $T = 100$; (b) Memory usage between TIDER and BRITS varies over T from 100 to 700 with fixed $N = 100$.

By following this principle, the optimal hyperparameters we obtained are listed in Table 5.

A.7 SUPPLEMENTAL SCALABILITY ANALYSIS

In Section 5.3, there is a little gap between memory usage of CSDI and TIDER in Figure 3(a), and little gap between memory usage of BRITS and TIDER in Figure 3(b). In Figure 3-(a) (resp. Figure 3-(b)) the memory usage gap between CSDI (resp. BRITS) and TIDER is overwhelmed by the large magnitude of other methods. Thus, we zoom in to give a comparison in this section. As depicted in Figure 7, there are still large memory usage gaps between TIDER and them, which demonstrates the scalability superiority of our proposed TIDER.