GROUP EQUIVARIANT GENERATIVE ADVERSARIAL NETWORKS

ABSTRACT

Recent improvements in generative adversarial visual synthesis incorporate real and fake image transformation in a self-supervised setting, leading to increased stability and perceptual fidelity. However, these approaches typically involve image augmentations via additional regularizers in the GAN objective and thus spend valuable network capacity towards approximating transformation equivariance instead of their desired task. In this work, we explicitly incorporate inductive symmetry priors into the network architectures via group-equivariant convolutional networks. Group-convolutions have higher expressive power with fewer samples and lead to better gradient feedback between generator and discriminator. Further, group-representations are especially relevant for modalities such as medical imaging, where image labels are typically invariant under rotation/reflection. We show that group-equivariance integrates seamlessly with recent techniques for GAN training across regularizers, architectures, and loss functions. We demonstrate the utility of our methods for conditional synthesis by improving generation in the limited data regime across globally-symmetric imaging datasets and even finding benefits for natural images with preferred orientation.

1 INTRODUCTION

Generative visual modeling is an area of active research, time and again finding diverse and creative applications. A prevailing approach is the generative adversarial network (GAN), wherein density estimation is implicitly approximated by a min-max game between two neural networks (Goodfellow et al., 2014). Recent GANs are capable of high-quality natural image synthesis and scale dramatically with increases in data and compute (Brock et al., 2018). However, GANs are prone to instability due to the difficulty of achieving a local equilibrium between the two networks. Frequent failures include one or both networks diverging or the generator only capturing a few modes of the empirical distribution. Several proposed remedies include modifying training objectives (Arjovsky et al., 2017; Jolicoeur-Martineau, 2018), hierarchical methods (Karras et al., 2017), instance selection (Sinha et al., 2019; 2020), latent optimization (Wu et al., 2019), and strongly regularizing one or both networks (Gulrajani et al., 2017; Miyato et al., 2018; Dieng et al., 2019), among others. In practice, one or all of the above techniques are ultimately adapted to specific use cases.

Further, limits on data quantity empirically exacerbate training stability issues more often due to discriminator overfitting. Recent work on GANs for small sample sizes can be roughly divided into transfer learning approaches (Wang et al., 2018; Noguchi & Harada, 2019; Mo et al., 2020; Zhao et al., 2020a) or methods which transform/augment the available training data and provide the discriminator with auxiliary tasks. For example, Chen et al. (2019) propose a multi-task discriminator which additionally predicts the degree by which an input image has been rotated, whereas Zhang et al. (2020); Zhao et al. (2020c) incorporate consistency regularization where the discriminator is penalized towards similar activations for transformed/augmented real and fake images. However, with consistency regularization and augmentation, network capacity is spent learning equivariance to transformation as opposed to the desired task and equivariance is not guaranteed.

In this work, we consider the problem of training *tabula rasa* on limited data which possess global and even local symmetries. We begin by noting that GANs ubiquitously use convolutional layers which exploit the approximate translation invariance and equivariance of image labels and distributions, respectively. Equivariance to geometric transformations is key to understanding image

Figure 1: Several image modalities have no preferred orientation for tasks such as classification. We improve their generative modeling by utilizing global image symmetries within a GAN framework.

representations (Bietti & Mairal, 2019). Unfortunately, other symmetries (e.g., rotations and reflections) inherent to modalities such as astronomy and medical imaging where galaxies and cells can be in arbitrary orientations are not accounted for by standard convolutional layers. To this end, Cohen & Welling (2016) proposed a group-theoretic generalization of convolutional layers (group-convolutions) which in addition to translation, exploit other inherent symmetries and increase the expressive capacity of a network thereby increasing its sample efficiency significantly in detection (Winkels & Cohen, 2019), classification (Veeling et al., 2018), and segmentation (Chidester et al., 2019). Importantly, equivariant networks outperform standard CNNs trained with augmentations from the corresponding group (Veeling et al., 2018, Table 1), (Lafarge et al., 2020a, Fig. 7).

Group-convolutions have since been extended to other symmetries on both finite and continuous groups. See Cohen et al. (2019); Esteves (2020) for a formal treatment of equivariant CNNs. Of note, capsule networks (Hinton et al., 2011; Sabour et al., 2017) are also equivariant and preliminary work has shown that using a capsule network for the GAN discriminator (Jaiswal et al., 2019; Upadhyay & Schrater, 2018) improves synthesis on toy datasets. However, equivariant capsule GANs require complex training strategies, restricted architectural choices which may not be compatible with recent insights in GAN training, and have not yet been shown to consistently scale beyond MNIST.

In this work, we improve the generative modeling of images with transformation invariant labels by using an inductive bias of symmetry. We replace all convolutions with group-convolutions thereby admitting a higher degree of weight sharing which enables a reduction in GAN sample complexity and increased visual fidelity. To our knowledge, we are the first to introduce group equivariance to GANs and use geometric considerations in both generator and discriminator. Code will be made publicly available. Our contributions are as follows,

1. We introduce a symmetry prior via group-equivariant convolutions in the generative adversarial framework.

2. We show that recent insights in improving GAN training are fully compatible with group-equivariance with careful reformulations.

3. We improve class-conditional image synthesis across a diversity of datasets, architectures, loss functions, and regularizations. These improvements are consistent for both globally symmetric images, and even natural images with preferred orientation.

2 METHODS

2.1 PRELIMINARIES

Groups and group-convolutions. A group is a set with an endowed binary function satisfying the properties of closure, associativity, identity, and invertibility. Of relevance, a two-dimensional symmetry group is the set of all transformations under which a geometric object is invariant with an endowed operation of composition. Equivariance to a finite symmetry group can be achieved by either transforming filters (Cohen & Welling, 2016) or feature maps (Dieleman et al., 2016).

Our work utilizes the finite groups $p4$ (compositions of 90-degree rotations and translations) and $p4m$ (compositions of 90-degree rotations, reflections, and translations). We consider an image as a function f on a rectangular grid $\mathbb{Z}^2$ and a feature map as a function on a group G.

Figure 2: An abbreviated illustration of group-convolutions used in our generator networks.

In group-theoretic terms, the first layer convolving an input f with filter ψ can be written as, $[f * \psi](g) = \sum_{y \in \mathbb{Z}^2} \sum_{k=1}^{K} f_k(y) \psi_k(g^{-1}y)$, where K is the number of channels and $g^{-1}y$ is the inverse group action of element g on $y \in \mathbb{Z}^2$, i.e., $g^{-1}y = y - g$. By considering g to be a member of $p4$ or $p4m$, a group-convolution maps input feature maps on $\mathbb{Z}^2$ to output feature maps $f * \psi$ on the respective group. When both ψ and f are functions on a group G, a group-convolution can be defined as, $[f * \psi](g) = \sum_{h \in G} \sum_{k=1}^{K} f_k(h) \psi_k(g^{-1}h)$. Finally, for tasks where the output is an image, it is necessary to bring the domain of feature maps from G back to $\mathbb{Z}^2$. We can pool the feature map for each filter over the set of transformations, using either average or maximum values, corresponding to average or max pooling over the group of rotations (or roto-reflections as appropriate). A transformation from G to $\mathbb{Z}^2$ can also be learned (Linmans et al., 2018), but we did not notice an immediate benefit to doing so in early testing and hence only use group pooling.

GAN optimization and stability. As we focus on the limited data setting where training instability is exacerbated, we briefly describe the two major stabilizing methods used in all experiments here. We regularize the discriminator by using a zero-centered gradient penalty (GP) on the real data as proposed by Mescheder et al. (2018) of the form, $R_1 := \frac{\gamma}{2} \mathbb{E}_{x \sim \mathbb{P}_{real}}[\|\nabla D(x)\|_2^2]$, where γ is the regularization weight, x is sampled from the real distribution $\mathbb{P}_{real}$, and D is the discriminator. This GP has been shown to cause convergence (in toy cases), alleviate catastrophic forgetting (Thanh-Tung & Tran, 2018), and strongly stabilize GAN training. However, empirical work has found that this GP achieves stability at the cost of worsening GAN evaluation scores (Brock et al., 2018).

A widely used technique for GAN stabilization is spectral normalization (Miyato et al., 2018), which constrains the discriminator to be 1-Lipschitz, thereby improving gradient feedback to the generator (Zhou et al., 2019; Chu et al., 2020). With spectral normalization, each layer is rescaled as, $W_{SN} = W/\sigma(W)$, where W is the weight matrix for a given layer and $\sigma(W)$ is its spectral norm. In practice, $\sigma(W)$ is estimated via a power iteration method as opposed to computing the full singular value decomposition during each training iteration. Finally, applying spectral normalization to both generator and discriminator empirically improves training significantly (Zhang et al., 2018).

2.2 GROUP EQUIVARIANT GENERATIVE ADVERSARIAL NETWORKS

Here, we outline how to induce a symmetry prior into the GAN framework. The literature has developed several techniques for normalization and conditioning of the individual networks, along with unique architectural choices - we extend these developments to the equivariant setting. We start by replacing all convolutional layers with group-convolutional layers where filters and feature maps are functions on a symmetry group G. Batch normalization moments (Ioffe & Szegedy, 2015) are calculated per group-feature map as opposed to spatial feature maps. Pointwise nonlinearities preserve equivariance for the groups considered here. Pre-activation residual blocks common to modern GANs are used freely as the sum of equivariant feature maps on G is also equivariant.

Generator. The generator is illustrated at a high-level in Figure 2. We use a fully connected layer to linearly project and reshape the concatenated noise vector $z \sim \mathcal{N}(0, I)$ and class embedding

Table 1: Min. & mean Fréchet distances (lower is better) of generated RotMNIST samples, evaluated at every 1K generator iterations. A boxplot visualizing all results is given in Appendix A.

			Min. & Mean Fréchet Distance Available Training Data		
Loss	Generator	Discriminator	33%	66%	100%
NSGAN-GP	CNN	CNN	(0.68, 8.15)	(0.84, 7.70)	(0.94, 8.36)
	CNN	G-CNN	(1.07, **3.59**)	(**0.55**, **2.89**)	(**0.49**, **3.23**)
	G-CNN	CNN	(0.89, 7.47)	(0.82, 7.47)	(0.81, 7.64)
	G-CNN	G-CNN	(**0.61**, 4.94)	(0.99, 3.40)	(0.73, 3.65)
RAGAN-GP	CNN	CNN	(1.34, 11.95)	(0.95, 10.98)	(1.28, 11.68)
	CNN	G-CNN	(0.84, **3.23**)	(**0.36**, 2.84)	(**0.56**, 3.06)
	G-CNN	CNN	(1.26, 9.14)	(0.86, 8.81)	(0.98, 9.95)
	G-CNN	G-CNN	(**0.73**, 3.46)	(0.61, **2.81**)	(0.57, **2.94**)
WGAN-GP	CNN	CNN	(3.43, 18.13)	(4.28, 17.77)	(4.99, 19.43)
	CNN	G-CNN	(0.76, 4.32)	(0.57, **3.63**)	(**0.29**, 3.65)
	G-CNN	CNN	(3.16, 17.47)	(3.12, 17.82)	(2.88, 17.50)
	G-CNN	G-CNN	(**0.58**, **3.37**)	(**0.52**, 3.66)	(0.58, **3.59**)

c into spatial feature maps on $\mathbb{Z}^2$. We then use spectrally-normalized group-convolutions, interspersed with pointwise-nonlinearities, and nearest-neighbours upsampling to increase spatial extent. We use upsampling followed by group-convolutions instead of transposed group-convolutions to reduce checkerboard artefacts (Odena et al., 2016). We further use a novel group-equivariant class-conditional batch normalization layer (described below) to normalize and class-condition image generation while also projecting the latent vector z to each level of the group-convolutional hierarchy. We finally max-pool over the set of transformations to obtain the generated image $x \in \mathbb{Z}^2$.

Discriminator. The group-equivariant discriminator receives an input $x \in \mathbb{Z}^2$, which it maps to a scalar indicating whether it is real or fake. We do this via spectrally normalized group-convolutions, pointwise-nonlinearities, and spatial-pooling layers to decrease spatial extent. After the final group-convolutional layer, we pool over the group and use global average pooling to obtain an invariant representation at the output. Finally, we condition the discriminator output via the projection method proposed by Miyato & Koyama (2018).

Importantly, the equivariance of group-convolutions depends on the convolutional stride. Strided convolutions were commonly used for downsampling in early GANs (Radford et al., 2015). However, stride values must be adjusted to the dataset to preserve equivariance, which makes comparisons to equivalent non-equivariant GAN architectures difficult. We therefore use pooling layers over the plane (commonly used in recent GANs) to downsample in all settings to preserve equivariance and enable a fair comparison.

Spectral Normalization. As the singular values of a matrix are invariant under compositions of 90-degree rotations, transpositions, and reflections - spectral normalization on a group-weight matrix preserves equivariance and we use it freely.

Class-conditional Batch Normalization. Conditional batch normalization (Perez et al., 2018) replaces the scale and shift of features with an affine transformation learned from the class label (and optionally from the latent vector as well (Brock et al., 2018)) via linear dense layers, and is widely used in generative networks. We propose a group-equivariance preserving conditional normalization by learning the affine transformation parameters per group-feature map, rather than each spatial feature. As we use fewer group-filters than equivalent non-equivariant GANs, we use fewer dense parameters to learn conditional scales and shifts.

3 EXPERIMENTS

Common setups. In each subsection, we list specific experimental design choices with full details available in App. B. For each comparison, the number of group-filters in each layer is divided by

Figure 3: Qualitative GAN interpolation (White, 2016) results. **(a)** Selected spherical interpolations between generated RotMNIST samples in either latent space (**top**) or between labels (**bottom**). Equivariant GANs interpolate intuitively between samples, whereas standard GANs do not. **(b)** Selected inter-label linear interpolations between two staining dyes in synthesized ANHIR images. The standard model (**top**) changes both structure and dye between the generated samples, whereas the equivariant model (**bottom**) better preserves structure while translating between dyes.

the square root of the cardinality of the symmetry set to ensure a similar number of parameters to the standard CNNs to enable fair comparison. We skew towards stabilizing training over absolute performance to compare models under the same settings to obviate extensive checkpointing typically required for BigGAN-like models. Optimization is performed via Adam (Kingma & Ba, 2014) with $\beta_1 = 0.0$ and $\beta_2 = 0.9$, as in Zhang et al. (2018); Brock et al. (2018). Unless otherwise noted, all discriminators are updated twice per generator update and employ unequal learning rates for the generator and discriminator following Heusel et al. (2017). We use an exponential moving average ($\alpha = 0.9999$) of generator weights across iterations when sampling images as in Brock et al. (2018). All initializations use the same random seed and all models are trained on a single NVIDIA GPU. A high-level overview of the small datasets considered here is presented in App. B Table 3.

Evaluation methodologies. GANs are commonly evaluated by embedding the real and generated images into the feature space of an ImageNet pre-trained network where similarity scores are computed. The Fréchet Inception Distance (FID) (Heusel et al., 2017) jointly captures sample fidelity and diversity and is presented for all experiments. To further evaluate both aspects explicitly, we present the improved precision and recall scores (Kynkäänniemi et al., 2019) for ablations on real-world datasets. As the medical imaging datasets (ANHIR and LYSTO) are not represented in ImageNet, we finetune Inception-v3 (Szegedy et al., 2016) prior to feature extraction for FID calculation as in Huang et al. (2018). For RotMNIST, we use features derived from the final pooling layer of the $p4$-CNN defined in Cohen & Welling (2016) to replace Inception-featurization. An analogous approach was taken in Binkowski et al. (2018) in their experiments on the canonical MNIST dataset. Natural image datasets (Food-101 and CIFAR-10) are evaluated with the official `Tensorflow` Inception-v3 weights. Importantly, we perform ablation studies on all datasets to evaluate group-equivariance in either or both networks.

3.1 Synthetic Experiments: Rotated MNIST

Rotated MNIST (Larochelle et al., 2007) provides random rotations of the MNIST dataset and is a common benchmark for equivariant CNNs which we use to measure sensitivity to dataset size, loss function, and equivariance in either network to motivate choices for real-world experiments. We experiment with three different proportions of training data: 33%, 66%, and 100%. Additionally, the non-saturating loss (Goodfellow et al., 2014) (NSGAN), the Wasserstein loss (Arjovsky et al., 2017) (WGAN), and the relativistic average loss (Jolicoeur-Martineau, 2018) (RaGAN) are tested. For the equivariant setting, all convolutions are replaced with $p4$-convolutions. $p4m$ is precluded as some digits do not possess mirror symmetry. All settings were trained for 20,000 generator iterations with a batch size of 64. Implementation details are available in Appendix B.2.1.

Table 2: FID evaluation (lower is better) of all real-world datasets across ablations and augmentation-based baseline comparisons. - indicates an inapplicable setting for the method.

	Setting	ANHIR	LYSTO	CIFAR-10	Food-101
Ablation	CNN in G & D	7.32	7.27	20.89	27.34
	G-CNN in G; CNN in D	6.93	6.68	21.20	24.16
	CNN in G; G-CNN in D	5.56	5.02	**17.09**	**16.91**
	G-CNN in G & D	**5.54**	**3.90**	17.49	17.73
+ Aug.	CNN in G & D + Standard Aug.	7.57	6.59	-	-
	CNN in G & D + bCR (Zhao et al., 2020c)	5.86	4.78	19.64	21.18
	CNN in G & D + AR (Chen et al., 2019)	-	-	19.59	20.39
	G-CNN in G & D + bCR (Zhao et al., 2020c)	**5.19**	**4.53**	**17.94**	**15.55**

Results. Fréchet distance of synthesized samples to the test set is calculated at every thousand generator iterations. As shown in Table 1, we find that under every configuration of loss and data availability considered, using $p4$-convolutions in either network improves both the mean and minimum Fréchet distance. Most of the gains to be made come from using a $p4$-equivariant discriminator, with the further addition of a $p4$-equivariant generator only helping in a few cases. This may be due to RotMNIST being a relatively simple benchmark. The NSGAN-GP and RAGAN-GP losses perform similarly, with WGAN-GP underperforming initially and ultimately achieving comparable results. Qualitatively, the equivariant model learns better representations as shown in Figure 3(a). Holding the class-label constant and interpolating between samples, we find that the standard GAN changes the shape of the digit in order to rotate it, whereas the equivariant model learns rotation in the latent space. Holding the latent constant and interpolating between classes shows that our model learns an intuitive interpolation between digits, whereas the standard GAN transforms the image immediately.

3.2 REAL-WORLD EXPERIMENTS

Datasets. $p4$ and $p4m$-equivariant networks are most useful when datasets possess global roto(-reflective) symmetry, yet have also been shown to benefit generic image representation due to local symmetries (Cohen & Welling, 2016; Romero et al., 2020). To this end, we experiment with two types of real-world datasets as detailed in Table 3 in App. B.1: (1) sets with roto(-reflective) symmetry, such that the image label is invariant under transformation; (2) natural images with preferred orientation (e.g., the boat class of images in CIFAR-10 cannot be upside-down). Briefly, they are:

ANHIR provides high-resolution pathology slides stained with 5 different dyes to highlight different cellular properties (Borovec et al., 2020; 2018). We extract 128×128 foreground patches from images of different scales, as described in App. B.1.2. We use the staining dye as conditioning.

LYSTO is a multi-organ pathology benchmark for the counting of immunohistochemistry stained lymphocytes (Ciompi et al., 2019). We re-purpose it here for conditional synthesis at a higher resolution of 256×256. As classification labels are not provided, we use the organ source as class labels. The use of organ sources as classes is validated in App. B.1.1. The high image resolution in addition to the limited sample size of 20,000 make LYSTO a challenging dataset for GANs.

CIFAR-10 is a natural image vision benchmark of both small resolution and sample size (Krizhevsky et al., 2009). Previous work (Weiler & Cesa, 2019; Romero et al., 2020) finds that equivariant-networks improve classification accuracy on CIFAR-10 and we include here it as a GAN benchmark.

Food-101 is a small natural image dataset of a 101 categories of food taken in various challenging settings of over/under exposure, label noise, etc. (Bossard et al., 2014). Further, datasets with a high number of classes are known to be challenging for GANs (Odena, 2019). Importantly, even though the objects in this dataset have a preferred pose due to common camera orientations, we speculate that roto-equivariance may be beneficial here as food photography commonly takes an *en face* or mildly oblique view. We resize the training set to 64×64 resolution for our experiments.

Baseline architecture. To produce a strong non-equivariant baseline, we face several design choices. State-of-the-art GANs follow either BigGAN (Brock et al., 2018) or StyleGAN2 (Karras et al., 2020b) in design. As StyleGAN2 has not yet been demonstrated to scale to *conditional* generation with a large number of classes (to our knowledge), we follow a BigGAN-like construction

Figure 4: Selected generated samples using the best performing equivariant models with no augmentation. Random samples are available in App. A. Layout inspired by Karras et al. (2020a).

Figure 5: Improved Precision and Recall (Kynkäänniemi et al., 2019) analysis of ablations for all snapshots of trained models in each setting (closer to top-right is better).

despite the stability of StyleGAN2. For our small datasets, we make the following modifications: (1) we use fewer channels; (2) we do not use orthogonal regularization; (3) we do not use hierarchical latent projection as we find in early testing that projecting the entire latent to each normalization layer achieves similar results; (4) we do not use attention as equivariant attention is an area of active research (Romero & Hoogendoorn, 2019; Romero et al., 2020) but currently has prohibitively high memory requirements and may not yet scale to GANs. Further details are available in App. B.2.

We then modify either generator (G) and/or discriminator (D) as in Section 2.2 to obtain the corresponding equivariant settings. We note that a discriminator invariant to roto-reflections would assign the same amount of realism to an upright natural image versus a rotated/reflected copy of the same image, allowing the generator to synthesize images at arbitrary orientations. Therefore, for CIFAR-10 and Food-101 we pool over rotations *before* the last residual block to enable the discriminator to detect when generated images are not in their canonical pose while maintaining most of the benefits of equivariance as studied in Weiler & Cesa (2019). We use $p4m$-equivariance for ANHIR and LYSTO and $p4$-equivariance for CIFAR-10 and Food-101 to reduce training time.

Comparisons. A natural comparison would be against standard GANs using augmentations drawn from the same group our model is equivariant to. However, augmentation on the real images alone would lead to the augmentations "leaking" into the generated images, e.g., vertical flip augmentation may lead to generated images being upside-down. Zhao et al. (2020c) propose balanced consistency regularization (bCR) for augmentations of both real and generated samples to alleviate this issue, and we thus use it as a comparison. We restrict the augmentations used in bCR to 90-degree rotations or 90-degree rotations and reflections as appropriate to enable a fair comparison against equivariant GANs. Using additional augmentations would help all methods across the board. We further compare against auxiliary rotations (AR) GAN (Chen et al., 2019) where real and fake images are

augmented with 90-degree rotations and the discriminator is tasked with predicting their orientation. We do not use AR for ANHIR and LYSTO as they have no canonical orientation. We also evaluate standard augmentation (reals only) for datasets where augmentation "leakage" is acceptable.

Results. Quantitative FID results of ablations and comparisons against baselines are presented in Table 2. Equivariant networks (G-CNN) outperform methods which use standard CNNs with or without augmentation across all datasets. For ANHIR and LYSTO, we find that $p4m$-equivariance in either network improves FID evaluation, with the best results coming from modifying both networks. However, for the upright datasets CIFAR-10 and Food-101 we find that having a $p4$-equivariant discriminator alone helps more than having both networks be $p4$-equivariant. When augmentation is used, we find that the standard CNNs improve significantly in performance, but are still outperformed by equivariant nets with no augmentation. We include a mixture of equivariant GANs and bCR for completeness and find that for ANHIR and Food-101, they have an additive effect, whereas they do not for LYSTO and CIFAR-10, indicating a dataset-sensitivity. Of note, we found that bCR with its suggested hyperparameters lead to immediate training collapse on ANHIR, LYSTO, and CIFAR-10, which was fixed by decreasing the strength of the regularization substantially. This may be due to the original work using several different types of augmentation and not just roto-reflections.

Qualitatively, as class differences in ANHIR should be stain (color) based, we visualize inter-class interpolations between synthesized samples in Figure 3(b). We find that our model better preserves structure while translating between stains, whereas the non-equivariant GAN struggles to do so. In our ablation study in terms of precision and recall in Figure 5, using $p4m$-equivariance in `G` and `D` achieves consistently higher recall for ANHIR and LYSTO. For Food-101, we find that `G-CNN in G and D` achieves higher precision, whereas `CNN in G and G-CNN in D` achieves higher recall. For CIFAR-10 precision and recall, we find no discernable differences between the two settings with lowest FID. Interestingly, for CIFAR-10 adding $p4$-equivariance to `G` but not `D` worsens FID but noticeably improves precision. These observations are consistent with our FID findings as FID tends to correlate better with recall (Karras et al., 2020a).

4 DISCUSSION

Future work. We present improved conditional image synthesis using equivariant networks, opening several potential future research directions: (1) As efficient implementations of equivariant attention develop, we will incorporate them to model long-range dependency; (2) StyleGAN2 uses antialiasing filtering (Zhang, 2019) to improve baseline translation equivariance, which may be integrated here as bilinear operations are rotation equivariant; (3) Equivariance to continuous groups may yield further increased data efficiency and more powerful representations. However, doing so may require non-trivial modifications to current GAN architectures as memory limitations could bottleneck continuous group-equivariant GANs at relevant image sizes. Further, adding more discretizations beyond 4 rotations on a continuous group such has $SE(2)$ may show diminishing returns (Lafarge et al., 2020a, Fig.7); (4) In parallel to our work, Karras et al. (2020a) propose a differentiable augmentation scheme for limited data GANs pertaining to *which* transformations to apply and learning the frequency of augmentation for generic images, with similar work presented in Zhao et al. (2020b). Our approach is fully complementary to these methods when employing transformations outside the considered group and will be integrated into future work; (5) Contemporaneously, Lafarge et al. (2020b) propose equivariant variational autoencoders allowing for control over generated orientations via structured latent spaces which may be used for equivariant GANs as well.

Conclusion. In this paper, we present a flexible framework for incorporating symmetry priors within GANs. In doing so, we improve the visual fidelity and sample complexity of GANs when trained on globally-symmetric images and even extending to natural images. Our experiments confirm this by improving on conventional GANs across a variety of datasets, ranging from medical imaging modalities to real-world images of food. Modifying either generator or discriminator generally leads to improvements in synthesis, with the latter typically having more impact. To our knowledge, our work is the first to show clear benefits of equivariant learning over standard GAN training on high-resolution conditional image generation beyond toy datasets. While this work is empirical, we believe that it strongly motivates future theoretical analysis of the interplay between GANs and equivariance. Finally, improved results over augmentation-based strategies are presented, demonstrating the benefits of explicit transformation equivariance over equivariance-approximating regularizations.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Alberto Bietti and Julien Mairal. Group invariance, stability to deformations, and complexity of deep convolutional representations. *The Journal of Machine Learning Research*, 20(1):876–924, 2019.

Mikolaj Binkowski, Dougal J. Sutherland, Michael Arbel, and Arthur Gretton. Demystifying MMD GANs. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018.

Jiří Borovec, Arrate Munoz-Barrutia, and Jan Kybic. Benchmarking of image registration methods for differently stained histological slides. In *2018 25th IEEE International Conference on Image Processing (ICIP)*, pp. 3368–3372. IEEE, 2018.

Jiří Borovec, Jan Kybic, Ignacio Arganda-Carreras, Dmitry V Sorokin, Gloria Bueno, Alexander V Khvostikov, Spyridon Bakas, I Eric, Chao Chang, Stefan Heldmann, et al. Anhir: automatic non-rigid histological image registration challenge. *IEEE Transactions on Medical Imaging*, 2020.

Lukas Bossard, Matthieu Guillaumin, and Luc Van Gool. Food-101 – mining discriminative components with random forests. In *European Conference on Computer Vision*, 2014.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Ting Chen, Xiaohua Zhai, Marvin Ritter, Mario Lucic, and Neil Houlsby. Self-supervised gans via auxiliary rotation loss. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 12154–12163, 2019.

Benjamin Chidester, That-Vinh Ton, Minh-Triet Tran, Jian Ma, and Minh N Do. Enhanced rotation-equivariant u-net for nuclear segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 0–0, 2019.

Casey Chu, Kentaro Minami, and Kenji Fukumizu. Smoothness and stability in gans. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=HJeOekHKwr.

Francesco Ciompi, Yiping Jiao, and Jeroen van der Laak. Lymphocyte assessment hackathon (lysto), October 2019. URL https://doi.org/10.5281/zenodo.3513571.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pp. 2990–2999, 2016.

Taco S Cohen, Mario Geiger, and Maurice Weiler. A general theory of equivariant cnns on homogeneous spaces. In *Advances in Neural Information Processing Systems*, pp. 9142–9153, 2019.

Sander Dieleman, Jeffrey De Fauw, and Koray Kavukcuoglu. Exploiting cyclic symmetry in convolutional neural networks. *arXiv preprint arXiv:1602.02660*, 2016.

Adji B Dieng, Francisco JR Ruiz, David M Blei, and Michalis K Titsias. Prescribed generative adversarial networks. *arXiv preprint arXiv:1910.04302*, 2019.

Carlos Esteves. Theoretical aspects of group equivariant neural networks. *arXiv preprint arXiv:2004.05154*, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pp. 5767–5777, 2017.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, pp. 6626–6637, 2017.

Geoffrey E Hinton, Alex Krizhevsky, and Sida D Wang. Transforming auto-encoders. In *International Conference on Artificial Neural Networks*, pp. 44–51. Springer, 2011.

Xun Huang, Ming-Yu Liu, Serge Belongie, and Jan Kautz. Multimodal unsupervised image-to-image translation. In *European Conference on Computer Vision*, pp. 179–196. Springer, 2018.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Ayush Jaiswal, Wael AbdAlmageed, Yue Wu, and Premkumar Natarajan. Capsulegan: Generative adversarial capsule network. In Laura Leal-Taixé and Stefan Roth (eds.), *Computer Vision – ECCV 2018 Workshops*, Cham, 2019. Springer International Publishing.

Alexia Jolicoeur-Martineau. The relativistic discriminator: a key element missing from standard gan. *arXiv preprint arXiv:1807.00734*, 2018.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Training generative adversarial networks with limited data, 2020a.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020b.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Tuomas Kynkäänniemi, Tero Karras, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Improved precision and recall metric for assessing generative models. In *Advances in Neural Information Processing Systems*, pp. 3929–3938, 2019.

Maxime W. Lafarge, Erik J. Bekkers, Josien P. W. Pluim, Remco Duits, and Mitko Veta. Roto-translation equivariant convolutional networks: Application to histopathology image analysis, 2020a.

Maxime W. Lafarge, Josien P. W. Pluim, and Mitko Veta. Orientation-disentangled unsupervised representation learning for computational pathology, 2020b.

Hugo Larochelle, Dumitru Erhan, Aaron Courville, James Bergstra, and Yoshua Bengio. An empirical evaluation of deep architectures on problems with many factors of variation. In *Proceedings of the 24th international conference on Machine learning*, pp. 473–480. ACM, 2007.

Jae Hyun Lim and Jong Chul Ye. Geometric gan. *arXiv preprint arXiv:1705.02894*, 2017.

Jasper Linmans, Jim Winkens, Bastiaan S Veeling, Taco S Cohen, and Max Welling. Sample efficient semantic segmentation using rotation equivariant convolutional networks. *arXiv preprint arXiv:1807.00583*, 2018.

Lars Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for gans do actually converge? *arXiv preprint arXiv:1801.04406*, 2018.

Takeru Miyato and Masanori Koyama. cgans with projection discriminator. *arXiv preprint arXiv:1802.05637*, 2018.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

Sangwoo Mo, Minsu Cho, and Jinwoo Shin. Freeze the discriminator: a simple baseline for fine-tuning gans, 2020.

Atsuhiro Noguchi and Tatsuya Harada. Image generation from small datasets via batch statistics adaptation. *arXiv preprint arXiv:1904.01774*, 2019.

Augustus Odena. Open questions about generative adversarial networks. *Distill*, 2019. doi: 10.23915/distill.00018. https://distill.pub/2019/gan-open-problems.

Augustus Odena, Vincent Dumoulin, and Chris Olah. Deconvolution and checkerboard artifacts. *Distill*, 1(10):e3, 2016.

Ethan Perez, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. Film: Visual reasoning with a general conditioning layer. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

David W Romero and Mark Hoogendoorn. Co-attentive equivariant neural networks: Focusing equivariance on transformations co-occurring in data. *arXiv preprint arXiv:1911.07849*, 2019.

David W. Romero, Erik J. Bekkers, Jakub M. Tomczak, and Mark Hoogendoorn. Attentive group equivariant convolutional networks, 2020.

Sara Sabour, Nicholas Frosst, and Geoffrey E Hinton. Dynamic routing between capsules. In *Advances in neural information processing systems*, pp. 3856–3866, 2017.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Samarth Sinha, Han Zhang, Anirudh Goyal, Yoshua Bengio, Hugo Larochelle, and Augustus Odena. Small-gan: Speeding up gan training using core-sets. *arXiv preprint arXiv:1910.13540*, 2019.

Samarth Sinha, Anirudh Goyal, Colin Raffel, and Augustus Odena. Top-k training of gans: Improving generators by making critics less critical. *arXiv preprint arXiv:2002.06224*, 2020.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Hoang Thanh-Tung and Truyen Tran. On catastrophic forgetting in generative adversarial networks. *arXiv preprint arXiv:1807.04015*, 2018.

Dustin Tran, Rajesh Ranganath, and David Blei. Hierarchical implicit models and likelihood-free variational inference. In *Advances in Neural Information Processing Systems*, pp. 5523–5533, 2017.

Yash Upadhyay and Paul Schrater. Generative adversarial network architectures for image synthesis using capsule networks. *arXiv preprint arXiv:1806.03796*, 2018.

Bastiaan S Veeling, Jasper Linmans, Jim Winkens, Taco Cohen, and Max Welling. Rotation equivariant cnns for digital pathology. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 210–218. Springer, 2018.

Yaxing Wang, Chenshen Wu, Luis Herranz, Joost van de Weijer, Abel Gonzalez-Garcia, and Bogdan Raducanu. Transferring gans: generating images from limited data. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 218–234, 2018.

Maurice Weiler and Gabriele Cesa. General e (2)-equivariant steerable cnns. In *Advances in Neural Information Processing Systems*, pp. 14334–14345, 2019.

Tom White. Sampling generative networks. *arXiv preprint arXiv:1609.04468*, 2016.

Marysia Winkels and Taco S Cohen. Pulmonary nodule detection in ct scans with equivariant cnns. *Medical image analysis*, 55:15–26, 2019.

Yan Wu, Jeff Donahue, David Balduzzi, Karen Simonyan, and Timothy Lillicrap. Logan: Latent optimisation for generative adversarial networks. *arXiv preprint arXiv:1912.00953*, 2019.

Han Zhang, Ian Goodfellow, Dimitris Metaxas, and Augustus Odena. Self-attention generative adversarial networks. *arXiv preprint arXiv:1805.08318*, 2018.

Han Zhang, Zizhao Zhang, Augustus Odena, and Honglak Lee. Consistency regularization for generative adversarial networks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=S1lxKlSKPH.

Richard Zhang. Making convolutional networks shift-invariant again. In *International Conference on Machine Learning*, pp. 7324–7334, 2019.

Miaoyun Zhao, Yulai Cong, and Lawrence Carin. On leveraging pretrained gans for limited-data generation. *arXiv preprint arXiv:2002.11810*, 2020a.

Shengyu Zhao, Zhijian Liu, Ji Lin, Jun-Yan Zhu, and Song Han. Differentiable augmentation for data-efficient gan training, 2020b.

Zhengli Zhao, Sameer Singh, Honglak Lee, Zizhao Zhang, Augustus Odena, and Han Zhang. Improved consistency regularization for gans, 2020c.

Zhiming Zhou, Jiadong Liang, Yuxuan Song, Lantao Yu, Hongwei Wang, Weinan Zhang, Yong Yu, and Zhihua Zhang. Lipschitz generative adversarial nets. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 7584–7593, 2019.

A   SUPPLEMENTARY RESULTS

Figure 6: A comparison of all GAN settings on Rotated MNIST. Each dot represents the Fréchet distance to the test set, which is evaluated every 1,000 generator iterations, for 20,000 iterations total. The top and bottom boxplots use a standard and group-equivariant CNN in the generator, respectively. In all settings, using a G-CNN in the discriminator lowers both mean and inter-quartile ranges for the Fréchet distance.

Figure 7: Random 64×64 Food-101 samples from arbitrarily chosen classes with no truncation taken from the best performing model snapshot with $p4$-equivariance (without augmentation) in the discriminator.

Figure 8: Random 128×128 ANHIR samples with no truncation taken from the best performing model snapshot with $p4m$-equivariance in both generator and discriminator (without augmentation). Selected real samples are shown in the left column for reference.

Figure 9: Random 256×256 LYSTO samples with no truncation taken from the best performing model snapshot with $p4m$-equivariance in both generator and discriminator (without augmentation). Selected real samples are shown in the left column for reference.

(a) RotMNIST   (b) CIFAR-10

Figure 10: Random samples for RotMNIST (28×28) and CIFAR-10 (32×32) sampled with $\sigma = 0.75$ truncation trained without augmentation.

Table 3: A summary of the datasets considered in this paper. The right-most column indicates whether the dataset has a preferred pose.

Dataset	Resolution	n_{classes}	n_{training}	n_{testing}	Pose Preference
Rotated MNIST	(28, 28)	10	12,000	50,000	No
ANHIR	(128, 128, 3)	5	28,407	9,469	No
LYSTO	(256, 256, 3)	3	20,000	-	No
CIFAR-10	(32, 32, 3)	10	50,000	10,000	Yes
Food-101	(64, 64, 3)	101	75,747	25,250	Yes

B   EXPERIMENTAL DETAILS

B.1   DATA PREPARATION

B.1.1   LYSTO CLASS CONDITIONING

To validate the assumption of the organ source being a discriminative feature, a suitable test would be to train a classifier to distinguish between sources. We partition the original training set with a 60/40 train/test split. The original testing set is not used as it has no publicly available organ source information. The dataset has 3 classes - colon, breast, and prostate. Holding out 20% of the new constructed training set for validation, we fine-tune ImageNet-pretrained VGG16 (Simonyan & Zisserman, 2014) and achieve 98% organ classification test accuracy, thus validating our assumption.

B.1.2   ANHIR PATCH EXTRACTION

To extract patches for image synthesis, we choose the `lung-lesion` images from the larger AN-HIR dataset, as these images are provided at different scales and possess diverse staining. The images were cropped to the nearest multiples of 128, and 128×128 patches were then extracted. Foreground/background masking was performed via K-means clustering, followed by morphological dilation. The images were then gridded into 128×128 patches, i.e., there was no overlap between patches. If a patch contained less than 10% foreground pixels, it was excluded from consideration.

B.2 ADDITIONAL IMPLEMENTATION DETAILS

The following subsections list dataset-specific training strategies. Unless noted, all layers use orthogonal initializations. Batch normalization momentum is set to 0.1, and LeakyReLU slopes are set to 0.2 (if used). Spectral normalization is used everywhere except for the dense layer which learns the class embedding as specified in the BigGAN `PyTorch` GitHub repository[1].

For ANHIR, LYSTO, and Food-101 we use the relativistic average adversarial loss (Jolicoeur-Martineau, 2018) for its stability and for CIFAR-10 we use the Hinge loss (Lim & Ye, 2017; Tran et al., 2017) to remain consistent with the literature for that dataset. For our implementation of auxiliary rotations GAN (Chen et al., 2019), we use the suggested regularization weights. For balanced consistency regularization (bCR) (Zhao et al., 2020c), we find that dataset-specific tuning of the regularization strength was required.

B.2.1 RotMNIST

Given the low resolution of Rotated MNIST, we take a straightforward approach to synthesis without residual connections. In the generator, we sample from a $64D$ Gaussian latent space, concatenate class embeddings, and linearly project as described in Section 2.2. Four spectrally-normalized convolutional layers are then used with class-conditional batch normalization employed after every convolution except for the first and last layer. The discriminator uses three spectrally normalized convolutional layers, with leaky ReLU non-linearities. Average pooling is used to reduce the spatial extent of the feature maps, with global average pooling and conditional projection used at the end of the sequence. For NSGAN and RaGAN, we use the R_1 GP, conservatively setting $\gamma = 0.1$. For WGAN, we use the GP defined in Gulrajani et al. (2017) to ensure the 1-Lipschitz constraint with the recommended weight of 10.0. Learning rates were set to $\eta_G = 0.0001$ and $\eta_D = 0.0004$, respectively. For the $p4$-equivariant models, max-pooling over rotations is used after the last group-convolutional layer in both generator and discriminator to get $\mathbb{Z}^2$ feature maps. Architectures are presented in Tables 4 and 5.

B.2.2 ANHIR

We sample from a $128D$ Gaussian latent space with a batch size of 32. The generator consists of 6 pre-activation residual blocks followed by a final convolutional layer to obtain a 3-channel output. We use class-conditional batch normalization after every convolution, except at the final layer. The discriminator uses 5 pre-activation residual blocks, followed by global average pooling and conditional projection. In the equivariant settings, we use residual blocks with $p4m$-convolutions for roto-reflective symmetries. We train with the relativisitic average loss and use the R_1 GP with $\gamma = 0.1$. Learning rates are set to $\eta_G = 0.0001$ and $\eta_D = 0.0004$. All models were trained for approximately 60,000 generator iterations. bCR weights for comparison were set to $\lambda_{real} = 0.1$ and $\lambda_{fake} = 0.05$ for roto-reflective augmentations, with higher values collapsing training. Architectures are presented in Tables 6 and 7.

B.2.3 LYSTO

Implementation for LYSTO is similar to that of App. B.2.2, with some key differences due to the greater difficulty of training. Due to memory constraints, we use a batch size of 16. We increase the number of residual blocks to 6 in both generator and discriminator and halve the number of filters. The equivariant settings used the $p4m$ roto-reflective symmetries. We initially experienced low sample diversity across a variety of hyperparameter settings. Contrary to recent literature, we find that using batch normalization in the discriminator in addition to spectral normalization greatly improves training for this dataset. Further, halving the learning rates for both networks to $\eta_G = 0.00005$ and $\eta_D = 0.0002$ and increasing the strength of the gradient penalty to 1.0 were necessary for ensuring training stability. As in App. B.2.2, all models were trained for approximately 60,000 generator iterations and bCR weights were set to $\lambda_{real} = 0.1$ and $\lambda_{fake} = 0.05$ for roto-reflective augmentations. As test set labels are not publicly available for LYSTO, we evaluate FID, Precision, and Recall to the training set itself as done in a subset of experiments within Jolicoeur-Martineau (2018) and Zhao et al. (2020b). Architectures are presented in Tables 8 and 9.

---

[1]https://github.com/ajbrock/BigGAN-PyTorch

B.2.4 CIFAR-10

For CIFAR-10, we make the following changes to our training parameters to be in accordance with prior art for BigGAN-like designs for this dataset: (1) layer weights are now initialized from $\mathcal{N}(0, 0.02)$; (2) average pooling is used in the discriminator instead of max pooling; (3) learning rates η_G and η_D are now equal and set to 0.0002; (4) the discriminator is updated four times per generator update; (5) architectures are modified as in Tables 10 and 11; (6) we use the Hinge loss instead of the relativistic average loss. We use a batch size of 64. Karras et al. (2020a) suggest an R_1 GP weight of $\gamma = 0.01$ for CIFAR-10 which we use here. We train all CIFAR-10 GANs for 100K generator iterations. bCR weights were set to $\lambda_{real} = 0.1$ and $\lambda_{fake} = 0.1$ for 90-degree rotation augmentations.

For the $p4$-equivariant discriminators, we move the pooling over the group to before the last residual block as stated in the main text. Alternatively, we experimented with using a single additional standard convolutional layer with 32 filters after the $p4$-residual blocks as a lightweight alternative to making an entire residual block non-equivariant but this worsened FID evaluation. Interestingly, we find that substituting Global Average Pooling for Global Sum Pooling in the CIFAR-10 discriminators lead to an improvement of $\sim$5 - 8 in terms of FID across the board. This architectural change to the ResNet-based GANs from Gulrajani et al. (2017) was originally made in Miyato et al. (2018), but to our knowledge has not been noted in the literature previously.

B.2.5 FOOD-101

Compared to the residual synthesis models in App. B.2.2 and B.2.3, we make several changes. We sample from a $64D$ latent Gaussian to lower the number of dense parameters and substantially increase the width of the residual blocks to account for the high number of image classes. We find that an $8\times$ increase in the number of channels for the initial projection from the latent vector and class embedding improves training significantly. We use 4 residual blocks each in both generator and discriminator. For the equivariant setting, we use only $p4$ rotational symmetries to reduce training time. Importantly, we increase the batch size to 64 and the R_1 GP to $\gamma = 1.0$, both of which improve the evaluation of all experimental settings. We train all GANs for $\sim$45K generator iterations. The suggested bCR weights of $\lambda_{real} = 10.0$ and $\lambda_{fake} = 10.0$ from Zhao et al. (2020c) were used here for 90-degree rotation augmentations. However, when bCR with default parameters was combined with $p4$-equivariance in G and D, augmentations start to 'leak' into the generated images (e.g., G generating upside-down plates), necessitating lower weights of $\lambda_{real} = 0.5$ and $\lambda_{fake} = 0.5$.

B.3 ARCHITECTURES

Architectures for the Rotated MNIST experiments are given in Tables 4 and 5, ANHIR in Tables 6 and 7, and LYSTO in Tables 8 and 9. The residual blocks used in the ANHIR, LYSTO, CIFAR-10, and Food-101 experiments are given in Figure 11. SN refers to spectral normalization and $(z2 - p4), (p4 - p4), (z2 - p4m), (p4m - p4m)$ refer to the type of convolution used.

Figure 11: Residual blocks in the group-equivariant settings used in RGB image generation architectures. The choice of $p4$ or $p4m$ is dataset-specific. The generator uses ResBlockG (left) and the discriminator uses ResBlockD (right). The first residual block in the convolutional sequence in either network uses $z2$-$p4m$ group-convolutions for the initial layer. The non-equivariant settings replace all group-convolutions and normalizations within the residual blocks with standard techniques. Visual design inspired by Brock et al. (2018).

Generator
Sample $z \in \mathbb{R}^{64} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 9\}$ into $\hat{y} \in \mathbb{R}^{64}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{128}$
Project and reshape h to $7 \times 7 \times 128$
3×3 ConvSN, $128 \rightarrow 512$
ReLU; Up $2\times$
3×3 ConvSN, $512 \rightarrow 256$
CCBN$(\cdot, h)$; ReLU; Up $2\times$
3×3 ConvSN, $256 \rightarrow 128$
CCBN$(\cdot, h)$; ReLU
3×3 ConvSN, $128 \rightarrow 1$
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{28 \times 28 \times 1}$
3×3 ConvSN, $1 \rightarrow 128$
LeakyReLU, Avg. Pool
3×3 ConvSN, $128 \rightarrow 256$
LeakyReLU, Avg. Pool
3×3 ConvSN, $256 \rightarrow 512$
LeakyReLU, Avg. Pool
Global Average Pool into f
Embed $y \in \{0, ..., 9\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 4: Architectures used for the standard generator and discriminator in the Rotated MNIST experiments.

Generator
Sample $z \in \mathbb{R}^{64} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 9\}$ into $\hat{y} \in \mathbb{R}^{64}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{128}$
Project and reshape h to $7 \times 7 \times 128$
$3 \times 3\ z2 - p4$ GConvSN, $128 \to 256$
ReLU; Up $2\times$
$3 \times 3\ p4 - p4$ GConvSN, $256 \to 128$
CCBN$(\cdot, h)$; ReLU; Up $2\times$
$3 \times 3\ p4 - p4$ GConvSN, $128 \to 64$
CCBN$(\cdot, h)$; ReLU
$3 \times 3\ p4 - p4$ GConvSN, $64 \to 1$
$p4$-Max Pool
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{28 \times 28 \times 1}$
$3 \times 3\ z2 - p4$ GConvSN, $1 \to 64$
LeakyReLU, Avg. Pool
$3 \times 3\ p4 - p4$ GConvSN, $64 \to 128$
LeakyReLU, Avg. Pool
$3 \times 3\ p4 - p4$ GConvSN, $128 \to 256$
LeakyReLU, Avg. Pool
$p4$-Max Pool
Global Average Pool into f
Embed $y \in \{0, ..., 9\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 5: Architectures used for the $p4$-equivariant generator and discriminator in the Rotated MNIST experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 4\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 128$
$z2 - z2$ ResBlockG, $128 \to 512$
$z2 - z2$ ResBlockG, $512 \to 256$
$z2 - z2$ ResBlockG, $256 \to 128$
$z2 - z2$ ResBlockG, $128 \to 64$
$z2 - z2$ ResBlockG, $64 \to 32$
BN; ReLU
3×3 ConvSN, $32 \to 3$
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{128 \times 128 \times 3}$
$z2 - z2$ ResBlockD, $3 \to 32$
$z2 - z2$ ResBlockD, $32 \to 64$
$z2 - z2$ ResBlockD, $64 \to 128$
$z2 - z2$ ResBlockD, $128 \to 256$
$z2 - z2$ ResBlockD, $256 \to 512$
ReLU
Global Average Pool into f
Embed $y \in \{0, ..., 4\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 6: Architectures used for the standard generator and discriminator in the ANHIR experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 4\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 128$
$z2 - p4m$ ResBlockG, $128 \to 181$
$p4m - p4m$ ResBlockG, $181 \to 90$
$p4m - p4m$ ResBlockG, $90 \to 45$
$p4m - p4m$ ResBlockG, $45 \to 22$
$p4m - p4m$ ResBlockG, $22 \to 11$
$p4m$-BN; ReLU
$3 \times 3\ p4m - p4m$ GConvSN, $11 \to 3$
$p4m$-Max Pool
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{128 \times 128 \times 3}$
$z2 - p4m$ ResBlockD, $3 \to 11$
$p4m - p4m$ ResBlockD, $11 \to 22$
$p4m - p4m$ ResBlockD, $22 \to 45$
$p4m - p4m$ ResBlockD, $45 \to 90$
$p4m - p4m$ ResBlockD, $90 \to 181$
ReLU
$p4m$-Max Pool
Global Average Pool into f
Embed $y \in \{0, ..., 4\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 7: Architectures used for the $p4m$-equivariant generator and discriminator in the ANHIR experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, 1, 2\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 128$
$z2 - z2$ ResBlockG, $128 \to 512$
$z2 - z2$ ResBlockG, $512 \to 256$
$z2 - z2$ ResBlockG, $256 \to 128$
$z2 - z2$ ResBlockG, $128 \to 64$
$z2 - z2$ ResBlockG, $64 \to 32$
$z2 - z2$ ResBlockG, $32 \to 16$
BN; ReLU
3×3 ConvSN, $16 \to 3$
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{256 \times 256 \times 3}$
$z2 - z2$ ResBlockD-BN, $3 \to 16$
$z2 - z2$ ResBlockD-BN, $16 \to 32$
$z2 - z2$ ResBlockD-BN, $32 \to 64$
$z2 - z2$ ResBlockD-BN, $64 \to 128$
$z2 - z2$ ResBlockD-BN, $128 \to 256$
$z2 - z2$ ResBlockD-BN, $256 \to 512$
ReLU
Global Average Pool into f
Embed $y \in \{0, 1, 2\}$ into $\hat{y}'$
Projection step($\hat{y}', f$)

Table 8: Architectures used for the standard generator and discriminator in the LYSTO experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, 1, 2\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 128$
$z2 - p4m$ ResBlockG, $128 \to 181$
$p4m - p4m$ ResBlockG, $181 \to 90$
$p4m - p4m$ ResBlockG, $90 \to 45$
$p4m - p4m$ ResBlockG, $45 \to 22$
$p4m - p4m$ ResBlockG, $22 \to 11$
$p4m - p4m$ ResBlockG, $11 \to 5$
$p4m$-BN; ReLU
3×3 $p4m - p4m$ GConvSN, $5 \to 3$
$p4m$-Max Pool
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{256 \times 256 \times 3}$
$z2 - p4m$ ResBlockD-BN, $3 \to 5$
$p4m - p4m$ ResBlockD-BN, $5 \to 11$
$p4m - p4m$ ResBlockD-BN, $11 \to 22$
$p4m - p4m$ ResBlockD-BN, $22 \to 45$
$p4m - p4m$ ResBlockD-BN, $45 \to 90$
$p4m - p4m$ ResBlockD-BN, $90 \to 181$
ReLU
$p4m$-Max Pool
Global Average Pool into f
Embed $y \in \{0, 1, 2\}$ into $\hat{y}'$
Projection step($\hat{y}', f$)

Table 9: Architectures used for the $p4m$-equivariant generator and discriminator in the LYSTO experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 9\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 256$
$z2 - z2$ ResBlockG, $256 \to 256$
$z2 - z2$ ResBlockG, $256 \to 256$
$z2 - z2$ ResBlockG, $256 \to 256$
BN; ReLU
3×3 ConvSN, $256 \to 3$
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{32 \times 32 \times 3}$
$z2 - z2$ ResBlockD (avg. pool), $3 \to 128$
$z2 - z2$ ResBlockD (avg. pool), $128 \to 128$
$z2 - z2$ ResBlockD (no downsample), $128 \to 128$
$z2 - z2$ ResBlockD (no downsample), $128 \to 128$
ReLU
Global Sum Pool into f
Embed $y \in \{0, ..., 9\}$ into $\hat{y}'$
Projection step($\hat{y}', f$)

Table 10: Architectures used for the standard generator and discriminator in the CIFAR-10 experiments.

Generator
Sample $z \in \mathbb{R}^{128} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 9\}$ into $\hat{y} \in \mathbb{R}^{128}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{256}$
Project and reshape h to $4 \times 4 \times 256$
$z2 - p4$ ResBlockG, $256 \rightarrow 128$
$p4 - p4$ ResBlockG, $128 \rightarrow 128$
$p4 - p4$ ResBlockG, $128 \rightarrow 128$
$p4$-BN; ReLU
$3 \times 3\ p4 - p4$ GConvSN, $128 \rightarrow 3$
$p4$-Max Pool
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{64 \times 64 \times 3}$
$z2 - p4$ ResBlockD (avg. pool),
$3 \rightarrow 64$
$z2 - p4$ ResBlockD (avg. pool),
$64 \rightarrow 64$
$p4 - p4$ ResBlockD (no downsample),
$64 \rightarrow 64$
$p4$-Max Pool
$z2 - z2$ ResBlockD (no downsample),
$64 \rightarrow 128$
ReLU
Global Sum Pool into f
Embed $y \in \{0, ..., 9\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 11: Architectures used for the $p4$-equivariant generator and discriminator in the CIFAR-10 experiments.

Generator
Sample $z \in \mathbb{R}^{64} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 100\}$ into $\hat{y} \in \mathbb{R}^{64}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{128}$
Project and reshape h to $4 \times 4 \times 1024$
$z2 - z2$ ResBlockG, $1024 \rightarrow 512$
$z2 - z2$ ResBlockG, $512 \rightarrow 384$
$z2 - z2$ ResBlockG, $384 \rightarrow 256$
$z2 - z2$ ResBlockG, $256 \rightarrow 192$
BN; ReLU
3×3 ConvSN, $192 \rightarrow 3$
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{64 \times 64 \times 3}$
$z2 - z2$ ResBlockD, $3 \rightarrow 128$
$z2 - z2$ ResBlockD, $128 \rightarrow 256$
$z2 - z2$ ResBlockD, $256 \rightarrow 512$
$z2 - z2$ ResBlockD, $512 \rightarrow 784$
ReLU
Global Average Pool into f
Embed $y \in \{0, ..., 100\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 12: Architectures used for the standard generator and discriminator in the Food-101 experiments.

Generator
Sample $z \in \mathbb{R}^{64} \sim \mathcal{N}(0, I)$
Embed $y \in \{0, ..., 100\}$ into $\hat{y} \in \mathbb{R}^{64}$
Concatenate z and $\hat{y}$ into $h \in \mathbb{R}^{128}$
Project and reshape h to $4 \times 4 \times 1024$
$z2 - p4$ ResBlockG, $1024 \rightarrow 256$
$p4 - p4$ ResBlockG, $256 \rightarrow 192$
$p4 - p4$ ResBlockG, $192 \rightarrow 128$
$p4 - p4$ ResBlockG, $128 \rightarrow 96$
$p4$-BN; ReLU
$3 \times 3\ p4 - p4$ GConvSN, $96 \rightarrow 3$
$p4$-Max Pool
tanh()

Discriminator
Input RGB image $x \in \mathbb{R}^{64 \times 64 \times 3}$
$z2 - p4$ ResBlockD, $3 \rightarrow 64$
$p4 - p4$ ResBlockD, $64 \rightarrow 128$
$p4 - p4$ ResBlockD, $128 \rightarrow 256$
$p4$-Max Pool
$z2 - z2$ ResBlockD, $256 \rightarrow 784$
ReLU
Global Average Pool into f
Embed $y \in \{0, ..., 100\}$ into $\hat{y}'$
Projection step$(\hat{y}', f)$

Table 13: Architectures used for the $p4$-equivariant generator and discriminator in the Food-101 experiments.