A Survey on Benchmarks of LLM-based GUI Agents

Abstract

LLM-based GUI agents have made rapid progress in understanding visual interfaces, interpreting user intentions, and executing multi-step operations across web, mobile, and desktop environments. As these agents become more capable, systematic and reproducible evaluation has become essential for measuring progress and identifying remaining weaknesses. This survey provides a comprehensive overview of benchmarks for LLM-based GUI agents, covering three major categories: grounding and QA tasks, navigation and multi-step reasoning tasks, and open-world environments that reflect realistic and dynamic software usage. We examine how existing benchmarks evaluate both component-level abilities, such as intent understanding, GUI grounding, navigation, and context tracking, and system-level abilities, such as adaptation, personalization, privacy protection, safety, and computational efficiency. By comparing datasets, environments, and evaluation metrics, the survey reveals clear trends in benchmark design, along with persistent gaps including limited adaptability, vulnerability to malicious interfaces and prompt attacks, lack of interpretability, and significant computational overhead. We highlight emerging directions such as safety aware evaluation, user-centric personalization, lightweight deployment, and zero-shot generalization. This survey aims to serve as a practical guide for researchers who design GUI agents, build benchmarks, or study LLM-driven user interface automation.

1 Introduction

Graphical User Interface (GUI) enables human users to interact with complex digital systems through visual elements like icons and buttons. GUI agents represent an important, application-oriented branch in the field of Artificial Intelligence. They are designed to mimic human users by performing atomic operations such as clicks, inputs, and scrolls to interact with complex digital environments, including web browsers, mobile applications, and desktop software. GUI agents demonstrate tremendous potential in numerous domains, such as enterprise software automation, mobile device assistance, creative tool manipulation, and accessibility technologies. However, GUI agents face unique challenges. They must accurately identify, locate, and comprehend the function of interface elements from visually dense layouts. Furthermore, they must comprehend the high-level goals and intentions of users and effectively decompose tasks into a sequence of executable operations.

Recently, the rise of Large Language Models (LLMs), particularly Multimodal LLMs (MLLMs), has provided a powerful solution to overcome these challenges. The exceptional reasoning, knowledge integration, and natural language understanding capabilities of LLMs have been integrated into the cognitive core of GUI agents, greatly empowering their task understanding, long-term planning, and adaptation abilities. This synergy marks a significant shift in the field, moving GUI agents from rule-driven approaches toward intelligent, decision-driven systems. Advanced agents (Liu et al., 2024; Qin et al., 2025; Song et al., 2025; Gu et al., 2025) have shown impressive performance in understanding the content of the screens and executing appropriate actions.

Given the significant leap in capabilities achieved by LLM-based GUI agents, a systematic, fair, and reproducible evaluation of their core competencies has become crucial for measuring agents and advancing the field. As illustrated in Figure 1, the field exhibits a dynamic co-evolution of GUI agent techniques,

Figure 1: Co-evolution of GUI agent techniques, benchmarks, and applications.

benchmarks, and applications. This feedback loop drives rapid progress: emerging techniques empower new applications, which in turn necessitate more challenging benchmarks to measure capability boundaries.

With new datasets and environments constantly emerging, these benchmarks exhibit substantial heterogeneity across task types, environment fidelity, and evaluation metrics, resulting in fragmentation of evaluation standards. Moreover, as the technology advances, benchmarks are shifting from simple UI grounding and QA tasks to multi-turn navigation tasks and more recently to open-world tasks that assess agents in authentic environments. A systematic review is essential to retrospect this development trajectory, distilling the trends of increasing evaluative difficulty and complexity to guide future research toward more realistic tasks. In this survey, we aim to systematically review existing benchmarks for GUI agents, establishing a clear taxonomy of task scenarios, encompassing grounding & QA, navigation tasks, and open-world environments. By comparing benchmark designs across datasets, environments, and evaluation metrics, we distill prominent trends in the evolution of GUI agent assessment and identify current limitations of agents and benchmarks, such as limited adaptability, vulnerability to malicious attacks, lack of explainability evaluation, and considerable computational cost. Furthermore, we highlight emerging research directions deserving closer attention, including safety-aware evaluation, user-centric personalization, lightweight deployment, and zero-shot generalization. Briefly, contributions are

- **Addressing the Critical Need for a Benchmark-Centric Survey.** The LLM-based GUI agent community critically lacks a dedicated survey focusing on benchmarks. Our work presents a systematic review from the perspective of assessment frameworks to resolve the fragmentation of evaluation standards, addressing this essential need.

- **Establishment of a Systematic Taxonomy**: The survey provides a comprehensive review of existing benchmarks for LLM-based GUI agents, organizing them into a clear taxonomy based on task scenarios.

- **Identification of Challenges and Future Directions**: The paper highlights persistent gaps in current benchmarks and GUI agents and outlines critical future research directions.

In the rest of this survey, Section 2 introduces the principles for benchmarking LLM-based GUI agents. Section 3 describes the taxonomy of existing benchmarks. Section 4 discusses the challenges and future directions of GUI agents and benchmarks. Section 5 concludes this paper.

Difference with Existing Surveys. While several recent surveys have examined the landscape of GUI agents, they primarily focus on the construction and methodological techniques of agents. For instance,

(Nguyen et al., 2025) and (Zhang et al., 2025) provide comprehensive overviews of agent architectures, and (Shi et al., 2025) specifically concentrates on the safety and trustworthiness aspects. In contrast, this survey is the first to systematically review the field from the perspective of **benchmarks and evaluation methodologies**. Instead of categorizing literature solely by agent techniques or platforms, we introduce a novel taxonomy based on Task Scenarios ranging from fundamental Grounding and QA to multi-step Navigation, and finally to complex Open-World environments. This perspective allows us to: (1) Trace the co-evolution of agent capabilities and evaluation standards; (2) Dissect the structural pillars of benchmarks (Dataset, Environment, Evaluator) to reveal how evaluation rigor is advancing; (3) Highlight the persistent gaps between benchmark scores and real-world deployment challenges. By focusing on the structure and advancement of evaluation methodologies, this work complements existing method-centric surveys and provides a roadmap for the next generation of rigorous GUI agent evaluation.

2 Principles for Benchmarking

This section describes what to evaluate and how to evaluate GUI agents. We begin by outlining the general pipeline and key components of a GUI agent, followed by a discussion of the evaluation objectives. We then present the overall architecture of the proposed benchmark.

2.1 General Pipeline of GUI Agent

As shown in Figure 2, the general pipeline of an LLM-based GUI agent operates as a continuous loop encompassing four main components: the *Perceiver*, *Planner*, *Action Executor*, and *Memory*. This iterative cycle allows the agent to complete tasks by observing its environment (the GUI), deciding on a course of action, executing that action, and learning from the result. For a more detailed understanding, interested readers may refer to comprehensive surveys on GUI agents, e.g., (Nguyen et al., 2025; Shi et al., 2025; Zhang et al., 2025).

Perceiver. As the foundational step, GUI perception is crucial for agents and primarily relies on two main modalities: structural and visual. Structural perception parses machine-readable data, such as HTML/Document Object Model (DOM) for websites or accessibility trees (A11y trees) for mobile/desktop software. While structural data offers robust element identification and interaction, it is not always accessible. In contrast, visual perception analyzes screenshots using computer vision techniques like OCR (Qian et al., 2022) to detect buttons, texts, or icons. The robust visual capabilities of MLLMs enable agents to understand GUIs across different environments.

Planner. LLMs equip GUI agents with hierarchical planning capabilities. At the high level, after perceiving the GUI state, the agent understands user intent and decomposes complex, multi-step tasks into a sequence of simpler subtasks. It often employs a Chain-of-Thought (CoT) (Wei et al., 2022) approach to maintain long-term consistency. At the low level, agents determine the next atomic action to execute based on the high-level plan and the current GUI observations.

Action Executor. This component uses tools to interact with UI elements and execute the planned action in the environment, involving simulating mouse clicks, keyboard presses, and touch gestures. Common tools include the Android Debug Bridge (ADB), libraries like `PyAutoGUI`, and system-level accessibility APIs. Virtual or simulated environments, such as Android emulators (Rawles et al., 2025), are frequently employed to facilitate scalable experimentation and access to richer interaction signals.

Memory. This component enables the agent to maintain context and improve performance over time. Memory is typically categorized as internal/short-term (Lu et al., 2023) and external/long-term (Wang et al., 2023). Internal memory refers to the history of actions, observations, and reasoning steps within a single task. External memory provides broader rules and knowledge about the UI and the task, including past successful trajectories. This mechanism allows agents to learn from experience and generalize to similar tasks.

2.2 Evaluation Objectives

To systematically assess the performance of LLM-based GUI agents, both the capabilities of individual components in the pipeline and the overall readiness for real-world deployment should be considered. Accordingly, we categorize the evaluation objectives into component-level and system-level capabilities. The former corresponds to the functional abilities embodied by the components of agents, while the latter reflects the practical demands for real-world deployment. As illustrated in Figure 2, this categorization aligns directly with the pipeline of GUI agents, providing a clear connection between agents and evaluation criteria.

Component-Level Capabilities. As mentioned above, component-level capabilities are important to reflect the functions of each individual components in the GUI agent pipeline. These foundational abilities are prerequisite for successful task execution.

- *Intent Understanding.* The GUI Agent must accurately recognize, parse, and ultimately comprehend the query of the user and the ultimate goal of the task. Since user instructions can often be ambiguous or incomplete, the ability to clarify and disambiguate the user intent is essential to ensure proper task alignment.

- *GUI Grounding.* This capability concerns the precise identification and localization of UI elements, including buttons, images, links, and text input fields. Reliable element localization forms the basis for all downstream interactive operations.

- *Navigation.* GUI agents must be able to plan and execute a sequence of actions to navigate through applications and achieve the goal of the task. This multi-step reasoning process requires the agent to deeply understand the logical dependencies and temporal relationships between individual actions.

- *Context Tracking.* Agents should be able to store and retrieve relevant information from past interactions. This memory ability is vital for supporting multi-turn interactions, allowing agents to maintain task coherence by recalling previous steps, user preferences, or data entered across multiple conversational exchanges.

System-Level Capabilities. Beyond core capabilities, the following system-level objectives evaluate the maturity and reliability of GUI agents for real-world deployment.

- *Adaptation.* GUIs vary from platforms, operation systems, applications and versions. A practical agent must perform reliably in diverse interfaces it has not seen before. High adaptability is a key prerequisite for real-world deployment. Furthermore, in authentic dynamic environments, the agent must demonstrate robustness in handling unexpected events (e.g., pop-ups, advertisements) and anomalies (e.g., UI response latency, element loading failures) to ensure uninterrupted task completion.

- *Personalization.* An advanced GUI agent should possess the capacity to learn and internalize user preferences and habits. This learned information should then be used to inform and refine its action strategy. This context-aware and customized capability enables the agent to provide a more efficient and tailored interaction experience, significantly enhancing the utility of agents and user satisfaction.

- *Privacy Protection.* GUI operations frequently involve personal and sensitive information of users. Consequently, a trustworthy GUI agent must be designed with robust security and privacy protections mechanisms. This includes the inherent need to recognize and reject illicit or harmful instructions, and to effectively counter malicious safety threats encountered in the real world, such as image forgery of UI elements, malicious pop-ups, or overlays. Indirect prompt injection poses a particularly serious challenge for LLM-based agents.

- *Computational Efficiency.* It is critical for optimal user experience and system scalability that GUI agents operate within reasonable computational and temporal constraints.

Figure 2: General pipelines and evaluation objectives of GUI agents and architecture of benchmarks.

2.3 Benchmarks Architecture

A well-designed benchmark must comprehensively capture the process through which a GUI agent operates and is evaluated. To this end, we posit that a complete agent benchmark is structured around three pillars as illustrated in Figure 2: the dataset, the environment, and the evaluator. The dataset defines the task and provides the ground truth; the environment offers the executable interface and stateful platform on which the agent performs actions; and the evaluator measures performance under well-defined metrics. Taken together, these components establish a reproducible and holistic framework for assessing GUI agents.

The Dataset. The dataset provides the foundational raw materials that instantiate the task scenario. It supplies the specific instructions, contexts, and reference solutions needed for evaluation. A dataset typically includes:

- *Task Instructions*: Natural language descriptions of the intent of users, which can range from atomic commands to complex, multi-intent instructions.

- *Initial States*: The starting conditions of the task, provided as screenshots, DOM/accessibility trees, or a combination thereof.

- *Reference Solutions*: The ground truth information crucial for automated evaluation, which may include the correct action trajectory, the expected final state of the UI, or a canonical successful response.

To increase the diversity, many modern benchmarks utilize parameterized task templates or systematic task generators to create vast, diverse sets of instructions from the dataset.

The Environments. The operational environments of benchmarks dictate the complexity and authenticity of the interaction. They can be grouped into three fundamental types:

- *Static Environments* (Non-Interactive): These environments capture GUI interfaces as fixed, non-interactive representations, such as screenshots or HTML snapshots. They record interactions as static data, enabling reproducible evaluation without needing the actual application to run. They are primarily used to test GUI grounding capabilities, as the actions do not change the environment state.

- *Simulated Environments* (Controlled Interaction): These environments recreate controlled, isolated, dynamic interaction scenarios, often using web page rendering engines (e.g., MiniWoB, WebArena) or simplified OS emulators. They strike a balance between reproducibility and dynamism, allowing the environment to respond to the agent's actions. This makes them well suited for scalable experimentation and training.

- *Real-World Environments* (Authentic Testing): Tasks run directly on live applications or websites, often utilizing tools like the Android Debug Bridge (ADB) or desktop automation libraries. These benchmarks offer the most authentic, comprehensive, and dynamic testing ground, directly mirroring real-world applicability. However, they present significant challenges in terms of reproducibility, execution stability, and handling out-of-distribution events.

The Evaluators. The evaluators are the scoring components that assess the performance and abilities of the GUI agents based on various metrics and measurements. Metrics are the quantitative standards used to formalize this assessment. Metrics can be categories by their evaluation methodology and the objectives they measure. Common evaluation methods and metrics include:

- *Result-Only Metrics.* These metrics focus solely on the final outcome of the task. *Accuracy* and *Success Rate* are typical examples, measuring the grounding and navigation abilities of GUI agents, respectively. *Intersection over Union (IoU)* is a fine-grained measure of localization precision, which calculates the ratio of intersection and overlap between the predicted bounding box and the ground-truth box.

- *Trajectory Matching.* For more fine-grained evaluation of GUI agents, benchmarks measure the similarity or exact match between the predicted action sequence of the agent and the ground-truth trajectory. *Action Matching Score* is a representative metric. For a step to be successful, all the action type (e.g., click, text input), the target UI element, and the action parameters must be correct.

- *Termination Reason.* These metrics helps researchers understand exactly why an agent failed or succeeded. The termination can be classified into several key categories: (1) Self-Reported Completion (SRC): the agent autonomously ends the task. It can be further divided into true success or premature termination, where the latter means that the agent reports success while the task was not actually finished. (2) Maximum Step Reached (MSR): the execution has exceeded a predefined maximum number of steps. A subcategory is the Overdue Termination, which MSR happens because the agent has effectively completed the task but failed to recognize its completion. (3) Error & Collapse. (4) Deemed Impossible: the agent proactively determines that the task is impossible to complete based on the current environment or constraints. This determination can be accurate or erroneous.

- *Efficiency Metrics.* Efficiency is typically quantified by *Time Cost (per Step)* and *Token Cost (per Step)*, which directly represents the computational and monetary resources consumed by the underlying LLMs for generation and processing.

- *Reliability Metrics.* These metrics guide GUI agents toward reliability and trustworthiness. *Accuracy/SR variation in different environments* intuitively measures the adaptability of a GUI agent. The *Harm Prevention Rate* indicates the proportion of risky tasks in which GUI agents can successfully avoid negative outcomes to users such as privacy leaks, economic losses, and ethical violations in real-world scenarios.

3 Taxonomy of Existing Benchmarks

This section provides an overview of GUI-agent benchmarks. The taxonomy is fundamentally driven by the Task Scenario where benchmarks are designed to address. The task scenario defines the core intellectual challenges posed to agents, inherently reflecting the evolution of required agent functions and goal complexity. We observe that progress in GUI agent benchmarking has proceeded from focusing on single-step GUI Grounding & QA tasks to multi-step Navigation tasks, and more recently to challenging Open-World tasks.

- **GUI Grounding & QA Tasks** demand precise localization of UI elements or information extraction from the GUI based on a natural language query, primarily testing the basic GUI perception and understanding capabilities of agents.

Figure 3: Task Scenarios of GUI agent benchmarks.

- **Navigation Tasks** challenge an agent to plan and orchestrate a sequence of executable actions to fulfill the goal of the user, focusing on its multi-step planning and sequential action execution.

- **Open-World Tasks** evaluate the agent by deploying it in authentic, dynamic, and often cross-application workflows that embody the inherent diversity and unpredictability of real-world software environments, serving as a comprehensive test of the integrated component-level and system-level capabilities.

Grounding & QA is the necessary prerequisite for Navigation, while Open-World tasks represent the evolution and generalization of Navigation tasks. The relation of these task scenarios is illustrated in Figure 3. To demonstrate the task spectrum, Figure 4 visualizes two representative examples: the fundamental GUI Grounding tasks and the complex Open-World tasks. In the sequel, we will systematically review the evolution of these benchmarks and delve into the representative methods and performance. Crucially, organizing the taxonomy by Task Scenario is the optimal approach for tracking the co-evolution of agent capabilities and evaluation standards, as it clearly reveals how the rigor of assessment is constantly elevated across datasets, environments, and evaluators.

3.1 GUI Grounding and QA Benchmarks

As introduced above, the first task type primarily concerns with addressing the fundamental problem of understanding and perception.

3.1.1 Overall Comparison

Typical ones are ScreenQA (Hsiao et al., 2025) and ScreenSpot (Cheng et al., 2024). ScreenQA requires the agent to answer questions or extract information from screenshots and metrics like Average F1 score are applied. ScreenSpot measures the grounding Accuracy of GUI agents with natural language instructions. The subsequent version of ScreenQA are ScreenQA-Short and Complex-ScreenQA (Baechler et al., 2024), which introduced alternative short answers and more challenging questions. An overview of Grounding and QA benchmarks is given by Table 1, we can observe that benchmarks in this domain evolve to include more complex and realistic tasks as well as more comprehensive metrics in diverse data and environments. Shifting from static snapshots to dynamic trajectories, GUI-World (Chen et al., 2025a) includes videos and key frames to evaluate the dynamic GUI understanding ability of agents across a wide spectrum of environments ranging from desktop and mobile to extended reality (XR). Furthermore, GUI-World introduced the LLM-as-a-Judge methodology to assigns a similarity score between the response of agents and the golden answer. ScreenSpot-V2 (Wu et al., 2024) fixed problems in ScreenSpot and introduced Intersection over Union (IoU) metric to more precisely evaluate the quality of agents in locating UI elements. ScreenSpot-Pro (Li et al., 2025) is a recent advancement of ScreenSpot which focus on high-resolution computer screens and professional

Figure 4: Examples of GUI Grounding tasks in ScreenSpot-Pro (left) and Open-World tasks in OSWorld (right). Note that Open-World tasks serve as a comprehensive example, representing the advanced evolution of Navigation tasks in authentic environments.

Benchmarks	Dataset	Environments	Evaluators	Venue	URL
ScreenQA	Based on RICO dataset, 86k+ QA pairs	Static Images (Mobile)	F1 Score	NAACL 2025	GitHub
ScreenSpot	Artificially cropped screenshots	Static Images (Cross-platforms)	Accuracy	ACL 2024	Hugging Face
ScreenQA-Short	Based on ScreenQA with alternative short answers	Static Images (Mobile)	F1 Score	IJCAI 2024	GitHub
Complex-ScreenQA	Extension to ScreenQA-Short focus on reasoning	Static Images (Mobile)	F1 Score	IJCAI 2024	GitHub
GUI-World	12k videos, 100k QA pairs	Dynamic GUI (Cross-platforms)	QA Performance (LLM-as-a-Judge)	ICLR 2025	Github
ScreenSpot-V2	Based on ScreenSpot, 1.2k+ revised grounding instructions	Static Images (Cross-platforms)	Accuracy, IoU	arXiv	Hugging Face
ScreenSpot-Pro	1.5k+ hi-res professional application screenshots	Static Images (Desktop)	Accuracy	ICLR 2025	Github
OSWorld-G	Based on OSWorld, 564 fine-grained annotated samples	Real OS (Desktop)	Accuracy, Success Rate	arXiv	Github
TransBench	1.4k+ cross-platform/version screenshots, 22k+ instructions	Static Images (Cross-platforms)	Accuracy, Average Distance	ACL 2025	TransBench

Table 1: Benchmarks focusing on Grounding and QA tasks.

scenario. OSWorld-G (Xie et al., 2025) extends this scope of simple element localization to include fine-grained operations (e.g., character-level cursor positioning, slider control) and rejection handling for infeasible commands (e.g., opening non-existent software). TransBench (Lu et al., 2025b) evaluates the adaptability of GUI agents through grounding tasks across different platforms, applications, and versions.

3.1.2 Case Study

As the prerequisite for any effective operation, the UI grounding task serves as a foundational test for all contemporary GUI agents, irrespective of their architectural backbones (LLMs or MLLMs). To address these

Model	Applications						AVG perf.
	Development	Creative	CAD	Scientific	Office	OS	
Hcompany/Holo2-30B-A3B	69.9	61.0	54.8	64.6	81.7	67.9	66.1
GTA1-32B	61.2	52.8	60.5	65.0	83.5	65.3	63.6
Holo1.5-72B	63.5	62.5	51.3	64.2	79.6	59.7	63.3
UI-Venus-72B	59.5	55.4	57.5	66.5	77.8	57.7	61.9
UI-TARS-1.5	63.9	50.4	58.2	69.3	79.6	51.0	61.6
Seed-1.5-VL	53.8	59.2	59.0	61.4	74.8	60.2	60.9
GUI-ARP-7B	59.2	52.5	61.7	62.2	77.8	54.6	60.8
GUI-AIMA-3B	55.2	48.7	57.5	64.2	79.6	58.7	59.6
Hcompany/Holo2-8B	55.5	52.2	52.5	61.0	80.0	56.6	58.9
GTA1-Qwen2.5VL-72B	57.2	51.0	49.8	63.0	77.0	57.1	58.4

Table 2: The Grounding Accuracy (%) leaderboard of ScreenSpot-Pro.

tasks, the evolution of agent technologies can be broadly categorized into three principal paradigms based on their perceptual input strategy:

- *Structural Text.* Early LLM-based agents relied exclusively on parsing GUI interfaces into structured textual representations, such as HTML/DOM or accessibility trees. The role of LLM is to process this complex text, alongside the user instruction. However, methods based solely on structure remain fragile when facing inaccessible structural data or dynamic content.

- *Visual Perception.* The limitations led to the integration of visual perception, enabled by the recent emergence of Vision-Language Models (VLMs). A pivotal technique in this domain is Set-of-Marks prompting (Yang et al., 2023), which involves augmenting screenshots with visual markers, typically numbered or lettered bounding boxes, to clearly delineate interactive components. This marking process often utilizes specialized element detection models for precise component delineation and Optical Character Recognition to capture text elements. The VLM then processes the visually augmented screenshot.

- *Comprehensive Multimodal Modeling.* Some advanced GUI agents have shifted towards a comprehensive multimodal modeling paradigm, recognizing that optimal grounding performance requires synthesizing information from all available data sources to overcome the limitations of any single modality. Supervised Fine-Tuning (SFT) and Reinforcement Learning (RL) on high quality multimodal data help agents achieve better performance.

To give readers a clear view of the current performance landscape of GUI agents, we report results on ScreenSpot-Pro, which evaluates grounding performance on professional computer applications. The leaderboard is shown in Table 2. As can be seen, high-resolution screens and professional software pose significant challenges for agents, and even the current state-of-the-art (SOTA) performance are far from satisfactory, revealing that although GUI grounding appears to be a relatively mature basic task, perception remains a major bottleneck in complex desktop environments. Recent multimodal agents, Holo2 (Andreux et al., 2025), GTA1 (Yang et al., 2025c), and UI-Venus (Gu et al., 2025) demonstrate leading performance. The performance of these agents is typically attained by leveraging SFT and RL on high-fidelity multimodal inputs, encompassing both screenshots and underlying structural HTML/A11y tree data.

3.2 Navigation and Multi-Step Reasoning Benchmarks

As the capabilities in single-step grounding tasks and intent understanding improved, the research focus shifted to navigation tasks. This type of benchmarks assess planning and multi-step reasoning of GUI agents and require them not only to perceive the interface but also to execute the correct sequence of operations.

3.2.1 Overall Comparison

Table 3 summarizes the key navigation benchmarks. MiniWoB++ (Liu et al., 2018) served as a pioneering benchmark focusing on simple web interaction tasks evaluated primarily by task success rate. However, the

Benchmarks	Dataset	Environments	Evaluators	Venue	URL
MiniWoB++	Based on MiniWoB, 104 web interaction tasks	Simulated (Web)	Success Rate (SR)	NeurIPS 2018	Github
Mind2Web	2350 tasks from 137 websites	Static Real Traces (Web)	Element Accuracy, Operation F1, Step SR	NeurIPS 2023	Github
AITW	715k episodes spanning 30k unique instructions	Static Real Traces (Mobile)	Action Matching Scores	NeurIPS 2023	Github
WebArena	812 tasks derived from 241 templates	Simulated (Web)	SR	ICLR 2024	Github
WebVLN	8990 records/paths with 14825 QA pairs derived from 3 shopping websites	Simulated (Web)	SR, SR weighted by Path Length	AAAI 2024	Github
VisualWebArena	Based on WebArena, 910 new visual web tasks	Simulated (Web)	Success Rate	ACL 2024	Github
MT-Mind2Web	720 multi-turn tasks based on Mind2Web	Simulated (Web)	Element Accuracy, Operation F1, Step/Turn SR	ACL 2024	Hugging Face
OmniAct	9802 task instructions, screenshots, and ground truth `PyAutoGUI` scripts	Static Real Traces (Cross-platforms)	Action Score, Sequence Score	ECCV 2024	Hugging Face
AndroidControl	15283 unique tasks over 833 Android apps	Simulated (Mobile)	Step-wise Accuracy	NeurIPS 2024	Github
MobileAgentBench	100 tasks across 10 open-source apps	Simulated (Mobile)	SR, Termination Reason, Time/Token Cost	AAAI 2025	Github
GUI-Odyssey	8334 episodes spanning 6 types of cross-app tasks, 212 apps, and 1.4k app combos	Simulated (Mobile)	SR, Action Matching Score	ICCV 2025	Github
VideoWebArena	2021 tasks based on video tutorials	Simulated (Web)	SR, Intermediate Score, Final Score	ICLR 2025	Github
UI-Vision	8227 tasks on 83 apps with dense annotations	Simulated (Desktop)	Step Success Rate	arXiv 2025	Github
FineState-Bench	2257 fine-grained tasks	Simulated (Cross-platforms)	Locate SR, Interact SR	arXiv 2025	Github

Table 3: Benchmarks focusing on Navigation tasks.

rapid advancement of LLMs has enabled modern agents to achieve near human-level performance on these simple tasks. WebArena (Zhou et al., 2024) was also a notable examples of benchmarks for web GUI agents, which includes tasks that are not possible to complete, marking an early exploration into self-awareness of agents.

A pivotal development in navigation evaluation is the adoption of more fine-grained metrics alongside the expansion of dataset scales. Mind2Web (Deng et al., 2023) utilized static real-world traces and introduced metrics such as Element Accuracy, Operation F1, and Step Success Rate to measure the correctness of the entire action trajectory. This methodology was extended to the mobile domain by AITW (Rawles et al., 2023), AndroidControl (Li et al., 2024), and GUI-Odyssey (Lu et al., 2025a), which employed Action Matching Scores and Step-wise Accuracy to assess operation precision. OmniAct (Kapoor et al., 2024) and UI-Vision (Nayak et al., 2025) further generalized this fine-grained evaluation approach to desktop and cross-platform environments. Simultaneously, the field witnessed a significant increase in data scale, evolving from hundreds of tasks in early benchmarks to thousands of trajectories, which is essential for training and evaluating robust GUI agents.

Beyond basic Success Rate (SR) and Step-wise SR, more advanced metrics have been proposed to capture the efficiency and reliability of GUI agents. WebVLN (Chen et al., 2024) introduced efficiency-oriented metrics, such as SR weighted by Path Length, to penalize redundant actions. To assess visual robustness,

VisualWebArena (Koh et al., 2024) extended the WebArena environment with 910 visually intensive tasks. VideoWebArena (Jang et al., 2025) further expanded the modality to video understanding, creating tasks based on video tutorials and proposing Intermediate and Final Scores to measure the performance. In terms of interaction complexity, MT-Mind2Web (Deng et al., 2024) generalized navigation to multi-turn scenarios, requiring agents to handle conversational interactions and maintain context over long horizons. Aiming for better interpretability and precision, MobileAgentBench (Wang et al., 2025a) introduced Termination Reasons that categorize failures into specific types to facilitate detailed error diagnosis. FineState-Bench (Ji et al., 2025) focused on fine-grained state control to test the ability of agent to handle precise operations.

3.2.2 Case Study

To tackle these complex environments, agents must utilize the four core components introduced in Section 2.1, coordinated through advanced alignment and training paradigms. As discussed in Section 3.1.2, approaches such as SFT and RL are also widely used in navigation tasks.

- *Supervised Fine-Tuning (SFT).* SFT aligns a general LLM or MLLM to the specialized requirements of GUI interaction and enables the model to learn fundamental UI interaction patterns, accurate element grounding, and the mapping from natural language instructions to executable low-level actions. High-quality human demonstration data that comprise detailed grounding information, instruction-action pairs, and complete task trajectories are necessary for this progress. In essence, SFT is crucial for achieving high fidelity in element identification and action prediction, thereby providing a robust base for subsequent, more advanced training.

- *Reinforcement Learning (RL).* Pure SFT policies are prone to overfitting to observed training trajectories and lack the mechanism to self-correct errors or effectively leverage environmental feedback. To overcome these limitations, researchers integrate RL, particularly Reinforcement Fine-Tuning (RFT), guided by either environmental success signals or explicit rule-based rewards. The primary objective of RL is to optimize the policy of agents to maximize the long-term cumulative reward, thereby achieving deep alignment with complex, multi-step task objectives. By optimizing for cumulative success, RL enables the agent to shift its focus from simple step-by-step reproduction to strategic sequence planning across multiple turns. Advanced RL algorithms, such as Direct Preference Optimization or Group Relative Policy Optimization, when combined with specialized reward functions, train the agent to adapt its policy iteratively. This process leads to enhanced adaptation across unseen UI layouts and superior robustness through self-correction upon encountering errors. Consequently, advanced GUI agents predominantly rely on a two-stage training paradigm (SFT → RL), or incorporate multi-turn RL techniques to reach SOTA performance.

In Table 4, we list the representative performance results on GUI-Odyssey, whose long-horizon cross-app navigation tasks have 15.4 average steps. This benchmark evaluates GUI agents by two core metrics, Action Matching Score (AMS) and Success Rate (SR). The GUI-Odyssey performance data clearly demarcates agent technology development. Top-tier general-purpose MLLMs, such as GPT-4o and Claude-computer-use, exhibit severely low SRs of 5.4% and 3.1%, respectively. In contrast, recent GUI agents like UI-Venus and UI-TARS (Qin et al., 2025) pushes the SR to over 70% and even near 90%. Their success is attributed to their End-to-End native agent architecture. Furthermore, these agents leverage large-scale training and often incorporates RL to optimize long-horizon decision-making. However, this success is still heavily reliant on domain-specific training data. To enable agents to operate in real-world scenarios where task types and applications exhibit combinatorial complexity,

Models	AMS	SR
Closed Models		
GPT-4o	37.5	5.4
Claude-computer-use	60.9	3.1
SeeClick	71.0	53.9
Open Models 7B		
Qwen2.5-VL-7B	67.4	52.4
OS-Atlas-7B	84.5	62.0
UI-TARS-7B	94.6	87.0
UI-Venus-7B	87.3	71.5
UI-S1-7B	76.3	59.5
Open Models 72B		
UI-TARS-72B	95.4	88.6
UI-Venus-72B	87.2	72.4

Table 4: Action Matching Score (AMS, %) and Success Rate (SR, %) performance of GUI agents in GUI-Odyssey. Data collected from (Wu et al., 2024; Qin et al., 2025; Lu et al., 2025c).

research must move beyond closed benchmarks and embrace an open-world evaluation paradigm that demands stronger reasoning and adaptation capabilities.

3.3 Open-World Environments and Generalization Benchmarks

Open-World Tasks represent the newest development in GUI agent benchmarks, aiming to evaluate the adaptability and reliability of agents in authentic, complex, and unconstrained GUI environments. These tasks require agents to operate across applications in dynamic unpredictable workflows and resist security risks, reflecting the inherent diversity and unpredictability of real-world software scenarios. As shown in Figure 3, Open-World Tasks represent an evolution and generalization of Navigation Tasks, currently posing the most significant challenge in assessing the practical deployment capability of agents.

3.3.1 Overall Comparison

OSWorld (Xie et al., 2024) and AndroidWorld (Rawles et al., 2025) are pioneering and representative examples of this transition, as they introduced scalable, realistic tests in computer and mobile environments, respectively. The framework of OSWorld was later extended by WindowsAgentArena (Bonatti et al., 2024) and macOSWorld (Yang et al., 2025a) to specifically evaluate GUI agents in Windows and macOS environments. To overcome the limitation of OSWorld that tasks have to be deterministic, OSUniverse (Davydova et al., 2025) supports non-deterministic tasks, such as looking up the weather, where the result changes dynamically with the environment, requiring agents to handle non-fixed ground truth. WorldGUI (Zhao et al., 2025) embraces various initial states to better evaluate the adaptability of GUI agents in scenarios that are closer to users.

Open-world benchmarks gives researchers a more comprehensive understanding of the capabilities and limitations of GUI agents. With more fine-grained metrics, they also highlight the significant gap between current technology and human-level performance.

Termination reasons have been analyzed by more benchmarks recently, such as CRAB (Xu et al., 2025), SPA-Bench (Chen et al., 2025b), Mobile-Eval-E (Wang et al., 2025c), and UI-NEXUS (Guo et al., 2025b). As we introduced in Section 2.3, these benchmarks categorize termination reasons into several types including Successful, Premature, Max steps reached and Collapse. This categorization helps in diagnosing specific weaknesses of GUI agents and provides insights for targeted improvements.

Efficiency is also considered by more benchmarks. CRAB, UI-NEXUS, and FingerTip (Yang et al., 2025b) introduced Time/Token Cost to evaluate the computational efficiency of GUI agents. MMBench-GUI (Wang et al., 2025b) also utilized Efficiency-Quality-Aware (EQA) to jointly evaluate both the success rate and efficiency and give a higher evaluation to GUI Agents that can complete tasks in fewer steps.

Meanwhile, benchmarks begin to take security into consideration. ST-WebAgentBench (Levy et al., 2025) requires the agents to complete tasks in accordance with organization and user policies, thereby enhancing their controllability. MobileSafetyBench (Lee et al., 2024) design tasks that involve 5 types of risks especially Indirect Prompt Injection to evaluate the harm prevention ability of GUI agents. AgentScan (Wu et al., 2025) and macOSWorld contain malicious attacks in their tasks.

Finally, LearnGUI (Liu et al., 2025) assessed the learning capability of mobile GUI agents by providing rich k-shot task combinations to encourage efficient knowledge transfer and generalization efficacy. FingerTip (Yang et al., 2025b) introduced two tracks, Proactive Suggestions and Personalized Execution, marking a shift of GUI agent evaluation from task completion to a higher-level assessment of how to better serve users.

Through this comprehensive review, the characteristics and evolution of Open-World benchmarks become evident: they feature more realistic environments, incorporate more complex tasks, utilize more fine-grained and diagnostic metrics, and increasingly emphasize the practicality of the agent.

Benchmarks	Dataset	Environments	Evaluators	Venue	URL
OSWorld	369 tasks on real desktop apps	Real OS (Desktop)	Success Rate (SR)	NeurIPS 2024	GitHub
AndroidWorld	116 parameterized tasks across 20 apps	Real OS (Mobile)	SR	ICLR 2025	GitHub
CRAB	Generating tasks from sub-tasks	Real OS (Cross-platforms)	SR, Termination Reason, Time/Token Cost	ACL 2025	GitHub
Win- dowsAgentArena	Based on OSWorld, 150+ Windows-specific tasks	Real OS (Windows)	SR	arXiv 2024	GitHub
ST- WebAgentBench	222 tasks paired with safety and trustworthiness policies and concise rules	Real OS (Web)	Completion Under Policy	ICML 2025	GitHub
SPA-Bench	340 tasks, including 150 single-app tasks and 20 cross-app tasks	Real OS (Mobile)	SR, Termination Reason	ICLR 2025	GitHub
MobileSafety- Bench	80 tasks grounded in daily life, including 5 types of risks	Real OS (Mobile)	Goal Achievement Rates, Harm Prevention Rates	arXiv 2024	GitHub
Mobile-Eval-E	25 mobile tasks including 19 multi-app tasks	Real OS (Mobile)	SR, Termination Reason, Satisfaction Score	arXiv 2025	Github
WorldGUI	611 tasks with various initial states	Real OS (Cross-platforms)	SR	arXiv 2025	GitHub
LearnGUI	Based on AMEX and AndroidWorld, 2252 offline few-shot tasks and 101 online tasks	Real OS (Mobile)	Action Type Accuracy, Action Match Accuracy	arXiv 2025	GitHub
OSUniverse	Including non-deterministic tasks	Real OS (Desktop)	SR, Weighted Score	arXiv 2025	GitHub
AgentScan	Tasks with malicious instructions and glitch tokens	Real OS (Mobile)	Attack Success Rate	arXiv 2025	arXiv
macOSWorld	Based on OSWorld, 202 multilingual macOS-specific tasks	Real OS (macOS)	SR, Safety Evaluation	arXiv 2025	Website
UI-NEXUS	100 task templates on 50 apps	Real OS (Mobile)	SR, Termination Reason, Time/Token Cost	arXiv 2025	Github
MMBench-GUI	8000+ tasks	Real OS (Cross-platforms)	SR, Efficiency-Quality-Aware (EQA) Score	arXiv 2025	Github
FingerTip	21437 real episodes covering 506 apps	Real OS (Mobile)	SR, Similarity, Time/Token Cost	arXiv 2025	arXiv

Table 5: Benchmarks focusing on Open-World tasks.

3.3.2 Case Study

The complexity and high realism of Open-World benchmarks necessitate the development of intelligent agents equipped with highly sophisticated planning and robust self-correction mechanisms. To meet these rigorous demands, the underlying technological paradigms for designing GUI agents have undergone a rapid and significant evolution. This architectural evolution, including the paradigms discussed below and the specific techniques introduced previously in Section 3.1.2 and 3.2.2, is comprehensively summarized in Figure 5.

- *ReAct.* ReAct (Yao et al., 2023) defines the fundamental control loop as the interleaving of ob-

Figure 5: GUI agent technology evolution.

Models	Chrome (46)	GIMP (26)	Calc (47)	Impress (47)	Writer (23)	OS (24)	Thunderbird (15)	VLC (17)	VS Code (23)	Workflow (101)	Total (369)
Agent S3 w/ GPT5	69.5	69.2	87.2	63.7	78.1	79.2	80.0	52.1	82.6	58.7	69.9
GTA1 w/ GPT5	58.6	76.9	63.8	65.5	60.7	79.2	80.0	57.9	82.6	50.9	63.4
Claude Sonnet 4.5	63.0	53.8	72.3	68.0	82.5	70.8	60.0	58.2	73.9	49.5	62.9
Agentic Lybic	63.0	73.1	60.9	69.4	65.2	75.0	66.7	80.7	82.6	41.6	61.9
CoACT-1	54.3	65.4	70.2	50.3	73.9	75.0	73.3	71.9	78.3	47.9	60.8
UI-TARS-2	63.0	50.0	66.0	56.4	60.9	41.7	73.3	49.9	73.9	34.1	53.1
AutoGLM-OS-9B	39.1	61.5	58.7	29.7	52.2	75.0	80.0	64.6	82.6	27.9	48.0

Table 6: The Success Rate (%) leaderboard of OSWorld.

servation, explicit reasoning steps (*Thought*), and executable actions (*Action*). This structure enables dynamic task decomposition and local optimization, ensuring coherence and alignment with the global goal across complex, multi-step trajectories.

- *Reflexion.* Reflexion (Shinn et al., 2023) introduces a meta-cognitive feedback loop critical for error recovery. Upon failure, the agent self-critiques its entire execution trajectory to generate a refined strategy (Reflection). This knowledge is then stored in memory, substantially enhancing the robustness and adaptability to adapt to dynamic or uncertain environments.

- *Multi-Agent System (MAS).* MAS (Hong et al., 2024) paradigm addresses the cognitive and computational load of extremely complex tasks by distributing the workflow among multiple specialized, autonomous agents. Typically organized hierarchically, MAS can improve scalability, efficiency, and fault tolerance of GUI agents by leveraging task-specific expertise and parallel execution for complex, cross-domain problems.

- *Test-Time Scaling.* Contemporary GUI agent research increasingly incorporates Test-Time Scaling strategy to enhance performance during inference (Yang et al., 2025c; Gonzalez-Pumariega et al., 2025). This is achieved by sampling multiple action proposals at each step or by even generating entire task trajectories. Such scaling leads to significant improvements in both immediate decision quality and overall task success rates.

In Table 6, we present the representative performance data on OSWorld. The leaderboard provides a breakdown of Success Rates across 9 application categories and composite Workflow, offering empirical insights into the current capability boundaries of GUI agents. The data reveals that the current SOTA performance is a total SR of 69.9% achieved by Agent S3 (Gonzalez-Pumariega et al., 2025). Other advanced models, such as GTA1 and Claude Sonnet 4.5, achieve SR over 60%. A critical insight from Table 6 is the stark performance disparity between single-application tasks and complex workflows. In isolated, domain-specific environments, agents demonstrate high competency. However, performance significantly degrades in the Workflow category, which involves multi-application tasks. The SOTA SR drops to 58.7% in this category, showing the difficulty of Open-World tasks. ReAct, Reflexion, and their variants are widely adopted by top-performing agents to tackle these challenges. Agentic Lybic (Guo et al., 2025a) and CoAcT-1 (Song et al., 2025) both implement Multi-Agent System, and Test-Time Scaling is adapted by GTA1 and Agent S3. These mechanisms optimize decision quality in complex environments, thereby enabling agents to achieve SOTA performance on the benchmark.

3.4 Observations

Our cross-category analysis of GUI agent benchmarks reveals several pivotal trends that define the maturation of the field and its enduring gaps.

Co-Evolution of Task Fidelity and Complexity. The benchmark landscape has systematically progressed from evaluating atomic capabilities (Grounding & QA) to sequential planning (Navigation) and finally to assessing integrated performance in authentic workflows (Open-World). This trajectory mirrors the pursuit of practical utility, pushing evaluation environments from static snapshots toward dynamic, real-world systems.

Shift Toward Multi-Faceted Evaluation. There is a clear trend away from relying solely on result-only metrics like SR. A comparison among Table 1, 3, and 5 reveals that modern benchmarks increasingly incorporate metrics such as Action Matching Scores, Termination Reason analysis, and efficiency metrics. This shift enables a more granular understanding of agent failures and the quality of the decision-making process.

The Persistent Generalization Gap. Performance data across benchmarks, particularly evident in Table 4 (GUI-Odyssey) and Table 6 (OSWorld), highlights a persistent challenge that agents can exhibit strong performance on specialized or closed-domain tasks but suffer significant performance degradation in cross-application workflows and open-ended settings. The lower success rates in the Workflow category of OSWorld, compared to single-app categories, starkly illustrates this gap. Future benchmarks must continue to stress-test this compositional and zero-shot generalization.

Prevailing Architectural Trends for Complex Tasks. In response to the demands of Navigation and Open-World settings, leading GUI agent designs have increasingly adopted a common set of methodological approaches. Techniques such as RL training, ReAct-style reasoning and Reflexion for self-correction are now widely employed. Additionally, Multi-Agent Systems and Test-Time Scaling are being integrated into advanced agent frameworks to enhance robustness and scalability. This trend reflects a growing consensus on the architectural components necessary for reliable, long-horizon GUI interaction.

In summary, the progression of GUI agent benchmarks reflects a clear trajectory from assessing isolated capabilities toward evaluating integrated, reliable, and generalizable agent behavior. Key observed trends include the move toward more realistic environments, the adoption of richer diagnostic metrics, and more advanced agent techniques. Together, these developments frame the central challenge ahead: bridging the current gap between benchmark performance and truly robust real-world GUI assistant.

4 Challenges and Future Directions

Despite the rapid evolution of GUI agents, significant discrepancies remain between benchmark performance and practical deployment. We synthesize these challenges into five key dimensions, highlighting the trade-offs in current methodologies and the necessary shifts for future research.

4.1 Lack of Explainability Evaluation

While the current evaluation for GUI agents has expanded significantly across multiple dimensions, as reflected in Section 3, the systematic assessment of decision explainability remains notably underdeveloped. Users currently need insight into why an agent makes specific decisions, particularly during failures or sensitive operations. Evaluation frameworks should integrate explainability. This could involve requiring agents to provide natural language justifications for key decisions, designing tasks that test logical consistency across multi-step plans, or incorporating interactive mechanisms that allow users to query the reasoning post-hoc. This is a important step toward building GUI agents that are transparent and trustworthy in sensitive environments.

4.2 The Challenge of Generalization

As shown and discussed in Section 3, Existing agents demonstrate limited adaptability when transferred to novel environments. Performance often degrades significantly when agents encounter operating systems, applications, versions, or language settings that differ from their training data. This suggests that current SOTA performance relies heavily on data coverage rather than a fundamental grasp of universal GUI interaction principles. To achieve true generalist GUI agents, research may focus on domain adaptation and meta-learning techniques. Benchmarks should specifically design zero-shot tracks that evaluate performance on unseen applications to rigorously test cross-platform generalization.

4.3 Security and Trustworthiness Vulnerabilities

As agents are granted extensive permissions to operate devices and accessibility to private data of users, security has become a important concern. Most existing benchmarks focus on functional completion and

barely assess the ability to identify and reject harmful or illicit instructions. While pioneering benchmarks like ST-WebAgentBench and MobileSafetyBench have emerged, current agents exhibit weak defenses against real-world threats, such as indirect prompt injection, UI forgery, and malicious overlays. Trustworthiness must be integrated into the core evaluation, pushing agents to develop robust safety and privacy protection mechanisms.

4.4 Shifting Towards User-Centric Tasks

Current benchmarks predominantly evaluate standardized, isolated tasks, neglecting the personalized nature of human-machine interaction. They lack mechanisms to assess the ability of GUI agents to learn user habits, maintain long-term memory, or adapt to personalized constraints over time. A truly helpful assistant must evolve from passive command execution to proactive suggestions and personalized workflows. The field must transition towards benchmarks that require agents to accumulate knowledge across multiple interactions and optimize workflows based on learned user profiles and historical data.

4.5 Light-Weighting and On-Device Deployment

The successful adoption of GUI agents in consumer-facing applications necessitates a rigorous assessment of their on-device deployment feasibility. This transition introduces a core challenge: how to effectively miniaturize large LLMs/MLLMs (as SOTA agents often rely on models above 7B) to meet strict computational and latency constraints. Model compression often results in significant performance degradation, particularly in core functions such as precise grounding and planning. While existing benchmarks have started to include efficiency metrics like Time/Token Costs, more critical physical constraints for on-device deployment such as memory/Video RAM footprint and power consumption remain largely undiagnosed.

5 Conclusion

GUI agents represent a pivotal step towards Artificial General Intelligence (AGI), bridging the gap between digital systems and human intentions. This survey has provided a comprehensive review of the rapid evolution of LLM-based GUI agent benchmarks, tracing the trajectory from Grounding and QA tasks to multi-step Navigation tasks, and finally to the complex, dynamic Open-World environments that define the current frontier. Our analysis reveals a clear co-evolutionary relationship: advancements in LLMs and MLLMs empower agents with stronger capabilities, which in turn necessitates benchmarks with higher fidelity, broader coverage, and stricter evaluation standards. The future of this field relies not just on building stronger models, but also on establishing rigorous, reproducible, and realistic benchmarks that can accurately measure the gap between autonomous agents and human users.

We hope this survey serves as a roadmap for researchers and developers, illuminating the current landscape and guiding the community towards creating GUI agents that are not only intelligent but also efficient, trustworthy, and truly capable of assisting users in the complex digital world.

References

M. Andreux, B. B. Skuk, H. Benchekroun, E. Biré, A. Bonnet, R. Bordie, N. Bout, M. Brunel, P.-L. Cedoz, A. Chassang, M. Chen, A. D. Constantinou, A. d'Andigné, H. de La Jonquière, A. Delfosse, L. Denoyer, A. Deprez, A. Derupti, M. Eickenberg, M. Federico, C. Kantor, X. Koegler, Y. Labbé, M. C. H. Lee, E. L. J. de Kergaradec, A. Mahla, A. Manevich, A. Maret, C. Masson, R. Maurin, A. Mena, P. Modard, A. Moyal, A. N. Kerbel, J. Revelle, M. L. Richter, M. Santos, L. Sifre, M. Theillard, M. Thibault, L. Thiry, L. Tronchon, N. Usunier, and T. Wu. Surfer-H meets Holo1: Cost-efficient web agent powered by open weights. *arXiv*, 2025.

G. Baechler, S. Sunkara, M. Wang, F. Zubach, H. Mansoor, V. Etter, V. Carbune, J. Lin, J. Chen, and A. Sharma. ScreenAI: A vision-language model for UI and infographics understanding. In *IJCAI*, pp. 3058–3068, 2024.

R. Bonatti, D. Zhao, F. Bonacci, D. Dupont, S. Abdali, Y. Li, Y. Lu, J. Wagle, K. Koishida, A. Bucker, L. Jang, and Z. Hui. Windows Agent Arena: Evaluating multi-modal OS agents at scale. *arXiv*, 2024.

D. Chen, Y. Huang, S. Wu, J. Tang, H. Zhou, Q. Zhang, Z. He, Y. Bai, C. Gao, L. Chen, Y. Li, C. Wang, Y. Yu, T. Zhou, Z. Li, Y. Gui, Y. Wan, P. Zhou, J. Gao, and L. Sun. GUI-World: A video benchmark and dataset for multimodal GUI-oriented understanding. In *ICLR*, 2025a.

J. Chen, D. Yuen, B. Xie, Y. Yang, G. Chen, Z. Wu, L. Yixing, X. Zhou, W. Liu, S. Wang, K. Zhou, R. Shao, L. Nie, Y. Wang, J. Hao, J. Wang, and K. Shao. SPA-Bench: A comprehensive benchmark for smartphone agent evaluation. In *ICLR*, 2025b.

Q. Chen, D. Pitawela, C. Zhao, G. Zhou, H.-T. Chen, and Q. Wu. WebVLN: Vision-and-language navigation on websites. In *AAAI*, pp. 1165–1173, 2024.

K. Cheng, Q. Sun, Y. Chu, F. Xu, Y. Li, J. Zhang, and Z. Wu. SeeClick: Harnessing GUI grounding for advanced visual GUI agents. In *ACL*, pp. 9313–9332, 2024.

M. Davydova, D. Jeffries, P. Barker, A. M. Flores, and S. Ryan. OSUniverse: Benchmark for multimodal GUI-navigation AI agents. *arXiv*, 2025.

X. Deng, Y. Gu, B. Zheng, S. Chen, S. Stevens, B. Wang, H. Sun, and Y. Su. Mind2Web: Towards a generalist agent for the web. In *NeurIPS*, 2023.

Y. Deng, X. Zhang, W. Zhang, Y. Yuan, S.-K. Ng, and T.-S. Chua. On the multi-turn instruction following for conversational web agents. In *ACL*, pp. 8795–8812, 2024.

G. Gonzalez-Pumariega, V. Tu, C.-L. Lee, J. Yang, A. Li, and X. E. Wang. The unreasonable effectiveness of scaling agents for computer use. *arXiv*, 2025.

Z. Gu, Z. Zeng, Z. Xu, X. Zhou, S. Shen, Y. Liu, B. Zhou, C. Meng, T. Xia, W. Chen, Y. Wen, J. Dou, F. Tang, J. Lin, Y. Liu, Z. Guo, Y. Gong, H. Jia, C. Gao, Y. Guo, Y. Deng, Z. Guo, L. Chen, and W. Wang. UI-Venus technical report: Building high-performance UI agents with RFT. *arXiv*, 2025.

L. Guo, B. Zhu, Q. Tao, K. Liu, X. Zhao, X. Qin, J. Gao, and G. Hao. Agentic lybic: Multi-agent execution system with tiered reasoning and orchestration. *arXiv*, 2025a.

Y. Guo, T. Miao, Z. Wu, P. Cheng, M. Zhou, and Z. Zhang. Atomic-to-compositional generalization for mobile agents with a new benchmark and scheduling system. *arXiv*, 2025b.

S. Hong, M. Zhuge, J. Chen, X. Zheng, Y. Cheng, J. Wang, C. Zhang, Z. Wang, S. K. S. Yau, Z. Lin, L. Zhou, C. Ran, L. Xiao, C. Wu, and J. Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *ICLR*, 2024.

Y.-C. Hsiao, F. Zubach, G. Baechler, S. Sunkara, V. Carbune, J. Lin, M. Wang, Y. Zhu, and J. Chen. ScreenQA: Large-scale question-answer pairs over mobile app screenshots. In *NAACL-HLT*, pp. 9427–9452, 2025.

L. K. Jang, Y. Li, D. Zhao, C. Ding, J. Lin, P. P. Liang, R. Bonatti, and K. Koishida. VideoWebArena: Evaluating long context multimodal agents with video understanding web tasks. In *ICLR*, 2025.

F. Ji, J. Yang, Z. Song, Y. Wang, Z. Cui, Y. Li, Q. Jiang, M. Fang, and X. Chen. FineState-Bench: A comprehensive benchmark for fine-grained state control in GUI agents. *arXiv*, 2025.

R. Kapoor, Y. P. Butala, M. Russak, J. Y. Koh, K. Kamble, W. AlShikh, and R. Salakhutdinov. OmniACT: A dataset and benchmark for enabling multimodal generalist autonomous agents for desktop and web. In *ECCV*, pp. 161–178, 2024.

J. Y. Koh, R. Lo, L. Jang, V. Duvvur, M. C. Lim, P.-Y. Huang, G. Neubig, S. Zhou, R. Salakhutdinov, and D. Fried. VisualWebArena: Evaluating multimodal agents on realistic visual web tasks. In *ACL*, pp. 881–905, 2024.

J. Lee, D. Hahm, J. S. Choi, W. B. Knox, and K. Lee. MobileSafetyBench: Evaluating safety of autonomous agents in mobile device control. *arXiv*, 2024.

I. Levy, B. wiesel, S. Marreed, A. Oved, A. Yaeli, and S. Shlomov. ST-WebAgentBench: A benchmark for evaluating safety and trustworthiness in web agents. In *ICML 2025 Workshop on Computer Use Agents*, 2025.

K. Li, Z. Meng, H. Lin, Z. Luo, Y. Tian, J. Ma, Z. Huang, and T.-S. Chua. ScreenSpot-Pro: GUI grounding for professional high-resolution computer use. In *ICLR 2025 Workshop LLM Reason and Plan*, 2025.

W. Li, W. E. Bishop, A. Li, C. Rawles, F. Campbell-Ajala, D. Tyamagundlu, and O. Riva. On the effects of data scale on UI control agents. In *NeurIPS*, 2024.

E. Z. Liu, K. Guu, P. Pasupat, T. Shi, and P. Liang. Reinforcement learning on web interfaces using workflow-guided exploration. In *ICLR*, 2018.

G. Liu, P. Zhao, L. Liu, Z. Chen, Y. Chai, S. Ren, H. Wang, S. He, and W. Meng. LearnAct: Few-shot mobile GUI agent with a unified demonstration benchmark. *arXiv*, 2025.

X. Liu, B. Qin, D. Liang, G. Dong, H. Lai, H. Zhang, H. Zhao, I. L. Iong, J. Sun, J. Wang, J. Gao, J. Shan, K. Liu, S. Zhang, S. Yao, S. Cheng, W. Yao, W. Zhao, X. Liu, X. Liu, X. Chen, X. Yang, Y. Yang, Y. Xu, Y. Yang, Y. Wang, Y. Xu, Z. Qi, Y. Dong, and J. Tang. AutoGLM: Autonomous foundation agents for GUIs. *arXiv*, 2024.

J. Lu, S. An, M. Lin, G. Pergola, Y. He, D. Yin, X. Sun, and Y. Wu. Memochat: Tuning LLMs to use memos for consistent long-range open-domain conversation. *arXiv*, 2023.

Q. Lu, W. Shao, Z. Liu, L. Du, F. Meng, B. Li, B. Chen, S. Huang, K. Zhang, and P. Luo. GUIOdyssey: A comprehensive dataset for cross-app GUI navigation on mobile devices. In *ICCV*, 2025a.

Y. Lu, Q. Yu, H. Wang, Z. Liu, W. Su, Y. Liu, Y. Guo, M. Liang, Y. Wang, and H. Wang. TransBench: Breaking barriers for transferable graphical user interface agents in dynamic digital environments. In *Findings of ACL*, pp. 12464–12478, 2025b.

Z. Lu, J. Ye, F. Tang, Y. Shen, H. Xu, Z. Zheng, W. Lu, M. Yan, F. Huang, J. Xiao, and Y. Zhuang. UI-S1: Advancing GUI automation via semi-online reinforcement learning. *arXiv*, 2025c.

S. Nayak, X. Jian, K. Q. Lin, J. A. Rodriguez, M. Kalsi, R. Awal, N. Chapados, M. T. Özsu, A. Agrawal, D. Vazquez, C. Pal, P. Taslakian, S. Gella, and S. Rajeswar. UI-Vision: A desktop-centric GUI benchmark for visual perception and interaction. *arXiv*, 2025.

D. Nguyen, J. Chen, Y. Wang, G. Wu, N. Park, Z. Hu, H. Lyu, J. Wu, R. Aponte, Y. Xia, X. Li, J. Shi, H. Chen, V. D. Lai, Z. Xie, S. Kim, R. Zhang, T. Yu, M. M. Tanjim, N. K. Ahmed, P. Mathur, S. Yoon, L. Yao, B. Kveton, J. Kil, T. H. Nguyen, T. Bui, T. Zhou, R. A. Rossi, and F. Dernoncourt. GUI agents: A survey. In *Findings of ACL*, pp. 22522–22538, 2025.

J. Qian, Y. Ma, C. Lin, and L. Chen. Accelerating OCR-based widget localization for test automation of GUI applications. In *ASE*, pp. 1–13, 2022.

Y. Qin, Y. Ye, J. Fang, H. Wang, S. Liang, S. Tian, J. Zhang, J. Li, Y. Li, S. Huang, W. Zhong, K. Li, J. Yang, Y. Miao, W. Lin, L. Liu, X. Jiang, Q. Ma, J. Li, X. Xiao, K. Cai, C. Li, Y. Zheng, C. Jin, C. Li, X. Zhou, M. Wang, H. Chen, Z. Li, H. Yang, H. Liu, F. Lin, T. Peng, X. Liu, and G. Shi. UI-TARS: Pioneering automated GUI interaction with native agents. *arXiv*, 2025.

C. Rawles, A. Li, D. Rodriguez, O. Riva, and T. Lillicrap. Android in the wild: A large-scale dataset for Android device control. In *NeurIPS*, 2023.

C. Rawles, S. Clinckemaillie, Y. Chang, J. Waltz, G. Lau, M. Fair, A. Li, W. E. Bishop, W. Li, F. Campbell-Ajala, D. K. Toyama, R. J. Berry, D. Tyamagundlu, T. P. Lillicrap, and O. Riva. AndroidWorld: A dynamic benchmarking environment for autonomous agents. In *ICLR*, 2025.

Y. Shi, W. Yu, W. Yao, W. Chen, and N. Liu. Towards trustworthy GUI agents: A survey. *arXiv*, 2025.

N. Shinn, F. Cassano, A. Gopinath, K. Narasimhan, and S. Yao. Reflexion: Language agents with verbal reinforcement learning. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *NeurIPS*, 2023.

L. Song, Y. Dai, V. Prabhu, J. Zhang, T. Shi, L. Li, J. Li, S. Savarese, Z. Chen, J. Zhao, R. Xu, and C. Xiong. CoAct-1: Computer-using agents with coding as actions. *arXiv*, 2025.

L. Wang, Y. Deng, Y. Zha, G. Mao, Q. Wang, T. Min, W. Chen, and S. Chen. MobileAgentBench: An efficient and user-friendly benchmark for mobile LLM agents. In *MARW at AAAI 2025*, 2025a.

W. Wang, L. Dong, H. Cheng, X. Liu, X. Yan, J. Gao, and F. Wei. Augmenting language models with long-term memory. In *NeurIPS*, 2023.

X. Wang, Z. Wu, J. Xie, Z. Ding, B. Yang, Z. Li, Z. Liu, Q. Li, X. Dong, Z. Chen, W. Wang, X. Zhao, J. Chen, H. Duan, T. Xie, C. Yang, S. Su, Y. Yu, Y. Huang, Y. Liu, X. Zhang, Y. Zhang, X. Yue, W. Su, X. Zhu, W. Shen, J. Dai, and W. Wang. MMBench-GUI: Hierarchical multi-platform evaluation framework for GUI agents. *arXiv*, 2025b.

Z. Wang, H. Xu, J. Wang, X. Zhang, M. Yan, J. Zhang, F. Huang, and H. Ji. Mobile-Agent-E: Self-evolving mobile assistant for complex tasks. *arXiv*, 2025c.

J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. H. Chi, Q. V. Le, and D. Zhou. Chain-of-thought prompting elicits reasoning in large language models. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *NeurIPS*, 2022.

L. Wu, C. Wang, T. Liu, Y. Zhao, and H. Wang. From assistants to adversaries: Exploring the security risks of mobile LLM agents. *arXiv*, 2025.

Z. Wu, Z. Wu, F. Xu, Y. Wang, Q. Sun, C. Jia, K. Cheng, Z. Ding, L. Chen, P. P. Liang, and Y. Qiao. OS-ATLAS: A foundation action model for generalist GUI agents. *arXiv*, 2024.

T. Xie, D. Zhang, J. Chen, X. Li, S. Zhao, R. Cao, T. J. Hua, Z. Cheng, D. Shin, F. Lei, Y. Liu, Y. Xu, S. Zhou, S. Savarese, C. Xiong, V. Zhong, and T. Yu. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. In *NeurIPS*, 2024.

T. Xie, J. Deng, X. Li, J. Yang, H. Wu, J. Chen, W. Hu, X. Wang, Y. Xu, Z. Wang, Y. Xu, J. Wang, D. Sahoo, T. Yu, and C. Xiong. Scaling computer-use grounding via user interface decomposition and synthesis. *arXiv*, 2025.

T. Xu, L. Chen, D.-J. Wu, Y. Chen, Z. Zhang, X. Yao, Z. Xie, Y. Chen, S. Liu, B. Qian, A. Yang, Z. Jin, J. Deng, P. Torr, B. Ghanem, and G. Li. CRAB: Cross-environment agent benchmark for multimodal language model agents. In *Findings of ACL*, pp. 21607–21647, 2025.

J. Yang, H. Zhang, F. Li, X. Zou, C. Li, and J. Gao. Set-of-mark prompting unleashes extraordinary visual grounding in GPT-4V. *arXiv*, 2023.

P. Yang, H. Ci, and M. Z. Shou. macOSWorld: A multilingual interactive benchmark for GUI agents. *arXiv*, 2025a.

Q. Yang, H. Li, H. Zhao, X. Yan, J. Ding, F. Xu, and Y. Li. FingerTip 20K: A benchmark for proactive and personalized mobile LLM agents. *arXiv*, 2025b.

Y. Yang, D. Li, Y. Dai, Y. Yang, Z. Luo, Z. Zhao, Z. Hu, J. Huang, A. Saha, Z. Chen, R. Xu, L. Pan, S. Savarese, C. Xiong, and J. Li. GTA1: GUI test-time scaling agent. *arXiv*, 2025c.

S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. R. Narasimhan, and Y. Cao. ReAct: Synergizing reasoning and acting in language models. In *ICLR*, 2023.

C. Zhang, S. He, J. Qian, B. Li, L. Li, S. Qin, Y. Kang, M. Ma, G. Liu, Q. Lin, S. Rajmohan, D. Zhang, and Q. Zhang. Large language model-brained GUI agents: A survey. *TMLR*, 2025. ISSN 2835-8856.

H. H. Zhao, K. Yang, W. Yu, D. Gao, and M. Z. Shou. WorldGUI: An interactive benchmark for desktop GUI automation from any starting point. *arXiv*, 2025.

S. Zhou, F. F. Xu, H. Zhu, X. Zhou, R. Lo, A. Sridhar, X. Cheng, T. Ou, Y. Bisk, D. Fried, U. Alon, and G. Neubig. WebArena: A realistic web environment for building autonomous agents. In *ICLR*, 2024.