CAN I TRUST YOU MORE?
MODEL-AGNOSTIC HIERARCHICAL EXPLANATIONS

ABSTRACT

Interactions such as double negation in sentences and scene interactions in images are common forms of complex dependencies captured by state-of-the-art machine learning models. We propose `Mahé`, a novel approach to provide **M**odel-**a**gnostic **h**ierarchical **é**xplanations of how powerful machine learning models, such as deep neural networks, capture these interactions as either dependent on or free of the context of data instances. Specifically, `Mahé` provides context-dependent explanations by a novel local interpretation algorithm that effectively captures any-order interactions, and obtains context-free explanations through generalizing context-dependent interactions to explain global behaviors. Experimental results show that `Mahé` obtains improved local interaction interpretations over state-of-the-art methods and successfully provides explanations of interactions that are context-free.

1 INTRODUCTION

State-of-the-art machine learning models, such as deep neural networks, are exceptional at modeling complex dependencies in structured data, such as text (Vaswani et al., 2017; Tai et al., 2015), images (He et al., 2016; Huang et al., 2017), and DNA sequences (Alipanahi et al., 2015; Zeng et al., 2016). However, there has been no clear explanation on what type of dependencies are captured in the black-box models that perform so well (Ribeiro et al., 2018; Murdoch et al., 2018).

In this paper, we make one of the first attempts at solving this important problem through interpreting two forms of structures, i.e., context-dependent representations and context-free representations. A context-dependent representation is the one in which a model's prediction depends specifically on a data instance level (such as a sentence or an image). In order to illustrate the concept, we consider an example in image analysis. A yellow round-shape object can be identified as the sun or the moon given its context, either bright blue sky or dark night. A context-free representation is one where the representation behaves similarly independent of instances (i.e., global behaviors). In a hypothetical task of classifying sentiment in sentences, each sentence carries very different meaning, but when "not" and "bad" depend on each other, their sentiment contribution is almost always positive - i.e., the structure is context-free.

To investigate context-dependent and context-free structure, we lend to existing definitions in interpretable machine learning (Ribeiro et al., 2016; Kim et al., 2018). A context-dependent interpretation is a local interpretation of the dependencies at or within the vicinity of a single data instance. Conversely, a context-free interpretation is a *global* interpretation of how those dependencies behave in a model irrespective of data instance. In this work, we study a key form of dependency: an *interaction* relationship between the prediction and input features. Interactions can describe arbitrarily complex relationships between these variables and are commonly captured by state-of-the-art models like deep neural networks (Tsang et al., 2018; Murdoch et al., 2018). Interactions which are context-dependent or context-free are therefore local or global interactions, respectively.

We propose `Mahé`, a framework for explaining the context-dependent and context-free structures of any complex prediction model, with a focus on explaining neural networks. The context-dependent explanations are built based on recent work on local intepretations (such as (Ribeiro et al., 2016; Murdoch et al., 2018; Singh et al., 2018)). Specifically, `Mahé` takes as input a model to explain and a data instance, and returns a hierarchical explanation, a format proposed by Singh et al. (2018) to show local group-variable relationships used in predictions (Figure 1). To provide context-free

Figure 1: An overview of the steps used to obtain a context-dependent hierarchical explanation. Step 1 inputs a data instance of interest (e.g. a sentence) into a complex model, in this case a classifier. Step 2 locally perturbs the data instance and obtains their predictions results from the model. Instead of only fitting a linear model as linear LIME does to the perturbed samples and outputs, Mahé fits a neural network to them to learn the highly nonlinear decision boundary used to classify the instance. The nonlinearity indicates that there should be an interaction between variables, and an interpretation of the neural network is used to extract the interactions (Tsang et al., 2018). Attribution scores of those interactions can then be shown for the data instance, as displayed in Step 3.

explanations, Mahé generalizes those context-dependent interactions with consistent behavior in a model and determines whether a local representation in the model is responsible for the global behavior. In this case, Mahé takes as input a model and representative data corresponding to an interaction of interest and returns whether or not that interaction is context-free. We conduct experiments on both synthetic datasets and real-world application datasets, which shows that Mahé's context-dependent explanations can significantly outperform state-of-the-art methods for local interaction interpretation, and Mahé is capable of successfully finding context-free explanations of interactions. In addition, we identify promising cases where the methodology for context-free explanations can successfully edit models. Our contributions are as follows: 1) Mahé achieves the task of improved context-dependent explanations based on interaction detection and fitting performance and model-agnostic generality, compared to state-of-the-art methods for local interaction interpretation, 2) Mahé is the first to provide context-free explanations of interactions in deep learning models, and 3) Mahé provides a promising direction for modifying context-free interactions in deep learning models without significant performance degradation.

2 RELATED WORKS

Attribution Interpretability: A common form of interpretation is feature attribution, which is concerned with how features of a data instance contribute to a model output. Within this category, there are two distinct approaches: additive and sensitivity attribution. Additive attribution interprets how much each feature contributes to the model output when these contributions are summed. In contrast, sensitivity attribution interprets how sensitive a model output is to changes in features. Examples of additive attribution techniques include LIME (Ribeiro et al., 2016) and CD (Murdoch et al., 2018). Examples of sensitivity attribution methods include Integrated Gradients (Sundararajan et al., 2017), DeepLIFT (Shrikumar et al., 2017), and SmoothGrad (Smilkov et al., 2017). Unlike previous approaches, Mahé provides additive attribution interpretations that consist of *non-additive groups* of variables (interactions) in addition to the normal additive contributions of each variable.

Interaction Interpretability: An interaction in its generic form is a non-additive effect between features on an outcome variable. Only until recently has there been development in interpreting non-additive interactions despite often being learned in complex machine learning models. The difficulty interpreting non-additive interactions stems from their lack of exact functional identity compared to, for example, a multiplicative interaction. Methods that exist to interpret non-additive interactions are NID (Tsang et al., 2018) and Additive Groves (Sorokina et al., 2008). In contrast, many more methods exist to interpret specific interactions, namely multiplicative ones. Notable methods include CD (Murdoch et al., 2018), Tree-Shap (Lundberg & Lee, 2017), and GLMs with multiplicative interactions (Purushotham et al., 2014). Unlike previous methods, our approach provides local interpretations of the more challenging *non-additive interaction*.

Locally Interpretable Model-Agnostic Explanations (LIME): LIME (Ribeiro et al., 2016) is a very popular type of model interpretation. Its popularity comes from additive attribution interpretations to explain the output of *any* prediction model. The original and most popular version of LIME uses a linear model to approximate model predictions in the local vicinity of a data instance. Since its introduction, variants of LIME have been proposed, for example Anchors (Ribeiro et al., 2018)

and LIME-SUP (Hu et al., 2018). While Anchors generates a form of context-free explanation, its method of selecting fully representative features for a prediction does not consider interactions. For example, Anchors assumes that (not, bad) "virtually guarentees" a sentiment prediction to be positive, whereas in Mahé this is not necessarily true; only their *interaction* is positive (See Table 6 for an example). LIME-SUP touches upon interactions but does not study their interpretation.

3 INTERACTION EXPLANATIONS

Let $f(\cdot)$ be a target function (model) of interest, e.g. a classifier, and $\phi(\cdot)$ be a local approximation of f and is interpretable in contrast to f. A common choice for ϕ is a linear model, which is interpretable in each linear term. Namely, for an data instance $\mathbf{x} \in \mathbb{R}^p$, weights $\mathbf{w} \in \mathbb{R}^p$ and bias b, interpretations are given by $w_i x_i$, known as *additive attributions* (Lundberg & Lee, 2017) from

$$\phi(\mathbf{x}) = \sum_{i=1}^{p} w_i x_i + b. \tag{1}$$

Given a set of n data points $\{\mathbf{x}^{(i)}\}_{i=1}^n$ that are infinitesimally close or local to $\mathbf{x}$, a linear approximation of $\mathcal{D} = \{(\mathbf{x}^{(1)}, f(\mathbf{x}^{(1)})), \ldots, (\mathbf{x}^{(n)}, f(\mathbf{x}^{(n)}))\}$ will accurately fit to the functional surface of f at the data instance, such that $\phi(\mathbf{x}) = f(\mathbf{x})$. Because it is possible in such scenarios that $\phi(\mathbf{x}) = f(\mathbf{x}) \approx b$, there must be some nonzero distances between $\mathbf{x}$ and $\mathbf{x}^{(i)}$ to obtain informative attribution scores. LIME, as it was originally proposed, uses a linear approximation as above where samples are generated in a nonzero local vicinity of $\mathbf{x}$ (Ribeiro et al., 2016). The drawback of linear LIME is that there is often an error $\epsilon = |f(\mathbf{x}) - \phi(\mathbf{x})| > 0$.

For complex models f, the functional surface at $\mathbf{x}$ can be nonlinear. Because $\mathcal{D}$ consists of $\mathbf{x}^{(i)}$ with distance $d > 0$ from $\mathbf{x}$, a closer fit to $f(\mathbf{x})$ in its nonlinear vicinity, i.e. $\{f(\mathbf{x}^{(i)})\}_{i=1}^n$, can be achieved with the following generalization of Eq. 1:

$$\phi(\mathbf{x}) = \sum_{i=1}^{p} g_i(x_i) + b, \tag{2}$$

where $g_i(\cdot)$ can be any function, for example one that is arbitrarily nonlinear. This function is called a generalized additive model (GAM) (Hastie & Tibshirani, 1990), and now attribution scores can be given by $g_i(x_i)$ for each feature i. For the purposes of interpreting individual feature attribution, the GAM may be enough. However, if we would like broader explanations, we can also obtain non-additive attributions or interactions between variables (Lou et al., 2013), which can provide an even better fit to the complex local vicinity. Augmenting Eq. 2 with interactions yields:

$$\phi_K(\mathbf{x}) = \sum_{i=1}^{p} g_i(x_i) + \sum_{i=1}^{K} g_i'(\mathbf{x}_\mathcal{I}) + b, \tag{3}$$

where $g_i'(\cdot)$ can again be any function, $\mathbf{x}_\mathcal{I} \in \mathbb{R}^{|\mathcal{I}|}$ are interacting variables corresponding to the variable indices $\mathcal{I}$, and $\{\mathcal{I}_i\}_{i=1}^K$ is a set of K interactions. Attribution scores are now generated from both g_i' and g_i'. In this paper, we learn g_i and g_i' using Multilayer Perceptrons (MLPs). ϕ or ϕ_K can be converted to classification by applying a sigmoid function.

Adding interactions that are truly present in the local vicinity augments the representational capacity of $\phi_K(\mathbf{x})$ to fit the vicinity. This is due to how non-additive interactions are defined: $\mathcal{I}$ corresponds to non-additive interacting features iff $g'(\cdot)$ (Eq. 3) cannot be decomposed into a sum of $|\mathcal{I}|$ arbitrary subfunctions δ, each not depending on a corresponding interacting variable (Tsang et al., 2018), i.e.

$$g'(\mathbf{x}_\mathcal{I}) \neq \sum_{i \in \mathcal{I}} \delta_i(\mathbf{x}_{\mathcal{I} \setminus \{i\}}).$$

4 Mahé FRAMEWORK

In this section, we introduce our Mahé framework, which can provide context-dependent and context-free explanations of interactions. To provide context-dependent explanations, we propose to use a two-step procedure that first identifies what variables interact locally, then learns a model of interactions (as Eq. 3) to provide a local interaction score at the data instance in question. The procedure of first detecting interactions then building non-additive models for them has been studied previously (Lou et al., 2013; Tsang et al., 2018); however, previous works have not focused on using the same non-additive models to provide local interaction attribution scores, which enable us to visualize interactions of any size as demonstrated later in §5.2.3.

4.1 Context-Dependent Explanations

Local Interaction Detection: To perform interaction detection on samples in the local vicinity of data instance $\mathbf{x}$, we first sample n points in the ϵ-neighborhood of $\mathbf{x}$ with a maximum neighborhood distance ϵ under a distance metric d. While the choice of d depends on the feature type(s) of $\mathbf{x}$, we always set $\epsilon = \sigma$, 1 standard deviation from the mean of a Gaussian weighted sampling kernel. When all features are continuous, neighborhood points are sampled with mean $\mathbf{x} \in \mathbb{R}^p$ and $d = \ell_2$ to generate $\mathbf{x}^{(1)}, \ldots, \mathbf{x}^{(n)}$, $\mathbf{x}^{(i)} \sim \mathcal{N}(\mathbf{x}, \sigma^2 \mathbf{I})$, where $\mathcal{N}$ is a normal distribution truncated at ϵ. When features are categorical, they are converted to one-hot binary representation. For $\mathbf{x}$ of binary features, we sample each point around $\mathbf{x}$ by first selecting a number of random features to flip (or perturb) from a uniform distribution between 0 and $\min(p, \epsilon')$. The max number of flips ϵ' is derived from ϵ for a distance metric that is usually cosine distance (Ribeiro et al., 2016). Distances between local samples and $\mathbf{x}$ are then weighted by a Gaussian kernel to become sample weights (e.g. the frequency each sample appears in the sampled dataset).[1] For context-dependent explanations, the exact choice of σ depends on the stability and interaction orders of explanations. The interaction orders may become too large and uninformative because the local vicinity area covers too much complex representation from $f(\cdot)$. Thus we recommend tuning σ to the task at hand.

Our framework is flexible to any interaction detection method that applies to the dataset $\mathcal{D} = \{(\mathbf{x}^{(1)}, f(\mathbf{x}^{(1)})), \ldots, (\mathbf{x}^{(n)}, f(\mathbf{x}^{(n)}))\}$. Since we seek to detect non-additive interactions, we use the neural interaction detection (NID) framework (Tsang et al., 2018), which interprets learned neural network weights to obtain interactions. To the best of our knowledge, this detection method is the only polynomial-time algorithm that accurately ranks any-order non-additive interactions after training one model, compared to alternative methods that must train an exponential number $O(2^p)$ of models. The basic idea of NID is to interpret an MLP's accurate representation of data to accurately identify the statistical interactions present in this data. Because MLPs learn interactions at nonlinear activation functions, NID performs feature interaction detection by tracing high-strength ℓ_1-regularized weights from features to common hidden units. In particular, NID efficiently detects any-order interactions by first assuming each first layer hidden unit in a trained MLP captures at most one interaction, then NID greedily identifies these interactions and their strengths through a 2D traversal over the MLP's input weight matrix, $\mathbf{W} \in \mathbb{R}^{p \times h}$. The result is that instead of testing for interactions by training $O(2^p)$ models, now only $O(1)$ models and $O(ph)$ tests are needed.

In addition to its efficiency, applying NID to our framework Mahé has several advantages. One is the universal approximation capabilities of MLPs (Hornik, 1991), allowing them to approximate arbitrary interacting functions in the potentially complex local vicinity of $f(\mathbf{x})$. Another advantage is the independence of features in the sampled points of $\mathcal{D}$. Normally, interaction detection methods cannot identify high interaction strengths involving a feature that is correlated with others because interaction signals spread and weaken among correlated variables (Sorokina et al., 2008). Without facing correlations, NID can focus more on interpreting the data-generating function, the target model f. One disadvantage of our application of NID is the curse of dimensionality for MLPs when p is large (e.g. $p > n$) (Theodoridis et al., 2008), which is oftentimes the case for images. In general, large input dimensions should be reduced as much as possible to avoid overfitting. For images, p is normally reduced in model-agnostic explanation methods by using segmented aggregations of pixels called superpixels as features (Ribeiro et al., 2016; Lundberg & Lee, 2017; Ribeiro et al., 2018).

Hierarchical Interaction Attributions: Upon obtaining an interaction ranking from NID, GAMs with interactions (Eq. 3) can be learned for different top-K interactions ranked by their strengths (Tsang et al., 2018). In the Mahé framework, there are $L + 1$ different levels of a *hierarchical explanation* which constitutes our context-dependent explanation. $K = 0$ in the first level without interaction explanations, and $K = L$ in the last level. When presenting the hierarchy such as Figure 1 Step 3, the first level shows the additive attributions of individual features from by a trained $\phi(\cdot)$ in Eqs. 1 or 2, such as the explanation from linear LIME. Subsequently, the parameters $\mathbf{w}$ of $\phi(\cdot; \mathbf{w}, b)$ are frozen before interaction models are added to construct $\phi_K(\cdot)$ in Eq. 3. The next levels of the hierarchy can be presented either as the interaction attribution of $g'_K(\cdot)$ as in Figure 1 or

---

[1] In cases where features are a mixture of continuous and one-hot categorical variables, a way of sampling points is to adapt the approach for binary features to handle the mixture of feature types (Ribeiro et al., 2016). The main difference now is that continuous features are drawn from a uniform distribution truncated at σ and are standard scaled to have similar magnitudes as the binary features. Since continuous features are present, d can be ℓ_2 distance, then a Gaussian kernel can be applied to sample distances as before.

those of $\{g'_i(\cdot)\}_{i=1}^K$ (Eq. 3), where at each level K is increased and $\{g'_i(\cdot)\}_{i=1}^K$, bias b are retrained. The practice of training interaction models g'_i on the residual of ϕ is used to prevent degeneracy of univariate functions in ϕ in the presence of any overlapping interaction functions (Lou et al., 2013). Since ϕ_K is trained at each hierarchical level on $\mathcal{D}$, the fit of each ϕ_K can also be explained via predictive performance, such as R^2 performance in Figure 1 Step 3. The stopping criteria for the number of hierarchical levels can depend on the predictive performance or user preference.

4.2 CONTEXT-FREE EXPLANATIONS

In order to provide context-free explanations, we propose determining whether the local interactions assumed to be context-dependent in §4.1 can generalize to explain global behavior in f. To this end, we first define ideal conditions for which a generic local explanation can generalize. For choosing distance metric d and sampling points in the local vicinity of $\mathbf{x}$, please refer to §4.1 and our considerations for generalizing explanations at the end of this section.

Definition 1 (Generalizing Local Explanations). *Let $f(\cdot)$ be the model output we wish to explain, and $\mathcal{X}_f$ be the data domain of f. Let a local explanation of f at $\mathbf{x} \in \mathcal{X}_f$ be some explanation E that is true for $f(\mathbf{x})$ and depends on samples $\mathbf{x}_\ell \in \mathcal{X}_f$ that are only in the local vicinity of $\mathbf{x}$, i.e. $d(\mathbf{x}, \mathbf{x}_\ell) \leq \epsilon$ provided a distance metric d and distance $\epsilon \geq 0$. The local explanation E is a global explanation if the following two conditions are met: 1) Explanation E is true for f at all data samples in $\mathcal{X}_f$, including samples outside the local vicinity of $\mathbf{x}$, i.e. all samples $\mathbf{x}_g \in \mathcal{X}_f$ satisfying $d(\mathbf{x}, \mathbf{x}_g) > \epsilon$. 2) There exists a sample $\mathbf{x}' \in \mathcal{X}_f$ and a local modification to $f(\mathbf{x}')$ (modifying $f(\mathbf{x}_\ell)$ in the vicinity $d(\mathbf{x}', \mathbf{x}_\ell) \leq \epsilon$) that changes E for all samples in $\mathcal{X}_f$ while still meeting condition 1).*

For example, consider a simple linear regression model we wish to explain, $f(\mathbf{x}) = w_1 x_1 + w_2 x_2$. Let its local explanation be the feature attributions $w_1 x_1$ and $w_2 x_2$. This local explanation is a global explanation because 1) for all values of x_1 and x_2, the feature attributions are still $w_1 x_1$ and $w_2 x_2$, and 2) if any of the weights are changed, e.g. $w_1 \to w'_1$, the attribution explanation will change, but the feature attributions are still $w'_1 x_1$ and $w_2 x_2$ for all values of x_1 and x_2.

Our context-free explanation of interaction $\mathcal{I}$ is: whenever local interaction $\mathcal{I}$ exists, its attribution will in general have the same polarity (or sign). Since it is impossible to empirically prove that a local explanation is true for all data instances globally (via Definition 1), this work is focused on providing *evidence* of context-free interactions. This evidence can be obtained by checking whether our explanation is consistent with the two conditions from Definition 1 for the interaction of interest $\mathcal{I}$: 1) For representative data instances in the domain of f, if local interaction $\mathcal{I}$ exists, does it always have the same attribution polarity? The representative data instances should be separated from each other at an average distance beyond ϵ. 2) Can local interaction $\mathcal{I}$ at a single data instance $\tilde{\mathbf{x}}$ be used to negate $\mathcal{I}$'s attribution polarity for all representative data instances where $\mathcal{I}$ exists?

The advantage of checking the response of f to local modification is determining whether global explanations found emperically in 1) are more than just coincidence as oftentimes only a limited number of representative data instances are available to test on. We propose to modify an interaction attribution of the model's output $f(\mathbf{x})$ at data instance $\mathbf{x}$ by utilizing a trained model $g'_k(\mathbf{x}_\mathcal{I})$ of interaction $\mathcal{I}_k$, where $1 \leq k \leq K$ (Eq. 3). Let $\tilde{g}'_k(\cdot)$ be a modified version of $g'_k(\cdot)$. We can then define a modified form of Eq. 3:

$$\tilde{\phi}_k(\mathbf{x}) = \phi(\mathbf{x}) + \tilde{g}'_k(\mathbf{x}_\mathcal{I}) + \sum_{i=1, i \neq k}^K g'_i(\mathbf{x}_\mathcal{I}). \quad (4)$$

Without retraining $\tilde{\phi}_k(\cdot)$, we use $\tilde{\phi}_k$ and the same local vicinity $\{\mathbf{x}^{(i)}\}_{i=1}^n$ in $\mathcal{D}$ to generate a new dataset $\tilde{\mathcal{D}} = \{(\mathbf{x}^{(1)}, \tilde{\phi}_k(\mathbf{x}^{(1)})), \ldots, (\mathbf{x}^{(n)}, \tilde{\phi}_k(\mathbf{x}^{(n)}))\}$. Finally, we can modify the interaction attribution of $f(\mathbf{x})$ by fine-tuning $f(\cdot)$ on dataset $\tilde{\mathcal{D}}$. In this paper, we modify interactions by negating them: $\tilde{g}'_k(\cdot) = -cg'_k(\cdot)$, where $-c$ negates the interaction attribution with a specified magnitude c.

Figure 2: An illustration of the hypothesis that certain local interactions, which are similar (left), are represented at a common manifold (right) in a model.

How can modifying a local interaction affect interactions outside its local vicinity? This would suggest that the manifold hypothesis is true for $f(\cdot)$'s representations of these interactions (Figure 2). The manifold hypothesis states that similar data lie near a low-dimensional manifold in a high-dimensional space (Turk & Pentland, 1991; Lee et al., 2003; Cayton,

2005). Studies have suggested that the hypothesis applies to the data representations learned by neural networks (Rifai et al., 2011; Basri & Jacobs, 2016). The hypothesis is frequently used to visualize how deep networks represent data clusters (Maaten & Hinton, 2008; LeCun et al., 2015), and it has been applied to representations of interactions (Reed et al., 2014), but not for neural networks.

Part of our objective is to generalize our explanation as much as possible. In the case of language-related tasks, we additionally generalize based on our meaning of a local interaction and the distance metric we use, d. In this paper, local interactions for language tasks do not have word interactions fixed to specific positions; instead, these interactions are only defined by the words themselves (the interaction values) and their positional order. For example, the ("not", "bad") interaction would match in the sentences: "this is not bad" and "this does not seemed to be that bad". For comparing texts and measuring the size of local vicinities, we use Levenshtein (edit) distance (Levenshtein, 1966), which allows us to compare sentences with different word counts. [2]

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

We evaluate the effectiveness of Mahé first on synthetic data and then on four real-world datasets. To evaluate context-dependent explanations of Mahé, we first evaluate the accuracy of Mahé at local interaction detection and modeling on the outputs of complex base models trained on synthetic ground truth interactions. We compare Mahé to Shap-Tree (Lundberg et al., 2018), ACD-MLP (Singh et al., 2018), and ACD-LSTM (Murdoch et al., 2018; Singh et al., 2018), which are local interaction modeling baselines for the respective models they explain: XGBoost (Chen & Guestrin, 2016), multilayer perceptrons (MLP), and long short-term memory networks (LSTM) (Hochreiter & Schmidhuber, 1997). $p = 10$ for synthetic data (Table 2).

In all other experiments, we study Mahé's explanations of state-of-the-art level models trained on real-world datasets. The state-of-the-art models are: 1) DNA-CNN, a 2-layer 1D convolutional neural network (CNN) trained on MYC-DNA binding data [3] (Mordelet et al., 2013; Yang et al., 2013; Alipanahi et al., 2015; Zeng et al., 2016; Wang et al., 2018), 2) Sentiment-LSTM, a 2-layer bi-directional LSTM trained on the Stanford Sentiment Treebank (SST) (Socher et al., 2013; Tai et al., 2015), 3) ResNet152, an image classifier pretrained on ImageNet '14 (Russakovsky et al., 2015; He et al., 2016), and 4) Transformer, a machine translation model pretrained on WMT-14 En→ Fr (Vaswani et al., 2017; Ott et al., 2018).

Table 1: Average p of test set samples used to evaluate Mahé's explanations of target models. *Superpixels are used to reduce the dimensionality of images (§4.1). †For Transformer, p and the dataset (Merity et al., 2016) are based on experimental design (§5.3).

models	dataset	average p
DNA-CNN	MYC-DNA	36
Sentiment-LSTM	SST	15.9 ± 7.0
ResNet152*	ImageNet '14	30.2 ± 1.4
Transformer†	WikiText-103	11.8 ± 2.3

Avg. p for our context-dependent evaluations, similar to our context-free tests, are shown in Table 1.

The following hyperparameters are used in our experiments. We use $n = 1k$ local-vicinity samples in $\mathcal{D}$ for synthetic experiments and $n = 5k$ for experiments explaining models of real-world datasets, with 80%-10%-10% train-validation-test splits to train and evaluate Mahé. The distance metrics for vicinity size are: ℓ_2 distance for synthetic experiments, cosine distance for DNA-CNN and ResNet152, and Levenshtein distance for Sentiment-LSTM and Transformer. We use on-off superpixel and word approaches to binary feature representation for explaining ResNet152 and Sentiment-LSTM respectively (Ribeiro et al., 2016; Lundberg & Lee, 2017), and the other experiments for real-world datasets use perturbation distributions that randomly perturbs features to belong to the same categories of original features, as in (Ribeiro et al., 2018). The superpixel segmenter we use is quick-shift (Vedaldi & Soatto, 2008; Ribeiro et al., 2016).

For the hyperparameters of the neural networks in Mahé, we use MLPs with 50-30-10 first-to-last hidden layer sizes to perform interaction detection in the NID framework (Tsang et al., 2018). These MLPs are trained with ℓ_1 regularization $\lambda_1 = 5e-4$. The learning rate used is always $5e-3$ except for Transformer experiments, whose learning rate of $5e-4$ helped with interaction detection under highly unbalanced output classes. The MLP-based interaction models in the GAM (Eq. 3)

---

[2]Unfortunately, for image-related tasks, we could not generalize our definition of local interactions despite the translation invariance of deep convnets.

[3]The motif and flanking regions of DNA sequences in the training set are shuffled to simulate unalignment.

(a) interaction fit (std. MSE; lower is better)   (b) interaction detection (R-precision; higher is better)

Figure 3: Results of synthetic experiments with Mahé and different baselines explaining base models XGBoost (tree), MLP, LSTM trained on F_{1-4} (Table 2) at $\sigma = 0.6$ (max$= 3.2$) are shown. (a) shows the average local fit in MSE of Mahé and baselines on the base models' representations of respective interactions. (b) shows the average R-precision of interaction rankings from each baseline. *Shap-Tree cannot detect or fit to a three-way interaction. †We assume interaction order is unknown, and ACD-MLP and ACD-LSTM require exhaustive search of all possible interactions.

always have architectures of 30-10. They are trained with ℓ_2 regularization of $\lambda_2 = 1e{-}5$ and learning rate of $1e{-}3$. Because learning GAMs can be slow, we make a linear approximation of the univariate functions in Eq. 3, such that $g_i(x_i) = x_i$. This approximation also allows us to make direct comparisons between Mahé and linear LIME, since x_i is exactly the linear part (Eq. 1). All neural networks train with early stopping, and Level $L + 1$ is decided where validation performance does not improve more than 10% with a patience of 2 levels. c ranges from 3 to 4 in our experiments.

5.2 CONTEXT-DEPENDENT EXPLANATIONS

5.2.1 SYNTHETIC EXPERIMENTS

In order to evaluate Mahé's context-dependent explanations, we first compare them to state-of-the-methods for local interaction interpretation. A standard way to evaluate the accuracy of interaction detection and modeling methods has been to experiment on synthetic data because ground truth interactions are generally unknown in real-world data (Hooker, 2004; Sorokina et al., 2008; Lou et al., 2013; Tsang et al., 2018). Similar to Hooker (2007), we evaluate interactions in a subset region of a synthetic function

Table 2: Data generating functions with interactions

$F_1(\mathbf{x}) =$	$10x_1x_2 + \sum_{i=3}^{10} x_i$
$F_2(\mathbf{x}) =$	$x_1x_2 + \sum_{i=3}^{10} x_i$
$F_3(\mathbf{x}) =$	$\exp(|x_1 + x_2|) + \sum_{i=3}^{10} x_i$
$F_4(\mathbf{x}) =$	$10x_1x_2x_3 + \sum_{i=4}^{10} x_i$

domain. We generate synthetic data using functions $F_1 - F_4$ (Table 2) with continuous features uniformly distributed between -1 to 1, train complex base models (as specified in §5.1) on this data, and run different local interaction interpretation methods on 10 trials of 20 data instances at randomly sampled locations on the synthetic function domain. Between trials, base models with different random initializations are trained to evaluate the stability of each interpretation method. We evaluate the performance of fitting to ground truth interactions by first assuming the true interacting variables are known, then computing the Mean Squared Error (MSE) between the predicted interaction attribution of each interpretation method and the ground truth at 1000 uniformly drawn locations within the local vicinity of a data instance, averaged over all randomly sampled data instances and trials (Figure 3a). We also evaluate the interaction detection performance of each method by comparing the average R-precision (Manning et al., 2008) of their interaction rankings across the same sampled data instances (Figure 3b). R-precision is the percentage of the top-R items in a ranking that are correct out of R, the number of correct items. Since $F_1 - F_4$ only ever have 1 ground truth interaction, R is always 1. Compared to Shap-Tree, ACD-MLP, and ACD-LSTM, the Mahé framework is the only one capable of detection *and* fitting, and it is the only model-agnostic approach.

5.2.2 EVALUATING ON REAL-WORLD DATA

In this section, we demonstrate our approaches to evaluating Mahé's context-dependent explanations on real-world data. We first evaluate the prediction performance of Mahé on the test set of $\mathcal{D}$ as interactions are added in Eq. 3, i.e. K increases. For a given value of σ, we run Mahé 10 times on each of 40 randomly selected data instances from the test sets associated with DNA-CNN, Sentiment-LSTM, and ResNet152. For Transformer, performance is examined on a specific grammar (*cet*) translation, to be detailed in §5.3. The local vicinity samples and model initializations in Mahé are randomized in every trial. We average prediction error over different σ: $0.4\sigma'$, $0.6\sigma'$, $0.8\sigma'$, and $1.0\sigma'$, where σ' is the average pairwise distance between data instances in respective test sets. Results are shown in Table 3 for K starting from 0, which is linear LIME, and increasing to the last hierarchical level L. Including interactions results in significant performance improvements.

Table 3: Average prediction performance (lower is better; 1-AUC for Transformer, MSE otherwise) with ($K > 0$) and without ($K = 0$) interactions for random data instances in the test sets of respective base models. Only results with detected interactions are shown. For each model, at least 80% of all tested data instances possessed interactions, yielding ≥ 1280 instances for each performance statistic.

	K	DNA-CNN	Sentiment-LSTM	ResNet152	Transformer
linear LIME	0	$8.8e{-}3 \pm 8.1e{-}4$	$8.6e{-}2 \pm 6.1e{-}3$	0.24 ± 0.059	0.23 ± 0.080
Mahé	1	$8e{-}3 \pm 1.1e{-}3$	$4.5e{-}2 \pm 6.8e{-}3$	0.20 ± 0.055	0.05 ± 0.016
Mahé	L	$6e{-}3 \pm 1.1e{-}3$	$1.9e{-}2 \pm 5.5e{-}3$	0.14 ± 0.047	0.05 ± 0.015

(a) Explanation A of negative prediction (b) Explanation B of negative prediction

Figure 4: Example of explanations that Mechanical Turk users choose from for a sentiment analysis task. (a) is linear LIME, (b) is Mahé. LIME explanations are shown as positive and negative contributions of each feature (word) to the prediction, and Mahé explanations are shown similarly with one of the contributions belonging to a single interaction or group of words.

An alternative approach to evaluating Mahé is to determine out of LIME and Mahé explanations, could human evaluators have a preference towards Mahé explanations? We recruit a total of 60 Amazon Mechanical Turk users to participate in comparing explanations of Sentiment-LSTM predictions. While the presented LIME explanations are standard, we adjust Mahé to only show the $K = 1$ interaction and merge its attribution with those of subsumed features to make the difference between LIME and Mahé subtle (Figure 4). We present evaluators with explanations for randomly selected test sentences under the main condition that these sentences must have a detected interaction, which was the case for $> 95\%$ of sentences. In total, there are explanations for 40 sentences, each of which is examined by 5 evaluators, and a majority vote of their preference is taken. Each evaluator is only allowed to pick between explanations for a maximum of 4 sentences. For the other conditions used to select which sentences to show evaluators and more examples like Figure 4, please see Appendix B. The result of this experiment is that the majority of preferred explanations (65%, $p = 0.029$) is with interactions, supporting their inclusion in hierarchical explanations.

5.2.3 HIERARCHICAL EXPLANATIONS

Examples of context-dependent hierarchical explanations for ResNet152, Sentiment-LSTM, and Transformer are shown in Figure 6, Table 6, and Appendix E respectively after page 9.

5.3 CONTEXT-FREE EXPLANATIONS

In this section, we show examples of context-free explanations of interactions found by Mahé. We first study the context-free interactions learned by Sentiment-LSTM. To have enough sentences for this evaluation, we use data from IMDB movie reviews (Maas et al., 2011) in addition to the test set of SST. Based on our results (Figure 5), we observe that the polarities of certain local interactions are almost always the same, where the words of matching interactions can be separated by any number of words in-between. To ensure that this global behavior is not a coincidence, we modify local interaction behavior in Sentiment-LSTM to check for a global change in this behavior (§4.2). As a result, when the model's local interaction attribution at a *single data instance* is negated, the attribution is almost always the opposite sign for the rest of the sentences. A notable insight about Sentiment-LSTM is that it appears to

Figure 5: Interaction polarity consistency in Sentiment-LSTM before and after model modification. (mean and std. errors shown)

Table 4: *cet* interactions before and after modifying Transformer. N_s is number of samples, and %*cet* is % of N_s samples $+$ or $-$ contributing to *cet*.

	Before modifying		After modifying	
Interaction	N_s	%*cet* $+$	N_s	%*cet* $-$
(this, event)	38	1.0	39	1.0
(this, article)	33	1.0	34	1.0
(this, incident)	31	1.0	29	0.93
(this, album)	24	1.0	40	1.0
(this, arrangement)	22	1.0	36	1.0
(that, afternoon)	22	1.0	27	1.0
(this, location)	20	1.0	22	0.95
(this, effect)	19	1.0	20	0.95

Table 5: Examples of En.-Fr. translations before and after modifying Transformer. Interacting elements are bolded. BLEU change is the % change in test BLEU score from modifying the bolded interaction in Transformer.

	Sample English-French Translations	BLEU change
English	**This event** took place on 10 August 2008.	
Fr. before	**Cet** événement a eu lieu le 10 Mars 2008.	
Fr. after	Cette rencontre a eu lieu le 10 Mars 2008.	(-3.7%)
English	**This incident** made it into the music video.	
Fr. before	**Cet** incident a été intégré dans le vidéo musical.	
Fr. after	C'est pas mal du tout ca!	(-3.4%)
English	The initial language of **this article** was French.	
Fr. before	La langue initiale de **cet** article était le Français.	
Fr. after	La langue originale du présent article était le Français.	(-2.8%)

represent (too, bad) and (only, worse) as globally positive sentiments, and Mahé's modification in large part rectifies this misbehavior (Figure 5). The modifications to Sentiment-LSTM only cause an average reduction of 1.5% test accuracy, indicating that the original learned representation stays largely intact. Results for $\sigma = 16$ are shown with the average pairwise edit distance between sentences being $\sigma' = 24.8$. Words in detected interactions are separated by 1.3 words on average.

Next, we study the possibility of identifying context-free interactions in Transformer on a known form of interaction in English-to-French translations: translations into a special French word for "this" or "that", *cet*, which only appears when the noun it modifies begins with a vowel. Some examples of *cet* interactions are (this, event), (this, article), and (this, incident), whose nouns have the same starting vowels in French. For out explanation task, the *presence* of *cet* is used as the prediction variable in local interaction extraction. To minimize the sources of *cet*, we limit original sentence lengths to 15 words. We modify Transformer (§4.2) through differentiating the max value of the *cet* output neurons over all translated words, and to have enough sentences, we perform translations on WikiText-103 (Merity et al., 2016). The results of context-free experiments on *cet* interactions of adjacent English words are shown in Table 4. The interactions always have positive polarities towards *cet*, and after modifying Transformer at a single data instance for a given interaction, its polarity almost always become negative. Examples of new translations from the modified Transformer are shown in the "after" rows in Table 5, where *cet* now disappears from the translations. The test BLEU score of Transformer only decreases by an average percent difference of -2.7% after modification. Results for $\sigma = 6$, $\sigma' = 10.5$ are shown.

Experiments on DNA-CNN and ResNet152 show similar results at fixed interaction positions (§4.2). For DNA-CNN, out of the 94 times a 6-way interaction of the CACGTG motif (Sharon et al., 2008) was detected in the test set, every time yielded a positive attribution polarity towards DNA-protein affinity, and the same was true after modifying the model in the opposite polarity (cosine distance $\sigma = 0.35$, $\sigma' = 0.408$). For ResNet152, context-free interactions are also found (cosine distance $\sigma = 0.4$, $\sigma' = 0.663$). However, because superpixels are used, the interactions found may contain artifacts caused by superpixel segmenters, yielding less intuitive interactions (see Appendix A).

5.4 Limitations

Although Mahé obtains accurate local interactions on synthetic data using NID, there is no guarantee that NID finds correct interactions. Mahé faces common issues of model-agnostic perturbation methods in interpreting high-dimensional feature spaces, choice of perturbation distribution, and speed (Ribeiro et al., 2016; 2018). Finally, an exhaustive search is used for context-free explanations.

6 Conclusion

In this work, we proposed Mahé, a model-agnostic framework of providing context-dependent and context-free explanations of local interactions. Mahé has demonstrated the capability of outperforming existing approaches to local interaction interpretation and has shown that local interactions can be context-free. In future work, we wish to make the process of finding context-free interactions more efficient, and study to what extent model behavior can be changed by editing its interactions or univariate effects. Finally, we would like to study the interpretations provided by Mahé more closely to find new insights into structured data.

Figure 6: Examples of context-dependent explanations in hierarchical format for ResNet152, where images come from the ImageNet test set. Interaction attributions of $\{g_i'(\cdot)\}_{i=1}^K$ are show at each $K-1$ level, $K \geq 1$ (§4.1). Colors in superpixels represent attribution scores and their polarity. Cyan regions positively contribute to the predicton, and red regions negatively contribute. Boundaries between overlapping interactions are merged when their attribution polarities match. From these examples, it is often seen that superpixels belonging to the same entity (or class in (d)) interact. Also shown is that ResNet152 selects interacting entities that support its prediction. These interpretations cannot be seen in linear LIME. (d) is an interesting example because water is not detected as an important interaction with buffalo in the prediction of water buffalo. This could be due to a variety of reasons. For example, many images of water buffalo in ImageNet do not have water, and the closest class, bison, also has a mixture of images with and without water[4]. ResNet152 is also prone to making mistakes despite it being state-of-the-art, having a top-1 misclassification rate of 21.7%.

Table 6: Examples of context-dependent hierarchical explanations on Sentiment-LSTM. The interaction attribution of $g_K'(\cdot)$ is shown at each $K-1$ level, $K \geq 1$ (§4.1) in color. Green means positively contributing to sentiment, and red the opposite. Visualized attributions of linear LIME and `Mahé` are normalized to the max attribution magnitudes (max magn.) shown. Top-5 attributions by magnitude are shown for LIME.

Method	Level	Fit (R^2)	Hierarchical Explanation	Max magn.
linear LIME	1	0.621	the film is really not so much bad as bland	0.744
`Mahé`	2	0.751	not, bad	
`Mahé`	3	0.916	not, bad, bland	
`Mahé`	4	0.926	film, not, bad, bland	0.119
linear LIME	1	0.519	a very average science fiction film	0.708
`Mahé`	2	0.598	science, fiction	
`Mahé`	3	0.819	a, average	
`Mahé`	4	0.923	a, very, average	0.213
linear LIME	1	0.612	a charming romantic comedy that is by far the lightest dogme film and among the most enjoyable	0.612
`Mahé`	2	0.856	charming, enjoyable	
`Mahé`	3	0.923	charming, lightest, enjoyable	0.072

---

[4] http://image-net.org/challenges/LSVRC/2014/browse-synsets

REFERENCES

Babak Alipanahi, Andrew Delong, Matthew T Weirauch, and Brendan J Frey. Predicting the sequence specificities of dna-and rna-binding proteins by deep learning. *Nature biotechnology*, 33 (8):831, 2015.

Ronen Basri and David Jacobs. Efficient representation of low-dimensional manifolds using deep networks. *arXiv preprint arXiv:1602.04723*, 2016.

Jacob Bien, Jonathan Taylor, and Robert Tibshirani. A lasso for hierarchical interactions. *Annals of statistics*, 41(3):1111, 2013.

Lawrence Cayton. Algorithms for manifold learning. *Univ. of California at San Diego Tech. Rep*, 12(1-17):1, 2005.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*, pp. 785–794. ACM, 2016.

Trevor J Hastie and Robert J Tibshirani. Generalized additive models, 1990.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Giles Hooker. Discovering additive structure in black box functions. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 575–580. ACM, 2004.

Giles Hooker. Generalized functional anova diagnostics for high-dimensional functions of dependent variables. *Journal of Computational and Graphical Statistics*, 16(3):709–732, 2007.

Kurt Hornik. Approximation capabilities of multilayer feedforward networks. *Neural networks*, 4 (2):251–257, 1991.

Linwei Hu, Jie Chen, Vijayan N Nair, and Agus Sudjianto. Locally interpretable models and effects based on supervised partitioning (lime-sup). *arXiv preprint arXiv:1806.00663*, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *CVPR*, volume 1, pp. 3, 2017.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International Conference on Machine Learning*, pp. 2673–2682, 2018.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436, 2015.

Kuang-Chih Lee, Jeffrey Ho, Ming-Hsuan Yang, and David Kriegman. Video-based face recognition using probabilistic appearance manifolds. In *Computer vision and pattern recognition, 2003. proceedings. 2003 ieee computer society conference on*, volume 1, pp. I–I. IEEE, 2003.

Vladimir I Levenshtein. Binary codes capable of correcting deletions, insertions, and reversals. In *Soviet physics doklady*, volume 10, pp. 707–710, 1966.

Yin Lou, Rich Caruana, Johannes Gehrke, and Giles Hooker. Accurate intelligible models with pairwise interactions. In *Proceedings of the 19th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 623–631. ACM, 2013.

Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, pp. 4765–4774, 2017.

Scott M Lundberg, Gabriel G Erion, and Su-In Lee. Consistent individualized feature attribution for tree ensembles. *arXiv preprint arXiv:1802.03888*, 2018.

Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pp. 142–150, Portland, Oregon, USA, June 2011. Association for Computational Linguistics. URL http://www.aclweb.org/anthology/P11-1015.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.

Christopher D. Manning, Prabhakar Raghavan, and Hinrich Schütze. *Introduction to Information Retrieval*. Cambridge University Press, New York, NY, USA, 2008. ISBN 0521865719, 9780521865715.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Fantine Mordelet, John Horton, Alexander J Hartemink, Barbara E Engelhardt, and Raluca Gordân. Stability selection for regression-based models of transcription factor–dna binding specificity. *Bioinformatics*, 29(13):i117–i125, 2013.

W James Murdoch, Peter J Liu, and Bin Yu. Beyond word importance: Contextual decomposition to extract interactions from lstms. *arXiv preprint arXiv:1801.05453*, 2018.

Myle Ott, Sergey Edunov, David Grangier, and Michael Auli. Scaling neural machine translation. *arXiv preprint arXiv:1806.00187*, 2018.

Sanjay Purushotham, Martin Renqiang Min, C-C Jay Kuo, and Rachel Ostroff. Factorized sparse learning models with interpretable high order feature interactions. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 552–561. ACM, 2014.

Scott Reed, Kihyuk Sohn, Yuting Zhang, and Honglak Lee. Learning to disentangle factors of variation with manifold interaction. In *International Conference on Machine Learning*, pp. 1431–1439, 2014.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Why should i trust you?: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1135–1144. ACM, 2016.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Anchors: High-precision model-agnostic explanations. In *AAAI Conference on Artificial Intelligence*, 2018.

Salah Rifai, Yann N Dauphin, Pascal Vincent, Yoshua Bengio, and Xavier Muller. The manifold tangent classifier. In *Advances in Neural Information Processing Systems*, pp. 2294–2302, 2011.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

Eilon Sharon, Shai Lubliner, and Eran Segal. A feature-based approach to modeling protein–dna interactions. *PLoS computational biology*, 4(8):e1000154, 2008.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. *arXiv preprint arXiv:1704.02685*, 2017.

Chandan Singh, W James Murdoch, and Bin Yu. Hierarchical interpretations for neural network predictions. *arXiv preprint arXiv:1806.05337*, 2018.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. Smoothgrad: removing noise by adding noise. *arXiv preprint arXiv:1706.03825*, 2017.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 conference on empirical methods in natural language processing*, pp. 1631–1642, 2013.

Daria Sorokina, Rich Caruana, Mirek Riedewald, and Daniel Fink. Detecting statistical interactions with additive groves of trees. In *Proceedings of the 25th international conference on Machine learning*, pp. 1000–1007. ACM, 2008.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pp. 3319–3328, 2017.

Kai Sheng Tai, Richard Socher, and Christopher D Manning. Improved semantic representations from tree-structured long short-term memory networks. *arXiv preprint arXiv:1503.00075*, 2015.

Sergios Theodoridis, Konstantinos Koutroumbas, et al. Pattern recognition. *IEEE Transactions on Neural Networks*, 19(2):376, 2008.

Michael Tsang, Dehua Cheng, and Yan Liu. Detecting statistical interactions from neural network weights. In *International Conference on Learning Representations*, 2018.

Matthew Turk and Alex Pentland. Eigenfaces for recognition. *Journal of cognitive neuroscience*, 3 (1):71–86, 1991.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pp. 5998–6008, 2017.

Andrea Vedaldi and Stefano Soatto. Quick shift and kernel methods for mode seeking. In *European Conference on Computer Vision*, pp. 705–718. Springer, 2008.

Meng Wang, Cheng Tai, Weinan E, and Liping Wei. Define: deep convolutional neural networks accurately quantify intensities of transcription factor-dna binding and facilitate evaluation of functional non-coding variants. *Nucleic acids research*, 46(11):e69–e69, 2018.

Lin Yang, Tianyin Zhou, Iris Dror, Anthony Mathelier, Wyeth W Wasserman, Raluca Gordân, and Remo Rohs. Tfbsshape: a motif database for dna shape features of transcription factor binding sites. *Nucleic acids research*, 42(D1):D148–D155, 2013.

Haoyang Zeng, Matthew D Edwards, Ge Liu, and David K Gifford. Convolutional neural network architectures for predicting dna–protein binding. *Bioinformatics*, 32(12):i121–i127, 2016.

SUPPLEMENTARY MATERIALS

A CONTEXT-FREE EXPLANATIONS IN RESNET152

Figure 7: Context-free explanations of interactions in ResNet152 for each image, evaluated over 40 tests before and after modification. Each test superimposes the interaction of interest onto a randomly selected background image from the test set of ImageNet. Corresponding predictions are shown above each image, and the percentage of consistent interaction polarity before and after modification are shown below in that order. The red color indicates a negative interaction attribution polarity before modification. After modification, the polarities become positive.

B FURTHER DETAILS OF MECHANICAL TURK EXPERIMENT

Several other conditions were used to choose which sentences to show Mechanical Turk evaluators besides requiring a detected interaction. We ensure that there is a significant attribution difference between LIME and Mahé by only choosing among sentences that have a polarity difference between Mahé's interaction and LIME's corresponding linear attributions. To reduce ambiguities of uninterpretable explanations arising from a misbehaving model - an issue also faced by Sundararajan et al. (2017) in interpretation evaluation - we only show explanations of sentences that the model classified correctly. We also attempt to limit the effort that evaluators need to analyze explanations by only showing sentences with 5-12 words with uniform representation of each sentence length.

An example of the interface that evaluators select from is shown in Figure 8. Randomly selected examples of comparisons that evaluators make are shown in Figure 9. The visualization tool for presenting additive attribution explanations is graciously provided by the official code repository of LIME [5].

Figure 8: Example of Mechanical Turk interface used by workers to select between explanations provided by linear LIME and Mahé.

---

[5]https://github.com/marcotcr/lime

(a) linear LIME explanations   (b) Mahé explanations at $K = 1$

Figure 9: Randomly selected comparisons between (a) linear LIME and (b) Mahé explanations of Sentiment-LSTM used in Mechanical Turk experiments (§5.2.2).

C   RUNTIME

Figures 10 and 11 show runtimes of context-dependent and -free explanations using Mahé. All experiments were conducted on Intel Xeon 2.4-2.6 GHz CPUs and Nvidia 1080 Ti GPUs. Experiments with MLPs were run on CPUs and inference/retraining of DNA-CNN, Sentiment-LSTM, ResNet152, and Transformer were run on GPUs.

Figure 10: Average runtime of linear LIME versus `Mahé` on context-dependent explanations. Runtimes for experiments in Table 3 are shown. "local inference" is the runtime for sampling in the local vicinity of a data instance and running inference though a black-box model for every sampled point. "NID" is the runtime for running NID interaction detection. "linear model" is the runtime for training a linear model (Eq. 1) to get linear attributions with LIME. "interaction model(s)" is the runtime for sequentially training interaction models (Eq. 3) to get interaction attributions with `Mahé`.

Figure 11: Runtime of `Mahé` for determining whether an interaction is context-free for a randomly selected interaction and 40 different contexts, run sequentially. Runtimes for checking interaction consistency before and after model retraining (fine-tuning) are shown. DNA-CNN takes longer here because we needed to relax the cutoff criteria of identifying the $L+1$-th hierarchical level to find the CACGTG interaction. For context-free experiments, a cutoff patience (§5.1) for Sentiment-LSTM, ResNet152, and Transformer was not needed in our experiments and is excluded in this runtime analysis. The patience for DNA-CNN was 2.

D   COMPARISONS TO BASELINES FOR CONTEXT-FREE EXPLANATIONS

Figure 12: Comparisons of `Mahé` to baselines for identifying consistent interaction polarity before modifying models. Results for explaining Sentiment-LSTM are shown on the same interactions identified in Figure 5. The baselines are GLM and GA^{2}M. GLM is a lasso-regularized generalized linear model with all pairs of multiplicative interaction terms (Bien et al., 2013), and GA^{2}M is a tree-based generalized additive model with pairwise non-additive interactions (Lou et al., 2013).

Figure 13: Comparisons of Mahé to baselines for identifying consistent negated interaction polarity after using the same baselines to locally modify Sentiment-LSTM on the interactions from Figure 12. Mahé shows more significant improvements over baselines than before negating interactions.

E   HIERARCHICAL EXPLANATIONS OF *cet* INTERACTIONS IN TRANSFORMER

Table 7: Examples of context-dependent hierarchical explanations on Transformer. The interaction attribution of $g'_K(\cdot)$ is shown at each $K - 1$ level, $K \geq 1$ (§4.1) in color. Green contributes towards *cet* translations, and red contributes the opposite. Visualized attributions of linear LIME and Mahé are normalized to the max attribution magnitudes (max magn.) shown. Top-5 attributions by magnitude are shown for LIME.

Method	Level	Fit (R^2)	Hierarchical Explanation	Max magn.
linear LIME	1	0.782	this article was last updated on substance in august 2012	0.657
Mahé	2	0.948	this, article	3.707
linear LIME	1	0.696	this effect takes part in making lead slightly less reactive chemically	0.643
Mahé	2	0.96	this, effect	2.459
linear LIME	1	0.734	the population size of this bird has not yet been quantified or estimated	0.605
Mahé	2	0.926	this, bird	1.211

F   MORE EXAMPLES OF INTERACTIONS WITH CONSISTENT POLARITIES IN SENTIMENT-LSTM

Table 8: Shown below are more examples of interactions with consistent polarities found by Mahé in Sentiment-LSTM. Num samples is the number of sentences from which the same interaction is found. Percent polarity is the percentage of interactions that have the specified attribution polarity. Avg. separation is the average separation of words in detected interactions.

Interaction	num samples	percent polarity		avg. separation between words
(not, good)	213	96.7%	negative	1.4
(falls, flat)	169	97.6%	negative	0.17
(not, funny)	155	97.4%	negative	0.65
(not, miss)	133	97.7%	positive	0.66
(still, love)	103	98.1%	positive	0.19
(bad, worst)	44	95.5%	positive	5.5
(never, off)	36	100%	positive	1.4