BOUNDARY-SEEKING GENERATIVE ADVERSARIAL NETWORKS

ABSTRACT

Generative adversarial networks (GANs, Goodfellow et al., 2014) are a learning framework that rely on training a discriminator to estimate a measure of difference between a target and generated distributions. GANs, as normally formulated, rely on the generated samples being completely differentiable w.r.t. the generative parameters, and thus do not work for discrete data. We introduce a method for training GANs with discrete data that uses the estimated difference measure from the discriminator to compute importance weights for generated samples, thus providing a policy gradient for training the generator. The importance weights have a strong connection to the decision boundary of the discriminator, and we call our method *boundary-seeking GANs* (BGANs). We demonstrate the effectiveness of the proposed algorithm with discrete image and character-based natural language generation. In addition, the boundary-seeking objective extends to continuous data, which can be used to improve stability of training.

1 INTRODUCTION

Generative adversarial networks (GAN, Goodfellow et al., 2014) involve a unique generative learning framework that uses two separate models with opposing, competing, or *adversarial* objectives. These two models are the *discriminator* and the *generator*. Training a GAN only requires back-propagating a learning signal that originates from a learned objective function, which corresponds to the loss of the discriminator trained in an adversarial manner. This framework is powerful because it trains a generator without relying on an explicit formulation of the probability density, using only samples from the generator to train.

GANs have been shown to generate often-diverse and realistic samples even when trained on high-dimensional large-scale continuous data (Radford et al., 2015). GANs however have a serious limitation on the type of variables they can model, because they require the composition of the generator and discriminator to be fully differentiable.

With discrete variables, this is not true. For instance, consider using a step function at the end of a generator in order to generate a discrete value. In this case, back-propagation alone cannot provide the training signal for the generator, because the derivative of a step function is 0 almost everywhere (and so would be the back-propagated signal). This is problematic, as many important real-world datasets are discrete, such as character- or word-based representations of language. The general issue of credit assignment for computational graphs with discrete operations (e.g. discrete stochastic neurons) is difficult, and only approximate solutions have been proposed in the past (Bengio et al., 2013; Gu et al., 2015; Gumbel & Lieblein, 1954; Jang et al., 2016; Maddison et al., 2016; Tucker et al., 2017). However, none of these have yet been shown to work with GANs.

In this work, we make the following contributions:

- We provide a theoretical foundation for *boundary-seeking GANs* (BGAN), a principled method for training a generator of discrete data using a discriminator optimized to estimate an f-divergence (Nguyen et al., 2010; Nowozin et al., 2016). We show how the discriminator can be used to formulate an *importance weight* which effectively provides a policy gradient for training the generator.

- We verify this approach quantitatively works across a set of f-divergences on a simple classification task. We also verify that this approach works on a variety of natural and synthetic discrete datasets.

- We show that the boundary-seeking objective extends theoretically to the continuous case and verify it works well with some common and difficult image benchmarks. Finally, we show that this objective has some improved stability properties within training and without.

2 BOUNDARY-SEEKING GANS

In this section, we will introduce boundary-seeking GANs (BGAN), an approach for training a generative model adversarially with discrete data, as well as provide its theoretical foundation. For BGAN, we assume the normal generative adversarial learning setting commonly found in work on GANs (Goodfellow et al., 2014), but these ideas should extend elsewhere.

2.1 GENERATIVE ADVERSARIAL LEARNING AND PROBLEM STATEMENT

Assume that we are given empirical samples from a target distribution, $\{x^{(i)} \in \mathcal{X}\}_{i=1}^M$, where $\mathcal{X}$ is the domain (such as the space of images, word- or character- based representations of natural language, etc.). Given a random variable Z over a space $\mathcal{Z}$ (such as $[0,1]^m$), we wish to find the optimal parameters, $\hat{\theta} \in \mathbb{R}^d$, of a function, $G_\theta : \mathcal{Z} \to \mathcal{X}$ (such as a deep neural network), whose induced probability distribution, $\mathbb{Q}_\theta$, describes well the empirical samples.

In order to put this more succinctly, it is beneficial to talk about a probability distribution of the empirical samples, $\mathbb{P}$, that is defined on the same space as $\mathbb{Q}_\theta$. We can now consider the *difference measure* between $\mathbb{P}$ and $\mathbb{Q}_\theta$, $D(\mathbb{P}, \mathbb{Q}_\theta)$, so that the problem can be formulated as finding the parameters:

$$\hat{\theta} = \arg\min_\theta D(\mathbb{P}, \mathbb{Q}_\theta). \tag{1}$$

Defining an appropriate difference measure is a long-running problem in machine learning and statistics, and choosing the best one depends on the specific setting. Here, we wish to avoid making strong assumptions on the exact forms of $\mathbb{P}$ or $\mathbb{Q}_\theta$, and we desire a solution that is scalable and works with very high dimensional data. Generative adversarial networks (GANs, Goodfellow et al., 2014) fulfill these criteria by introducing a *discriminator function*, $D_\phi : \mathcal{X} \to \mathbb{R}$, with parameters, ϕ, then defining a *value function*,

$$\mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, D_\phi) = \mathbb{E}_\mathbb{P}\left[\log D_\phi(x)\right] + \mathbb{E}_{h(z)}\left[\log(1 - D_\phi(G(z)))\right], \tag{2}$$

where samples z are drawn from a simple prior, $h(z)$ (such as $U(0,1)$ or $\mathcal{N}(0,1)$). Here, D_ϕ is a neural network with a sigmoid output activation, and as such can be interpreted as a simple binary classifier, and the value function can be interpreted as the negative of the *Bayes risk*. GANs train the discriminator to maximize this value function (minimize the mis-classification rate of samples coming from $\mathbb{P}$ or $\mathbb{Q}_\theta$), while the generator is trained to minimize it. In other words, GANs solve an optimization problem:

$$(\hat{\theta}, \hat{\phi}) = \arg\max_\phi \arg\min_\theta \mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, D_\phi). \tag{3}$$

Optimization using only back-propogation and stochastic gradient descent is possible when the generated samples are completely differentiable w.r.t. the parameters of the generator, θ.

In the non-parametric limit of an optimal discriminator, the value function is equal to a scaled and shifted version of the Jensen-Shannon divergence, $2 * \mathcal{D}_{JSD}(\mathbb{P}||\mathbb{Q}_\theta) + \log 4$,[1] which implies the generator is minimizing this divergence in this limit. f-GAN (Nowozin et al., 2016) generalized this idea over all f-divergences, which includes the Jensen-Shannon (and hence also GANs) but also the Kullback–Leibler, Pearson χ^2, and squared-Hellinger. Their work provides a nice formalism for talking about GANs that use f-divergences, which we rely on here.

---

[1]Note that this has an absolute minimum, so that the above optimization is a Nash-equilibrium

Definition 2.1 (f-divergence and its dual formulation). Let $f : \mathbb{R}_+ \to \mathbb{R}$ be a convex lower semi-continuous function and $f^\star : \mathcal{C} \subseteq \mathbb{R} \to \mathbb{R}$ be the complex conjugate with domain $\mathcal{C}$. Next, let $\mathcal{T}$ be an arbitrary family of functions, $\mathcal{T} = \{T : \mathcal{X} \to \mathcal{C}\}$. Finally, let $\mathbb{P}$ and $\mathbb{Q}$ be distributions that are completely differentiable w.r.t. the same measure, μ.[2] The f-divergence, $\mathcal{D}_f(\mathbb{P}||\mathbb{Q}_\theta)$, generated by f, and its dual representation are (Nguyen et al., 2010):

$$\mathcal{D}_f(\mathbb{P}||\mathbb{Q}) = \mathbb{E}_{\mathbb{Q}_\theta}\left[f\left(\frac{d\mathbb{P}/d\mu}{d\mathbb{Q}/d\mu} \right) \right] = \sup_{T \in \mathcal{T}} \mathbb{E}_{\mathbb{P}}[T(x)] - \mathbb{E}_{\mathbb{Q}}[f^\star(T(x))]. \tag{4}$$

The dual form allows us to change a problem involving likelihood ratios (which may be intractable) to an optimization problem over $\mathcal{T}$. This kind of optimization is well-studied if $\mathcal{T}$ is a family of neural networks with parameters ϕ, so the supremum can be found with gradient ascent (Nowozin et al., 2016).

Definition 2.2 (Variational lower-bound for the f-divergence). Let $T_\phi = \nu \circ F_\phi$ be a function, which is the composition of an activation function, $\nu : \mathbb{R} \to \mathcal{C}$ and a neural network, $F_\phi : \mathcal{X} \to \mathbb{R}$. We can write the *lower-bound* of the supremum in Equation 4 as:

$$\mathcal{D}_f(\mathbb{P}||\mathbb{Q}_\theta) \geq \mathbb{E}_{\mathbb{P}}[\nu \circ F_\phi(x)] - \mathbb{E}_{\mathbb{Q}_\theta}[f^\star(\nu \circ F_\phi(x))] = \mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, T_\phi). \tag{5}$$

It can be easily verified that, for $\nu(y) = -\log(1 + e^{-y})$, $f(u) = u \log u + (1 + u) \log(1 + u)$, and setting $T = \log D$, the variational lower-bound becomes exactly equal to the GAN value function.

GANs are extremely powerful for training a generator of continuous data, leveraging a dual representation along with a neural network with theoretically unlimited capacity to estimate a difference measure. For the remainder of this work, we will refer to $T_\phi = \nu \circ F_\phi$ as the *discriminator* and F_ϕ as the *statistic network* (which is a slight deviation from other works). We will generalize the term *GAN* to refer to all models that simultaneously minimize and maximize a *variational lower-bound*, $\mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, T_\phi)$, of a difference measure (such as a divergence or distance). In principle, this extends to variants of GANs which are based on integral probability metrics (IPMs, Sriperumbudur et al., 2009) that leverage a dual representation, such as those that rely on restricting $\mathcal{T}$ through parameteric regularization (Arjovsky et al., 2017) or by constraining its output distribution (Mroueh & Sercu, 2017; Mroueh et al., 2017; Sutherland et al., 2016).

2.2 ESTIMATION OF THE TARGET DISTRIBUTION

Here we will show that, with the variational lower-bound of an f-divergence along with a family of positive activation functions, $\nu : \mathbb{R} \to \mathbb{R}_+$, we can estimate the target distribution, $\mathbb{P}$, using the generated distribution, $\mathbb{Q}_\theta$, and the discriminator, T_ϕ.

Theorem 1. *Let f be a convex function and $T^\star \in \mathcal{T}$ a function that satisfies the equality in Equation 4 in the non-parametric limit. Let us assume that $\mathbb{P}$ and $\mathbb{Q}_\theta(x)$ are absolutely continuous w.r.t. a measure μ and hence admit densities, $p(x)$ and $q_\theta(x)$. Then the target density function, $p(x)$, is equal to $(\partial f^\star/\partial T)(T^\star(x))q_\theta(x)$.*

Proof. Following the definition of the f-divergence, $\mathcal{D}_f(\mathbb{P}||\mathbb{Q}_\theta)$, and the complex conjugate, we have:

$$\mathcal{D}_f(\mathbb{P}||\mathbb{Q}_\theta) = \mathbb{E}_{\mathbb{Q}_\theta}\left[f\left(\frac{p(x)}{q(x)} \right) \right] = \mathbb{E}_{\mathbb{Q}_\theta}\left[\sup_t \left\{ t \frac{p(x)}{q(x)} - f^\star(t) \right\} \right]. \tag{6}$$

As $f^\star$ is convex, there is an absolute maximum when $\frac{\partial f^\star}{\partial t}(t) = \frac{p(x)}{q_\theta(x)}$. Rephrasing t as a function, $T(x)$, and by the definition of $T^\star(x)$, we arrive at the desired result. $\qquad \square$

Theorem 1 indicates that the target density function can be re-written in terms of a generated density function and a scaling factor. We refer to this scaling factor, $w^\star(x) = (\partial f^\star/\partial T)(T^\star(x))$, as the optimal *importance weight* to make the connection to importance sampling. In the case of the f-divergence used in Goodfellow et al. (2014), the optimal importance weight equals $w^\star(x) = e^{F^\star(x)} = D^\star(x)/(1 - D^\star(x))$.

---

[2]μ can be thought of in this context as x, so that it can be said that $\mathbb{P}$ and $\mathbb{Q}$ have density functions on x.

Table 1: Important weights and nonlinearities that ensure

Importance weights for f-divergences		
f-divergence	$\nu(y)$	$w(x) = (\partial f^\star / \partial T)(T(x))$
GAN	$-\log\left(1 + e^{-y}\right)$	$-\frac{1}{1 - e^{-T_\phi}} = e^{F_\phi(x)}$
Jensen-Shannon	$\log 2 - \log\left(1 + e^{-y}\right)$	$-\frac{1}{2 - e^{-T_\phi}} = e^{F_\phi(x)}$
KL	$y + 1$	$e^{(T_\phi(x) - 1)} = e^{F_\phi(x)}$
Reverse KL	$-e^{-y}$	$-\frac{1}{T_\phi(x)} = e^{F_\phi(x)}$
Squared-Hellinger	$1 - e^{-v/2}$	$\frac{1}{(1 - T_\phi(x))^2} = e^{F_\phi(x)}$

In general, an optimal discriminator is hard to guarantee in the saddle-point optimization process, so in practice, T_ϕ will define a lower-bound that is not exactly tight w.r.t. the f-divergence. Nonetheless, we can define an estimator for the target density function using a sub-optimal T_ϕ.

Definition 2.3 (f-divergence importance weight function estimator). Let f be a convex lower semi-continuous function with complex conjugate, $f^\star : \mathcal{C} \to \mathbb{R}$ and let $T_\phi(x) = \nu \circ F_\phi(x)$ be the composition of an activation function, $\nu : \mathbb{R} \to \mathbb{R}_+ \subseteq \mathcal{C}$, and a neural network $F_\phi : \mathcal{X} \to \mathbb{R}$. Let $w(x) = (\partial f^\star / \partial T)(T(x))$ and $\beta = \mathbb{E}_{\mathbb{Q}_\phi}[w(x)]$ be a partition function. The f-divergence importance weight function estimator, $\tilde{p}(x)$ is

$$\tilde{p}(x) = \frac{w(x)}{\beta} q_\theta(x). \tag{7}$$

The non-negativity of ν is important as the densities are positive. Table 1 provides a set of f-divergences (following suggestions of Nowozin et al. (2016) with only slight modifications) which are suitable candidates and yield positive importance weights. Surprisingly, each of these yield the same function over the neural network before the activation function: $w(x) = e^{F_\phi(x)}$.[3] It should be noted that $\tilde{p}(x)$ is a potentially biased estimator for the true density; however, the bias only depends on the tightness of the variational lower-bound: the tighter the bound, the lower the bias. This problem reiterates the problem with all GANs, where proofs of convergence are only provided in the optimal or near-optimal limit (Goodfellow et al., 2014; Nowozin et al., 2016; Mao et al., 2016).

2.3 BOUNDARY-SEEKING GANS

As mentioned above and repeated here, GANs only work *when the value function is completely differentiable w.r.t. the parameters of the generator, θ*. The gradients that would otherwise be used to train the generator of discrete variables are zero almost everywhere, so it is impossible to train the generator directly using the value function. Approximations for the back-propagated signal exist (Bengio et al., 2013; Gu et al., 2015; Gumbel & Lieblein, 1954; Jang et al., 2016; Maddison et al., 2016; Tucker et al., 2017), but as of this writing, none has been shown to work satisfactorily in training GANs with discrete data.

Here, we introduce the boundary-seeking GAN as a method for training GANs with discrete data. We first introduce a policy gradient based on the KL-divergence which uses the importance weights as a reward signal. We then introduce a lower-variance gradient which defines a unique reward signal for each z and prove this can be used to solve our original problem.

Policy gradient based on importance sampling Equation 7 offers an option for training a generator in an adversarial way. If we know the explicit density function, q_θ, (such as a multivariate Bernoulli distribution), then we can, using $\tilde{p}(x)$ as a target (keeping it fixed w.r.t. optimization of θ), train the generator using the gradient of the KL-divergence:

$$\nabla_\theta \mathcal{D}_{KL}(\tilde{p}(x) || q_\theta) = -\mathbb{E}_{\mathbb{Q}_\theta}\left[\frac{w(x)}{\beta} \nabla_\theta \log q_\theta(x)\right]. \tag{8}$$

Here, the connection to importance sampling is even clearer, and this gradient resembles other importance sampling methods for training generative models in the discrete setting (Bornschein &

---

[3]Note also that the normalized weights resemble softmax probabilities

---

Algorithm 1 . Discrete Boundary Seeking GANs

$(\theta, \phi) \leftarrow$ initialize the parameters of the generator and statistic network
repeat
    $\hat{x}^{(n)} \sim \mathbb{P}$ ▷ Draw N samples from the empirical distribution
    $z^{(n)} \sim h(z)$ ▷ Draw N samples from the prior distribution
    $x^{(m|n)} \sim g_\theta(x \mid z^{(n)})$ ▷ Draw M samples from each conditional $g_\theta(x \mid z^{(m)})$
    $w(x^{(m|n)}) \leftarrow f^\star(\nu \circ F_\phi(x^{(m|n)}))$
    $\tilde{w}(x^{(m|n)}) \leftarrow w(x^{(m|n)}) / \sum_{m'} w(x^{(m'|n)})$ ▷ Compute the un-normalized and normalized
importance weights
    $\mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, T_\phi) \leftarrow \frac{1}{N} \sum_n F_\phi(\hat{x}^{(n)}) - \frac{1}{N} \sum_n \frac{1}{M} \sum_m w(x^{(m|n)})$ ▷ Estimate the variational
lower-bound
    $\phi \leftarrow \phi + \gamma_d \nabla_\phi \mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, T_\phi)$ ▷ Optimize the discriminator parameters
    $\theta \leftarrow \theta + \gamma_g \frac{1}{N} \sum_{n,m} \tilde{w}(x^{(m|n)}) \nabla_\theta \log g_\theta(x \mid z)$ ▷ Optimize the generator parameters
until convergence

Bengio, 2014; Rubinstein & Kroese, 2016). However, we expect the variance of this estimator will be high, as it requires estimating the partition function, β (for instance, using Monte-Carlo sampling). We address reducing the variance from estimating the normalized importance weights next.

Lower-variance policy gradient   Let $q_\theta(x) = \int_{\mathcal{Z}} g_\theta(x \mid z) h(z) dz$ be a probability density function with a conditional density, $g_\theta(x \mid z) : \mathcal{Z} \rightarrow [0,1]^d$ (e.g., a multivariate Bernoulli distribution), and prior over z, $h(z)$. Let $\alpha(z) = \mathbb{E}_{g_\theta(x|z)}[w(x)] = \int_{\mathcal{X}} g_\theta(x \mid z) w(x) dx$ be a partition function over the conditional distribution. Let us define $\tilde{p}(x \mid z) = \frac{w(x)}{\alpha(z)} g_\theta(x \mid z)$ as the (normalized) conditional distribution weighted by $\frac{w(x)}{\alpha(z)}$. The expected conditional KL-divergence over the prior, $h(z)$ is:

$$\mathbb{E}_{h(z)}[\mathcal{D}_{KL}(\tilde{p}(x \mid z) \| g_\theta(x \mid z))] = \int_{\mathcal{Z}} h(z) \mathcal{D}_{KL}(\tilde{p}(x \mid z) \| g_\theta(x \mid z)) dz \tag{9}$$

Let $x^{(m)} \sim g_\theta(x \mid z)$ be samples from the prior and $\tilde{w}(x^{(m)}) = \frac{w(x^{(m)})}{\sum_{m'} x^{(m')}}$ be a Monte-Carlo estimate of the normalized importance weights. The gradient of the expected conditional KL-divergence w.r.t. the generator parameters, θ, becomes:

$$\nabla_\theta \mathbb{E}_{h(z)}[\mathcal{D}_{KL}(\tilde{p}(x \mid z) \| g_\theta(x \mid z))] = -\mathbb{E}_{h(z)}\left[\sum_m \tilde{w}(x^{(m)}) \nabla_\theta \log g_\theta(x \mid z)\right], \tag{10}$$

where we have approximated the expectation over the conditional distribution using the Monte-Carlo estimate.

Minimizing the expected conditional KL-divergences is stricter than minimizing the KL-divergence in Equation 7, as it requires all of the conditional distributions to match independently. We can show that the KL-divergence of the marginal probabilities is zero when the expectation of the conditional KL-divergence is zero.

Theorem 2. *Let the expectation of the conditional KL-divergence be defined as in Equation 9. Then* $\mathbb{E}_{h(z)}[\mathcal{D}_{KL}(\tilde{p}(x \mid z) \| g_\theta(x \mid z))] = 0 \implies \mathcal{D}_{KL}(\tilde{p}(x) \| q_\theta) = 0.$

Proof. As the conditional KL-divergence is has an absolute minimum at zero, the expectation can only be zero when the all of the conditional KL-divergences are zero. In other words:

$$\mathbb{E}_{h(z)}[\mathcal{D}_{KL}(\tilde{p}(x \mid z) \| g_\theta(x \mid z))] = 0 \implies \tilde{p}(x \mid z) = g_\theta(x \mid z). \tag{11}$$

As per the definition of $\tilde{p}(x \mid z)$, this implies that $\alpha(z) = w(x) = C$ is a constant. If $w(x)$ is a constant, then the partition function $\beta = C\mathbb{E}_{\mathbb{Q}_\theta}[1] = C$ is a constant. Finally, when $\frac{w(x)}{\beta} = 1$, $\tilde{p}(x) = q_\theta \implies \mathcal{D}_{KL}(\tilde{p}(x) \| q_\theta) = 0.$ $\square$

Algorithm 1 describes the training procedure for discrete BGAN. This algorithm requires an additional M times more computation to compute the normalized importance weights, though these can be computed in parallel exchanging space for time.

Connection to classification decision boundaries   The variational lower-bound and the importance weights have an important connection to classifiers, Bayes risk, and decision boundaries. Notably, we notice that the variational lower-bound has a maxima w.r.t. T at $\partial f^\star / \partial T(T) = 1$. These are the values of T for which the discriminator, which can be thought of as a *classifier*, has maximum Bayes risk. We can show that, as the discriminator minimizes the Bayes risk, the gradient in Equation 8 is zero when the generated samples lie on the decision boundary, which maximizes the Bayes risk. Following this observation, we call this method *boundary-seeking GANs* (BGAN).

Connection to policy gradients   REINFORCE is a common technique for dealing with discrete data in GANs (Che et al., 2017; Press et al., 2017). Equation 9 is a policy gradient in the special case that the reward is the normalized importance weights. This reward approaches the likelihood ratio in the non-parametric limit of an optimal discriminator. Here, we make another connection to REINFORCE as it is commonly used, with baselines, by deriving the gradient of the reversed KL-divergence.

Definition 2.4 (REINFORCE-based BGAN). Let $T_\phi(x)$ be a statistic network that measures an f-divergence such that $\partial f^\star / \partial T(T_\phi(x)) = e^{F_\phi(x)}$ Consider the gradient of the *reversed* KL-divergence:

$$\nabla_\theta \mathcal{D}_{KL}\left(q_\theta \| \tilde{p}\right) = -\mathbb{E}_{h(z)}\left[\sum_m (\log w(x^{(m)}) - \log \beta + 1)\nabla_\theta \log g_\theta(x \mid z)\right]$$

$$= -\mathbb{E}_{h(z)}\left[\sum_m (F_\phi(x) - b)\nabla_\theta \log g_\theta(x \mid z)\right] \tag{12}$$

From this, it is clear that we can consider the output of the statistic network, $F_\phi(x)$, to be a *reward* and $b = \log \beta = \mathbb{E}_{\mathbb{Q}_\theta}[w(x)]$ to be the analog of a baseline.[4]

2.4   CONTINUOUS VARIABLES AND THE STABILITY OF GANS

For continuous variables, minimizing the variational lower-bound suffices as an optimization technique as we have the full benefit of back-propagation to train the generator parameters, θ. However, while the convergence of the discriminator is straightforward, to our knowledge there is no general proof of convergence for the generator except in the non-parametric limit or near-optimal case. What's worse is the value function can be arbitrarily large and negative. Let us assume that $\max T = M < \infty$ is unique. As $f^\star$ is convex, the minimum of the variational lower-bound over θ is:

$$\inf_\theta \mathcal{V}(\mathbb{P}, \mathbb{Q}_\theta, D_\phi) = \inf_\theta \mathbb{E}_{\mathbb{P}}[T_\phi(x)] - \mathbb{E}_{\mathbb{Q}_\theta}[f^\star(T_\phi(x))]$$

$$= \mathbb{E}_{\mathbb{P}}[T_\phi(x)] - \sup_\theta \mathbb{E}_{\mathbb{Q}_\theta}[f^\star(T_\phi(x))] = \mathbb{E}_{\mathbb{P}}[T_\phi(x)] - f^\star(M). \tag{13}$$

In other words, the generator objective is optimal when the generated distribution, $\mathbb{Q}_\theta$, is nonzero only for the set $\{x \mid T(x) = M\}$. Even outside this worst-case scenario, the additional consequence of this minimization is that this variational lower-bound can become looser w.r.t. the f-divergence, with no guarantee that the generator would actually improve. Generally, this is avoided by training the discriminator in conjunction with the generator, possibly for many steps for every generator update. However, this clearly remains one source of potential instability in GANs.

Equation 7 reveals an alternate objective for the generator that should improve stability. Notably, we observe that for a given estimator, $\tilde{p}(x)$, $q_\theta(x)$ matches when $w(x) = (\partial f^\star / \partial T)(T(x)) = 1$.

Definition 2.5 (Continuous BGAN objective for the generator). Let $G_\theta : \mathcal{Z} \to \mathcal{X}$ be a generator function that takes as input a latent variable drawn from a simple prior, $z \sim h(z)$. Let T_ϕ be

---

[4]Note that we have removed the additional constant as $\mathbb{E}_{q_\theta[1*\nabla_\theta q_\theta]} = 0$

the discriminator function and $w(x) = \partial f^\star / \partial T(T_\phi)$ be the importance weights. We define the continuous BGAN objective as: $\hat{\theta} = \arg\min_\theta (\log w(G_\theta(z)))^2$. We chose the $\log$, as with our treatments of f-divergences in Table 1, the objective is just the square of the statistic network output:

$$\hat{\theta} = \arg\min_\theta F_\phi(G_\theta(z))^2. \tag{14}$$

3 RELATED WORK AND DISCUSSION

Importance sampling   Our method is very similar to reweighted wake-sleep (RWS, Bornschein & Bengio, 2014), which is a method for training Helmholtz machines with discrete variables. RWS also relies on minimizing the KL divergence, the gradients of which also involve a policy gradient over the likelihood ratio. Neural variational inference and learning (NVIL, Mnih & Gregor, 2014), on the other hand, relies on the reverse KL. These two methods are analogous to our importance sampling and REINFORCE-based BGAN formulations above.

GAN for discrete variables   Training GANs with discrete data is an active and unsolved area of research, particularly with language model data involving recurrent neural network (RNN) generators (Yu et al., 2016; Li et al., 2017). Many REINFORCE-based methods have been proposed for language modeling (Yu et al., 2016; Che et al., 2017). There have been some improvements recently on training GANs on language data with REINFORCE (Press et al., 2017) or by rephrasing the problem into a GAN over some continuous space (Lamb et al., 2016; Kim et al., 2017; Gulrajani et al., 2017). However, much of the advances here amount to architectural choices or better optimization procedures, which is out of the scope of this work.

Remarks on stabilizing adversarial learning, IPMs, and regularization   A number of variants of GANs have been introduced recently to address stability issues with GANs. Specifically, generated samples tend to collapse to a set of singular values that resemble the data on neither a per-sample or distribution basis. Several early attempts in modifying the train procedure (Berthelot et al., 2017; Salimans et al., 2016) as well as the identifying of a taxonomy of working architectures (Radford et al., 2015) addressed stability in some limited setting, but it wasn't until Wasserstein GANs (WGAN, Arjovsky et al., 2017) were introduced that there was any significant progress on reliable training of GANs.

WGANs rely on an integral probability metric (IPM, Sriperumbudur et al., 2009) that is the dual to the *Wasserstein distance*. Other GANs based on IPMs, such as Fisher GAN (Mroueh & Sercu, 2017) tout improved stability in training. In contrast to GANs based on f-divergences, besides being based on *metrics* that are "weak", IPMs rely on restricting $\mathcal{T}$ to a subset of all possible functions. For instance in WGANs, $\mathcal{T} = \{T \mid \|T\|_L \leq K\}$, is the set of K-Lipschitz functions. Ensuring a statistic network, T_ϕ, with a large number of parameters is Lipschitz-continuous is *hard*, and these methods rely on some sort of regularization to satisfy the necessary constraints. This includes the original formulation of WGANs, which relied on weight-clipping, and a later work (Gulrajani et al., 2017) which used a gradient penalty over interpolations between real and generated data.

Unfortunately, the above works provide little details on whether T_ϕ is actually in the constrained set in practice, as this is probably very hard to evaluate in the high-dimensional setting. Recently, Roth et al. (2017) introduced a gradient norm penalty similar to that in Gulrajani et al. (2017) without interpolations and which is formulated in terms of f-divergences. In our work, we've found that this approach greatly improves stability, and we use it in nearly all of our results. That said, it is still unclear empirically how the discriminator objective plays a strong role in stabilizing adversarial learning, but at this time it appears that correctly regularizing the discriminator is sufficient.

4 DISCRETE VARIABLES: EXPERIMENTS AND RESULTS

4.1 ADVERSARIAL CLASSIFICATION

We first verify the gradient estimator provided by BGAN works quantitatively in the discrete setting by evaluating its ability to train a classifier. We perform this task with the CIFAR-10

dataset (Krizhevsky & Hinton, 2009). The "generator" in this setting is a multinomial distribution, $g_\theta(y \mid x)$ modeled by the softmax output of a neural network. The discriminator, $T_\phi(x, y)$, takes as input an image / label pair so that the variational lower-bound is:

$$\mathcal{V}(\mathbb{P}_{XY}, \mathbb{Q}_{Y|X}\mathbb{P}_X, T_\phi) = \mathbb{E}_{p(x,y)}[T_\phi(x, y)] - \mathbb{E}_{g_\theta(y|x)p(x)}[f^\star(T_\phi(x, y))] \tag{15}$$

For these experiments, we used a simple 4-layer convolutional neural network with an additional 3 fully-connected layers. We trained the importance sampling BGAN on the set of f-divergences given in Table 1 as well as the REINFORCE counterpart for 200 epochs and report the accuracy on the test set. In addition, we ran a simple classification baseline trained on cross-entropy as well as a continuous approximation to the problem as used in WGAN-based approaches (Gulrajani et al., 2017). No regularization other than batch normalization (BN, Ioffe & Szegedy, 2015) was used with the generator, while gradient norm penalty (Roth et al., 2017) was used on the statistic networks. For WGAN, we used clipping, and chose the clipping parameter, the number of discriminator updates, and the learning rate separately based on training set performance. The baseline for the REINFORCE method was learned using a moving average of the reward.

Table 2: Adversarial classification on CIFAR-10. All methods are BGAN with importance sampling (left) or REINFORCE (right) except for the baseline (cross-entropy) and Wasserstein GAN (WGAN)

	Measure	Error(%)	
	Baseline	26.6	
	WGAN (clipping)	72.3	
		IS	REINFORCE
BGAN	GAN	26.2	27.1
	Jensen-Shannon	26.0	27.7
	KL	28.1	28.0
	Reverse KL	27.8	28.2
	Squared-Hellinger	27.0	28.0

Our results are summarized in Table 2. Overall, BGAN performed similarly to the baseline on the test set, with the REINFORCE method performing only slightly worse. For WGAN, despite our best efforts, we could only achieve an error rate of 72.3% on the test set, and this was after a total of 600 epochs to train. Our efforts to train WGAN using gradient penalty failed completely. This probably should not be interpreted as BGAN being better than WGAN in the discrete setting in general; WGAN worked for us on higher-dimensional data.

4.2 DISCRETE IMAGE AND NATURAL LANGUAGE GENERATION

Image data: binary MNIST and quantized CelebA   We tested BGAN using two imaging benchmarks: the common discretized MNIST dataset (Salakhutdinov & Murray, 2008) and a new quantized version of the CelebA dataset (see Liu et al., 2015, for the original CelebA dataset).

For CelebA quantization, we first downsampled the images from 64×64 to 32×32. We then generated a 16-color palette using Pillow, a fork of the Python Imaging Project (https://python-pillow.org). This palette was then used to quantize the RGB values of the CelebA samples to a one-hot representation of 16 colors. Our models used deep convolutional GANs (DCGAN, Radford et al., 2015). The generator is fed a vector of 64 i.i.d. random variables drawn from a uniform distribution, $[0, 1]$. The output nonlinearity was sigmoid for MNIST to model the Bernoulli centers for each pixel, while the output was softmax for quantized CelebA.

Our results show that training the importance-weighted BGAN on discrete MNIST data is stable and produces realistic and highly variable generated handwritten digits (Figure 1). For quantized CelebA, the generator trained as a BGAN produced reasonably realistic images which resemble the original dataset well and with good diversity.

1-billion word   Next, we test BGAN in a natural language setting with the 1-billion word dataset (Chelba et al., 2013), modeling at the character-level and limiting the dataset to sentences of at least 32 and truncating to 32 characters. For character-level language generation, we follow the

Figure 1: Left: Random samples from the generator trained as a boundary-seeking GAN (BGAN) with discrete MNIST data. Shown are the Bernoulli centers of the generator conditional distribution.

Figure 2: Left: Ground-truth 16-color (4-bit) quantized CelebA images downsampled to 32×32. Right: Samples produced from the generator trained as a boundary-seeking GAN on the quantized CelebA for 50 epochs.

Table 3: Random samples drawn from a generator trained with the discrete BGAN objective. The model is able to successfully learn many important character-level English language patterns.

And it 's miant a quert could he	He weirst placed produces hopesi	What 's word your changerg bette
" We pait of condels of money wi	Sance Jory Chorotic , Sen doesin	In Lep Edger 's begins of a find",
Lankard Avaloma was Mr. Palin ,	What was like one of the July 2	" I stroke like we all call on a
Thene says the sounded Sunday in	The BBC nothing overton and slea	With there was a passes ipposing
About dose and warthestrinds fro	College is out in contesting rev	And tear he jumped by even a roy

architecture of recent work (Gulrajani et al., 2017), and use deep convolutional neural networks for both the generator and discriminator.

Training with BGAN yielded stable, reliably good character-level generation (Table 3), though generation is poor compared to recurrent neural network-based methods (Sutskever et al., 2011; Mikolov, 2012). However, we are not aware of any previous work in which a discrete GAN, without any continuous relaxation (Gulrajani et al., 2017), was successfully trained from scratch without pretraining and without an auxiliary supervised loss to generate any sensible text. Despite the low quality of the text relative to supervised recurrent language models, the result demonstrates the stability and capability of the proposed boundary-seeking criterion for training discrete GANs.

5 CONTINUOUS VARIABLES: EXPERIMENTS AND RESULTS

Here we present results for training the generator on the boundary-seeking objective function. In these experiments, we use the original GAN variational lower-bound from Goodfellow et al. (2014), only modifying the generator function. All results use gradient norm regularization (Roth et al., 2017) to ensure stability.

5.1 GENERATION BENCHMARKS

We test here the ability of continuous BGAN to train on high-dimensional data. In these experiments, we train on the CelebA and LSUN (Yu et al., 2015) datasets. The discriminator and generator were both modeled as 4-layer Resnets (He et al., 2016).

Figure 3 shows examples from BGAN trained on these datasets. Overall, the sample quality is very good. However, the story here isn't that BGAN necessarily generates better images than using the variational lower-bound to train the generator, since we found that images of similar quality could be attained without the boundary-seeking loss as long as gradient norm regularization was used, rather we confirm that BGAN works well in the high-dimensional setting.

5.2 STABILITY OF CONTINUOUS BGAN

As mentioned above, gradient norm regularization greatly improves stability and allows for training with very large architectures. However, training still relies on a delicate balance between the

CelebA   LSUN

Figure 3: Highly realistic samples from a generator trained with BGAN on the CelebA and LSUN datasets. These models were trained using a deep ResNet architecture with gradient norm regularization (Roth et al., 2017).

Figure 4: Training a GAN with different generator loss functions and 5 updates for the generator for every update of the discriminator. Over-optimizing the generator can lead to instability and poorer results depending on the generator objective function. Samples for GAN and GAN with the proxy loss are quite poor at 50 discriminator epochs (250 generator epochs), while BGAN is noticeably better. At 100 epochs, these models have improved, though are still considerably behind BGAN.

generator and discriminator: over-training the generator may destabilize learning and lead to worse results. We find that the BGAN objective is resilient to such over-training.

Stability in training with an overoptimized generator   To test this, we train on the CIFAR-10 dataset using a simple DCGAN architecture. We use the original GAN objective for the discriminator, but vary the generator loss as the variational lower-bound, the proxy loss (i.e., the generator loss function used in Goodfellow et al., 2014), and the boundary-seeking loss (BGAN). To better study the effect of these losses, we update the generator for 5 steps for every discriminator step.

Our results (Figure 5) show that over-optimizing the generator significantly degrades sample quality. However, in this difficult setting, BGAN learns to generate reasonable samples in fewer epochs than other objective functions, demonstrating improved stability.

Following the generator gradient   We further test the different objectives by looking at the effect of gradient descent on the pixels. In this setting, we train a DCGAN (Radford et al., 2015) using the proxy loss. We then optimize the discriminator by training it for another 1000 updates. Next, we

Figure 5: Following the generator objective using gradient descent on the pixels. BGAN and the proxy have sharp initial gradients that decay to zero quickly, while the variational lower-bound objective gradient slowly increases. The variational lower-bound objective leads to very poor images, while the proxy and BGAN objectives are noticeably better. Overall, BGAN performs the best in this task, indicating that its objective will not overly disrupt adversarial learning.

perform gradient descent directly on the pixels, the original variational lower-bound, the proxy, and the boundary seeking losses separately.

Our results show that following the BGAN objective at the pixel-level causes the least degradation of image quality. This indicates that, in training, the BGAN objective is the least likely to disrupt adversarial learning.

6 CONCLUSION

Reinterpreting the generator objective to match the proposal target distribution reveals a novel learning algorithm for training a generative adversarial network (GANs, Goodfellow et al., 2014). This proposed approach of boundary-seeking provides us with a unified framework under which learning algorithms for both discrete and continuous variables are derived. Empirically, we verified our approach quantitatively and showed the effectiveness of training a GAN with the proposed learning algorithm, which we call a boundary-seeking GAN (BGAN), on both discrete and continuous variables, as well as demonstrated some properties of stability.

REFERENCES

Arjovsky, Martin, Chintala, Soumith, and Bottou, Léon. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Bengio, Yoshua, Léonard, Nicholas, and Courville, Aaron. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Berthelot, David, Schumm, Tom, and Metz, Luke. Began: Boundary equilibrium generative adversarial networks. *arXiv preprint arXiv:1703.10717*, 2017.

Bornschein, Jörg and Bengio, Yoshua. Reweighted wake-sleep. *arXiv preprint arXiv:1406.2751*, 2014.

Che, Tong, Li, Yanran, Zhang, Ruixiang, Hjelm, R Devon, Li, Weijie, Song, Yangqiu, and Bengio, Yoshua. Maximum-likelihood augmented discrete generative adversarial networks. *arXiv preprint*, 2017.

Chelba, Ciprian, Mikolov, Tomas, Schuster, Mike, Ge, Qi, Brants, Thorsten, Koehn, Phillipp, and Robinson, Tony. One billion word benchmark for measuring progress in statistical language modeling. *arXiv preprint arXiv:1312.3005*, 2013.

Goodfellow, Ian, Pouget-Abadie, Jean, Mirza, Mehdi, Xu, Bing, Warde-Farley, David, Ozair, Sherjil, Courville, Aaron, and Bengio, Yoshua. Generative adversarial nets. In *Advances in Neural Information Processing Systems*, pp. 2672–2680, 2014.

Gu, Shixiang, Levine, Sergey, Sutskever, Ilya, and Mnih, Andriy. Muprop: Unbiased backpropagation for stochastic neural networks. *arXiv preprint arXiv:1511.05176*, 2015.

Gulrajani, Ishaan, Ahmed, Faruk, Arjovsky, Martin, Dumoulin, Vincent, and Courville, Aaron. Improved training of wasserstein gans. *arXiv preprint arXiv:1704.00028*, 2017.

Gumbel, Emil Julius and Lieblein, Julius. Statistical theory of extreme values and some practical applications: a series of lectures. *US Govt. Print. Office*, 1954.

He, Kaiming, Zhang, Xiangyu, Ren, Shaoqing, and Sun, Jian. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Ioffe, Sergey and Szegedy, Christian. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Jang, Eric, Gu, Shixiang, and Poole, Ben. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Kim, Yoon, Zhang, Kelly, Rush, Alexander M, LeCun, Yann, et al. Adversarially regularized autoencoders for generating discrete structures. *arXiv preprint arXiv:1706.04223*, 2017.

Krizhevsky, Alex and Hinton, Geoffrey. Learning multiple layers of features from tiny images. *Citeseer*, 2009.

Lamb, Alex M, GOYAL, Anirudh Goyal ALIAS PARTH, Zhang, Ying, Zhang, Saizheng, Courville, Aaron C, and Bengio, Yoshua. Professor forcing: A new algorithm for training recurrent networks. In *Advances In Neural Information Processing Systems*, pp. 4601–4609, 2016.

Li, Jiwei, Monroe, Will, Shi, Tianlin, Ritter, Alan, and Jurafsky, Dan. Adversarial learning for neural dialogue generation. *arXiv preprint arXiv:1701.06547*, 2017.

Liu, Ziwei, Luo, Ping, Wang, Xiaogang, and Tang, Xiaoou. Deep learning face attributes in the wild. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3730–3738, 2015.

Maddison, Chris J, Mnih, Andriy, and Teh, Yee Whye. The concrete distribution: A continuous relaxation of discrete random variables. *arXiv preprint arXiv:1611.00712*, 2016.

Mao, Xudong, Li, Qing, Xie, Haoran, Lau, Raymond YK, Wang, Zhen, and Smolley, Stephen Paul. Least squares generative adversarial networks. *arXiv preprint ArXiv:1611.04076*, 2016.

Mikolov, Tomáš. *Statistical Language Models Based on Neural Networks*. PhD thesis, Ph. D. thesis, Brno University of Technology, 2012.

Mnih, Andriy and Gregor, Karol. Neural variational inference and learning in belief networks. In *Proceedings of the 31st International Conference on Machine Learning (ICML-14)*, pp. 1791–1799, 2014.

Mroueh, Youssef and Sercu, Tom. Fisher gan. *arXiv preprint arXiv:1705.09675*, 2017.

Mroueh, Youssef, Sercu, Tom, and Goel, Vaibhava. Mcgan: Mean and covariance feature matching gan. *arXiv preprint arXiv:1702.08398*, 2017.

Nguyen, XuanLong, Wainwright, Martin J, and Jordan, Michael I. Estimating divergence functionals and the likelihood ratio by convex risk minimization. *IEEE Transactions on Information Theory*, 56(11):5847–5861, 2010.

Nowozin, Sebastian, Cseke, Botond, and Tomioka, Ryota. f-gan: Training generative neural samplers using variational divergence minimization. In *Advances in Neural Information Processing Systems*, pp. 271–279, 2016.

Press, Ofir, Bar, Amir, Bogin, Ben, Berant, Jonathan, and Wolf, Lior. Language generation with recurrent generative adversarial networks without pre-training. *arXiv preprint arXiv:1706.01399*, 2017.

Radford, Alec, Metz, Luke, and Chintala, Soumith. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Roth, Kevin, Lucchi, Aurelien, Nowozin, Sebastian, and Hofmann, Thomas. Stabilizing training of generative adversarial networks through regularization. *arXiv preprint arXiv:1705.09367*, 2017.

Rubinstein, Reuven Y and Kroese, Dirk P. *Simulation and the Monte Carlo method*, volume 10. John Wiley & Sons, 2016.

Salakhutdinov, Ruslan and Murray, Iain. On the quantitative analysis of deep belief networks. In *Proceedings of the 25th international conference on Machine learning*, pp. 872–879. ACM, 2008.

Salimans, Tim, Goodfellow, Ian, Zaremba, Wojciech, Cheung, Vicki, Radford, Alec, and Chen, Xi. Improved techniques for training gans. In *Advances in Neural Information Processing Systems*, pp. 2234–2242, 2016.

Sriperumbudur, Bharath K, Fukumizu, Kenji, Gretton, Arthur, Schölkopf, Bernhard, and Lanckriet, Gert RG. On integral probability metrics,\phi-divergences and binary classification. *arXiv preprint arXiv:0901.2698*, 2009.

Sutherland, Dougal J, Tung, Hsiao-Yu, Strathmann, Heiko, De, Soumyajit, Ramdas, Aaditya, Smola, Alex, and Gretton, Arthur. Generative models and model criticism via optimized maximum mean discrepancy. *arXiv preprint arXiv:1611.04488*, 2016.

Sutskever, Ilya, Martens, James, and Hinton, Geoffrey E. Generating text with recurrent neural networks. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pp. 1017–1024, 2011.

Tucker, George, Mnih, Andriy, Maddison, Chris J, and Sohl-Dickstein, Jascha. Rebar: Low-variance, unbiased gradient estimates for discrete latent variable models. *arXiv preprint arXiv:1703.07370*, 2017.

Yu, Fisher, Zhang, Yinda, Song, Shuran, Seff, Ari, and Xiao, Jianxiong. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Yu, Lantao, Zhang, Weinan, Wang, Jun, and Yu, Yong. Seqgan: sequence generative adversarial nets with policy gradient. *arXiv preprint arXiv:1609.05473*, 2016.