LEARNING TO GROUP: A BOTTOM-UP FRAMEWORK FOR 3D PART DISCOVERY IN UNSEEN CATEGORIES

ABSTRACT

We address the problem of learning to discover 3D parts for objects in unseen categories. Being able to learn the geometry prior of parts and transfer this prior to unseen categories pose fundamental challenges on data-driven shape segmentation approaches. Formulated as a contextual bandit problem, we propose a learning-based iterative grouping framework which learns a grouping policy to progressively merge small part proposals into bigger ones in a bottom-up fashion. At the core of our approach is to restrict the local context for extracting part-level features, which encourages the generalizability to novel categories. On a recently proposed large-scale fine-grained 3D part dataset, PartNet, we demonstrate that our method can transfer knowledge of parts learned from 3 training categories to 21 unseen testing categories without seeing any annotated samples. Quantitative comparisons against four strong shape segmentation baselines shows that we achieve the state-of-the-art performance.

1 INTRODUCTION

Perceptual grouping has been a long-standing problem in the study of vision systems (Hoffman & Richards, 1984). The process of perceptual grouping determines which regions of the visual input belong together as parts of higher-order perceptual units. Back to the 1930s, Wertheimer (1938) listed several vital factors, such as similarity, proximity, and good continuation, which lead to visual grouping. In the era of deep learning, high-level cues can be learned from massive annotated datasets. However, even to this day, learning-based segmentation algorithms are still far inferior to human visual systems when it comes to unseen categories. In this paper, we present a new general learning-based framework for the perceptual grouping task, focusing especially on the case of 3D shape part discovery in the zero-shot learning setting.

With the power of big data, deep neural networks that learn data-driven features to segment shape parts, such as (Kalogerakis et al., 2010; Graham et al., 2018; Mo et al., 2019), have demonstrated the state-of-the-art performance on many shape segmentation benchmarks (Yi et al., 2016; Mo et al., 2019). The key to success is to train with large-scale annotated training samples and learn to extract features that maximally ex-

Figure 1: Shape Segmentation Results on unseen categories. Left column shows the results of SOTA deep-learning method with using global contextual information and right is ours.

ploit the data structure of the training categories. These networks usually have large receptive fields that extract features from the whole input shape and take advantage of learning global context for understanding part semantics and shape structures. While learning such features with global contextual information leads to superior performance on the training categories, they often fail miserably on unseen categories (Figure 1), as big domain gaps are observed across seen and unseen categories.

On the contrary, classical shape segmentation methods, such as (Kaick et al., 2014), that use manually designed features with relatively more local context, though giving inferior segmentation results, can perform much better for unseen object classes. In fact, many globally different shapes share similar parts locally. For example, airplanes, cars, and swivel chairs all have wheels as sub-components,

even though the global geometry is totally different. Having the knowledge of wheels learned from airplanes should help recognize wheels for cars and swivel chairs, since the local geometry and semantic functionality of wheels share across the boundary of object classes. Also, automatic part discovery for unseen categories is more favorable than collecting manually labeled ground-truth for every new category for shape segmentation.

In this paper, we aim to combine the benefits of learning data-driven part priors and extracting local-context features to perform part discovery across object categories in a zero-shot setting. We start from learning to propose a pool of superpixel-like sub-parts within local context for each shape. Then, we learn a grouping policy that seeks to gradually increase the part local context and group sub-parts for final part proposals. What lies in the heart of our algorithm is to learn a function to assess whether two parts should be grouped. Different from prior deep segmentation work that learns point features, our formulation essentially learns part-level features. Borrowing ideas from Reinforcement Learning (RL), we formalize the process as a contextual bandit problem and train a local grouping policy to pick a pair of sub-parts to group iteratively. In both steps, we learn features within part local context aiming for generalizing to unseen categories. Our *learning-based agglomerative clustering* framework deviates drastically from the prevailing deep segmentation pipelines and makes one step towards generalizable part discovery in unseen object categories.

To summarize, we make the following contributions:

- We formulate the task of zero-shot part discovery on a large-scale fine-grained shape segmentation benchmark PartNet (Mo et al., 2019);
- We propose a learning-based agglomerative clustering framework that learns to do part proposals and grouping from training categories and generalizes to unseen novel categories;
- We quantitatively compare our approach to several baseline methods and demonstrate the state-of-the-art results for part discovery in unseen object categories.

2   RELATED WORK

Shape segmentation has been a classic and fundamental problem in computer vision and graphics. Dated back to 1990s, researchers have started to design heuristic geometric criterion for segmenting 3D meshes, including methods based on morphological watersheds (Mangan & Whitaker, 1999), K-means (Shlafman et al., 2002), core extraction (Katz et al., 2005), graph cuts (Golovinskiy & Funkhouser, 2008), random walks (Lai et al., 2008), spectral clustering (Liu & Zhang, 2004) and primitive fitting (Attene et al., 2006a), to name a few. See Attene et al. (2006b); Shamir (2008); Chen et al. (2009) for more comprehensive surveys on mesh segmentation. Many papers study mesh co-segmentation that discover consistent part segmentation over a collection of shapes (Golovinskiy & Funkhouser, 2009; Huang et al., 2011; Sidi et al., 2011; Hu et al., 2012; Wang et al., 2012; Van Kaick et al., 2013). Our approach takes point clouds as inputs as they are closer to the real-world scanners. Different from meshes, point cloud data lacks the local vertex normal and connectivity information. Kaick et al. (2014) segments point cloud shapes under the part convexity constraints. Our work learns shared part priors from training categories and thus can adapt to different segmentation granularity required by different end-stream tasks.

In recent years, with the increasing availability of annotated shape segmentation datasets (Chen et al., 2009; Yi et al., 2016; Mo et al., 2019), many supervised learning approaches succeed in refreshing the state-of-the-arts. Kalogerakis et al. (2010); Guo et al. (2015); Wang et al. (2018a) learn to label mesh faces with semantic labels defined by human. See Xu et al. (2016) for a recent survey. More recent works propose novel 3D deep network architectures segmenting shapes represented as 2D images (Kalogerakis et al., 2017), 3D voxels (Maturana & Scherer, 2015), sparse volumetric representations (Klokov & Lempitsky, 2017; Riegler et al., 2017; Wang et al., 2017; Graham et al., 2018), point clouds (Qi et al., 2017a;b; Wang et al., 2018b; Yi et al., 2019) and graph-based representations (Yi et al., 2017). These methods take advantage of sufficient training samples of seen categories and demonstrate appealing performance for shape segmentation. However, they often perform much worse when testing on unseen categories, as the networks overfit their weights to the global shape context in training categories. Our work focus on learning context-free part knowledges and perform part discovery in a zero-shot setting on novel object classes.

There are also a few relevant works trying to reduce supervisions for shape part segmentation. Makadia & Yumer (2014) learns from sparsely labeled data that only one vertex per part is given the

ground-truth. Yi et al. (2016) proposes an active learning framework to propogate part labels from a selected sets of shapes with human labeling. Lv et al. (2012) proposes a semi-supervised Conditional Random Field (CRF) optimization model for mesh segmentation. Shu et al. (2016) proposes an unsupervised learning method for learning features to group superpixels on meshes. Our work processes point cloud data and focus on a zero-shot setting, while part knowledge can be learned from training categories and transferred to unseen categories.

Our work is also related to many recent research studying learning based bottom-up methods for 2D instance segmentation. These methods learn an per-pixel embedding and utilize a clustering algorithm (Newell et al., 2017; Fathi et al., 2017) as post-process or integrating a recurrent mean-shift module (Kong & Fowlkes, 2018) to generate final instances. Bai & Urtasun (2017) predicts the energy of the watershed transform and Liu et al. (2017) predicts object breakpoints and use a cascade of networks to group the pixels into lines, components and objects sequentially. Our work is significant different from previous methods as our method does not rely on an fully convolutional neural network to process the whole scene. Our work can generalize better to unseen categories as our method reduces the influences of context.

3 PROBLEM FORMULATION

We consider the task of zero-shot shape part discovery on 3D point clouds in unseen object categories. For a 3D shape S (*e.g.* a 3D chair model), we consider the point cloud $C_S = \{p_1, p_2, \cdots, p_N\}$ sampled from the surface of the 3D model. A part $P_i = \{p_{i_1}, p_{i_2}, \cdots, p_{i_t}\} \subseteq C_S$ defines a group of points that has certain interesting semantics for some specific downstream task. A set of part proposal $\mathcal{P}_S = \{P_1, P_2, \cdots, P_S\}$ comprises of several interesting part regions on S that are useful for various tasks. The task of shape part discovery on point clouds is to produce $\mathcal{P}_S^{pred}$ for each input shape point cloud C_S. Ground-truth proposal set $\mathcal{P}_S^{gt}$ is a manually labeled set of parts that are useful for some human-defined downstream tasks. A good algorithm should predict $\mathcal{P}_S^{pred}$ such that $\mathcal{P}_S^{gt} \subseteq \mathcal{P}_S^{pred}$ within an upper-bound limit of part numbers M.

A category of shapes $T = \{S_1, S_2, \cdots\}$ gathers all shapes that belong to one semantic category. For example, T_{chair} includes all chair 3D models in a dataset. Zero-shot shape part discovery considers two sets of object categories $\mathcal{T}_{train} = \{T_1, T_2, \cdots, T_u\}$ and $\mathcal{T}_{test} = \{T_{u+1}, T_{u+2}, \cdots, T_v\}$, where $T_i \cap T_j = \emptyset$ for any $i \neq j$. For each shape $S \in T \in \mathcal{T}_{train}$, a manually labeled part proposal subset $\mathcal{P}_S^{gt} \subseteq \mathcal{P}_S$ is given for algorithms to use. It provides algorithms an opportunity to develop the concept of parts in the training categories. No ground-truth part proposals are provided for shapes in testing categories $\mathcal{T}_{test}$. Algorithms are expected to predict $\mathcal{P}_S^{pred}$ for any shape $S \in T \in \mathcal{T}_{test}$.

4 METHOD

Our method starts with proposing a set of small superpixel-like (Ren & Malik, 2003) sub-parts of the given shape. We refer readers to Appendix A for more details of our sub-part proposing method. Given a set of sub-parts, our method iteratively groups together the sub-parts belonging to the same parts in ground-truth and produce larger sub-parts, until no sub-part can further group each other. The remaining sub-parts in the final stage become a pool of part proposals for the input shape.

Our perceptual grouping process is a sequential decision process. We formulate the perceptual grouping process as a contextual bandit (one-step Markov Decision Process) (Langford & Zhang, 2007). In each iteration, we use a policy network to select a pair of sub-parts and send it to the verification network to verify whether we should group the selected pair of sub-parts. If yes, we group the selected pair of sub-parts into a larger sub-part. Otherwise, we will not consider this pair in the latter grouping process. Our policy network is composed of two sub-modules: a purity module and a rectification module. The purity module inputs unary information and measures how likely two sub-parts belong to the same part in ground-truth after grouping and the rectification module inputs binary information and further decides the pair to select. We describe more technical network design choices in Section 4.1. To train the entire pipeline, we borrow the on-policy training scheme from Reinforcement Learning (RL) to train these networks, in order to match the data distribution during training and inference stages, as described in Section 4.2.

4.1 MODULE DESIGNS

Figure 2: Network Architectures for Three Network Modules. N is the point number of input sampled from a sub-part. f is the dimension of feature.

Purity Module: Two sub-parts that belong to the same ground-truth part should group together. We define *purity score* $U(P)$ for a sub-part P as the maximum ratio of the intersection of P with the ground-truth parts $\{P_i^{gt}\}$. More formally,

$$U(P) = \max_{P_i^{gt}} \frac{\sum_p I[p \in P]I[p \in P_i^{gt}]}{\sum_p I[p \in P]} \tag{1}$$

where p enumerates all points in the shape point cloud and I is the indicator function.

We train a purity module to predict the purity score. It employs a PointNet that takes as input a merged sub-part $P_{ij} = P_i \cup P_j$ and predicts the purity score. Figure 2 (a) shows the architecture.

Rectification Module: We observe that a purity module is not enough to fully select the best pair of sub-parts to group in practice. For example, when a big sub-part tries to group with a small one from a different ground-truth part, the part geometry of the grouping outcome is primarily dominated by the big sub-part, and thus the purity module tends to produce a high purity score, which results in selecting a pair that should not be grouped. To address this issue, we consider learning a rectification module to correct the failure case given by the purity module.

We design the rectification module as in Figure 2 (b). The rectification module takes two sub-parts as inputs, extracts features using a shared PointNet, concatenates the two part features and outputs a real-valued *rectification score* $R(P)$, based purely on local information. Different from the purity module that takes the grouped subpart as input, the rectification module explicitly takes two sub-parts as inputs in order to compare the two sub-part features for decision making.

Policy Network: We define *policy score* by making the product of *purity score* and *rectification score*. We define the policy $\pi(P_i, P_j|\mathcal{P})$ as a distribution over all possible pairs characterized by a softmax layer as shown in line 6 of Algorithm 1. The goal of the policy is to maximize the objective

$$\operatorname*{maximize}_{\pi} E_{a \sim \pi(P_i, P_j|\mathcal{P})} \left[\pi(a|\mathcal{P})M(a) \right].$$

The reward, or the merge-ability score $M(P_i, P_j)$ defines whether we could group two sub-parts P_i and P_j. To compute the reward $M(P_i, P_j)$: we first calculate the instance label of the corresponding ground-truth part for sub-parts P_i, P_j as l_i and l_j. We set $M(P_i, P_j)$ to be one if the two sub-parts have the same instance label and the purity scores of two sub-parts are greater than 0.8.

Verification Network: Since the policy scores sum to one overall pairs of sub-parts, there is no explicit signal from the policy network on whether the pair should be grouped. We train a separate verification network that is specialized to verify whether we should group the selected pair. Here also exists a cascaded structure where the verification network will focus on the pairs selected by the policy network and make a double verification.

The verification network takes a pair of shape as input and outputs values from zero to one after a Sigmoid layer. Figure 2 (c) illustrates the network architecture: a PointNet first extracts the part

---

Algorithm 1 Sub-Part Pair Selection and Grouping.

Input: A sub-parts pool $\mathcal{P} = \{P_i\}_{i \leq n}$
Input: Purity module U; Rectification module R; Verification network V
1: **for** $i, j \leq n$ **do**
2:      Group two shapes: $P'_{ij} \leftarrow \{P_i \cup P_j\}$
3:      Calculate the purity score $u_{i,j} \leftarrow U(P'_{ij})$
4:      Calculate the rectification score $r_{ij} \leftarrow R(P_i, P_j)$
5: **end for**
6: Calculate policy $\pi(P_i, P_j) \leftarrow \frac{e^{r_{ij} u_{ij}}}{\sum_{i,j} e^{r_{ij} u_{ij}}}$
7: **if** isTraining **then**
8:      Sample pair $P_i, P_j \sim \pi(P_i, P_j)$
9: **else**
10:      Select the $P_i, P_j = \arg\max \pi(P_i, P_j)$
11: **end if**
12: **if** $V(P_i, P_j)$ is True **then**
13:      Delete P_i, P_j from the pool
14:      Add P'_{ij} into the pool
15: **end if**

---

feature for each sub-part, then two sub-part point clouds are augmented with the extracted part features and concatenated together to pass through another PointNet to obtain the final score. Notice that our design of the verification network is a combination of the purity module and rectification module. We want to extract both the input sub-part features and the part feature after grouping.

4.2   Network Training

In this section, we illustrate how to train the two networks jointly as an entire pipeline. We use Reinforcement Learning (RL) on-policy training and borrow the standard RL training techniques, such as epsilon-greedy exploration and replay buffer sampling. We also discuss the detailed loss designs for training the policy network and the verification network.

RL On-policy Training   Borrowing ideas from the field of Reinforcement Learning (RL), we train the policy network and the verification network in an on-policy fashion. On-policy training alternates between the data sampling step and the network training step. The data sampling step fixes the network parameters and then runs the inference-time pipeline to collect the grouping trajectories, including all pairs of sub-parts seen during the process and all the grouping operations taken by the pipeline. The network training step uses the trajectory data collected from the data sampling step to compute losses for different network modules and performs steps of gradient descents to update the network parameters. We fully describe the on-policy training algorithm in Algorithm 2.

We adapt epsilon-greedy strategy (Mnih et al., 2013) into the training stage. We start from involving 80% random sampling samples during inference as selected pairs and decay the ratio with 10% step size in each epoch. We find that random actions not only improve the exploration in the action space and but also serve as the data-augmentation role. The random actions collect more samples to train the networks, which improves the transfer performance in unseen categories.

Also, purely on-policy training would drop all experience but only use the data sampled by current policy. This is not data efficient, so we borrow the idea from DQN (Mnih et al., 2013) and use the replay buffer to store and utilize the experience. The replay buffer stores all the states and actions during the inference stage. When updating the policy networks, we sample a batch of transitions, *i.e.* , the grouped sub-parts, and the sub-part pools when the algorithm groups the sub-parts from the replay buffer. The batch data is used to compute losses and gradients to update the two networks.

Training Losses   As shown in Algorithm 2, to train the networks, we sample a batch of data $(P_i^k, P_j^k, \mathcal{P}^k)_{k \leq N}$ from the replay buffer, where P_i^k, P_j^k is the grouped pair and $\mathcal{P}^k$ is the corresponding sub-parts pool. We first calculate the reward M_{gt}^k and ground-truth purity score U_{gt}^k for each data in the batch. For updating the rectification module, we fix the purity module and calculate the policy gradient (Sutton et al., 2000) of the policy network with the reward M_{gt}^k shown in line 11. As the rectification module is a part of the policy network, the gradient will update the rectification

---

Algorithm 2 RL On-policy Training Algorithm.

Input: Purity module U_θ parameterized by θ; Rectification module π_ϕ parameterized by ϕ; Verification network V

1: Initialize buffer B and the networks
2: **while** True **do**
3:     Sample shape S and its ground truth-label gt.
4:     Preprocess S to get a sub-parts pool $\mathcal{P} = \{P_i\}_{i \leq n}$
5:     **while** $\exists$ Mergable sub-parts **do**
6:         Select and group two sub-parts P_i, P_j with Algorithm 1
7:         Store $(P_i, P_j, \mathcal{P})$ in B and update sub-part pool $\mathcal{P}$
8:         Sample batch of data $(P_i^k, P_j^k, \mathcal{P}^k)_{k \leq N}$ from the buffer
9:         Set purity score $U_{gt}^k = U(P_i^k \cup P_j^k)$
10:        Set reward $M_{gt}^k = M(P_i^k, P_j^k)$
11:        Update purity module by minimizing the l_2 loss with purity score U_{gt}^k:

$$\mathcal{L}_{\text{purity}} = \frac{1}{N} \sum_{k \leq N} \| U_\theta(P_{ij}^k) - U_{gt}^k \|_2^2$$

12:        Update rectification module with policy gradient:

$$\nabla_\phi \approx \frac{1}{N} \sum_{k \leq N} \nabla \log \pi_\phi(P_i^k, P_j^k | \mathcal{P}^k) M_{gt}^k$$

13:        Update verification network by minimizing the cross entropy loss :

$$\mathcal{L}_{\text{verification}} = \frac{1}{N} \sum_{k \leq N} M_{gt}^k \log V(P_i^k, P_j^k) + (1 - M_{gt}^k) \log\left(1 - V(P_i^k, P_j^k)\right)$$

14:     **end while**
15: **end while**

---

module by backpropagation. We then use the l_2 loss in line 12 to train the purity module and use the cross entropy loss in line 13 to train the verification network.

5 EXPERIMENTS AND ANALYSIS

In this section, we conduct quantitative evaluations of our proposed framework and present extensive comparisons to four previous state-of-the-art shape segmentation methods using PartNet dataset (Mo et al., 2019) in zero-shot part discovery setting. We also show a diagnostic analysis of how the discovered part knowledge transfers across different object categories.

5.1 DATASET AND EVALUATION

We use the recently proposed PartNet dataset (Mo et al., 2019) as the main testbed. PartNet provides fine-grained, hierarchical and instance-level part annotations for 26,671 3D models from 24 object categories. PartNet defines up to three levels of non-overlapping part segmentation for each object category, from coarse-grained parts (*e.g.* chair back, chair base) to fine-grained ones (*e.g.* chair back vertical bar, swivel chair wheel). Unless otherwise noticed, we use 3 categories (*i.e.* Chair, Storage Furniture and Lamp)[1] for training and take the rest 21 categories as unseen categories for testing.

In zero-shot part discovery setting, we aim to propose parts that are useful under various different use cases. PartNet provides multi-level human-defined semantic parts that can serve as a sub-sampled pool of interesting parts. Thus, we adopt Mean Recall (Hosang et al., 2015; Sung et al., 2018) as the evaluation metric to measure how the predicted part pool covers the PartNet-defined parts. To elaborate on the calculation of Mean Recall, we first define R_t as the fraction of ground-truth parts

---

[1]We pick the three categories because they are big categories with several thousand models per category and provide a large variety of parts for learning.

that have Intersection-over-Union (IoU) over t with any predicted part. Mean Recall is then defined as the average values of R_t's where t varies from 0.5 to 0.95 with 0.05 as a step size.

5.2 BASELINE METHODS

We compare our approach to four previous state-of-the-art methods as follows:

- **PartNet-InsSeg**: Mo et al. (2019) proposed a part instance segmentation network that employs a PointNet++ (Qi et al., 2017b) as the backbone that takes as input the whole shape point cloud and directly predicts 200 part instance masks. The method is a top-down label-prediction method that uses the global shape information.
- **SGPN**: Wang et al. (2018b) presented a learning-based bottom-up grouping method, which learns to extract per-point features and compute pairwise affinity matrix for point grouping. The method also uses PointNet++ features with global shape context.
- **GSPN**: Yi et al. (2019) introduced a deep region-based method that learns generative models for part proposals. The method proposes local part bounding boxes but still uses globally-aware PointNet++ features for predicting boxes and part masks inside boxes.
- **WCSeg**: Kaick et al. (2014) is a non-learning based method based on the convexity assumption of parts. The method leverages hand-engineered heuristics to segment shapes, and thus is agnostic to the boundary of object categories.

All the three deep learning based methods take advantage of the global shape context to achieve state-of-the-art shape part segmentation results on PartNet. However, these networks are prone to over-fitting to training categories and have a hard time transferring part knowledge to unseen categories. WCSeg, as a non-learning based method, demonstrates good generalization capability to unseen categories, but is limited by the part convexity assumption.

	Seen Category				Unseen Category								
				Avg.									
PartNet	**55.7**	50.5	**23.8**	**47.8**	18.2	9.7	40.7	73.5	30.3	30.4	43.6	32.1	16.5
SGPN	42.2	44.2	11.5	36	21.4	7	46.7	53.3	27.7	8.7	34.8	28.9	25.5
GSPN	39.7	43.7	14.4	34.4	35	8.4	46.9	72.8	42.3	**40.6**	57.8	37.4	28.4
WCSeg	29.6	53	2.9	28.5	**43.1**	8.7	**59.1**	69.8	38.7	27.5	61.1	32.3	**38**
Ours	50.9	**57.1**	22	45.9	41.5	**11.3**	49.3	**75.7**	**43.8**	31	**66.7**	**38.2**	34.4
	Unseen Category												
													Avg.
PartNet	16.6	52.5	0.4	33.6	82.1	29.6	33	25	0.8	38.9	13.6	36.8	35.7
SGPN	20	37	0.4	31	67.3	7.2	13.3	5.9	6.4	34.8	7.75	27.5	30.8
GSPN	25.3	31.7	0.4	18.9	92.9	**39.2**	40.6	26.4	3.7	34.6	12.7	41.4	34.7
WCSeg	**47.8**	**53.4**	0.3	**62.4**	62.1	30	52.6	19.9	**46.3**	30.2	13.2	33	33
Ours	32.3	40	0.4	46.6	**96.9**	35.9	**53.3**	**27.6**	16.7	**45**	**15.2**	**43.4**	**42.9**

Table 1: Quantitative Evaluation. The number is the average among mean recall of three levels segmentation results in PartNet. Two Avg. are average among seen and unseen categories over shape numbers, respectively.

5.3 RESULTS AND ANALYSIS

We compare our proposed framework to the four baseline methods under the Mean Recall metric. For PartNet-InsSeg, SGPN, GSPN and our method, we train three networks corresponding to three levels of segmentation for training categories (*e.g.* Chair, Storage Furniture and Lamp). We remove the part semantics prediction branch from the three baseline methods, as semantics are not transferable to novel testing categories. For WCSeg, point normals are required by the routine to check local patch continuity. PartNet experiments (Mo et al., 2019) usually assume no such point normals as inputs. Thus, we approximately compute normals based on the input point clouds by reconstructing surface with ball pivoting (Bernardini et al., 1999). Then, to obtain three-levels of part proposals for WCSeg, we manually tune hyperparameters in the procedure at each level of part annotations on training categories to match the average part prediction counts per level to the ground-truth counts in PartNet. Since the segmentation levels for different categories may not share consistent part granularity (*e.g.* display level-2 parts may correspond to chair level-3 parts), we gather together the part proposals generated by methods at all three levels as a joint pool of proposals for evaluation on

levels of unseen categories. For the proposed method, we involve appropriate context only on seen categories as presented in Appendix B.1.

We present quantitative and qualitative evaluations to baseline methods in Table 1, Figure 3 and Appendix C. For each testing category, we report the average values of Mean Recall scores at all levels. See the appendix Table 6 for detailed numbers at all levels. We observe that our approach achieves the best performance on average among all testing novel categories, while championing 11 out of 20 categories.

Figure 3: Qualitative results on unseen categories. More visualizations can be found in Appendix C.

5.4 PART KNOWLEDGE TRANSFER ANALYSIS

The core of our method is to learn local-context part knowledge from training categories that is able to transfer to novel unseen categories. Such learned part knowledge may also include non-transferable category-specific information, such as the part geometry and the part boundary types. Training our framework on more various object categories is beneficial to learn more generalizable knowledge that shares in common. However, due to the difficulties in acquiring human annotated fine-grained parts (*e.g.* PartNet (Mo et al., 2019)), we can often conduct training on a few training categories. Thus, we are interested to know how to select categories to achieve the best performance in all categories.

Different object categories have different part patterns that block part knowledge transfers across category boundaries. However, presumably, similar categories, such as tables and

	Train Category		
	🪑	🪑	🛋
🪑	37.1	23.7	8.3
🛋	32.6	33.5	8.8
🛋	30.9	18.8	33.4

Table 2: Cross-validation experiments for analyzing how part knowledge transfers across category boundaries.

chairs, often share common part patterns that are easier to transfer. For example, tables and chairs are both composed of legs, surfaces, bar stretchers and wheels, which offers a good opportunity for transferring local-context part knowledge. We analyze the capability of transferring part knowledge across category boundaries under our framework. Table 2 presents experimental results of doing cross-validation using chairs, tables and lamps by training on one category and testing on another. We observe that, chairs and tables transfer part knowledge to each other as expected, while the network trained on lamps demonstrates much worse performance on generalizing to chairs and tables.

6 CONCLUSION

In this paper, we introduced an data-driven iterative perceptual grouping pipeline for the task of zero-shot 3D shape part discovery. At the core of our method is to learn part-level features within part local contexts, in order to generalize the part discovery process to unseen novel categories. We conducted extensive evaluation and analysis of our method and presented thorough quantitative comparisons to four state-of-the-art shape segmentation algorithms. We demonstrated that our method successfully extracts locally-aware part knowledge from training categories and transfers the knowledge to unseen novel categories. Our method achieved the best performance over all four baseline methods on the PartNet dataset.

REFERENCES

Bogdan Alexe, Thomas Deselaers, and Vittorio Ferrari. Measuring the objectness of image windows. *IEEE transactions on pattern analysis and machine intelligence*, 34(11):2189–2202, 2012.

Marco Attene, Bianca Falcidieno, and Michela Spagnuolo. Hierarchical mesh segmentation based on fitting primitives. *The Visual Computer*, 22(3):181–193, 2006a.

Marco Attene, Sagi Katz, Michela Mortara, Giuseppe Patané, Michela Spagnuolo, and Ayellet Tal. Mesh segmentation-a comparative study. In *IEEE International Conference on Shape Modeling and Applications 2006 (SMI'06)*, pp. 7–7. IEEE, 2006b.

Min Bai and Raquel Urtasun. Deep watershed transform for instance segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5221–5229, 2017.

Fausto Bernardini, Joshua Mittleman, Holly Rushmeier, Cláudio Silva, and Gabriel Taubin. The ball-pivoting algorithm for surface reconstruction. *IEEE transactions on visualization and computer graphics*, 5(4):349–359, 1999.

Xiaobai Chen, Aleksey Golovinskiy, and Thomas Funkhouser. A benchmark for 3D mesh segmentation. *ACM Transactions on Graphics (Proc. SIGGRAPH)*, 28(3), August 2009.

Alireza Fathi, Zbigniew Wojna, Vivek Rathod, Peng Wang, Hyun Oh Song, Sergio Guadarrama, and Kevin P Murphy. Semantic instance segmentation via deep metric learning. *arXiv preprint arXiv:1703.10277*, 2017.

Aleksey Golovinskiy and Thomas Funkhouser. Randomized cuts for 3d mesh analysis. In *ACM transactions on graphics (TOG)*, volume 27, pp. 145. ACM, 2008.

Aleksey Golovinskiy and Thomas Funkhouser. Consistent segmentation of 3d models. *Computers & Graphics*, 33(3):262–269, 2009.

Benjamin Graham, Martin Engelcke, and Laurens van der Maaten. 3d semantic segmentation with submanifold sparse convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9224–9232, 2018.

Kan Guo, Dongqing Zou, and Xiaowu Chen. 3d mesh labeling via deep convolutional neural networks. *ACM Transactions on Graphics (TOG)*, 35(1):3, 2015.

Donald D Hoffman and Whitman A Richards. Parts of recognition. *Cognition*, 18(1-3):65–96, 1984.

Jan Hosang, Rodrigo Benenson, Piotr Dollár, and Bernt Schiele. What makes for effective detection proposals? *IEEE transactions on pattern analysis and machine intelligence*, 38(4):814–830, 2015.

Ruizhen Hu, Lubin Fan, and Ligang Liu. Co-segmentation of 3d shapes via subspace clustering. In *Computer graphics forum*, volume 31, pp. 1703–1713. Wiley Online Library, 2012.

Qixing Huang, Vladlen Koltun, and Leonidas Guibas. Joint shape segmentation with linear programming. In *ACM transactions on graphics (TOG)*, volume 30, pp. 125. ACM, 2011.

Oliver Van Kaick, Noa Fish, Yanir Kleiman, Shmuel Asafi, and Daniel Cohen-Or. Shape segmentation by approximate convexity analysis. *ACM Transactions on Graphics (TOG)*, 34(1):4, 2014.

Evangelos Kalogerakis, Aaron Hertzmann, and Karan Singh. Learning 3d mesh segmentation and labeling. In *ACM Transactions on Graphics (TOG)*, volume 29, pp. 102. ACM, 2010.

Evangelos Kalogerakis, Melinos Averkiou, Subhransu Maji, and Siddhartha Chaudhuri. 3d shape segmentation with projective convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3779–3788, 2017.

Sagi Katz, George Leifman, and Ayellet Tal. Mesh segmentation using feature point and core extraction. *The Visual Computer*, 21(8-10):649–658, 2005.

Roman Klokov and Victor Lempitsky. Escape from cells: Deep kd-networks for the recognition of 3d point cloud models. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 863–872, 2017.

Shu Kong and Charless C Fowlkes. Recurrent pixel embedding for instance grouping. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9018–9028, 2018.

Yu-Kun Lai, Shi-Min Hu, Ralph R Martin, and Paul L Rosin. Fast mesh segmentation using random walks. In *Proceedings of the 2008 ACM symposium on Solid and physical modeling*, pp. 183–191. ACM, 2008.

John Langford and Tong Zhang. The epoch-greedy algorithm for contextual multi-armed bandits. In *Proceedings of the 20th International Conference on Neural Information Processing Systems*, pp. 817–824. Citeseer, 2007.

Rong Liu and Hao Zhang. Segmentation of 3d meshes through spectral clustering. In *12th Pacific Conference on Computer Graphics and Applications, 2004. PG 2004. Proceedings.*, pp. 298–305. IEEE, 2004.

Shu Liu, Jiaya Jia, Sanja Fidler, and Raquel Urtasun. Sgn: Sequential grouping networks for instance segmentation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3496–3504, 2017.

Jiajun Lv, Xinlei Chen, Jin Huang, and Hujun Bao. Semi-supervised mesh segmentation and labeling. In *Computer Graphics Forum*, volume 31, pp. 2241–2248. Wiley Online Library, 2012.

Ameesh Makadia and Mehmet Ersin Yumer. Learning 3d part detection from sparsely labeled data. In *2014 2nd International Conference on 3D Vision*, volume 1, pp. 311–318. IEEE, 2014.

Alan P Mangan and Ross T Whitaker. Partitioning 3d surface meshes using watershed segmentation. *IEEE Transactions on Visualization and Computer Graphics*, 5(4):308–321, 1999.

Daniel Maturana and Sebastian Scherer. 3d convolutional neural networks for landing zone detection from lidar. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3471–3478. IEEE, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Kaichun Mo, Shilin Zhu, Angel X Chang, Li Yi, Subarna Tripathi, Leonidas J Guibas, and Hao Su. Partnet: A large-scale benchmark for fine-grained and hierarchical part-level 3d object understanding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 909–918, 2019.

Alejandro Newell, Zhiao Huang, and Jia Deng. Associative embedding: End-to-end learning for joint detection and grouping. In *Advances in Neural Information Processing Systems*, pp. 2277–2287, 2017.

Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 652–660, 2017a.

Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. In *Advances in Neural Information Processing Systems 30*. 2017b.

Xiaofeng Ren and Jitendra Malik. Learning a classification model for segmentation. In *null*, pp. 10. IEEE, 2003.

Gernot Riegler, Ali Osman Ulusoy, and Andreas Geiger. Octnet: Learning deep 3d representations at high resolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3577–3586, 2017.

Ariel Shamir. A survey on mesh segmentation techniques. In *Computer graphics forum*, volume 27, pp. 1539–1556. Wiley Online Library, 2008.

Shymon Shlafman, Ayellet Tal, and Sagi Katz. Metamorphosis of polyhedral surfaces using decomposition. In *Computer graphics forum*, volume 21, pp. 219–228. Wiley Online Library, 2002.

Zhenyu Shu, Chengwu Qi, Shiqing Xin, Chao Hu, Li Wang, Yu Zhang, and Ligang Liu. Unsupervised 3d shape segmentation and co-segmentation via deep learning. *Computer Aided Geometric Design*, 43:39–52, 2016.

Oana Sidi, Oliver van Kaick, Yanir Kleiman, Hao Zhang, and Daniel Cohen-Or. *Unsupervised co-segmentation of a set of shapes via descriptor-space spectral clustering*, volume 30. ACM, 2011.

Minhyuk Sung, Hao Su, Ronald Yu, and Leonidas J Guibas. Deep functional dictionaries: Learning consistent semantic structures on 3d models from functions. In *Advances in Neural Information Processing Systems*, pp. 485–495, 2018.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pp. 1057–1063, 2000.

Oliver Van Kaick, Kai Xu, Hao Zhang, Yanzhen Wang, Shuyang Sun, Ariel Shamir, and Daniel Cohen-Or. Co-hierarchical analysis of shape structures. *ACM Transactions on Graphics (TOG)*, 32(4):69, 2013.

Peng-Shuai Wang, Yang Liu, Yu-Xiao Guo, Chun-Yu Sun, and Xin Tong. O-cnn: Octree-based convolutional neural networks for 3d shape analysis. *ACM Transactions on Graphics (TOG)*, 36 (4):72, 2017.

Pengyu Wang, Yuan Gan, Panpan Shui, Fenggen Yu, Yan Zhang, Songle Chen, and Zhengxing Sun. 3d shape segmentation via shape fully convolutional networks. *Computers & Graphics*, 70: 128–139, 2018a.

Weiyue Wang, Ronald Yu, Qiangui Huang, and Ulrich Neumann. Sgpn: Similarity group proposal network for 3d point cloud instance segmentation. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018b.

Yunhai Wang, Shmulik Asafi, Oliver Van Kaick, Hao Zhang, Daniel Cohen-Or, and Baoquan Chen. Active co-analysis of a set of shapes. *ACM Transactions on Graphics (TOG)*, 31(6):165, 2012.

Max Wertheimer. Laws of organization in perceptual forms. 1938.

Kai Xu, Vladimir G Kim, Qixing Huang, Niloy Mitra, and Evangelos Kalogerakis. Data-driven shape analysis and processing. In *SIGGRAPH ASIA 2016 Courses*, pp. 4. ACM, 2016.

Li Yi, Vladimir G Kim, Duygu Ceylan, I Shen, Mengyan Yan, Hao Su, Cewu Lu, Qixing Huang, Alla Sheffer, Leonidas Guibas, et al. A scalable active framework for region annotation in 3d shape collections. *ACM Transactions on Graphics (TOG)*, 35(6):210, 2016.

Li Yi, Hao Su, Xingwen Guo, and Leonidas J Guibas. Syncspeccnn: Synchronized spectral cnn for 3d shape segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2282–2290, 2017.

Li Yi, Wang Zhao, He Wang, Minhyuk Sung, and Leonidas J Guibas. Gspn: Generative shape proposal network for 3d instance segmentation in point cloud. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3947–3956, 2019.

A   Sub-Part Proposal Module

Given a shape represented as a point cloud, we first propose a pool of small superpixel-like (Ren & Malik, 2003) sub-parts as the building blocks. We employ furthest point sampling to sample 128 seed points on each input shape. To capture the local part context, we extract PointNet (Qi et al., 2017a) features with 64 points sampling within a local 0.04-radius[2] neighborhood around each seed point. In the training phase, all the 64 points will be sampled from the same instance. Then, we train a local PointNet segmentation network that takes as inputs 512 points within a 0.2-radius ball around every seed point and output a binary segmentation mask indicating a sub-part proposal. If the point belongs to the instance is the same as the small ball, it will be classified into 1. We call this module as the sub-part proposal module and illustrate it in Figure 4.

In the inference phase, we can not guarantee the 64 points sampled within a 0.04-radius ball are all coming from the same part. However, in our experiments, we observe those sub-part proposals will have a low purity score due to the poor center feature extracted from the 64 points across different parts. Also, even the center feature extraction is good, some sub-parts may also cover multiple parts in ground-truth. So in our experiments, we remove the sub-parts whose purity score lower than 0.8, and the remain sub-parts form our initial sub-part pool.

Figure 4: Learning-based sub-part proposal module.

The input of this learning module is constrained in a local region, thus will not be affected by the global context. To validate the transferring performance of this module, we train the module on Chair, Storage Furniture, and Lamp with Level-3 annotations and test on all categories with evaluating by the most fine-grained level annotations of each category. The results are listed in Table 3. Since the part patterns in Table are very similar to the patterns in Chair, we can see the zero-shot performance on Table is close to the performance on training categories. This phenomenon also aligns the analysis in Section 5.4.

	Seen Category			Unseen Category								
PosAcc	94.1	95.8	91.7	88.7	86.7	97.1	97.1	88.2	87.7	90.6	84.3	88.3
NegAcc	66.5	61.3	73.8	59.9	64.9	12.9	20.2	20.3	42	66	60.6	31.9
	Unseen Category											
PosAcc	96.4	98.1	98.6	98.1	97	86.2	96.3	86.3	91.7	95.9	93.6	89.1
NegAcc	39.4	40.7	3.8	33.7	77.6	42.8	45.5	46.9	62.3	67.7	31.1	36.2

Table 3: Quantitative evaluation of the proposal module. PosAcc and NegAcc refer to positive accuracy and negative accuracy of the binary segmentation.

B   Ablation Studies

B.1   Context Effects

In this section, we conduct experiments about the effects of involving more context for training models on seen categories and unseen categories. We add a branch to the verification network and

---

[2]All shape point clouds are normalized into a unit-radius sphere.

extend it into Figure 5. This branch takes all the sub-parts where the minimum distance with the input sub-part pair $\ell_2 \leq 0.01$ as input and thus encodes more context information for decision making. Note that the involved context is still restricted in a very local region and the module can not "see" the whole shape. Now, there are two branches can be used to determine whether we should group the pair. The original binary branch is driven by purely local contextual information. The newly added one encodes more context information.

Figure 5: The extended verification network with two prediction branches. The above branch exploits pure local context. The below branch encode more context to make decisions.

To test the effectiveness of involving more context, we train the model with the extended verification network on Chair, Storage Furniture, and Lamp and test them in two ways. 1) We make decisions by only using the original binary branch. 2) We make decisions by using the original binary branch when the size of the sub-part pool is ≥ 32 and using the newly added branch when the size of the sub-part pool is ≤ 32. We choose 32 as an empirical threshold here based on our observation that when the size of the pool is ≤ 32, the sub-parts in the pool will be relative large and the additional local context will help make grouping decisions in most scenarios.

From the results listed in Table 4, we can point out that the involved context helps to consistently improve the performance on seen categories, but has negative effects on unseen categories in most scenarios. When the context is similar between the seen categories and unseen categories, such as patterns between Storage Furniture and Bed, the involved context can help make decisions. The phenomenon indicates a future direction that we train the model with involving more context but use them on unseen categories only when we found a similar context we have seen during training. It also raises the possibilities that, for the proposed method, we can achieve higher performance on seen categories without degrading the performance on unseen categories by involving such context only when testing on seen categories, and discarding it for unseen categories. We adopt this way for obtaining final scores in Appendix C.2.

Context		Seen Category			Unseen Category						
w/	L1	63.5	69	25.1	38.1	14.4	57.5	71.3	57.4	33.9	70
	L2	47.6	57.9	21.1	-	12.3	-	-	-	27.9	-
	L3	41.5	44.5	19.8	-	10.9	34.6	-	27.9	19	60.7
	Avg.	**50.9**	**57.1**	**22**	38.1	**12.3**	46.1	71.3	42.7	26.9	65.4
w/o	L1	59.8	67	24.4	41.5	13.9	61.9	75.7	59.3	40.3	71.2
	L2	44.6	55.2	19.2	-	10.7	-	-	-	30.4	-
	L3	39.1	42.9	18.1	-	9.4	36.6	-	28.3	22.3	62.2
	Avg.	47.8	55	20.6	**41.5**	11.3	**49.3**	**75.7**	**43.8**	**31**	**66.7**

Table 4: Quantitative evaluation of involving more context. w/ and w/o denote making decision with and without involving more context, respectively. Note that we only introduce more context in the late grouping process and the involved context is still restricted in a very local region. The number is the mean recall of segmentation results. The L1, L2 and L3 refer to the three levels of segmentation defined in PartNet. Avg. is the average among mean recall of three levels segmentation results in PartNet.

B.2 COMPONENTS ANALYSIS

In our pipeline, we use the policy network to learn to pick pairs of sub-parts and adopt on-policy training for boosting the performance. For the policy network, it consists of the purity module and the rectification module, which process the unary information and binary information respectively. Here, we show the quantitative results and validate the effectiveness of these components. The results are listed in Table 5, where we train the model on the Chair of level-3 annotations.

- **Purity Module:** The purity module takes the unary information (a grouped pair) as input and output the purity score. Similar to the objectness score Alexe et al. (2012) used in object detection, the purity score serves as the partness score to measure the quality of the proposal. We optimize the purity module by regressing the ground-truth purity scores and use such meaningful supervision to help learn the policy. The results of "no purity" row in Table 5 show the effectiveness of this module.
- **Rectification Module:** The rectification module is involved to rectify the failure cases for the purity network. Our experiments shows that without the rectification module, our decision process will easily converge to a trajectory that a pair of sub-part with unbalanced size will usually be chosen to group results in situations that one huge sub-part dominate the sub-part pool and bring in performance drop as shown in Table 5, the "no rectification" row. Please also refer to Appendix B.3 to see some relating qualitative results.
- **On-Policy Training:** The on-policy training will sample training data that matches the inference process without the requirement of carefully designing the sampling strategy. Without it, our networks suffer from a decrease in performance as shown in Table 5, the "off-policy" row.

models	Test Category										
no purity	36.6	30.4	5.1	37.6	7.8	31.2	63	22.5	9.9	53.7	22.9
no rectification	36.3	30.2	4.5	37.2	8	30.2	57.6	22.8	9.7	55.2	21.4
off-policy	35.8	29.5	4.7	35.2	8.5	28.7	53.3	20.6	8.8	52	23.1
full-model	37.1	30.9	5.3	40.9	9	32.7	66.5	23.5	10.6	56.4	23.8

Table 5: Quantitative results of ablation studies. We train the models on the Chair of level-3 annotations and test on the listed categories. The number is the mean recall of the most fine-grained annotations of each category.

B.3 RELATIVE SIZE VISUALIZATIONS

We involve the rectification module and learn the policy to pick pairs of sub-parts for grouping. The rectification module may bring several benefits. Here we demonstrate the effectiveness of the rectification module from one aspect that this module will encourage to pick equal size pairs of sub-parts. In our experiments, we found if we only follow the guidance of the purity network, our policy will tend to choose the pair comprising one big sub-part and one small sub-part. Like the descriptions in Section 4.1, the geometry of such unequal size pairs will be dominated by the big sub-part and thus raise the possibilities of errors. The rectification module can alleviate this situation and encourage the learned policy to choose more equal size pairs.

To evaluate this point, we define the relative size for the selected pairs. Given a pair of sub-parts P_i and P_j, we define the relative size as $\frac{P_i}{P_j} + \frac{P_j}{P_i}$ where the smaller value means the size of the pair P_i and P_j are more equal, and the minimum value is 2. We train two models with and without the rectification module separately on Chair of level-3 annotations and test on Chair. We plot the relative size for the process of grouping and show some randomly sampled results in Figure 6. Every picture shows the grouping process for one shape, the x-axis is the iteration number of the process, the y-axis is the defined metric. As the process going, the sub-part will become larger. From the results, we can clearly see the rectification module helps to choose more equal size pairs. Only when it comes to the late stage, where the size of parts is various and it is hard to find size equal pairs, our policy will pick size unequal pairs. Therefore, the rectification module helps to prevent the trajectory converging to catastrophic cases in which larger sub-parts dominate the feature for purity score prediction and fail to predict the purity for the grouped sub-parts. Also, intuitively,

the intermediate sub-parts generated during the grouping process may have various patterns and are irregular. This increases the burden of models to recognize, and the learned "equal-size selection" like rule may help to form regular intermediate sub-parts and alleviate this issue.

w/o the rectification module   w/ the rectification module

Figure 6: Qualitative results. Figures show the changes of the relative size of a pair of sub-parts during the grouping process. The X-axis is the iteration number and Y-axis is the relative size defined in Appendix B.3. Each row represents the grouping process for the same shape. The left column is the results without the rectification module.

C FULL EXPERIMENTS

C.1 IMPLEMENTATION DETAILS

We will train our model on three categories (Chair, Storage Furniture, and Lamp) and test on all categories. For each method, we train three models corresponding to three levels of segmentation annotations for training categories. All the point clouds of shapes used in our experiments have 10000 points. For the compared baselines, the input size is 10000 points. For our proposed method, the input size of a sub-part is 1024. Since our task does not need semantic labels, so we remove the semantic segmentation loss for all the deep learning methods.

- **PartNet-InsSeg:** We follow the default settings and hyper-parameters described in the paper where the maximum instance number is 200, and loss weights are 1 except 0.1 for the regularization term. We train the model for a total of 120 epochs with the learning rate starting from 0.001 and decaying 0.5 every 15 epochs. The whole training process will take 4 days on a single 1080Ti GPU.
- **SGPN:** Following the same experiment setting in Mo et al. (2019), where the max group number is set to 200. The learning rate is 0.0001 initially and decays by a factor of 0.8 every 40000 iterations. The model is trained on 1 1080Ti GPU for 51 epochs. It takes 3 days to train the network and 1 day to test on the full PartNet test set.
- **GSPN:** The maximum number of detection per shape is 200. The number of points of each generated instance is set to 512. NMS of threshold 0.8 is applied after proposal generation. As in Yi et al. (2019), we train GSPN first for 20 epochs and then fine-tune it jointly with R-PointNet for another 20 epochs. The learning rate is initialized to 0.001 and decays by a factor of 0.7 every 10000 steps. Each stage of training takes 2 days respectively.
- **WCSeg:** This method requires out-ward normal as input which is lacked in the point clouds. In order to perform this method and compare it as fair as possible, we first generate out-ward normals for input point clouds as follows: a) we employ ball-pivoting Bernardini et al. (1999) to reconstruct surface for input point clouds. b) we keep one face fixed and re-orient the faces order coherently so that the generated face normal is all out-ward. c) we transfer the face normals back to the vertices' normals.
  With the point cloud and the calculated normals as input, we then follow the parameters the same as the original paper Kaick et al. (2014). As a traditional method, the performance is very sensitive to all pre-defined parameters, we only manually tune one parameter to keep the performance and let the generated part number better matches three different levels of ground truth. More specifically, we randomly select half of the test set from three seen categories (i.e. Chair, Lamp, Storage Furniture) as data set for our grid search. Then we conduct a grid search regarding the parameter σ in WCSeg. We choose the range of $[0.02, 0.22]$ and the step size of 0.01 as the searched grid for σ. Though it is hard to continuously control the output part number by tuning the parameters in the WCSeg algorithm, we eventually select $\sigma = 0.22$ for Level-1 $\sigma = 0.17$ for Level-2, and $\sigma = 0.12$ for Level-3 and use such parameters for all the experiments shown in our paper. This method does not require training. For the inference, WCSeg takes about 3 minutes to process each shape and about 4 days to finish testing over PartNet's part instance segmentation dataset on our Intel Xeon E5-2660 v2 CPU cluster with more than 40 CPU cores used.
- **Our:** For each shape, we first use the sub-part proposal module to generate sub-part proposals as described in Appendix A. For training the proposal module, we use batch size 12 and learning rate starting from 0.001 and decaying 0.5 every 15 epochs for 120 epochs. After this, we will gain 128 proposals and then remove the proposals whose purity score is lower than 0.8. The rest proposals form our initial sub-parts pool. In the training phase, we can calculate the ground-truth purity score according to the annotations. In the inference phase, we will use the trained purity module to predict the purity score. To short the whole training time, we train the proposal module on level-3 data and use it for training the policy network and verification network on all three levels.
  After gaining the initial sub-part pool, we begin our grouping process. During the process, we will use the policy network comprising the purity module and the rectification module to pick the pair of sub-parts and use the verification network to determine whether we should group the pair. If a pair of sub-parts should be grouped, we will add the new grouped part into the sub-parts pool and remove the input two sub-parts from the pool. We will

iteratively group the sub-parts until no more available pairs. So for each shape, we generate a trajectory and collect training data from the trajectory.

In the training phase, for each iteration, we sample 64 pairs and calculate the policy score by using both the purity module and the rectification module. To accelerate the training process, we sample 10 pairs not 1 pair from the 64 pairs and send them to the verification network to determine whether we should group the pair of sub-parts. The 10 pairs comprise rank n pairs and $10 - n$ random sampling pairs since we adapt epsilon-greedy strategy where start from involving 8 random sampling samples and decay the number with 1 in each epoch. The minimal number of random sampling pairs is 1. In the inference phase, for each iteration, we will calculate the policy score for all pairs and send the pair with the highest score to the verification network. Note that we use the prediction of the verification network not the ground-truth annotations to determine whether we should group and generate the trajectory. According to ablation studies in Appendix B.2, this on-policy manual is important for the final performance. For the level-3 model, we choose the pairs where two sub-parts are close to each other within the minimum distance $\ell_2 \le 0.01$. For the level-1 and level-2 model, we will first choose the neighboring pairs and group them. When all neighboring pairs have been processed, we remove the neighboring constraints and group the pairs until no more available pairs.

We collect the training data from the trajectories and form the replay buffer for each module, where each replay buffer only can hold up to data from 4 trajectories. The size of the input point cloud to all three modules is 1024 by sampling from the sub-parts. In each iteration, we train all the modules on corresponding replay buffers. We train the modules for a total of 1200 iterations with the learning rate starting from 0.001 and decaying 0.5 every 150 epochs. The batch size for the purity module, the verification network is 128, for the rectification module is 2. The whole training process will take 4 days on a single 1080Ti GPU. For the inference, the method takes about 3 seconds to process each shape.

C.2 FULL EXPERIMENTAL RESULTS

We present the full table including Mean Recall scores at all levels and the performance on seen categories in Table 6. We involve more context only on seen categories the same as the way presented in Appendix B.1.

C.3 MORE QUALITATIVE RESULTS

We provide qualitative results of GSPN, SGPN, WCSeg, PartNet-InsSeg, and our proposed methods for the zero-shot part discovery. We train the models on Chair, Lamp, and Storage Furniture of level-3 (the most fine-grained level) of PartNet Dataset and test on the other unseen categories. We also list the corresponding most fine-grained ground-truth annotations for reference (Some categories may only have the level-1 annotation). Note that the ground-truth annotation only provides one possible segmentation that satisfies category-specific human-defined semantic meanings.

	Seen Category				Unseen Category								
	(icon)	(icon)	(icon)	SAvg.	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)
P1	74.4	64.3	27.6	62.3	18.2	14.7	49.6	73.5	33.4	37.3	43.2	42.4	24.2
P2	50.8	48	22.2	44.1	-	7.8	-	-	-	32.2	-	-	-
P3	42	39.3	21.6	37	-	6.6	31.8	-	27.1	21.6	44	21.8	8.7
Avg.	**55.7**	50.5	**23.8**	**47.8**	18.2	9.7	40.7	73.5	30.3	30.4	43.6	32.1	16.5
S1	57.1	56.2	13.6	47.5	21.4	10.7	57.6	53.3	37.5	13	38.4	44.1	43.1
S2	38.2	42.1	11.4	33.2	-	6.3	-	-	-	7.9	-	23.7	-
S3	31.3	34.4	9.4	27.2	-	4	35.8	-	17.9	5.2	31.2	19	7.9
Avg	42.2	44.2	11.5	36	21.4	7	46.7	53.3	27.7	8.7	34.8	28.9	25.5
G1	56.7	57.8	17.7	48.5	34.4	17.2	56	72.8	55.6	53.5	63.7	55.6	46.9
G2	35.2	42	13.5	31.9	-	4.6	-	-	-	40.5	-	30.2	-
G3	27.1	31.2	12.1	24.7	-	3.4	37.8	-	28.9	27.8	51.9	26.5	9.9
Avg.	39.7	43.7	14.4	35	34.4	8.4	46.9	72.8	42.3	**40.6**	57.8	37.4	28.4
W1	29	55.8	5.4	29.3	43.1	13.6	70.1	69.8	48.7	42.3	64.1	44.9	50.2
W2	30.7	53.2	1.5	28.9	-	6.9	-	-	-	23.4	-	27.5	-
W3	29.2	50	1.8	27.5	-	5.7	48.1	-	28.7	16.9	58	24.6	25.8
Avg.	29.6	53	2.9	28.5	**43.1**	8.7	**59.1**	69.8	38.7	27.5	61.1	32.3	**38**
O1	63.5	69	25.1	56.3	41.5	13.9	61.9	75.7	59.3	40.3	71.2	56.9	57.3
O2	47.6	57.9	21.1	43.9	-	10.7	-	-	-	30.4	-	31.5	-
O3	41.5	44.5	19.8	37.4	-	9.4	36.6	-	28.3	22.3	62.2	26.1	11.5
Avg.	50.9	**57.1**	22	45.9	41.5	**11.3**	49.3	**75.7**	**43.8**	31	**66.7**	**38.2**	34.4

	Unseen Category												
	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	(icon)	UAvg.
P1	19.4	52.5	0.4	43.2	82.1	42	33	31.6	0.8	56	23.6	38	47.9
P2	-	-	-	-	-	28.5	-	25.4	-	32.4	-	-	31.7
P3	13.8	-	-	23.9	-	18.3	-	18	-	28.4	3.6	35.5	27.6
Avg.	16.6	52.5	0.4	33.6	82.1	29.6	33	25	0.8	38.9	13.6	36.8	35.7
S1	23.3	37	0.4	39.3	67.3	11.1	13.3	7.5	6.4	48.2	12.7	28.6	41
S2	-	-	-	-	-	7.1	-	5.4	-	29.4	-	-	27.3
S3	16.6	-	-	22.7	-	3.4	-	4.9	-	26.7	2.8	26.3	24.1
Avg.	20	37	0.4	31	67.3	7.2	13.3	5.9	6.4	34.8	7.8	27.5	30.8
G1	32.5	31.7	0.4	25.6	92.9	62.3	40.6	41.4	3.7	49.9	23.2	42.4	48.6
G2	-	-	-	-	-	34.6	-	24.4	-	28.8	-	-	28.7
G3	18	-	-	12.2	-	20.7	-	13.4	-	25	2.2	40.3	26.7
Avg.	25.3	31.7	0.4	18.9	92.9	**39.2**	40.6	26.4	3.7	34.6	12.7	41.35	34.7
W1	46.3	53.4	0.3	67.7	62.1	51.3	52.6	38.4	46.3	38.2	23.3	34.2	42.9
W2	-	-	-	-	-	22.3	-	13.2	-	27.7	-	-	26.8
W3	49.2	-	-	57.1	-	16.5	-	8.1	-	24.6	3	31.7	29.2
Avg.	**47.8**	**53.4**	0.3	**62.4**	62.1	30	52.6	19.9	**46.3**	30.2	13.2	33	33
O1	39.1	40	0.4	54.7	96.9	56.4	53.3	43	16.7	63.5	25.3	45.2	58.4
O2	-	-	-	-	-	32	-	22.9	-	37.8	-	-	36.5
O3	25.5	-	-	38.5	-	19.2	-	16.8	-	33.6	5	41.6	33.8
Avg.	32.3	40	0.4	46.6	**96.9**	35.9	**53.3**	**27.6**	16.7	**45**	**15.2**	**43.4**	**42.9**

Table 6: Quantitative Evaluation. Algorithm P, S, G, W, O refer to PartNet-InsSeg, SGPN, GSPN, WCSeg and Ours, respectively. The number 1, 2 and 3 refer to the three levels of segmentation defined in PartNet. We put short lines for the levels that are not defined. Avg. is the average among mean recall of three levels segmentation results in PartNet. SAvg. is average among seen categories over shape numbers, while UAvg. is average among unseen categories over shape numbers.