Progressive Feature Interaction Search for Deep Sparse Network

Abstract

Deep sparse networks (DSNs), of which the crux is exploring the high-order feature interactions, have become the state-of-the-art on the prediction task with high-sparsity features. However, these models suffer from low computation efficiency, including large model size and slow model inference, which largely limits these models' application value. In this work, we approach this problem with neural architecture search by automatically searching the critical component in DSNs, the feature-interaction layer. We propose a distilled search space to cover the desired architectures with fewer parameters. We then develop a progressive search algorithm for efficient search on the space and well capture the order-priority property in sparse prediction tasks. Experiments on three real-world benchmark datasets show promising results of PROFIT in both accuracy and efficiency. Further studies validate the feasibility of our designed search space and search algorithm.

1 Introduction

The deep sparse network (DSN) [9, 5] is a special type of deep networks, which targets learning from sparse and categorical features. Such a learning problem frequently appears in many industrial applications. Take the click-through rate (CTR) prediction as an example, features like user id, user age, item id, and item category, are usually sparse and high-multidimensional [5]. In advertisement recommendation [28], there are sparse features such as category, brand, etc. In fraud detection [24], there are sparse features such as income level, region, etc.

A general DSN framework (see Figure 1) consists of three layers. First, the embedding layer transforms the raw sparse features into dense embeddings. Then the feature-interaction layer can construct cross-features of raw features' embeddings via feature-interaction operation. The cross-features are further fed into the output layer to calculate the prediction score. To achieve high prediction accuracy, researchers found that the crux of the deep sparse networks is to design complex feature-interaction layers [9, 32, 6, 18, 26]. For example, in Figure 1, the second-order cross-feature, `AB`, is constructed by two raw features, `A` and `B`, via feature interaction. DeepFM [9] feed the two-order cross-features into multi-layer perceptions for implicitly generating high-order cross-features. Further advances replace the MLP in DeepFM with more complex neural networks, including deep cross network in xDeepFM [18], outer product network in PNN [26], self-attention network in AutoInt [32], and logarithmic transformation network in AFN [6]. Since these deep neural networks work as a black box, high-order cross-features are learned in an implicit manner.

Neural architecture search (NAS) [8, 41, 42, 23], has become a powerful approach in replacing human experts in proposing both effective and lightweight models for various areas such as computer vision [35], natural language processing [30], etc. More recently, there are some works that adopt neural architecture search for designing the feature-interaction layer in DSN, AutoFIS [20] and AutoGroup [19], by explicitly searching for powerful cross-features. Although the searched feature-

Figure 1: Illustration of deep sparse networks and feature-interaction layer.

interaction layer is more lightweight to some extent, these methods are suffering from high search costs, resulting in limited prediction performance and application value. However, these works require extremely large search costs, limiting their application values on large datasets.

In general, the human-designed DSNs are faced with the efficiency issue since they only pursue prediction accuracy. In fact, efficiency has a very high impact on the application value of machine learning models in real-world scenarios [3, 34, 29]. Considering that today's machine learning systems are always deployed at diverse hardware platforms, inference time and model size are the two most significant factors. Specifically, the inference time can largely affect the time delay of the user services, which largely affects the application value. The model size can determine whether the model can be deployed at specific devices, which sets the constraint to the model's application scenarios, especially for edge devices. Therefore, these complicated deep sparse networks are still limited due to their inferior efficiency.

In this work, to address the above-mentioned efficiency-accuracy dilemma of state-of-the-art deep sparse networks, we propose to utilize neural architecture search to design both lightweight and effective models. This problem of NAS-based DSN design suffers from two challenges. First, the search space is at the exponential level, and searching in this space is an NP-hard problem. Second, in sparse prediction tasks, there exists the order-priority property, which is hard to handle. To tackle them, we propose a PROFIT method (short for **PRO**gressive **F**eature **InT**eraction Search). We first design a distilled search space, a low-rank approximation of the full search space, which can vastly reduce the difficulty of finding desired models. More precisely, the full search space, which uses a tensor to represent all possible architectures, is approximated by the composition of low-rank tensors. We then develop a progressive search algorithm that searches cross-features from lower orders to higher orders sequentially. When searching for the higher orders, the corresponding architecture parameters of lower orders are fixed, helping distinguish the various importance of different orders, *i.e.* order-priority property. We conduct experiments on three real-world benchmark datasets and compare both accuracy and efficiency with state-of-the-art models. Empirical results demonstrate that the model searched by our PROFIT can achieve high accuracy while keeping low computation cost and model size. Further studies verify the feasibility of each design, consisting of the search space and search algorithm.

We summarize the contributions of this work as follows.

- We propose a neural architecture search method to design data-specific deep sparse networks.
- The proposed search space and search algorithm well address the limitations of existing works.
- Our method can achieve good prediction performance by automatically exploring high-order feature interaction while keeping a small model size and fast inference.

2 Related Work

2.1 Neural Architecture Search (NAS)

Neural architecture search (NAS) [41, 1] replaces human experts in designing neural networks architectures. It has been demonstrated a promising approach in many research areas, e.g., vision [35, 21, 4] and natural language processing [30]. There are two significant perspectives that determines its utility: *search space* and *search algorithm*.

- The search space is defined as the set of all possible architectures. It is task-specific and should be general enough to cover existing models but not too general to incur high search costs.

- The search algorithm attempts to find the desired architecture in a given space. A good search algorithm should well explore domain properties to find good architectures and achieve high search efficiency.

Although the development of deep neural networks achieves great success in plenty of machine learning tasks, it becomes a big issue to handle the rapid growth of model size. Precisely, it is challenging to deploy the machine learning models on diverse computation platforms, especially for edge devices such as users' mobile phones, of which the inference efficiency is largely constrained by the hardware. Recently, to address such a challenge, some pioneer works [10, 2] propose NAS methods for automatically designing lightweight models for computer vision tasks, which can reduce the inference time on edge devices.

2.2 Deep Sparse Networks (DSNs)

As mentioned in Section 1, deep sparse networks (DSNs) serve as the state-of-the-art solution for the sparse prediction task. Its crux is to extract cross-features, which can have strong abilities in prediction, from raw input features.

Here, for the sparse prediction task, we recap the evolution from earlier shallow models to DSNs. Factorization machine [28] is a pioneer work that assigned a linear matrix factorization operation to all possible second-order cross-features (built with two raw features), which was extended by NFM [12] and AFM [37]. To overcome the shortcomings of these shallow feature-interaction operations, deep sparse networks [9, 18, 6, 32, 26] are proposed. In general, deep sparse networks adopt neural feature-interaction layers to extracting cross-features, as illustrated in Figure 1. Wide&Deep [5] and DeepFM [9] feed the low-order features into multi-layer perceptrons (MLPs) to implicitly reveal any order cross-features. More complex neural networks are proposed to serve as the feature-interaction layer, replacing MLPs, such as the compressed interaction network (CIN) in xDeepFM [18], outer product network in PNN [26], and stacked self-attention networks in AutoInt [32]. Slightly different from the above-mentioned works that have deterministic highest order, AFN [6] used a logarithmic transformation layer to convert the order to a learnable parameter and then adopted a feature summation as the feature-interaction layer, which fuzzes the order of cross-features. However, there is no model that can achieve both promising efficiency and high accuracy. Thus, it is important to solve the efficiency-accuracy dilemma in DSNs.

With the power of NAS, we approach the problem by *explicitly* search cross-features for the feature-interaction layer. We approach the design of deep sparse networks as a NAS problem, to obtain architecture with both high accuracy and high efficiency. Recently, there are some works [20, 24, 19] adopting NAS to help explicitly search powerful cross-features as the feature-interaction layer. Although the searched feature-interaction layer is more lightweight, these methods suffer from high search costs.

3 The Proposed Method

Existing works of DSNs [18, 32, 6] have shown that the feature-interaction layer is an important component. It can be defined as a network module of which the input is embeddings of raw features, and the output is interactions of embeddings. The interactions have extracted features' co-relations and can then be fed to the output layer for obtaining the final prediction results. A feature-interaction layer that extracts o-th order cross-features can be formulated as

$$\mathbf{Layer}_o = \big\{\mathbf{f}_{c_1} \odot \mathbf{f}_{c_2} \cdots \odot \mathbf{f}_{c_o} | c_o \in \mathcal{C}_o\big\}, \text{ s.t. } |\mathcal{C}_o| \leq N_o, \tag{1}$$

of which $\mathbf{c}$ denotes a l-size vector of involved features' indexes of a o-th cross-feature ($c_o, c_2, ..., c_o$ are indexes of raw features), $\mathbf{f}$ denotes the embeddings of raw features (*i.e.*, the output of embedding layer), and $\mathcal{C}_o$ denotes the set of o-th order cross-features on which there is a sparsity constraint of N_o, ensuring both the quality of cross-features and the model efficiency. The feature interaction is perturbation invariant, i.e., $\mathbf{f}_1 \odot \mathbf{f}_2 = \mathbf{f}_2 \odot \mathbf{f}_1$. The element-wise product is the most used operation for feature interaction [18, 32, 6]. Let $\mathbf{F} = \{\mathbf{f}_1, \mathbf{f}_2, \cdots, \mathbf{f}_M\}$. Then, in short, the general objective of DSN can be formulated as follows,

$$\min_{\mathbf{F}} \mathcal{L}\big(\phi(\mathbf{F}, \{\mathcal{C}_o\}); \mathcal{D}\big), \tag{2}$$

where $\mathcal{L}$ denotes the loss function and ϕ is the prediction function, of which a linear predictor or MLP can be used.

The objective of the NAS problem should be finding good sets of feature-interaction cells, $\{\mathcal{C}_o\}$, with o from 1 to O, formulated as follows.

Definition 1 (AutoDSN) *The search problem can be formulated as:*

$$\{\mathcal{C}_o\}^* = \min_{\{\mathcal{C}_o\}} \mathcal{L}\big(\phi(\mathbf{F}^*, \{\mathcal{C}_o\}); \mathcal{D}_{val}\big), \ s.t. \ \begin{cases} \mathbf{F}^* = \arg\min_{\mathbf{F}} \mathcal{L}\big(\phi(\mathbf{F}, \{\mathcal{C}_o\}); \mathcal{D}_{tra}\big), \\ |\mathcal{C}_o| \le N_o, \quad \forall o = 1, 2, ..., O, \end{cases}$$

where $\mathcal{D}_{tra}$ and $\mathcal{D}_{val}$ denote the training and validation datasets, respectively.

For the AutoDSN problem, it is a challenging problem due to multiple aspects. First, the search space for $\mathcal{C}$ is relatively large, which burdens the search cost. Second, the desired sets are discrete, and there are also sparse constraints, leading it an NP-hard problem. Third, the desired cross-features are closely co-related with each other, from lower orders to higher orders, which should be carefully considered.

3.1 Revisiting Existing NAS Approach

For the search problem in Definition 1, an intuitive NAS-based solution is to use a parameterized vector to represent all cross-features' importance. Such solution was recently proposed by AutoFIS [20], assigning different weights to cross-features and using the continuous relaxation, similar as DARTS [23]. For o-order cross-feature, a o-th order tensor $\mathcal{A}$ can be introduced, where $\mathcal{A}_{c_1, c_2, \cdots, c_o}$ represents the weight of a cross-feature involved with raw features $\{\mathbf{f}_{c_1}, \mathbf{f}_{c_2}, \cdots, \mathbf{f}_{c_o}\}$. Then, a feature-interaction layer in (1) is expressed as

$$\sum_{c \in \mathcal{C}_{\text{full}}} \mathcal{A}_{c_1 c_2 \cdots c_o} (f_{c_1} \odot f_{c_2} \odot \cdots \odot f_{c_o}), \tag{3}$$

where $\mathcal{C}_{\text{full}}$ denotes the set of all possible cross-features. Then the NAS problem with a continuous space can be re-formulated as follows,

$$\mathcal{A}^* = \min_{\mathcal{A}} \mathcal{L}\big(\psi(\mathbf{F}^*, \mathcal{A}); \mathcal{D}_{\text{val}}\big), \ \text{s.t.} \ \mathbf{F}^* = \arg\min_{\mathbf{F}} \mathcal{L}\big(\psi(\mathbf{F}, \mathcal{A}); \mathcal{D}_{\text{tra}}\big), \tag{4}$$

where ψ is the prediction function, which first reserves N_o cross-features with the top-N_o weights to meet the sparsity constraint and then feed reserved features to output layer. That is, it is similar with ϕ in Definition 1. Such a continuous space can overcome the issue of discrete search space and the learned architecture parameters provide explicit meaning, *i.e.* the importance of cross-features.

Nevertheless, it ignores the different orders of cross-features, from 1 to O, and consider them as the same, which results in a very large-size weight tensor $\mathcal{A}$, with length $\sum_{o=1}^{O} C_M^o$, where M denotes the number of raw features. Such a NAS problem with a continuous space still has two critical issues.

- First, representation of the search space takes too many architecture parameters, which slows down the optimization procedure. With M fields of raw features and the desired feature order O, the size of architecture parameter for the search space of cross-feature is close to C_M^O, which approximately equals to M^O considering $M \gg O$. Obviously, M^O is a too large number in the gradient-based NAS. For example, the widely-used Criteo benchmark dataset has $M = 39$ of fields of raw features. If we choose the highest order as 4, then $C_{39}^4 = 82{,}251$. Such a parameter number is much larger compared with existing works of gradient-based NAS [23, 38], of which the number would always be fewer than one hundred. Therefore, the challenge of large search space is still unresolved.
- Second, such design still ignores the *order-priority property* in deep sparse prediction tasks. Specifically, the property consists of two characteristics revealed by human practice: higher-order features' quality can be relevant to their de-generated low-order ones, and lower-order cross-features are likely to be more vital compared with higher-order ones.

3.2 Proposed Search Method

To address the above-mentioned two limitations in Section 3.1, we present our solution PROFIT here with 1) a *distilled low-rank approximated search space* to address the space issue and 2) a *progressive search algorithm* to take order-priority property into consideration.

(a) Singular values of $\mathcal{A}$ for the second-order cross-features

(b) Correlations between low-order and high-order cross-features.

Figure 2: Key observations on search space (left) and search algorithm (right) for PROFIT.

3.2.1 Distilling the Search Space

As above, the architecture parameter, i.e., tensor $\mathcal{A}$, can be too large and ignore priorities on feature interactions. This can lead to high search costs and not be capable for finding desired architectures. Here, we study the property of $\mathcal{A}$ and attempt to approximate it with much fewer parameters.

We conduct an experiment on the Criteo dataset and set the max order as two due to the computation cost. This dataset has 39 fields, thus weights $\mathcal{A}$ for all second-order interactions can be represented by a matrix of size 39×39. Singular values from $\mathcal{A}$ and a randomly generated matrix are compared in Figure 2 (a). We can observe that the parameter matrix has several dominant singular values, exhibits a low-rank property. Besides, note that feature interaction is perturbation invariant, i.e., $f_1 \odot f_2 = f_2 \odot f_1$, which means the tensor should be symmetric. Thus, we propose to distilled tensor $\mathcal{A}$ as

$$\mathcal{A} \approx g(\{\boldsymbol{\beta}^o\}) \equiv \sum_{r=1}^{R} \underbrace{\boldsymbol{\beta}^r \circ \cdots \circ \boldsymbol{\beta}^r}_{\boldsymbol{\beta}^r \text{ repeats } O \text{ times.}}, \tag{5}$$

where each $\boldsymbol{\beta}^r \in \mathbb{R}^{1 \times M}$, and $R \ll M$ is the positive integer. Equation (5) can also be seen as a symmetric CP decomposition [16] for the tensor $\mathcal{A}$. Subsequently, the search problem in Definition 1 is transformed as

$$\{\boldsymbol{\beta}^o\}^* = \min_{\beta} \mathcal{L}\big(\psi(\mathbf{F}^*, g(\{\boldsymbol{\beta}^o\})); \mathcal{D}_{\text{val}}\big), \quad \text{s.t. } \mathbf{F}^* = \arg\min_{\mathbf{F}} \mathcal{L}\big(\psi(\mathbf{F}, g(\{\boldsymbol{\beta}^o\})); \mathcal{D}_{\text{tra}}\big). \tag{6}$$

Comparing with the original $\mathcal{A}$ in (4), of which size is about M^O and grows exponentially with O, $\{\boldsymbol{\beta}^r\}$ is of size $M \times O$ and can be much smaller. Thus, the number of architecture parameters is reduced significantly.

3.2.2 Progressive Search Algorithm

As mentioned above, different orders of cross-features are highly correlated. To confirm that higher-order cross-features that are constructed by important lower-order cross-features tend to be important, since the ML1M dataset has fewer fields of features and then a full space of high-order features are easier to optimize, we conduct the experiment on the ML1M dataset. We still use $\mathcal{A}$ in (3) and set the maximum order to two and three. The relative ranking is computed according to the importance weights of all same-order cross-features. For example, a second-order cross-feature with the relative ranking as one means it is the most important second-order cross-feature. For a given 2nd-order cross-feature, $\mathbf{f}_{c_1} \odot \mathbf{f}_{c_2}$, we can also compute the average relative ranking of third-order cross-features that consists of c_1 and c_2. We study whether an important second-order cross-feature can generate important third-order cross-features. The relative ranking is shown at Figure 2 (b), and experimental details are in Appendix A.5. We can easily observe that a good 2nd-order cross-feature is more likely to generate a good 3rd-order cross-feature. Note that these points are not monotonically increasing, with some *special* points such as the 5-th one. It shows the necessity of utilizing auxiliary parameter to model the high-order cross-features.

The above motivates us to adopt a progressive strategy to search for the architecture parameters from lower orders to higher orders, to tackle the problem of modeling order-priority. The complete steps are in Algorithm 1. Specifically, when searching for o-th order cross-feature, at step 2, we propose

Algorithm 1 Progressive gradient descent.

1: **for** $o = 1, \ldots, O$ **do**
2:     fix $\boldsymbol{\beta}^1, \boldsymbol{\beta}^2, ..., \boldsymbol{\beta}^{o-1}$;
3:     **for** $epoch = 1, \ldots, E_o$ **do**
4:         Update architecture parameters $\boldsymbol{\beta}^o$ using gradients $\nabla_{\boldsymbol{\beta}^o} \mathcal{L}\big(\psi(\mathbf{F}, g(\{\boldsymbol{\beta}^o\})); \mathcal{D}_{\text{val}}\big)$;
5:         Update embedding parameters $\mathbf{F}$ using gradients $\nabla_{\mathbf{F}} \mathcal{L}\big(\psi(\mathbf{F}, g(\{\boldsymbol{\beta}^o\})); \mathcal{D}_{\text{tra}}\big)$;
6:     **end for**
7: **end for**

---

to fix the architecture parameters with order lower than o, i.e., $\{\boldsymbol{\beta}^1, \ldots, \boldsymbol{\beta}^{o-1}\}$. Then, following existing works [23, 20, 40], at step 4 and 5, we also use gradient descent to update both architecture and embedding parameters.

3.2.3 Retraining the Searched Lightweight Model

Finally, as the existing NAS works [23, 41] reveal, it is better to re-train the model with the obtained embedding parameters. In our task, to ensure both the prediction accuracy and model efficiency, we only reserve the cross-features with top-N_o importance weights to meet the sparsity constraints. The reason is in two folds. First, some features do not benefit the task, and removing them can benefit the training procedure to achieve better prediction accuracy. Second, more importantly, only reserving N_o cross-features can largely reduce the model size and inference times, ensuring the real-world deployment on various hardware platforms.

3.3 Discussion

In this work, we focus on automatically searching for feature interaction layer for 1) effective cross-features and 2) high model inference efficiency. By distilling the search space and progressive updates of architecture parameters, our method can design data-specific feature interaction layer for DSNs in a more efficient and effective way than existing methods.

There are some works [22, 17] utilizing progressive search strategies for designing architectures of convolutional neural networks (CNNs). In these works, the progressive search manner can also help reduce searching costs. In our work, progressive search not only accelerates the search but also help capture the order-priority property in DSNs (see Figure 2).

Besides, it is worth mentioning there is another research direction closely related to this work, network sparsification [27, 36, 11, 39], which aims to prune the network components or parameters to reduce the network size while keeping a little performance decrease. Different from them, our work searches for the architecture in an interpretable and explicit manner: finding architectures that reserve important cross-features and remove useless ones; for network pruning models, embedding parameters are dropped in an implicit manner — the pruning masks are always implicitly learned from data, does not provide any interpretability. In deep sparse prediction tasks, it is more significant to explicitly lighten the model at the level of cross-feature, while existing works of network sparsification or network pruning is at the level of latent dimension.

4 Experiments

4.1 Settings

Datasets. To validate the effectiveness of our proposed PROFIT, we conduct experiments on three benchmark datasets (Criteo, Avazu and ML1M) widely used in existing works of deep sparse networks [6, 32, 18] to evaluate the performance, of which the details are provided in the Appendix.

Baselines. We compare our PROFIT with state-of-the-art methods for sparse prediction. We choose methods that are widely used and open-source:

- First-order method: logistic regression [13] (denoted as "LR");
- Second-order methods: we compared with the most widely-used second-order method factorization machine [28] (denoted as "FM") and the state-of-the-art second-order method attentive factorization

Table 1: Testing performance on Loss and AUC over three datasets.

Dataset		Criteo		Avazu		ML1M	
Order	Model	Loss	AUC	Loss	AUC	Loss	AUC
First	LR	0.4568	0.7936	0.3934	0.7570	0.5880	0.7418
Second	FM	0.4552	0.7954	0.3809	0.7803	0.5387	0.7938
	AFM	0.4538	0.7969	0.3832	0.7764	0.5530	0.7809
High	PNN	0.4508	0.8029	0.3798	0.7839	0.5254	0.8042
	AutoInt	0.4443	0.8074	0.3786	0.7849	0.5285	0.8014
	AFN	0.4428	0.8094	0.3803	0.7818	0.5294	0.8038
	DeepFM	0.4469	0.8050	0.3787	0.7844	0.5318	0.8044
	xDeepFM	0.4430	0.8093	0.3781	0.7856	**0.5280**	0.8069
NAS	AutoFIS	0.4537	0.7971	0.3815	0.7794	0.5353	0.7956
	PROFIT	**0.4427**	**0.8095**	**0.3735**	**0.7883**	0.5281	**0.8077**

machine [37][1] (denoted as "AFM"). NFM [12] is a de-generated version of AFM and thus we do not compared with it.

- Higher-order methods with deep feature-interaction layers: deep factorization machine DeepFM [9] extreme deep factorization machine [18][2] (denoted as "DeepFM") , extreme deep factorization machine [18][3] (denoted as "xDeepFM"), product neural network [26][4] (denoted as "PNN"), automatic feature Interaction learning [32] (denoted as "AutoInt") [5] and adaptive factorization network [6][6] (denoted as "AFN").

These human-designed baselines models are also selected as the representative DSN models for comparison in the AutoFIS paper. Besides, there is another recent work, i.e., AutoGroup [19], which is very similar to AutoFIS. Considering it has very close prediction performance and search cost compared with AutoFIS and is not open-source, we only compare AutoFIS in our experiments. There are some recent works [31, 15] approaching the problem via automatically fusing human-designed models, which is still restrained by human-designed feature-interaction layers (they are not open-source either and thus we do not compare with them). As mentioned above, there are some pioneer works that propose NAS methods for lightweight CNN models for computer vision tasks. Here we do not compare with them since it is hard to adapt them to the deep sparse networks.

Evaluation Metrics. We evalua te models from two perspectives, prediction performance and inference efficiency. For accuracy, we use two standard metrics, Logloss (denoted as "Loss") [25] and AUC [7], following [6, 9, 18, 28, 26]. For efficiency, we also use two standard metrics, inference time and model size, which are also widely used in existing works of deep sparse networks [32, 14].

Hyper-parameter Settings. To ensure the reproducibility of experimental results, here we introduce the implementation setting, of which more details are in Appendix.We implement our methods using PyTorch. We apply Adam with a learning rate of 0.001 and a mini-batch size of 4096, a widely-used setting in existing works [6, 32]. We set the embedding sizes to 16 in all the models. We use the same neural network structure ({400, 400, 400}) for all methods that adopts MLP for a fair comparison, following [6, 32]. All the other hyper-parameters are tuned on the validation set. To make the results more reliable, for each instance, we run the repetitive experiments for three times with different random seeds and report the average value.

4.2 Benchmark Comparison

Prediction accuracy. In Table 1, we present the prediction performance of all these methods, from which we have the following observations. First, models with higher-order cross-features can achieve better prediction performance than lower-order ones, which verifies the rationality of exploring high-order feature interactions. Second, with the carefully designed search space and search algorithm, PROFIT can achieve the best prediction performance on three benchmark datasets (or very close

---

[1]https://github.com/hexiangnan/attentional_factorization_machine

[2]https://github.com/ChenglongChen/tensorflow-DeepFM

[3]https://github.com/Leavingseason/xDeepFM

[4]https://github.com/shenweichen/DeepCTR

[5]https://github.com/DeepGraphLearning/RecommenderSystems. Although AutoInt uses the term "automatic", but it is not different from the definition of "automatic" in AutoML.

[6]https://github.com/WeiyuCheng/AFN-AAAI-20

Figure 3: Performance comparison of PROFIT and baseline models. ("Size" refers to the model size without feature embedding layer. "Time" refers to the inference time for one million samples.)

to the best baseline). Third, the deep sparse networks achieve better performance compared with shallow models, which demonstrates the necessity of designing powerful deep sparse networks. Note that due to the limitations in search space and algorithm, which making the searching procedure very slow, AutoFIS does not achieve promising results compared with human-designed ones[7].

Efficiency. We further compare the efficiency and present the results in Figure 3. We can observe that PROFIT is lightweight and fast-to-infer among all compared methods.

Figure 4: Performance of utilizing different orders' cross-features on ML1M dataset.

Table 2: Performance of searched model with progressive/one-step/random search.

Search	Criteo		Avazu		ML1M	
Algo.	Loss	AUC	Loss	AUC	Loss	AUC
Random with PS	0.4724	0.7718	0.4012	0.7499	0.5744	0.7692
One-step Search	0.4459	0.8077	0.3761	0.7851	0.5355	0.8053
PROFIT	0.4427	0.8095	0.3735	0.7883	0.5281	0.8077

4.3 Understanding the Search Strategy

Progressive search. In order to validate the effectiveness of the progressive manner in our search algorithm, we compared with the performance that utilizes a one-step manner. It can be regarded as the de-generated version of our PROFIT that replaces our progressive search with one step, and the details of its searching procedure are shown in Appendix A.4. We also compare the random search with PS (parameter sharing), of which architecture parameters are randomly assigned, and the model parameters are shared during the search procedures. The final performance of the searched architectures is shown in Table 2. The curve of validation performance during the searching procedure is shown in Figure 5.

From these results, we can observe that random search achieves the worst performance since it does not explore any domain properties, as we have analyzed in Section 3.1. Also, with the simple one-step search algorithm, the performance is poorer compared with the progressive search algorithm. This validates the rationality of our design of progressive search, which can well capture the order-priority

---

[7]In the original paper of AutoFIS, it achieves slightly better performance compared with human-crafted baselines when setting the max order of cross-features as three. However, during our experiments, for the Criteo dataset and Avazu dataset, we find it cannot be optimized due to too large search space and computation costs. Thus, we only report the results setting max order to two for these two datasets.

property of cross-features in the deep sparse prediction task. In short, the effectiveness of our design of progressive search is well validated by the results.

(a) Criteo

(b) Avazu

Figure 5: The validation performance during searching with progressive/one-step/random search.

Distilled search space. First, we conduct experiments to study the searched results if different search space is used. We compared our distilled space, i.e., Eqn (6), with a full space, i.e. Eqn (4). We choose the order of three. The curve of validation performance during the search procedure of two large-scale datasets, Avazu and Criteo, is shown in Figure 6, and the final results are shown in Table 3. We can observe that searching in the distilled space can easily reach a promising validation performance. However, when searching in the full space, it requires a higher computation cost, and as a result, it is hard to obtain good architecture parameters. As a result, the distilled search space obtains better prediction performance. These results show that with a reduced budget for searching, using the distilled space is a much better choice compared with the original full search space.

(a) Criteo

(b) Avazu

Figure 6: The validation performance during searching with different search space (please note that we use validation performance to illustrate the searching procedure following existing NAS works).

Table 3: Searched model's performance with different search space.

Dataset	Criteo		Avazu		ML1M	
Model	Loss	AUC	Loss	AUC	Loss	AUC
Full Space	0.4533	0.7975	0.3802	0.7807	0.5353	0.7957
PROFIT's Space	0.4427	0.8095	0.3735	0.7883	0.5281	0.8077

5 Conclusion

In this work, we approached the problem of deep sparse prediction with neural architecture search. We propose a distilled search space which is a low-rank approximation of the full space, significantly reducing the search cost. We then propose a progressive differentiable search algorithm that can efficiently search for desired models in the space while being consistent with the order-priority property. Extensive experiments on three real-world benchmark datasets demonstrate that our proposed PROFIT can achieve both high accuracy and high efficiency. Further studies illustrate that the proposed search space and search algorithm of PROFIT is feasible. As for future work, we will explore more on how dataset characteristics affect the searching results.

References

[1] Bowen Baker, Otkrist Gupta, Nikhil Naik, and Ramesh Raskar. Designing neural network architectures using reinforcement learning. In *International Conference on Learning Representations (ICLR)*, 2017.

[2] Han Cai, Chuang Gan, Tianzhe Wang, Zhekai Zhang, and Song Han. Once-for-all: Train one network and specialize it for efficient deployment. In *International Conference on Learning Representations (ICLR)*, 2019.

[3] Han Cai, Ligeng Zhu, and Song Han. Proxylessnas: Direct neural architecture search on target task and hardware. In *International Conference on Learning Representations (ICLR)*, 2019.

[4] Yukang Chen, Tong Yang, Xiangyu Zhang, Gaofeng Meng, Xinyu Xiao, and Jian Sun. Detnas: Backbone search for object detection. In *Advances in neural information processing systems (NeurIPS)*, pages 6638–6648, 2019.

[5] Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, et al. Wide & deep learning for recommender systems. In *Proceedings of the 1st workshop on deep learning for recommender systems*, pages 7–10, 2016.

[6] Weiyu Cheng, Yanyan Shen, and Linpeng Huang. Adaptive factorization network: Learning adaptive-order feature interactions. In *The AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

[7] Corinna Cortes and Mehryar Mohri. Auc optimization vs. error rate minimization. In *Advances in neural information processing systems (NeurIPS)*, pages 313–320, 2004.

[8] Thomas Elsken, Jan Hendrik Metzen, Frank Hutter, et al. Neural architecture search: A survey. *Journal of Machine Learning Research (JMLR)*, 20(55):1–21, 2019.

[9] Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. Deepfm: a factorization-machine based neural network for ctr prediction. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2017.

[10] Zichao Guo, Xiangyu Zhang, Haoyuan Mu, Wen Heng, Zechun Liu, Yichen Wei, and Jian Sun. Single path one-shot neural architecture search with uniform sampling. In *European Conference on Computer Vision (ECCV)*, pages 544–560. Springer, 2020.

[11] Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. 2016.

[12] Xiangnan He and Tat-Seng Chua. Neural factorization machines for sparse predictive analytics. In *Proceedings of the 40th International ACM SIGIR conference on Research and Development in Information Retrieval (SIGIR)*, pages 355–364, 2017.

[13] David W Hosmer Jr, Stanley Lemeshow, and Rodney X Sturdivant. *Applied logistic regression*, volume 398. John Wiley & Sons, 2013.

[14] Yuchin Juan, Yong Zhuang, Wei-Sheng Chin, and Chih-Jen Lin. Field-aware factorization machines for ctr prediction. In *Proceedings of the 10th ACM conference on recommender systems (RecSys)*, pages 43–50, 2016.

[15] Farhan Khawar, Xu Hang, Ruiming Tang, Bin Liu, Zhenguo Li, and Xiuqiang He. Autofeature: Searching for feature interactions and their architectures for click-through rate prediction. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management (CIKM)*, pages 625–634, 2020.

[16] Tamara G Kolda and Brett W Bader. Tensor decompositions and applications. *SIAM review*, 51(3):455–500, 2009.

[17] Guohao Li, Guocheng Qian, Itzel C Delgadillo, Matthias Muller, Ali Thabet, and Bernard Ghanem. SGAS: Sequential greedy architecture search. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1620–1630, 2020.

[18] Jianxun Lian, Xiaohuan Zhou, Fuzheng Zhang, Zhongxia Chen, Xing Xie, and Guangzhong Sun. xdeepfm: Combining explicit and implicit feature interactions for recommender systems. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD)*, pages 1754–1763, 2018.

[19] Bin Liu, Niannan Xue, Huifeng Guo, Ruiming Tang, Stefanos Zafeiriou, Xiuqiang He, and Zhenguo Li. Autogroup: Automatic feature grouping for modelling explicit high-order feature interactions in ctr prediction. In *International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, pages 199–208, 2020.

[20] Bin Liu, Chenxu Zhu, Guilin Li, Weinan Zhang, Jincai Lai, Ruiming Tang, Xiuqiang He, Zhenguo Li, and Yong Yu. Autofis: Automatic feature interaction selection in factorization models for click-through rate prediction. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD)*, 2020.

[21] Chenxi Liu, Liang-Chieh Chen, Florian Schroff, Hartwig Adam, Wei Hua, Alan L Yuille, and Li Fei-Fei. Auto-deeplab: Hierarchical neural architecture search for semantic image segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 82–92, 2019.

[22] Chenxi Liu, Barret Zoph, Maxim Neumann, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search. In *European Conference on Computer Vision (ECCV)*, pages 19–34, 2018.

[23] Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable architecture search. 2019.

[24] Yuanfei Luo, Mengshuo Wang, Hao Zhou, Quanming Yao, Wei-Wei Tu, Yuqiang Chen, Wenyuan Dai, and Qiang Yang. Autocross: Automatic feature crossing for tabular data in real-world applications. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD)*, pages 1936–1945, 2019.

[25] Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

[26] Yanru Qu, Han Cai, Kan Ren, Weinan Zhang, Yong Yu, Ying Wen, and Jun Wang. Product-based neural networks for user response prediction. In *2016 IEEE 16th International Conference on Data Mining (ICDM)*, pages 1149–1154. IEEE, 2016.

[27] Russell Reed. Pruning algorithms-a survey. *IEEE transactions on Neural Networks*, 4(5):740–747, 1993.

[28] Steffen Rendle. Factorization machines. In *2010 IEEE International Conference on Data Mining (ICDM)*, pages 995–1000. IEEE, 2010.

[29] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR)*, pages 4510–4520, 2018.

[30] David So, Quoc Le, and Chen Liang. The evolved transformer. In *International Conference on Machine Learning (ICML)*, pages 5877–5886, 2019.

[31] Qingquan Song, Dehua Cheng, Hanning Zhou, Jiyan Yang, Yuandong Tian, and Xia Hu. Towards automated neural interaction discovery for click-through rate prediction. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD)*, pages 945–955, 2020.

[32] Weiping Song, Chence Shi, Zhiping Xiao, Zhijian Duan, Yewen Xu, Ming Zhang, and Jian Tang. Autoint: Automatic feature interaction learning via self-attentive neural networks. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management (CIKM)*, pages 1161–1170, 2019.

[33] Xiaoyuan Su and Taghi M Khoshgoftaar. A survey of collaborative filtering techniques. *Advances in artificial intelligence*, 2009, 2009.

[34] Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2820–2828, 2019.

[35] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning (ICML)*, pages 6105–6114, 2019.

[36] Wei Wen, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Learning structured sparsity in deep neural networks. In *Advances in neural information processing systems (NeurIPS)*, 2016.

[37] Jun Xiao, Hao Ye, Xiangnan He, Hanwang Zhang, Fei Wu, and Tat-Seng Chua. Attentional factorization machines: Learning the weight of feature interactions via attention networks. 2017.

[38] Sirui Xie, Hehui Zheng, Chunxiao Liu, and Liang Lin. Snas: stochastic neural architecture search. In *International Conference on Learning Representations (ICLR)*, 2019.

[39] Niannan Xue, Bin Liu, Huifeng Guo, Ruiming Tang, Fengwei Zhou, Stefanos P Zafeiriou, Yuzhou Zhang, Jun Wang, and Zhenguo Li. Autohash: Learning higher-order feature interactions for deep ctr prediction. *IEEE Transactions on Knowledge and Data Engineering (TKDE)*, 2020.

[40] Quanming Yao, Ju Xu, Wei-Wei Tu, and Zhanxing Zhu. Efficient neural architecture search via proximal iterations. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pages 6664–6671, 2020.

[41] Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. In *International Conference on Learning Representations (ICLR)*, 2017.

[42] Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR)*, pages 8697–8710, 2018.