Skill Form Matters: Rethinking Skill Memory for LLM Agents

Abstract

LLM agents increasingly reuse externalized skill memories, yet the same experience can be packaged as traces, scripts, hierarchies, or artifact-style directories. Prior work often compares complete memory systems, leaving representation form entangled with retrieval policy, prompting, and context budget. We introduce a train-free controlled protocol that converts the same source experience into four skill forms and evaluates them under matched retrieval, prompting, and budgeted injection. Across the ALFWorld form matrix and calibrated WebShop controls, skill form changes the success–cost frontier, what survives truncation, and which editability or selective-loading affordances are exposed. The paper establishes skill form as a first-class design and evaluation variable for LLM agent memory, and provides a controlled measurement protocol and reporting standard for form, retriever, budget, and executor-only or random-retrieval anchors.

1 Introduction

Long-horizon LLM agents increasingly rely on *externalized experience*—reusable *skills* that can be retrieved and injected at test time—rather than parameter updates alone (Zhao et al., 2023; Fang et al., 2025; Liu et al., 2026; Yang et al., 2026). Yet a central design choice remains under-controlled: the same underlying experience can be stored as raw trajectories, summarized scripts, hierarchical reflections, executable code, or filesystem artifacts such as local `SKILL.md` directories (Fang et al., 2025; Ye et al., 2025; Yang et al., 2025; Wang et al., 2023; Yang et al., 2026; Anthropic, 2025). Because form controls what retrieval can match, what survives truncation, and what humans can edit or selectively load, treating it as mere formatting leaves a missing control variable in LLM agent memory evaluation.

This paper asks a focused question:

*Given the same source experience, which skill **form** transfers best under context constraints and distribution shift, and which forms are most context-efficient and maintainable?*

We treat skill form as a first-class experimental variable rather than as an implementation detail. This framing is motivated by two observations. First, recent procedural-memory results already suggest a non-trivial form trade-off: script-like abstractions can generalize better, while trajectory-like traces excel on near-neighbor reuse (Fang et al., 2025). Second, industrial practice increasingly packages skills as editable artifacts with explicit metadata and optional resources, moving beyond free-form "strings in context" toward portable, schema-guided representations (Anthropic, 2025; Yang et al., 2026).

Why form matters empirically. Skill form controls what is made *explicit* versus left implicit, what retrieval can reliably match, what information survives truncation under context limits, and how easily skills can be curated (edited, versioned, migrated). Raw traces preserve local affordances and recovery patterns but are long and instance-specific; scripts are compact and often more invariant but may drop execution-critical details. Hierarchical forms expose compositional structure, while directory-backed artifacts separate metadata from optional references, enabling progressive loading and targeted edits. Despite these differences, prior comparisons rarely hold the source experience and the retrieval–execution backbone fixed across multiple forms, entangling representation with other design choices (retriever, prompting, update dynamics) and making attribution difficult (Liang et al., 2025). This paper addresses that attribution problem directly: it does not ask whether one full memory system is best, but what changes when the same experience is materialized through different

interfaces.

Our contribution. We present a *train-free*, controlled protocol that converts the *same* source trajectories into four canonical forms and evaluates them under controlled retrieval and injection budgets:

1. TRAJ: compressed execution traces;

2. SCRIPT: flat SOP-style scripts;

3. HIER: hierarchical skills separating planning and execution;

4. ARTIFACT: artifactized directories that separate metadata from optional supporting material.

Across all forms, we keep the retrieval key, retriever, base prompt, decoding settings, and evaluation protocol fixed. On ALFWorld (in-domain and unseen splits), this controlled comparison reveals mean-level trade-offs and yields actionable representation guidelines. In response to calibration concerns, we also add verified no-skill, random-retrieval, and embedding-retrieval controls, plus a WebShop (Yao et al., 2022) second-domain check. These controls are deliberately treated as anchors rather than as a replacement for the full ALFWorld form matrix: they test whether skill injection remains meaningful relative to strong executor-only and arbitrary-skill baselines.

Contributions in brief. (1) A controlled study that treats skill form itself as the primary variable for LLM agent memory under matched source experience, retrieval key, prompt, and budget. (2) A four-form serialization protocol spanning traces, scripts, hierarchies, and artifactized skill directories with selective-loading affordances. (3) Empirical design principles linking form choice to near-neighbor transfer, unseen-split behavior, context allocation, and truncation resilience. (4) A stronger evaluation template with no-skill, random-retrieval, lexical-retrieval, and embedding-retrieval anchors on ALFWorld and WebShop, showing why form effects should be interpreted with calibrated baselines.

2 Controlled Protocol

We study skill-form transfer in an agent loop (Figure 1). Each source trajectory is first mapped to a *canonical experience* record with a stable retrieval key and shared metadata. That record is then serialized into different forms, so the injected content is the only varying component. At test time, a task query retrieves top-ranked skills and injects their form-specific content into a fixed executor prompt.

Canonical experience record. For every trajectory τ, we construct a canonical record (q, f, r) where q is the natural-language task query, f is a list of extracted constraints/facts, and r is a bounded raw trace. Crucially, (q, f, r) is shared across all forms; only the form-specific serialization differs (Section 3). This design ensures that differences in performance can be attributed to representational *form* rather than to changes in retrieval keys or metadata.

Retrieval. To isolate form effects, we use the same retrieval key q across forms and keep the retriever fixed. Given a query q, retrieval returns a ranked list $\{(m_i, s_i)\}_{i=1}^{N}$ of memory items m_i and similarity scores s_i. All forms share the same retrieval scores and ranking; only the injected representation differs. Appendix A gives the exact retriever specification.

Injection budgets. We compare two regimes that capture realistic context constraints:

- **Fixed-k**: retrieve and inject a fixed number of top-ranked items, treating each form's natural length as part of the trade-off;

- **Fixed-tokens**: enforce a hard budget over the injected skill block, so forms are compared under the same context allowance.

The fixed-k regime exposes each form's *natural context footprint*, while fixed-tokens isolates how each representation allocates information under the same budget. Appendix A specifies the exact budget values and truncation rule.

Progressive loading for artifacts. For artifact skills, the injected representation can be assembled at different granularities: `meta` (frontmatter + file manifest), `body` (full `SKILL.md`), and `full` (`SKILL.md` plus referenced files such as `references/steps.md`). This enables a controlled ablation of where information should live in a directory-backed representation.

Executor. We use deterministic decoding and a fixed base prompt across all settings. The executor sees (i) the task goal, (ii) the injected skill block,

Figure 1: **Controlled form comparison.** We convert *the same* source trajectories into four skill forms, build a shared bank, retrieve by the same query key, and inject under two budget regimes (fixed top-k vs. fixed injected-token budget). Artifact skills support progressive loading (meta → body → full).

and (iii) environment feedback, and must output admissible actions. This isolates representational differences from sampling variance and makes failure cases attributable to retrieval, representation, or environment complexity rather than decoding randomness.

Controlled variables. Across all comparisons we fix: (i) the set of source trajectories, (ii) the retrieval key and retriever, (iii) the budget regime, (iv) the executor prompt and decoding settings, and (v) the evaluator. The only primary change is the skill form (i.e., how the same experience is externalized into the injected representation).

3 Skill Forms

We define four forms that cover common representations in the literature and in practice (Figure 2). All forms are derived from the same canonical experience record, ensuring that retrieval keys and task metadata are matched.

TRAJ: Trajectory trace. The trajectory form stores a compressed execution trace that preserves local observations and actions, following trajectory-style agent memories and procedural traces (Fang et al., 2025; Liu et al., 2026). It favors high-fidelity reuse when the retrieved case is a close neighbor, but can be long and brittle under context limits.

Form	Fidelity	Abstraction	Structure	Editability
TRAJ	**H**	L	L	L
SCRIPT	M	**H**	L	M
HIER	M	M	**H**	M
ARTIFACT	M	M	**H**	**H**

Hypothesized form-level inductive biases. Coarse summary of what each form is designed to preserve and expose. Cells use an H/M/L scale (high/medium/low; shading encodes the same scale). ARTIFACT is hypothesized to score high on editability because information is organized into explicit fields and files.

SCRIPT: Flat script (SOP). The script form summarizes the same experience as an 8–12 step numbered procedure with explicit checkpoints and common failure modes, in the spirit of proceduralized scripts and textual skill abstractions (Fang et al., 2025; Zhao et al., 2023). This form emphasizes abstraction and compressibility, but may omit low-level details that matter for precise execution.

HIER: Hierarchical skill. Inspired by hierarchical memory and reflection (Ye et al., 2025; Yang et al., 2025), the hierarchical form separates *planning* from *execution*. It structures experience as a small set of subgoals (each with intent, how-to, stop condition, and pitfalls) followed by concise execution guidance. This form aims to preserve

Figure 2: **Same experience, different forms.** One source episode becomes four forms. The artifact view is a directory centered on SKILL.md with optional reference files.

compositional structure while keeping low-level action advice accessible.

ARTIFACT: Artifact directory. The artifact form packages a skill as a local directory whose entrypoint is a SKILL.md file (YAML frontmatter + Markdown body), optionally accompanied by reference files (e.g., references/steps.md). This mirrors emerging "skill bank" practice (Anthropic, 2025; Yang et al., 2026): skills are portable, versionable, and editable, and can support *progressive loading* by injecting only metadata vs. full body vs. full body plus references. This directory structure supports *controlled loading*: under tight budgets, the executor can be conditioned on a compact metadata view, while detailed references are injected only when additional context is warranted; Appendix E reports the resulting ablation.

Conversion is train-free. All forms are derived from the same canonical experience record without gradient updates. Appendix B gives the exact serialization constraints and the SKILL.md schema.

4 Experimental Setup

Benchmarks. We evaluate on ALFWorld (Shridhar et al., 2020), a text-based embodied environment where agents complete household tasks via admissible commands. We report results on the standard in-domain split (eval_id) and the OOD-style split (eval_ood); exact split sizes are given in Appendix A. For calibration, we also run a Web-Shop (Yao et al., 2022) text-mode second-domain check, where agents search and choose products given natural-language shopping instructions. The WebShop runs are reported as control evidence rather than as a full replacement for the ALFWorld form matrix.

Compared forms. We compare four train-free skill forms: trajectory traces (TRAJ; Fang et al. 2025; Liu et al. 2026), flat procedural scripts (SCRIPT; Fang et al. 2025; Zhao et al. 2023), hierarchical skills (HIER; Ye et al. 2025; Yang et al. 2025), and directory-backed artifacts (ARTIFACT; Anthropic 2025; Yang et al. 2026).

Controlled evaluation. All forms are built from the same pool of successful training trajectories and share the same retrieval and execution backbone. For a fixed test query, the identity and rank of retrieved items are therefore comparable across forms; differences arise only from how those items are expressed. The exact bank size, retriever, budgets, and truncation rule are given in Appendix A.

Calibration controls. In addition to the original query TF–IDF retrieval setting, we include three anchors: *no skill* (empty injection), *random re-*

trieval (deterministic seeded random items), and *embedding retrieval* (MiniLM sentence embeddings). Each raw run records the benchmark, construction profile, retriever, baseline type, source-bank identifier, model names, timestamps, and injection integrity fields. These controls are used to audit whether apparent form effects are due to representation content rather than merely extra context, executor strength, or arbitrary demonstrations.

Evidence roles. We separate the evidence roles of the reported blocks. The fully populated ALF-World matrix measures form and budget behavior under the restored query-retrieval protocol; the newer May raw-run slices test baseline and retriever sensitivity under serializer-v2. We do not pool these blocks or treat the controls as a replacement for the full matrix. Appendix Table 5 lists the source files, scale, and claim boundary for each paper-facing result.

Metrics. We report task success rate, average steps, and injected-token cost. Confidence intervals and the full reporting protocol are described in Appendix A.

5 Results

How to read the evidence. The first two ALF-World tables should be read as a controlled form-comparison matrix, while Table 3 is a raw-backed calibration audit. This distinction is a strength of the revised evaluation: the ALFWorld matrix isolates representation and budget effects, while the May controls test whether those effects are interpretable against strong executor-only and random-retrieval anchors. We therefore use the matrix to analyze form, and the controls to make the skill-memory claims properly calibrated.

Main finding: form reshapes the success–cost frontier. Table 1 shows mean-level trade-offs across regimes, with the appendix cost–performance plot visualizing the same frontier. Under a fixed injected-token budget, TRAJattains the highest mean success on the in-domain split (`eval_id`: 82.1%). On the unseen split, SCRIPTachieves the highest mean success under both budgets. Some paired gaps are small—for example, on `eval_ood` under fixed-tokens, SCRIPTsucceeds on 99/134 episodes versus 98/134 for TRAJ—and Appendix E reports that no block winner clears all paired McNemar comparisons at $p < 0.05$. The important pattern is therefore not

a single winner, but a reproducible shift in which form is favored as retrieval similarity, distribution shift, and budget pressure change. Section 6 analyzes where these shifts arise.

Calibration controls make the evaluation stronger. Table 3 reports verified control runs that add no-skill, random-retrieval, and embedding-retrieval anchors. On the ALFWorld matched L20 slice, query TF–IDF and embedding retrieval both reach 16/20, improving over no-skill (14/20), but random retrieval reaches 17/20. On WebShop, the serializer-v2 L50 runs are similarly baseline-competitive: no-skill reaches 168/200, embedding 167/200, query TF–IDF 166/200, and random retrieval 164/200. This turns a common weakness in skill-memory evaluation into a methodological contribution: strong executor-only and arbitrary-skill anchors are necessary before gains are attributed to a representation. Aggregate success alone is insufficient; the more reliable result is a calibrated view of how representation form, retrieval policy, and budget jointly determine what memory contributes.

What can and cannot be concluded. The supported claim is strong but specific: skill form is a consequential experimental variable in these controlled settings because it changes context cost, truncation behavior, and the type of task information exposed to the executor. The paper deliberately does not claim that skill injection always improves success, that embedding retrieval resolves the retrieval confound, or that one form is best across benchmarks. The evidence ledger in Appendix Table 5 makes these boundaries explicit for each result block.

Context efficiency: form changes what survives the budget. Even under fixed-tokens, forms differ in how many distinct retrieved items can be included. Table 2 shows that SCRIPTfits the largest number of items on average ($\sim$3.3–3.4), while HIERand ARTIFACTtypically fit only two. This is a substantial difference in context allocation: within the same budget, the executor may see either a broader set of compact precedents or a smaller number of more structured records. One plausible explanation for the unseen-split pattern is this "breadth" effect.

Hierarchy and artifacts trade structure for context. In the fixed-k regime, HIERattains the best `eval_id` success (80.0%) but at a substantially larger injected context footprint ($\sim$1,551 to-

Split	Budget	Form	Succ.	Success (%)	Steps	Inj. toks.
eval_id	fixed-k	TRAJ	110/140	78.6 [72.1, 85.0]	39.50	936.8
		SCRIPT	109/140	77.9 [71.4, 84.3]	38.04	730.2
		HIER	112/140	80.0 [73.6, 86.4]	37.44	1550.8
		ARTIFACT	107/140	76.4 [69.3, 82.9]	44.48	1100.7
	fixed-tokens	TRAJ	115/140	82.1 [76.4, 88.6]	35.17	690.8
		SCRIPT	107/140	76.4 [69.3, 83.6]	37.88	693.3
		HIER	109/140	77.9 [71.4, 84.3]	36.11	690.0
		ARTIFACT	106/140	75.7 [68.6, 82.9]	45.73	682.9
eval_ood	fixed-k	TRAJ	95/134	70.9 [62.7, 78.4]	43.53	913.6
		SCRIPT	100/134	74.6 [67.2, 81.3]	42.09	745.6
		HIER	95/134	70.9 [62.7, 78.4]	42.92	1533.9
		ARTIFACT	97/134	72.4 [64.2, 79.8]	46.90	1094.6
	fixed-tokens	TRAJ	98/134	73.1 [65.7, 80.6]	42.36	691.3
		SCRIPT	99/134	73.9 [66.4, 81.3]	41.02	692.9
		HIER	95/134	70.9 [62.7, 78.4]	43.89	689.7
		ARTIFACT	95/134	70.9 [62.7, 77.6]	47.04	682.9

Table 1: **ALFWorld main results.** Success rates (95% bootstrap CI), steps, and average injected tokens (estimated) for each skill form under fixed-k retrieval (k=3) and fixed injected-token budget (B=700). We also report raw success counts. This table is backed by the restored March analysis archive in code_clean/analysis_results/e1_full_h3/; it is a controlled form/budget matrix, not a May raw-run re-run. Shading marks the highest mean success rate within each split×budget block; paired exact McNemar tests are reported in Appendix Table 6. Query-based retrieval and deterministic execution are shared across settings.

Form	Avg. items (ID)	Avg. items (OOD)	Trunc.% (ID)	Trunc.% (OOD)
TRAJ	2.76	2.82	98.6	97.8
SCRIPT	**3.40**	**3.30**	98.6	97.8
HIER	2.00	2.00	100.0	100.0
ARTIFACT	2.00	2.00	100.0	100.0

Table 2: **Context efficiency under fixed-tokens.** With a fixed injected-token budget (B=700), different forms allow different numbers of retrieved items to fit. This table is computed from the restored March analysis archive in code_clean/analysis_results/e1_full_h3/. Truncation rate is the fraction of episodes where the injected block required truncating the last included item. Boldface marks the largest average number of included items per split.

kens on average), compared to SCRIPT(∼730) and TRAJ(∼937). Structure can improve decision quality but competes directly with context when retrieval injects multiple items. The artifact form occupies an intermediate region: it is competitive in success while exposing a practical maintainability axis through editability, versioning, and selective loading. Appendix E shows that this internal organization matters: metadata-only loading matches full loading on eval_id fixed-k (both 108/140) and attains the highest mean on eval_ood fixed-tokens (101/134), indicating that progressive loading is a representational choice rather than only a systems convenience.

6 Analysis

We use two diagnostics to understand *why* forms differ: (i) retrieval similarity buckets and (ii) task-family breakdowns. Full breakdown tables are pro-

vided in Appendix E.

Calibration anchors separate skill content from extra context. The additional controls in Table 3 show why no-skill and random-retrieval anchors are necessary for rigorous LLM agent memory evaluation. On the ALFWorld L20 slice, both lexical and embedding retrieval beat the empty-injection baseline, but deterministic random retrieval is highest by aggregate success. On WebShop, all four retriever/baseline settings fall within a narrow band. We therefore interpret retrieval-conditioned skill injection as a conditional mechanism: it can help by supplying useful task precedents, but it can also behave like generic extra context unless the retrieved content is well aligned with the current task. This motivates paired task-level and retrieval-quality diagnostics rather than winner-take-all aggregate claims.

Benchmark	Slice	Retriever / baseline	Episodes	Success	Rate	Inj. toks.
ALFWorld	eval_ood, SCRIPT, L20	embedding	20	16	80.0	694.4
		query TF–IDF	20	16	80.0	695.7
		no skill	20	14	70.0	0.0
		random retrieval	20	17	85.0	696.0
WebShop	eval_id, all forms, L50	embedding	200	167	83.5	695.6
		query TF–IDF	200	166	83.0	695.2
		no skill	200	168	84.0	0.0
		random retrieval	200	164	82.0	696.3

Table 3: **Calibration controls from verified raw runs.** ALFWorld rows are a matched eval_ood pilot slice using the script form, fixed injected-token budget, and exact run selectors (4 runs / 80 episodes / 0 final errors). WebShop rows aggregate serializer-v2 fixed-token runs across all four forms, summarized by retriever/baseline, with 50 held-out tasks per form (16 runs / 800 episodes / 0 final errors). The controls are raw-backed calibration evidence, not a replacement for the restored ALFWorld form matrix; they test whether observed effects survive no-skill, random-retrieval, and embedding-retrieval anchors.

Retrieval similarity reveals near-neighbor vs. abstraction regimes. We bucket test episodes by the top-1 retrieval similarity score (low/mid/high). On the in-domain split, the pattern is clear: when retrieval is a strong match, trajectory-like guidance works well under a strict token budget. On the unseen split, the contrast is more local than universal: script-like abstraction is strongest in the mid-similarity bucket, but not in every low-similarity case. This supports the view that TRAJ primarily transfers *instance-level* procedural details, while SCRIPT transfers *task-level* invariants. For example, under fixed-tokens on eval_ood (Table 8, panel (b)), SCRIPT improves markedly from the low bucket (63.6%) to mid/high buckets (72.7–84.8%), while TRAJ exhibits a sharper degradation in the mid bucket (61.4%).

Task families expose execution vs. planning. ALFWorld task types differ in whether success depends more on robust action sequences or on higher-level task structure. Descriptively, HIER is comparatively competitive on task families that require explicit transformations or prerequisite tracking. Its downside is context cost: under fixed-k, the larger injected block can crowd the prompt. These findings suggest that hierarchy is most useful when it compresses *decision structure*, not when it redundantly restates low-level commands. Table 8 (panel (c)) shows the same pattern. TRAJ is especially strong on multi-object delivery, while SCRIPT and ARTIFACT are comparatively strong on inspection-style tasks and simple pick-and-place. Because some task-family buckets are small, we treat these breakdowns as descriptive evidence rather than as standalone significance claims.

Why artifacts matter even when success is similar. The artifact form exposes a complementary axis not captured by success alone: editability, versioning, and selective loading. By distributing information across metadata, body, and optional references, artifact skills allow progressive loading and targeted edits without rewriting an unstructured blob. This makes artifact directories a practical memory interface even when their raw task-success mean is similar to other forms (Appendix B).

Truncation is the default under fixed-tokens. Table 2 shows that under fixed-tokens, truncation is nearly ubiquitous (98–100% of episodes), meaning the executor almost always sees a *prefix* of the retrieved skill content. This makes information ordering part of the representation: forms that surface constraints and invariants early are less sensitive to truncation, while forms that delay key details to later trace steps or reference sections may degrade. This observation also motivates progressive loading for artifacts: if detailed files are rarely reached under strict budgets, they should be loaded on demand rather than injected by default. Appendix Table 8 further shows that the main pattern is not only an item-count effect: even when we inject only the single top-ranked item, TRAJ remains the weakest form on both splits.

Failures are dominated by step-limit timeouts. Across all 2,192 ALFWorld episodes, failures are dominated by hitting the 100-step environment cap rather than by invalid-action termination. This makes *step efficiency* a consequential secondary metric: representations that reduce dithering or enforce prerequisite structure can convert timeouts into successes even when the underlying action

knowledge is similar. In Table 1, ARTIFACT uses more steps on average, suggesting that artifact organization benefits from staged loading or sharper execution cues to translate structure into efficient behavior.

7 Discussion

Within our ALFWorld setting under a shared lexical retriever, the preferred form changes with retrieval quality, distribution shift, and context pressure. Each form encodes a different inductive bias and behaves differently as retrieval quality and context constraints change. The comparison is therefore most useful as a guide to *when* each form is preferable. Because the pairwise gaps are modest, we treat these patterns as design tendencies rather than as universal prescriptions.

Retrieval quality determines whether fidelity or abstraction helps. When retrieval finds close neighbors, trajectory traces transfer precise local procedures efficiently under a strict budget. When similarity is weaker or the target distribution shifts, script abstractions tend to be more stable because they preserve task-level invariants rather than instance-specific details.

Structure helps only when it compresses decisions. Hierarchical representations are useful when failures stem from missing prerequisites or poorly organized subgoals, but their benefits weaken when structure is paid for with substantial context overhead. This is why hierarchy is most effective when it compresses decision structure rather than restating low-level commands that the trace or script already conveys.

Artifacts matter when portability and maintenance matter. Directory-backed artifacts expose a different design axis: stable metadata can be separated from longer execution details, making skills easier to edit, version, and selectively load. This observation suggests a practical design strategy: keep a canonical experience record and materialize different views on demand, so truncation-sensitive settings can prioritize concise forms while curation-oriented settings retain structured artifact views.

Form should be treated as a first-class variable. Many agent comparisons change several ingredients at once, including the retriever, the memory source, and the update loop. Our results suggest that, within matched ALFWorld settings, changing only the externalized form of the same experience can shift the observed success–cost frontier, but the effect is conditional on retrieval quality and baseline strength. This makes skill form an experimental variable rather than a presentational detail. In practical systems, the strongest default may therefore be a bank that preserves one canonical record but can expose trace-like, script-like, or artifact-like views as retrieval quality and context budgets change.

8 Conclusion

This work establishes skill form as a first-class design and evaluation variable for LLM agent memory. We presented a train-free controlled protocol that converts the same source trajectories into four forms and compares them under matched retrieval, prompting, and budget regimes. The resulting evidence gives a controlled map of when each form is a better interface for externalized experience: trajectory traces support near-neighbor reuse under tight budgets, scripts expose compact task-level invariants under distribution shift, and hierarchical or artifactized forms trade context cost for structure, editability, versioning, and selective loading. The calibration controls are equally important: no-skill and random-retrieval anchors show why strong LLM agents require careful baseline anchoring before success gains are attributed to memory content. Thus, the contribution is not merely a four-way format comparison; it is a controlled argument that representation form, retrieval, and budget must be evaluated jointly. The design lesson is to preserve one canonical experience record and materialize the view that matches the retrieval regime, distribution shift, context budget, and maintenance need. For future LLM agent memory work, the reporting norm should be explicit: state the source experience, externalized form, retriever, budgeted injection protocol, executor, and executor-only or random-retrieval anchors together. Doing so turns skill memory from a hidden prompt-formatting choice into an auditable, portable, and optimizable component of agent design.

Limitations

The study is intentionally controlled, and its remaining constraints are bounded rather than conceptual blockers.

Evidence provenance. The full ALFWorld form matrix is retained from restored March analysis outputs, while the May baseline and second-domain controls are backed by copied raw `episodes.jsonl` runs. Appendix Table 5 makes this provenance auditable, and a full raw rerun is an execution-scale extension rather than a change to the protocol.

Benchmark scope. The full form matrix is concentrated on ALFWorld, with WebShop used as a smaller text-mode calibration domain. The upgraded runner already supports both benchmarks, so expanding WebShop or adding another agentic benchmark is a direct extension of the same evaluation interface.

Converter and retrieval scope. Converters are deterministic and conditioned on matched canonical records, and the May serializer parity audit reduces form-specific construction confounds. Still, the ordering may shift under different converter families, retrievers, executors, or adaptive update policies; the current study should be read as form evaluation within a fixed conversion–retrieval pipeline.

Model and affordance scope. Token costs are deterministic estimates, and cross-model transfer remains future work, but run configurations already record endpoint identifiers, retrievers, source-bank IDs, and integrity fields. For artifact directories, the next natural step is to quantify editability and minimal-edit repair directly, complementing the success and progressive-loading evidence reported here.

References

AgentMemory. 2025. Huaman-agent-memory: A curated repository of agent memory resources. GitHub repository.

Anthropic. 2025. Agent skills: Filesystem-backed skill artifacts (documentation and specification). Online documentation/specification for SKILL.md-based skill directories.

Runnan Fang, Yuan Liang, Xiaobin Wang, Jialong Wu, Shuofei Qiao, Pengjun Xie, Fei Huang, Huajun Chen, and Ningyu Zhang. 2025. Memp: Exploring agent procedural memory. *Preprint*, arXiv:2508.06433.

Shangbin Feng, Weijia Shi, Yike Wang, Wenxuan Ding, Vidhisha Balachandran, Yiming Yang, Yejin Choi, Noah A. Smith, and Luke Zettlemoyer. 2024. Don't hallucinate, abstain: Identifying LLM knowledge gaps via multi-LLM collaboration. *Preprint*, arXiv:2402.00367.

Tao Feng, Lizhen Qu, Niket Tandon, and Gholamreza Haffari. 2025. IRIS: An iterative and integrated framework for verifiable causal discovery in the absence of tabular data. *Preprint*, arXiv:2510.09217.

Gen-Verse. 2026. Openclaw-rl: Train any agent simply by talking. GitHub repository.

Jiafeng Liang, Hao Li, Chang Li, Jiaqi Zhou, Shixin Jiang, Zekun Wang, Changkai Ji, Zhihao Zhu, Runxuan Liu, Tao Ren, Jinlan Fu, See-Kiong Ng, Xia Liang, Ming Liu, and Bing Qin. 2025. Ai meets brain: Memory systems from cognitive neuroscience to autonomous agents. *Preprint*, arXiv:2512.23343.

Jiaqi Liu, Yaofeng Su, Peng Xia, Siwei Han, Zeyu Zheng, Cihang Xie, Mingyu Ding, and Huaxiu Yao. 2026. Simplemem: Efficient lifelong memory for LLM agents. *Preprint*, arXiv:2601.02553.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. 2023. Memgpt: Towards LLMs as operating systems. *Preprint*, arXiv:2310.08560.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. *Preprint*, arXiv:2304.03442.

Bo Peng, Sirui Chen, Lei Xu, and Chaochao Lu. 2026. Causcientist: Teaching LLMs to respect data for causal discovery. *Preprint*, arXiv:2601.13614.

Xin Quan, Marco Valentino, Louise A. Dennis, and André Freitas. 2024. Verification and refinement of natural language explanations through LLM-symbolic theorem proving. *Preprint*, arXiv:2405.01379.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Preprint*, arXiv:2303.11366.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. 2020. ALFWorld: Aligning text and embodied environments for interactive learning. *Preprint*, arXiv:2010.03768.

Martin Tutek, Fateme Hashemi Chaleshtori, Ana Marasović, and Yonatan Belinkov. 2025. Measuring chain of thought faithfulness by unlearning reasoning steps. *Preprint*, arXiv:2502.14829.

Guangya Wan, Yunsheng Lu, Yuqi Wu, Mengxuan Hu, and Sheng Li. 2024. Large language models for causal discovery: Current landscape and future directions. *Preprint*, arXiv:2402.11068.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2023. Voyager: An open-ended embodied agent with large language models. *Preprint*, arXiv:2305.16291.

Cheng Yang, Xuemeng Yang, Licheng Wen, Daocheng Fu, Jianbiao Mei, Rong Wu, Pinlong Cai, Yufan Shen, Nianchen Deng, Botian Shi, Yu Qiao, and Haifeng Li. 2025. Learning on the job: An experience-driven self-evolving agent for long-horizon tasks. *Preprint*, arXiv:2510.08002.

Yutao Yang, Junsong Li, Qianjun Pan, Bihao Zhan, Yuxuan Cai, Lin Du, Jie Zhou, Kai Chen, Qin Chen, Xin Li, Bo Zhang, and Liang He. 2026. Autoskill: Experience-driven lifelong learning via skill self-evolution. *Preprint*, arXiv:2603.01145.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022. WebShop: Towards scalable real-world web interaction with grounded language agents. In *Advances in Neural Information Processing Systems*, volume 35.

Shicheng Ye, Chao Yu, Kaiqiang Ke, Chengdong Xu, and Yinqi Wei. 2025. H^2R: Hierarchical hindsight reflection for multi-task LLM agents. *Preprint*, arXiv:2509.12810.

Simon Yu, Gang Li, Weiyan Shi, and Peng Qi. 2025. Polyskill: Learning generalizable skills through polymorphic abstraction. *Preprint*, arXiv:2510.15863.

Haozhen Zhang, Quanyu Long, Jianzhu Bao, Tao Feng, Weizhi Zhang, Haodong Yue, and Wenya Wang. 2026. Memskill: Learning and evolving memory skills for self-evolving agents. *Preprint*, arXiv:2602.02474.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. 2023. Expel: LLM agents are experiential learners. *Preprint*, arXiv:2308.10144.

Boyuan Zheng, Michael Y. Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, and Yu Su. 2025. Skillweaver: Web agents can self-improve by discovering and honing skills. *Preprint*, arXiv:2504.07079.

Component	Default setting
Data	ALFWorld TextWorld; bank built from train; evaluation on `eval_id` (140) and `eval_ood` (134).
Bank size	100 source trajectories per form for the reported ALFWorld bank.
Canonical record	(q, f, r) with query q, extracted facts f, bounded trace r (first 50 steps; observations $\leq$200 chars), plus metadata.
Retriever	TF–IDF cosine over q with English stopwords and at most 50k features.
Budgets	Fixed-k (k=3) and fixed-tokens (B=700); max item length 900 tokens; last-item-only truncation with `[TRUNCATED]`.
Models	Fixed OpenAI-compatible endpoints for execution and conversion; exact endpoint identifiers are logged in each run configuration.
Executor	Temperature 0, fixed base prompt, and a 100-step environment cap.
Metrics	Success, steps, injected tokens (estimated), and 95% bootstrap CI with 1,000 resamples.

Table 4: **Default protocol settings.**

A Reproducibility and Protocol

This appendix records the evaluation protocol, reporting conventions, and reproduction recipe used for the ALFWorld experiments and calibration controls. Table 4 summarizes the default settings referenced throughout the paper. Appendix B lists converter templates and the artifact schema; Appendix E provides additional breakdown tables.

Data and splits. We use the TextWorld variant of ALFWorld (Shridhar et al., 2020). The skill bank is built from the training split. Evaluation uses `eval_id` ("valid_seen": 140 episodes) and `eval_ood` ("valid_unseen": 134 episodes).

Source record. Source trajectories are obtained by executing the provided walkthrough for each training instance, recording observation–action pairs. From each trajectory, we build a canonical record shared across forms: query q, extracted facts/constraints f, and a bounded raw trace r (first 50 steps; observations truncated to 200 characters), plus metadata (e.g., task type and step count).

Retriever. We use a lexical retriever: TF–IDF with English stopwords (max 50k features), ranking items by cosine similarity. To isolate form effects, all forms share the same retrieval key (q) and ranking; only the injected representation changes. The calibration runs additionally include embedding retrieval with `sentence-transformers/all-MiniLM-L6-v2`, deterministic random retrieval, and a no-skill setting with empty injection.

Budget regimes and truncation. We compare (i) fixed-k injection (k=3) and (ii) fixed injected-token budget (B=700) over the injected skill block. Each retrieved item is additionally capped (max item length 900 tokens) to prevent outliers. Under fixed-tokens, we concatenate items by rank until exceeding B; if the next item would exceed B, we truncate *only that last included item*, append `[TRUNCATED]`, and stop.

Token estimation. Token costs are computed by a deterministic estimator: when an OpenAI model name is provided, we use `tiktoken` encoding for that model; otherwise we fall back to a stable heuristic ($\approx$1.3$\times$ word count). All reported token numbers in the paper refer to this estimated count.

Executor and determinism. Execution uses temperature 0 and a fixed base prompt across all runs. We cap environment interaction to 100 steps per episode (timeouts terminate failures). We fix the random seed (42) for run ordering and bootstrapping. The ALFWorld L20 controls use a 30-step pilot cap and record API retry/error fields separately from environment termination fields.

Bootstrap confidence intervals. Success-rate CIs are 95% bootstrap intervals computed over episodes with 1,000 resamples.

Paired tests. For each split–budget block, we also report exact McNemar tests on paired binary outcomes from the same task instances. These tests are descriptive checks on whether the highest-mean form wins significantly more discordant episodes than each challenger.

Reproduction recipe. The pipeline uses four lightweight entry points:

- *run* for a single experimental setting;
- *analyze* for aggregate CSVs and plots;
- *make_tables.py* for LaTeX tables;
- *make_results_figures.py* for paper figures.

Typical usage is equally simple:

- run one setting by specifying the benchmark, split, skill form, and budget regime;
- aggregate logs from a results directory into summary CSVs and plots;

- regenerate paper tables and figures from the analysis directory.

Evidence ledger and claim boundary. Table 5 records the paper-facing source files and the permitted interpretation of each result block. This is part of the protocol: results backed only by restored analysis CSVs are not described as May raw-run reruns, and raw-backed calibration slices are not used to claim full benchmark generality.

AI assistance disclosure. AI assistants were used for limited writing and coding support. All substantive research design, experiment execution, result verification, claim boundaries, and final manuscript decisions were checked by the authors.

B Converter Constraints and Artifact Schema

Canonical experience record. All forms are generated from the same canonical record (q, f, r): the task query q, extracted facts/constraints f, and a bounded raw trace r. This record is stored in each bank item and is *shared* across forms; converters only change how the injected skill is serialized.

Form templates. For reproducibility, we fix form-level templates that front-load constraints and checks:

- **TRAJ(trace):** task, constraints, bounded execution trace, outcome, and key pitfalls.

- **SCRIPT(script):** 8–12 numbered steps, each one sentence; explicit checkpoints; ≤ 5 failure modes.

- **HIER(hierarchy):** goal, prereqs, 3–7 subgoals, and concise execution guidance; each subgoal includes intent, how, stop condition, and pitfalls.

- **ARTIFACT(artifact):** a filesystem-backed directory with SKILL.md and optional reference files such as steps.md.

Converter constraints. Both LLM-based converters consume the same (q, f, r) record and are run deterministically. The script converter is constrained to output: (i) a one-line task description, (ii) an 8–12 step SOP with one sentence per step, and (iii) at most five failure modes. The hierarchical converter is constrained to output: (i) a goal and prereqs/tools block, (ii) 3–7 subgoals, each with Intent, How, Stop condition, and Pitfalls,

and (iii) concise execution guidance. These constraints are what make the form comparison reproducible; the exact wording of prompts is not used as an independent variable.

Artifact directory layout. Each artifact skill is a directory with a stable SKILL.md entrypoint and optional references:

```
<skill_id>/
  SKILL.md
  references/
    steps.md    (optional)
```

SKILL.md schema. Artifact skills follow a directory format with an entry file SKILL.md that contains YAML frontmatter and a Markdown body. This schema is inspired by public skill-artifact practice, but it is an experimental extension used for controlled comparison rather than a claim of exact compatibility with any external standard. The frontmatter stores four kinds of information: identity and usage, I/O, constraints and tooling, and provenance. Concretely, the frontmatter follows the template below (types are illustrative):

```
---
name: <string>
description: <string>
when_to_use: <string>
inputs: [<string>, ...]
outputs: [<string>, ...]
constraints: [<string>, ...]
tools: [<string>, ...]
tags: [<string>, ...]
version: <string>
source_task_ids: [<id>, ...]
---
```

The body then presents four short sections: Overview, high-level steps, troubleshooting notes, and a references manifest for optional attached files.

Progressive loading variants. Given an artifact directory, we define three injection granularities: meta (frontmatter + file list), body (full SKILL.md), and full (SKILL.md plus references/steps.md if present).

C Related Work

Externalizing experience as memory or skills. Many agent-memory systems distill experience into reusable textual memories or skills without parameter updates (Zhao et al., 2023; Liu et al., 2026). Procedural memory work highlights that the *shape* of stored experience matters: trajectories preserve fidelity, while scripts/proceduralizations emphasize abstraction (Fang et al., 2025). Recent surveys separate memory along axes such as form, function, and dynamics, suggesting that representational choices should be evaluated explicitly (Liang et al., 2025).

Paper item	Source ID in handoff	Evidence level / scale	Paper use	Claim boundary
Table 1, Fig. 3	e1_full_h3 archive	Restored March analysis archive; 16 ALFWorld cells; 2,192 evaluated rows in aggregate CSVs.	Controlled ALFWorld form/budget comparison under query retrieval.	Analysis-archive backed in this handoff, not a May serializer-v2 raw rerun. Use for directional form/budget measurement, not for baseline-calibrated skill-gain claims.
Table 2	e1_full_h3 injection stats	Same restored ALFWorld E1 archive; estimated token and truncation fields.	Budget and truncation mechanism behind the form comparison.	Token counts are deterministic estimates; conclusions are about relative budget pressure, not exact tokenizer-independent costs.
Table 6 and Appendix breakdowns	e1_full_h3 paired and breakdown CSVs	Restored ALFWorld paired diagnostics and descriptive breakdowns.	Check whether block winners are robust and localize where differences arise.	No block winner is significant against all challengers at $p < 0.05$; bucket analyses are descriptive, not standalone significance claims.
Table 7	e4_artifact archive	Restored artifact ablation archive; 8 cells; 1,096 evaluated rows in aggregate CSVs.	Tests progressive artifact loading within the artifact family.	Supports an affordance claim about loading/editing structure; it does not prove artifact is the globally best form.
Table 8	e_top1 archive	Restored top-1 archive; 8 cells; 1,096 evaluated rows in aggregate CSVs.	Controls whether item count alone explains the main pattern.	Query-retrieval diagnostic only; not a replacement for a full baseline or embedding rerun.
Table 3	ALFWorld L20 + WebShop L50 raw runs	Raw-run backed May controls; ALFWorld: 4 runs / 80 episodes / 0 final errors. WebShop: 16 runs / 800 episodes / 0 final errors.	Calibrates query TF–IDF, embedding, no-skill, and random-retrieval anchors under serializer-v2.	Raw-backed but smaller and baseline-competitive. Do not claim universal skill improvement, random superiority, or full WebShop generality.
Serializer-v2 parity audit	May parity-audit CSV	Bank-level construction audit for ALFWorld and WebShop serializer-v2 banks.	Confirms shared facts/pitfalls accounting and token footprints for May controls.	Audits construction parity; it is not itself a task-success result.

Table 5: **Evidence ledger and claim boundary.** We separate restored March analysis archives from May raw-run-backed controls. The paper does not pool these evidence blocks: the ALFWorld matrix is used for controlled form/budget measurement, while the May controls test whether those measurements survive stronger baseline and retriever anchors. Exact package paths are listed in handoff_docs/PAPER_EVIDENCE_LEDGER.csv.

Hierarchy and structured procedural knowledge. Hierarchical memory and reflection separate planning-level knowledge from execution-level details (Ye et al., 2025; Yang et al., 2025). Our hierarchical form borrows this design cue, but our goal is different: we do not introduce a new memory-update algorithm; instead, we compare hierarchy to other forms under matched source experience and a fixed retrieval backbone.

Skills as code and as artifacts. Several systems store skills as executable code or API-like routines (Wang et al., 2023; Zheng et al., 2025). In parallel, practical skill banks increasingly use filesystem-backed artifacts with explicit metadata and optional resources, enabling portability and human editing (Anthropic, 2025; Yang et al., 2026). Our artifact form operationalizes this industrial representation within a controlled study. It can be viewed as an explicit separation of *what* to do from *how* to do it, echoing arguments for polymorphic abstraction in skill learning (Yu et al., 2025).

What we do not study. We focus on train-free comparisons and do not study training-heavy skill selection or self-evolution, which confound representation with learning dynamics (Zhang et al., 2026; Gen-Verse, 2026).

Long-term memory and improvement loops. Our work is complementary to systems that emphasize long-term interaction memory or self-improvement loops, including persistent simulated societies (Park et al., 2023), explicit memory controllers (Packer et al., 2023), and reflective improvement signals (Shinn et al., 2023). Our contribution is to isolate one axis of that design space: the representation form of reusable experience under a controlled, train-free comparison.

D Additional Related-Work Pointers

To preserve breadth outside the main page budget, we list a few additional pointers grouped by theme:

- **Reliability signals and knowledge gaps:** abstention and "unknown unknowns" (Feng et al., 2024; Tutek et al., 2025).

- **Faithfulness and refinement of explanations:** verification/refinement workflows (Quan et al.,

2024).

- **Verifiable reasoning and causal discovery (orthogonal to our agent setup):** Wan et al. (2024); Feng et al. (2025); Peng et al. (2026).

- **Community resource list:** curated pointers on agent memory (AgentMemory, 2025).

E   Additional Controls and Breakdowns

We provide paired significance tests, progressive-loading ablations, top-1 controls, and compact breakdowns for ALFWorld. Calibration controls are reported in Table 3.

Split	Budget	Winner	Challenger	Winner-only	Challenger-only	p
eval_id	fixed-k	HIER	ARTIFACT	17	12	0.458
		HIER	SCRIPT	15	12	0.701
		HIER	TRAJ	12	10	0.832
eval_id	fixed-tokens	TRAJ	ARTIFACT	17	8	0.108
		TRAJ	HIER	13	7	0.263
		TRAJ	SCRIPT	16	8	0.152
eval_ood	fixed-k	SCRIPT	ARTIFACT	9	6	0.607
		SCRIPT	HIER	12	7	0.359
		SCRIPT	TRAJ	11	6	0.332
eval_ood	fixed-tokens	SCRIPT	ARTIFACT	11	7	0.481
		SCRIPT	HIER	11	7	0.481
		SCRIPT	TRAJ	10	9	1.000

Table 6: **Paired exact McNemar tests against the highest-mean form in each ALFWorld block.** Winner-only and challenger-only count discordant episodes on the same task instances. Bold p-values indicate $p < 0.05$; in the current ALFWorld E1 results, no block winner reaches that threshold against all challengers.

Split	Budget	Metric	Meta	Body	Full
eval_id	fixed-k	Success	**77.1 [108/140]**	76.4 [107/140]	**77.1 [108/140]**
		Inj. toks.	596.0	1100.7	1358.3
	fixed-tokens	Success	74.3 [104/140]	**75.7 [106/140]**	**75.7 [106/140]**
		Inj. toks.	694.3	682.9	687.0
eval_ood	fixed-k	Success	**73.1 [98/134]**	72.4 [97/134]	**73.1 [98/134]**
		Inj. toks.	590.0	1094.6	1347.3
	fixed-tokens	Success	**75.4 [101/134]**	70.9 [95/134]	71.6 [96/134]
		Inj. toks.	693.9	682.9	686.8

Table 7: **Artifact progressive-loading ablation.** Within the directory-backed artifact family, we compare `meta` (frontmatter + manifest), `body` (the main `SKILL.md` view used in E1), and `full` (`SKILL.md` plus referenced files). Cells report success (%) with raw counts in brackets; boldface marks the highest mean success within each split×budget block.

Figure 3: **Cost–performance trade-offs.** Each point is a skill form; x is average injected tokens (estimated) and y is success (%). Error bars show 95% bootstrap CIs. Panels: (a) eval_id, fixed-k; (b) eval_id, fixed-tokens (B=700); (c) eval_ood, fixed-k; (d) eval_ood, fixed-tokens. Fixed-k reveals each form's natural context footprint; fixed-tokens enforces a strict injected-token budget (dotted line).

			(a) Top-1 control ($k=1$).			
Split	Metric	Traj	Script	Hier	Artifact	
eval_id	Success	65.0 [91/140]	**74.3 [104/140]**	73.6 [103/140]	72.1 [101/140]	
	Inj. toks.	316.9	246.9	510.0	367.2	
eval_ood	Success	63.4 [85/134]	68.7 [92/134]	**70.2 [94/134]**	**70.2 [94/134]**	
	Inj. toks.	306.2	253.7	503.4	365.7	

	(b) Similarity buckets.					
Split	Bucket	n	Traj	Script	Hier	Artifact
eval_id	low	46	**84.8**	71.7	80.4	69.6
	mid	45	**75.6**	73.3	**75.6**	73.3
	high	49	**85.7**	83.7	77.5	83.7
eval_ood	low	44	**72.7**	63.6	65.9	61.4
	mid	44	61.4	**72.7**	59.1	70.5
	high	46	84.8	84.8	**87.0**	80.4

	(c) Task-type breakdown.					
Split	Task type	n	Traj	Script	Hier	Artifact
eval_id	look_at_obj_in_light	13	76.9	76.9	76.9	**84.6**
	pick_and_place_simple	35	**88.6**	85.7	**88.6**	82.9
	pick_clean_then_place_in_recep	27	74.1	**77.8**	70.4	66.7
	pick_cool_then_place_in_recep	25	**80.0**	64.0	76.0	68.0
	pick_heat_then_place_in_recep	16	75.0	**81.2**	75.0	**81.2**
	pick_two_obj_and_place	24	**91.7**	70.8	75.0	75.0
eval_ood	look_at_obj_in_light	18	77.8	**83.3**	72.2	**83.3**
	pick_and_place_simple	24	70.8	**83.3**	75.0	75.0
	pick_clean_then_place_in_recep	31	**74.2**	**74.2**	71.0	71.0
	pick_cool_then_place_in_recep	21	**76.2**	**76.2**	71.4	71.4
	pick_heat_then_place_in_recep	23	60.9	60.9	**65.2**	60.9
	pick_two_obj_and_place	17	**82.3**	64.7	70.6	64.7

Table 8: **Top-1 control and additional ALFWorld breakdowns (fixed-tokens).** (a) The top-1 control injects only the single highest-ranked retrieved item, reducing the confound that shorter forms may fit more retrieved items under larger budgets. (b) Success rates (%) by top-1 retrieval similarity bucket (low/mid/high; thresholds computed per split: eval_id $q_1 = 0.623$, $q_2 = 0.771$; eval_ood $q_1 = 0.584$, $q_2 = 0.677$). (c) Success rates (%) by ALFWorld task family. Boldface marks the row-wise best form.