Proof Artifact Co-training for Theorem Proving with Language Models

Abstract

Labeled data for imitation learning of theorem proving in large libraries of formalized mathematics is scarce as such libraries require years of concentrated effort by human specialists to be built. This is particularly challenging when applying large Transformer language models to tactic prediction, because the scaling of performance with respect to model size is quickly disrupted in the data-scarce, easily-overfitted regime. We propose PACT (**P**roof **A**rtifact **C**o-**T**raining), a general methodology for extracting abundant self-supervised data from kernel-level proof terms for joint training alongside the usual tactic prediction objective. We apply this methodology to Lean, a proof assistant host to some of the most sophisticated formalized mathematics to date. We instrument Lean with a neural theorem prover driven by a Transformer language model and show that PACT improves theorem proving success rate on a held-out suite of test theorems from 32% to 48%.

1 Introduction

Deep learning-driven automated theorem proving in large libraries of formalized mathematics (henceforth "neural theorem proving") has been the focus of increased attention in recent years. Labeled data for imitation learning of theorem proving is scarce—formalization is notoriously labor-intensive, with an estimated cost of 2.5 man-years per megabyte of formalized mathematics (Wiedijk, 2000), and complex projects require years of labor from human specialists. Within a fixed corpus of (possibly unproven) theorem statements, it is possible to augment a seed dataset of human proofs with new successful trajectories using reinforcement learning or expert iteration. However, this is quite computationally intensive, and without a way to expand the curriculum of theorems, the agent will inevitably saturate and suffer from data starvation.

Data scarcity is a particularly thorny obstruction for applying large language models (LLMs) to neural theorem proving. LLMs have achieved spectacular success in data-rich regimes such as plain text (Brown et al., 2020), images (Dosovitskiy et al., 2020), and joint text-image modeling (Radford et al.), and the performance of decoder-only Transformers has been empirically shown to obey scaling power laws in model and data size (Henighan et al., 2020). However, existing datasets of human proof steps for neural theorem proving are extremely small and exist at scales at which overfitting occurs extremely rapidly, disrupting the scaling of performance with respect to model size (Kaplan et al., 2020).

We make two contributions towards addressing the problem of data scarcity in the context of formal mathematics. First, we introduce PACT (**P**roof **A**rtifact **C**o-**T**raining), a general methodology for extracting self-supervised auxiliary tasks for jointly training a language model alongside a tactic prediction objective for interactive theorem proving. Second, we present LeanStep, a collection of datasets and a machine learning environment for the Lean 3 theorem prover with support for PACT, supervised learning of tactic prediction, theorem proving evaluation, and reinforcement learning.

We train large language models on these data and demonstrate that PACT significantly improves theorem proving success rate on a held-out suite of test theorems, from 32% to 48%. We then embark on a careful study of the effects of pre-training vs. co-training and show that PACT combined with *WebMath* pre-training (Polu & Sutskever, 2020) achieves the best validation loss and theorem proving success rate. Finally, on an out-of-distribution collection of thousands of theorems (some involving novel definitions) added to Lean's mathematical library after we extracted our train/test data, we

achieve a theorem proving success rate of 37%, suggesting strong generalization and usefulness at the frontier of formalized mathematics.

2 BACKGROUND AND RELATED WORK

LEAN   Lean is an interactive theorem prover and functional programming language (de Moura et al., 2015). It has an extremely active community and is host to some of the most sophisticated formalized mathematics in the world, including scheme theory (Buzzard et al., 2019), forcing (Han & van Doorn, 2020), perfectoid spaces (Buzzard et al., 2020), and condensed mathematics (Scholze, 2020). Lean's foundational logic is a dependent type theory called the calculus of inductive constructions (Pfenning & Paulin-Mohring, 1989). This design means that terms, types and proofs are all represented with a single datatype called an *expression*. A *proof term* is a Lean expression whose type is a proposition, *i.e.* a theorem. This proof term serves as a checkable artifact for verifying the proposition. Lean uses a small, trusted kernel to verify proof terms. The primary repository of formalized mathematics in Lean is `mathlib` (mathlib, 2020). At the time of writing, 140 contributors have contributed almost 500,000 lines of code; `mathlib` contains over 46,000 formalized lemmas backed by over 21,000 definitions, covering topics such as algebraic geometry, computability, measure theory, category theory. The range of theories and the monolithic, unified organization of `mathlib` makes it an excellent foundation for a neural theorem proving dataset.

MACHINE LEARNING IN INTERACTIVE THEOREM PROVING   In a tactic-based interactive theorem prover (ITP) such as Lean, a proof is a list of tactics, *i.e.* small proof-term-generating programs. Tactics can be simple one-word commands, *e.g.* `refl`, or be composed of many nested parts, *e.g.*

```
simpa [le_antisymm_iff, norm_nonneg] using @norm_eq_zero α _ g
```

Here the brackets enclose a list of simplifier rules (which often are just lemmas from the library), and `@norm_eq_zero α _ g` is a proof term applying the lemma `norm_eq_zero` to the local variables α and `g`.

Other ML and neural theorem provers for tactic-based ITPs take one of two approaches to tactic generation. TacticToe (Gauthier et al., 2018) for HOL4 and Tactician (Blaauwbroek et al., 2020) for Coq use k-NN to select similar tactics in the training set and apply modifications to the result, *e.g.* swapping the tactic variables with those found in the local context. HOList/DeepHOL (Bansal et al., 2019b;a; Paliwal et al., 2020) for HOL Light; and CoqGym/ASTactic (Yang & Deng, 2019) and ProverBot9001 (Sanchez-Stern et al., 2020) for Coq hard code the DSL for every tactic command. The model chooses a tactic command, and then fills in the tactic arguments using specialized argument selectors (such as a lemma selector, a local hypothesis selector, and/or a variable selector). None of these selectors currently synthesis arbitrary terms. This prevents the tactic synthesis from constructing tactics with proof terms, such as `@norm_eq_zero α _ g`, or directly proving an existential, *e.g.* `∃ (x : ℝ), x + 3 = 0`, by supplying the witnessing term `-3`.

By directly applying Transformer-based language modeling to tactic generation, our prover `lean gptf` has a simple design. Instead of incorporating a separate premise selection (*i.e.* lemma selection) module we just co-train our language model on additional theorem data extracted from the `mathlib` library. In short, we replace engineered components with additional data. Our tactic generator is able to synthesis tactics of any form found in `mathlib` including, for example, the `@simpa` example above as a one line proof to a test theorem, even though the string `@norm_eq_zero` does not occur in our dataset. (See more examples in the appendix.) We leave as future work the possibility of re-integrating specialized components, *e.g.* lemma selection, found in other works (possibly as, say, a source of additional prompts for the language model).

Language models have also been explored in the first-order ITP Mizar for conjecturing and proof synthesis (Urban & Jakubuv, 2020). While their work shows the promise of such approaches, is not intended as a complete end-to-end theorem prover. For Metamath, which does not use tactics, language modeling approaches have been quite successful. Holophrasm (Whalen, 2016), MetaGen (Wang & Deng, 2020), and GPT-f (Polu & Sutskever, 2020) all use RNNs or Transformers to generate proof steps. Indeed, our paper builds on the work of Metamath GPT-f (Polu & Sutskever, 2020) (MM GPT-f). Whereas MM GPT-f trained primarily on the Metamath proof step objective (*i.e.* guessing the next lemma to be applied to a goal, which is similar to our NEXTLEMMA task

in Section 3.2), we co-train on a diverse suite of self-supervised tasks extracted from Lean proof terms and demonstrate significant improvements in theorem proving performance when doing so. This is our main result.

REASONING WITH TRANSFORMERS   Besides theorem proving, a number of recent papers have shown that language models, especially Transformers, are capable of something like mathematical and logical reasoning in integration (Lample & Charton, 2020), differential equations (Charton et al., 2020), Boolean satisfiability (Finkbeiner et al., 2020), and inferring missing proof steps (Li et al., 2021).

A closely-related vein of work has shown that pre-training Transformers on data engineered to reflect inductive biases conducive to mathematical reasoning is beneficial for downstream mathematical reasoning tasks (Rabe et al., 2020; Wu et al., 2021). Our work both builds on and departs from these ideas in several crucial aspects. Unlike skip-tree training (Rabe et al., 2020), which focuses solely on predicting masked subterms of theorem *statements*, PACT derives its self-supervised training data from far more complex *proofs*. Unlike LIME (Wu et al., 2021), which uses purely synthetic data and is presented as a pre-training methodology, our self-supervised tasks are extracted from non-synthetic human proofs. Moreover, we show that not only are Transformers capable of performing well on auxiliary tasks gathered from low-level proof artifact data, but that we can directly leverage this data via co-training to greatly improve performance on high-level theorem proving.

MACHINE LEARNING WITH PROOF ARTIFACTS   The idea of mining low-level proof artifacts was previously explored by Kaliszyk and Urban in the context of automated lemma extraction (Kaliszyk & Urban, 2015b; Kaliszyk et al., 2015). It has also been previous observed that training on fully elaborated Coq terms (Nie et al., 2020) helps with a downstream theorem naming task. However, similar to previous work on skip-tree training, their dataset focuses solely on theorem statements, *i.e.* types, does not cover the far more complex proof terms, and does not evaluate the effect of such training on theorem proving evaluations.

While there exist environments and datasets for other formal mathematics libraries (Kaliszyk et al., 2017; Li et al., 2021; Huang et al., 2018; Kaliszyk & Urban, 2015a), LEANSTEP is the first and only tactic proof dataset for the Lean theorem prover. This makes available a large set of formal mathematical data to researchers covering a diverse and deep spectrum of pure mathematics. Moreover, LEANSTEP is unique in that it contains both high-level human-written tactics as well as kernel-level proof terms, which enables the extraction of self-supervised tasks for PACT (Section 3.2).

3   THE LEANSTEP DATASETS AND MACHINE LEARNING ENVIRONMENT

3.1   HUMAN TACTIC PROOF STEPS

Tactics in Lean are metaprograms (Ebner et al., 2017), which can construct Lean expressions, such as proof terms. A *tactic state* which tracks the partial proof term constructed so far, the list of open goals, and other metadata is threaded through each tactic invocation. Lean has special support for treating tactics as an extensible domain-specific language (DSL); this DSL is how Lean is typically used as an interactive theorem prover. The DSL amounts to a linear chain of comma-separated invocations. The Lean *proof step* task is to predict the next tactic given this goal state.

Our human tactic proof step dataset consists of source-target pairs of strings, one for each tactic invocation in the Lean core library and in `mathlib`. The source string is the pretty-printed tactic state. The target string is the tactic invocation as entered by a human author of the source code. This data is gathered by hooking into the Lean parser and Lean's compilation process. We refer to the task of predicting the next human tactic proof step given a tactic state as the *proofstep objective*.

3.2   PROOF ARTIFACT CO-TRAINING

In this section, we describe the PACT task suite and how data for these tasks are extracted.

For every proof term τ, we record the type Γ of τ, its name `nm`, and a list `ps` of all premises (*i.e.* named references to other lemmas in the library) which are used in τ. We then recurse through τ, tracking a list `bs` of bound variables which we update whenever navigating into the body of a

λ-expression. At every sub-term $\tau' \subseteq \tau$ we record τ', its type Γ', the current state of `bs`, and the following data:

1. A *tactic state*, where the goal is set to be Γ' and the list of hypotheses in the local context is set to be the list `bs`, *i.e.* those bound variables in scope at τ'.

2. A *partial proof term*, *i.e.* τ with τ' masked out.

3. A *premise selection bitmask*, *i.e.* Boolean labels for every `p` in `ps` indicating whether `p` is used in τ'.

4. A *local context bitmask*, *i.e.* similar Boolean labels for every `b` in `bs` indicating whether `b` is used in τ'.

5. An optional *next lemma*: if the first step of τ' is to apply a premise `p` in `ps`, we record `p`.

Whenever we record a term, we record both *pretty-printed* and far more explicit *fully elaborated* versions of it. The fully elaborated terms explicitly display enormous amounts of type information which are usually silently inferred by Lean. From these data, we assemble the following language modeling tasks:

1. **Next lemma prediction.** Given the tactic state, predict the next lemma to be applied.

2. **Proof term prediction.** Given the tactic state, predict the entire proof term τ'.

3. **Skip-proof.** Given the partial proof term, predict the masked-out subterm τ'.

4. **Type prediction.** Given the partial proof term, predict the type Γ' of the masked-out subterm τ'.

5. **Tactic state elaboration.** Given the tactic state, predict the fully elaborated tactic state.

6. **Proof term elaboration.** Given τ, predict the fully elaborated version of τ.

7. **Premise classification.** Given the tactic state and a premise $p \in ps$, predict either `<TRUE>` or `<FALSE>` according to the premise selection bitmask.

8. **Local context classification.** Given the tactic state (which consists of a list of local assumptions `bs` and the goal Γ'), predict the sublist of `bs` which is true on the local context bitmask.

9. **Theorem naming.** Given the type Γ of the top-level proof term τ, predict the name `nm`.

We remark that our next lemma prediction task is precisely the low-level `PROOFSTEP` objective studied in (Polu & Sutskever, 2020), and our skip-proof task superficially resembles, but is much more difficult than the skip-tree task studied in (Rabe et al., 2020), as proof terms tend to be far more complex than the syntax trees of theorem statements.

3.3 THE LEANSTEP MACHINE LEARNING ENVIRONMENT

We instrument Lean for automatic theorem proving with a language model, including utilities for (1) setting the runtime environment at a particular theorem (ensuring proofs are never circular), (2) serializing the tactic state as environment observations for a theorem-proving agent, (3) exposing Lean's parser to re-parse strings emitted by a language model into tactic invocations, and (4) executing and capturing the results of the re-parsed tactics, enabling the recording of trajectories for expert iteration and reinforcement learning.

In addition to this general instrumentation, we implement a generic best-first search algorithm for theorem proving; it forms the basis for our evaluations and is written entirely in Lean itself. The algorithm is parametrized by an oracle (Ω : `tactic_state` $\rightarrow$ `list (string × float)`) that accepts a tactic state and returns a list of strings and heuristic scores. The search is controlled by a priority queue of *search nodes*, which consist of a tactic state (*i.e.* a partial proof) and search metadata. In the outer loop of the algorithm—which continues until either the theorem is completely proved (*i.e.* no goals are remaining on the current node), the priority queue is empty (*i.e.* the search has failed), or a pre-set timeout or budget of iterations is exceeded—we pop a node off the queue, serialize the associated tactic state and use it query the oracle, producing a list of candidates `cs` : `list (string × float)`. We then loop over the candidates `cs` to produce a list of new

search nodes, by re-parsing each string into a tactic and adding a new node if the parsed tactic advances the proof without raising errors. These new search nodes are then re-inserted into the queue in order of decreasing priority and the search continues. We optionally constrain the search by enforcing maximum width and depth limits w_{max} and d_{max} that guard insertion into the queue. When considering nodes for insertion, any node whose depth exceeds d_{max} is ignored, and all nodes are ignored if the queue size is strictly larger than w_{max}. Due to the flexibility in assigning heuristic scores and in choosing the maximum width and depth hyperparameters, our algorithm is quite general—for example, it reduces to (1) a greedy depth-first search when $w_{max} = 0$, and (2) a naïve breadth-first search when heuristic scores are identical and $w_{max} = d_{max} = \infty$.

4 EXPERIMENTS

TRAINING   In all of our experiments, we use decoder-only Transformers similar to GPT-3 (Brown et al., 2020). Unless mentioned otherwise, all of our models have 24 layers with $d_{model} = 1536$ and 24 heads, accruing to 837M trainable parameters. They are also pre-trained on `WebMath` (Polu & Sutskever, 2020) for 72B tokens. We use the standard `BPE` encoding (Brown et al., 2020), a batch size of 512 and a learning rate of 0.00025 with a cosine schedule and a 100-step ramp-up.

We use an 80-5-15 train-validation-test split. We split all datapoints deterministically by *theorem name*, by hashing each name to a float in $(0, 1)$. This ensures, for example, that proof steps used to prove a test theorem never appear in the training data and vice-versa.

When fine-tuning a model we load its saved parameters but re-initialize the optimizer. We start each training for a fixed number of tokens (defining the cosine schedule) and record the number of tokens consumed as we reach a minimal validation loss. We use the minimum validation loss snapshot to evaluate each model on our held-out test set.

We partition our datasets into three groups:

1. `tactic`: the dataset described in Section 3.1.
2. `mix1`: the union of the PACT tasks **next lemma prediction** and **proof term prediction** (Section 3.2), selected because of their close relation to `tactic`.
3. `mix2`: all other datasets described in Section 3.2.

This grouping is motivated by the impossibility to ablate each dataset separately given our compute budget. They nonetheless enable us to study the effect of tasks that are very close to the `tactic` objective in comparison to others. Our choice of **next lemma prediction** and **proof term prediction** for `mix1` is motivated by the observation that these tasks are closely related to the theorem proving objective: a proof can be given entirely in terms of a sequence of lemmas to apply (as in Metamath), or the proof can be finished in one step by supplying the entire proof term. Despite their logical similarity to the `PROOFSTEP` objective, we nevertheless use different keywords in the prompt to the model to disambiguate (`NEXTLEMMA` and `PROOFTERM`) from (`PROOFSTEP`) because the data is noisy and represents a significant distribution shift: during pretty-printing, subtrees of proof terms beyond a certain depth are dropped entirely, there is generally no guarantee that they can be re-parsed, and the data is much more verbose than what humans typically supply in source code.

THEOREM PROVING EVALUATION   We run theorem-proving evaluations on our held-out `test` set, comprising 3071 theorems. Since the split was conducted by theorem name, the proofs of these theorems never appear in the training data. For each theorem in the test set, we set the runtime environment to the location where the theorem is proved in the source code, preventing the use of theorems defined later in `mathlib` and ensuring that we never derive circular proofs. We run the proof search algorithm using either the `tidy` or the `gptf` backend. In all of our experiments, we use a maximum width of $w_{max} = 16$, a maximum depth of $d_{max} = 128$, a maximum budget of 512 iterations of the outer loop, a timeout of 5 seconds per tactic execution, and a global timeout of 600 seconds per theorem. Because sampling completions from our models is much slower (≈ 1 second) than querying the constant `baseline` oracle (instantaneous), the `baseline` proof search runs through many more rounds of proof search than `gptf` before timeout.

We report the pass-rate (*i.e.* percentage of theorems proved) from the randomly-chosen held-out test set, following (Whalen, 2016), (Bansal et al., 2019c), and others. We provide an alternative pass-rate

`tactic`	
tactic proof steps	`GOAL <TacticState> PROOFSTEP <Tactic>`
`mix1`	
next lemma prediction	`GOAL <TacticState> NEXTLEMMA apply (<NextLemma>)`
proof term prediction	`GOAL <TacticState> PROOFTERM exact (<ProofTerm>)`
`mix2`	
skip proof	`RESULT <MaskedProofTerm> SKIPPROOF <ProofTerm>`
type prediction	`RESULT <MaskedProofTerm> PREDICTTYPE <Type>`
tactic state elaboration	`GOAL <TacticState> ELABGOAL <ElaboratedTacticState>`
proof term elaboration	`PROOFTERM <ProofTerm> ELABPROOFTERM <ElaboratedProofTerm>`
premise classification	`GOAL <TacticState> CLASSIFYPREMISE <Premise> <True|False>`
local context classification	`GOAL <TacticState> CLASSIFYLOCALS <LocalsList>`
theorem naming	`TYPE <Type> NAME <Name>`

Figure 1: Auto-regressive objectives used for each task described in Section 3. Placeholders represented with brackets (such as `<TacticState>`) are substituted by the context-completion pairs from each datasets in the prompts above. Each task is presented to the model with its respective keyword (`PROOFSTEP`, `NEXTLEMMA`,...). We wrap the completions of `mix1` tasks (with `apply(...)` and `exact(...)` respectively) as a hint that they are related to the respective Lean tactics; this is not directly possible for the other tasks.

at the end of this section, using theorems added to `mathlib` after our dataset was collected. We average over three evaluation runs when reporting the pass rate.

EFFECT OF CO-TRAINING VS PRE-TRAINING   We first study the effects of pre-training versus co-training with the `mix1` and `mix2` datasets. We pre-train using the methodology described above (potentially pre-training first on `WebMath`, and then on a PACT dataset in sequence). For co-training, we simply concatenate and shuffle the datasets together without applying any particular weight to a given dataset.

The main results are presented in Figure 2. Pre-training exhibits an effective transfer from `mix-1` and/or `mix-2` but the best result is achieved by co-training with both these datasets. With this setup, we are able to train for much longer (71B tokens vs 22B+18B for the best pre-training setup) before overfitting on the `PROOFSTEP` task. We hypothesize that PACT regularizes overfitting to the `PROOFSTEP` task while still imparting useful knowledge to the model due to large amounts of mutual information, and that this is the main driver of increased performance.

ABLATING WEBMATH PRE-TRAINING   Next, we ablate the effect of `WebMath` pre-training. As expected, co-trained models suffer from a performance drop without `Webmath` pretraining. but we were more interested in measuring the effect on pre-trained models on `mix-1` and `mix-2`, as they may not benefit from `WebMath` as much due to the two successive pre-training steps.

We report the optimal validation losses in Figure 3. `WebMath` appears as substantially beneficial even in the sequential pre-training setup. This indicates that PACT is not a replacement for `WebMath` pre-training, but rather a complementary method for enhancing the performance of language models for theorem proving.

ABLATING REGULARIZATION   We rule out the possibility that the benefits from PACT come from simply regularizing our models on the scarce `tactic` data alone. We checked that a `WebMath > tactic` model trained with 15% residual dropout achieved a minimum validation loss of 1.01 and 33.6% pass rate, far below the 48.4% PACT pass rate.

EFFECT OF MODEL SIZE   Finally, we study how performance scales with respect to model size. We use the best training setup reported in Figure 2, `WebMath > mix1 + mix2 + tactic`. The `837m` model is our main model. The `163m` and `121m` models respectively have 12 and 6 layers, with $d_{\text{model}} = 768$. The learning rates are respectively adjusted to 0.0014 and 0.0016.

Model	Tokens elapsed	mix1	mix2	tactic	Pass-rate
Baselines					
refl					1.1%
tidy-bfs					9.9%
WebMath > tactic	1B			1.02	32.2%
Pre-training					
WebMath > mix1	11B	*0.08*			
WebMath > mix2	16B		*0.08*		
WebMath > mix1 + mix2	22B	*0.11*	*0.08*		
WebMath > mix1 > tactic	1B			1.00	39.8%
WebMath > mix1 + mix2 > tactic	1B			0.97	44.0%
Co-training (PACT)					
WebMath > mix1 + tactic	18B	*0.08*		0.94	40.0%
WebMath > mix2 + tactic	75B		*0.09*	0.93	46.0%
WebMath > mix1 + mix2 + tactic	71B	*0.09*	*0.09*	**0.91**	**48.4**%
Pre-training and co-training					
WebMath > mix2 > mix1 + tactic	18B	*0.08*		0.93	46.9%

Figure 2: Comparison of pre-training and co-training on mix-1 and mix-2. > denotes a pre-training step and + denotes a co-training. As an example, WebMath > mix2 > mix1 + tactic signifies a model successively pre-trained on WebMath then mix2 and finally co-trained as a fine-tuning step on mix1 and tactic. Columns mix1, mix2, tactic report the optimal validation loss achieved on these respective datasets. We provide a detailed description of experiment runtime and computing infrastructure in the appendix.

Model	Tokens budget	Tokens elapsed	mix1	mix2	tactic
Baselines					
tactic	32B	1B			1.59
Pre-training					
mix1	32B	20B	*0.12*		
mix2	32B	25B		*0.10*	
mix1 + mix2	32B	27B	*0.13*	*0.10*	
mix1 > tactic	32B	1B			1.26
mix1 + mix2 > tactic	32B	1B			1.16
Co-training					
mix1 + tactic	32B	27B	*0.11*		1.12
mix2 + tactic	96B	75B		*0.10*	1.02
mix1 + mix2 + tactic	96B	71B	*0.10*	*0.11*	**1.07**
Pre-training and co-training					
mix2 > mix1 + tactic	32B	26B	*0.11*		1.09

Figure 3: Validation losses achieved in the pre-training and co-training setups without WebMath pre-training. See Figure 2 for a description of the columns and the models nomenclature used.

Model	Tokens budget	Tokens elapsed	`mix1`	`mix2`	`tactic`	Pass-rate
`121m`	96B	82B	*0.13*	*0.10*	1.23	35.1%
`163m`	96B	80B	*0.12*	*0.09*	1.11	39.8%
`837m`	96B	71B	*0.09*	*0.09*	**0.91**	**48.4%**

Figure 4: Validation losses and pass-rates achieved for various model sizes using PACT. See Figure 2 for a description of the columns. The setup used is `WebMath > mix1 + mix2 + tactic`.

As demonstrated by Figure 4, performance is highly correlated with model size, with larger models generally achieving better generalization even in the overfitted regime. We leave as future work a careful study of how evaluation performance is affected when scaling to multi-billion parameter models, as well as the feasibility of deploying them for interactive use by Lean users.

TIME-STRATIFIED EVALUATION   In the 5 week period that separated our last dataset extraction and the writing of this paper, `mathlib` grew by 30K lines of code, adding 2807 new theorems. Evaluating our models on these new theorem statements gives a unique way to assess their capability to assist humans in formalizing proofs and to test their generalization to completely unseen theorems and definitions. This evaluation set also addresses one of the weaknesses of using a random split of theorems from a formal mathematics library, namely that the split is non-chronological; *e.g.* test theorems can appear as lemmas in proofs of train theorems.

We call this temporally held-out test set `future-mathlib` and evaluate our best model as well as the `refl` and `tidy-bfs` baselines on it. In contrast to evaluation on our `test` split, the `refl` baseline (simply attempting a proof by the `refl` tactic) closes 328 proofs (11.6%), demonstrating an important skew towards trivial boilerplate lemmas generally defined to provide alternate interfaces to new definitions. The `tidy-bfs` baseline closed 611 proofs (21.8%), and our best model `wm-tt-m1-m2` closed 1043 proofs (37.1%), proving 94% of the `refl` lemmas. We attribute the weaker performance to heavy distribution shift: by the nature of the dataset, the `future-mathlib` theorems frequently involve new definitions and concepts which the model was never exposed to during training. Nevertheless, the success rate remains high enough to suggest strong generalization and usefulness at the frontier of formalized mathematics.

5 DISCUSSION

CHAINED TACTIC PREDICTIONS   In Lean, multiple tactic commands can be chained together using semicolons. Our data pipeline treats these tactic chains as a single sequence in our training data, and they are occasionally predicted by the model. Such chained tactic applications are difficult for human formalizers to synthesize on their own, as they require reasoning about the semantics of multiple tactics in sequence and their effects on the tactic state, and the examples present in the training data are usually optimized by hand from longer, less succinct proofs. We observed that PACT significantly boosts the capability of our models to *successfully* predict longer chained tactic applications. This occurs despite the fact that tactic chaining specific to the tactic proofstep dataset and does not appear in the PACT data whatsoever. We supply more detail in the appendix.

THEOREM NAMING   We also evaluate our best PACT model (`wm-to-tt-m1-m2`) on the theorem naming task, using the theorem statements and human-supplied names from the `future-mathlib` evaluation set. It achieved 20% acc@1, 27% acc@10, and 30% acc@16. An inspection of its outputs reveals that even when its predictions diverge from the ground truth, they are often idiomatic and semantically correct alternatives. We supply more detail in the appendix.

IMPACT ON LEAN COMMUNITY   Lean's `mathlib` (mathlib, 2020) is a rapidly growing open source library of formal mathematics which has grown considerably in size each year for the past four years.[1] Our work has been welcomed by members of this community, with Lean power users

---

[1]See `https://leanprover-community.github.io/mathlib_stats.html` for up-to-date statistics on `mathlib`'s size and growth over time.

describing some of the new proofs found by GPT-f as "nontrivial" and "clever". More than one-third of the proofs found by our models are shorter and produce smaller proof terms (sometimes by several orders of magnitude) than the ground truth. Manually inspecting a small, non-cherry picked sample of these shorter proofs has led to 19 GPT-f co-authored commits to `mathlib`, some of which reduce proof term sizes and theorem compilation times by an order of magnitude. We supply more detail in the appendix.

POTENTIAL SOCIETAL IMPACT   Strong automated reasoning systems have enormous potential impact for mathematical research and scientific progress in other disciplines. The methods that we discuss in this paper could accelerate the development of strong automated reasoning systems. We have also observed that our language models absorb stylistic biases from their training data which could be amplified via reinforcement learning. However, since we focus on mathematics codified in proof assistants, we believe that there is little immediate negative societal impact from our work.

FUTURE DIRECTIONS   There are many elaborations on the training data, training methodology, and tree search wrapping `lean-gptf` which can be reasonably expected to improve its performance at theorem proving. Our dataset can be synthetically augmented using similar methods as (Polu & Sutskever, 2020). Our dataset could be cleaned further, and proofs minimized. Merely making the decoded rewrites robust by only using the largest prefix of successful rewrites significantly boosts the success rate of suggested rewrites. In a similar vein, predicted lemmas generated as arguments to unsuccessful tactic applications could be cached and re-used as hints for an intermittently-queried hammer. The increased success rate of chained tactic predictions mentioned above shows the feasibility of having language models perform multiple reasoning steps in a single query, potentially improving the efficiency of the proof search. From the experiments described in Section 4, it is clear that the composition of the dataset used for co-training significantly affects performance on theorem proving. Although we uniformly sampled across all co-training tasks, it would be interesting to optimize a dynamic mixture schedule, perhaps annealing towards a desired task.

CONCLUSION   There is a sense in which PACT is merely an application of the well known principle that compute in the form of search should be exchanged for training signal whenever possible. In Lean, typeclass inference relies on a backtracking Prolog-style search; the elaborator performs search to disambiguate overloaded notation and infer types; Lean tactics have complex semantics precisely because they can perform search to find subproofs automatically. The work done by these subroutines is preserved in the proof artifacts, and PACT can be viewed as a way of extracting this information offline for more training signal.

We have presented PACT as a way of addressing the data scarcity issue for learning theorem proving from human tactic scripts in proof assistant libraries. Another well-studied solution for this is expert iteration and reinforcement learning. In the setting of HOL Light, and under the assumption of a hardcoded finite action space of tactics, DeepHOLZero in conjunction with supervised seed data was able to achieve up to 70% proof success rate on the HOList theorem proving task. Similarly, in a set-up much closer to ours, MM GPT-f demonstrated the feasibility of expert iteration when using generative language models for theorem proving.

Within a fixed corpus of theorems (and hence proof terms), however, both PACT and RL are fundamentally constrained by a lack of exploration—as the performance of the theorem proving agent improves, it will eventually saturate and become starved for data, and its curriculum will need to be expanded. Although self-supervised methods such as PACT represent a way to significantly improve the data-efficiency of reinforcement learning loops over existing theorem prover libraries, the development of continuously self-improving and infinitely scalable neural theorem provers remains contingent on sufficiently powerful exploration and automated curriculum generation; we consider these challenges to be of paramount importance.

6   REPRODUCIBILITY STATEMENT

The source code used to generate the Lean datasets and run the evaluation is open source and made available in the following repositories:

Lean theorem proving environment :
```
<anonymized>
```

Tactic step data pipeline :
```
<anonymized>
```

PACT data pipeline :
```
<anonymized>
```

Our Transformer model was pre-trained on two proprietary datasets. The first is the same mix used by GPT-3 (Brown et al., 2020) and the second is `WebMath` (Polu & Sutskever, 2020). More details can be found in the appendix.

While our weights and the API through which we query our models are not currently public, techniques for training decoder-only transformers and efficiently performing inference with them are well-known. Our released theorem proving code is agnostic to these implementation details and will work with any language model exposed via an HTTP server. The provided code also supports querying a locally hosted transformer from the open-source library `fairseq` via the Fairseq CLI (Ott et al., 2019).

We have released a simplified version of the proof search described in Section 3.3 as a tactic to the Lean community in a public beta, opening the way for our models to directly accelerate the development of formalized mathematics and for human experts to provide feedback and additional training signal in a virtuous cycle. The tactic and code are available at `<anonymized>`, and users who sign up for the beta are granted access to our Transformer model through an API.

REFERENCES

Kshitij Bansal, Sarah M. Loos, Markus N. Rabe, and Christian Szegedy. Learning to reason in large theories without imitation. *CoRR*, abs/1905.10501, 2019a. URL http://arxiv.org/abs/1905.10501.

Kshitij Bansal, Sarah M. Loos, Markus N. Rabe, Christian Szegedy, and Stewart Wilcox. Holist: An environment for machine learning of higher order logic theorem proving. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 454–463. PMLR, 2019b. URL http://proceedings.mlr.press/v97/bansal19a.html.

Kshitij Bansal, Sarah M Loos, Markus N Rabe, Christian Szegedy, and Stewart Wilcox. HOList: An environment for machine learning of higher-order theorem proving (extended version). *arXiv preprint arXiv:1904.03241*, 2019c.

Lasse Blaauwbroek, Josef Urban, and Herman Geuvers. The tactician - A seamless, interactive tactic learner and prover for coq. In Christoph Benzmüller and Bruce R. Miller (eds.), *Intelligent Computer Mathematics - 13th International Conference, CICM 2020, Bertinoro, Italy, July 26-31, 2020, Proceedings*, volume 12236 of *Lecture Notes in Computer Science*, pp. 271–277. Springer, 2020. doi: 10.1007/978-3-030-53518-6_17. URL https://doi.org/10.1007/978-3-030-53518-6_17.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Kevin Buzzard, Chris Hughes, Kenny Lau, Amelia Livingston, Ramon Fernández Mir, and Scott Morrison. Schemes in lean. *arXiv preprint arXiv:2101.02602*, 2019.

Kevin Buzzard, Johan Commelin, and Patrick Massot. Formalising perfectoid spaces. In Jasmin Blanchette and Catalin Hritcu (eds.), *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs, CPP 2020, New Orleans, LA, USA, January 20-21, 2020*, pp. 299–312. ACM, 2020. doi: 10.1145/3372885.3373830. URL https://doi.org/10.1145/3372885.3373830.

François Charton, Amaury Hayat, and Guillaume Lample. Deep differential system stability - learning advanced computations from examples. *CoRR*, abs/2006.06462, 2020. URL https://arxiv.org/abs/2006.06462.

Leonardo Mendonça de Moura, Soonho Kong, Jeremy Avigad, Floris van Doorn, and Jakob von Raumer. The lean theorem prover (system description). In Amy P. Felty and Aart Middeldorp (eds.), *Automated Deduction - CADE-25 - 25th International Conference on Automated Deduction, Berlin, Germany, August 1-7, 2015, Proceedings*, volume 9195 of *Lecture Notes in Computer Science*, pp. 378–388. Springer, 2015. doi: 10.1007/978-3-319-21401-6_26. URL https://doi.org/10.1007/978-3-319-21401-6_26.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *CoRR*, abs/2010.11929, 2020. URL https://arxiv.org/abs/2010.11929.

Gabriel Ebner, Sebastian Ullrich, Jared Roesch, Jeremy Avigad, and Leonardo de Moura. A metaprogramming framework for formal verification. *Proc. ACM Program. Lang.*, 1(ICFP):34:1–34:29, 2017. doi: 10.1145/3110278. URL https://doi.org/10.1145/3110278.

Bernd Finkbeiner, Christopher Hahn, Markus N. Rabe, and Frederik Schmitt. Teaching temporal logics to neural networks. *CoRR*, abs/2003.04218, 2020. URL https://arxiv.org/abs/2003.04218.

M. Ganesalingam and W. T. Gowers. A fully automatic theorem prover with human-style output. *J. Autom. Reason.*, 58(2):253–291, 2017. doi: 10.1007/s10817-016-9377-1. URL https://doi.org/10.1007/s10817-016-9377-1.

Thibault Gauthier, Cezary Kaliszyk, Josef Urban, Ramana Kumar, and Michael Norrish. Learning to prove with tactics. *CoRR*, abs/1804.00596, 2018. URL http://arxiv.org/abs/1804.00596.

Jesse Michael Han and Floris van Doorn. A formal proof of the independence of the continuum hypothesis. In Jasmin Blanchette and Catalin Hritcu (eds.), *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs, CPP 2020, New Orleans, LA, USA, January 20-21, 2020*, pp. 353–366. ACM, 2020. doi: 10.1145/3372885.3373826. URL https://doi.org/10.1145/3372885.3373826.

Tom Henighan, Jared Kaplan, Mor Katz, Mark Chen, Christopher Hesse, Jacob Jackson, Heewoo Jun, Tom B. Brown, Prafulla Dhariwal, Scott Gray, Chris Hallacy, Benjamin Mann, Alec Radford, Aditya Ramesh, Nick Ryder, Daniel M. Ziegler, John Schulman, Dario Amodei, and Sam McCandlish. Scaling laws for autoregressive generative modeling. *CoRR*, abs/2010.14701, 2020. URL https://arxiv.org/abs/2010.14701.

Daniel Huang, Prafulla Dhariwal, Dawn Song, and Ilya Sutskever. Gamepad: A learning environment for theorem proving. *CoRR*, abs/1806.00608, 2018. URL http://arxiv.org/abs/1806.00608.

Cezary Kaliszyk and Josef Urban. Mizar 40 for mizar 40. *J. Autom. Reason.*, 55(3):245–256, 2015a. doi: 10.1007/s10817-015-9330-8. URL https://doi.org/10.1007/s10817-015-9330-8.

Cezary Kaliszyk and Josef Urban. Learning-assisted theorem proving with millions of lemmas. *J. Symb. Comput.*, 69:109–128, 2015b. doi: 10.1016/j.jsc.2014.09.032. URL https://doi.org/10.1016/j.jsc.2014.09.032.

Cezary Kaliszyk, Josef Urban, and Jirí Vyskocil. Lemmatization for stronger reasoning in large theories. In Carsten Lutz and Silvio Ranise (eds.), *Frontiers of Combining Systems - 10th International Symposium, FroCoS 2015, Wroclaw, Poland, September 21-24, 2015. Proceedings*, volume 9322 of *Lecture Notes in Computer Science*, pp. 341–356. Springer, 2015. doi: 10.1007/ 978-3-319-24246-0_21. URL https://doi.org/10.1007/978-3-319-24246-0_ 21.

Cezary Kaliszyk, François Chollet, and Christian Szegedy. Holstep: A machine learning dataset for higher-order logic theorem proving. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=ryuxYmvel.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *CoRR*, abs/2001.08361, 2020. URL https://arxiv.org/abs/2001.08361.

Guillaume Lample and François Charton. Deep learning for symbolic mathematics. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id= S1eZYeHFDS.

Wenda Li, Lei Yu, Yuhuai Wu, and Lawrence C. Paulson. Isarstep: a benchmark for high-level mathematical reasoning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=Pzj6fzU6wkj.

mathlib. The lean mathematical library. In Jasmin Blanchette and Catalin Hritcu (eds.), *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs, CPP 2020, New Orleans, LA, USA, January 20-21, 2020*, pp. 367–381. ACM, 2020. doi: 10.1145/3372885. 3373824. URL https://doi.org/10.1145/3372885.3373824.

Pengyu Nie, Karl Palmskog, Junyi Jessy Li, and Milos Gligoric. Deep generation of coq lemma names using elaborated terms. In Nicolas Peltier and Viorica Sofronie-Stokkermans (eds.), *Automated Reasoning - 10th International Joint Conference, IJCAR 2020, Paris, France, July 1-4, 2020, Proceedings, Part II*, volume 12167 of *Lecture Notes in Computer Science*, pp. 97–118. Springer, 2020. doi: 10.1007/978-3-030-51054-1_6. URL https://doi.org/10.1007/ 978-3-030-51054-1_6.

Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. In Waleed Ammar, Annie Louis, and Nasrin Mostafazadeh (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Demonstrations*, pp. 48–53. Association for Computational Linguistics, 2019. doi: 10.18653/v1/n19-4009. URL https://doi.org/10. 18653/v1/n19-4009.

Aditya Paliwal, Sarah M. Loos, Markus N. Rabe, Kshitij Bansal, and Christian Szegedy. Graph representations for higher-order logic and theorem proving. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 2967–2974. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/5689.

Frank Pfenning and Christine Paulin-Mohring. Inductively defined types in the calculus of constructions. In Michael G. Main, Austin Melton, Michael W. Mislove, and David A. Schmidt (eds.), *Mathematical Foundations of Programming Semantics, 5th International Conference, Tulane University, New Orleans, Louisiana, USA, March 29 - April 1, 1989, Proceedings*, volume 442 of *Lecture Notes in Computer Science*, pp. 209–228. Springer, 1989. doi: 10.1007/BFb0040259. URL https://doi.org/10.1007/BFb0040259.

Stanislas Polu and Ilya Sutskever. Generative language modeling for automated theorem proving. *CoRR*, abs/2009.03393, 2020. URL https://arxiv.org/abs/2009.03393.

Markus N. Rabe, Dennis Lee, Kshitij Bansal, and Christian Szegedy. Mathematical reasoning via self-supervised skip-tree training. *CoRR*, abs/2006.04757, 2020. URL `https://arxiv.org/abs/2006.04757`.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning Transferable Visual Models From Natural Language Supervision.

Alex Sanchez-Stern, Yousef Alhessi, Lawrence K. Saul, and Sorin Lerner. Generating correctness proofs with neural networks. In Koushik Sen and Mayur Naik (eds.), *Proceedings of the 4th ACM SIGPLAN International Workshop on Machine Learning and Programming Languages, MAPL@PLDI 2020, London, UK, June 15, 2020*, pp. 1–10. ACM, 2020. doi: 10.1145/3394450.3397466. URL `https://doi.org/10.1145/3394450.3397466`.

Peter Scholze. Liquid tensor experiment. `https://xenaproject.wordpress.com/2020/12/05/liquid-tensor-experiment/`, 2020. Formalization available at `https://github.com/leanprover-community/lean-liquid`.

Josef Urban and Jan Jakubuv. First neural conjecturing datasets and experiments. In Christoph Benzmüller and Bruce R. Miller (eds.), *Intelligent Computer Mathematics - 13th International Conference, CICM 2020, Bertinoro, Italy, July 26-31, 2020, Proceedings*, volume 12236 of *Lecture Notes in Computer Science*, pp. 315–323. Springer, 2020. doi: 10.1007/978-3-030-53518-6_24. URL `https://doi.org/10.1007/978-3-030-53518-6_24`.

Mingzhe Wang and Jia Deng. Learning to prove theorems by learning to generate theorems. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/d2a27e83d429f0dcae6b937cf440aeb1-Abstract.html`.

Daniel Whalen. Holophrasm: a neural automated theorem prover for higher-order logic. *CoRR*, abs/1608.02644, 2016. URL `http://arxiv.org/abs/1608.02644`.

Freek Wiedijk. The De Bruijn factor, 2000. URL `http://www.cs.ru.nl/F.Wiedijk/factor/factor.pdf`.

Yuhuai Wu, Markus N. Rabe, Wenda Li, Jimmy Ba, Roger B. Grosse, and Christian Szegedy. LIME: learning inductive bias for primitives of mathematical reasoning. *CoRR*, abs/2101.06223, 2021. URL `https://arxiv.org/abs/2101.06223`.

Kaiyu Yang and Jia Deng. Learning to prove theorems via interacting with proof assistants. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6984–6994. PMLR, 2019. URL `http://proceedings.mlr.press/v97/yang19a.html`.

APPENDIX A: DATASETS

PRE-TRAINING DATASETS

We pre-train on `WebMath` as described in (Polu & Sutskever, 2020). `WebMath` pre-trained models are also pre-trained on the mix used by GPT-3 (Brown et al., 2020) which includes a filtered `CommonCrawl`, `WebText2`, `Book1`, `Book2` and `Wikipedia`. `WebMath` includes Python-only `GitHub` data, as well as `arXiv` and `Math StackExchange`.

From these datasets, a potential risk for test-set contamination (presence of `mathlib`) exists for the crawled datasets, namely `CommonCrawl`, `WebText2`, and (in case of a filtering bug) Python-only `GitHub`. The other datasets (in particular `arXiv` and `Math StackExchange`) may contain short references of `mathlib` code but in shape and forms that would not lead to effective contamination.

To assess the contamination risk related with the crawled datasets, we run full-scans searching for the following `mathlib`-specific strings on `CommonCrawl`, `WebText2`, and Python-only `GitHub`. Note that we expect these strings to match even if presented in HTML on the Web as these datasets contain text rendered versions of the page crawled online.

```
"{ rintro ⟨"
"{ rcases h"
"irrational_sqrt_two : irrational (sqrt 2)"
```

Despite the two first strings occurring respectively 266 and 101 times in `mathlib`, we found 0 occurrence of any of the three strings in `WebText2`, Python-only `GitHub`, or `CommonCrawl`; negating any suspicion of effective test-set contamination.

At the same time we looked for the following Metamath specific and HOL specific strings:

```
Metamath:
    "( ph -> A = C )"
    "( ph -> A R C )"
    "( sqrt ` 2 ) e/ QQ"
HOL:
    "apply (rule "
    "apply (drule "
```

We found 0 occurrence of the Metamath-related strings but interestingly found a non-negligible amount of HOL-related documents, which does not constitute a test-set contamination but potentially benefits the downstream tasks studied in this paper.

DATASET SIZES

- `tactic`: ≈128K examples.
- `mix1`
    - **Next lemma prediction**: ≈2.5M examples
    - **Proof term prediction**: ≈2.9M examples
- `mix2`
    - **Skip-proof**: ≈1.7M examples
    - **Type-prediction**: ≈1.7M examples
    - **Tactic state elaboration**: ≈346K examples
    - **Proof term elaboration**: ≈1.0M examples
    - **Premise classification**: ≈9.3M examples
    - **Local context classification**: ≈2.0M examples
    - **Theorem naming**: ≈32K examples.

EXAMPLE DATAPOINTS

We present datapoints extracted from a toy example, namely the proof of the Peirce identity, viz.

```
lemma peirce_identity {P Q :Prop} : ((P → Q) → P) → P :=
begin
  apply or.elim (em P),
  intros h _,
  exact h,
  tauto!
end
```

From this, we can extract four `tactic` datapoints (i.e. human-generated tactic proof steps):

```
-- GOAL P Q : Prop ⊢ ((P → Q) → P) → P PROOFSTEP apply or.elim (em P)
-- GOAL P Q : Prop ⊢ P → ((P → Q) → P) → P  P Q : Prop ⊢ ¬P → ((P →
    Q) → P) → P PROOFSTEP intros h _
-- GOAL P Q : Prop, h : P, α̃ : (P → Q) → P ⊢ P  P Q : Prop ⊢ ¬P → ((P
    → Q) → P) → P PROOFSTEP exact h
-- GOAL P Q : Prop ⊢ ¬P → ((P → Q) → P) → P PROOFSTEP tauto!
```

In contrast, we can extract dozens of raw PACT datapoints. Due to space constraints, we list a representative sample of four such datapoints, from each of which we can derive the nine self-supervised auxiliary PACT tasks studied in our present work. For example, proof term prediction is precisely predicting the `"proof_term"` given the concatenation of `"hyps"`, `"⊢"`, and the `"goal"`, skip-proof is predicting the `"proof_term"` given `"result"`, etc.

```
  DATAPOINT:
---
{ "decl_nm":"peirce_identity",
  "decl_tp":"∀ {P Q : Prop}, ((P → Q) → P) → P",
  "hyps":[["P", "Prop"], ["Q", "Prop"], ["ǎ", "¬P"], ["ǎ_1", "(P → Q) →
    P"], ["ǎ_1", "¬(P → Q)"]],
  "hyps_mask":[true, false, false, false, false],
  "decl_premises":[["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["decidable.not_imp", "∀ {a b : Prop} [_inst_1 : decidable a], ¬(a →
    b) ↔ a ∧ ¬b"],
   ["iff.mp", "∀ {a b : Prop}, (a ↔ b) → a → b"],
   ["and.dcases_on",
    "∀ {a b : Prop} {C : a ∧ b → Prop} (n : a ∧ b), (∀ (left : a)
    (right : b), C _) → C n"],
   ["decidable.not_or_of_imp", "∀ {a b : Prop} [_inst_1 : decidable a],
    (a → b) → ¬a ∨ b"],
   ["or.dcases_on",
    "∀ {a b : Prop} {C : a ∨ b → Prop} (n : a ∨ b), (∀ (h : a), C _) →
    (∀ (h : b), C _) → C n"],
   ["em", "∀ (p : Prop), p ∨ ¬p"],
   ["or.elim", "∀ {a b c : Prop}, a ∨ b → (a → c) → (b → c) → c"]],
  "decl_premises_mask":[false, false, true, false, false, false, false,
    false, false],
  "goal":"∀ {b : Prop} [_inst_1 : decidable P], ¬(P → b) ↔ P ∧ ¬b",
  "proof_term":"decidable.not_imp",
  "result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q) → P),
    h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P), (decidable.not_or_of_imp ǎ
    _1).dcases_on (λ (ǎ_1 : ¬(P → Q)), ((PREDICT Q
    (classical.prop_decidable P)).mp ǎ_1).dcases_on (λ (ǎ_1_left : P)
    (ǎ_1_right : ¬Q), absurd ǎ_1_left ǎ)) (λ (ǎ_1 : P), absurd ǎ_1 ǎ))",
  "next_lemma":["decidable.not_imp", "∀ {a b : Prop} [_inst_1 :
    decidable a], ¬(a → b) ↔ a ∧ ¬b"],
  "goal_is_prop":true,
  "verbose_proof_term":"@decidable.not_imp P",
  "verbose_goal":"∀ {b : Prop} [_inst_1 : decidable P], ¬(P → b) ↔ P ∧
    ¬b",
  "verbose_result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q)
    → P), h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P),
    (@decidable.not_or_of_imp (P → Q) P (classical.prop_decidable (P →
    Q)) ǎ_1).dcases_on (λ (ǎ_1 : ¬(P → Q)), (@iff.mp (¬(P → Q)) (P ∧ ¬
    Q) (PREDICT Q (classical.prop_decidable P)) ǎ_1).dcases_on (λ
    (ǎ_1_left : P) (ǎ_1_right : ¬Q), @absurd P P ǎ_1_left ǎ)) (λ (ǎ_1 :
    P), @absurd P P ǎ_1 ǎ))"}
---

DATAPOINT:
---
{ "decl_nm":"peirce_identity",
  "decl_tp":"∀ {P Q : Prop}, ((P → Q) → P) → P",
  "hyps":[["P", "Prop"], ["Q", "Prop"], ["ǎ", "¬P"], ["ǎ_1", "(P → Q) →
    P"], ["ǎ_1", "¬(P → Q)"]],
  "hyps_mask":[false, true, false, false, false],
  "decl_premises":[["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["decidable.not_imp", "∀ {a b : Prop} [_inst_1 : decidable a], ¬(a →
    b) ↔ a ∧ ¬b"],
   ["iff.mp", "∀ {a b : Prop}, (a ↔ b) → a → b"],
   ["and.dcases_on",
```

```
     "∀ {a b : Prop} {C : a ∧ b → Prop} (n : a ∧ b), (∀ (left : a)
      (right : b), C _) → C n"],
     ["decidable.not_or_of_imp", "∀ {a b : Prop} [_inst_1 : decidable a],
      (a → b) → ¬a ∨ b"],
     ["or.dcases_on",
      "∀ {a b : Prop} {C : a ∨ b → Prop} (n : a ∨ b), (∀ (h : a), C _) →
      (∀ (h : b), C _) → C n"],
     ["em", "∀ (p : Prop), p ∨ ¬p"],
     ["or.elim", "∀ {a b c : Prop}, a ∨ b → (a → c) → (b → c) → c"]],
   "decl_premises_mask":[false, false, false, false, false, false, false,
    false, false],
   "goal":"Prop",
   "proof_term":"Q",
   "result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q) → P),
    h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P), (decidable.not_or_of_imp ǎ
    _1).dcases_on (λ (ǎ_1 : ¬(P → Q)), (decidable.not_imp.mp ǎ
    _1).dcases_on (λ (ǎ_1_left : P) (ǎ_1_right : ¬Q), absurd ǎ_1_left ǎ
    )) (λ (ǎ_1 : P), absurd ǎ_1 ǎ))",
   "next_lemma":["Q", "Prop"],
   "goal_is_prop":false,
   "verbose_proof_term":"Q",
   "verbose_goal":"Prop",
   "verbose_result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q)
    → P), h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P),
    (@decidable.not_or_of_imp (P → Q) P (classical.prop_decidable (P →
    Q)) ǎ_1).dcases_on (λ (ǎ_1 : ¬(P → Q)), ((@decidable.not_imp P
    PREDICT (classical.prop_decidable P)).mp ǎ_1).dcases_on (λ (ǎ_1_left
    : P) (ǎ_1_right : ¬Q), @absurd P P ǎ_1_left ǎ)) (λ (ǎ_1 : P),
    @absurd P P ǎ_1 ǎ))"}
---

DATAPOINT:
---
{ "decl_nm":"peirce_identity",
  "decl_tp":"∀ {P Q : Prop}, ((P → Q) → P) → P",
  "hyps":[["P", "Prop"], ["Q", "Prop"], ["ǎ", "¬P"], ["ǎ_1", "(P → Q) →
    P"], ["ǎ_1", "¬(P → Q)"]],
  "hyps_mask":[true, true, false, false, false],
  "decl_premises":[["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["decidable.not_imp", "∀ {a b : Prop} [_inst_1 : decidable a], ¬(a →
    b) ↔ a ∧ ¬b"],
   ["iff.mp", "∀ {a b : Prop}, (a ↔ b) → a → b"],
   ["and.dcases_on",
    "∀ {a b : Prop} {C : a ∧ b → Prop} (n : a ∧ b), (∀ (left : a)
    (right : b), C _) → C n"],
   ["decidable.not_or_of_imp", "∀ {a b : Prop} [_inst_1 : decidable a],
    (a → b) → ¬a ∨ b"],
   ["or.dcases_on",
    "∀ {a b : Prop} {C : a ∨ b → Prop} (n : a ∨ b), (∀ (h : a), C _) →
    (∀ (h : b), C _) → C n"],
   ["em", "∀ (p : Prop), p ∨ ¬p"],
   ["or.elim", "∀ {a b c : Prop}, a ∨ b → (a → c) → (b → c) → c"]],
  "decl_premises_mask":[false, false, true, false, false, false, false,
   false, false],
  "goal":"∀ [_inst_1 : decidable P], ¬(P → Q) ↔ P ∧ ¬Q",
  "proof_term":"decidable.not_imp",
  "result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q) → P),
   h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P), (decidable.not_or_of_imp ǎ
   _1).dcases_on (λ (ǎ_1 : ¬(P → Q)), ((PREDICT
   (classical.prop_decidable P)).mp ǎ_1).dcases_on (λ (ǎ_1_left : P)
   (ǎ_1_right : ¬Q), absurd ǎ_1_left ǎ)) (λ (ǎ_1 : P), absurd ǎ_1 ǎ))",
  "next_lemma":["decidable.not_imp", "∀ {a b : Prop} [_inst_1 :
   decidable a], ¬(a → b) ↔ a ∧ ¬b"],
  "goal_is_prop":true,
```

```
  "verbose_proof_term":"@decidable.not_imp P Q",
  "verbose_goal":"∀ [_inst_1 : decidable P], ¬(P → Q) ↔ P ∧ ¬Q",
  "verbose_result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q)
    → P), h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P),
    (@decidable.not_or_of_imp (P → Q) P (classical.prop_decidable (P →
    Q)) ǎ_1).dcases_on (λ (ǎ_1 : ¬(P → Q)), (@iff.mp (¬(P → Q)) (P ∧ ¬
    Q) (PREDICT (classical.prop_decidable P)) ǎ_1).dcases_on (λ
    (ǎ_1_left : P) (ǎ_1_right : ¬Q), @absurd P P ǎ_1_left ǎ)) (λ (ǎ_1 :
    P), @absurd P P ǎ_1 ǎ))"}
---

DATAPOINT:
---
{ "decl_nm":"peirce_identity",
  "decl_tp":"∀ {P Q : Prop}, ((P → Q) → P) → P",
  "hyps":[["P", "Prop"], ["Q", "Prop"], ["ǎ", "¬P"], ["ǎ_1", "(P → Q) →
    P"], ["ǎ_1", "¬(P → Q)"]],
  "hyps_mask":[false, false, false, false, false],
  "decl_premises":[["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["absurd", "∀ {a b : Prop}, a → ¬a → b"],
   ["decidable.not_imp", "∀ {a b : Prop} [_inst_1 : decidable a], ¬(a →
   b) ↔ a ∧ ¬b"],
   ["iff.mp", "∀ {a b : Prop}, (a ↔ b) → a → b"],
   ["and.dcases_on",
    "∀ {a b : Prop} {C : a ∧ b → Prop} (n : a ∧ b), (∀ (left : a)
    (right : b), C _) → C n"],
   ["decidable.not_or_of_imp", "∀ {a b : Prop} [_inst_1 : decidable a],
   (a → b) → ¬a ∨ b"],
   ["or.dcases_on",
    "∀ {a b : Prop} {C : a ∨ b → Prop} (n : a ∨ b), (∀ (h : a), C _) →
    (∀ (h : b), C _) → C n"],
   ["em", "∀ (p : Prop), p ∨ ¬p"],
   ["or.elim", "∀ {a b c : Prop}, a ∨ b → (a → c) → (b → c) → c"]],
  "decl_premises_mask":[false, false, false, false, false, false, false,
   false, false],
  "goal":"Π (a : Prop), decidable a",
  "proof_term":"classical.prop_decidable",
  "result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q) → P),
   h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P), (decidable.not_or_of_imp ǎ
   _1).dcases_on (λ (ǎ_1 : ¬(P → Q)), (decidable.not_imp.mp ǎ
   _1).dcases_on (λ (ǎ_1_left : P) (ǎ_1_right : ¬Q), absurd ǎ_1_left ǎ
   )) (λ (ǎ_1 : P), absurd ǎ_1 ǎ))",
  "next_lemma":["classical.prop_decidable", "Π (a : Prop), decidable a"],
  "goal_is_prop":false,
  "verbose_proof_term":"classical.prop_decidable",
  "verbose_goal":"Π (a : Prop), decidable a",
  "verbose_result":"λ {P Q : Prop}, (em P).elim (λ (h : P) (ǎ : (P → Q)
    → P), h) (λ (ǎ : ¬P) (ǎ_1 : (P → Q) → P),
    (@decidable.not_or_of_imp (P → Q) P (PREDICT (P → Q)) ǎ
    _1).dcases_on (λ (ǎ_1 : ¬(P → Q)), ((@decidable.not_imp P Q
    (PREDICT P)).mp ǎ_1).dcases_on (λ (ǎ_1_left : P) (ǎ_1_right : ¬Q),
    @absurd P P ǎ_1_left ǎ)) (λ (ǎ_1 : P), @absurd P P ǎ_1 ǎ))"}
---
```

APPENDIX B: EXPERIMENTS

CHAINED TACTIC PREDICTION

Individual Lean tactics are chained together with commas. However, the Lean interactive tactic DSL also includes a number of other tactic combinators for creating composite tactics. A frequently used combinator is the infix semicolon `t; s` which will perform the tactic `t` and then apply the tactic `s` to each of the resulting subgoals produced by `t`. Our data pipeline for human tactic proof steps treats these semicolon-chained tactics as a single string for the language modeling objective. Thus,

Table 1: Counting the number of semicolon-chained tactics predicted by our models that appear *in successful proofs*. Each column headed by a number n; indicates the number of times that a suggestion appeared with n occurrences of '; '.

MODEL	1;	2;	3;	4;	MEAN
wm-to-tt	215	49	2	0	1.199
wm-to-tt-m1	186	39	5	1	1.225
wm-to-tt-m1-m2	**328**	**82**	**12**	**3**	**1.271**

our models learn to occasionally emit multiple-step tactic predictions using semicolons. For example, `wm-to-tt-m1-m2` solved the following lemma in category theory with a single prediction chaining four tactics in a row:

```
theorem category_theory.grothendieck.congr
  {X Y : grothendieck F} {f g : X ⟶ Y} (h : f = g) :
  f.fiber = eq_to_hom (by subst h) ≫ g.fiber :=
begin
  rcases X; rcases Y; subst h; simp
end
```

One way of measuring the sophistication of predicted tactics is to consider the number of successful proofs on the evaluation set which have this composite form using semicolon-chaining. We display this analysis in Table 1, which shows that training with PACT in addition to the human-made tactics causes longer semicolon-chained tactics to be successfully predicted during theorem proving. This is remarkable because the semicolon idiom is specific to the tactic DSL which does not occur in the PACT data whatsoever, and yet the co-training causes longer and more frequent successful composite tactic predictions.

THEOREM NAMING CASE STUDY

We included *theorem naming* as part of the PACT task suite. By `mathlib` convention, theorem names are essentially snake-cased, natural language summaries of the type signature of a theorem, and so the theorem naming task is analogous to a formal-to-informal translation task. We evaluate the ability of our best model (in terms of theorem proving success rate) `wm-to-tt-m1-m2` on its ability to guess theorem names on the completely unseen `future-mathlib` set of theorems. The distribution shift inherent in the `future-mathlib` dataset particularly impacts the theorem naming task, because many of the ground-truth names will involve names for concepts that were only defined in `mathlib` *after* we extracted our training data.

On the $\approx$2.8K `future-mathlib` theorems, we queried `wm-to-tt-m1-m2` for up to $N = 16$ candidates. We order these candidates into a list `xs` by decreasing cumulative log-probability and calculate the top-K accuracy by checking if any of the first K candidates of `xs` match the ground truth exactly. The model `wm-to-tt-m1-m2` was able to achieve 20.1% top-1 accuracy, 21.1% top-3 accuracy, 26.7% top-10 accuracy, and 30.0% top-16 accuracy. We display a sample of correct top-1 guesses (Figure 5) and a sample of failed guesses in (Figure 6). We note that the failed guesses, while containing no syntactic matches, are both semantically reasonable and syntactically very similar to the ground truth.

TEST SET EVALUATION BREAKDOWN BY MODULE

Lean's `mathlib` is organized into top-level modules, which roughly organize theorems into mathematical subject area. In Figure 7, we break down the evaluation results on our `test` set between our PACT-trained models `wm-to-tt-m1-m2` and `wm-to-tt-m1` and our baselines `wm-to-tt` and `tidy`. We see that full PACT mostly dominates over co-training on just the `mix1` tasks over all subject areas, and that `wm-to-tt-m1` dominates the model `wm-to-tt` trained on human tactic proof steps only.

	Correct top-1 guesses
Theorem statement	$\forall$ {α : Type u_1} {β : Type u_2} [_inst_1 : decidable_eq α]
[_inst_2 : decidable_eq β] (s : finset α) (t : finset β),
s.product t = s.bUnion
(λ (a : α), finset.image (λ (b : β), (a, b)) t)
Ground truth	finset.product_eq_bUnion
Theorem statement	$\forall$ {α : Type u_1} {β : Type u_2} [_inst_1 : topological_space α]
[_inst_2 : topological_space β] {f : $\alpha \rightarrow \beta$},
quotient_map f $\rightarrow$ function.surjective f
Ground truth	quotient_map.surjective
Theorem statement	$\forall$ {α : Type u_1} {β : Type u_2} (f : $\alpha \rightarrow$ option β)
(x : option α), x.pbind (λ (a : α) (_x : a $\in$ x), f a) = x.bind f
Ground truth	option.pbind_eq_bind
Theorem statement	$\forall$ {C : Type u$_1$} [_inst_1 : category_theory.category C]
{G : C $\Rightarrow$ C} [_inst_2 : category_theory.comonad G]
{A B : category_theory.comonad.coalgebra G} (h : A.A $\cong$ B.A)
(w : A.a $\gg$ G.map h.hom = h.hom $\gg$ B.a),
(category_theory.comonad.coalgebra.iso_mk h w).hom.f = h.hom
Ground truth	category_theory.comonad.coalgebra.iso_mk_hom_f
Theorem statement	$\forall$ {**k** : Type u_1} {E : Type u_2} [_inst_1 : is_R_or_C ,**k**]
[_inst_2 : inner_product_space **k** E]
[_inst_4 : normed_space $\mathbb{R}$ E] [_inst_5 : is_scalar_tower $\mathbb{R}$ **k** E]
(p x : E $\times$ E),
$\Uparrow$(fderiv_inner_clm p) x =
has_inner.inner p.fst x.snd + has_inner.inner x.fst p.snd
Ground truth	fderiv_inner_clm_apply

Figure 5: A sample of correct top-1 guesses by our best model wm-to-tt-m1-m2 on the *theorem naming* task. We performed this experiment on the future-mathlib evaluation set, which comprises entirely unseen theorems added to mathlib only after we last extracted training data.

	Incorrect guesses
Theorem statement	$\forall$ {α : Type u_1} (t : ordnode α) (x : α),
t.dual.find_min$'$ x = ordnode.find_max$'$ x t
Guesses (top 8)	ordinal.find_min$'$_eq, ordinal.find_min$'$_eq_max$'$, ordinal.find_min$'$_def,
ordinal.find_min$'$_eq_max, ordinal.find_min$'$, ordinal.dual_find_min$'$,
ordinal.find_min$'$_gt, ordinal.find_min$'$_q
Ground truth	ordnode.find_min$'$_dual
Theorem statement	$\forall$ {α : Type u_1} {β : Type u_3} {γ : Type u_5} [_inst_1 :
measurable_space α] [_inst_3 : measurable_space β]
[_inst_5 : measurable_space γ] {μ : measure_theory.measure α}
{ν : measure_theory.measure β}
[_inst_8 : measure_theory.sigma_finite ν]
{f : $\alpha \times \beta \to \gamma$},
ae_measurable f (μ.prod ν) $\to$ ($\forall^{\text{m}}$(x : α) $\partial\mu$,
ae_measurable (λ (y : β), f (x, y)) ν)
Guesses (top 8)	measure_theory.ae_prod, measure_theory.ae_of_ae_prod,
measure_theory.ae_eq_prod_of_ae, measure_theory.ae_ae_of_ae_prod,
measure_theory.ae_measure_prod_mk_left,
measure_theory.ae_prod_of_ae_prod,
measure_theory.ae_measure_prod, measure_theory.ae_eq_refl
Ground truth	ae_measurable.prod_mk_left
Theorem statement	$\forall$ {α : Type u_1} {β : Type u_2} {γ : Type u_3}
{f : filter α} {h : set $\alpha \to$ set β} {m : $\gamma \to \beta$}
{l : filter γ}, filter.tendsto m l (f.lift$'$ h) $\leftrightarrow$
$\forall$ (s : set α), s $\in$ f $\to$ ($\forall^{\text{f}}$ (a : γ) in l, m a $\in$ h s)
Guesses (top 8)	filter.tendsto_lift$'$_iff, filter.tendsto_lift$'$_def
Ground truth	filter.tendsto_lift$'$
Theorem statement	$\forall$ {R : Type} [_inst_1 : comm_ring R]
{d : $\mathbb{Z}$} (f : $\mathbb{Z}\sqrt{}$d $\to^{+*}$ R),
$\uparrow$($\Uparrow$(zsqrtd.lift.symm) f) = $\Uparrow$f zsqrtd.sqrtd
Guesses (top 8)	zsqrtd.coe_lift_symm, zsqrtd.coe_lift.symm, zsqrtd.lift.coe_symm_apply,
zsqrtd.lift_symm_apply, zsqrtd.lift.coe_coe_symm,
zsqrtd.lift.coe_symm_coe,
zsqrtd.lift.symm_coe_zsqrtd, zsqrtd.lift_symm_to_zsqrtd
Ground truth	zsqrtd.lift_symm_apply_coe

Figure 6: A sample of incorrect guesses by our best model wm-to-tt-m1-m2 on the *theorem naming* task. We performed this experiment on the future-mathlib evaluation set, which comprises entirely unseen theorems added to mathlib only after we last extracted training data. Most of the top-8 guesses displayed in the above table are very similar to the ground truth, in some cases being equivalent up to permutation of underscore-separated tokens. Note that for the first example, the concept of ordnode was not in the training data whatsoever and all predictions are in the syntactically similar ordinal namespace.

Figure 7: A breakdown of theorem proving success rate on the `test` set for `wm-to-tt-m1-m2`, `wm-to-tt-m1`, `wm-to-tt`, and the `tidy` baseline across top-level modules in Lean's `mathlib`. We see that `wm-to-tt-m1-m2` mostly dominates `wm-to-tt-m1` and the models trained using PACT dominate the model `wm-to-tt` trained on human tactic proof steps.

BASELINE DESCRIPTION

The `tidy` backend is determined by a constant oracle

$$\Omega : \texttt{tactic\_state} \rightarrow \texttt{list (string × float)}$$

which always returns the same list of tactics, namely:

```
meta def tidy_default_tactics : list (string × float) :=
list.map (flip prod.mk 0.0) [
    "refl"
,   "exact dec_trivial"
,   "assumption"
,   "tactic.intros1"
,   "tactic.auto_cases"
,   "apply_auto_param"
,   "dsimp at *"
,   "simp at *"
,   "ext1"
,   "fsplit"
,   "injections_and_clear"
,   "solve_by_elim"
,   "norm_cast"
]
```

Unlike the `gptf` backend, which generates a list of candidates in parallel independently, `tidy` enjoys the advantage that the list of tactics it emits is carefully chosen and ordered in order to optimize the proof search—this is based on the "waterfall" technique of the human-style automated theorem prover described in (Ganesalingam & Gowers, 2017).

COMPUTATIONAL RESOURCE ESTIMATES

For each evaluation loop over the `test` set, we distributed the theorems over a pool of 32 CPU workers whose inference requests were load-balanced over 4 `V100` GPUs. Each evaluation required ≈ 10 hours with $\approx 30\%$ GPU utilization. We observed that our evaluation was bottlenecked by

inference and in practice, we hosted up to three evaluation loops at once on a VM with 80 logical cores without achieving full CPU utilization. In addition to the wall-clock timeout of 600s, we also limited the proof search to a logical timeout of `512` iterations, where one iteration corresponds to a single expansion of a node of the BFS search tree. In practice, so much time was spent either blocked on inference or performing the tactic executions in the inner loop of each iteration that we rarely exceeded the logical timeout, usually exceeding the wall-clock timeout instead.

Fine-tuning on our largest dataset `mix1 + mix2 + tactic` required 26 hours using 64 `A100` GPUs exhibiting high `FP16` usage, totalling an estimated ≈1.5K `A100(FP16)`-hours. This gives an estimated cost of 17.33 `A100(FP16)`-hours per billion elapsed tokens during training. We note that when calculating the number of elapsed tokens for training, we overestimate the actual number of tokens effectively trained on by summing full context windows (in this case, 2048 tokens).

APPENDIX C: EXAMPLE PROOFS

Lean's `mathlib` is one of the most active open-source software projects in the world. More than one-third of the proofs found by our models are shorter and produce smaller proof terms than the ground truth, leading to dozens of GPT-f co-authored commits to `mathlib`. We examine some of the proofs found by our models in more detail.

LIE_ALGEBRA.MORPHISM.MAP_BOT_IFF

This proof produces a proof term which is 4X smaller than the original:

```
lemma map_bot_iff : I.map f = ⊥ ↔ I ≤ f.ker :=
by { rw ← le_bot_iff, apply lie_ideal.map_le_iff_le_comap }
```

The original, human-written proof is much longer, viz.

```
lemma map_bot_iff : I.map f = ⊥ ↔ I ≤ f.ker :=
begin
  rw le_ker_iff, unfold lie_ideal.map, split; intros h,
  { rwa [eq_bot_iff, lie_submodule.lie_span_le, set.image_subset_iff,
    lie_submodule.bot_coe] at h,},
  { suffices : f '' I = ↑(⊥ : lie_ideal R L'), { rw [this,
    lie_submodule.lie_span_eq], },
    ext x, rw [lie_submodule.bot_coe, set.mem_singleton_iff,
    set.mem_image],
    split,
    { rintros ⟨y, hy, hx⟩, rw ← hx, exact h y hy, },
    { intros hx, use 0, simp [hx], }, },
end
```

PRIMREC.OF_EQUIV

This proof produces a proof term which is 12X smaller than the original:

```
theorem of_equiv {β} {e : β ≃ α} :
  by haveI := primcodable.of_equiv α e; exact
  primrec e :=
by letI : primcodable β := primcodable.of_equiv α e; exact encode_iff.1
    primrec.encode
```

The author of the original proof and maintainer of that package commented:

> `encode_iff.1 primrec.encode` is clever, it's a way to translate `primrec` across an equivalence when the encode function is defined as `encode x = encode (e x)` where `e` is the isomorphism.

As far as they knew, this trick was never used before in the `computability` package.

REAL.TAN_EQ_SIN_DIV_COS

This proof demonstrates our model's library knowledge and ability at premise selection.

```
lemma real.tan_eq_sin_div_cos (x : ℝ) : tan x = sin x / cos x :=
begin
  rw ← of_real_inj,
  simp only [complex.tan_eq_sin_div_cos, of_real_sin, of_real_cos,
    of_real_div, of_real_tan]
end
```

Our model was able to predict this entire list of `simp` lemmas in one shot. Note that the lemma `complex.tan_eq_sin_div_cos` in this list is the *complex number* version of the result, i.e. ∀ (x : ℂ), tan x = sin x / cos x. The previous human-written version of the proof did not use the more general version of the lemma on complex numbers, demonstrating our model's ability to find more general cases of lemmas. We contrast this with the human-written ground truth, which is more complex and performs a case analysis using the complex cosine:

```
  lemma tan_eq_sin_div_cos : tan x = sin x / cos x :=
if h : complex.cos x = 0 then by simp [sin, cos, tan, *, complex.tan,
    div_eq_mul_inv] at *
else
  by rw [sin, cos, tan, complex.tan, ← of_real_inj, div_eq_mul_inv,
    mul_re];
  simp [norm_sq, (div_div_eq_div_mul _ _ _).symm, div_self h]; refl
```

SYM2.IS_DIAG_IFF_PROJ_EQ

The proof of this lemma is longer than the ground truth and was not contributed to `mathlib`, but we describe it here because the proof is original and includes a nontrivial instantiation of an existential quantifier.

```
theorem sym2.is_diag_iff_proj_eq (z : α × α) :
  is_diag ⟦z⟧ ↔ z.1 = z.2 :=
begin
    intros,
    simp only [is_diag, prod.ext_iff, quot.exists_rep, iff_true,
    not_true, eq_self_iff_true],
    simp [diag], split,
    { rintros ⟨y, hy⟩, cases hy; refl },
    intro h, cases z, existsi z_snd,
    cases h, refl,
end
```

Before `existsi z_snd`, the goal state is

```
z_fst z_snd: α
h: (z_fst, z_snd).fst = (z_fst, z_snd).snd
⊢ ∃ (y : α), (y, y) ≈ (z_fst, z_snd)
```

This goal state never appeared in `mathlib`.

NORM_LE_ZERO_IFF

The following proof is remarkable because it uses fewer tactic steps and takes a different route to the proof than the ground truth, uses a complex idiom `simpa [...]` using `@...`, and was predicted in one shot.

```
lemma norm_le_zero_iff {α : Type u_1} [_inst_1 : normed_group α]
  {g : α} : ‖g‖ ≤ 0 ↔ g = 0 :=
by { simpa [le_antisymm_iff, norm_nonneg] using @norm_eq_zero α _ g }
-- ground truth:
-- by { rw[←dist_zero_right],
--      exact dist_le_zero }
```

The lemmas supplied between the square brackets are used to simplify the main goal. The lemma supplied after the keyword `using` can further simplify the lemmas supplied between the square brackets. The `@` modifier makes all arguments explicit. The string `@norm_eq_zero` never appeared in our training data but the prediction includes the correct number of correctly typed arguments, and even replaces the second argument with a placeholder `_`, correctly guessing that it can be inferred by the elaborator. Finally, this again showcases the strength of our models as premise selectors: all three lemmas `le_antisymm_iff`, `norm_nonneg`, and `norm_eq_zero` were not used in the human-supplied proof but are necessary for this proof.

Moving forward, we hope that our neural theorem provers will continue to find ways to improve `mathlib` and assist in creating new proofs. More generally, we hope neural theorem proving will one day be become a routine part of the formalization workflow.