Scaling Infrastructure to Support Multi-Trillion Parameter LLM Training

ISCA 2023 Submission **#NaN** – Confidential Draft – Do NOT Distribute!!

Abstract—This paper discusses efficient system designs for Large Language Model (LLM) scaling to up to 128 trillion parameters. We use a comprehensive analytical performance model to analyze how such models could be trained on current systems while maintaining 75% Model FLOPS Utilization (MFU). We first show how tensor offloading alone can be used to dramatically increase the size of trainable LLMs. We analyze performance bottlenecks when scaling on systems up to 16,384 GPUs and with models up to 128T parameters. Our findings suggest that current H100 GPUs with 80 GiB of HBM enabled with 512 GiB of tensor offloading can scale efficiency to 11T parameters and getting to 128T parameters requires 120 GiB of HBM and 2 TiB of offloading memory, yielding 75%+ MFU, which is uncommon even when training much smaller LLMs today.

I. Introduction

We wish to consider what software and system configurations might permit existing Large Language Models (LLMs), now at about 1 trillion parameters [9], to scale with greater efficiency to even larger model sizes. Our analysis is driven by the continued success and efficacy of LLMs in a variety of applications [1], [2], [5], [9], [12], [14], [19] and motivated by the observation that Model FLOPS Utilization (MFU)—a common metric of efficiency for assessing how well specialized Artificial Intelligence (AI) accelerators are utilized during model training—can be as low as 50% or less [13].

A significant improvement to MFU will be necessary to increase model sizes by 10× (10 trillion parameters) or higher on architectures similar to current systems. With a space requirement of 20 bytes per parameter, to store just the model's weights and optimizer step we would need more than 200 TB of memory. For a system based on NVIDIA H100 [11] Graphics Processing Unit (GPU) with 80 GiB of high bandwidth memory (HBM) memory each, we would need 2,500 GPUs and a fully model-parallel implementation to train such a model. No known model-parallelism technique at this scale would be able to provide anywhere near 50% MFU.

Motivated by this example, we aim to establish the system limitations that prevent us from training multi-trillion parameter models on large systems built using clusters of 8 interconnected GPUs, similar to NVIDIA DGX and HGX. We start by presenting a methodology for choosing well structured multi-trillion parameter LLMs. Then, using our own fast analytical performance model of transformer-based LLM training, we search a space of billions of system configurations and execution strategies. This paper explains a few of our findings, which may be summarized as follows.

1) Training a hundred-trillion parameter LLM is feasible but requires an secondary memory pool up to 1 TiB per GPU with a bandwidth of 100 GB/s bidirectionally.
2) Strong scaling for a 1T model stalls around 12,288 GPUs, as matrix multiply becomes small and inefficient and cannot overlap communication.
3) Scaling beyond 10T models requires more first-level memory, with HBM size scaling with model size.
4) Growing model and system size beyond 10T parameters and 10k GPUs demands a larger fast-network domain and more targeted software optimizations.

Overall, we find it will be critical to co-design the LLM, software, and hardware to attain high performance and efficiency.

II. Experiments Methodology

For performance estimation we use Calculon, a fast analytical model of LLM training performance that we developed. Calculon can estimate the time and resource usage for a given LLM, system configuration, and software execution strategy in about 1 millisecond, allowing us to explore large design spaces consisting of many billions of such configurations. Calculon models LLM training with tensor parallelism (TP), pipeline parallelism (PP), and data parallelism (DP), allowing searches to determine optimal split-parallelism configurations. We perform experiments that vary system size, model size, memory capacity, bandwidth, and NVLink domain sizes, working with the FP8 data format supported by H100. For each system, we pick an execution strategy that considers multiple state-of-the-art software optimizations [6], [9], [15]–[17] and picks the best-performing one. Given the large search spaces, we cannot present our experiments fully and instead focus on a few of the most important trends we have discovered.

Fig. 1. Node architecture used for system modeling.

Our analysis assumes a networked system of compute nodes whose node-architecture is depicted in Fig. 1. It is similar to DGX or HGX in structure and connectivity. The only difference is the addition of offload memory attached to GPU in addition to HBM. Such memory can be connected via compute express link (CXL), or be hosted by Central Processing Unit (CPU) and made directly accessible from GPU, similarly to Grace-Hopper [10].

III. Model Co-design Discussion

We consider scaling LLMs from the perspective of finding roadblocks for efficient LLM training. An important parameter to consider while scaling LLMs is the ratio between the hidden dimension of the transformer block and the number of blocks (a.k.a., transformer layers). This is referred to as an LLM's *aspect ratio*. Some recent research claims the ideal aspect ratio is a constant 128 [4], while others claim that the aspect ratio should increase exponentially with the number of blocks [7]. Both of these analyses were performed on LLMs 2 to 5 orders of magnitude smaller than today's production LLMs. As we don't see consensus among the LLM experts, we follow the apparent current practice suggested by Table I, which is to extrapolate aspect ratios linearly with the number of transformer blocks. Nevertheless, our methodology of analysis will work for any aspect ratio scaling function.

TABLE I
ASPECT RATIOS OF CURRENT LLMS.

Name	Hidden	# Blocks	Aspect Ratio
GPT2-1.5B [14]	1600	48	33.3
Jurassic-6.5B [8]	4096	32	128
PaLM-8B [2]	4096	32	128
GPT3-13B [1]	5140	40	128.5
Megatron-40B [9]	6144	40	153.6
PaLM-62B [2]	8192	64	128
Chinchilla-64B [3]	8192	80	102.4
GPT3-175B [1]	12288	96	128
Jurassic-175B [8]	13824	76	181.9
Megatron-309B [9]	16384	96	170.7
TuringNLG-530B [18]	20480	105	195
PaLM-540B [2]	18432	118	156
Megatron-1T [9]	25600	128	200

Fig. 2. Performance comparison of two 11T models.

One of the challenges in scaling LLMs is mapping the models onto the available computing hardware. Some models, such as GPT-3 [1] with 175 billion parameters across 96

blocks, are designed with many dimensions as powers of two or multiples of powers of two, making them well-suited for typical system designs, which are a commonly built in powers of two. However, other models are not as easy to map. Turing-NLG [18] has 530 billion parameters across 105 blocks, an odd number which results less possible mapping solutions. PaLM [2] has 540 billion parameters across 118 blocks, a prime number multiplied by 2 which results in even less possible mapping solutions.

Fig. 2 compares two similarly sized models of about 11 trillion parameters. One has a nice power of two number of blocks (256) and the other has a prime number multiplied by two (254). When mapped onto 4,096 processors, the 256 block model yields 15,612,832 possible mapping solutions while the 254 block model yields only 842,080, 18.5× less. The 256 block model yields 36% higher execution performance. While the 254 block model yields a 54% MFU, the 256 block model yields 75%.

Fig. 3. Linear scaling of the hidden size with number of transformer blocks, in steps of 8,192 for hidden size and 32 for number of blocks. Each cell contains model size and hidden to blocks ratio. Red color represents narrower models, blue color represents wider ones. Optimal choices are represented by white color in the frame, model size and ratio in bold.

To address this challenge, we propose scaling the number of blocks and attention heads with a step size that is a power of two which makes it easier to scale such models over tensor and pipeline parallelism and providing better overall performance. Fig. 3 scales in steps of 32 for models up to 128 trillion parameters. These models all result in many millions of mapping solutions on various common system designs and across many system sizes.

The hidden step size shown in Fig. 3 is 8,192, however, when finding the most optimal (closest to ideal aspect ratio),

we use a step size of 1,024. For the remainder of this paper we use the model configurations found in Table II. All models have a sequence size of 8,192, the feed forward size is fixed to $4\times$ the hidden size, and the number of attention heads is equal to the number of blocks. For all experiments we limited the maximum batch size to 3,072.

TABLE II
TWELVE MULTI-TRILLION PARAMETER LLMS, FROM 1T TO 128T.

Name	Hidden	Attn Size	# Blocks	Aspect Ratio
1T	24,576	192	128	192
2T	32,768	205	160	204.8
4T	40,960	213	192	213.3
7T	50,176	224	224	224
11T	60,416	236	256	236
18T	70,656	245	288	245
26T	81,920	256	320	256
37T	94,208	268	352	267.6
53T	106,496	277	384	277.3
72T	119,808	288	416	288
96T	134,144	299	448	299.4
128T	148,480	309	480	309.3

IV. TENSOR OFFLOADING FOR LLM SCALING

Fig. 4. Comparison of LLM scaling on 4,096 GPUs with and without offload memory. Such memory enables high training efficiency beyond 100T models.

While scaling out LLMs using standard DGX/HGX H100s with 8 NVLink-connected GPUs is possible, achieving high performance is not trivial. Fig. 4a shows the training efficiency while scaling up model size on a fixed system size of 4,096 GPUs. Even the smallest model size, 1T, reaches only 60% efficiency and rapidly decays until 18T where it can no longer run. The main scalability issue is the lack of memory to store weights and activations during training. This in turn forces the use of activation recomputation and higher model parallelism. A large pipeline parallelism with a lack of spare memory forces an excessive time overhead in the form of a pipeline bubble. A large tensor parallelism beyond the NVLink size of 8 increases communication time due to a lack of bandwidth.

These issues can be addressed by a secondary memory pool, where unused tensors from inactive transformer blocks can be transferred and retrieved as needed [17]. This could be implemented as CPU host memory, an array of PCIe attached SSDs, or CXL-attached memory. Fig. 4b shows the training efficiency when using tensor offloading with a capacity of 1 TiB per GPU at infinite bandwidth. Thus, with

enough offloading capacity and infinite offloading bandwidth, we could train models at least up to 128T parameters.

Fig. 5. Efficiency of offload memory compared to infinite offload bandwidth.

Fig. 5 inspects offloading capacities of 256 GiB, 512 GiB, 1 TiB, and 2 TiB. It compares the relative slowdown of using 50 GB/s and 100 GB/s of offloading bandwidth per direction compared to infinite bandwidth. We see that 50 GB/s experiences significant slowdown for larger model sizes on 4,096 GPUs system. With 100 GB/s offloading memory, the majority of the systems have nearly the same performance as infinite bandwidth, which makes it an excellent target bandwidth. While not a trivial amount of bandwidth, 100 GB/s could be implemented by 32 lanes of PCI-E 5.0 or CXL; it is also well below the speed of the CPU-to-GPU link of the NVIDIA Grace-Hopper package [10]. Utilizing offload memory is not only efficient but within reach of current technology.

Fig. 6. Training efficiency with model and system scaling using offloading memory with infinite bandwidth. Green dash line indicates 75% MFU, red dash line indicates 50% MFU.

Fig. 6 shows the training efficiency when using offloading running at 100 GB/s with capacities of 256 GiB, 512 GiB, 1 TiB, and 2 TiB across 4,096, 8,192, 12,288, and 16,384 GPUs. The major trends shown are:

- Small models on large systems leads to low efficiency.
- Large models on small systems leads to low efficiency.

- 256 GiB rarely produces good efficiency.
- For 8k, 12k, and 16k GPUs, 512 GiB is mostly sufficient.
- 1 TiB is nearly identical to 2 TiB.

V. MODEL STRONG SCALING

Fig. 7. Batch time and memory consumption break down for 1T model strong scaling from 4,096 to 16,384 GPUs.

In this section we analyze the strong scaling of the 1T parameter model from 4,096 to 16,384 GPUs inspecting NVLink domain sizes of 8 and 16. Fig. 7 shows that scaling of training up to 12,288 GPUs fares well but suffers at 16,384 GPUs. NVLink size 8 is sufficient up to 12,228 GPUs but NVLink size 16 is needed for higher efficiency at 16,384 GPUs. Adding extra processors requires assigning them to tensor, pipeline, or data parallelism and none of them are *free*. We identified several reasons for a lack of scaling at 16,384 GPUs.

1) When increasing TP the tensor may be divided too small to maintain a high compute efficiency in the GPU.
2) When increasing TP the size of each message may become small enough to become latency dominated.
3) When attempting to overlap TP communication and computation, increasing TP reduces the computation size but communication size remains the same. At particular FLOPs/bandwidth ratios, the communication will be exposed leading to low efficiency.
4) When overlapping TP communication and computation, to sustain the high bandwidth of NVLink the GPU must dedicate many cores to communication reducing its computation speed. Adding a specialized direct memory access (DMA)-like engine for communication would eliminate this overhead allowing optimal overlap.
5) Increasing PP either increases the pipeline bubble overhead or requires more memory for higher levels of interleaving to reduce the pipeline bubble.
6) Increasing DP requires more memory due to replication.
7) We constrain our models to have a maximum batch size of 3,072 to conserve the convergence properties of prior studies. This means that maximum available DP is 3,072, the rest must be either TP or PP.

VI. SCALING MODELS BEYOND 10T PARAMETERS

In this section we test weak scaling by growing the model sizes to 128T parameters. Fig. 8 shows model scaling on 4,096 GPUs enabled with 80 GiB and 120 GiB of HBM and

Fig. 8. Efficiency and memory consumption for LLM training on 4,096 GPUs. Green dash line indicates 75% MFU, red dash line indicates 50%. Memory consumption presented for the 120 GiB HBM and 2 TiB offload memory.

256 GiB, 512 GiB, 1 TiB, and 2 TiB of offloading capacity. This figure demonstrates that while scaling model training on 4,096 GPUs works well with 80 GiB of HBM for models up to 11T parameters, HBM size must increase to 120 GiB for scaling further, even when given extra offloading memory. This happens because even when offloading is used, there must be enough HBM memory to hold two transformer blocks, the one used in computation and the one needed for offloading and prefetching. During model scaling, the transformer block size grows mostly due to weights and activations. Unsurprisingly, offload memory capacity also needs to scale aaccordingly.

Our experiments indicate that growing the HBM size to 120 GiB and offload memory to 2 TiB is enough to maintain the further model scaling to 100T parameters. We can see that past 11T parameter, models occupy most of the available memories. This indicates that further efficiency improvements are possible, either by providing more memory, or by increasing the size of the NVLink domain to reduce per-GPU weight space and increase local microbatch size. These experiments show that the proposed LLMs can scale up to 128T parameters while maintaining an MFU above 75%, more than typically seen on current systems for much smaller LLMs.

VII. CONCLUSION

Our co-design analysis reveals that well structured multi-trillion parameter LLMs are able to train efficiently at 75%+ MFU when supplied with optimal settings and a secondary memory pool for tensor offloading. We analyzed strong scaling of models, finding optimal configuration strategies and quantitatively revealing fundamental limitations. We analyzed weak scaling of models, showing successful scaling up to 11T parameters with only tensor offloading, and showing successful scaling up to 128T parameters using a 120 GiB HBM and a 2 TiB offloading memory.

REFERENCES

[1] T. B. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. Henighan, R. Child, A. Ramesh, D. M. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei, "Language models are few-shot learners," in *Proceedings of the 34th International Conference on Neural Information Processing Systems*, ser. NIPS'20. Red Hook, NY, USA: Curran Associates Inc., 2020.

[2] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, P. Schuh, K. Shi, S. Tsvyashchenko, J. Maynez, A. Rao, P. Barnes, Y. Tay, N. Shazeer, V. Prabhakaran, E. Reif, N. Du, B. Hutchinson, R. Pope, J. Bradbury, J. Austin, M. Isard, G. Gur-Ari, P. Yin, T. Duke, A. Levskaya, S. Ghemawat, S. Dev, H. Michalewski, X. Garcia, V. Misra, K. Robinson, L. Fedus, D. Zhou, D. Ippolito, D. Luan, H. Lim, B. Zoph, A. Spiridonov, R. Sepassi, D. Dohan, S. Agrawal, M. Omernick, A. M. Dai, T. S. Pillai, M. Pellat, A. Lewkowycz, E. Moreira, R. Child, O. Polozov, K. Lee, Z. Zhou, X. Wang, B. Saeta, M. Diaz, O. Firat, M. Catasta, J. Wei, K. Meier-Hellstern, D. Eck, J. Dean, S. Petrov, and N. Fiedel, "Palm: Scaling language modeling with pathways," 2022.

[3] J. Hoffmann, S. Borgeaud, A. Mensch, E. Buchatskaya, T. Cai, E. Rutherford, D. de Las Casas, L. A. Hendricks, J. Welbl, A. Clark, T. Hennigan, E. Noland, K. Millican, G. van den Driessche, B. Damoc, A. Guy, S. Osindero, K. Simonyan, E. Elsen, J. W. Rae, O. Vinyals, and L. Sifre, "Training compute-optimal large language models," 2022.

[4] J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, and D. Amodei, "Scaling laws for neural language models," 2020.

[5] D. M. Katz, M. J. Bommarito, S. Gao, and P. Arredondo, "Gpt-4 passes the bar exam," *SSRN Electronic Journal*, 2023. [Online]. Available: https://ssrn.com/abstract=4389233

[6] V. Korthikanti, J. Casper, S. Lym, L. McAfee, M. Andersch, M. Shoeybi, and B. Catanzaro, "Reducing activation recomputation in large transformer models," 2022. [Online]. Available: https://arxiv.org/abs/2205.05198

[7] Y. Levine, N. Wies, O. Sharir, H. Bata, and A. Shashua, "Limits to depth efficiencies of self-attention," in *Advances in Neural Information Processing Systems*, H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, Eds., vol. 33. Curran Associates, Inc., 2020, pp. 22 640–22 651. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2020/file/ff4dfdf5904e920ce52b48c1cef97829-Paper.pdf

[8] O. Lieber, O. Sharir, B. Lenz, and Y. Shoham, "Jurassic-1: Technical details and evaluation," AI21 Labs, Tech. Rep., Aug. 2021.

[9] D. Narayanan, M. Shoeybi, J. Casper, P. LeGresley, M. Patwary, V. Korthikanti, D. Vainbrand, P. Kashinkunti, J. Bernauer, B. Catanzaro, A. Phanishayee, and M. Zaharia, "Efficient large-scale language model training on gpu clusters using megatron-lm," in *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*, ser. SC '21. New York, NY, USA: Association for Computing Machinery, 2021. [Online]. Available: https://doi.org/10.1145/3458817.3476209

[10] NVIDIA, "Nvidia grace hopper superchip architecture," 2022. [Online]. Available: https://resources.nvidia.com/en-us-grace-cpu/nvidia-grace-hopper

[11] NVIDIA, "Nvidia h100 tensor core gpu architecture," 2022. [Online]. Available: https://images.nvidia.com/aem-dam/en-zz/Solutions/data-center/nvidia-ampere-architecture-whitepaper.pdf

[12] OpenAI, "Gpt-4 technical report," 2023.

[13] D. Patterson, J. Gonzalez, Q. Le, C. Liang, L.-M. Munguia, D. Rothchild, D. So, M. Texier, and J. Dean, "Carbon emissions and large neural network training," 2021. [Online]. Available: https://arxiv.org/abs/2104.10350

[14] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever, "Language models are unsupervised multitask learners," 2019.

[15] S. Rajbhandari, J. Rasley, O. Ruwase, and Y. He, "Zero: Memory optimizations toward training trillion parameter models," in *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*, ser. SC '20. IEEE Press, 2020.

[16] J. Rasley, S. Rajbhandari, O. Ruwase, and Y. He, "Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters," in *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, ser. KDD '20. New York, NY, USA: Association for Computing Machinery, 2020, p. 3505–3506. [Online]. Available: https://doi.org/10.1145/3394486.3406703

[17] J. Ren, S. Rajbhandari, R. Y. Aminabadi, O. Ruwase, S. Yang, M. Zhang, D. Li, and Y. He, "Zero-offload: Democratizing billion-scale model training," in *2021 USENIX Annual Technical Conference, USENIX ATC 2021, July 14-16, 2021*, I. Calciu and G. Kuenning, Eds. USENIX Association, 2021, pp. 551–564. [Online]. Available: https://www.usenix.org/conference/atc21/presentation/ren-jie

[18] S. Smith, M. Patwary, B. Norick, P. LeGresley, S. Rajbhandari, J. Casper, Z. Liu, S. Prabhumoye, G. Zerveas, V. Korthikanti, E. Zhang, R. Child, R. Y. Aminabadi, J. Bernauer, X. Song, M. Shoeybi, Y. He, M. Houston, S. Tiwary, and B. Catanzaro, "Using deepspeed and megatron to train megatron-turing nlg 530b, a large-scale generative language model," 2022. [Online]. Available: https://arxiv.org/abs/2201.11990

[19] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, A. Rodriguez, A. Joulin, E. Grave, and G. Lample, "Llama: Open and efficient foundation language models," 2023.